

BLADE VERSA 45 INTEGRATED Select Gallonage Smoothbore Nozzle & Shutoff

Overview

The BLADE VERSA 45 integrates a smoothbore nozzle and shutoff into a single, more compact and lightweight solution—streamlining operations without sacrificing performance. VERSA™ delivers a clear wildland advantage, combining selectable gallonage with consistent reach, velocity, and penetration at any flow. Independent controls and BLADE technology ensure precise, efficient water application in changing conditions.

Specifications

	IMPERIAL	METRIC
Target Flow	45 gpm	170 lpm
Target Pressure	100 psi	7 bar
Weight	3 lb	1.36 kg
Length	7.5 in.	190.5 mm
Width	3.75 in.	92.25 mm
Height	4 in.	101.6 mm



Features

- One piece shutoff and nozzle
- Select gallonage range of 15 - 45 GPM
- Solid tight pattern with large water droplets
- Hard-coat anodized aluminum construction
- Available with 1" and 1.5" NH or NPSH threads
- Perfect for wildland & WUI applications
- NFPA 1960/1964 compliant
- 5-Year Mechanical Warranty

Flow Rates

IMPERIAL	METRIC
45 gpm (100 psi)	170 lpm (7 bar)
30 gpm (100 psi)	113 lpm (7 bar)
15 gpm (100 psi)	56 lpm (7 bar)



**NFPA
COMPLIANT**