ARAMARK Campus Services
POS Interface

XML interfaces

ARAMARK Confidential

Prepared by
Campus Services IT

May 25, 2004

Relay Transaction Server: Response Messages

Attached are the ARAMARK Campus Services Replay Transaction Server response messages and status codes. These messages and status codes will be standardized from multiple POS Systems the Transaction Server will interact between.

The Status tag message will be Valid, InValid and UnKnown. These messages will represent if the transaction was processed successfully. The StatusCode number will represent the actual success issue or error of the Status tag. The ResponseMessage tag was created to be a response message back to the customer. This message can be customized to your specifications if needed. The ResponseText is primarily used for Error messages and for a subset of the response back from the POS system.

Status Codes

0+		Successful Return values
-1	.. –1000	Processor Messages
-1001	.. –2000	Transaction Messages
-2001	.. –3000	Communication Responses

Status	StatusCode	Definition
Valid	0	ResponseText: VALID $XXXX.XX ResponseMessage: Customer Balance is XXXXX.XX
Valid	100	ResponseText: CR BAL $XX.XX ResponseMessage: Customer Balance is -XXXXX.XX

Status	StatusCode	Definition
InValid	-1	ResponseText: NOT REGISTERED ResponseMessage: `Customer not Registered`
InValid	-2	ResponseText: `EXPIRED CARD` ResponseMessage: `Expired Card`
InValid	-3	ResponseText: LOST CARD,GRAB ResponseMessage: `Card Reported Lost.`
InValid	-4	ResponseText: SUSPENDED CARD ResponseMessage: `Suspended Card`

InValid	-5	ResponseText: SEE MANAGER ResponseMessage: See Manager
InValid	-6	ResponseText: OVER DAILY LIMIT ResponseMessage: Customer Over Daily Limit
InValid	-7	ResponseText: OLD ISSUE # ResponseMessage: Customer using invalid issued Card.
InValid	-8	ResponseText: INVALID ResponseMessage: Invalid Transaction
InValid	-9	**ResponseText:** FAILED XXXX **ResponseMessage:** FAILED XXXX
InValid	-10	ResponseText: INVALID FUNCTION ResponseMessage: Transaction can not be processed at this time.
InValid	-11	ResponseText: HALL CLOSED ResponseMessage: HALL CLOSED
InValid	-12	ResponseText: COMM ERROR-RETRY ResponseMessage: COMM ERROR-RETRY
InValid	-13	ResponseText: INVALID ZONE ResponseMessage: Transaction can not be completed during this time period.
InValid	-14	ResponseText: NOT CR MERCHANT ResponseMessage: NOT CR MERCHANT
InValid	-15	ResponseText: MEAL PL NOT FND ResponseMessage: Meal Plan assigned to patron does not exist.
InValid	-100	ResponseText: OFFLINE ResponseMessage: Offline

Transaction Specification Errors

Status	StatusCode	Definition
InValid	-1001	ResponseMessage: Begin DateTime could not be converted to a Date/Time.
InValid	-1002	ResponseMessage: End DateTime could not be converted to a Date/Time.
InValid	-1003	ResponseMessage: Offline entry was not a 'TRUE' or 'FALSE'.
InValid	-1004	ResponseMessage: Transaction Number formatting is incorrect.
InValid	-1005	ResponseMessage: Revenue Center Number formatting is incorrect.
InValid	-1006	ResponseMessage: Operator Formatting is incorrect.
InValid	-1007	ResponseMessage: Customer Number must be greater then 0 characters.
InValid	-1008	ResponseMessage: Amount formatting is incorrect.
InValid	-1009	ResponseMessage: Unit Count formatting is incorrect.
InValid	-1010	ResponseMessage: Invalid Transaction Type Code.
InValid	-1011	ResponseMessage: Amount is Greater/Less than Maximum Amount allow.
InValid	-1012	ResponseMessage: Amount can not be negative.
InValid	-1013	ResponseMessage: Transaction Number can not be greater then 6 Characters.
InValid	-1014	ResponseMessage: Transaction could not be Validated Successfully.
InValid	-1015	ResponseMessage: Incorrect Account Name parameter value Or Configuration settings not found for specified Account Name Or 'Invalid Account Name : Config File.
InValid	-1016	ResponseMessage: InValid POS Solution

Communication Specification Errors

Status	StatusCode	Definition
InValid	-2001	ResponseMessage: Server Error Message * Transaction could not be processed for an Unknown Server processing Issue
InValid	-2002	ResponseMessage: Server result did not parse correctly.

InValid	-2003	ResponseMessage: `Server not available using IP XXXXXXXX Port XXXX`