Aramark Gateway Interface Specification

Version: 1.0.0 DRAFT
Last Modified: 01/19/2005
Confidential – Proprietary

Copyright © 2004 USA Technologies,
All Rights Reserved

1.0 Introduction

This document describes the interface to USA Technologies' Aramark Gateway. The Aramark Gateway is a web service that handles requests for Aramark services from the Aramark Relay Transaction Server. The Aramark Gateway receives and processes SOAP messages that represent requests for Aramark transaction services. The Aramark Gateway returns a response, also in the form of a SOAP message, that represents the result of a request for Aramark transaction services.

There are five types of transaction services supported by the Aramark Gateway: inquiry, decliningBalance, credit, cashEquivalency and board. The cashEquivalency and board transaction services are currently not supported by the Aramark Relay Transaction Server.

Copyright © 2004 USA Technologies, All Rights Reserved

2.0 Transaction Services

Applications can request Aramark Transaction Services from the Aramark Gateway by sending a properly formatted SOAP message to the gateway. The gateway will accept such messages using HTTP as a transport protocol. The Aramark Gateway is implemented as an Apache Axis web service.

Any application that requests Aramark services through the gateway must provide several data elements as listed in the following sections. The request must pass validation tests as documented in the XML Schema in section 3.0. Please consult "ARAMARK Campus Services POS Interface" by Aramark for more information regarding the elements listed below.

	Element	Description	Required
1	remoteServerAddress	URL of Aramark Relay Server's web service	*
2	account	Account Name ** Must be same name as setup on Relay Transaction Server & relates to a POS device	*
3	cardNumber	Customer Account Number	*
4	resultDate	Date and Time of the Transaction	*
5	operatorID	Operation Number from system sending over request	
6	transactionID	ID of the Transaction	
7	revenueCenterID	Optional Field to record transactions to a Revenue Center	
8	offline	"TRUE" or "FALSE"	*
9	debitAmount	Amount to be deducted from the customer's account	* for declining Balance request
10	creditAmount	Amount to be credited to the customer's account	* for credit request
11	enableEncryption	"TRUE" of "FALSE"	*
12	cryptoKey	Encryption key to use when communicating with Aramark Relay Transaction Server. Each terminal may have its own encryption key.	* if encryption is enabled
13	cryptoIV	Encryption initialization vector to use when communicating with Aramark Relay Transaction Server. Each terminal may have its own encryption initialization vector.	* if encryption is enabled

The reply returned by the gateway follows a common pattern. Please consult "ARAMARK Campus Services POS Interface" by Aramark for more information regarding the elements listed below. Return values include:

POSResponse

	Element	Type	Description
1	POSResponse	struct	Root element of POSResponse
2	POSResponse_Transaction	struct	A single Transaction that's been responded to from a POS

POSResponse_Transaction

Element	Type	Description
POSResponse_Transaction	struct	Subtype of POSResponse
DateTimeStamp	string	DateTime stamp of a single Transaction that's been

Copyright © 2004 USA Technologies, All Rights Reserved

		responded to from a POS
TransactionTypeCode	string	INQUIRY, DECLININGBALANCE, CREDIT, CASHEQUIVALENCY, BOARD
Status	string	Transaction success code (Valid, InValid, UnKnown, NotRegistered)
StatusCode	string	POS Transaction response code
ResponseMessage	string	POS message, Potentially for Customer
ResponseText	string	POS Text / Error Messages
POSResponse_Customer	struct	Customer that this transaction relates to

POSResponse_Customer

Element	Type	Description
POSResponse_Customer	struct	Subtype of POSResponse_Transaction
CustomerID	string	Customer Card Number
CustomerIssueID	string	Customer Card Number Issue Number
FirstName	string	Customer First name
LastName	string	Customer Last name
Amount	string	Customer Account Balance
TaxLines	struct	Structure of TaxLines

TaxLines

Element	Type	Description
TaxAuthorityID	string	TaxNumber
UseTax	string	TRUE or FALSE value if tax is used

Copyright © 2004 USA Technologies, All Rights Reserved

2.1 Inquiry

The Inquiry method allows for inquires to be requested to the POS system. An XML response will be sent back with the detailed information below. Please see the XML schema definitions in section 3.0 for more information. Inquiry transactions are always online, so the Offline tag must be set to FALSE.

Below is a sample SOAP message that implements an inquiry request.

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:xsi="http://www.w3.org/1999/XMLSchema-instance" xmlns:SOAP-
ENC="http://schemas.xmlsoap.org/soap/encoding/" xmlns:SOAP-
ENV="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsd="http://www.w3.org/1999/XMLSchema" SOAP-
ENV:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
  <SOAP-ENV:Body>
        <inquiry>
          <remoteServerAddress
          xsi:type="xsd:string">http://demo.aramarkcampusit.com/Relay_V2/RelayService.asmx
          </remoteServerAddress>
           <account xsi:type="xsd:string">ScanPlus_90</account>
           <cardNumber xsi:type="xsd:string">999999999</cardNumber>
           <resultDate xsi:type="xsd:string">2004-12-02T10:05:00.0000000-04:00</resultDate>
           <operatorID xsi:type="xsd:string"/>
           <transactionID xsi:type="xsd:string">123456</transactionID>
           <revenueCenterID xsi:type="xsd:string"/>
           <offline xsi:type="xsd:string">FALSE</offline>
           <enableEncryption xsi:type="xsd:string">TRUE</enableEncryption>
           <cryptoKey xsi:type="xsd:string">g9f9tr4j34t66lkjgovjo8rs</cryptoKey>
           <cryptoIV xsi:type="xsd:string">vgv8gfd9</cryptoIV>
        </inquiry>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

Below is a sample SOAP message that implements an inquiry response.

```
<?xml version="1.0" encoding="UTF-8"?>
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsd="http://www.w3.org/1999/XMLSchema" xmlns:xsi="http://www.w3.org/1999/XMLSchema-
instance">
 <soapenv:Body>
  <inquiryResponse soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
   <inquiryReturn href="#id0"/>
  </inquiryResponse>
  <multiRef id="id0" soapenc:root="0"
soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
xsi:type="ns1:POSResponse" xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:ns1="http://relayservice.webservices.educationaramark.com">
   <Account xsi:type="ns2:string"
xmlns:ns2="http://www.w3.org/2001/XMLSchema">ScanPlus_90</Account>
   <Transaction href="#id1"/>
  </multiRef>
  <multiRef id="id1" soapenc:root="0"
soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
xsi:type="ns3:POSResponse_Transaction" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
instance" xmlns:ns3="http://relayservice.webservices.educationaramark.com"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/">
   <BeginDateTimeStamp xsi:type="ns4:string"
xmlns:ns4="http://www.w3.org/2001/XMLSchema">12/16/2004 12:01:50 PM</BeginDateTimeStamp>
   <TransactionTypeCode xsi:type="ns5:string"
xmlns:ns5="http://www.w3.org/2001/XMLSchema">INQUIRY</TransactionTypeCode>
   <Status xsi:type="ns6:string"
xmlns:ns6="http://www.w3.org/2001/XMLSchema">VALID</Status>
   <StatusCode xsi:type="ns7:string"
xmlns:ns7="http://www.w3.org/2001/XMLSchema">0</StatusCode>
```

Copyright © 2004 USA Technologies, All Rights Reserved

```
   <ResponseMessage xsi:type="ns8:string"
xmlns:ns8="http://www.w3.org/2001/XMLSchema">Customer Balance is
$235.00</ResponseMessage>
   <ResponseText xsi:type="ns9:string" xmlns:ns9="http://www.w3.org/2001/XMLSchema">VALID
$235.00</ResponseText>
   <Customer href="#id2"/>
  </multiRef>
  <multiRef id="id2" soapenc:root="0"
soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
xsi:type="ns10:POSResponse_Customer" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
instance" xmlns:ns10="http://relayservice.webservices.educationaramark.com"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/">
   <CustomerID xsi:type="ns11:string"
xmlns:ns11="http://www.w3.org/2001/XMLSchema">999999999</CustomerID>
   <CusotmerIssueID xsi:type="ns12:string"
xmlns:ns12="http://www.w3.org/2001/XMLSchema"></CusotmerIssueID>
   <FirstName xsi:type="ns13:string"
xmlns:ns13="http://www.w3.org/2001/XMLSchema">Test1</FirstName>
   <LastName xsi:type="ns14:string"
xmlns:ns14="http://www.w3.org/2001/XMLSchema">Test1</LastName>
   <Amount xsi:type="ns15:string"
xmlns:ns15="http://www.w3.org/2001/XMLSchema">235.00</Amount>
   <Tax href="#id3"/>
  </multiRef>
  <multiRef id="id3" soapenc:root="0"
soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
xsi:type="ns16:ArrayOfTaxLines" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:ns16="http://relayservice.webservices.educationaramark.com"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/">
   <TaxLines href="#id4"/>
   <TaxLines href="#id5"/>
   <TaxLines href="#id6"/>
   <TaxLines href="#id7"/>
  </multiRef>
  <multiRef id="id7" soapenc:root="0"
soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
xsi:type="ns17:TaxLines" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:ns17="http://relayservice.webservices.educationaramark.com"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/">
   <TaxAuthorityID xsi:type="ns18:string"
xmlns:ns18="http://www.w3.org/2001/XMLSchema">Tax4</TaxAuthorityID>
   <UseTax xsi:type="ns19:string"
xmlns:ns19="http://www.w3.org/2001/XMLSchema">TRUE</UseTax>
  </multiRef>
  <multiRef id="id4" soapenc:root="0"
soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
xsi:type="ns20:TaxLines" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:ns20="http://relayservice.webservices.educationaramark.com"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/">
   <TaxAuthorityID xsi:type="ns21:string"
xmlns:ns21="http://www.w3.org/2001/XMLSchema">Tax1</TaxAuthorityID>
   <UseTax xsi:type="ns22:string"
xmlns:ns22="http://www.w3.org/2001/XMLSchema">TRUE</UseTax>
  </multiRef>
  <multiRef id="id6" soapenc:root="0"
soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
xsi:type="ns23:TaxLines" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:ns23="http://relayservice.webservices.educationaramark.com"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/">
   <TaxAuthorityID xsi:type="ns24:string"
xmlns:ns24="http://www.w3.org/2001/XMLSchema">Tax3</TaxAuthorityID>
   <UseTax xsi:type="ns25:string"
xmlns:ns25="http://www.w3.org/2001/XMLSchema">TRUE</UseTax>
  </multiRef>
  <multiRef id="id5" soapenc:root="0"
soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
xsi:type="ns26:TaxLines" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:ns26="http://relayservice.webservices.educationaramark.com"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/">
   <TaxAuthorityID xsi:type="ns27:string"
xmlns:ns27="http://www.w3.org/2001/XMLSchema">Tax2</TaxAuthorityID>
```


Copyright © 2004 USA Technologies, All Rights Reserved

```
   <UseTax xsi:type="ns28:string"
xmlns:ns28="http://www.w3.org/2001/XMLSchema">TRUE</UseTax>
  </multiRef>
 </soapenv:Body>
</soapenv:Envelope>
```


Copyright © 2004 USA Technologies, All Rights Reserved

2.2 Declining Balance

The Declining Balance transaction method allows for debits to be deducted from a customer's account. An XML response will be sent back with the detailed information below. Please see the XML schema definitions in section 3.0 for more information.

Below is a sample SOAP message that implements a decliningBalance request.

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:xsi="http://www.w3.org/1999/XMLSchema-instance" xmlns:SOAP-
ENC="http://schemas.xmlsoap.org/soap/encoding/" xmlns:SOAP-
ENV="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsd="http://www.w3.org/1999/XMLSchema" SOAP-
ENV:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
  <SOAP-ENV:Body>
    <decliningBalance>
        <remoteServerAddress
        xsi:type="xsd:string">http://demo.aramarkcampusit.com/Relay_V2/RelayService.asmx</
        remoteServerAddress>
        <account xsi:type="xsd:string">ScanPlus_90</account>
        <cardNumber xsi:type="xsd:string">999999999</cardNumber>
        <resultDate xsi:type="xsd:string">2004-12-02T10:05:00.0000000-04:00</resultDate>
        <operatorID xsi:type="xsd:string"/>
        <transactionID xsi:type="xsd:string">123456</transactionID>
        <revenueCenterID xsi:type="xsd:string"/>
        <offline xsi:type="xsd:string">FALSE</offline>
        <debitAmount xsi:type="xsd:string">1.00</debitAmount>
        <enableEncryption xsi:type="xsd:string">TRUE</enableEncryption>
        <cryptoKey xsi:type="xsd:string">g9f9tr4j34t66lkjgovjo8rs</cryptoKey>
        <cryptoIV xsi:type="xsd:string">vgv8gfd9</cryptoIV>
    </decliningBalance>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

Below is a sample SOAP message that implements a decliningBalance response.

```
<?xml version="1.0" encoding="UTF-8"?>
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsd="http://www.w3.org/1999/XMLSchema" xmlns:xsi="http://www.w3.org/1999/XMLSchema-
instance">
 <soapenv:Body>
  <decliningBalanceResponse
soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
   <decliningBalanceReturn href="#id0"/>
  </decliningBalanceResponse>
  <multiRef id="id0" soapenc:root="0"
soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
xsi:type="ns1:POSResponse" xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:ns1="http://relayservice.webservices.educationaramark.com">
   <Account xsi:type="ns2:string"
xmlns:ns2="http://www.w3.org/2001/XMLSchema">ScanPlus_90</Account>
   <Transaction href="#id1"/>
  </multiRef>
  <multiRef id="id1" soapenc:root="0"
soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
xsi:type="ns3:POSResponse_Transaction" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
instance" xmlns:ns3="http://relayservice.webservices.educationaramark.com"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/">
   <BeginDateTimeStamp xsi:type="ns4:string"
xmlns:ns4="http://www.w3.org/2001/XMLSchema">12/16/2004 1:26:29 PM</BeginDateTimeStamp>
   <TransactionTypeCode xsi:type="ns5:string"
xmlns:ns5="http://www.w3.org/2001/XMLSchema">DECLININGBALANCE</TransactionTypeCode>
   <Status xsi:type="ns6:string"
xmlns:ns6="http://www.w3.org/2001/XMLSchema">VALID</Status>
   <StatusCode xsi:type="ns7:string"
xmlns:ns7="http://www.w3.org/2001/XMLSchema">0</StatusCode>
```

Copyright © 2004 USA Technologies, All Rights Reserved

```
   <ResponseMessage xsi:type="ns8:string"
xmlns:ns8="http://www.w3.org/2001/XMLSchema">Customer Balance is
$234.00</ResponseMessage>
   <ResponseText xsi:type="ns9:string" xmlns:ns9="http://www.w3.org/2001/XMLSchema">VALID
$234.00</ResponseText>
   <Customer href="#id2"/>
  </multiRef>
  <multiRef id="id2" soapenc:root="0"
soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
xsi:type="ns10:POSResponse_Customer" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
instance" xmlns:ns10="http://relayservice.webservices.educationaramark.com"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/">
   <CustomerID xsi:type="ns11:string"
xmlns:ns11="http://www.w3.org/2001/XMLSchema">999999999</CustomerID>
   <CusotmerIssueID xsi:type="ns12:string"
xmlns:ns12="http://www.w3.org/2001/XMLSchema"></CusotmerIssueID>
   <FirstName xsi:type="ns13:string"
xmlns:ns13="http://www.w3.org/2001/XMLSchema">Test1</FirstName>
   <LastName xsi:type="ns14:string"
xmlns:ns14="http://www.w3.org/2001/XMLSchema">Test1</LastName>
   <Amount xsi:type="ns15:string"
xmlns:ns15="http://www.w3.org/2001/XMLSchema">234.00</Amount>
   <Tax xsi:type="ns10:ArrayOfTaxLines" xsi:null="true"
xmlns:xsi="http://www.w3.org/1999/XMLSchema-instance"/>
  </multiRef>
 </soapenv:Body>
</soapenv:Envelope>
```


Copyright © 2004 USA Technologies, All Rights Reserved

2.3 Credit

The Credit transaction method allows for credits/refunds to be placed onto a customer's account. An XML response will be send back with the detailed information below.

Below is a sample SOAP message that implements a credit request.

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope xmlns:xsi="http://www.w3.org/1999/XMLSchema-instance" xmlns:SOAP-
ENC="http://schemas.xmlsoap.org/soap/encoding/" xmlns:SOAP-
ENV="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsd="http://www.w3.org/1999/XMLSchema" SOAP-
ENV:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
  <SOAP-ENV:Body>
    <credit>
        <remoteServerAddress
        xsi:type="xsd:string">http://demo.aramarkcampusit.com/Relay_V2/RelayService.asmx</
        remoteServerAddress>
       <account xsi:type="xsd:string">ScanPlus_90</account>
       <cardNumber xsi:type="xsd:string">999999999</cardNumber>
       <resultDate xsi:type="xsd:string">2004-12-02T10:05:00.0000000-04:00</resultDate>
       <operatorID xsi:type="xsd:string"/>
       <transactionID xsi:type="xsd:string">123456</transactionID>
       <revenueCenterID xsi:type="xsd:string"/>
       <offline xsi:type="xsd:string">FALSE</offline>
       <creditAmount xsi:type="xsd:string">1.00</creditAmount>
       <enableEncryption xsi:type="xsd:string">TRUE</enableEncryption>
       <cryptoKey xsi:type="xsd:string">g9f9tr4j34t66lkjgovjo8rs</cryptoKey>
       <cryptoIV xsi:type="xsd:string">vgv8gfd9</cryptoIV>
    </credit>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

Below is a sample SOAP message that implements a credit response.

```
<?xml version="1.0" encoding="UTF-8"?>
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsd="http://www.w3.org/1999/XMLSchema" xmlns:xsi="http://www.w3.org/1999/XMLSchema-
instance">
 <soapenv:Body>
  <creditResponse soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
   <creditReturn href="#id0"/>
  </creditResponse>
  <multiRef id="id0" soapenc:root="0"
soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
xsi:type="ns1:POSResponse" xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:ns1="http://relayservice.webservices.educationaramark.com">
   <Account xsi:type="ns2:string"
xmlns:ns2="http://www.w3.org/2001/XMLSchema">ScanPlus_90</Account>
   <Transaction href="#id1"/>
  </multiRef>
  <multiRef id="id1" soapenc:root="0"
soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
xsi:type="ns3:POSResponse_Transaction" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
instance" xmlns:ns3="http://relayservice.webservices.educationaramark.com"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/">
   <BeginDateTimeStamp xsi:type="ns4:string"
xmlns:ns4="http://www.w3.org/2001/XMLSchema">12/16/2004 1:36:52 PM</BeginDateTimeStamp>
   <TransactionTypeCode xsi:type="ns5:string"
xmlns:ns5="http://www.w3.org/2001/XMLSchema">CREDIT</TransactionTypeCode>
   <Status xsi:type="ns6:string"
xmlns:ns6="http://www.w3.org/2001/XMLSchema">VALID</Status>
   <StatusCode xsi:type="ns7:string"
xmlns:ns7="http://www.w3.org/2001/XMLSchema">0</StatusCode>
```

Copyright © 2004 USA Technologies, All Rights Reserved

```
   <ResponseMessage xsi:type="ns8:string"
xmlns:ns8="http://www.w3.org/2001/XMLSchema">Customer Balance is
$235.00</ResponseMessage>
   <ResponseText xsi:type="ns9:string" xmlns:ns9="http://www.w3.org/2001/XMLSchema">VALID
$235.00</ResponseText>
   <Customer href="#id2"/>
  </multiRef>
  <multiRef id="id2" soapenc:root="0"
soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
xsi:type="ns10:POSResponse_Customer" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
instance" xmlns:ns10="http://relayservice.webservices.educationaramark.com"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/">
   <CustomerID xsi:type="ns11:string"
xmlns:ns11="http://www.w3.org/2001/XMLSchema">999999999</CustomerID>
   <CusotmerIssueID xsi:type="ns12:string"
xmlns:ns12="http://www.w3.org/2001/XMLSchema"></CusotmerIssueID>
   <FirstName xsi:type="ns13:string"
xmlns:ns13="http://www.w3.org/2001/XMLSchema">Test1</FirstName>
   <LastName xsi:type="ns14:string"
xmlns:ns14="http://www.w3.org/2001/XMLSchema">Test1</LastName>
   <Amount xsi:type="ns15:string"
xmlns:ns15="http://www.w3.org/2001/XMLSchema">235.00</Amount>
   <Tax xsi:type="ns10:ArrayOfTaxLines" xsi:null="true"
xmlns:xsi="http://www.w3.org/1999/XMLSchema-instance"/>
  </multiRef>
 </soapenv:Body>
</soapenv:Envelope>
```


Copyright © 2004 USA Technologies, All Rights Reserved

3.0 WSDL / XML Schema

This section documents the Aramark Gateway web service description and XML schema used to validate requests. A complete listing of the gateway's WSDL file follows.


```xml
<?xml version="1.0" encoding="UTF-8"?>
        <wsdl:definitions targetNamespace="urn:aramark.usatech.com"
        xmlns="http://schemas.xmlsoap.org/wsdl/"
        xmlns:apachesoap="http://xml.apache.org/xml-soap"
        xmlns:impl="urn:aramark.usatech.com" xmlns:intf="urn:aramark.usatech.com"
        xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
        xmlns:tns1="http://relayservice.webservices.educationaramark.com"
        xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/"
        xmlns:wsdlsoap="http://schemas.xmlsoap.org/wsdl/soap/"
        xmlns:xsd="http://www.w3.org/2001/XMLSchema"><wsdl:types><schema
        targetNamespace="http://relayservice.webservices.educationaramark.com"
        xmlns="http://www.w3.org/2001/XMLSchema"><import
        namespace="http://schemas.xmlsoap.org/soap/encoding/"/><complexType
        name="TaxLines"><sequence><element maxOccurs="1" minOccurs="0"
        name="TaxAuthorityID" nillable="true" type="xsd:string"/><element maxOccurs="1"
        minOccurs="0" name="UseTax" nillable="true"
        type="xsd:string"/></sequence></complexType><complexType
        name="ArrayOfTaxLines"><sequence><element maxOccurs="unbounded" minOccurs="0"
        name="TaxLines" nillable="true"
        type="tns1:TaxLines"/></sequence></complexType><complexType
        name="POSResponse_Customer"><sequence><element maxOccurs="1" minOccurs="0"
        name="CustomerID" nillable="true" type="xsd:string"/><element maxOccurs="1"
        minOccurs="0" name="CusotmerIssueID" nillable="true" type="xsd:string"/><element
        maxOccurs="1" minOccurs="0" name="FirstName" nillable="true"
        type="xsd:string"/><element maxOccurs="1" minOccurs="0" name="LastName"
        nillable="true" type="xsd:string"/><element maxOccurs="1" minOccurs="0"
        name="Amount" nillable="true" type="xsd:string"/><element maxOccurs="1"
        minOccurs="0" name="Tax" nillable="true"
        type="tns1:ArrayOfTaxLines"/></sequence></complexType><complexType
        name="POSResponse_Transaction"><sequence><element maxOccurs="1" minOccurs="0"
        name="BeginDateTimeStamp" nillable="true" type="xsd:string"/><element
        maxOccurs="1" minOccurs="0" name="TransactionTypeCode" nillable="true"
        type="xsd:string"/><element maxOccurs="1" minOccurs="0" name="Status"
        nillable="true" type="xsd:string"/><element maxOccurs="1" minOccurs="0"
        name="StatusCode" nillable="true" type="xsd:string"/><element maxOccurs="1"
        minOccurs="0" name="ResponseMessage" nillable="true" type="xsd:string"/><element
        maxOccurs="1" minOccurs="0" name="ResponseText" nillable="true"
        type="xsd:string"/><element name="Customer" nillable="true"
        type="tns1:POSResponse_Customer"/></sequence></complexType><complexType
        name="POSResponse"><sequence><element maxOccurs="1" minOccurs="0" name="Account"
        nillable="true" type="xsd:string"/><element name="Transaction" nillable="true"
        type="tns1:POSResponse_Transaction"/></sequence></complexType></schema><schema
        targetNamespace="urn:aramark.usatech.com"
        xmlns="http://www.w3.org/2001/XMLSchema"><import
        namespace="http://schemas.xmlsoap.org/soap/encoding/"/><complexType
        name="AramarkException"><sequence><element name="description" nillable="true"
        type="xsd:string"/><element name="responseMessage" nillable="true"
        type="xsd:string"/><element name="responseText" nillable="true"
        type="xsd:string"/><element name="status" nillable="true"
        type="xsd:string"/><element name="statusCode" nillable="true"
        type="xsd:string"/></sequence></complexType></schema></wsdl:types>
  <wsdl:message name="inquiryResponse">
    <wsdl:part name="inquiryReturn" type="tns1:POSResponse"/>
  </wsdl:message>
  <wsdl:message name="creditResponse">
    <wsdl:part name="creditReturn" type="tns1:POSResponse"/>
  </wsdl:message>
  <wsdl:message name="creditRequest">
    <wsdl:part name="remoteServerAddress" type="xsd:string"/>
    <wsdl:part name="account" type="xsd:string"/>
    <wsdl:part name="cardNumber" type="xsd:string"/>
    <wsdl:part name="resultDate" type="xsd:string"/>
    <wsdl:part name="operatorID" type="xsd:string"/>
```


Copyright © 2004 USA Technologies, All Rights Reserved

```
  <wsdl:part name="transactionID" type="xsd:string"/>
  <wsdl:part name="revenueCenterID" type="xsd:string"/>
  <wsdl:part name="offline" type="xsd:string"/>
  <wsdl:part name="creditAmount" type="xsd:string"/>
  <wsdl:part name="enableEncryption" type="xsd:string"/>
  <wsdl:part name="cryptoKey" type="xsd:string"/>
  <wsdl:part name="cryptoIV" type="xsd:string"/>
</wsdl:message>
<wsdl:message name="boardRequest">
  <wsdl:part name="remoteServerAddress" type="xsd:string"/>
  <wsdl:part name="account" type="xsd:string"/>
  <wsdl:part name="cardNumber" type="xsd:string"/>
  <wsdl:part name="resultDate" type="xsd:string"/>
  <wsdl:part name="operatorID" type="xsd:string"/>
  <wsdl:part name="transactionID" type="xsd:string"/>
  <wsdl:part name="revenueCenterID" type="xsd:string"/>
  <wsdl:part name="offline" type="xsd:string"/>
  <wsdl:part name="unitCount" type="xsd:string"/>
  <wsdl:part name="enableEncryption" type="xsd:string"/>
  <wsdl:part name="cryptoKey" type="xsd:string"/>
  <wsdl:part name="cryptoIV" type="xsd:string"/>
</wsdl:message>
<wsdl:message name="cashEquivalencyResponse">
  <wsdl:part name="cashEquivalencyReturn" type="tns1:POSResponse"/>
</wsdl:message>
<wsdl:message name="cashEquivalencyRequest">
  <wsdl:part name="remoteServerAddress" type="xsd:string"/>
  <wsdl:part name="account" type="xsd:string"/>
  <wsdl:part name="cardNumber" type="xsd:string"/>
  <wsdl:part name="resultDate" type="xsd:string"/>
  <wsdl:part name="operatorID" type="xsd:string"/>
  <wsdl:part name="transactionID" type="xsd:string"/>
  <wsdl:part name="revenueCenterID" type="xsd:string"/>
  <wsdl:part name="offline" type="xsd:string"/>
  <wsdl:part name="cashAmount" type="xsd:string"/>
  <wsdl:part name="enableEncryption" type="xsd:string"/>
  <wsdl:part name="cryptoKey" type="xsd:string"/>
  <wsdl:part name="cryptoIV" type="xsd:string"/>
</wsdl:message>
<wsdl:message name="inquiryRequest">
  <wsdl:part name="remoteServerAddress" type="xsd:string"/>
  <wsdl:part name="account" type="xsd:string"/>
  <wsdl:part name="cardNumber" type="xsd:string"/>
  <wsdl:part name="resultDate" type="xsd:string"/>
  <wsdl:part name="operatorID" type="xsd:string"/>
  <wsdl:part name="transactionID" type="xsd:string"/>
  <wsdl:part name="revenueCenterID" type="xsd:string"/>
  <wsdl:part name="offline" type="xsd:string"/>
  <wsdl:part name="enableEncryption" type="xsd:string"/>
  <wsdl:part name="cryptoKey" type="xsd:string"/>
  <wsdl:part name="cryptoIV" type="xsd:string"/>
</wsdl:message>
<wsdl:message name="getVersionRequest">
</wsdl:message>
<wsdl:message name="sampleMessageRequest">
</wsdl:message>
<wsdl:message name="declineingBalanceResponse">
  <wsdl:part name="declineingBalanceReturn" type="tns1:POSResponse"/>
</wsdl:message>
<wsdl:message name="getVersionResponse">
  <wsdl:part name="getVersionReturn" type="xsd:string"/>
</wsdl:message>
<wsdl:message name="boardResponse">
  <wsdl:part name="boardReturn" type="tns1:POSResponse"/>
</wsdl:message>
<wsdl:message name="AramarkException">
  <wsdl:part name="fault" type="impl:AramarkException"/>
</wsdl:message>
<wsdl:message name="declineingBalanceRequest">
  <wsdl:part name="remoteServerAddress" type="xsd:string"/>
  <wsdl:part name="account" type="xsd:string"/>
```

Copyright © 2004 USA Technologies, All Rights Reserved

```
    <wsdl:part name="cardNumber" type="xsd:string"/>
    <wsdl:part name="resultDate" type="xsd:string"/>
    <wsdl:part name="operatorID" type="xsd:string"/>
    <wsdl:part name="transactionID" type="xsd:string"/>
    <wsdl:part name="revenueCenterID" type="xsd:string"/>
    <wsdl:part name="offline" type="xsd:string"/>
    <wsdl:part name="debitAmount" type="xsd:string"/>
    <wsdl:part name="enableEncryption" type="xsd:string"/>
    <wsdl:part name="cryptoKey" type="xsd:string"/>
    <wsdl:part name="cryptoIV" type="xsd:string"/>
  </wsdl:message>
  <wsdl:message name="sampleMessageResponse">
    <wsdl:part name="sampleMessageReturn" type="tns1:POSResponse"/>
  </wsdl:message>
  <wsdl:portType name="WSClient">
    <wsdl:operation name="getVersion">
      <wsdl:input message="impl:getVersionRequest" name="getVersionRequest"/>
      <wsdl:output message="impl:getVersionResponse" name="getVersionResponse"/>
    </wsdl:operation>
    <wsdl:operation name="inquiry" parameterOrder="remoteServerAddress account cardNumber
resultDate operatorID transactionID revenueCenterID offline enableEncryption cryptoKey
cryptoIV">
      <wsdl:input message="impl:inquiryRequest" name="inquiryRequest"/>
      <wsdl:output message="impl:inquiryResponse" name="inquiryResponse"/>
      <wsdl:fault message="impl:AramarkException" name="AramarkException"/>
    </wsdl:operation>
    <wsdl:operation name="decliningBalance" parameterOrder="remoteServerAddress account
cardNumber resultDate operatorID transactionID revenueCenterID offline debitAmount
enableEncryption cryptoKey cryptoIV">
      <wsdl:input message="impl:decliningBalanceRequest" name="decliningBalanceRequest"/>
      <wsdl:output message="impl:decliningBalanceResponse"
name="decliningBalanceResponse"/>
      <wsdl:fault message="impl:AramarkException" name="AramarkException"/>
    </wsdl:operation>
    <wsdl:operation name="credit" parameterOrder="remoteServerAddress account cardNumber
resultDate operatorID transactionID revenueCenterID offline creditAmount enableEncryption
cryptoKey cryptoIV">
      <wsdl:input message="impl:creditRequest" name="creditRequest"/>
      <wsdl:output message="impl:creditResponse" name="creditResponse"/>
      <wsdl:fault message="impl:AramarkException" name="AramarkException"/>
    </wsdl:operation>
    <wsdl:operation name="board" parameterOrder="remoteServerAddress account cardNumber
resultDate operatorID transactionID revenueCenterID offline unitCount enableEncryption
cryptoKey cryptoIV">
      <wsdl:input message="impl:boardRequest" name="boardRequest"/>
      <wsdl:output message="impl:boardResponse" name="boardResponse"/>
      <wsdl:fault message="impl:AramarkException" name="AramarkException"/>
    </wsdl:operation>
    <wsdl:operation name="cashEquivalency" parameterOrder="remoteServerAddress account
cardNumber resultDate operatorID transactionID revenueCenterID offline cashAmount
enableEncryption cryptoKey cryptoIV">
      <wsdl:input message="impl:cashEquivalencyRequest" name="cashEquivalencyRequest"/>
      <wsdl:output message="impl:cashEquivalencyResponse"
name="cashEquivalencyResponse"/>
      <wsdl:fault message="impl:AramarkException" name="AramarkException"/>
    </wsdl:operation>
    <wsdl:operation name="sampleMessage">
      <wsdl:input message="impl:sampleMessageRequest" name="sampleMessageRequest"/>
      <wsdl:output message="impl:sampleMessageResponse" name="sampleMessageResponse"/>
      <wsdl:fault message="impl:AramarkException" name="AramarkException"/>
    </wsdl:operation>
  </wsdl:portType>
  <wsdl:binding name="aramarkgatewaySoapBinding" type="impl:WSClient">
    <wsdlsoap:binding style="rpc" transport="http://schemas.xmlsoap.org/soap/http"/>
    <wsdl:operation name="getVersion">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="getVersionRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="urn:aramark.usatech.com" use="encoded"/>
      </wsdl:input>
      <wsdl:output name="getVersionResponse">
```


Copyright © 2004 USA Technologies, All Rights Reserved

```
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="urn:aramark.usatech.com" use="encoded"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="inquiry">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="inquiryRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="urn:aramark.usatech.com" use="encoded"/>
      </wsdl:input>
      <wsdl:output name="inquiryResponse">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="urn:aramark.usatech.com" use="encoded"/>
      </wsdl:output>
      <wsdl:fault name="AramarkException">
        <wsdlsoap:fault encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="urn:aramark.usatech.com" use="encoded"/>
      </wsdl:fault>
    </wsdl:operation>
    <wsdl:operation name="decliningBalance">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="decliningBalanceRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="urn:aramark.usatech.com" use="encoded"/>
      </wsdl:input>
      <wsdl:output name="decliningBalanceResponse">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="urn:aramark.usatech.com" use="encoded"/>
      </wsdl:output>
      <wsdl:fault name="AramarkException">
        <wsdlsoap:fault encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="urn:aramark.usatech.com" use="encoded"/>
      </wsdl:fault>
    </wsdl:operation>
    <wsdl:operation name="credit">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="creditRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="urn:aramark.usatech.com" use="encoded"/>
      </wsdl:input>
      <wsdl:output name="creditResponse">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="urn:aramark.usatech.com" use="encoded"/>
      </wsdl:output>
      <wsdl:fault name="AramarkException">
        <wsdlsoap:fault encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="urn:aramark.usatech.com" use="encoded"/>
      </wsdl:fault>
    </wsdl:operation>
    <wsdl:operation name="board">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="boardRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="urn:aramark.usatech.com" use="encoded"/>
      </wsdl:input>
      <wsdl:output name="boardResponse">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="urn:aramark.usatech.com" use="encoded"/>
      </wsdl:output>
      <wsdl:fault name="AramarkException">
        <wsdlsoap:fault encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="urn:aramark.usatech.com" use="encoded"/>
      </wsdl:fault>
    </wsdl:operation>
    <wsdl:operation name="cashEquivalency">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="cashEquivalencyRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="urn:aramark.usatech.com" use="encoded"/>
      </wsdl:input>
      <wsdl:output name="cashEquivalencyResponse">
```

Copyright © 2004 USA Technologies, All Rights Reserved

```
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="urn:aramark.usatech.com" use="encoded"/>
      </wsdl:output>
      <wsdl:fault name="AramarkException">
        <wsdlsoap:fault encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="urn:aramark.usatech.com" use="encoded"/>
      </wsdl:fault>
    </wsdl:operation>
    <wsdl:operation name="sampleMessage">
      <wsdlsoap:operation soapAction=""/>
      <wsdl:input name="sampleMessageRequest">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="urn:aramark.usatech.com" use="encoded"/>
      </wsdl:input>
      <wsdl:output name="sampleMessageResponse">
        <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="urn:aramark.usatech.com" use="encoded"/>
      </wsdl:output>
      <wsdl:fault name="AramarkException">
        <wsdlsoap:fault encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="urn:aramark.usatech.com" use="encoded"/>
      </wsdl:fault>
    </wsdl:operation>
  </wsdl:binding>
  <wsdl:service name="WSClientService">
    <wsdl:port binding="impl:aramarkgatewaySoapBinding" name="aramarkgateway">
      <wsdlsoap:address location="http://localhost:9100/axis/services/aramarkgateway"/>
    </wsdl:port>
  </wsdl:service>
</wsdl:definitions>
```

Copyright © 2004 USA Technologies, All Rights Reserved

4.0 Transport Protocol

This section documents the Aramark Gateway transport protocol. A request for Aramark services will contain a header followed by the SOAP request.

Below is a sample header produced by Perl SOAP::Lite client that implements an inquiry request.

```
POST /axis/services/aramarkgateway HTTP/1.1
TE: deflate,gzip;q=0.3
Connection: TE, close
Accept: text/xml
Accept: multipart/*
Host: localhost:12345
User-Agent: SOAP::Lite/Perl/0.60
Content-Length: 962
Content-Type: text/xml; charset=utf-8
SOAPAction: "#inquiry"
```

The reply from the Aramark Gateway will contain the following header followed by the SOAP response.

```
HTTP/1.1 200 OK
Set-Cookie: JSESSIONID=DF768ADA5AA5E2B688A2A8930E88BC4E; Path=/axis
Content-Type: text/xml;charset=utf-8
Date: Thu, 16 Dec 2004 17:02:00 GMT
Server: Apache-Coyote/1.1
Connection: close
```

Copyright © 2004 USA Technologies, All Rights Reserved

5.0 Error Handling

This section documents the error responses generated as a result of receiving exceptions or faulty messages. In such cases Aramark Gateway will return a message of AramarkException complex type in the SOAP response. If Aramark Gateway receives an invalid response from Aramark Relay Transaction Server, the responseMessage, responseText, status and statusCode fields will be populated with information received from Aramark Relay Transaction Server. In case of a general exception, the description field will contain the exception message.

Below is a sample AramarkException SOAP response received from Aramark Gateway after sending invalid customer information in the request.


```
<?xml version="1.0" encoding="UTF-8"?>
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
instance">
 <soapenv:Body>
  <soapenv:Fault>
   <faultcode>soapenv:Server.generalException</faultcode>
   <faultstring></faultstring>
   <detail>
    <ns1:fault href="#id0" xmlns:ns1="urn:aramark.usatech.com"/>
    <ns2:exceptionName
xmlns:ns2="http://xml.apache.org/axis/">com.usatech.aramark.webservice.AramarkException</
ns2:exceptionName>
   </detail>
  </soapenv:Fault>
  <multiRef id="id0" soapenc:root="0"
soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
xsi:type="ns3:AramarkException" xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:ns3="urn:aramark.usatech.com">
   <description xsi:type="xsd:string">Received INVALID response status from Aramark Web
Service</description>
   <responseMessage xsi:type="xsd:string">Customer not Registered</responseMessage>
   <responseText xsi:type="xsd:string">NOT REGISTERED</responseText>
   <status xsi:type="xsd:string">InValid</status>
   <statusCode xsi:type="xsd:string">-1</statusCode>
  </multiRef>
 </soapenv:Body>
</soapenv:Envelope>
```


Copyright © 2004 USA Technologies, All Rights Reserved