

1. Pobieramy potrzebną paczkę ze strony <http://www.yiiframework.com/download/>

```
damian@raspberrypi:~  
damian@raspberrypi:~$ wget https://github.com/yiisoft/yii2/releases/download/2.0.11/yii-basic-app-2.0.11.tgz
```

```
damian@raspberrypi:~  
damian@raspberrypi:~$ wget https://github.com/yiisoft/yii2/releases/download/2.0.11/yii-basic-app-2.0.11.tgz  
--2017-03-06 17:44:10-- https://github.com/yiisoft/yii2/releases/download/2.0.11/yii-basic-app-2.0.11.tgz  
Translacja github.com (github.com)... 192.30.253.112, 192.30.253.113  
Łączenie się z github.com (github.com)[192.30.253.112]:443... połączono.  
Żądanie HTTP wysłano, oczekiwanie na odpowiedź... 302 Found  
Lokalizacja: https://github-cloud.s3.amazonaws.com/releases/3431193/48025dfa-e8aa-11e6-8e5a-34ea3cf35c01.tgz?X-Amz-Algorithm=AWS4-HMAC-SHA256&X-Amz-Credential=AKIAISTNZFOVBIJMK3TQ%2F20170306%2Fus-east-1%2F%3Faws4_request&X-Amz-Date=20170306T195024Z&X-Amz-Expires=300&X-Amz-Signature=a865de90e310ffdca0b20fda08272108f4e651ebae77f8b0b3e871b33b3f14e4&X-Amz-SignedHeaders=host&actor_id=0&response-content-disposition=attachment%3B%20filename%3Dyii-basic-app-2.0.11.tgz&response-content-type=application%2Foctet-stream [podążanie]  
--2017-03-06 17:44:11-- https://github-cloud.s3.amazonaws.com/releases/3431193/48025dfa-e8aa-11e6-8e5a-34ea3cf35c01.tgz?X-Amz-Algorithm=AWS4-HMAC-SHA256&X-Amz-Credential=AKIAISTNZFOVBIJMK3TQ%2F20170306%2Fus-east-1%2F%3Faws4_request&X-Amz-Date=20170306T195024Z&X-Amz-Expires=300&X-Amz-Signature=a865de90e310ffdca0b20fda08272108f4e651ebae77f8b0b3e871b33b3f14e4&X-Amz-SignedHeaders=host&actor_id=0&response-content-disposition=attachment%3B%20filename%3Dyii-basic-app-2.0.11.tgz&response-content-type=application%2Foctet-stream  
Translacja github-cloud.s3.amazonaws.com (github-cloud.s3.amazonaws.com)... 54.231.11.144  
Łączenie się z github-cloud.s3.amazonaws.com (github-cloud.s3.amazonaws.com)[54.231.11.144]:443... połączono.  
Żądanie HTTP wysłano, oczekiwanie na odpowiedź... 200 OK  
Długość: 7460613 (7,1M) [application/octet-stream]  
Zapis do: 'yii-basic-app-2.0.11.tgz'  
  
yii-basic-app-2.0.11.tgz 100%[=====] 7,11M 829KB/s w 9,3s  
  
2017-03-06 17:44:21 (781 KB/s) - zapisano 'yii-basic-app-2.0.11.tgz' [7460613/7460613]  
damian@raspberrypi:~$
```

2. Rozpakowujemy zawartość pliku yii-basic-app-2.0.11.tgz w głównym folderze.

```
damian@raspberrypi: ~/www/yii
damian@raspberrypi:~/www/yii $ tar zxvf yii-basic-app-2.0.11.tgz
basic/
basic/web/
basic/web/favicon.ico
basic/web/assets/
basic/web/assets/.gitignore
basic/web/css/
basic/web/css/site.css
basic/web/index.php
basic/web/index-test.php
basic/web/robots.txt
basic/commands/
basic/commands/HelloController.php
basic/requirements.php
basic/vendor/
basic/vendor/bin/
basic/vendor/bin/phpunit
basic/vendor/bin/yii
basic/vendor/bin/codecept
basic/vendor/bin/markdown
basic/vendor/autoload.php
basic/vendor/yiisoft/
basic/vendor/yiisoft/yii2-bootstrap/
basic/vendor/yiisoft/yii2-bootstrap/Alert.php
basic/vendor/yiisoft/yii2-bootstrap/InputGroup.php
basic/vendor/yiisoft/yii2-bootstrap/CHANGELOG.md
basic/vendor/yiisoft/yii2-bootstrap/BootstrapPluginAsset.php
basic/vendor/yiisoft/yii2-bootstrap/BaseHtml.php
basic/vendor/yiisoft/yii2-bootstrap/Widget.php
basic/vendor/yiisoft/yii2-bootstrap/Dropdown.php
basic/vendor/yiisoft/yii2-bootstrap/Collapse.php
basic/vendor/yiisoft/yii2-bootstrap/composer.json
basic/vendor/yiisoft/yii2-bootstrap/Modal.php
basic/vendor/yiisoft/yii2-bootstrap/ButtonGroup.php
basic/vendor/yiisoft/yii2-bootstrap/ToggleButtonGroup.php
basic/vendor/yiisoft/yii2-bootstrap/README.md
basic/vendor/yiisoft/yii2-bootstrap/Nav.php
```

3. Do wszystkich plików i katalogów przypisujemy właściciela i grupę (www-data)

```
damian@raspberrypi: ~/www
damian@raspberrypi:~/www $ sudo chown www-data:www-data yii -R
```

4. Grupie nadajemy prawa do całości

```
damian@raspberrypi: ~/www
damian@raspberrypi:~/www $ sudo chmod 775 yii/ -R
```

5. Edytujemy plik /basic/config/web.php

```
damian@raspberrypi: ~/www/yii/basic/config
GNU nano 2.2.6          Plik: web.php          Zmieniony
<?php
$params = require(__DIR__ . '/params.php');

$config = [
    'id' => 'basic',
    'basePath' => dirname(__DIR__),
    'bootstrap' => ['log'],
    'components' => [
        'request' => [
            // !!! insert a secret key in the following (if it is empty) - this is required by cookie validation
            'cookieValidationKey' => '',
        ],
        'cache' => [
            'class' => 'yii\caching\FileCache',
        ],
        'user' => [
            'identityClass' => 'app\models\User',
            'enableAutoLogin' => true,
        ],
        'errorHandler' => [
            'errorAction' => 'site/error',
        ],
        'mailer' => [
            'class' => 'yii\swiftmailer\Mailer',
            // send all mails to a file by default. You have to set
            // 'useFileTransport' to false and configure a transport
            // for the mailer to send real emails.
            'useFileTransport' => true,
        ],
        'log' => [
            'traceLevel' => YII_DEBUG ? 3 : 0,
            'targets' => [
                [
                    'class' => 'yii\log\FileTarget',
                    'levels' => ['error', 'warning'],
                ],
            ],
        ],
    ],
];
```

```
damian@raspberrypi: ~/www/yii/basic/config
GNU nano 2.2.6 Plik: web.php Zmieniony
<?php
$params = require(__DIR__ . '/params.php');
$config = [
    'id' => 'basic',
    'basePath' => dirname(__DIR__),
    'bootstrap' => ['log'],
    'components' => [
        'request' => [
            // !!! insert a secret key in the following (if it is empty) - this is required by cookie validation
            'cookieValidationKey' => 'projekt',
        ],
        'cache' => [
            'class' => 'yii\caching\FileCache',
        ],
        'user' => [
            'identityClass' => 'app\models\User',
            'enableAutoLogin' => true,
        ],
        'errorHandler' => [
            'errorAction' => 'site/error',
        ],
        'mailer' => [
            'class' => 'yii\swiftmailer\Mailer',
            // send all mails to a file by default. You have to set
            // 'useFileTransport' to false and configure a transport
            // for the mailer to send real emails.
            'useFileTransport' => true,
        ],
        'log' => [
            'traceLevel' => YII_DEBUG ? 3 : 0,
            'targets' => [
                [
                    'class' => 'yii\log\FileTarget',
                    'levels' => ['error', 'warning'],
                ],
            ],
        ],
    ],
];
```

6. Sprawdzamy poprawność instalacji pod adresem <http://damian24.pl/yii/basic/web>

