


# Dumb7Fill (/Dumb7Fill)

✖ It's time for us to say farewell... Regretfully, we've made the tough decision to close Wikispaces. Find out why, and what will happen, here (<http://blog.wikispaces.com>)  Bearbeiten 0 (/Dumb7Fill#discussion) 49 (/page/history/Dumb7Fill) ... (/page/menu/Dumb7Fill)

## Table of Contents

[Occluded Fill](#)  
[Seven Fill Cycles](#)  
[Fill Loop](#)  
[Unrolled Loop](#)  
[Attack Fill](#)  
[Comparison with Kogge-Stone](#)  
[All Directions](#)  
[Generalized Rays](#)  
[Loop Version](#)  
[Unrolled Attacks](#)  
[See also](#)  
[External Links](#)  
[What links here?](#)

[Home](#) \* [Board Representation](#) \* [Bitboards](#) \* [Sliding Piece Attacks](#) \* [Dumb7Fill](#)

**Dumb7Fill** - the obvious, straight forward [flood-fill](#) approach works **set-wise** - **seven** times one fill-cycle by [one step only](#) in one of eight [directions](#). We rely on the [compass rose](#) to identify ray-directions.

noWe		nort		noEa
	+7	+8	+9	
	\		/	
west	-1 <-	0 ->	+1	east
	/		\	
	-9	-8	-7	
soWe		sout		soEa



Code samples and bitboard diagrams rely on [Little endian file and rank mapping](#).

## Occluded Fill

An [occluded](#) fill includes the flood generating [sliding pieces](#), but excludes the blocker. It is base of attack fills. One additional [direction shift](#) excludes the sliders but includes the blocker.

## Seven Fill Cycles

The sliding pieces generate the flood. They were [shifted one step](#) in the desired direction and [intersected](#) with the set of empty squares, the propagator. The flood aggregates the intersection and the cycle repeats six further times to cover the maximum [distance](#) on the [chessboard](#). A blocker, not member of propagator, stops the flood in that particular ray-direction for one sliding piece. Therefor occluded fill contains the initial generator but excludes any blocker.

```
U64 sout0ccl(U64 gen, U64 pro) {
    for (int cycle = 0; cycle < 7; cycle++)
        gen |= pro & (gen >> 8);
    return gen;
}
```

## Fill Loop

Alternatively one may save move-instructions by introducing an explicit flood accumulator, and to probably terminate the loop early if the flood stops:

```
U64 sout0ccl(U64 gen, U64 pro) {
    U64 flood = 0;
    while (gen) {
        flood |= gen;
        gen = (gen >> 8) & pro;
    }
    return flood;
}
```

## Unrolled Loop

It's time for us to say farewell. Regretfully, we've made the tough decision to close Wikispaces. Find out why, and what will happen, here (<http://blog.wikispaces.com>)

```
U64 sout0cc1(U64 gen, U64 pro) {
    U64 flood = gen;
    flood |= gen = (gen >> 8) & pro;
    flood |= gen = (gen >> 8) & pro;
    flood |= gen = (gen >> 8) & pro;
    flood |= gen = (gen >> 8) & pro;
    flood |= gen = (gen >> 8) & pro;
    flood |= gen = (gen >> 8) & pro;
    flood |= (gen >> 8) & pro;
    return flood;
}
```

Some south fill cycles in slow motion:

```
flood = gen =
brooks|bqueen    empty
1 . . . . .      . 1 1 1 1 1 . 1
. . . 1 . . . .  1 1 . . 1 . 1 .
. . . . . . . .  1 . 1 1 1 1 . 1
. . . . . . . .  1 1 . 1 1 1 1 1
. . . . . 1 . .  1 1 1 . 1 . 1 1
. . . . . . . .  1 1 . 1 1 1 1 .
. . . . . . . .  . . . 1 1 . . 1
. . . . . . . .  . 1 1 . 1 1 . 1
1.fill
gen = gen >> 8 & empty    => flood
. . . . . . . . . . . . . . 1 . . . . .
1 . . . . . . . . . . . . . 1 . . 1 . . .
. . . 1 . . . . . . . . . . 1 . . . . .
. . . . . . . . . . . . . . . . . . . .
. . . . . . . . . . . . . . . . . 1 . .
. . . . . 1 . . . . . . . . . 1 . . . .
. . . . . . . . . . . . . . . . . . . .
. . . . . . . . . . . . . . . . . . . .
2.fill
gen = gen >> 8 & empty    flood |= ...
. . . . . . . . . . . . . . 1 . . . . .
. . . . . . . . . . . . . . 1 . . 1 . . .
1 . . . . . . . . . . . . . 1 . . 1 . . .
. . . 1 . . . . . . . . . . 1 . . . . .
. . . . . . . . . . . . . . . . . 1 . .
. . . . . . . . . . . . . . . . . 1 . .
. . . . . 1 . . . . . . . . . 0 . . . . .
. . . . . . . . . . . . . . . . . . . .
3.fill
gen = gen >> 8 & empty    flood |= ...
. . . . . . . . . . . . . . 1 . . . . .
. . . . . . . . . . . . . . 1 . . 1 . . .
. . . . . . . . . . . . . . 1 . . 1 . . .
1 . . . . . . . . . . . . . 1 . . 1 . . .
. . . 1 . . . . . . . . . . 0 . . . . .
. . . . . . . . . . . . . . . . . 1 . .
. . . . . . . . . . . . . . . . . 1 . .
. . . . . . . . . . . . . . . . . . . .
...
6.fill
gen = gen >> 8 & empty    flood |= ...
. . . . . . . . . . . . . . 1 . . . . .
. . . . . . . . . . . . . . 1 . . 1 . . .
. . . . . . . . . . . . . . 1 . . 1 . . .
. . . . . . . . . . . . . . 1 . . 1 . . .
. . . . . . . . . . . . . . 1 . . . . 1 .
. . . . . . . . . . . . . . 1 . . . . 1 .
1 . . . . . . . . . . . . . 0 . . . . .
. . . . . . . . . . . . . . . . . . . .
```

The flood already stopped, the final 7th fill cycles don't change anything.

**Attack Fill** It's time for us to say farewell... Regretfully, we've made the tough decision to close Wikispaces. Find out why, and what will happen, here (<http://blog.wikispaces.com>)  
To get attacks, one additional [direction shift](#) of the occluded fill is necessary to exclude the rooks/queen and include the blocker:

```
U64 soutAttacks (U64 rooks, U64 empty) {return soutOne(soutOccl(rooks, empty));}
```

Comparison with Kogge-Stone

To combine the dumb7fill as attack getter, we also can take advantage of [outer square](#) occupancy doesn't affect the attack set. We need one fill cycle less, before the final shift. That takes 19 operations. In anticipation to [parallel prefix](#), a [Kogge-Stone](#) approach takes 14 instructions, 5 less. Kogge-Stone needs more move-instructions and a temporary register to compute generator as well as propagator, while dumb7fill uses a const propagator:

dumb7fill	Kogge-Stone Algorithm
U64 soutAttacks(U64 rooks, U64 empty) { U64 flood = rooks; flood  = rooks = (rooks >> 8) & empty; flood  = rooks = (rooks >> 8) & empty; flood  = rooks = (rooks >> 8) & empty; flood  = rooks = (rooks >> 8) & empty; flood  = rooks = (rooks >> 8) & empty; flood  = (rooks >> 8) & empty; return flood >> 8; }	U64 soutAttacks(U64 rooks, U64 empty) { rooks  = empty & (rooks >> 8); empty = empty & (empty >> 8); rooks  = empty & (rooks >> 16); empty = empty & (empty >> 16); rooks  = empty & (rooks >> 32); return rooks >> 8; }
in x86/64 assembly ; dumb7fill ; rooks rdx ; empty rcx  mov rax, rdx  shr rdx, 8 and rdx, rcx or rax, rdx  shr rdx, 8 and rdx, rcx or rax, rdx  shr rdx, 8 and rdx, rcx or rax, rdx  shr rdx, 8 and rdx, rcx or rax, rdx  shr rdx, 8 and rdx, rcx or rax, rdx  shr rax, 8  1 move 19 operations 20 instructions	in x86/64 assembly ; koggeStone ; rooks rdx ; empty rcx  mov rax, rdx shr rax, 8 and rax, rcx or rdx, rax  mov rax, rcx shr rax, 8 and rcx, rax  mov rax, rdx shr rax, 16 and rax, rcx or rdx, rax  mov rax, rcx shr rax, 16 and rcx, rax  mov rax, rdx shr rax, 32 and rax, rcx or rax, rdx  shr rax, 8  5 moves 14 operations 19 instructions

Thus, dumb7fill is not that bad, specially if processing several directions in parallel, like south and north, all east and all west attacks.

All Directions

```
U64 soutAttacks(U64 rooks, U64 empty) {  
  U64 flood = rooks;  
  flood |= rooks = (rooks >> 8) & empty;
```

```

flood |= rooks = (rooks >> 8) & empty;
flood |= rooks = (rooks >> 8) & empty;
flood |= rooks = (rooks >> 8) & empty;
flood |= rooks = (rooks >> 8) & empty;
flood |= rooks = (rooks >> 8) & empty;
flood |= rooks = (rooks >> 8) & empty;
flood |= rooks = (rooks >> 8) & empty;
flood |= rooks = (rooks >> 8) & empty;
return flood >> 8;
}

```

It's time for us to say farewell. Regrettably, we've made the tough decision to close Wikispaces. Find out why, and what will happen, here (<http://blog.wikispaces.com>).

```

U64 nortAttacks(U64 rooks, U64 empty) {
    U64 flood = rooks;
    flood |= rooks = (rooks << 8) & empty;
    flood |= rooks = (rooks << 8) & empty;
    flood |= rooks = (rooks << 8) & empty;
    flood |= rooks = (rooks << 8) & empty;
    flood |= rooks = (rooks << 8) & empty;
    flood |= rooks = (rooks << 8) & empty;
    flood |= rooks = (rooks << 8) & empty;
    return flood << 8;
}

```

Horizontal fills need to consider wraps from H-file to A-file and vice versa. Fortunately this can be combined by intersection of ~A-file or ~H-file with the propagator:

```

U64 eastAttacks(U64 rooks, U64 empty) {
    const U64 notA = C64(0xfefefefefefefefe);
    U64 flood = rooks;
    empty &= notA;
    flood |= rooks = (rooks << 1) & empty;
    flood |= rooks = (rooks << 1) & empty;
    flood |= rooks = (rooks << 1) & empty;
    flood |= rooks = (rooks << 1) & empty;
    flood |= rooks = (rooks << 1) & empty;
    flood |= rooks = (rooks << 1) & empty;
    flood |= rooks = (rooks << 1) & empty;
    return (flood << 1) & notA ;
}

U64 noEaAttacks(U64 bishops, U64 empty) {
    const U64 notA = C64(0xfefefefefefefefe);
    U64 flood = bishops;
    empty &= notA;
    flood |= bishops = (bishops << 9) & empty;
    flood |= bishops = (bishops << 9) & empty;
    flood |= bishops = (bishops << 9) & empty;
    flood |= bishops = (bishops << 9) & empty;
    flood |= bishops = (bishops << 9) & empty;
    flood |= bishops = (bishops << 9) & empty;
    flood |= bishops = (bishops << 9) & empty;
    flood |= bishops = (bishops << 9) & empty;
    return (flood << 9) & notA ;
}

U64 soEaAttacks(U64 bishops, U64 empty) {
    const U64 notA = C64(0xfefefefefefefefe);
    U64 flood = bishops;
    empty &= notA;
    flood |= bishops = (bishops >> 7) & empty;
    flood |= bishops = (bishops >> 7) & empty;
    flood |= bishops = (bishops >> 7) & empty;
    flood |= bishops = (bishops >> 7) & empty;
    flood |= bishops = (bishops >> 7) & empty;
    flood |= bishops = (bishops >> 7) & empty;
    flood |= bishops = (bishops >> 7) & empty;
    flood |= bishops = (bishops >> 7) & empty;
    return (flood >> 7) & notA ;
}

U64 westAttacks(U64 rooks, U64 empty) {
    const U64 notH = C64(0x7f7f7f7f7f7f7f7f);
    U64 flood = rooks;
    empty &= notH;
    flood |= rooks = (rooks >> 1) & empty;
    flood |= rooks = (rooks >> 1) & empty;
    flood |= rooks = (rooks >> 1) & empty;
    flood |= rooks = (rooks >> 1) & empty;
    flood |= rooks = (rooks >> 1) & empty;
    flood |= rooks = (rooks >> 1) & empty;
    flood |= rooks = (rooks >> 1) & empty;
    flood |= rooks = (rooks >> 1) & empty;
    return (flood >> 1) & notH ;
}

```

```
}
```

```
U64 nowAttacks(U64 bishops, U64 empty) {
    // It's time for us to say farewell. Regrettably, we've made the tough decision to close Wikispaces. Find out why, and what will
    // happen here: http://blog.wikispaces.com
    const U64 notH = C64(0x7f7f7f7f7f7f7f7f);
    U64 flood = bishops;
    empty &= notH;
    flood |= bishops = (bishops >> 9) & empty;
    flood |= bishops = (bishops >> 9) & empty;
    flood |= bishops = (bishops >> 9) & empty;
    flood |= bishops = (bishops >> 9) & empty;
    flood |= bishops = (bishops >> 9) & empty;
    flood |= bishops = (bishops >> 9) & empty;
    flood |= bishops = (bishops >> 9) & empty;
    return (flood >> 9) & notH ;
}
```

```
U64 nowAttacks(U64 bishops, U64 empty) {
    const U64 notH = C64(0x7f7f7f7f7f7f7f7f);
    U64 flood = bishops;
    empty &= notH;
    flood |= bishops = (bishops << 7) & empty;
    flood |= bishops = (bishops << 7) & empty;
    flood |= bishops = (bishops << 7) & empty;
    flood |= bishops = (bishops << 7) & empty;
    flood |= bishops = (bishops << 7) & empty;
    flood |= bishops = (bishops << 7) & empty;
    flood |= bishops = (bishops << 7) & empty;
    flood |= bishops = (bishops << 7) & empty;
    return (flood << 7) & notH ;
}
```

## Generalized Rays

Since [rotate](#) works like a [generalized shift](#) with positive or negative shift amount - since it internally applies a modulo 64 and makes  $-i = 64-i$ . We need to clear either the lower or upper bits by intersection with a mask, which might be combined with the wrap-and's for [one step](#). It might be applied to get attacks for both sides with a direction parameter and small lookups for shift amount and wrap-and's - instead of multiple code for eight directions. Of course generalized shift will be a bit slower due to lookups and using `cl` as the shift amount register.

## Loop Version

This is the loop-version:

```
U64 occludedFill (U64 gen, U64 pro, int dir8) {
    U64 flood = 0;
    if (gen) {
        int r = shift[dir8]; // {+1,7,8,9}
        pro &= avoidWrap[dir8];
        do {
            flood |= gen;
            gen = rotateLeft(gen, r) & pro;
        } while (gen);
    }
    return flood;
}

U64 shiftOne (U64 b, int dir8) {
    int r = shift[dir8]; // {+1,7,8,9}
    return rotateLeft(b, r) & avoidWrap[dir8];
}

U64 slidingAttacks (U64 sliders, U64 empty, int dir8) {
    U64 fill = occludedFill(sliders, empty, dir8)
    return shiftOne(fill, dir8);
}

// positive left, negative right shifts
int shift[8] = {9, 1,-7,-8,-9,-1, 7, 8};

U64 avoidWrap[8] =
{
    0xfefefefefefefe00,
    0xfefefefefefefefe,
    0x00fefefefefefefe,
```

```

0x00fffffffffffff,
0x007f7f7f7f7f7f,
0x7f7f7f7f7f7f7f,
0x7f7f7f7f7f7f00,
0xffffffffffff00,
};

```

It's time for us to say farewell... Regretfully, we've made the tough decision to close Wikispaces. Find out why, and what will happen, here (<http://blog.wikispaces.com>)

The avoidWrap masks by some arbitrary dir8 enumeration and shift amount:

```

6 == nowe -> +7      7 == nort -> +8      0 == noEa -> +9
0x7F7F7F7F7F7F00  0xFFFFFFFFFFFF00  0xFEFEFEFEFEFE00

1 1 1 1 1 1 1 .    1 1 1 1 1 1 1 1    . 1 1 1 1 1 1 1
1 1 1 1 1 1 1 .    1 1 1 1 1 1 1 1    . 1 1 1 1 1 1 1
1 1 1 1 1 1 1 .    1 1 1 1 1 1 1 1    . 1 1 1 1 1 1 1
1 1 1 1 1 1 1 .    1 1 1 1 1 1 1 1    . 1 1 1 1 1 1 1
1 1 1 1 1 1 1 .    1 1 1 1 1 1 1 1    . 1 1 1 1 1 1 1
1 1 1 1 1 1 1 .    1 1 1 1 1 1 1 1    . 1 1 1 1 1 1 1
1 1 1 1 1 1 1 .    1 1 1 1 1 1 1 1    . 1 1 1 1 1 1 1
1 1 1 1 1 1 1 .    1 1 1 1 1 1 1 1    . 1 1 1 1 1 1 1
. . . . . . . .    . . . . . . . .    . . . . . . . .

5 == west -> -1      1 == east -> +1
0x7F7F7F7F7F7F00  0xFEFEFEFEFEFEFEFE

1 1 1 1 1 1 1 .    . 1 1 1 1 1 1 1
1 1 1 1 1 1 1 .    . 1 1 1 1 1 1 1
1 1 1 1 1 1 1 .    . 1 1 1 1 1 1 1
1 1 1 1 1 1 1 .    . 1 1 1 1 1 1 1
1 1 1 1 1 1 1 .    . 1 1 1 1 1 1 1
1 1 1 1 1 1 1 .    . 1 1 1 1 1 1 1
1 1 1 1 1 1 1 .    . 1 1 1 1 1 1 1
1 1 1 1 1 1 1 .    . 1 1 1 1 1 1 1
1 1 1 1 1 1 1 .    . 1 1 1 1 1 1 1

4 == soWe -> -9      3 == sout -> -8      2 == soEa -> -7
0x007F7F7F7F7F00  0x00FFFFFFFFFFFF  0x00FEFEFEFEFEFEFE

. . . . . . . .    . . . . . . . .    . . . . . . . .
1 1 1 1 1 1 1 .    1 1 1 1 1 1 1 1    . 1 1 1 1 1 1 1
1 1 1 1 1 1 1 .    1 1 1 1 1 1 1 1    . 1 1 1 1 1 1 1
1 1 1 1 1 1 1 .    1 1 1 1 1 1 1 1    . 1 1 1 1 1 1 1
1 1 1 1 1 1 1 .    1 1 1 1 1 1 1 1    . 1 1 1 1 1 1 1
1 1 1 1 1 1 1 .    1 1 1 1 1 1 1 1    . 1 1 1 1 1 1 1
1 1 1 1 1 1 1 .    1 1 1 1 1 1 1 1    . 1 1 1 1 1 1 1
1 1 1 1 1 1 1 .    1 1 1 1 1 1 1 1    . 1 1 1 1 1 1 1
1 1 1 1 1 1 1 .    1 1 1 1 1 1 1 1    . 1 1 1 1 1 1 1

```

## Unrolled Attacks

The generalized unrolled sliding attack getter:

```

U64 slidingAttacks (U64 sliders, U64 empty, int dir8) {
    U64 flood = sliders;
    int r = shift[dir8]; // {+1,7,8,9}
    empty &= avoidWrap[dir8];
    flood |= sliders = rotateLeft(sliders, r) & empty;
    flood |= sliders = rotateLeft(sliders, r) & empty;
    flood |= sliders = rotateLeft(sliders, r) & empty;
    flood |= sliders = rotateLeft(sliders, r) & empty;
    flood |= sliders = rotateLeft(sliders, r) & empty;
    flood |= sliders = rotateLeft(sliders, r) & empty;
    return rotateLeft(flood, r) & avoidWrap[dir8];
}

```

## See also

- [AVX2 Dumb7Fill](#)
- [Fill Algorithms](#)
- [Kogge-Stone Algorithm](#)
- [Pieces versus Directions](#)

## External Links

- [bitboard mobility](#) Copyright (c) 2003, [Gunnar Andersson](#) » [Othello](#), [Mobility](#).

- [Weather Report - Seventh Arrow / Umbrellas, 1971](#) , [YouTube](#) Video

[Joe Zawinui](#), [Wayne Shorter](#), [Miroslav Vitouš](#), [Alphonse Mouzon](#), [Dom Um Romão](#)

✖ It's time for us to say farewell... Regretfully, we've made the tough decision to close Wikispaces. Find out why, and what will happen, here (<http://blog.wikispaces.com>)

## Weather Report - Seventh Arrow / Umbrellas



### What links here?

Page	Date Edited
<a href="#">AVX2</a>	Aug 8, 2017
<a href="#">DirGolem</a>	Jun 5, 2016
<a href="#">Dumb7Fill</a>	May 27, 2016
<a href="#">Efficient Generation of Sliding Piece Attacks</a>	Nov 5, 2016
<a href="#">Fill Algorithms</a>	Nov 6, 2013
<a href="#">Gaviota</a>	Jan 21, 2018
<a href="#">General Setwise Operations</a>	Feb 25, 2018
<a href="#">Gunnar Andersson</a>	Jun 23, 2011
<a href="#">Influence Quantity of Pieces</a>	Jul 21, 2017
<a href="#">John L. Jerz</a>	Jul 15, 2013
<a href="#">Kogge-Stone Algorithm</a>	Sep 17, 2016
<a href="#">Lachex</a>	Jan 7, 2016
<a href="#">Little Wing</a>	Oct 26, 2017
<a href="#">Mobility</a>	Jan 17, 2018
<a href="#">Othello</a>	Jan 4, 2018
<a href="#">Pieces versus Directions</a>	Oct 6, 2016
<a href="#">Sequential Logic</a>	May 10, 2017
<a href="#">Shifted Bitboards</a>	Jan 9, 2011
<a href="#">SIMD and SWAR Techniques</a>	Jun 27, 2017
<a href="#">Sliding Piece Attacks</a>	May 27, 2016
<a href="#">More Links</a>	

[Up one Level](#)