

SOFTWARE	ERROR	IMAGE	CAUSE	RESOLUTION
Chat Recorder	Chat ID(s) this has been configured to record but can't see : 10.0.1.1\SMARTChat7_Parc des Princes	LINK	Chat Recorder can't see SMARTChat 7 which is Ref Mix A	Make sure SMARTChat1 is launched on 10.0.1.21. If still no good, check the location of SMARTChats haven't changed on smartfile and CHATRecorder doesn't have a red deploy sign to action.
DataFeedArchiver	Failed creating archive: No cameras are selected	LINK	DataFeedArchiver is likely trying to export angles on an event that has already been archived previously, meaning it can't do it again.	Kill DFA then delete all backup export clips on -.39/Export. Reset Working Directory for DFA and relaunch.
DataFeedArchiver	Failed creating archive: Cannot create "\\10.0.2.39\exports..."	LINK	DFA is trying to create an archive in a folder which doesn't exist or isn't shared.	Create and share the expected destination folder (in this example \\10.0.2.39\exports)
DataFeedArchiver	Failed creating archive: Timed out when attempting to access "\\10.0.2.39\exports..."	LINK	DFA is trying to create an archive in a folder which doesn't exist or isn't shared. Alternatively, your network connection between the DFA server and the folder server could be slow and timing out	Create and share the expected destination folder (in this example \\10.0.2.39\exports). Make sure the network connection is stable and you can access destination folder from DFA server.
Football Clip Feed Generator	Getting a "503 Service Temporarily Unavailable" when typing the following URL : https://api.stage.football.data.hawkeyeinnovations.com:9484/clipFeedGenerator/actuator/health	LINK	The FSP API connection is temporarily down and match events from the platform will not be accessible.	Inform Remote Support about this issue if this hasn't already been raised.
Football Clip Feed Generator	Not getting the "Status Up" message in Chrome to confirm the connection to FSP API when typing the following URL : https://api.stage.football.data.hawkeyeinnovations.com:9484/clipFeedGenerator/actuator/health		Cause #1 : You don't have an internet connection on the server you are trying to access the URL with. Cause #2 : The firewall used in the van, or the internet provider, is blocking the port dedicated to FSP API which is 9484	Solution #1 : Make sure you have a functional internet connection on the server used to test the URL. Solution #2 : Unblock port 9484 in the firewall settings (ask remote support for help on this) or get the internet provider to unblock it their end.
HEO	Cannot use card 2 because it is linked to card 1. You need to change the connector settings in Blackmagic Desktop Video Setup to fix this.		The connector settings in Desktop Video Setup are mapped so that SDI1 & SDI2 are connected.	Go to Blackmagic Desktop Video Setup, open settings when Decklink Quad (1) is selected, go to "Connectors" and make sure the "Connection" is set to SDI1 instead of SDI1 &SDI2.
HEO	Cannot initialise Decklink output. Display mode "1080p50" is not supported on this card	LINK	The decklink card used probably doesn't support progressive formats	Ideally, change decklink quad for a compatible one.
OffsideLine	Cannot obtain context from pool for a captured frame	LINK	Cause #1 : Faulty decklink card input, leading to dropped frames Cause #2 : High CPU (usually over 75%), meaning the software can't handle	Solution #1 : Identify whether decklink input or BNC cable is faulty (check VideoHub) Solution #2 : Improve CPU load on server by node balancing or killing/moving software
OffsideLine	CRITICAL ERROR: Shared buffer error: "Error initialising shared buffer "\\CAMERA1_BUFFER": FramesSharedBuffer::CreateOrAccess: ERROR.\nbuffer CAMERA1_BUFFER exists with: \nimages=YUV422P_8Bit\nwidth=1920\nheight=540\nmax audio packet size=0\nnumber of frames=10\n\nCannot attempt to access using: \nimages=YUV422P_8Bit\nwidth=1920\nheight=1080\nmax audio packet size=0\nand number of frames=10"	LINK	The offsideLine is sharing it buffer in 2 separate formats and can't access both simultaneously. This can happen for 2 reasons : Cause #1 : OffsideLine was initially launched without applying the correct deinterlacing productions, and was then redeployed and launched with the correct production, meaning the disk buffer contains both buffer types. Cause #2 : If still seeing this after Cause #1, this would be because the OffsideLine is still connected to another instance (OMCA for example) which hasn't been redeployed and launched with the updated settings and is therefore running the old buffer settings.	Solution #1 : Once you have applied the correct productions (Deinterlace Offside False applied if progressive feeds from HB), clear buffers on the OffsideLine disk and then launch your OffsideLine. Solution #2 : Redeploy and launch the connected instance (most likely an OMCA).
OffsideLine	ERROR: Invalid Decklink option: "10 bit conversion of progressive to interlaced is not supported"	LINK	We are seeing this issue because we are trying to deinterlace a 10 bit input on our OffsideLine but our feed is currently running in an interlaced format. Alternatively, it could be that we have told the OffsideLine to convert a 10bit feed when we are actually receiving it as an 8 bit input (almost always 8 bit). If HB feed is progressive, it is likely that you have "VAR_Offside_Maintain_Progressive" applied but not "Deinterlace Offside False"	If providing EPTS, make sure you have VAR_Offside_Maintain_Progressive applied, as well as Deinterlace Offside False applied if HB is providing a progressive format.
OffsideLine	Failed to load pitch model from file: "Filepath pitch_model.json"		pitch_model.json file does not exist for said stadium in OffsideStadiums production	Add pitch_model.json exists in the appropriate stadium folder in OffsideStadiums production (might need to create the stadium folder too)
OffsideLine	The interlaced format (non-EPTS games) of the OffsideLine footage is incorrect, displaying a vertical rectangle format.	LINK	If HB is providing progressive footage, this means you are deinterlacing your footage most likely because you don't have "General/Deinterlace Offside False" applied globally	If in progressive footage, apply "General/Deinterlace Offside False" production to Global and reapply productions.
OffsideLine	The interlaced format (non-EPTS games) of the OffsideLine footage is incorrect, displaying horizontal rectangle format.	LINK	If HB is providing interlaced footage, this means you are not deinterlacing your footage most likely because you have "General/Deinterlace Offside False" applied globally	If in interlaced footage, delete "General/Deinterlace Offside False" production from Global and reapply productions.
OffsideLine	The progressive format (EPTS games) of the OffsideLine footage is incorrect, displaying a vertical rectangle format.	LINK	If HB is providing progressive footage and you have "VAR_Maintain_Progressive" production applied globally, this means you are deinterlacing your footage most likely because you don't have "General/Deinterlace Offside False" applied globally	If in progressive footage, apply "General/Deinterlace Offside False" production to Global and reapply productions.
OffsideLine	The progressive format (EPTS games) of the OffsideLine footage is incorrect, displaying horizontal rectangle format.	LINK	If HB is providing interlaced footage and you have "VAR_Maintain_Progressive" production applied globally, this means you are not deinterlacing your footage most likely because you have "General/Deinterlace Offside False" applied globally	If in interlaced footage, delete "General/Deinterlace Offside False" production from Global and reapply productions.
OffsideLine	Warning: Line Tracking: "Line tracking is disabled"	LINK	The offsideLine you are looking at has line tracking disabled, most likely because this is an R2.	If you want it enabled for some reason, you can either go on the OffsideLine and ticked "Enable Line Tracking" or hit Alt+X in Viewer and tick the "Enable Line Tracking" option for the matching OffsideLine in that panel.
SMART Remote Client	Screen displays "Waiting for Data..." when trying to Smart Remote onto a machine	LINK	The network connection between both servers is too slow for the data to go through.	Improve your network connection between both servers (both ways). Make sure your bandwidth is sufficient and no other servers are slowing the entire network.
SMARTArchiver	Cannot connect to SMARTElastic on http://10.0.2.41:9201	LINK	The SMARTElastic mentioned is not launched.	Launch the SMARTElastic mentioned and make sure you get a successful connection
SMARTArchiver	SMARTElastic: Exception when updating data: WinHttpRequestResponse: 12002: The operation timed out	LINK	The Archiver can't work because the Elastic mentioned is not working or launched.	Refer to the SMARTElastic instances for more information on errors and how to solve them. Once all your Elastic instances are working, you will see connections to Viewers etc at the top of the GUI
SMARTBlender	ERROR: Cannot connect to SDI output buffer: "Buffer: DOI_Buffer_VVC3_Blender1, Error: Audio is not being produced fast enough, dropping a packet"	LINK	The format between Blender and the resulting output instance do not match (p50 vs i50)	Make sure the Blender and the previous VVC (containing the audio) have the same format. In UEFA this is set up correctly for interlace formats, and requires Progressive_Output_UEFA production for P formats
SMARTBlender	SDI output error: "Dropping frame on SDI Output as we've processed two down fields in a row"		The format between Blender and the resulting output instance do not match	Make sure the Blender and the resulting HEO have the same format. In UEFA this is set up correctly for interlace formats, and requires Progressive_Output_UEFA production for P formats
SMARTChat	Registry Key: "SOFTWARE\Microsoft\Microsoft NTCurrentVersion\Multimedia\SystemProfile\NetworkThrottlingIndex" has a value of -1but the recommended value is 50. Please change the value and restart the PC.	LINK	This will not prevent the SMARTChat or Chat Controller from working as expected but might slightly affect the network capacity of audio setup so best to change it. The Network Throttling Index on your server has a wrong value that needs changing.	Go to the Registry Editor, then double-clicking on NetworkThrottlingIndex. Click "Adapt", click "Decimal" and change the number to 50. Restart the PC.
SMARTChat	SMARTChat's output device is disconnected or unavailable.		The headset linked to the SMARTChat was disconnected or disabled.	Make sure the headset is physically connected and appears in Windows Sounds.
SMARTChat	Audio input device "VAR (HyperX Virtual Surround Sound)" doesn't support the required audio settings.		This happens when you change the name of an audio input device in Windows Sounds Recording tab.	Kill SMARTChat, then go to Windows Sound and disable + reenable the recording and playback device you are trying to use for this SMARTChat. Reset WD on the SMARTChat then launch.
SMARTChat	Audio output device "VAR (HyperX Virtual Surround Sound)" doesn't support the required audio settings.		This happens when you change the name of an audio output device in Windows Sounds Playback tab.	Kill SMARTChat, then go to Windows Sound and disable + reenable the recording and playback device you are trying to use for this SMARTChat. Reset WD on the SMARTChat then launch.
SMARTData	FATAL : password authentication failed for user "postgres"		PostgreSQL is needed for SMARTData to work and it is not installed	Install PostgreSQL using linked guide
SMARTElastic	SMARTElastic: Failed to get data: WinHttpRequest: 12029: A connection with the server could not be established	LINK	Cause #1 : The instance can't access the server because of software blocking it (i.e. firewall enabled). Cause #2 : A previous SMARTElastic has been launched on this server before but with different conflicting settings	Solution #1 : Disable Firewall on server, the connection should work immediately. Solution #2 : Delete the existing SMARTElastic Working Directory then reset WD and launch. It's worth noting you will often need to delete the SMARTElastic folder in the specific drive it writes too in addition to the WD.
SMARTElastic	Error sending request to host : WinHttpRequest: 12002: The operation timed out	LINK	Cause #1 : The instance can't access the server because of software blocking it (i.e. firewall enabled). Cause #2 : A previous SMARTElastic has been launched on this server before but with different conflicting settings	Solution #1 : Disable Firewall on server, the connection should work immediately. Solution #2 : Delete the existing SMARTElastic Working Directory then reset WD and launch. It's worth noting you will often need to delete the SMARTElastic folder in the specific drive it writes too in addition to the WD.
SMARTElastic	Cannot allocate because allocation is not permitted to any of the nodes	LINK	SMARTElastic is trying to run but is blocked by the firewall on your server	Disable your firewall on the server, the connection should work within seconds
SMARTElastic	SMARTElastic: Failed to delete by query data in archivers-1: Service Unavailable	LINK	The instance can't find the archivers-1 folder as the SMARTElastic connection is not working as expected. One or more of the SMARTElastics in the cluster haven't established a working connection. Check which SMARTElastic is not seeing the relevant folders in its GUI. Cause #1 : The SMARTElastic on one server might be struggling because of software blocking it (i.e. firewall enabled). Cause #2 : A previous SMARTElastic has been launched on this server before but with different conflicting settings	Solution #1 : Disable Firewall on server, the connection should work immediately. Solution #2 : Delete the existing SMARTElastic Working Directory then reset WD and launch. It's worth noting you will often need to delete the SMARTElastic folder in the specific drive it writes too in addition to the WD.
SMARTGraphics	Triple "Video Assistant Referee" displayed as VAR message on Giant Screen output, instead of correct VAR messages	LINK	SMARTGraphics is not sending the VAR messages as it is not receiving them properly from the CSV text file.	Reimport the master CSV file in VARDict application (Settings). If this doesn't work, you will want to reapply the rundown.json in SMARTGraphics Chrome page so that it know what to look for. Final solution is to reset WD of SMARTGraphics and then reimport the package which will reset the information.

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]

[illegible]