# Section 1 - Qt Creator Familiarisation see the official manual

## **Useful Qt Creator keyboard shortcuts**

- CTRL-'DEL' toggle code folding
- CTRL-'/' toggle comment
- CTRL-'A'-'I' auto-indent selected text
- CTRL-'TAB' go to previously selected file
- F4 switch from hpp to cpp or back
- SHIFT-'F4' switch to UI file and back
- CTRL-SHIFT-'B' build all
- CTRL-ALT-'C' compile current file
- ALT-'G'-'C' git commit
- ALT-'ENTER' list quick fixes
- ALT-'ENTER' list quick fixes; when inheriting abstract base class place cursor next to class name (e.g. class MyClass: public AbstractClass),
   then select 'Insert Virtual Functions of Base Class'
- CTRL-SHIFT-'R' rename symbol under cursor
- ALT-'0' toggle left pane (usually includes the project explorer)
- ALT-'1..10' toggle tabs on the bottom pane
- F1 context sensitive help; ESC twice to close
- CTRL-SHIFT-'V' shows clipboard stack
- · CTRL-'M' toggle bookmark
- Use capitals to abbreviate class names and get a list, e.g. QSI gives a drop down including QStandardItem
  - Then ALT-'ENTER' for a quick fix to #include the header if not already included
- · Default quick fix for change to parameter list
- Create a faux c#-style region:
  - #pragma <REGION> {
  - #pragma <ENDREGION> }

# Directory and file locations

## Designer widget plugins:

- For standalone designer, copy to: C:\Qt\Tools\QtCreator\bin\plugins\designer
- For Qt Creator internal designer, copy to C:\Qt\<QT\_VERSION>\<BUILD\_KIT>\plugins\designer
- · Copy dependencies to:
  - C:\Qt\<QT VERSION>\<BUILD KIT>\bin
  - C:\Qt\Tools\QtCreator\bin

## **Custom templates:**

- Copy from: C:\Qt\Tools\QtCreator\share\qtcreator\templates\wizards
- Copy to: C:\Users\<USER NAME>\AppData\Roaming\QtProject\qtcreator\templates\wizards

#### Other locations:

• snippets.xml C:\Users\<USER\_NAME>\AppData\Roaming\QtProject\qtcreator\snippets

## Other Qt Creator features

#### Command line options - See here

## Window split

## **Custom templates - See here**

#### **External tools**

## Creator variables See here for a general discussion

#### Most useful/most often used:

```
%{ActiveProject:Path} - root path (where your .pro file lives)
%{ActiveProjectBuildConfig:Path} - output path for build operations
%{ActiveProjectBuildConfig:Type} - e.g. release | debug | profile
%{ActiveProject:Name} - name of the current ActiveProject
%{UUID} - generate a new UUID
%{CPP:LicenceTemplate} - licences template from 'Preferences'
%{CurrentDate:Locale} - date in locale specific format (e.g. 04/04/2024)
%{CurrentDate:ISO} - date in ISO format (e.g. 2024-04-04)
%{CurrentDate:RFC} - date in RFC format (e.g. 04 Apr 2024)
%{CurrentTime:Locale} - time in locale specific format (e.g. 12:12:12)
%{CurrentTime:RFC} - time in ISO format (same as above)
```