

CORGI ETF TRUST · N-PORT IN-HOUSE SERVICE

N-PORT In-House Runbook

A field-by-field operating guide showing what supplies each value, exactly where it is entered, how human review works, and what blocks release.

As of August 3, 2026 · Source boundary corrected

Controlling rule: no file, value, mapping, or pre-fill delivered by U.S. Bank may populate the in-house filing. Those artifacts are read-only comparison evidence.

1. Purpose and non-negotiable boundary

This runbook operates an N-PORT service built from independent sources. U.S. Bank custody exports, EagleSTAR attachments, prepared filings, email attachments, and prior master workbooks are benchmark outputs only. They may never be copied, merged, seeded, or used to clear a production exception.

Stop rule: if the only available answer comes from U.S. Bank, record the field as missing and keep the filing blocked.

2. Status language

STATUS	USE IT WHEN	OPERATOR ACTION
MISSING	The field or evidence does not exist.	Obtain it from the named independent owner/source.
BLOCKED	Release must stop because an applicable item is missing, invalid, stale, unapproved, prohibited, or unreconciled.	Do not promote to LIVE.
REVIEW	A human decision or confirmation is required.	Enter the value only in the named exception location and attach evidence.
CLEAR	Source, cutoff, validation, reconciliation, and approval all pass.	Retain the evidence and proceed.

3. What the source labels mean

Deterministic rule: these are dataset categories, not claims that a system or file exists. The real system name, real path, cutoff, hash, count, preparer, and reviewer are supplied on the Sources sheet for the specific fund and period.

EVIDENCE CATEGORY	DATASET VALUE	CAN SUPPORT	WHEN REQUIRED	WHO RECORDS THE ACTUAL SOURCE
Positions	internal_positions	Part C base rows and values	Required	Actual source system is recorded by Operations in Sources
Fund accounting	internal_fund_accounting	B.1/B.2, gains, returns, cash	Required when fields apply	Actual GL/NAV source is recorded by Fund Accounting
Create/redeem	internal_create_redeem	Calculated sales/redemptions only	Optional input; review still required	Actual order system is recorded by Capital Markets

EVIDENCE CATEGORY	DATASET VALUE	CAN SUPPORT	WHEN REQUIRED	WHO RECORDS THE ACTUAL SOURCE
Security/reference	internal_security_reference	Identifiers, country, categories, debt/reference terms	As applicable	Actual independent or licensed source is recorded in Sources
Liquidity	internal_liquidity	C.7	Only if policy requires C.7	Actual liquidity-risk evidence is recorded in Sources
Derivatives/risk	internal_derivatives	C.11 and B.9/B.10	Only for applicable holdings/regimes	Actual trade/risk evidence is recorded in Sources

4. Exact operating workflow

Use this order every time. Do not skip ahead. A command that returns a blocker means stop, correct the named workbook row or source evidence, and rerun that command.

Step 1 - Check the input format

Run:

```
Set-Location "C:\Users\damie\nportvalidation"
& ".\env\Scripts\nport.exe" schema
```

System: Prints the required and conditional `positions.csv` columns.

Human: Export independent positions to `data/intake/<period>/<fund>/positions.csv`. If available, place the independent order file beside it as `create_redeem_orders.csv`.

Stop if: Either file came from or was derived from U.S. Bank or EagleSTAR.

Step 2 - Create the fund review workbook

Run:

```
& ".\env\Scripts\nport.exe" prepare-review FDRS 2026-06 --positions ".\data\intake\2026-06\fdrs\positions.csv"
--orders ".\data\intake\2026-06\fdrs\create_redeem_orders.csv"
```

System: Creates or refreshes `data/funds/fdrs/filings/2026-06/human_review.xlsx`. Omit `--orders` when no independent order export exists.

Human: Confirm the printed fund, period, positions path, and workbook path are correct.

Pass when: The command prints `Prepared:` and the expected workbook path.

Step 3 - Register source evidence

Run: No new command. Open `human_review.xlsx` and use the `Sources` sheet.

System: Carries the positions/orders paths, SHA-256, and record counts into the workbook. If a source file changes, its status returns to `PENDING`.

Human: For every source actually used, complete `sourceSystem`, `sourcePath`, `sourceAsOf`, `acquiredAt`, `preparedBy`, `reviewedBy`, `reviewedAt`, `status`, and `comment`. The reviewer must be a different person.

Pass when: Every cited source is independent, period-aligned, complete, and `APPROVED`.

Step 4 - Resolve the field review queue

Run: No new command. In the workbook, filter `FundFields` and `HoldingFields` to `MISSING` or `NEEDS_REVIEW`.

System: Shows the exact `targetFile`, `recordKey`, `fieldName`, current value, and gap ID.

Human: Enter `proposedValue`, `sourceId`, `sourceAsOf`, `reviewer`, `reviewedAt`, and `comment`. Use `APPROVED` for a supported value. Use `NOT_APPLICABLE` only with evidence and a factual reason. Do not edit `SYSTEM_DERIVED` or `SYSTEM_CONTROL` rows.

Pass when: No applicable row remains `MISSING` or `NEEDS_REVIEW`.

Step 5 - Complete two-person approval

Run: No new command. Use the workbook's `Approvals` sheet.

Human: One person completes `PREPARER`; a different person completes `REVIEWER`. Both enter name, ISO-8601 `approvedAt`, `APPROVED` status, and `comment`.

Pass when: Both approval rows are complete and the names differ.

Step 6 - Run the blocker gate

Run:

```
& ".\env\Scripts\nport.exe" review-status FDRS 2026-06
```

System: Prints every unresolved field, source, approval, cutoff, hash, count, or reconciliation issue.

Human: Fix the exact row named after `Fix:`, save the workbook, and rerun this command.

Pass when: The command prints `READY - zero review blockers`.

Step 7 - Test without retaining output

Run:

```
& ".\env\Scripts\nport.exe" build FDRS 2026-06 --from-review --dry-run
```

System: Finalizes in temporary storage, validates canonical data, generates XML, and runs XSD validation.

Human: Read every reported error. Return to the named source or workbook row; never patch generated XML.

Pass when: The command prints DRY RUN PASSED.

Step 8 - Build, then compare

Run:

```
& ".\env\Scripts\nport.exe" build FDRS 2026-06 --from-review  
& ".\env\Scripts\nport.exe" compare-reference --internal ".\output\FDRS_2026-06.xml" --reference "<aligned-reference.xml>"
```

System: Writes a versioned clean bundle under data/builds/fdrs/2026-06/<run-id>/, writes XML under output/, and performs a read-only comparison.

Human: Confirm the internal and reference outputs use the same fund identity and report date. Document gaps; never copy comparison values back into the filing.

Pass when: The clean bundle, receipt, validated XML, and documented comparison all exist.

Run the workflow for every fund

Scope rule: the service is not limited to FDRS. Each fund has its own positions file, review workbook, source evidence, approvals, clean bundle, and XML. Never reuse one fund's workbook or approval for another fund.

Phase A - generate one review workbook per intake folder. The folder name is the fund ticker. The loop requires positions.csv and includes create_redeem_orders.csv only when that file exists.

```
$period = "2026-06"  
$nport = ".\env\Scripts\nport.exe"  
$intakeRoot = Join-Path ".\data\intake" $period  
  
foreach ($fundFolder in Get-ChildItem -LiteralPath $intakeRoot -Directory) {  
    $fund = $fundFolder.Name.ToLowerInvariant()  
    $positions = Join-Path $fundFolder.FullName "positions.csv"  
    $orders = Join-Path $fundFolder.FullName "create_redeem_orders.csv"  
    if (-not (Test-Path -LiteralPath $positions)) {  
        throw "Missing independent positions file for $fund: $positions"  
    }  
    $reviewArgs = @("prepare-review", $fund, $period, "--positions", $positions)  
    if (Test-Path -LiteralPath $orders) {  
        $reviewArgs += @("--orders", $orders)  
    }  
    & $nport @reviewArgs  
    if ($LASTEXITCODE -ne 0) { throw "prepare-review failed for $fund" }  
}
```

Phase B - pause for human review. Reviewers complete Sources, FundFields, HoldingFields, and Approvals separately for every fund. Do not run the build loop before this work is complete.

Phase C - check every prepared workbook. The loop exits with a list of blocked funds if any review is incomplete.

```
$period = "2026-06"
$nport = ".\env\Scripts\nport.exe"
$failedFunds = @()

foreach ($book in Get-ChildItem -Path ".\data\funds\*\filings\$period\human_review.xlsx" -File) {
    $fund = $book.Directory.Parent.Parent.Name.ToLowerInvariant()
    & $nport review-status $fund $period
    if ($LASTEXITCODE -ne 0) { $failedFunds += $fund }
}
if ($failedFunds.Count -gt 0) {
    throw "Blocked funds: $($failedFunds -join ', ')"
}
```

Phase D - build every review-ready fund. Run only after Phase C finishes without an error.

```
$period = "2026-06"
$nport = ".\env\Scripts\nport.exe"

foreach ($book in Get-ChildItem -Path ".\data\funds\*\filings\$period\human_review.xlsx" -File) {
    $fund = $book.Directory.Parent.Parent.Name.ToLowerInvariant()
    & $nport build $fund $period --from-review
    if ($LASTEXITCODE -ne 0) { throw "build failed for $fund" }
}
```

Complete command reference

COMMAND	STAGE	WHAT IT DOES	WRITES DATA?
nport schema	Intake design	Prints every canonical positions.csv column, type, and applicability rule.	No
nport prepare-review <fund> <period> --positions <file> [--orders <file>]	Template	Creates or refreshes the fund-period review workbook and source rows.	Yes - human_review.xlsx
nport review-status <fund> <period>	Gate	Lists every unresolved field, evidence, approval, source, and reconciliation blocker.	No
nport finalize-review <fund> <period>	Finalization	Writes a versioned clean canonical bundle only when the review has zero blockers.	Yes - data/builds/...
COMMAND	STAGE	WHAT IT DOES	WRITES DATA?
nport build <fund> <period> --from-review --dry-run	Pre-release test	Finalizes in temporary storage and validates without retaining a bundle or XML.	No retained output
nport build <fund> <period> --from-review	Release build	Finalizes the approved review, generates XML, and runs schema validation.	Yes - clean bundle and XML
nport compare-reference --internal <xml> --reference <xml>	Post-build comparison	Performs a read-only structural comparison after dates and fund identity are aligned.	No filing inputs
nport check-schema	Maintenance	Checks the local N-PORT schema files and version.	Cache only when applicable

COMMAND	STAGE	WHAT IT DOES	WRITES DATA?
<code>nport pull --ticker <ticker> --list</code>	External research	Lists recent EDGAR N-PORT filings; it is not an input adapter.	No, unless an explicit output download is requested

Disabled write paths: masters, split, mergehumanreview, enrich, merge, new-filing, build-master, split-master, build-filing-master, and split-filing-master. Do not use them for the independent service.

5. Review workbook template

SHEET	KEY	WHAT THE HUMAN EDITS	RESULT	RELEASE RULE
Summary	Fund + period	Nothing	Shows scope, stop rule, and next command	Read-only
GapGuide	gapId	Nothing	Explains all 13 gaps, evidence template, and exact destination	Read-only
FundFields	targetFile + fieldName	proposedValue, sourceId, sourceAsOf, status, reviewer, reviewedAt, comment	Approved config and filing-level values	Every required row resolved
HoldingFields	recordKey + fieldName	Same seven review columns	Approved holding exceptions	Every surfaced required row resolved

SHEET	KEY	WHAT THE HUMAN EDITS	RESULT	RELEASE RULE
Sources	sourceId	Actual system/path/cutoff/hash/count plus dual-review evidence	Generated source manifest	Every used source approved, independent, and unchanged
Approvals	role	Name, approvedAt, status, comment	Package approval	Different preparer and reviewer
Reconciliation	check	Nothing; correct upstream values/evidence	NAV equation and position-count results	Every automated check passes

The workbook is a controlled exception and approval layer. It does not make unsupported data true. It only accepts a value when the row points to an approved source and the required review evidence is complete.

6. Status and timestamp rules

VALUE	EXACT MEANING	REQUIRED EVIDENCE
MISSING	No usable value has been supplied.	None yet; remains a blocker when applicable.
NEEDS_REVIEW	A value exists but has not been approved.	Independent source plus reviewer decision.
APPROVED	The proposed/current value is supported and accepted.	sourceId, matching sourceAsOf, reviewer, reviewedAt, approved Sources row.

VALUE	EXACT MEANING	REQUIRED EVIDENCE
NOT_APPLICABLE	A conditional field does not apply to this fund/holding.	sourceId, reviewer, reviewedAt, and a factual reason in comment.
SYSTEM_DERIVED	The system calculates the value from approved period/policy inputs.	No manual override.
SYSTEM_CONTROL	The system owns the release-state value.	No manual override.

Use ISO-8601, for example 2026-08-03T16:30:00-05:00. The example is a format illustration, not an asserted review time.

7. Current blocker checklist and exact fix location

File-name rule: these are expected templates. Use the actual independent source filename; never create an empty placeholder.

ID / STATUS	GAP / AFFECTED FIELDS	REQUIRED FILE TEMPLATES
G-001 DATA BLOCKER	Independent position population All Part C holdings, including GPTZ if the fund owns it	data/intake/<period>/<fund>/positions.csv clean bundle: holdings.csv
G-002 DATA BLOCKER	Independent fund-accounting close Assets, liabilities, net assets, balance-sheet items, gains, returns, and cash	accounting_close.csv or accounting_close.pdf clean bundle: filing_data.txt
G-003 PARTLY AUTOMATED	Create/redeem flows mon1/2/3 Sales, Redemption, and Reinvestment	create_redeem_orders.csv reinvestment_support.csv (if applicable)
G-004 ENGINEERED	Fund policy and static data Fiscal year-end, filing type, derivatives regime, applicability, identity, and signer fields	fund_policy_approval.pdf fund_static_data.csv clean bundle: fund_config.txt
ID / STATUS	GAP / AFFECTED FIELDS	REQUIRED FILE TEMPLATES
G-005 ENGINEERED	Source manifest Lineage for every accepted source	human_review.xlsx clean bundle: source_manifest.csv
G-006 ENGINEERED CONTROL	Prohibited comparison inputs U.S. Bank, EagleSTAR, prepared filings, legacy masters, and derived canonical files	comparison only: data/custodian/* data/fund_accounting/* data/master/*.xlsx legacy data/funds/* files
G-007 ENGINEERED	Human-review evidence Value/disposition, source, cutoff, reviewer, time, reason, and two-person approval	human_review.xlsx field_provenance.csv review_receipt.json
G-008 DATA BLOCKER IF SWAPS	Swap economics Counterparty, LEI, notional, value, termination, and receive/pay leg terms	swap_trade_export.csv executed_swap_confirmations.pdf

ID / STATUS	GAP / AFFECTED FIELDS	REQUIRED FILE TEMPLATES
G-009 DATA BLOCKER IF APPLICABLE	B.2.f / B.3 / B.5.c / B.9 / B.10 Cash outside C/D, risk metrics, monthly categories, derivatives exposure, or VaR	cash_ledger.csv risk_metrics.csv rule_18f4_results.csv var_backtesting.csv monthly_return_categories.csv
G-010 DATA BLOCKER IF APPLICABLE	C.7 liquidity liquidityClassificationJson and liquidityCircumstancesJson by holding	liquidity_classifications.csv liquidity_circumstances.csv (if applicable)
G-011 DATA BLOCKER FOR OPTIONS	Option terms and delta Delta, exercise terms, expiry, and underlying/reference identity	option_trade_terms.csv option_delta.csv
G-012 PARTLY ENGINEERED	Reconciliation NAV equation and position count are automated; GL, derivatives, and flow tie-outs still need source reports	reconciliation.csv positions_to_gl_reconciliation.csv flow_reconciliation.csv derivatives_reconciliation.csv

ID / STATUS	GAP / AFFECTED FIELDS	REQUIRED FILE TEMPLATES
G-013 RESIDUAL CONTROL LIMIT	Origin assurance Local files cannot prove a reviewer did not manually copy and relabel a prohibited value	source_origin_attestation.pdf review_receipt.json

Exact fix location and proof

ID	EXACTLY WHERE TO FIX	OWNER	PROOF TO CLOSE
G-001	prepare-review <fund> <period> --positions <independent.csv>; review surfaced rows in HoldingFields.	Operations	Approved POSITIONS row, period-end cutoff, hash, row count, and position-count reconciliation
G-002	Add the internal close file to Sources; enter supported values in FundFields where targetFile=filing_data.txt.	Fund Accounting	Each row cites the approved source; NAV equation passes
G-003	Pass --orders to prepare-review. Review calculated sales/redemptions in FundFields. Enter reinvestment only from separate internal evidence.	Capital Markets + Accounting	Accepted-order calculation, cutoff review, and independent reconciliation
G-004	Use FundFields where targetFile=fund_config.txt. No separate fund_registry.csv is required.	Compliance / Legal	Approved value, effective date, approver, timestamp, and internal policy reference
ID	EXACTLY WHERE TO FIX	OWNER	PROOF TO CLOSE
G-005	Complete Sources. Finalize-review creates source_manifest.csv automatically.	Operations	Path exists; cutoff, hash, count, preparer, reviewer, and approval are complete
G-006	Do not add them to Sources. Known labels and repository landing paths are rejected.	Engineering + Operations	Prohibited-source check passes; legacy writers remain disabled
G-007	Complete FundFields, HoldingFields, Sources, and Approvals in the fund-period workbook.	Operations	review-status returns zero blockers; review receipt hashes workbook and outputs
G-008	Use HoldingFields for the swap record. Cite internal trade evidence or an independently retained executed confirmation.	Derivatives Operations	All required swap fields supported; valuation reconciles

ID	EXACTLY WHERE TO FIX	OWNER	PROOF TO CLOSE
G-009	Use FundFields. Enter a supported value or NOT_APPLICABLE with source, reviewer, time, and reason.	Accounting + Risk	Fund policy determines applicability; preflight enforces applicable sections
G-010	Use HoldingFields for each surfaced holding and cite internal liquidity-risk evidence.	Liquidity Risk	100% applicable holding coverage and approval evidence
G-011	Use HoldingFields for the option record and cite internal trade/risk evidence at the cutoff.	Derivatives Risk	Required option fields supported and validated
G-012	Clear automated results in Reconciliation and attach the other internal control reports in Sources.	Accounting + Operations	No automated exception; independent control reports reviewed
ID	EXACTLY WHERE TO FIX	OWNER	PROOF TO CLOSE
G-013	Use source-system attestations, hashes, dual review, and the receipt. This remains a governance control without authenticated connectors.	Operations + Compliance	Documented origin attestation; no claim that local code can prove origin

8. How to read the field trace

Actual lineage is not authorization. The second column states what the current/legacy code really used, including Bloomberg formulas, U.S. Bank custody, EagleSTAR, seeded review workbooks, constants, and no-feed fields. Those legacy writers are disabled or prohibited for the new production build. The fourth column is the only production workflow.

The trace is generated from the canonical config, filing, and holding field maps. Generation stops if field counts change or the verified lineage anchors no longer resolve.

Verification performed: 72 rows: code anchor located for each; Bloomberg claims checked against BLOOMBERG_SPECS (10 cols) + risk sheet (4 cols); EagleSTAR claims checked against 17 writer keys; Human-review claims checked against 15 review value columns; Custodian claims checked against 67 transform-assigned keys; filing_master HEADER: 55 columns, 0 unmapped; Exhaustive canonical trace: 170 fields (30 config, 56 filing, 84 holding).

9. Exhaustive field trace - fund configuration

All 30 accepted fund-configuration fields are listed. `requiredSources` is derived from approved `Sources` rows in the new workflow; it is not typed as business data.

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
cik	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=cik. Enter proposedValue and cite an approved independent Sources row.
ccc	fund_config.txt (current); EDGAR filer administrator	Injected only at execution; never copied from comparison files src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=ccc. Enter proposedValue and cite an approved independent Sources row.
regName	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regName. Enter proposedValue and cite an approved independent Sources row.
regFileNumber	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regFileNumber. Enter proposedValue and cite an approved independent Sources row.

Fund configuration (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
regCik	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regCik. Enter proposedValue and cite an approved independent Sources row.
regLei	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regLei. Enter proposedValue and cite an approved independent Sources row.
regStreet1	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regStreet1. Enter proposedValue and cite an approved independent Sources row.
regStreet2	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regStreet2. Enter proposedValue and cite an approved independent Sources row.

Fund configuration (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
regCity	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regCity. Enter proposedValue and cite an approved independent Sources row.
regState	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regState. Enter proposedValue and cite an approved independent Sources row.
regCountry	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regCountry. Enter proposedValue and cite an approved independent Sources row.
regZipOrPostalCode	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regZipOrPostalCode. Enter proposedValue and cite an approved independent Sources row.

Fund configuration (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
regPhone	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regPhone. Enter proposedValue and cite an approved independent Sources row.
seriesName	fund_config.txt (current static value)	Direct identifier mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=seriesName. Enter proposedValue and cite an approved independent Sources row.
seriesId	fund_config.txt (current static value)	Direct identifier mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=seriesId. Enter proposedValue and cite an approved independent Sources row.
seriesLei	fund_config.txt (current static value)	Direct identifier mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=seriesLei. Enter proposedValue and cite an approved independent Sources row.

Fund configuration (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
classId	fund_config.txt (current static value)	Direct identifier mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=classId. Enter proposedValue and cite an approved independent Sources row.
signerOrg	fund_config.txt (current static value)	Direct mapping; evidence retained with filing approval src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=signerOrg. Enter proposedValue and cite an approved independent Sources row.
signerName	fund_config.txt (current static value)	Direct mapping; evidence retained with filing approval src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=signerName. Enter proposedValue and cite an approved independent Sources row.
signerTitle	fund_config.txt (current static value)	Direct mapping; evidence retained with filing approval src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=signerTitle. Enter proposedValue and cite an approved independent Sources row.

Fund configuration (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
fiscalYearEndMMDD	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=fiscalYearEndMMDD. Enter proposedValue and cite an approved independent Sources row.
derivativesRegimePolicy	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=derivativesRegimePolicy. Enter proposedValue and cite an approved independent Sources row.
liquidityRequired	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=liquidityRequired. Enter proposedValue and cite an approved independent Sources row.
cashB2fRequired	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=cashB2fRequired. Enter proposedValue and cite an approved independent Sources row.

Fund configuration (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
policyEffectiveFrom	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=policyEffectiveFrom. Enter proposedValue and cite an approved independent Sources row.
policyEffectiveTo	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=policyEffectiveTo. Enter proposedValue and cite an approved independent Sources row.
policyApprovedBy	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=policyApprovedBy. Enter proposedValue and cite an approved independent Sources row.
policyApprovedAt	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=policyApprovedAt. Enter proposedValue and cite an approved independent Sources row.

Fund configuration (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
policySourceRef	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=policySourceRef. Enter proposedValue and cite an approved independent Sources row.
requiredSources	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	System-derived from APPROVED rows on Sources; the reviewer does not type it.

10. Exhaustive field trace - filing-level data

All 56 accepted filing-level fields are listed. A legacy constant is reported as a constant; it is not silently reclassified as sourced data.

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
submissionType	Tool-derived filing period/default; future approved fund registry	filing_master.py derives the period; policy.py overrides from an approved registry when present src/nport/filing_master.py:66	SYSTEM_DERIVED after the period and approved fund-policy rows pass review.
liveTestFlag	Filing Operations and authorized signer workflow	Operator-controlled status/date with release gate src/nport/cli.py:1181	SYSTEM_CONTROL; remains TEST until all release controls pass.
repPdEnd	Tool-derived filing period/default; future approved fund registry	filing_master.py derives the period; policy.py overrides from an approved registry when present src/nport/custodian.py:808	SYSTEM_DERIVED after the period and approved fund-policy rows pass review.
repPdDate	Tool-derived filing period/default; future approved fund registry	filing_master.py derives the period; policy.py overrides from an approved registry when present src/nport/custodian.py:808	SYSTEM_DERIVED after the period and approved fund-policy rows pass review.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
isFinalFiling	Filing Operations and authorized signer workflow	Operator-controlled status/date with release gate src/nport/filing_master.py:66	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=isFinalFiling. Use APPROVED or a supported NOT_APPLICABLE disposition.
dateSigned	Filing Operations and authorized signer workflow	Operator-controlled status/date with release gate src/nport/filing_master.py:118	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=dateSigned. Use APPROVED or a supported NOT_APPLICABLE disposition.
totAssets	Gmail export - U.S. Bank EagleSTAR Trial Balance; custodian fallback	eaglestar.py overrides filing_master.py custody-derived fallback src/nport/eaglestar.py:310	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=totAssets. Use APPROVED or a supported NOT_APPLICABLE disposition.
totLiabs	Gmail export - U.S. Bank EagleSTAR Trial Balance; custodian fallback	eaglestar.py overrides filing_master.py custody-derived fallback src/nport/eaglestar.py:312	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=totLiabs. Use APPROVED or a supported NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
netAssets	Gmail export - U.S. Bank EagleSTAR Trial Balance; custodian fallback	eaglestar.py overrides filing_master.py custody-derived fallback src/nport/eaglestar.py:314	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=netAssets. Use APPROVED or a supported NOT_APPLICABLE disposition.
assetsAttrMiscSec	Gmail export - U.S. Bank EagleSTAR Trial Balance; custodian fallback	eaglestar.py overrides filing_master.py custody-derived fallback src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=assetsAttrMiscSec. Use APPROVED or a supported NOT_APPLICABLE disposition.
assetsInvested	Gmail export - U.S. Bank EagleSTAR Trial Balance; custodian fallback	eaglestar.py overrides filing_master.py custody-derived fallback src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=assetsInvested. Use APPROVED or a supported NOT_APPLICABLE disposition.
amtPayOneYrBanksBorr	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayOneYrBanksBorr. Use APPROVED or a supported NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
amtPayOneYrCtrldComp	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayOneYrCtrldComp. Use APPROVED or a supported NOT_APPLICABLE disposition.
amtPayOneYrOthAffil	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayOneYrOthAffil. Use APPROVED or a supported NOT_APPLICABLE disposition.
amtPayOneYrOther	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:307	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayOneYrOther. Use APPROVED or a supported NOT_APPLICABLE disposition.
amtPayAftOneYrBanksBorr	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayAftOneYrBanksBorr. Use APPROVED or a supported NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
amtPayAftOneYrCtrlComp	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayAftOneYrCtrlComp. Use APPROVED or a supported NOT_APPLICABLE disposition.
amtPayAftOneYrOthAffil	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayAftOneYrOthAffil. Use APPROVED or a supported NOT_APPLICABLE disposition.
amtPayAftOneYrOthher	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayAftOneYrOthher. Use APPROVED or a supported NOT_APPLICABLE disposition.
delayDeliv	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=delayDeliv. Use APPROVED or a supported NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
standByCommit	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=standByCommit. Use APPROVED or a supported NOT_APPLICABLE disposition.
liquidPref	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=liquidPref. Use APPROVED or a supported NOT_APPLICABLE disposition.
isNonCashCollateral	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=isNonCashCollateral. Use APPROVED or a supported NOT_APPLICABLE disposition.
rtn1	Bloomberg formula in filing_master.xlsx	BDP custom total-return formula for each reporting month src/nport/filing_master.py:48	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=rtn1. Use APPROVED or a supported NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
rtn2	Bloomberg formula in filing_master.xlsx	BDP custom total-return formula for each reporting month src/nport/filing_master.py:48	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=rtn2. Use APPROVED or a supported NOT_APPLICABLE disposition.
rtn3	Bloomberg formula in filing_master.xlsx	BDP custom total-return formula for each reporting month src/nport/filing_master.py:48	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=rtn3. Use APPROVED or a supported NOT_APPLICABLE disposition.
netRealizedGainMon1	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=netRealizedGainMon1. Use APPROVED or a supported NOT_APPLICABLE disposition.
netUnrealizedApprMon1	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=netUnrealizedApprMon1. Use APPROVED or a supported NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
netRealizedGainMon2	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=netRealizedGainMon2. Use APPROVED or a supported NOT_APPLICABLE disposition.
netUnrealizedApprMon2	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=netUnrealizedApprMon2. Use APPROVED or a supported NOT_APPLICABLE disposition.
netRealizedGainMon3	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=netRealizedGainMon3. Use APPROVED or a supported NOT_APPLICABLE disposition.
netUnrealizedApprMon3	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=netUnrealizedApprMon3. Use APPROVED or a supported NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
mon1Sales	Gmail export - EagleSTAR Trial Balance	eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon1Sales. Use APPROVED or a supported NOT_APPLICABLE disposition.
mon1Redemption	Gmail export - EagleSTAR Trial Balance	eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon1Redemption. Use APPROVED or a supported NOT_APPLICABLE disposition.
mon1Reinvestment	No current feed; filing_master.py supplies N/A	Create/redeem orders do not contain reinvested distributions src/nport/models.py:84	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon1Reinvestment. Use APPROVED or a supported NOT_APPLICABLE disposition.
mon2Sales	Gmail export - EagleSTAR Trial Balance	eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon2Sales. Use APPROVED or a supported NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
mon2Redemption	Gmail export - EagleSTAR Trial Balance	eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon2Redemption. Use APPROVED or a supported NOT_APPLICABLE disposition.
mon2Reinvestment	No current feed; filing_master.py supplies N/A	Create/redeem orders do not contain reinvested distributions src/nport/models.py:87	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon2Reinvestment. Use APPROVED or a supported NOT_APPLICABLE disposition.
mon3Sales	Gmail export - EagleSTAR Trial Balance	eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon3Sales. Use APPROVED or a supported NOT_APPLICABLE disposition.
mon3Redemption	Gmail export - EagleSTAR Trial Balance	eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon3Redemption. Use APPROVED or a supported NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
mon3Reinvestment	No current feed; filing_master.py supplies N/A	Create/redeem orders do not contain reinvested distributions src/nport/models.py:90	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon3Reinvestment. Use APPROVED or a supported NOT_APPLICABLE disposition.
nameDesignatedIndex	Human-review workbook designated_index sheet (legacy 497K seed)	humanreview.py seed values merge through filing_master.py src/nport/master_sheet.py:748	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=nameDesignatedIndex. Use APPROVED or a supported NOT_APPLICABLE disposition.
indexIdentifier	Human-review workbook designated_index sheet (legacy 497K seed)	humanreview.py seed values merge through filing_master.py src/nport/master_sheet.py:748	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=indexIdentifier. Use APPROVED or a supported NOT_APPLICABLE disposition.
curMetricsJson	Bloomberg formulas plus U.S. Bank custodian market value	filing_master.py aggregates duration/rating fields after workbook calculation src/nport/filing_master.py:40	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=curMetricsJson. Use APPROVED or a supported NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
creditSprdRiskIgJson	Bloomberg formulas plus U.S. Bank custodian market value	filing_master.py aggregates duration/rating fields after workbook calculation src/nport/filing_master.py:40	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=creditSprdRiskIgJson. Use APPROVED or a supported NOT_APPLICABLE disposition.
creditSprdRiskNonigJson	Bloomberg formulas plus U.S. Bank custodian market value	filing_master.py aggregates duration/rating fields after workbook calculation src/nport/filing_master.py:40	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=creditSprdRiskNonigJson. Use APPROVED or a supported NOT_APPLICABLE disposition.
cashNotReportedInCoRD	No current feed	Typed field exists; no Gmail, custodian, create/redeem, or Bloomberg writer src/nport/models.py:100	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=cashNotReportedInCoRD. Use APPROVED or a supported NOT_APPLICABLE disposition.
monthlyReturnCategoriesJson	No current feed	Typed field exists; no Gmail, custodian, create/redeem, or Bloomberg writer src/nport/models.py:101	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=monthlyReturnCategoriesJson. Use APPROVED or a supported NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
derivativesRegime	No current populated source; future approved fund registry	policy.py derives it only when the registry exists src/nport/filing_master.py:321	SYSTEM_DERIVED after the period and approved fund-policy rows pass review.
derivExposurePct	No current feed	B.9/B.10 typed fields and preflight gates exist, but no writer populates them src/nport/models.py:103	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=derivExposurePct. Use APPROVED or a supported NOT_APPLICABLE disposition.
derivCurrencyExposurePct	No current feed	B.9/B.10 typed fields and preflight gates exist, but no writer populates them src/nport/models.py:104	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=derivCurrencyExposurePct. Use APPROVED or a supported NOT_APPLICABLE disposition.
derivInterestRateExposurePct	No current feed	B.9/B.10 typed fields and preflight gates exist, but no writer populates them src/nport/models.py:105	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=derivInterestRateExposurePct. Use APPROVED or a supported NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
derivDaysInExcess	No current feed	B.9/B.10 typed fields and preflight gates exist, but no writer populates them src/nport/models.py:106	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=derivDaysInExcess. Use APPROVED or a supported NOT_APPLICABLE disposition.
medianDailyVarPct	No current feed	B.9/B.10 typed fields and preflight gates exist, but no writer populates them src/nport/models.py:107	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=medianDailyVarPct. Use APPROVED or a supported NOT_APPLICABLE disposition.
medianVarRatioPct	No current feed	B.9/B.10 typed fields and preflight gates exist, but no writer populates them src/nport/models.py:108	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=medianVarRatioPct. Use APPROVED or a supported NOT_APPLICABLE disposition.
backtestingExceptions	No current feed	B.9/B.10 typed fields and preflight gates exist, but no writer populates them src/nport/models.py:109	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=backtestingExceptions. Use APPROVED or a supported NOT_APPLICABLE disposition.

11. Exhaustive field trace - holdings

All 84 accepted holdings fields are listed and grouped by filing condition. Present base values remain tied to the approved POSITIONS source; missing required and review-sensitive values are surfaced in HoldingFields.

Base

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
name	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. <code>src/nport/custodian.py:107</code>	Base value is positions.csv column name. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=name. Requirement: always.
lei	Bloomberg workbook formula for conventional securities; explicit constants on some derivative/UST paths	BDP enrichment owns conventional-security values; custodian code sets N/A/US or the U.S. Treasury LEI on identified special paths. <code>src/nport/master_sheet.py:128</code>	Base value is positions.csv column lei. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=lei. Requirement: always.
title	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. <code>src/nport/custodian.py:107</code>	Base value is positions.csv column title. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=title. Requirement: always.
cusip	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. <code>src/nport/custodian.py:107</code>	Base value is positions.csv column cusip. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=cusip. Requirement: always.

Base (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
isin	Bloomberg workbook formula for conventional securities; explicit constants on some derivative/UST paths	BDP enrichment owns conventional-security values; custodian code sets N/A/US or the U.S. Treasury LEI on identified special paths. <code>src/nport/master_sheet.py:128</code>	Base value is positions.csv column isin. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=isin. Requirement: never.
ticker	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. <code>src/nport/custodian.py:107</code>	Base value is positions.csv column ticker. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=ticker. Requirement: never.
balance	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. <code>src/nport/custodian.py:679</code>	Base value is positions.csv column balance. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=balance. Requirement: always.
units	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. <code>src/nport/custodian.py:680</code>	Base value is positions.csv column units. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=units. Requirement: always.

Base (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
curCd	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:662	Base value is positions.csv column curCd. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=curCd. Requirement: always.
valUSD	U.S. Bank custodian CSV for non-swaps; EagleSTAR PVal for swaps	MarketValue is used for non-swaps; swap value is replaced with matched unrealized PVal. src/nport/eaglestar.py:206	Base value is positions.csv column valUSD. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=valUSD. Requirement: always.
pctVal	Derived from filed valUSD and filed netAssets	The legacy transform recalculates the percentage after accounting overrides. src/nport/custodian.py:125	Base value is positions.csv column pctVal. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=pctVal. Requirement: always.
payoffProfile	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:662	Base value is positions.csv column payoffProfile. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=payoffProfile. Requirement: always.

Base (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
assetCat	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:108	Base value is positions.csv column assetCat. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=assetCat. Requirement: always.
issuerCat	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:108	Base value is positions.csv column issuerCat. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=issuerCat. Requirement: always.
invCountry	Bloomberg workbook formula for conventional securities; explicit constants on some derivative/UST paths	BDP enrichment owns conventional-security values; custodian code sets N/A/US or the U.S. Treasury LEI on identified special paths. src/nport/master_sheet.py:157	Base value is positions.csv column invCountry. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=invCountry. Requirement: always.
isRestrictedSec	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:662	Base value is positions.csv column isRestrictedSec. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=isRestrictedSec. Requirement: always.

Base (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
fairValLevel	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:662	Base value is positions.csv column fairValLevel. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=fairValLevel. Requirement: always.
isCashCollateral	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:662	Base value is positions.csv column isCashCollateral. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=isCashCollateral. Requirement: always.
isNonCashCollateral	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:662	Base value is positions.csv column isNonCashCollateral. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=isNonCashCollateral. Requirement: always.
isLoanByFund	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:662	Base value is positions.csv column isLoanByFund. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=isLoanByFund. Requirement: always.

Conditional

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
issuerConditionalDesc	Tool constant only on the legacy swap path; otherwise no verified writer	custodian.py sets N/A for swaps; other issuerCat=OTHER cases are not populated automatically. src/nport/custodian.py:662	Base value is positions.csv column issuerConditionalDesc. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=issuerConditionalDesc. Requirement: conditional - issuerCat==OTHER.
assetConditionalDesc	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:137	Base value is positions.csv column assetConditionalDesc. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=assetConditionalDesc. Requirement: conditional - assetCat==OTHER.
otherDesc	Tool-generated identifier only for legacy option/swap paths	custodian.py writes USER DEFINED plus an internally constructed option/swap identifier; other paths remain blank. src/nport/custodian.py:662	Base value is positions.csv column otherDesc. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=otherDesc. Requirement: never.
otherValue	Tool-generated identifier only for legacy option/swap paths	custodian.py writes USER DEFINED plus an internally constructed option/swap identifier; other paths remain blank. src/nport/custodian.py:662	Base value is positions.csv column otherValue. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=otherValue. Requirement: never.

Conditional (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
exchangeRt	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:140	Base value is positions.csv column exchangeRt. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=exchangeRt. Requirement: conditional - non-USD currency.

Debt

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
maturityDt	Bloomberg workbook formula; U.S. Treasury name parser exists in the direct custodian transform	Corporate/debt master enrichment uses BDP; the alternate direct Treasury path parses coupon and maturity from SecurityName. src/nport/master_sheet.py:101	Base value is positions.csv column maturityDt. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=maturityDt. Requirement: conditional - debt security.
couponKind	Bloomberg workbook formula; U.S. Treasury name parser exists in the direct custodian transform	Corporate/debt master enrichment uses BDP; the alternate direct Treasury path parses coupon and maturity from SecurityName. src/nport/master_sheet.py:101	Base value is positions.csv column couponKind. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=couponKind. Requirement: conditional - maturityDt set.
annualizedRt	Bloomberg workbook formula; U.S. Treasury name parser exists in the direct custodian transform	Corporate/debt master enrichment uses BDP; the alternate direct Treasury path parses coupon and maturity from SecurityName. src/nport/master_sheet.py:101	Base value is positions.csv column annualizedRt. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=annualizedRt. Requirement: conditional - maturityDt set.
isDefault	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:137	Base value is positions.csv column isDefault. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=isDefault. Requirement: conditional - maturityDt set.

Debt (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
areIntrstPmntsInArns	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:137	Base value is positions.csv column areIntrstPmntsInArns. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=areIntrstPmntsInArns. Requirement: conditional - maturityDt set.
isPaidKind	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:137	Base value is positions.csv column isPaidKind. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=isPaidKind. Requirement: conditional - maturityDt set.

Deriv Common

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
derivCat	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:114	Base value is positions.csv column derivCat. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=derivCat. Requirement: conditional - derivative holding.
counterpartyName	Seeded human-review overlay for swaps; OCC tool constant for options	Swap values come from the legacy counterparty sheet; option values use the OCC constants in custodian.py. src/nport/master_sheet.py:776	Base value is positions.csv column counterpartyName. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=counterpartyName. Requirement: conditional - derivCat set.
counterpartyLei	Seeded human-review overlay for swaps; OCC tool constant for options	Swap values come from the legacy counterparty sheet; option values use the OCC constants in custodian.py. src/nport/master_sheet.py:776	Base value is positions.csv column counterpartyLei. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=counterpartyLei. Requirement: conditional - derivCat set.
unrealizedAppr	Gmail export - U.S. Bank EagleSTAR PVal attachment	Matched by Primary Asset ID and written as the derivative unrealized amount. src/nport/eaglestar.py:206	Base value is positions.csv column unrealizedAppr. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=unrealizedAppr. Requirement: conditional - derivCat set.

Option

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
putOrCall	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:115	Base value is positions.csv column putOrCall. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=putOrCall. Requirement: conditional - derivCat in OPT/SWO/WAR.
writtenOrPur	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:115	Base value is positions.csv column writtenOrPur. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=writtenOrPur. Requirement: conditional - derivCat in OPT/SWO/WAR.
shareNo	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:662	Base value is positions.csv column shareNo. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=shareNo. Requirement: never.
exercisePrice	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:115	Base value is positions.csv column exercisePrice. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=exercisePrice. Requirement: conditional - derivCat in OPT/SWO/WAR.

Option (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
exercisePriceCurCd	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:115	Base value is positions.csv column exercisePriceCurCd. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=exercisePriceCurCd. Requirement: never.
expDt	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:116	Base value is positions.csv column expDt. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=expDt. Requirement: conditional - derivCat in OPT/SWO/WAR.
delta	Manual value preserved in security_master.xlsx; no automated feed	The legacy master preserves the workbook cell; it does not calculate or source delta. src/nport/models.py:160	Base value is positions.csv column delta. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=delta. Requirement: conditional - derivCat in OPT/SWO/WAR.

Ref Instrument

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
refInstType	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:117	Base value is positions.csv column refInstType. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=refInstType. Requirement: never.
refIndexName	Seeded legacy human-review workbook overlay	master_sheet.py copies the reviewed/seeded workbook value when present; the old workbook lacks mandatory reviewer/time/evidence fields. src/nport/master_sheet.py:789	Base value is positions.csv column refIndexName. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=refIndexName. Requirement: conditional - refInstType==indexBasket.
refIndexIdentifier	Seeded legacy human-review workbook overlay	master_sheet.py copies the reviewed/seeded workbook value when present; the old workbook lacks mandatory reviewer/time/evidence fields. src/nport/master_sheet.py:789	Base value is positions.csv column refIndexIdentifier. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=refIndexIdentifier. Requirement: conditional - refInstType==indexBasket.
refIssuerName	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:129	Base value is positions.csv column refIssuerName. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=refIssuerName. Requirement: conditional - refInstType==otherRefInst.

Ref Instrument (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
refIssueTitle	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:129	Base value is positions.csv column refIssueTitle. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=refIssueTitle. Requirement: conditional - refInstType==otherRefInst.
refCusip	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:130	Base value is positions.csv column refCusip. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=refCusip. Requirement: never.
refIsin	Bloomberg workbook formula on the reference security	BDP enrichment uses the reference CUSIP/security key. src/nport/master_sheet.py:129	Base value is positions.csv column refIsin. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=refIsin. Requirement: never.
refTicker	Bloomberg workbook formula on the reference security	BDP enrichment uses the reference CUSIP/security key. src/nport/master_sheet.py:129	Base value is positions.csv column refTicker. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=refTicker. Requirement: never.

Swap

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
swapFlag	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:124	Base value is positions.csv column swapFlag. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=swapFlag. Requirement: conditional - derivCat==SWP.
terminationDt	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:124	Base value is positions.csv column terminationDt. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=terminationDt. Requirement: conditional - derivCat==SWP.
upfrontPmnt	Builder fallback, not a sourced legacy field	builder.py emits 0 when the accepted holding column is blank. src/nport/builder.py:497	Base value is positions.csv column upfrontPmnt. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=upfrontPmnt. Requirement: never.
pmntCurCd	Builder fallback, not a sourced legacy field	builder.py uses the holding currency when the accepted holding column is blank. src/nport/builder.py:498	Base value is positions.csv column pmntCurCd. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=pmntCurCd. Requirement: never.

Swap (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
upfrontRcpt	Builder fallback, not a sourced legacy field	builder.py emits 0 when the accepted holding column is blank. src/nport/builder.py:499	Base value is positions.csv column upfrontRcpt. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=upfrontRcpt. Requirement: never.
rcptCurCd	Builder fallback, not a sourced legacy field	builder.py uses the holding currency when the accepted holding column is blank. src/nport/builder.py:500	Base value is positions.csv column rcptCurCd. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=rcptCurCd. Requirement: never.
notionalAmt	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:124	Base value is positions.csv column notionalAmt. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=notionalAmt. Requirement: conditional - derivCat==SWP.
swapCurCd	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:124	Base value is positions.csv column swapCurCd. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=swapCurCd. Requirement: never.

Swap (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
recFixedOrFloating	Seeded legacy human-review workbook overlay	master_sheet.py copies the reviewed/seeded workbook value when present; the old workbook lacks mandatory reviewer/time/evidence fields. src/nport/master_sheet.py:748	Base value is positions.csv column recFixedOrFloating. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=recFixedOrFloating. Requirement: conditional - derivCat==SWP.
recFixedRt	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:181	Base value is positions.csv column recFixedRt. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=recFixedRt. Requirement: conditional - recFixedOrFloating==Fixed.
recFloatingRtIndex	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:182	Base value is positions.csv column recFloatingRtIndex. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=recFloatingRtIndex. Requirement: conditional - recFixedOrFloating==Floating.
recFloatingRtSpread	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:183	Base value is positions.csv column recFloatingRtSpread. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=recFloatingRtSpread. Requirement: conditional - recFixedOrFloating==Floating.

Swap (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
recPmntAmt	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:184</code>	Base value is positions.csv column recPmntAmt. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=recPmntAmt. Requirement: never.
recCurCd	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:185</code>	Base value is positions.csv column recCurCd. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=recCurCd. Requirement: never.
recRateTenor	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:186</code>	Base value is positions.csv column recRateTenor. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=recRateTenor. Requirement: never.
recRateUnit	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:187</code>	Base value is positions.csv column recRateUnit. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=recRateUnit. Requirement: never.

Swap (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
recResetDt	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:188</code>	Base value is positions.csv column recResetDt. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=recResetDt. Requirement: never.
recResetUnit	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:189</code>	Base value is positions.csv column recResetUnit. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=recResetUnit. Requirement: never.
recDesc	Seeded legacy human-review workbook overlay	master_sheet.py copies the reviewed/seeded workbook value when present; the old workbook lacks mandatory reviewer/time/evidence fields. <code>src/nport/master_sheet.py:748</code>	Base value is positions.csv column recDesc. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=recDesc. Requirement: never.
pmntDesc	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:192</code>	Base value is positions.csv column pmntDesc. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=pmntDesc. Requirement: never.

Swap (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
pmntFixedOrFloating	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:127	Base value is positions.csv column pmntFixedOrFloating. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=pmntFixedOrFloating. Requirement: conditional - derivCat==SWP.
pmntFixedRt	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:194	Base value is positions.csv column pmntFixedRt. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=pmntFixedRt. Requirement: conditional - pmntFixedOrFloating==Fixed.
pmntFloatingRtIndex	Seeded legacy human-review workbook overlay	master_sheet.py copies the reviewed/seeded workbook value when present; the old workbook lacks mandatory reviewer/time/evidence fields. src/nport/master_sheet.py:748	Base value is positions.csv column pmntFloatingRtIndex. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=pmntFloatingRtIndex. Requirement: conditional - pmntFixedOrFloating==Floating.
pmntFloatingRtSpread	Seeded legacy human-review workbook overlay	master_sheet.py copies the reviewed/seeded workbook value when present; the old workbook lacks mandatory reviewer/time/evidence fields. src/nport/master_sheet.py:748	Base value is positions.csv column pmntFloatingRtSpread. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=pmntFloatingRtSpread. Requirement: conditional - pmntFixedOrFloating==Floating.

Swap (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
pmntPmntAmt	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:197	Base value is positions.csv column pmntPmntAmt. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=pmntPmntAmt. Requirement: never.
pmntCurCdLeg	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:128	Base value is positions.csv column pmntCurCdLeg. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=pmntCurCdLeg. Requirement: never.
pmntRateTenor	Seeded legacy human-review workbook overlay	master_sheet.py copies the reviewed/seeded workbook value when present; the old workbook lacks mandatory reviewer/time/evidence fields. src/nport/master_sheet.py:748	Base value is positions.csv column pmntRateTenor. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=pmntRateTenor. Requirement: never.
pmntRateUnit	Seeded legacy human-review workbook overlay	master_sheet.py copies the reviewed/seeded workbook value when present; the old workbook lacks mandatory reviewer/time/evidence fields. src/nport/master_sheet.py:748	Base value is positions.csv column pmntRateUnit. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=pmntRateUnit. Requirement: never.

Swap (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
pmntResetDt	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:201</code>	Base value is positions.csv column pmntResetDt. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=pmntResetDt. Requirement: never.
pmntResetUnit	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:202</code>	Base value is positions.csv column pmntResetUnit. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=pmntResetUnit. Requirement: never.

Forward

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
payoffProfDeriv	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:204</code>	Base value is positions.csv column payoffProfDeriv. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=payoffProfDeriv. Requirement: conditional - derivCat in FWD/FUT.

Other Deriv

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
otherDerivDesc	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:206</code>	Base value is positions.csv column otherDerivDesc. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=otherDerivDesc. Requirement: conditional - derivCat==OTH.

Liquidity

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
liquidityClassificationJson	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:209</code>	Base value is positions.csv column liquidityClassificationJson. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=liquidityClassificationJson. Requirement: conditional - fund policy requires C.7.
liquidityCircumstancesJson	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:210</code>	Base value is positions.csv column liquidityCircumstancesJson. If missing or review-sensitive, use HoldingFields: recordKey=, fieldName=liquidityCircumstancesJson. Requirement: never.

12. Release decision

The code may build only after `review-status` returns zero blockers. That requires applicable fields to be resolved from approved independent sources, source cutoffs to match the report period, source hashes and counts to match, two-person approval to be complete, automated reconciliation to pass, canonical validation to pass, and XSD validation to pass. The local workflow cannot prove that a person did not copy and relabel a prohibited value; origin attestation remains a human governance control.

Generated from the repository field contracts and source controls on 2026-08-03.