

CORGI ETF TRUST · N-PORT IN-HOUSE SERVICE

N-PORT In-House Runbook

A field-by-field operating guide showing what supplies each value, exactly where it is entered, how the input workflow runs, and what blocks release.

As of August 4, 2026 · Source-independent workflow

Controlling rule: no file, value, mapping, or pre-fill delivered by U.S. Bank may populate the in-house filing. Those artifacts are read-only comparison evidence.

1. Purpose and non-negotiable boundary

This runbook operates an N-PORT service built from independent sources. U.S. Bank custody exports, EagleSTAR attachments, prepared filings, email attachments, and prior master workbooks are benchmark outputs only. They may never be copied, merged, seeded, or used to clear a production exception.

Stop rule: if the only available answer comes from U.S. Bank, record the field as MISSING and keep the filing NOT READY.

2. Status language

STATUS	USE IT WHEN	OPERATOR ACTION
MISSING	The field or evidence does not exist, but the workbook shows where to enter it.	Obtain it from the named independent owner/source and complete that row.
NOT READY	One or more open inputs or validation errors remain.	Fix the exact workbook row or upstream file printed by build.
PROVIDED	A supported current or proposed value is ready for build.	Keep its sourceId traceable.
CLEAR	Source, cutoff, validation, and reconciliation all pass.	Retain the inputs and proceed.

3. What the source labels mean

Deterministic rule: these are dataset categories, not claims that a system or file exists. The real system name, real path, and filing cutoff are recorded on Sources; the program calculates hashes and counts.

EVIDENCE CATEGORY	DATASET VALUE	CAN SUPPORT	WHEN REQUIRED	WHO RECORDS THE ACTUAL SOURCE
Positions	internal_positions	Part C base rows and values	Required	Actual source system is recorded by Operations in Sources
Fund accounting	internal_fund_accounting	B.1/B.2, gains, returns, cash	Required when fields apply	Actual GL/NAV source is recorded by Fund Accounting
Create/redeem	internal_create_redeem	Calculated sales/redemptions only	Optional input; unsupported flow categories remain MISSING	Actual order system is recorded by Capital Markets

EVIDENCE CATEGORY	DATASET VALUE	CAN SUPPORT	WHEN REQUIRED	WHO RECORDS THE ACTUAL SOURCE
Bloomberg	internal_bloomberg_reference	Returns and supported security/reference fields	When generated formulas are used	Generated source row; open, calculate, and save on Bloomberg
Security/reference	internal_security_reference	Identifiers, country, categories, debt/reference terms not supplied by Bloomberg	As applicable	Actual independent or licensed source is recorded in Sources
Liquidity	internal_liquidity	C.7	Only if policy requires C.7	Actual liquidity-risk evidence is recorded in Sources

EVIDENCE CATEGORY	DATASET VALUE	CAN SUPPORT	WHEN REQUIRED	WHO RECORDS THE ACTUAL SOURCE
Derivatives/risk	internal_derivatives	C.11 and B.9/B.10	Only for applicable holdings/regimes	Actual trade/risk evidence is recorded in Sources
Reconciliation controls	internal_reconciliation_control	Independent GL, flow, and derivative totals	Every generated ReconciliationInputs row	Accounting records the real control report on Sources

4. Exact operating workflow

Use this order every time. Do not skip ahead. If build reports an open input or validation error, correct the named workbook row or upstream file and rerun the same command.

Step 1 - Check the input format

Run:

```
Set-Location "C:\Users\damie\nportvalidation"
& ".\env\Scripts\nport.exe" schema
```

System: Prints the required and conditional positions.csv columns.

Human: Export independent positions to data/intake/<period>/<fund>/positions.csv. If available, place the independent order file beside it as create_redeem_orders.csv.

Stop if: Either file came from or was derived from U.S. Bank or EagleSTAR.

Step 2 - Run the preparation automation

Run:

```
& ".\env\Scripts\nport.exe" prepare FDRS 2026-06 --positions ".\data\intake\2026-06\fdrs\positions.csv" --orders ".\data\intake\2026-06\fdrs\create_redeem_orders.csv"
```

System: Creates data/funds/fdrs/filings/2026-06/filing_inputs.xlsx, calculates controls for the supplied files, and inserts Bloomberg formulas. Omit --orders when unavailable.

Pass when: The command prints the expected workbook path.

Step 3 - Open and save on Bloomberg

Run: Open `filing_inputs.xlsx` in Excel on a logged-in Bloomberg terminal.

System: The Bloomberg Excel Add-In calculates the visible formulas on the Bloomberg sheet.

Human: Wait until formulas show values or explicit Bloomberg errors, then save and close the workbook.

Pass when: The workbook is saved with calculated values; unresolved Bloomberg errors remain visible and will block.

Step 4 - Complete the remaining inputs

Run: Reopen `filing_inputs.xlsx`.

Human: Complete each real non-Bloomberg source on Sources. Filter `FundFields` and `HoldingFields` to MISSING; use PROVIDED with a `sourceId`, or NOT_APPLICABLE with `sourceId` and a factual comment. Then filter `ReconciliationInputs` to MISSING. For every generated check, enter the independent `controlValue`, policy-approved tolerance, `sourceId`, status, and comment. The reconciliation source must be different from the source that supplied the filed-side value. Do not type the filed-side actual; build calculates it. Do not edit `SYSTEM_DERIVED` or `SYSTEM_CONTROL`. Leave file hash/count blank; build calculates them.

Pass when: No applicable `FundFields`, `HoldingFields`, or `ReconciliationInputs` row remains MISSING.

Step 5 - Run the final automation

Run:

```
& ".\venv\Scripts\nport.exe" build FDRS 2026-06 --from-inputs
```

System: Checks every field and source, reconciles, writes a clean versioned bundle, generates XML, and runs XSD validation.

Human: If NOT READY, correct the exact workbook row or upstream file printed by the command and rerun the same command.

Pass when: The clean bundle and validated XML are written.

Step 6 - Optional aligned comparison

Run:

```
& ".\venv\Scripts\nport.exe" compare-reference --internal ".\output\FDRS_2026-06.xml" --reference "<aligned-reference.xml>"
```

System: Writes a versioned clean bundle under `data/builds/fdrs/2026-06/<run-id>/`, writes XML under `output/`, and performs a read-only comparison.

Human: Confirm the internal and reference outputs use the same fund identity and report date. Document gaps; never copy comparison values back into the filing.

Pass when: The clean bundle, receipt, validated XML, and documented comparison all exist.

Run the workflow for every fund

Scope rule: the service is not limited to FDRS. Each fund has its own positions file, input workbook, source evidence, clean bundle, and XML.

Phase A - generate one input workbook per intake folder. The folder name is the fund ticker.

```
$period = "2026-06"
$nport = ".\env\Scripts\nport.exe"
$intakeRoot = Join-Path ".\data\intake" $period

foreach ($fundFolder in Get-ChildItem -LiteralPath $intakeRoot -Directory) {
    $fund = $fundFolder.Name.ToLowerInvariant()
    $positions = Join-Path $fundFolder.FullName "positions.csv"
    $orders = Join-Path $fundFolder.FullName "create_redeem_orders.csv"
    if (-not (Test-Path -LiteralPath $positions)) {
        throw "Missing independent positions file for $fund: $positions"
    }
    $prepareArgs = @("prepare", $fund, $period, "--positions", $positions)
    if (Test-Path -LiteralPath $orders) {
        $prepareArgs += @("--orders", $orders)
    }
    & $nport @prepareArgs
    if ($LASTEXITCODE -ne 0) { throw "prepare failed for $fund" }
}
```

Phase B - Bloomberg and remaining inputs. Open, calculate, and save each workbook on Bloomberg; then fill each fund's remaining field rows and ReconciliationInputs control rows.

Phase C - build. The loop stops at the first fund that is not ready.

```
$period = "2026-06"
$nport = ".\env\Scripts\nport.exe"

foreach ($book in Get-ChildItem -Path ".\data\funds\*\filings\$period\filing_inputs.xlsx" -File) {
    $fund = $book.Directory.Parent.Parent.Name.ToLowerInvariant()
    & $nport build $fund $period --from-inputs
    if ($LASTEXITCODE -ne 0) { throw "build failed for $fund" }
}
```

Complete command reference

COMMAND	STAGE	WHAT IT DOES	WRITES DATA?
nport schema	Intake design	Prints every canonical positions.csv column, type, and applicability rule.	No
nport prepare <fund> <period> --positions <file> [--orders <file>]	Prepare	Creates filing_inputs.xlsx, source rows, gap rows, supplied-file controls, and Bloomberg formulas.	Yes - filing_inputs.xlsx
nport build <fund> <period> --from-inputs	Validate and build	Prints exact open inputs/errors or writes the clean bundle and schema-valid XML.	Only when all inputs and validations clear
nport compare-reference --internal <xml> --reference <xml>	Post-build comparison	Performs a read-only structural comparison after dates and fund identity are aligned.	No filing inputs

COMMAND	STAGE	WHAT IT DOES	WRITES DATA?
nport check-schema	Maintenance	Checks the local N-PORT schema files and version.	Cache only when applicable
nport pull --ticker <ticker> --list	External research	Lists recent EDGAR N-PORT filings; it is not an input adapter.	No, unless an explicit output download is requested

Disabled write paths: masters, split, mergehumanreview, enrich, merge, new-filing, build-master, split-master, build-filing-master, and split-filing-master. Do not use them for the independent service.

5. Filing input workbook

SHEET	KEY	WHAT THE HUMAN EDITS	RESULT	RELEASE RULE
Summary	Fund + period	Nothing	Shows scope, stop rule, and next command	Read-only
Bloomberg	targetFile + recordKey + fieldName	Nothing; formulas calculate in Excel	Supported returns and security/reference values	Blank/error results remain MISSING
GapGuide	gapId	Nothing	Explains every tracked item, evidence template, and exact destination	Read-only
FundFields	targetFile + fieldName	proposedValue, sourceId, status, comment	Config and filing-level input values	Every applicable row resolved

SHEET	KEY	WHAT THE HUMAN EDITS	RESULT	RELEASE RULE
HoldingFields	recordKey + fieldName	proposedValue, sourceId, status, comment	Holding exceptions	Every surfaced applicable row resolved
Sources	sourceId	Actual system, path, sourceAsOf, and comment	Generated source manifest	Every used source is independent, current, and unchanged
ReconciliationInputs	checkId	controlValue, tolerance, sourceId, status, comment	Independent control side of position-to-GL, flows, and derivative checks	Every generated row resolved; source differs from filed side
Reconciliation	check	Nothing; correct upstream filed input or ReconciliationInputs	Build-calculated actual, control, difference, tolerance, and result	Every automated check passes

The workbook is an input and exception layer. It does not make unsupported data true. A supplied value is usable only when its row points to a complete independent source record.

Fund-configuration safeguard: for targetFile=fund_config.txt, enter proposedValue from the cited independent source. The existing currentValue is reference-only and cannot be accepted by changing status alone.

6. Status and source rules

VALUE	EXACT MEANING	REQUIRED EVIDENCE
MISSING	No usable value has been supplied.	The row remains an open input when applicable.
PROVIDED	A supported current or proposed value is ready for the build.	Resolved value, sourceId, and a complete Sources row.
NOT_APPLICABLE	A conditional field does not apply to this fund/holding.	sourceId plus a factual reason in comment.

VALUE	EXACT MEANING	REQUIRED EVIDENCE
SYSTEM_DERIVED	The system calculates the value from validated period/policy inputs.	No manual override.
SYSTEM_CONTROL	The system owns the release-state value.	No manual override.

sourceAsOf is recorded once on the Sources row and must equal the filing period end. No separate sign-off metadata is required.

7. Current input checklist and exact fix location

Centralized remediation: use only this fund-period's `filing_inputs.xlsx`. Do not create gap-specific workbooks or empty evidence templates. Register the real supporting file or system once on Sources, then enter the supported value in the named workbook row.

ID / STATUS	WHAT MUST BE RESOLVED	SINGLE REVIEW DESTINATION
G-001 OPEN INPUT	Independent position population All Part C holdings, including GPTZ if the fund owns it	<code>filing_inputs.xlsx</code> CLI + Sources + HoldingFields
G-002 OPEN INPUT	Independent fund-accounting close Assets, liabilities, net assets, balance-sheet items, gains, returns, and cash	<code>filing_inputs.xlsx</code> Sources + FundFields
G-003 PARTLY AUTOMATED INPUT	Create/redeem flows mon1/2/3 Sales, Redemption, and Reinvestment	<code>filing_inputs.xlsx</code> CLI + Sources + FundFields
G-004 OPEN INPUT	Fund policy and static data Fiscal year-end, filing type, derivatives regime, applicability, identity, and signer fields	<code>filing_inputs.xlsx</code> Sources + FundFields

ID / STATUS	WHAT MUST BE RESOLVED	SINGLE REVIEW DESTINATION
G-005 ENGINEERED	Source manifest Lineage for every accepted source	<code>filing_inputs.xlsx</code> Sources
G-006 ENGINEERED CONTROL	Prohibited comparison inputs U.S. Bank, EagleSTAR, prepared filings, legacy masters, and derived canonical files	<code>filing_inputs.xlsx</code> Sources + supplied paths
G-007 ENGINEERED	Manual input trace Value/disposition, source, filing cutoff, and reason	<code>filing_inputs.xlsx</code> FundFields + HoldingFields + Sources
G-008 CONDITIONAL OPEN INPUT	Swap economics Counterparty, LEI, notional, value, termination, and receive/pay leg terms	<code>filing_inputs.xlsx</code> Sources + HoldingFields

ID / STATUS	WHAT MUST BE RESOLVED	SINGLE REVIEW DESTINATION
G-009 CONDITIONAL OPEN INPUT	B.2.f / B.3 / B.5.c / B.9 / B.10 Cash outside C/D, risk metrics, monthly categories, derivatives exposure, or VaR	filing_inputs.xlsx Sources + FundFields
G-010 CONDITIONAL OPEN INPUT	C.7 liquidity liquidityClassificationJson and liquidityCircumstancesJson by holding	filing_inputs.xlsx Sources + HoldingFields
G-011 CONDITIONAL OPEN INPUT	Option terms and delta Delta, exercise terms, expiry, and underlying/reference identity	filing_inputs.xlsx Sources + HoldingFields
G-012 IMPLEMENTED INPUT + VALIDATION	Independent reconciliation Position-to-GL, monthly flows, derivative totals when applicable, NAV equation, and position count	filing_inputs.xlsx Sources + ReconciliationInputs

ID / STATUS	WHAT MUST BE RESOLVED	SINGLE REVIEW DESTINATION
G-013 OUT OF ACTIVE SCOPE	Origin assurance Local files cannot prove a person did not manually copy and relabel a prohibited value	No workbook field

Exact fix location and proof

ID	SHEET / ENTRY POINT	EXACT ACTION	OWNER	COMPLETION TEST
G-001	CLI + Sources + HoldingFields	prepare <fund> <period> --positions <independent.csv>; complete Sources[sourceId=POSITIONS]; then resolve HoldingFields[gapId starts G-001].	Operations	POSITIONS source row, period-end cutoff, hash, row count, and position-count reconciliation
G-002	Sources + FundFields	Add Sources[sourceId=<accounting ID>]; fill FundFields[gapId starts G-002] columns proposedValue, sourceId, status, comment.	Fund Accounting	Each PROVIDED row cites the independent source; NAV equation passes
G-003	CLI + Sources + FundFields	Pass --orders to prepare; complete Sources[sourceId=ORDERS]; fill only unresolved FundFields[gapId starts G-003].	Capital Markets + Accounting	Accepted-order calculation, filing cutoff, and independent reconciliation
ID	SHEET / ENTRY POINT	EXACT ACTION	OWNER	COMPLETION TEST
G-004	Sources + FundFields	Add the actual policy/static source row; fill FundFields[targetFile=fund_config.txt] proposedValue, sourceId, status, comment. currentValue is reference-only.	Compliance / Legal	Supported value, effective date, and internal policy reference
G-005	Sources	For every used sourceId, complete dataset, sourceType, sourceSystem, sourcePath, sourceAsOf, comment. Build calculates blank file hash/count.	Operations	System, path, cutoff, hash, and count are complete
G-006	Sources + supplied paths	Delete the prohibited Sources row/path and replace each dependent field sourceId with a real independent source. No replacement value is entered from comparison files.	Engineering + Operations	Prohibited-source check passes; legacy writers remain disabled

ID	SHEET / ENTRY POINT	EXACT ACTION	OWNER	COMPLETION TEST
G-007	FundFields + HoldingFields + Sources	For each PROVIDED row, supply value and sourceId. For each NOT_APPLICABLE row, supply sourceId and factual comment.	Operations	Build reports zero open inputs/errors; input receipt hashes workbook and outputs
G-008	Sources + HoldingFields	Add Sources[sourceId=<swap ID>]; fill HoldingFields[gapId starts G-008] for each swap recordKey.	Derivatives Operations	All required swap fields supported; valuation reconciles
G-009	Sources + FundFields	Add the actual accounting/risk Sources row; fill FundFields[gapId starts G-009] with PROVIDED or source-backed NOT_APPLICABLE.	Accounting + Risk	Fund policy determines applicability; preflight enforces applicable sections
ID	SHEET / ENTRY POINT	EXACT ACTION	OWNER	COMPLETION TEST
G-010	Sources + HoldingFields	Add Sources[sourceId=<liquidity ID>]; fill HoldingFields[gapId starts G-010] for every applicable recordKey.	Liquidity Risk	100% applicable holding coverage and source evidence
G-011	Sources + HoldingFields	Add Sources[sourceId=<option/risk ID>]; fill HoldingFields[gapId starts G-011] for each option recordKey.	Derivatives Risk	Required option fields supported and validated
G-012	Sources + ReconciliationInputs	Add each independent control source on Sources. In every generated ReconciliationInputs row enter controlValue, tolerance, sourceId, status, and comment. The control source must differ from the source supplying the filed-side value.	Accounting + Operations	Every generated control is resolved and every build-calculated reconciliation row is PASS
ID	SHEET / ENTRY POINT	EXACT ACTION	OWNER	COMPLETION TEST
G-013	No workbook field	Nothing can be entered to prove origin technically. Use an authenticated connector or explicitly accepted external governance control.	Operations + Compliance	Documented independent origin; no claim that local code can prove origin

8. How to read the field trace

Actual lineage is not authorization. The second column states what the current/legacy code really used, including Bloomberg formulas, U.S. Bank custody, EagleSTAR, seeded review workbooks, constants, and no-feed fields. Those legacy writers are disabled or prohibited for the new production build. The fourth column is the only production workflow.

The trace is generated from the canonical config, filing, and holding field maps. Generation stops if field counts change or the verified lineage anchors no longer resolve.

Verification performed: 72 rows: code anchor located for each; Bloomberg claims checked against BLOOMBERG_SPECS (10 cols) + risk sheet (4 cols); EagleSTAR claims checked against 17 writer keys; Human-review claims checked against 15 review value columns; Custodian claims checked against 67 transform-assigned keys; filing_master HEADER: 55 columns, 0 unmapped; Exhaustive canonical trace: 170 fields (30 config, 56 filing, 84 holding).

9. Exhaustive field trace - fund configuration

All 30 accepted fund-configuration fields are listed. `requiredSources` is derived from source IDs used by PROVIDED and NOT_APPLICABLE rows; it is not typed as business data. `policyApprovedBy` and `policyApprovedAt` are retained only as compatibility keys and are not requested by the input workbook.

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
cik	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=cik. Enter proposedValue, sourceId, and status=PROVIDED.
ccc	fund_config.txt (current); EDGAR filer administrator	Injected only at execution; never copied from comparison files src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=ccc. Enter proposedValue, sourceId, and status=PROVIDED.
regName	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regName. Enter proposedValue, sourceId, and status=PROVIDED.
regFileNumber	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regFileNumber. Enter proposedValue, sourceId, and status=PROVIDED.

Fund configuration (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
regCik	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regCik. Enter proposedValue, sourceId, and status=PROVIDED.
regLei	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regLei. Enter proposedValue, sourceId, and status=PROVIDED.
regStreet1	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regStreet1. Enter proposedValue, sourceId, and status=PROVIDED.
regStreet2	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regStreet2. Enter proposedValue, sourceId, and status=PROVIDED.

Fund configuration (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
regCity	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regCity. Enter proposedValue, sourceId, and status=PROVIDED.
regState	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regState. Enter proposedValue, sourceId, and status=PROVIDED.
regCountry	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regCountry. Enter proposedValue, sourceId, and status=PROVIDED.
regZipOrPostalCode	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regZipOrPostalCode. Enter proposedValue, sourceId, and status=PROVIDED.

Fund configuration (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
regPhone	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regPhone. Enter proposedValue, sourceId, and status=PROVIDED.
seriesName	fund_config.txt (current static value)	Direct identifier mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=seriesName. Enter proposedValue, sourceId, and status=PROVIDED.
seriesId	fund_config.txt (current static value)	Direct identifier mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=seriesId. Enter proposedValue, sourceId, and status=PROVIDED.
seriesLei	fund_config.txt (current static value)	Direct identifier mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=seriesLei. Enter proposedValue, sourceId, and status=PROVIDED.

Fund configuration (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
classId	fund_config.txt (current static value)	Direct identifier mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=classId. Enter proposedValue, sourceId, and status=PROVIDED.
signerOrg	fund_config.txt (current static value)	Direct mapping; evidence retained with filing approval src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=signerOrg. Enter proposedValue, sourceId, and status=PROVIDED.
signerName	fund_config.txt (current static value)	Direct mapping; evidence retained with filing approval src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=signerName. Enter proposedValue, sourceId, and status=PROVIDED.
signerTitle	fund_config.txt (current static value)	Direct mapping; evidence retained with filing approval src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=signerTitle. Enter proposedValue, sourceId, and status=PROVIDED.

Fund configuration (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
fiscalYearEndMMDD	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=fiscalYearEndMMDD. Enter proposedValue, sourceId, and status=PROVIDED.
derivativesRegimePolicy	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=derivativesRegimePolicy. Enter proposedValue, sourceId, and status=PROVIDED.
liquidityRequired	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=liquidityRequired. Enter proposedValue, sourceId, and status=PROVIDED.
cashB2fRequired	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=cashB2fRequired. Enter proposedValue, sourceId, and status=PROVIDED.

Fund configuration (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
policyEffectiveFrom	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=policyEffectiveFrom. Enter proposedValue, sourceId, and status=PROVIDED.
policyEffectiveTo	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=policyEffectiveTo. Enter proposedValue, sourceId, and status=PROVIDED.
policyApprovedBy	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	Retired compatibility key; the new input workbook does not request or gate on this metadata.
policyApprovedAt	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	Retired compatibility key; the new input workbook does not request or gate on this metadata.

Fund configuration (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
policySourceRef	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=policySourceRef. Enter proposedValue, sourceId, and status=PROVIDED.
requiredSources	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	System-derived from sourceIds used by PROVIDED or NOT_APPLICABLE rows; the operator does not type it.

10. Exhaustive field trace - filing-level data

All 56 accepted filing-level fields are listed. A legacy constant is reported as a constant; it is not silently reclassified as sourced data.

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
submissionType	Tool-derived filing period/default; future approved fund registry	filing_master.py derives the period; policy.py overrides from an approved registry when present src/nport/filing_master.py:66	SYSTEM_DERIVED after the period and supplied fund-policy rows pass validation.
liveTestFlag	Filing Operations and authorized signer workflow	Operator-controlled status/date with release gate src/nport/cli.py:1209	SYSTEM_CONTROL; remains TEST until all release controls pass.
repPdEnd	Tool-derived filing period/default; future approved fund registry	filing_master.py derives the period; policy.py overrides from an approved registry when present src/nport/custodian.py:808	SYSTEM_DERIVED after the period and supplied fund-policy rows pass validation.
repPdDate	Tool-derived filing period/default; future approved fund registry	filing_master.py derives the period; policy.py overrides from an approved registry when present src/nport/custodian.py:808	SYSTEM_DERIVED after the period and supplied fund-policy rows pass validation.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
isFinalFiling	Filing Operations and authorized signer workflow	Operator-controlled status/date with release gate src/nport/filing_master.py:66	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=isFinalFiling. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
dateSigned	Filing Operations and authorized signer workflow	Operator-controlled status/date with release gate src/nport/filing_master.py:118	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=dateSigned. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
totAssets	Gmail export - U.S. Bank EagleSTAR Trial Balance; custodian fallback	eaglestar.py overrides filing_master.py custody-derived fallback src/nport/eaglestar.py:310	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=totAssets. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
totLiabs	Gmail export - U.S. Bank EagleSTAR Trial Balance; custodian fallback	eaglestar.py overrides filing_master.py custody-derived fallback src/nport/eaglestar.py:312	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=totLiabs. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
netAssets	Gmail export - U.S. Bank EagleSTAR Trial Balance; custodian fallback	eaglestar.py overrides filing_master.py custody-derived fallback src/nport/eaglestar.py:314	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=netAssets. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
assetsAttrMiscSec	Gmail export - U.S. Bank EagleSTAR Trial Balance; custodian fallback	eaglestar.py overrides filing_master.py custody-derived fallback src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=assetsAttrMiscSec. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
assetsInvested	Gmail export - U.S. Bank EagleSTAR Trial Balance; custodian fallback	eaglestar.py overrides filing_master.py custody-derived fallback src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=assetsInvested. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
amtPayOneYrBanksBorr	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayOneYrBanksBorr. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
amtPayOneYrCtrldComp	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayOneYrCtrldComp. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
amtPayOneYrOthAffil	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayOneYrOthAffil. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
amtPayOneYrOther	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:307	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayOneYrOther. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
amtPayAftOneYrBanksBorr	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayAftOneYrBanksBorr. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
amtPayAftOneYrCtrlComp	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayAftOneYrCtrlComp. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
amtPayAftOneYrOthAffil	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayAftOneYrOthAffil. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
amtPayAftOneYrOthher	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayAftOneYrOthher. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
delayDeliv	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=delayDeliv. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
standByCommit	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=standByCommit. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
liquidPref	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=liquidPref. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
isNonCashCollateral	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=isNonCashCollateral. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
rtn1	Bloomberg formula in filing_master.xlsx	BDP custom total-return formula for each reporting month src/nport/filing_master.py:48	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=rtn1. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
rtn2	Bloomberg formula in filing_master.xlsx	BDP custom total-return formula for each reporting month src/nport/filing_master.py:48	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=rtn2. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
rtn3	Bloomberg formula in filing_master.xlsx	BDP custom total-return formula for each reporting month src/nport/filing_master.py:48	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=rtn3. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
netRealizedGainMon1	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=netRealizedGainMon1. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
netUnrealizedApprMon1	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=netUnrealizedApprMon1. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
netRealizedGainMon2	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=netRealizedGainMon2. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
netUnrealizedApprMon2	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=netUnrealizedApprMon2. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
netRealizedGainMon3	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=netRealizedGainMon3. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
netUnrealizedApprMon3	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=netUnrealizedApprMon3. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
mon1Sales	Gmail export - EagleSTAR Trial Balance	eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon1Sales. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
mon1Redemption	Gmail export - EagleSTAR Trial Balance	eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon1Redemption. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
mon1Reinvestment	No current feed; filing_master.py supplies N/A	Create/redeem orders do not contain reinvested distributions src/nport/models.py:84	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon1Reinvestment. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
mon2Sales	Gmail export - EagleSTAR Trial Balance	eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon2Sales. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
mon2Redemption	Gmail export - EagleSTAR Trial Balance	eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon2Redemption. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
mon2Reinvestment	No current feed; filing_master.py supplies N/A	Create/redeem orders do not contain reinvested distributions src/nport/models.py:87	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon2Reinvestment. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
mon3Sales	Gmail export - EagleSTAR Trial Balance	eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon3Sales. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
mon3Redemption	Gmail export - EagleSTAR Trial Balance	eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon3Redemption. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
mon3Reinvestment	No current feed; filing_master.py supplies N/A	Create/redeem orders do not contain reinvested distributions src/nport/models.py:90	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon3Reinvestment. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
nameDesignatedIndex	Human-review workbook designated_index sheet (legacy 497K seed)	humanreview.py seed values merge through filing_master.py src/nport/master_sheet.py:748	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=nameDesignatedIndex. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
indexIdentifier	Human-review workbook designated_index sheet (legacy 497K seed)	humanreview.py seed values merge through filing_master.py src/nport/master_sheet.py:748	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=indexIdentifier. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
curMetricsJson	Bloomberg formulas plus U.S. Bank custodian market value	filing_master.py aggregates duration/rating fields after workbook calculation src/nport/filing_master.py:40	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=curMetricsJson. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
creditSprdRiskIgJson	Bloomberg formulas plus U.S. Bank custodian market value	filing_master.py aggregates duration/rating fields after workbook calculation src/nport/filing_master.py:40	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=creditSprdRiskIgJson. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
creditSprdRiskNonigJson	Bloomberg formulas plus U.S. Bank custodian market value	filing_master.py aggregates duration/rating fields after workbook calculation src/nport/filing_master.py:40	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=creditSprdRiskNonigJson. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
cashNotReportedInCoRD	No current feed	Typed field exists; no Gmail, custodian, create/redeem, or Bloomberg writer src/nport/models.py:100	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=cashNotReportedInCoRD. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
monthlyReturnCategoriesJson	No current feed	Typed field exists; no Gmail, custodian, create/redeem, or Bloomberg writer src/nport/models.py:101	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=monthlyReturnCategoriesJson. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
derivativesRegime	No current populated source; future approved fund registry	policy.py derives it only when the registry exists src/nport/filing_master.py:321	SYSTEM_DERIVED after the period and supplied fund-policy rows pass validation.
derivExposurePct	No current feed	B.9/B.10 typed fields and preflight gates exist, but no writer populates them src/nport/models.py:103	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=derivExposurePct. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
derivCurrencyExposurePct	No current feed	B.9/B.10 typed fields and preflight gates exist, but no writer populates them src/nport/models.py:104	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=derivCurrencyExposurePct. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
derivInterestRateExposurePct	No current feed	B.9/B.10 typed fields and preflight gates exist, but no writer populates them src/nport/models.py:105	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=derivInterestRateExposurePct. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.

Filing-level data (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
derivDaysInExcess	No current feed	B.9/B.10 typed fields and preflight gates exist, but no writer populates them src/nport/models.py:106	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=derivDaysInExcess. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
medianDailyVarPct	No current feed	B.9/B.10 typed fields and preflight gates exist, but no writer populates them src/nport/models.py:107	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=medianDailyVarPct. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
medianVarRatioPct	No current feed	B.9/B.10 typed fields and preflight gates exist, but no writer populates them src/nport/models.py:108	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=medianVarRatioPct. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.
backtestingExceptions	No current feed	B.9/B.10 typed fields and preflight gates exist, but no writer populates them src/nport/models.py:109	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=backtestingExceptions. Use PROVIDED or a source-backed NOT_APPLICABLE disposition.

11. Exhaustive field trace - holdings

All 84 accepted holdings fields are listed and grouped by filing condition. Present base values remain tied to the independent POSITIONS source; missing required and exception-sensitive values are surfaced in HoldingFields.

Base

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
name	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. <code>src/nport/custodian.py:107</code>	Base value is positions.csv column name. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=name. Requirement: always.
lei	Bloomberg workbook formula for conventional securities; explicit constants on some derivative/UST paths	BDP enrichment owns conventional-security values; custodian code sets N/A/US or the U.S. Treasury LEI on identified special paths. <code>src/nport/master_sheet.py:128</code>	Base value is positions.csv column lei. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=lei. Requirement: always.
title	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. <code>src/nport/custodian.py:107</code>	Base value is positions.csv column title. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=title. Requirement: always.
cusip	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. <code>src/nport/custodian.py:107</code>	Base value is positions.csv column cusip. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=cusip. Requirement: always.

Base (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
isin	Bloomberg workbook formula for conventional securities; explicit constants on some derivative/UST paths	BDP enrichment owns conventional-security values; custodian code sets N/A/US or the U.S. Treasury LEI on identified special paths. <code>src/nport/master_sheet.py:128</code>	Base value is positions.csv column isin. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=isin. Requirement: never.
ticker	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. <code>src/nport/custodian.py:107</code>	Base value is positions.csv column ticker. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=ticker. Requirement: never.
balance	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. <code>src/nport/custodian.py:679</code>	Base value is positions.csv column balance. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=balance. Requirement: always.
units	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. <code>src/nport/custodian.py:680</code>	Base value is positions.csv column units. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=units. Requirement: always.

Base (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
curCd	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:662	Base value is positions.csv column curCd. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=curCd. Requirement: always.
valUSD	U.S. Bank custodian CSV for non-swaps; EagleSTAR PVal for swaps	MarketValue is used for non-swaps; swap value is replaced with matched unrealized PVal. src/nport/eaglestar.py:206	Base value is positions.csv column valUSD. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=valUSD. Requirement: always.
pctVal	Derived from filed valUSD and filed netAssets	The legacy transform recalculates the percentage after accounting overrides. src/nport/custodian.py:125	Base value is positions.csv column pctVal. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pctVal. Requirement: always.
payoffProfile	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:662	Base value is positions.csv column payoffProfile. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=payoffProfile. Requirement: always.

Base (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
assetCat	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:108	Base value is positions.csv column assetCat. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=assetCat. Requirement: always.
issuerCat	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:108	Base value is positions.csv column issuerCat. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=issuerCat. Requirement: always.
invCountry	Bloomberg workbook formula for conventional securities; explicit constants on some derivative/UST paths	BDP enrichment owns conventional-security values; custodian code sets N/A/US or the U.S. Treasury LEI on identified special paths. src/nport/master_sheet.py:157	Base value is positions.csv column invCountry. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=invCountry. Requirement: always.
isRestrictedSec	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:662	Base value is positions.csv column isRestrictedSec. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=isRestrictedSec. Requirement: always.

Base (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
fairValLevel	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:662	Base value is positions.csv column fairValLevel. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=fairValLevel. Requirement: always.
isCashCollateral	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:662	Base value is positions.csv column isCashCollateral. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=isCashCollateral. Requirement: always.
isNonCashCollateral	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:662	Base value is positions.csv column isNonCashCollateral. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=isNonCashCollateral. Requirement: always.
isLoanByFund	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:662	Base value is positions.csv column isLoanByFund. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=isLoanByFund. Requirement: always.

Conditional

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
issuerConditionalDesc	Tool constant only on the legacy swap path; otherwise no verified writer	custodian.py sets N/A for swaps; other issuerCat=OTHER cases are not populated automatically. src/nport/custodian.py:662	Base value is positions.csv column issuerConditionalDesc. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=issuerConditionalDesc. Requirement: conditional - issuerCat==OTHER.
assetConditionalDesc	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:137	Base value is positions.csv column assetConditionalDesc. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=assetConditionalDesc. Requirement: conditional - assetCat==OTHER.
otherDesc	Tool-generated identifier only for legacy option/swap paths	custodian.py writes USER DEFINED plus an internally constructed option/swap identifier; other paths remain blank. src/nport/custodian.py:662	Base value is positions.csv column otherDesc. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=otherDesc. Requirement: never.
otherValue	Tool-generated identifier only for legacy option/swap paths	custodian.py writes USER DEFINED plus an internally constructed option/swap identifier; other paths remain blank. src/nport/custodian.py:662	Base value is positions.csv column otherValue. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=otherValue. Requirement: never.

Conditional (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
exchangeRt	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:140</code>	Base value is positions.csv column exchangeRt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=exchangeRt. Requirement: conditional - non-USD currency.

Debt

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
maturityDt	Bloomberg workbook formula; U.S. Treasury name parser exists in the direct custodian transform	Corporate/debt master enrichment uses BDP; the alternate direct Treasury path parses coupon and maturity from SecurityName. <code>src/nport/master_sheet.py:101</code>	Base value is positions.csv column maturityDt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=maturityDt. Requirement: conditional - debt security.
couponKind	Bloomberg workbook formula; U.S. Treasury name parser exists in the direct custodian transform	Corporate/debt master enrichment uses BDP; the alternate direct Treasury path parses coupon and maturity from SecurityName. <code>src/nport/master_sheet.py:101</code>	Base value is positions.csv column couponKind. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=couponKind. Requirement: conditional - maturityDt set.
annualizedRt	Bloomberg workbook formula; U.S. Treasury name parser exists in the direct custodian transform	Corporate/debt master enrichment uses BDP; the alternate direct Treasury path parses coupon and maturity from SecurityName. <code>src/nport/master_sheet.py:101</code>	Base value is positions.csv column annualizedRt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=annualizedRt. Requirement: conditional - maturityDt set.
isDefault	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. <code>src/nport/custodian.py:137</code>	Base value is positions.csv column isDefault. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=isDefault. Requirement: conditional - maturityDt set.

Debt (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
areIntrstPmntsInArrs	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. <code>src/nport/custodian.py:137</code>	Base value is positions.csv column areIntrstPmntsInArrs. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=areIntrstPmntsInArrs. Requirement: conditional - maturityDt set.
isPaidKind	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. <code>src/nport/custodian.py:137</code>	Base value is positions.csv column isPaidKind. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=isPaidKind. Requirement: conditional - maturityDt set.

Deriv Common

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
derivCat	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:114	Base value is positions.csv column derivCat. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=derivCat. Requirement: conditional - derivative holding.
counterpartyName	Seeded human-review overlay for swaps; OCC tool constant for options	Swap values come from the legacy counterparty sheet; option values use the OCC constants in custodian.py. src/nport/master_sheet.py:776	Base value is positions.csv column counterpartyName. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=counterpartyName. Requirement: conditional - derivCat set.
counterpartyLei	Seeded human-review overlay for swaps; OCC tool constant for options	Swap values come from the legacy counterparty sheet; option values use the OCC constants in custodian.py. src/nport/master_sheet.py:776	Base value is positions.csv column counterpartyLei. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=counterpartyLei. Requirement: conditional - derivCat set.
unrealizedAppr	Gmail export - U.S. Bank EagleSTAR PVal attachment	Matched by Primary Asset ID and written as the derivative unrealized amount. src/nport/eaglestar.py:206	Base value is positions.csv column unrealizedAppr. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=unrealizedAppr. Requirement: conditional - derivCat set.

Option

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
putOrCall	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:115	Base value is positions.csv column putOrCall. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=putOrCall. Requirement: conditional - derivCat in OPT/SWO/WAR.
writtenOrPur	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:115	Base value is positions.csv column writtenOrPur. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=writtenOrPur. Requirement: conditional - derivCat in OPT/SWO/WAR.
shareNo	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:662	Base value is positions.csv column shareNo. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=shareNo. Requirement: never.
exercisePrice	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:115	Base value is positions.csv column exercisePrice. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=exercisePrice. Requirement: conditional - derivCat in OPT/SWO/WAR.

Option (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
exercisePriceCurCd	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:115	Base value is positions.csv column exercisePriceCurCd. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=exercisePriceCurCd. Requirement: never.
expDt	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:116	Base value is positions.csv column expDt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=expDt. Requirement: conditional - derivCat in OPT/SWO/WAR.
delta	Manual value preserved in security_master.xlsx; no automated feed	The legacy master preserves the workbook cell; it does not calculate or source delta. src/nport/models.py:160	Base value is positions.csv column delta. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=delta. Requirement: conditional - derivCat in OPT/SWO/WAR.

Ref Instrument

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
refInstType	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:117	Base value is positions.csv column refInstType. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refInstType. Requirement: never.
refIndexName	Seeded legacy human-review workbook overlay	master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin. src/nport/master_sheet.py:789	Base value is positions.csv column refIndexName. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refIndexName. Requirement: conditional - refInstType==indexBasket.
refIndexIdentifier	Seeded legacy human-review workbook overlay	master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin. src/nport/master_sheet.py:789	Base value is positions.csv column refIndexIdentifier. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refIndexIdentifier. Requirement: conditional - refInstType==indexBasket.
refIssuerName	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:129	Base value is positions.csv column refIssuerName. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refIssuerName. Requirement: conditional - refInstType==otherRefInst.

Ref Instrument (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
refIssueTitle	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:129	Base value is positions.csv column refIssueTitle. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refIssueTitle. Requirement: conditional - refInstType==otherRefInst.
refCusip	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:130	Base value is positions.csv column refCusip. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refCusip. Requirement: never.
refIsin	Bloomberg workbook formula on the reference security	BDP enrichment uses the reference CUSIP/security key. src/nport/master_sheet.py:129	Base value is positions.csv column refIsin. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refIsin. Requirement: never.
refTicker	Bloomberg workbook formula on the reference security	BDP enrichment uses the reference CUSIP/security key. src/nport/master_sheet.py:129	Base value is positions.csv column refTicker. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refTicker. Requirement: never.

Swap

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
swapFlag	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:124	Base value is positions.csv column swapFlag. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=swapFlag. Requirement: conditional - derivCat==SWP.
terminationDt	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:124	Base value is positions.csv column terminationDt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=terminationDt. Requirement: conditional - derivCat==SWP.
upfrontPmnt	Builder fallback, not a sourced legacy field	builder.py emits 0 when the accepted holding column is blank. src/nport/builder.py:497	Base value is positions.csv column upfrontPmnt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=upfrontPmnt. Requirement: never.
pmntCurCd	Builder fallback, not a sourced legacy field	builder.py uses the holding currency when the accepted holding column is blank. src/nport/builder.py:498	Base value is positions.csv column pmntCurCd. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntCurCd. Requirement: never.

Swap (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
upfrontRcpt	Builder fallback, not a sourced legacy field	builder.py emits 0 when the accepted holding column is blank. src/nport/builder.py:499	Base value is positions.csv column upfrontRcpt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=upfrontRcpt. Requirement: never.
rcptCurCd	Builder fallback, not a sourced legacy field	builder.py uses the holding currency when the accepted holding column is blank. src/nport/builder.py:500	Base value is positions.csv column rcptCurCd. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=rcptCurCd. Requirement: never.
notionalAmt	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:124	Base value is positions.csv column notionalAmt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=notionalAmt. Requirement: conditional - derivCat==SWP.
swapCurCd	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:124	Base value is positions.csv column swapCurCd. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=swapCurCd. Requirement: never.

Swap (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
recFixedOrFloating	Seeded legacy human-review workbook overlay	master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin. src/nport/master_sheet.py:748	Base value is positions.csv column recFixedOrFloating. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recFixedOrFloating. Requirement: conditional - derivCat==SWP.
recFixedRt	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:181	Base value is positions.csv column recFixedRt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recFixedRt. Requirement: conditional - recFixedOrFloating==Fixed.
recFloatingRtIndex	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:182	Base value is positions.csv column recFloatingRtIndex. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recFloatingRtIndex. Requirement: conditional - recFixedOrFloating==Floating.
recFloatingRtSpread	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:183	Base value is positions.csv column recFloatingRtSpread. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recFloatingRtSpread. Requirement: conditional - recFixedOrFloating==Floating.

Swap (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
recPmntAmt	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:184</code>	Base value is positions.csv column recPmntAmt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recPmntAmt. Requirement: never.
recCurCd	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:185</code>	Base value is positions.csv column recCurCd. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recCurCd. Requirement: never.
recRateTenor	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:186</code>	Base value is positions.csv column recRateTenor. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recRateTenor. Requirement: never.
recRateUnit	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:187</code>	Base value is positions.csv column recRateUnit. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recRateUnit. Requirement: never.

Swap (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
recResetDt	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:188</code>	Base value is positions.csv column recResetDt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recResetDt. Requirement: never.
recResetUnit	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:189</code>	Base value is positions.csv column recResetUnit. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recResetUnit. Requirement: never.
recDesc	Seeded legacy human-review workbook overlay	master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin. <code>src/nport/master_sheet.py:748</code>	Base value is positions.csv column recDesc. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recDesc. Requirement: never.
pmntDesc	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:192</code>	Base value is positions.csv column pmntDesc. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntDesc. Requirement: never.

Swap (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
pmntFixedOrFloating	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:127	Base value is positions.csv column pmntFixedOrFloating. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntFixedOrFloating. Requirement: conditional - derivCat==SWP.
pmntFixedRt	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:194	Base value is positions.csv column pmntFixedRt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntFixedRt. Requirement: conditional - pmntFixedOrFloating==Fixed.
pmntFloatingRtIndex	Seeded legacy human-review workbook overlay	master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin. src/nport/master_sheet.py:748	Base value is positions.csv column pmntFloatingRtIndex. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntFloatingRtIndex. Requirement: conditional - pmntFixedOrFloating==Floating.
pmntFloatingRtSpread	Seeded legacy human-review workbook overlay	master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin. src/nport/master_sheet.py:748	Base value is positions.csv column pmntFloatingRtSpread. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntFloatingRtSpread. Requirement: conditional - pmntFixedOrFloating==Floating.

Swap (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
pmntPmntAmt	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:197	Base value is positions.csv column pmntPmntAmt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntPmntAmt. Requirement: never.
pmntCurCdLeg	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:128	Base value is positions.csv column pmntCurCdLeg. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntCurCdLeg. Requirement: never.
pmntRateTenor	Seeded legacy human-review workbook overlay	master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin. src/nport/master_sheet.py:748	Base value is positions.csv column pmntRateTenor. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntRateTenor. Requirement: never.
pmntRateUnit	Seeded legacy human-review workbook overlay	master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin. src/nport/master_sheet.py:748	Base value is positions.csv column pmntRateUnit. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntRateUnit. Requirement: never.

Swap (continued)

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
pmntResetDt	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:201</code>	Base value is positions.csv column pmntResetDt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntResetDt. Requirement: never.
pmntResetUnit	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:202</code>	Base value is positions.csv column pmntResetUnit. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntResetUnit. Requirement: never.

Forward

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
payoffProfDeriv	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:204</code>	Base value is positions.csv column payoffProfDeriv. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=payoffProfDeriv. Requirement: conditional - derivCat in FWD/FUT.

Other Deriv

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
otherDerivDesc	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:206</code>	Base value is positions.csv column otherDerivDesc. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=otherDerivDesc. Requirement: conditional - derivCat==OTH.

Liquidity

CANONICAL FIELD	ACTUAL CURRENT/LEGACY ORIGIN	TRANSFORM AND LIVE CODE LOCATION	NEW INDEPENDENT WORKFLOW
liquidityClassificationJson	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:209</code>	Base value is positions.csv column liquidityClassificationJson. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=liquidityClassificationJson. Requirement: conditional - fund policy requires C.7.
liquidityCircumstancesJson	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:210</code>	Base value is positions.csv column liquidityCircumstancesJson. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=liquidityCircumstancesJson. Requirement: never.

12. Release decision

nport build <fund> <period> --from-inputs writes output only after every applicable field and reconciliation control is resolved, control sources are independent of filed-side sources, source cutoffs match the report period, source hashes and counts match, prohibited sources are absent, all reconciliations pass, canonical validation passes, and XSD validation passes. G-013 is outside the active remediation plan; no claim is made that a local file path authenticates origin.

Generated from the repository field contracts and source controls on 2026-08-04.