

# N-PORT In-House Runbook

A field-by-field operating guide showing what supplies each value, exactly where it is entered, how the input workflow runs, and what blocks release.

As of August 4, 2026 · Source-independent workflow

**Controlling rule:** no file, value, mapping, or pre-fill delivered by U.S. Bank may populate the in-house filing. Those artifacts are read-only comparison evidence.

## 1. Purpose and non-negotiable boundary

This runbook operates an N-PORT service built from independent sources. U.S. Bank custody exports, EagleSTAR attachments, prepared filings, email attachments, and prior master workbooks are benchmark outputs only. They may never be copied, merged, seeded, or used to clear a production exception.

**Stop rule:** if the only available answer comes from U.S. Bank, record the field as MISSING and keep the filing NOT READY.

## 2. Status language

| Status    | Use it when                                                        | Operator action                                               |
|-----------|--------------------------------------------------------------------|---------------------------------------------------------------|
| MISSING   | A required XML value or policy/ applicability input is unresolved. | Complete the exact FundFields or HoldingFields row.           |
| NOT READY | One or more open inputs or validation errors remain.               | Fix the exact workbook row or upstream file printed by build. |
| PROVIDED  | A current or proposed value is ready for build.                    | Set status; sourceId is optional.                             |
| CLEAR     | XML fields, applicability, validation, and reconciliation pass.    | Retain the inputs and proceed.                                |

## 3. What matters to the filing

**Release rule:** source labels do not appear in N-PORT XML. The build gates only XML values, policy/ applicability inputs that change XML, reconciliation results, canonical validation, and XSD validation.

| Item | Appears in XML | Where the human acts | Release effect |
|------|----------------|----------------------|----------------|
|------|----------------|----------------------|----------------|

| XML value                     | Yes            | FundFields or HoldingFields              | Value/format/requiredness blocks build                       |
|-------------------------------|----------------|------------------------------------------|--------------------------------------------------------------|
| Policy/applicability driver   | Indirectly     | FundFields<br>targetFile=fund_config.txt | Blocks because it changes dates, form, or XML sections       |
| Reconciliation control        | No             | ReconciliationInputs                     | Blocks only when the calculated difference exceeds tolerance |
| Item                          | Appears in XML | Where the human acts                     | Release effect                                               |
| sourceId / Sources metadata   | No             | Optional                                 | Never blocks XML; retained only for diagnostics              |
| U.S. Bank/EagleSTAR reference | No             | Do not input                             | Rejected as a prohibited comparison-output input             |

## 4. Exact operating workflow

**Use this order every time.** Do not skip ahead. If build reports an open input or validation error, correct the named workbook row or upstream file and rerun the same command.

### Step 1 - Check the input format

#### Run:

```
Set-Location "C:\Users\damie\nportvalidation"
& ".\venv\Scripts\nport.exe" schema
```

#### System:

Prints the required and conditional `positions.csv` columns.

#### Human:

Export independent positions to `data/intake/<period>/<fund>/positions.csv`. If available, place the independent order file beside it as `create_redeem_orders.csv`.

#### Stop if:

Either file came from or was derived from U.S. Bank or EagleSTAR.

### Step 2 - Run the preparation automation

#### Run:

```
& ".\venv\Scripts\nport.exe" prepare FDRS 2026-06 --positions ".
\data\intake\2026-06\fdrs\positions.csv" --orders ".
\data\intake\2026-06\fdrs\create_redeem_orders.csv"
```

#### System:

Creates `data/funds/fdrs/filings/2026-06/filing_inputs.xlsx`, calculates controls for the supplied files, and inserts Bloomberg formulas. Omit `--orders` when unavailable.

#### Pass when:

The command prints the expected workbook path.

### Step 3 - Open and save on Bloomberg

**Run:**

Open `filing_inputs.xlsx` in Excel on a logged-in Bloomberg terminal.

**System:**

The Bloomberg Excel Add-In calculates the visible formulas on the `Bloomberg` sheet.

**Human:**

Wait until formulas show values or explicit Bloomberg errors, then save and close the workbook.

**Pass when:**

The workbook is saved with calculated values; unresolved Bloomberg errors remain visible and will block.

### Step 4 - Complete the remaining inputs

**Run:**

Reopen `filing_inputs.xlsx`.

**Human:**

Ignore `Sources` for XML completion. Filter `FundFields` and `HoldingFields` to `MISSING`. For `PROVIDED`, set `status` and enter `proposedValue` only when the automated/current value is absent or must be corrected; fund-config rows require `proposedValue` when applicable. For `NOT_APPLICABLE`, leave `proposedValue` blank and enter `status` plus a factual `comment`. In `ReconciliationInputs`, enter `controlValue`, `tolerance`, `status`, and `comment`. `sourceId` is optional everywhere.

**Pass when:**

Build reports zero open XML inputs and validation/reconciliation errors.

### Step 5 - Run the final automation

**Run:**

```
& ".\venv\Scripts\nport.exe" build FDRS 2026-06 --from-inputs
```

**System:**

Checks XML values, policy/applicability, and reconciliation; writes a clean bundle; generates XML; and runs XSD validation.

**Human:**

If `NOT READY`, correct the exact workbook row or upstream file printed by the command and rerun the same command.

**Pass when:**

The clean bundle and validated XML are written.

### Step 6 - Optional aligned comparison

**Run:**

```
& ".\venv\Scripts\nport.exe" compare-reference --internal ".\output\FDRS_2026-06.xml" --reference "<aligned-reference.xml>"
```

### System:

Writes a versioned clean bundle under `data/builds/fdrs/2026-06/<run-id>/`, writes XML under `output/`, and performs a read-only comparison.

### Human:

Confirm the internal and reference outputs use the same fund identity and report date. Document gaps; never copy comparison values back into the filing.

### Pass when:

The clean bundle, receipt, validated XML, and documented comparison all exist.

## Run the workflow for every fund

**Scope rule:** the service is not limited to FDRS. Each fund has its own positions file, input workbook, clean bundle, and XML.

**Phase A - generate one input workbook per intake folder.** The folder name is the fund ticker.

```
$period = "2026-06"
$nport = ".\env\Scripts\nport.exe"
$intakeRoot = Join-Path ".\data\intake" $period

foreach ($fundFolder in Get-ChildItem -LiteralPath $intakeRoot -Directory) {
    $fund = $fundFolder.Name.ToLowerInvariant()
    $positions = Join-Path $fundFolder.FullName "positions.csv"
    $orders = Join-Path $fundFolder.FullName "create_redeem_orders.csv"
    if (-not (Test-Path -LiteralPath $positions)) {
        throw "Missing independent positions file for $fund: $positions"
    }
    $prepareArgs = @("prepare", $fund, $period, "--positions", $positions)
    if (Test-Path -LiteralPath $orders) {
        $prepareArgs += @("--orders", $orders)
    }
    & $nport @prepareArgs
    if ($LASTEXITCODE -ne 0) { throw "prepare failed for $fund" }
}
```

**Phase B - Bloomberg and remaining inputs.** Open, calculate, and save each workbook on Bloomberg; then fill each fund's remaining field rows and ReconciliationInputs control rows.

**Phase C - build.** The loop stops at the first fund that is not ready.

```
$period = "2026-06"
$nport = ".\env\Scripts\nport.exe"

foreach ($book in Get-ChildItem -Path ".\data\funds*\filings\$period\filing_inputs.xlsx" -File) {
    $fund = $book.Directory.Parent.Parent.Name.ToLowerInvariant()
    & $nport build $fund $period --from-inputs
    if ($LASTEXITCODE -ne 0) { throw "build failed for $fund" }
}
```

## Complete command reference

| Command                   | Stage         | What it does                                                               | Writes data? |
|---------------------------|---------------|----------------------------------------------------------------------------|--------------|
| <code>nport schema</code> | Intake design | Prints every canonical positions.csv column, type, and applicability rule. | No           |

|                                                                                                                 |                       |                                                                                       |                                            |
|-----------------------------------------------------------------------------------------------------------------|-----------------------|---------------------------------------------------------------------------------------|--------------------------------------------|
| <code>nport prepare &lt;fund&gt;<br/>&lt;period&gt; --positions &lt;file&gt;<br/>[--orders &lt;file&gt;]</code> | Prepare               | Creates filing_inputs.xlsx, gap rows, reconciliation inputs, and Bloomberg formulas.  | Yes - filing_inputs.xlsx                   |
| <code>nport build &lt;fund&gt; &lt;period&gt;<br/>--from-inputs</code>                                          | Validate and build    | Prints exact open inputs/errors or writes the clean bundle and schema-valid XML.      | Only when all inputs and validations clear |
| <code>nport compare-reference --<br/>internal &lt;xml&gt; --reference<br/>&lt;xml&gt;</code>                    | Post-build comparison | Performs a read-only structural comparison after dates and fund identity are aligned. | No filing inputs                           |

  

| Command                                                    | Stage             | What it does                                                   | Writes data?                                        |
|------------------------------------------------------------|-------------------|----------------------------------------------------------------|-----------------------------------------------------|
| <code>nport check-schema</code>                            | Maintenance       | Checks the local N-PORT schema files and version.              | Cache only when applicable                          |
| <code>nport pull --ticker<br/>&lt;ticker&gt; --list</code> | External research | Lists recent EDGAR N-PORT filings; it is not an input adapter. | No, unless an explicit output download is requested |

**Disabled write paths:** masters, split, mergehumanreview, enrich, merge, new-filing, build-master, split-master, build-filing-master, and split-filing-master. Do not use them for the independent service.

## 5. Post-automation human entry queue

**Automation handoff:** run `prepare`, open/save the workbook on Bloomberg, then work only in `filing_inputs.xlsx`. Filter `FundFields` and `HoldingFields` to `MISSING`. Work only the values, policy decisions, and reconciliation controls listed below. Do not complete Sources for XML release.

| Sheet         | Rows to work            | What the reviewer types                                                                                                                                           | What the system owns                                                                                                  |
|---------------|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| FundFields    | Filter status = MISSING | PROVIDED: proposedValue when no automated value exists, plus status. NOT_APPLICABLE: status and factual comment; leave proposedValue blank. sourceId is optional. | For targetFile=fund_config.txt, proposedValue is required whenever the field applies; currentValue is reference-only. |
| HoldingFields | Filter status = MISSING | PROVIDED: status; add proposedValue only when currentValue is blank or must be corrected. NOT_APPLICABLE: status and factual comment. sourceId is optional.       | Enter only rows generated for the supplied positions. Do not add holdings or invent missing rows.                     |

  

| Sheet                | Rows to work            | What the reviewer types                                                                                                                                                        | What the system owns                                                                         |
|----------------------|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|
| ReconciliationInputs | Every generated checkId | PROVIDED: controlValue, tolerance, status, comment. A flow may be NOT_APPLICABLE only when its filed flow is N/A; then enter status and factual comment. sourceId is optional. | Never type actualBasis or the filed-side actual. Build calculates the actual and difference. |
| Sources              | Optional only           | Nothing is required for XML. Automation retains technical paths needed to reload supplied files; optional sourceId notes may be added for diagnostics.                         | Source labels, paths, hashes, counts, and as-of dates never serialize into N-PORT XML.       |

## Exact field names that may remain after automation

| Queue                                        | When the reviewer acts                                                                                               | fieldName / checkId                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|----------------------------------------------|----------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fund configuration - identity/static         | Every generated row is a human confirmation from independent evidence                                                | cik, ccc, regName, regFileNumber, regCik, regLei, regStreet1, regStreet2, regCity, regState, regCountry, regZipOrPostalCode, regPhone, seriesName, seriesId, seriesLei, classId, signerOrg, signerName, signerTitle                                                                                                                                                                                                                                                                                                |
| Fund configuration - policy                  | Confirm from the current policy record. policyEffectiveTo may remain blank when the policy is open-ended.            | fiscalYearEndMMDD, derivativesRegimePolicy, liquidityRequired, cashB2fRequired, policyEffectiveFrom, policyEffectiveTo                                                                                                                                                                                                                                                                                                                                                                                             |
| Queue                                        | When the reviewer acts                                                                                               | fieldName / checkId                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Filing - accounting, signer, and core values | Enter only rows still MISSING                                                                                        | isFinalFiling, dateSigned, totAssets, totLiabs, netAssets, assetsAttrMiscSec, assetsInvested, amtPayOneYrBanksBorr, amtPayOneYrCtrlComp, amtPayOneYrOthAffil, amtPayOneYrOther, amtPayAftOneYrBanksBorr, amtPayAftOneYrCtrlComp, amtPayAftOneYrOthAffil, amtPayAftOneYrOther, delayDeliv, standByCommit, liquidPref, isNonCashCollateral, netRealizedGainMon1, netUnrealizedApprMon1, netRealizedGainMon2, netUnrealizedApprMon2, netRealizedGainMon3, netUnrealizedApprMon3, nameDesignatedIndex, indexIdentifier |
| Filing - monthly returns                     | Bloomberg normally populates these; enter only if still MISSING and another independent source supports them         | rtn1, rtn2, rtn3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Queue                                        | When the reviewer acts                                                                                               | fieldName / checkId                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Filing - create/redeem flows                 | Orders may populate these; enter only the rows still MISSING                                                         | mon1Sales, mon1Redemption, mon1Reinvestment, mon2Sales, mon2Redemption, mon2Reinvestment, mon3Sales, mon3Redemption, mon3Reinvestment                                                                                                                                                                                                                                                                                                                                                                              |
| Filing - conditional risk sections           | Enter PROVIDED when applicable, or NOT_APPLICABLE with a factual comment when policy says the section does not apply | curMetricsJson, creditSprdRiskIgJson, creditSprdRiskNonigJson, cashNotReportedInCoRD, monthlyReturnCategoriesJson, derivExposurePct, derivCurrencyExposurePct, derivInterestRateExposurePct, derivDaysInExcess, medianDailyVarPct, medianVarRatioPct, backtestingExceptions                                                                                                                                                                                                                                        |
| Queue                                        | When the reviewer acts                                                                                               | fieldName / checkId                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

|                |                                                                                                                                                              |                                                                                                                                                                                                                                                                                       |
|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Holdings       | The exact queue is dynamic: every generated HoldingFields row whose status remains MISSING. fieldName and recordKey identify exactly what and which holding. | Possible fields are listed by condition in the runbook's exhaustive holding trace; no hidden holding inputs exist.                                                                                                                                                                    |
| Reconciliation | Every generated ReconciliationInputs check                                                                                                                   | POSITIONS_TO_GL, FLOW:mon1Sales, FLOW:mon1Redemption, FLOW:mon1Reinvestment, FLOW:mon2Sales, FLOW:mon2Redemption, FLOW:mon2Reinvestment, FLOW:mon3Sales, FLOW:mon3Redemption, FLOW:mon3Reinvestment, DERIVATIVE_MARKET_VALUE (when generated), DERIVATIVE_UNREALIZED (when generated) |

**Do not edit:** Summary, Bloomberg formulas, GapGuide, Reconciliation, gapId, targetFile, recordKey, fieldName, currentValue, actualBasis, SYSTEM\_DERIVED rows, or SYSTEM\_CONTROL rows.

**Permitted blanks:** policyEffectiveTo may stay blank for an open-ended policy; nameDesignatedIndex and indexIdentifier are required only for relative VaR; holding isin and ticker may remain blank when another permitted identifier path is valid.

## 6. Filing input workbook

| Sheet      | Key                                | What the human edits                                                                         | Result                                                                | Release rule                       |
|------------|------------------------------------|----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------|------------------------------------|
| Summary    | Fund + period                      | Nothing                                                                                      | Shows scope, stop rule, and next command                              | Read-only                          |
| Bloomberg  | targetFile + recordKey + fieldName | Nothing; formulas calculate in Excel                                                         | Supported returns and security/reference values                       | Blank/error results remain MISSING |
| GapGuide   | gapId                              | Nothing                                                                                      | Explains every tracked item, evidence template, and exact destination | Read-only                          |
| FundFields | targetFile + fieldName             | PROVIDED: proposedValue if needed + status. N/A: status + factual comment. sourceId optional | Config and filing-level XML values                                    | Candidate rows have status MISSING |

  

| Sheet                | Key                   | What the human edits                                                                                      | Result                                                              | Release rule                                   |
|----------------------|-----------------------|-----------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------|------------------------------------------------|
| HoldingFields        | recordKey + fieldName | PROVIDED: status + proposedValue only to supply/correct. N/A: status + factual comment. sourceId optional | Holding XML exceptions                                              | Only generated candidate rows                  |
| Sources              | sourceId              | Nothing required; optional trace only                                                                     | Diagnostic sidecar metadata                                         | Does not gate XML                              |
| ReconciliationInputs | checkId               | controlValue, tolerance, status, comment; sourceId optional                                               | Control side of position-to-GL, flows, and derivative checks        | Every generated difference is within tolerance |
| Reconciliation       | check                 | Nothing; correct upstream filed input or ReconciliationInputs                                             | Build-calculated actual, control, difference, tolerance, and result | Every automated check passes                   |

**The workbook does not make data true.** Enter only known values; never infer from comparison output. Source metadata is optional and does not validate a value.

**Fund-configuration safeguard:** for `targetFile=fund_config.txt`, enter `proposedValue`. The existing `currentValue` is reference-only and cannot be accepted by changing status alone.

## 7. Status rules

| Value          | Exact meaning                                                        | Required entry                                                           |
|----------------|----------------------------------------------------------------------|--------------------------------------------------------------------------|
| MISSING        | No usable value has been supplied.                                   | The row remains an open input when applicable.                           |
| PROVIDED       | A current or proposed value is ready for the build.                  | Resolved value and status. <code>sourceId</code> optional.               |
| NOT_APPLICABLE | A conditional field does not apply to this fund/holding.             | Status plus a factual reason in comment. <code>sourceId</code> optional. |
| Value          | Exact meaning                                                        | Required entry                                                           |
| SYSTEM_DERIVED | The system calculates the value from validated period/policy inputs. | No manual override.                                                      |
| SYSTEM_CONTROL | The system owns the release-state value.                             | No manual override.                                                      |

`sourceId`, `sourceAsOf`, hashes, and counts are optional diagnostic metadata. None appears in the XML.

## 8. Current input checklist and exact fix location

**Centralized remediation:** use only this fund-period's `filing_inputs.xlsx`. Enter XML values/dispositions in `FundFields` or `HoldingFields` and controls in `ReconciliationInputs`. Do not create gap-specific templates or complete Sources for release.

| ID / status                                   | What must be resolved                                                                                            | Single review destination                                           |
|-----------------------------------------------|------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------|
| <b>G-001</b><br><b>OPEN INPUT</b>             | <b>Position population</b><br>All Part C holdings                                                                | <code>filing_inputs.xlsx</code><br>CLI + <code>HoldingFields</code> |
| <b>G-002</b><br><b>OPEN INPUT</b>             | <b>Fund-accounting values</b><br>Assets, liabilities, net assets, balance-sheet items, gains, returns, and cash  | <code>filing_inputs.xlsx</code><br><code>FundFields</code>          |
| <b>G-003</b><br><b>PARTLY AUTOMATED INPUT</b> | <b>Create/redeem flows</b><br>Monthly sales, redemptions, and reinvestments                                      | <code>filing_inputs.xlsx</code><br>CLI + <code>FundFields</code>    |
| <b>G-004</b><br><b>OPEN INPUT</b>             | <b>Policy and static data</b><br>Fiscal year-end, derivatives regime, applicability, identity, and signer fields | <code>filing_inputs.xlsx</code><br><code>FundFields</code>          |
| ID / status                                   | What must be resolved                                                                                            | Single review destination                                           |



|                                               |                                                                                          |                                                  |
|-----------------------------------------------|------------------------------------------------------------------------------------------|--------------------------------------------------|
| <b>G-005</b><br><b>OPTIONAL</b>               | <b>Source manifest</b><br>Diagnostic provenance only; no XML element                     | filing_inputs.xlsx<br>Sources                    |
| <b>G-006</b><br><b>INPUT BOUNDARY</b>         | <b>Prohibited comparison inputs</b><br>U.S. Bank, EagleSTAR, and prepared filing outputs | filing_inputs.xlsx<br>CLI + optional Sources     |
| <b>G-007</b><br><b>OPTIONAL</b>               | <b>Manual provenance</b><br>sourceId and provenance sidecars; no XML element             | filing_inputs.xlsx<br>FundFields + HoldingFields |
| <b>G-008</b><br><b>CONDITIONAL OPEN INPUT</b> | <b>Swap economics</b><br>Counterparty, LEI, notional, value, termination, and leg terms  | filing_inputs.xlsx<br>HoldingFields              |

| ID / status                                   | What must be resolved                                                                                                       | Single review destination                  |
|-----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|
| <b>G-009</b><br><b>CONDITIONAL OPEN INPUT</b> | <b>B.2.f / B.3 / B.5.c / B.9 / B.10</b><br>Cash outside C/D, risk metrics, monthly categories, derivatives exposure, or VaR | filing_inputs.xlsx<br>FundFields           |
| <b>G-010</b><br><b>CONDITIONAL OPEN INPUT</b> | <b>C.7 liquidity</b><br>Liquidity classification/circumstances by holding                                                   | filing_inputs.xlsx<br>HoldingFields        |
| <b>G-011</b><br><b>CONDITIONAL OPEN INPUT</b> | <b>Option terms and delta</b><br>Delta, exercise terms, expiry, and reference identity                                      | filing_inputs.xlsx<br>HoldingFields        |
| <b>G-012</b><br><b>ACCURACY GATE</b>          | <b>Reconciliation</b><br>Position-to-GL, monthly flows, derivative totals, and NAV equation                                 | filing_inputs.xlsx<br>ReconciliationInputs |

| ID / status                                | What must be resolved                                                                         | Single review destination |
|--------------------------------------------|-----------------------------------------------------------------------------------------------|---------------------------|
| <b>G-013</b><br><b>OUT OF ACTIVE SCOPE</b> | <b>Origin assurance</b><br>Source metadata cannot authenticate origin and does not affect XML | No workbook entry         |

## Exact fix location and proof

| ID           | Sheet / entry point | Exact action                                                                                                | Owner                               | Completion test                                                   |
|--------------|---------------------|-------------------------------------------------------------------------------------------------------------|-------------------------------------|-------------------------------------------------------------------|
| <b>G-001</b> | CLI + HoldingFields | prepare <fund><br><period> --positions<br><independent.csv>;<br>then resolve MISSING<br>HoldingFields rows. | <b>Operations</b>                   | The file loads and every required holding value validates         |
| <b>G-002</b> | FundFields          | Filter gapId G-002; enter proposedValue and status. Use a factual comment for NOT_APPLICABLE.               | <b>Fund Accounting</b>              | Every applicable XML value is present and the NAV equation passes |
| <b>G-003</b> | CLI + FundFields    | Pass --orders to prepare; enter only unresolved G-003 proposedValue/status rows.                            | <b>Capital Markets + Accounting</b> | Every applicable flow value is present and reconciles             |
| ID           | Sheet / entry point | Exact action                                                                                                | Owner                               | Completion test                                                   |

| <b>G-004</b> | FundFields                 | For targetFile=fund_config.txt enter proposedValue/status; policyEffectiveTo may be blank if open-ended.          | <b>Compliance / Legal</b>       | Every XML-impacting policy/static value validates                       |
|--------------|----------------------------|-------------------------------------------------------------------------------------------------------------------|---------------------------------|-------------------------------------------------------------------------|
| <b>G-005</b> | Sources                    | No reviewer entry is required for XML release.                                                                    | <b>None</b>                     | Never blocks XML generation                                             |
| <b>G-006</b> | CLI + optional Sources     | Remove any prohibited supplied path/reference. Never copy comparison values into the workbook.                    | <b>Engineering + Operations</b> | No prohibited comparison output is used as an input                     |
| <b>ID</b>    | <b>Sheet / entry point</b> | <b>Exact action</b>                                                                                               | <b>Owner</b>                    | <b>Completion test</b>                                                  |
| <b>G-007</b> | FundFields + HoldingFields | No sourceId is required. For NOT_APPLICABLE, enter only a factual comment plus status.                            | <b>None</b>                     | Never blocks XML generation                                             |
| <b>G-008</b> | HoldingFields              | Filter gapId G-008 and enter proposedValue/status for each named recordKey.                                       | <b>Derivatives Operations</b>   | All required swap XML fields validate and valuation reconciles          |
| <b>G-009</b> | FundFields                 | Filter gapId G-009; enter proposedValue/status or factual NOT_APPLICABLE comment.                                 | <b>Accounting + Risk</b>        | Policy determines applicability; every applicable XML section validates |
| <b>ID</b>    | <b>Sheet / entry point</b> | <b>Exact action</b>                                                                                               | <b>Owner</b>                    | <b>Completion test</b>                                                  |
| <b>G-010</b> | HoldingFields              | Filter gapId G-010 and enter proposedValue/status for each named recordKey.                                       | <b>Liquidity Risk</b>           | Every applicable holding has valid C.7 XML content                      |
| <b>G-011</b> | HoldingFields              | Filter gapId G-011 and enter proposedValue/status for each named recordKey.                                       | <b>Derivatives Risk</b>         | Every required option XML field validates                               |
| <b>G-012</b> | ReconciliationInputs       | Enter controlValue, tolerance, status, and comment. sourceId is optional. Build calculates actual and difference. | <b>Accounting + Operations</b>  | Every calculated difference is within tolerance                         |
| <b>ID</b>    | <b>Sheet / entry point</b> | <b>Exact action</b>                                                                                               | <b>Owner</b>                    | <b>Completion test</b>                                                  |
| <b>G-013</b> | No workbook entry          | No action in this workflow.                                                                                       | <b>None</b>                     | Does not gate XML generation                                            |

## 9. How to read the field trace

---

**Actual lineage is not authorization.** The second column states what the current/legacy code really used, including Bloomberg formulas, U.S. Bank custody, EagleSTAR, seeded review workbooks, constants, and no-feed fields. Those legacy writers are disabled or prohibited for the new production build. The fourth column is the only production workflow.

The trace is generated from the canonical config, filing, and holding field maps. Generation stops if field counts change or the verified lineage anchors no longer resolve.

Verification performed: 72 rows: code anchor located for each; Bloomberg claims checked against BLOOMBERG\_SPECS (10 cols) + risk sheet (4 cols); EagleSTAR claims checked against 17 writer keys; Human-review claims checked against 15 review value columns; Custodian claims checked against 67 transform-assigned keys; filing\_master HEADER: 55 columns, 0 unmapped; Exhaustive canonical trace: 170 fields (30 config, 56 filing, 84 holding).

## 10. Exhaustive field trace - fund configuration

All 30 accepted fund-configuration fields are listed. `requiredSources`, `policySourceRef`, `policyApprovedBy`, and `policyApprovedAt` are compatibility/provenance keys: they are not requested by the workbook and do not affect XML.

| Canonical field            | Actual current/legacy origin                                         | Transform and live code location                                                                          | New independent workflow                                                                                                                                                                                                                         |
|----------------------------|----------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>cik</code>           | <code>fund_config.txt</code> (current static value)                  | Direct mapping; stable-identity reconciliation<br><code>src/nport/config.py:241</code>                    | FundFields:<br><code>targetFile=fund_config.txt</code> ,<br><code>recordKey=FUND</code> ,<br><code>fieldName=cik</code> . Enter<br><code>proposedValue</code> and<br><code>status=PROVIDED</code> ; <code>sourceId</code> is optional.           |
| <code>ccc</code>           | <code>fund_config.txt</code> (current);<br>EDGAR filer administrator | Injected only at execution; never<br>copied from comparison files<br><code>src/nport/config.py:241</code> | FundFields:<br><code>targetFile=fund_config.txt</code> ,<br><code>recordKey=FUND</code> ,<br><code>fieldName=ccc</code> . Enter<br><code>proposedValue</code> and<br><code>status=PROVIDED</code> ; <code>sourceId</code> is optional.           |
| <code>regName</code>       | <code>fund_config.txt</code> (current static value)                  | Direct mapping; stable-identity reconciliation<br><code>src/nport/config.py:241</code>                    | FundFields:<br><code>targetFile=fund_config.txt</code> ,<br><code>recordKey=FUND</code> ,<br><code>fieldName=regName</code> . Enter<br><code>proposedValue</code> and<br><code>status=PROVIDED</code> ; <code>sourceId</code> is optional.       |
| <code>regFileNumber</code> | <code>fund_config.txt</code> (current static value)                  | Direct mapping; stable-identity reconciliation<br><code>src/nport/config.py:241</code>                    | FundFields:<br><code>targetFile=fund_config.txt</code> ,<br><code>recordKey=FUND</code> ,<br><code>fieldName=regFileNumber</code> .<br>Enter <code>proposedValue</code> and<br><code>status=PROVIDED</code> ; <code>sourceId</code> is optional. |

### Fund configuration (continued)

| Canonical field     | Actual current/legacy origin                        | Transform and live code location                                                       | New independent workflow                                                                                                                                                                                                                  |
|---------------------|-----------------------------------------------------|----------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>regCik</code> | <code>fund_config.txt</code> (current static value) | Direct mapping; stable-identity reconciliation<br><code>src/nport/config.py:241</code> | FundFields:<br><code>targetFile=fund_config.txt</code> ,<br><code>recordKey=FUND</code> ,<br><code>fieldName=regCik</code> . Enter<br><code>proposedValue</code> and<br><code>status=PROVIDED</code> ; <code>sourceId</code> is optional. |
| <code>regLei</code> | <code>fund_config.txt</code> (current static value) | Direct mapping; stable-identity reconciliation<br><code>src/nport/config.py:241</code> | FundFields:<br><code>targetFile=fund_config.txt</code> ,<br><code>recordKey=FUND</code> ,<br><code>fieldName=regLei</code> . Enter<br><code>proposedValue</code> and<br><code>status=PROVIDED</code> ; <code>sourceId</code> is optional. |

|            |                                        |                                                                                        |                                                                                                                                                                |
|------------|----------------------------------------|----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| regStreet1 | fund_config.txt (current static value) | Direct mapping; stable-identity reconciliation<br><code>src/nport/config.py:241</code> | FundFields:<br>targetFile=fund_config.txt,<br>recordKey=FUND,<br>fieldName=regStreet1. Enter<br>proposedValue and<br>status=PROVIDED; sourceId is<br>optional. |
| regStreet2 | fund_config.txt (current static value) | Direct mapping; stable-identity reconciliation<br><code>src/nport/config.py:241</code> | FundFields:<br>targetFile=fund_config.txt,<br>recordKey=FUND,<br>fieldName=regStreet2. Enter<br>proposedValue and<br>status=PROVIDED; sourceId is<br>optional. |

### Fund configuration (continued)

| Canonical field    | Actual current/legacy origin           | Transform and live code location                                                       | New independent workflow                                                                                                                                               |
|--------------------|----------------------------------------|----------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| regCity            | fund_config.txt (current static value) | Direct mapping; stable-identity reconciliation<br><code>src/nport/config.py:241</code> | FundFields:<br>targetFile=fund_config.txt,<br>recordKey=FUND,<br>fieldName=regCity. Enter<br>proposedValue and<br>status=PROVIDED; sourceId is<br>optional.            |
| regState           | fund_config.txt (current static value) | Direct mapping; stable-identity reconciliation<br><code>src/nport/config.py:241</code> | FundFields:<br>targetFile=fund_config.txt,<br>recordKey=FUND,<br>fieldName=regState. Enter<br>proposedValue and<br>status=PROVIDED; sourceId is<br>optional.           |
| regCountry         | fund_config.txt (current static value) | Direct mapping; stable-identity reconciliation<br><code>src/nport/config.py:241</code> | FundFields:<br>targetFile=fund_config.txt,<br>recordKey=FUND,<br>fieldName=regCountry. Enter<br>proposedValue and<br>status=PROVIDED; sourceId is<br>optional.         |
| regZipOrPostalCode | fund_config.txt (current static value) | Direct mapping; stable-identity reconciliation<br><code>src/nport/config.py:241</code> | FundFields:<br>targetFile=fund_config.txt,<br>recordKey=FUND,<br>fieldName=regZipOrPostalCode.<br>Enter proposedValue and<br>status=PROVIDED; sourceId is<br>optional. |

### Fund configuration (continued)

| Canonical field | Actual current/legacy origin           | Transform and live code location                                                       | New independent workflow                                                                                                                                     |
|-----------------|----------------------------------------|----------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| regPhone        | fund_config.txt (current static value) | Direct mapping; stable-identity reconciliation<br><code>src/nport/config.py:241</code> | FundFields:<br>targetFile=fund_config.txt,<br>recordKey=FUND,<br>fieldName=regPhone. Enter<br>proposedValue and<br>status=PROVIDED; sourceId is<br>optional. |

|            |                                        |                                                                                      |                                                                                                                                                                |
|------------|----------------------------------------|--------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| seriesName | fund_config.txt (current static value) | Direct identifier mapping; stable-identity reconciliation<br>src/nport/config.py:241 | FundFields:<br>targetFile=fund_config.txt,<br>recordKey=FUND,<br>fieldName=seriesName. Enter<br>proposedValue and<br>status=PROVIDED; sourceId is<br>optional. |
| seriesId   | fund_config.txt (current static value) | Direct identifier mapping; stable-identity reconciliation<br>src/nport/config.py:241 | FundFields:<br>targetFile=fund_config.txt,<br>recordKey=FUND,<br>fieldName=seriesId. Enter<br>proposedValue and<br>status=PROVIDED; sourceId is<br>optional.   |
| seriesLei  | fund_config.txt (current static value) | Direct identifier mapping; stable-identity reconciliation<br>src/nport/config.py:241 | FundFields:<br>targetFile=fund_config.txt,<br>recordKey=FUND,<br>fieldName=seriesLei. Enter<br>proposedValue and<br>status=PROVIDED; sourceId is<br>optional.  |

#### Fund configuration (continued)

| Canonical field | Actual current/legacy origin           | Transform and live code location                                                     | New independent workflow                                                                                                                                        |
|-----------------|----------------------------------------|--------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| classId         | fund_config.txt (current static value) | Direct identifier mapping; stable-identity reconciliation<br>src/nport/config.py:241 | FundFields:<br>targetFile=fund_config.txt,<br>recordKey=FUND,<br>fieldName=classId. Enter<br>proposedValue and<br>status=PROVIDED; sourceId is<br>optional.     |
| signerOrg       | fund_config.txt (current static value) | Direct mapping; evidence retained with filing approval<br>src/nport/config.py:241    | FundFields:<br>targetFile=fund_config.txt,<br>recordKey=FUND,<br>fieldName=signerOrg. Enter<br>proposedValue and<br>status=PROVIDED; sourceId is<br>optional.   |
| signerName      | fund_config.txt (current static value) | Direct mapping; evidence retained with filing approval<br>src/nport/config.py:241    | FundFields:<br>targetFile=fund_config.txt,<br>recordKey=FUND,<br>fieldName=signerName. Enter<br>proposedValue and<br>status=PROVIDED; sourceId is<br>optional.  |
| signerTitle     | fund_config.txt (current static value) | Direct mapping; evidence retained with filing approval<br>src/nport/config.py:241    | FundFields:<br>targetFile=fund_config.txt,<br>recordKey=FUND,<br>fieldName=signerTitle. Enter<br>proposedValue and<br>status=PROVIDED; sourceId is<br>optional. |

#### Fund configuration (continued)

| Canonical field | Actual current/legacy origin | Transform and live code location | New independent workflow |
|-----------------|------------------------------|----------------------------------|--------------------------|
|-----------------|------------------------------|----------------------------------|--------------------------|

|                         |                                        |                                                                           |                                                                                                                                                                           |
|-------------------------|----------------------------------------|---------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fiscalYearEndMMDD       | fund_config.txt (current static value) | Direct mapping; stable-identity reconciliation<br>src/nport/config.py:241 | FundFields:<br>targetFile=fund_config.txt,<br>recordKey=FUND,<br>fieldName=fiscalYearEndMMDD.<br>Enter proposedValue and<br>status=PROVIDED; sourceId is<br>optional.     |
| derivativesRegimePolicy | fund_config.txt (current static value) | Direct mapping; stable-identity reconciliation<br>src/nport/config.py:241 | FundFields:<br>targetFile=fund_config.txt,<br>recordKey=FUND,<br>fieldName=derivativesRegimePolic<br>Enter proposedValue and<br>status=PROVIDED; sourceId is<br>optional. |
| liquidityRequired       | fund_config.txt (current static value) | Direct mapping; stable-identity reconciliation<br>src/nport/config.py:241 | FundFields:<br>targetFile=fund_config.txt,<br>recordKey=FUND,<br>fieldName=liquidityRequired.<br>Enter proposedValue and<br>status=PROVIDED; sourceId is<br>optional.     |
| cashB2fRequired         | fund_config.txt (current static value) | Direct mapping; stable-identity reconciliation<br>src/nport/config.py:241 | FundFields:<br>targetFile=fund_config.txt,<br>recordKey=FUND,<br>fieldName=cashB2fRequired.<br>Enter proposedValue and<br>status=PROVIDED; sourceId is<br>optional.       |

#### Fund configuration (continued)

| Canonical field     | Actual current/legacy origin           | Transform and live code location                                          | New independent workflow                                                                                                                                                |
|---------------------|----------------------------------------|---------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| policyEffectiveFrom | fund_config.txt (current static value) | Direct mapping; stable-identity reconciliation<br>src/nport/config.py:241 | FundFields:<br>targetFile=fund_config.txt,<br>recordKey=FUND,<br>fieldName=policyEffectiveFrom.<br>Enter proposedValue and<br>status=PROVIDED; sourceId is<br>optional. |
| policyEffectiveTo   | fund_config.txt (current static value) | Direct mapping; stable-identity reconciliation<br>src/nport/config.py:241 | FundFields:<br>targetFile=fund_config.txt,<br>recordKey=FUND,<br>fieldName=policyEffectiveTo.<br>Enter proposedValue and<br>status=PROVIDED; sourceId is<br>optional.   |
| policyApprovedBy    | fund_config.txt (current static value) | Direct mapping; stable-identity reconciliation<br>src/nport/config.py:241 | Compatibility/provenance key; it<br>is not requested and does not<br>affect XML.                                                                                        |
| policyApprovedAt    | fund_config.txt (current static value) | Direct mapping; stable-identity reconciliation<br>src/nport/config.py:241 | Compatibility/provenance key; it<br>is not requested and does not<br>affect XML.                                                                                        |

#### Fund configuration (continued)

| Canonical field | Actual current/legacy origin           | Transform and live code location                                          | New independent workflow                                                         |
|-----------------|----------------------------------------|---------------------------------------------------------------------------|----------------------------------------------------------------------------------|
| policySourceRef | fund_config.txt (current static value) | Direct mapping; stable-identity reconciliation<br>src/nport/config.py:241 | Compatibility/provenance key; it<br>is not requested and does not<br>affect XML. |

|                 |                                        |                                                                           |                                                                            |
|-----------------|----------------------------------------|---------------------------------------------------------------------------|----------------------------------------------------------------------------|
| requiredSources | fund_config.txt (current static value) | Direct mapping; stable-identity reconciliation<br>src/nport/config.py:241 | Optional provenance metadata; it is not requested and does not affect XML. |
|-----------------|----------------------------------------|---------------------------------------------------------------------------|----------------------------------------------------------------------------|

---



## 11. Exhaustive field trace - filing-level data

All 56 accepted filing-level fields are listed. A legacy constant is reported as a constant; it is not silently reclassified as sourced data.

| Canonical field | Actual current/legacy origin                                      | Transform and live code location                                                                                                 | New independent workflow                                                       |
|-----------------|-------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|
| submissionType  | Tool-derived filing period/default; future approved fund registry | filing_master.py derives the period; policy.py overrides from an approved registry when present<br>src/nport/filing_master.py:66 | SYSTEM_DERIVED after the period and supplied fund-policy rows pass validation. |
| liveTestFlag    | Filing Operations and authorized signer workflow                  | Operator-controlled status/date with release gate<br>src/nport/cli.py:1198                                                       | SYSTEM_CONTROL; remains TEST until all release controls pass.                  |
| repPdEnd        | Tool-derived filing period/default; future approved fund registry | filing_master.py derives the period; policy.py overrides from an approved registry when present<br>src/nport/custodian.py:808    | SYSTEM_DERIVED after the period and supplied fund-policy rows pass validation. |
| repPdDate       | Tool-derived filing period/default; future approved fund registry | filing_master.py derives the period; policy.py overrides from an approved registry when present<br>src/nport/custodian.py:808    | SYSTEM_DERIVED after the period and supplied fund-policy rows pass validation. |

### Filing-level data (continued)

| Canonical field | Actual current/legacy origin                                         | Transform and live code location                                                               | New independent workflow                                                                                                                                                |
|-----------------|----------------------------------------------------------------------|------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| isFinalFiling   | Filing Operations and authorized signer workflow                     | Operator-controlled status/date with release gate<br>src/nport/filing_master.py:66             | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=isFinalFiling. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional. |
| dateSigned      | Filing Operations and authorized signer workflow                     | Operator-controlled status/date with release gate<br>src/nport/filing_master.py:118            | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=dateSigned. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.    |
| totAssets       | Gmail export - U.S. Bank EagleSTAR Trial Balance; custodian fallback | eaglestar.py overrides filing_master.py custody-derived fallback<br>src/nport/eaglestar.py:310 | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=totAssets. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.     |

|          |                                                                      |                                                                                                   |                                                                                                                                                                    |
|----------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| totLiabs | Gmail export - U.S. Bank EagleSTAR Trial Balance; custodian fallback | eaglestar.py overrides<br>filing_master.py custody-derived fallback<br>src/nport/eaglestar.py:312 | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=totLiabs. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional. |
|----------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|

#### Filing-level data (continued)

| Canonical field      | Actual current/legacy origin                                                        | Transform and live code location                                                                                           | New independent workflow                                                                                                                                                     |
|----------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| netAssets            | Gmail export - U.S. Bank EagleSTAR Trial Balance; custodian fallback                | eaglestar.py overrides<br>filing_master.py custody-derived fallback<br>src/nport/eaglestar.py:314                          | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=netAssets. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.          |
| assetsAttrMiscSec    | Gmail export - U.S. Bank EagleSTAR Trial Balance; custodian fallback                | eaglestar.py overrides<br>filing_master.py custody-derived fallback<br>src/nport/eaglestar.py:206                          | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=assetsAttrMiscSec. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.  |
| assetsInvested       | Gmail export - U.S. Bank EagleSTAR Trial Balance; custodian fallback                | eaglestar.py overrides<br>filing_master.py custody-derived fallback<br>src/nport/eaglestar.py:206                          | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=assetsInvested. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.     |
| amtPayOneYrBanksBorr | Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified | eaglestar.py writes mapped accounting values;<br>filing_master.py supplies explicit defaults<br>src/nport/eaglestar.py:206 | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=amtPayOneYrBanksBc. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional. |

#### Filing-level data (continued)

| Canonical field       | Actual current/legacy origin                                                        | Transform and live code location                                                                                           | New independent workflow                                                                                                                                                       |
|-----------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| amtPayOneYrCtrlldComp | Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified | eaglestar.py writes mapped accounting values;<br>filing_master.py supplies explicit defaults<br>src/nport/eaglestar.py:206 | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=amtPayOneYrCtrlldCon. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional. |

|                         |                                                                                     |                                                                                                                         |                                                                                                                                                                             |
|-------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| amtPayOneYrOthAffil     | Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified | eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults<br>src/nport/eaglestar.py:206 | FundFields:<br>targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayOneYrOthAffil. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.     |
| amtPayOneYrOther        | Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified | eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults<br>src/nport/eaglestar.py:307 | FundFields:<br>targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayOneYrOther. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.        |
| amtPayAftOneYrBanksBorr | Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified | eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults<br>src/nport/eaglestar.py:206 | FundFields:<br>targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayAftOneYrBanksBorr. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional. |

#### Filing-level data (continued)

| Canonical field          | Actual current/legacy origin                                                        | Transform and live code location                                                                                        | New independent workflow                                                                                                                                                     |
|--------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| amtPayAftOneYrCtrlldComp | Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified | eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults<br>src/nport/eaglestar.py:206 | FundFields:<br>targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayAftOneYrCtrlldComp. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional. |
| amtPayAftOneYrOthAffil   | Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified | eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults<br>src/nport/eaglestar.py:206 | FundFields:<br>targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayAftOneYrOthAffil. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.   |
| amtPayAftOneYrOther      | Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified | eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults<br>src/nport/eaglestar.py:206 | FundFields:<br>targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayAftOneYrOther. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.      |
| delayDeliv               | Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified | eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults<br>src/nport/eaglestar.py:206 | FundFields:<br>targetFile=filing_data.txt, recordKey=FUND, fieldName=delayDeliv. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.               |

#### Filing-level data (continued)

| Canonical field     | Actual current/legacy origin                                                        | Transform and live code location                                                                                           | New independent workflow                                                                                                                                                      |
|---------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| standByCommit       | Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified | eaglestar.py writes mapped accounting values;<br>filing_master.py supplies explicit defaults<br>src/nport/eaglestar.py:206 | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=standByCommit. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.       |
| liquidPref          | Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified | eaglestar.py writes mapped accounting values;<br>filing_master.py supplies explicit defaults<br>src/nport/eaglestar.py:206 | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=liquidPref. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.          |
| isNonCashCollateral | Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified | eaglestar.py writes mapped accounting values;<br>filing_master.py supplies explicit defaults<br>src/nport/eaglestar.py:206 | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=isNonCashCollateral. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional. |
| rtn1                | Bloomberg formula in filing_master.xlsx                                             | BDP custom total-return formula for each reporting month<br>src/nport/<br>filing_master.py:48                              | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=rtn1. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.                |

#### Filing-level data (continued)

| Canonical field     | Actual current/legacy origin                                                        | Transform and live code location                                                                                           | New independent workflow                                                                                                                                                      |
|---------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| rtn2                | Bloomberg formula in filing_master.xlsx                                             | BDP custom total-return formula for each reporting month<br>src/nport/<br>filing_master.py:48                              | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=rtn2. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.                |
| rtn3                | Bloomberg formula in filing_master.xlsx                                             | BDP custom total-return formula for each reporting month<br>src/nport/<br>filing_master.py:48                              | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=rtn3. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.                |
| netRealizedGainMon1 | Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified | eaglestar.py writes mapped accounting values;<br>filing_master.py supplies explicit defaults<br>src/nport/eaglestar.py:206 | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=netRealizedGainMon1. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional. |

|                       |                                                                                     |                                                                                                                         |                                                                                                                                                                                  |
|-----------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| netUnrealizedApprMon1 | Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified | eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults<br>src/nport/eaglestar.py:206 | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=netUnrealizedApprMon<br>Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional. |
|-----------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

#### Filing-level data (continued)

| Canonical field       | Actual current/legacy origin                                                        | Transform and live code location                                                                                        | New independent workflow                                                                                                                                                         |
|-----------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| netRealizedGainMon2   | Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified | eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults<br>src/nport/eaglestar.py:206 | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=netRealizedGainMon2.<br>Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional. |
| netUnrealizedApprMon2 | Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified | eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults<br>src/nport/eaglestar.py:206 | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=netUnrealizedApprMon<br>Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional. |
| netRealizedGainMon3   | Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified | eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults<br>src/nport/eaglestar.py:206 | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=netRealizedGainMon3.<br>Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional. |
| netUnrealizedApprMon3 | Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified | eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults<br>src/nport/eaglestar.py:206 | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=netUnrealizedApprMon<br>Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional. |

#### Filing-level data (continued)

| Canonical field | Actual current/legacy origin           | Transform and live code location                                                                                               | New independent workflow                                                                                                                                            |
|-----------------|----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| mon1Sales       | Gmail export - EagleSTAR Trial Balance | eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only<br>src/nport/eaglestar.py:206 | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=mon1Sales. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional. |

|                  |                                                |                                                                                                                                |                                                                                                                                                                               |
|------------------|------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| mon1Redemption   | Gmail export - EagleSTAR Trial Balance         | eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only<br>src/nport/eaglestar.py:206 | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=mon1Redemption.<br>Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.   |
| mon1Reinvestment | No current feed; filing_master.py supplies N/A | Create/redeem orders do not contain reinvested distributions<br>src/nport/models.py:84                                         | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=mon1Reinvestment.<br>Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional. |
| mon2Sales        | Gmail export - EagleSTAR Trial Balance         | eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only<br>src/nport/eaglestar.py:206 | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=mon2Sales. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.           |

#### Filing-level data (continued)

| Canonical field  | Actual current/legacy origin                   | Transform and live code location                                                                                               | New independent workflow                                                                                                                                                      |
|------------------|------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| mon2Redemption   | Gmail export - EagleSTAR Trial Balance         | eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only<br>src/nport/eaglestar.py:206 | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=mon2Redemption.<br>Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.   |
| mon2Reinvestment | No current feed; filing_master.py supplies N/A | Create/redeem orders do not contain reinvested distributions<br>src/nport/models.py:87                                         | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=mon2Reinvestment.<br>Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional. |
| mon3Sales        | Gmail export - EagleSTAR Trial Balance         | eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only<br>src/nport/eaglestar.py:206 | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=mon3Sales. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.           |
| mon3Redemption   | Gmail export - EagleSTAR Trial Balance         | eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only<br>src/nport/eaglestar.py:206 | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=mon3Redemption.<br>Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.   |

#### Filing-level data (continued)

| Canonical field     | Actual current/legacy origin                                          | Transform and live code location                                                                                         | New independent workflow                                                                                                                                                                  |
|---------------------|-----------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| mon3Reinvestment    | No current feed; filing_master.py supplies N/A                        | Create/redeem orders do not contain reinvested distributions<br>src/nport/models.py:90                                   | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=mon3Reinvestment.<br>Use PROVIDED, or<br>NOT_APPLICABLE with a<br>factual comment; sourceId is<br>optional.    |
| nameDesignatedIndex | Human-review workbook<br>designated_index sheet (legacy<br>497K seed) | humanreview.py seed values<br>merge through filing_master.py<br>src/nport/<br>master_sheet.py:748                        | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=nameDesignatedIndex.<br>Use PROVIDED, or<br>NOT_APPLICABLE with a<br>factual comment; sourceId is<br>optional. |
| indexIdentifier     | Human-review workbook<br>designated_index sheet (legacy<br>497K seed) | humanreview.py seed values<br>merge through filing_master.py<br>src/nport/<br>master_sheet.py:748                        | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=indexIdentifier. Use<br>PROVIDED, or<br>NOT_APPLICABLE with a<br>factual comment; sourceId is<br>optional.     |
| curMetricsJson      | Bloomberg formulas plus U.S.<br>Bank custodian market value           | filing_master.py aggregates<br>duration/rating fields after<br>workbook calculation<br>src/nport/<br>filing_master.py:40 | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=curMetricsJson. Use<br>PROVIDED, or<br>NOT_APPLICABLE with a<br>factual comment; sourceId is<br>optional.      |

#### Filing-level data (continued)

| Canonical field         | Actual current/legacy origin                                | Transform and live code location                                                                                         | New independent workflow                                                                                                                                                                   |
|-------------------------|-------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| creditSprdRiskIgJson    | Bloomberg formulas plus U.S.<br>Bank custodian market value | filing_master.py aggregates<br>duration/rating fields after<br>workbook calculation<br>src/nport/<br>filing_master.py:40 | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=creditSprdRiskIgJson.<br>Use PROVIDED, or<br>NOT_APPLICABLE with a<br>factual comment; sourceId is<br>optional. |
| creditSprdRiskNonigJson | Bloomberg formulas plus U.S.<br>Bank custodian market value | filing_master.py aggregates<br>duration/rating fields after<br>workbook calculation<br>src/nport/<br>filing_master.py:40 | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=creditSprdRiskNonigJs<br>Use PROVIDED, or<br>NOT_APPLICABLE with a<br>factual comment; sourceId is<br>optional. |
| cashNotReportedInCoRD   | No current feed                                             | Typed field exists; no Gmail,<br>custodian, create/redeem, or<br>Bloomberg writer<br>src/nport/models.py:100             | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=cashNotReportedInCO<br>Use PROVIDED, or<br>NOT_APPLICABLE with a<br>factual comment; sourceId is<br>optional.   |

|                             |                 |                                                                                                                     |                                                                                                                                                                                              |
|-----------------------------|-----------------|---------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| monthlyReturnCategoriesJson | No current feed | Typed field exists; no Gmail, custodian, create/redeem, or Bloomberg writer<br><code>src/nport/models.py:101</code> | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=monthlyReturnCategories<br>Use PROVIDED, or<br>NOT_APPLICABLE with a<br>factual comment; sourceId is<br>optional. |
|-----------------------------|-----------------|---------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

#### Filing-level data (continued)

| Canonical field              | Actual current/legacy origin                               | Transform and live code location                                                                                      | New independent workflow                                                                                                                                                                           |
|------------------------------|------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| derivativesRegime            | No current populated source; future approved fund registry | policy.py derives it only when the registry exists<br><code>src/nport/filing_master.py:321</code>                     | SYSTEM_DERIVED after the period and supplied fund-policy rows pass validation.                                                                                                                     |
| derivExposurePct             | No current feed                                            | B.9/B.10 typed fields and preflight gates exist, but no writer populates them<br><code>src/nport/models.py:103</code> | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=derivExposurePct.<br>Use PROVIDED, or<br>NOT_APPLICABLE with a<br>factual comment; sourceId is<br>optional.             |
| derivCurrencyExposurePct     | No current feed                                            | B.9/B.10 typed fields and preflight gates exist, but no writer populates them<br><code>src/nport/models.py:104</code> | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=derivCurrencyExposurePct.<br>Use PROVIDED, or<br>NOT_APPLICABLE with a<br>factual comment; sourceId is<br>optional.     |
| derivInterestRateExposurePct | No current feed                                            | B.9/B.10 typed fields and preflight gates exist, but no writer populates them<br><code>src/nport/models.py:105</code> | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=derivInterestRateExposurePct.<br>Use PROVIDED, or<br>NOT_APPLICABLE with a<br>factual comment; sourceId is<br>optional. |

#### Filing-level data (continued)

| Canonical field   | Actual current/legacy origin | Transform and live code location                                                                                      | New independent workflow                                                                                                                                                                |
|-------------------|------------------------------|-----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| derivDaysInExcess | No current feed              | B.9/B.10 typed fields and preflight gates exist, but no writer populates them<br><code>src/nport/models.py:106</code> | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=derivDaysInExcess.<br>Use PROVIDED, or<br>NOT_APPLICABLE with a<br>factual comment; sourceId is<br>optional. |
| medianDailyVarPct | No current feed              | B.9/B.10 typed fields and preflight gates exist, but no writer populates them<br><code>src/nport/models.py:107</code> | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=medianDailyVarPct.<br>Use PROVIDED, or<br>NOT_APPLICABLE with a<br>factual comment; sourceId is<br>optional. |



|                       |                 |                                                                                                                       |                                                                                                                                                                                    |
|-----------------------|-----------------|-----------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| medianVarRatioPct     | No current feed | B.9/B.10 typed fields and preflight gates exist, but no writer populates them<br><code>src/nport/models.py:108</code> | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=medianVarRatioPct.<br>Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.     |
| backtestingExceptions | No current feed | B.9/B.10 typed fields and preflight gates exist, but no writer populates them<br><code>src/nport/models.py:109</code> | FundFields:<br>targetFile=filing_data.txt,<br>recordKey=FUND,<br>fieldName=backtestingExceptions.<br>Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional. |

## 12. Exhaustive field trace - holdings

All 84 accepted holdings fields are listed and grouped by filing condition. Present base values remain tied to the independent POSITIONS source; missing required and exception-sensitive values are surfaced in HoldingFields.

### Base

| Canonical field | Actual current/legacy origin                                                                            | Transform and live code location                                                                                                                                                 | New independent workflow                                                                                                                          |
|-----------------|---------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| name            | U.S. Bank custodian CSV                                                                                 | The legacy custodian transform copies or parses the value from the custody row.<br><code>src/nport/custodian.py:107</code>                                                       | Base value is positions.csv column name. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=name. Requirement: always.   |
| lei             | Bloomberg workbook formula for conventional securities; explicit constants on some derivative/UST paths | BDP enrichment owns conventional-security values; custodian code sets N/A/US or the U.S. Treasury LEI on identified special paths.<br><code>src/nport/master_sheet.py:128</code> | Base value is positions.csv column lei. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=lei. Requirement: always.     |
| title           | U.S. Bank custodian CSV                                                                                 | The legacy custodian transform copies or parses the value from the custody row.<br><code>src/nport/custodian.py:107</code>                                                       | Base value is positions.csv column title. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=title. Requirement: always. |
| cusip           | U.S. Bank custodian CSV                                                                                 | The legacy custodian transform copies or parses the value from the custody row.<br><code>src/nport/custodian.py:107</code>                                                       | Base value is positions.csv column cusip. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=cusip. Requirement: always. |

### Base (continued)

| Canonical field | Actual current/legacy origin                                                                            | Transform and live code location                                                                                                                                                 | New independent workflow                                                                                                                              |
|-----------------|---------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| isin            | Bloomberg workbook formula for conventional securities; explicit constants on some derivative/UST paths | BDP enrichment owns conventional-security values; custodian code sets N/A/US or the U.S. Treasury LEI on identified special paths.<br><code>src/nport/master_sheet.py:128</code> | Base value is positions.csv column isin. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=isin. Requirement: never.        |
| ticker          | U.S. Bank custodian CSV                                                                                 | The legacy custodian transform copies or parses the value from the custody row.<br><code>src/nport/custodian.py:107</code>                                                       | Base value is positions.csv column ticker. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=ticker. Requirement: never.    |
| balance         | U.S. Bank custodian CSV                                                                                 | The legacy custodian transform copies or parses the value from the custody row.<br><code>src/nport/custodian.py:679</code>                                                       | Base value is positions.csv column balance. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=balance. Requirement: always. |

|       |                                                 |                                                                                                                      |                                                                                                                                                   |
|-------|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| units | Tool constant or classification in custodian.py | The legacy custodian transform assigns the value according to its holding-type branch.<br>src/nport/custodian.py:680 | Base value is positions.csv column units. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=units. Requirement: always. |
|-------|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|

## Base (continued)

| Canonical field | Actual current/legacy origin                                    | Transform and live code location                                                                                      | New independent workflow                                                                                                                                          |
|-----------------|-----------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| curCd           | Tool constant or classification in custodian.py                 | The legacy custodian transform assigns the value according to its holding-type branch.<br>src/nport/custodian.py:662  | Base value is positions.csv column curCd. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=curCd. Requirement: always.                 |
| valUSD          | U.S. Bank custodian CSV for non-swaps; EagleSTAR PVal for swaps | MarketValue is used for non-swaps; swap value is replaced with matched unrealized PVal.<br>src/nport/eaglestar.py:206 | Base value is positions.csv column valUSD. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=valUSD. Requirement: always.               |
| pctVal          | Derived from filed valUSD and filed netAssets                   | The legacy transform recalculates the percentage after accounting overrides.<br>src/nport/custodian.py:125            | Base value is positions.csv column pctVal. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pctVal. Requirement: always.               |
| payoffProfile   | U.S. Bank custodian CSV                                         | The legacy custodian transform copies or parses the value from the custody row.<br>src/nport/custodian.py:662         | Base value is positions.csv column payoffProfile. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=payoffProfile. Requirement: always. |

## Base (continued)

| Canonical field | Actual current/legacy origin                                                                            | Transform and live code location                                                                                                                                    | New independent workflow                                                                                                                                    |
|-----------------|---------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| assetCat        | Tool constant or classification in custodian.py                                                         | The legacy custodian transform assigns the value according to its holding-type branch.<br>src/nport/custodian.py:108                                                | Base value is positions.csv column assetCat. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=assetCat. Requirement: always.     |
| issuerCat       | Tool constant or classification in custodian.py                                                         | The legacy custodian transform assigns the value according to its holding-type branch.<br>src/nport/custodian.py:108                                                | Base value is positions.csv column issuerCat. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=issuerCat. Requirement: always.   |
| invCountry      | Bloomberg workbook formula for conventional securities; explicit constants on some derivative/UST paths | BDP enrichment owns conventional-security values; custodian code sets N/A/US or the U.S. Treasury LEI on identified special paths.<br>src/nport/master_sheet.py:157 | Base value is positions.csv column invCountry. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=invCountry. Requirement: always. |

|                 |                                                 |                                                                                                                      |                                                                                                                                                                       |
|-----------------|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| isRestrictedSec | Tool constant or classification in custodian.py | The legacy custodian transform assigns the value according to its holding-type branch.<br>src/nport/custodian.py:662 | Base value is positions.csv column isRestrictedSec. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=isRestrictedSec. Requirement: always. |
|-----------------|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Base (continued)

| Canonical field     | Actual current/legacy origin                    | Transform and live code location                                                                                     | New independent workflow                                                                                                                                                      |
|---------------------|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fairValLevel        | Tool constant or classification in custodian.py | The legacy custodian transform assigns the value according to its holding-type branch.<br>src/nport/custodian.py:662 | Base value is positions.csv column fairValLevel. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=fairValLevel. Requirement: always.               |
| isCashCollateral    | Tool constant or classification in custodian.py | The legacy custodian transform assigns the value according to its holding-type branch.<br>src/nport/custodian.py:662 | Base value is positions.csv column isCashCollateral. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=isCashCollateral. Requirement: always.       |
| isNonCashCollateral | Tool constant or classification in custodian.py | The legacy custodian transform assigns the value according to its holding-type branch.<br>src/nport/custodian.py:662 | Base value is positions.csv column isNonCashCollateral. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=isNonCashCollateral. Requirement: always. |
| isLoanByFund        | Tool constant or classification in custodian.py | The legacy custodian transform assigns the value according to its holding-type branch.<br>src/nport/custodian.py:662 | Base value is positions.csv column isLoanByFund. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=isLoanByFund. Requirement: always.               |

## Conditional

| Canonical field       | Actual current/legacy origin                                             | Transform and live code location                                                                                                                | New independent workflow                                                                                                                                                                                  |
|-----------------------|--------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| issuerConditionalDesc | Tool constant only on the legacy swap path; otherwise no verified writer | custodian.py sets N/A for swaps; other issuerCat=OTHER cases are not populated automatically.<br>src/nport/custodian.py:662                     | Base value is positions.csv column issuerConditionalDesc. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=issuerConditionalDesc. Requirement: conditional - issuerCat==OTHER. |
| assetConditionalDesc  | No verified automated writer in the legacy pipeline                      | The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it.<br>src/nport/models.py:137   | Base value is positions.csv column assetConditionalDesc. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=assetConditionalDesc. Requirement: conditional - assetCat==OTHER.    |
| otherDesc             | Tool-generated identifier only for legacy option/swap paths              | custodian.py writes USER DEFINED plus an internally constructed option/swap identifier; other paths remain blank.<br>src/nport/custodian.py:662 | Base value is positions.csv column otherDesc. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=otherDesc. Requirement: never.                                                  |

|            |                                                             |                                                                                                                                                 |                                                                                                                                                            |
|------------|-------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| otherValue | Tool-generated identifier only for legacy option/swap paths | custodian.py writes USER DEFINED plus an internally constructed option/swap identifier; other paths remain blank.<br>src/nport/custodian.py:662 | Base value is positions.csv column otherValue. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=otherValue. Requirement: never. |
|------------|-------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Conditional (continued)

| Canonical field | Actual current/legacy origin                        | Transform and live code location                                                                                                              | New independent workflow                                                                                                                                                            |
|-----------------|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| exchangeRt      | No verified automated writer in the legacy pipeline | The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it.<br>src/nport/models.py:140 | Base value is positions.csv column exchangeRt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=exchangeRt. Requirement: conditional - non-USD currency. |

## Debt

| Canonical field | Actual current/legacy origin                                                                   | Transform and live code location                                                                                                                             | New independent workflow                                                                                                                                                              |
|-----------------|------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| maturityDt      | Bloomberg workbook formula; U.S. Treasury name parser exists in the direct custodian transform | Corporate/debt master enrichment uses BDP; the alternate direct Treasury path parses coupon and maturity from SecurityName.<br>src/nport/master_sheet.py:101 | Base value is positions.csv column maturityDt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=maturityDt. Requirement: conditional - debt security.      |
| couponKind      | Bloomberg workbook formula; U.S. Treasury name parser exists in the direct custodian transform | Corporate/debt master enrichment uses BDP; the alternate direct Treasury path parses coupon and maturity from SecurityName.<br>src/nport/master_sheet.py:101 | Base value is positions.csv column couponKind. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=couponKind. Requirement: conditional - maturityDt set.     |
| annualizedRt    | Bloomberg workbook formula; U.S. Treasury name parser exists in the direct custodian transform | Corporate/debt master enrichment uses BDP; the alternate direct Treasury path parses coupon and maturity from SecurityName.<br>src/nport/master_sheet.py:101 | Base value is positions.csv column annualizedRt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=annualizedRt. Requirement: conditional - maturityDt set. |
| isDefault       | Tool constant or classification in custodian.py                                                | The legacy custodian transform assigns the value according to its holding-type branch.<br>src/nport/custodian.py:137                                         | Base value is positions.csv column isDefault. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=isDefault. Requirement: conditional - maturityDt set.       |

## Debt (continued)

| Canonical field      | Actual current/legacy origin                    | Transform and live code location                                                                                     | New independent workflow                                                                                                                                                                              |
|----------------------|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| areIntrstPmntsInArRs | Tool constant or classification in custodian.py | The legacy custodian transform assigns the value according to its holding-type branch.<br>src/nport/custodian.py:137 | Base value is positions.csv column areIntrstPmntsInArRs. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=areIntrstPmntsInArRs. Requirement: conditional - maturityDt set. |

|            |                                                 |                                                                                                                                   |                                                                                                                                                                                   |
|------------|-------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| isPaidKind | Tool constant or classification in custodian.py | The legacy custodian transform assigns the value according to its holding-type branch.<br><code>src/nport/custodian.py:137</code> | Base value is positions.csv column isPaidKind. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=isPaidKind. Requirement: conditional - maturityDt set. |
|------------|-------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Deriv Common

| Canonical field  | Actual current/legacy origin                                         | Transform and live code location                                                                                                                        | New independent workflow                                                                                                                                                                    |
|------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| derivCat         | Tool constant or classification in custodian.py                      | The legacy custodian transform assigns the value according to its holding-type branch.<br><code>src/nport/custodian.py:114</code>                       | Base value is positions.csv column derivCat. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=derivCat. Requirement: conditional - derivative holding.           |
| counterpartyName | Seeded human-review overlay for swaps; OCC tool constant for options | Swap values come from the legacy counterparty sheet; option values use the OCC constants in custodian.py.<br><code>src/nport/master_sheet.py:776</code> | Base value is positions.csv column counterpartyName. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=counterpartyName. Requirement: conditional - derivCat set. |
| counterpartyLei  | Seeded human-review overlay for swaps; OCC tool constant for options | Swap values come from the legacy counterparty sheet; option values use the OCC constants in custodian.py.<br><code>src/nport/master_sheet.py:776</code> | Base value is positions.csv column counterpartyLei. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=counterpartyLei. Requirement: conditional - derivCat set.   |
| unrealizedAppr   | Gmail export - U.S. Bank EagleSTAR PVal attachment                   | Matched by Primary Asset ID and written as the derivative unrealized amount.<br><code>src/nport/eaglestar.py:206</code>                                 | Base value is positions.csv column unrealizedAppr. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=unrealizedAppr. Requirement: conditional - derivCat set.     |

## Option

| Canonical field | Actual current/legacy origin | Transform and live code location                                                                                           | New independent workflow                                                                                                                                                                       |
|-----------------|------------------------------|----------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| putOrCall       | U.S. Bank custodian CSV      | The legacy custodian transform copies or parses the value from the custody row.<br><code>src/nport/custodian.py:115</code> | Base value is positions.csv column putOrCall. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=putOrCall. Requirement: conditional - derivCat in OPT/SWO/WAR.       |
| writtenOrPur    | U.S. Bank custodian CSV      | The legacy custodian transform copies or parses the value from the custody row.<br><code>src/nport/custodian.py:115</code> | Base value is positions.csv column writtenOrPur. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=writtenOrPur. Requirement: conditional - derivCat in OPT/SWO/WAR. |

|               |                                                 |                                                                                                                                   |                                                                                                                                                                                                  |
|---------------|-------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| shareNo       | Tool constant or classification in custodian.py | The legacy custodian transform assigns the value according to its holding-type branch.<br><code>src/nport/custodian.py:662</code> | Base value is positions.csv column shareNo. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=shareNo. Requirement: never.                                             |
| exercisePrice | U.S. Bank custodian CSV                         | The legacy custodian transform copies or parses the value from the custody row.<br><code>src/nport/custodian.py:115</code>        | Base value is positions.csv column exercisePrice. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=exercisePrice. Requirement: conditional - derivCat in OPT/SWO/WAR. |

### Option (continued)

| Canonical field    | Actual current/legacy origin                                      | Transform and live code location                                                                                                  | New independent workflow                                                                                                                                                         |
|--------------------|-------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| exercisePriceCurCd | Tool constant or classification in custodian.py                   | The legacy custodian transform assigns the value according to its holding-type branch.<br><code>src/nport/custodian.py:115</code> | Base value is positions.csv column exercisePriceCurCd. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=exercisePriceCurCd. Requirement: never.       |
| expDt              | U.S. Bank custodian CSV                                           | The legacy custodian transform copies or parses the value from the custody row.<br><code>src/nport/custodian.py:116</code>        | Base value is positions.csv column expDt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=expDt. Requirement: conditional - derivCat in OPT/SWO/WAR. |
| delta              | Manual value preserved in security_master.xlsx; no automated feed | The legacy master preserves the workbook cell; it does not calculate or source delta.<br><code>src/nport/models.py:160</code>     | Base value is positions.csv column delta. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=delta. Requirement: conditional - derivCat in OPT/SWO/WAR. |

### Ref Instrument

| Canonical field    | Actual current/legacy origin                    | Transform and live code location                                                                                                                                         | New independent workflow                                                                                                                                                                                    |
|--------------------|-------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| refInstType        | Tool constant or classification in custodian.py | The legacy custodian transform assigns the value according to its holding-type branch.<br><code>src/nport/custodian.py:117</code>                                        | Base value is positions.csv column refInstType. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refInstType. Requirement: never.                                                |
| refIndexName       | Seeded legacy human-review workbook overlay     | master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin.<br><code>src/nport/master_sheet.py:789</code> | Base value is positions.csv column refIndexName. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refIndexName. Requirement: conditional - refInstType==indexBasket.             |
| refIndexIdentifier | Seeded legacy human-review workbook overlay     | master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin.<br><code>src/nport/master_sheet.py:789</code> | Base value is positions.csv column refIndexIdentifier. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refIndexIdentifier. Requirement: conditional - refInstType==indexBasket. |

|               |                         |                                                                                                               |                                                                                                                                                                                                    |
|---------------|-------------------------|---------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| refIssuerName | U.S. Bank custodian CSV | The legacy custodian transform copies or parses the value from the custody row.<br>src/nport/custodian.py:129 | Base value is positions.csv column refIssuerName. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refIssuerName. Requirement: conditional - refInstType==otherRefInst. |
|---------------|-------------------------|---------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Ref Instrument (continued)

| Canonical field | Actual current/legacy origin                         | Transform and live code location                                                                              | New independent workflow                                                                                                                                                                           |
|-----------------|------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| refIssueTitle   | U.S. Bank custodian CSV                              | The legacy custodian transform copies or parses the value from the custody row.<br>src/nport/custodian.py:129 | Base value is positions.csv column refIssueTitle. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refIssueTitle. Requirement: conditional - refInstType==otherRefInst. |
| refCusip        | U.S. Bank custodian CSV                              | The legacy custodian transform copies or parses the value from the custody row.<br>src/nport/custodian.py:130 | Base value is positions.csv column refCusip. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refCusip. Requirement: never.                                             |
| refIsin         | Bloomberg workbook formula on the reference security | BDP enrichment uses the reference CUSIP/security key.<br>src/nport/master_sheet.py:129                        | Base value is positions.csv column refIsin. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refIsin. Requirement: never.                                               |
| refTicker       | Bloomberg workbook formula on the reference security | BDP enrichment uses the reference CUSIP/security key.<br>src/nport/master_sheet.py:129                        | Base value is positions.csv column refTicker. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refTicker. Requirement: never.                                           |

## Swap

| Canonical field | Actual current/legacy origin                    | Transform and live code location                                                                                     | New independent workflow                                                                                                                                                               |
|-----------------|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| swapFlag        | Tool constant or classification in custodian.py | The legacy custodian transform assigns the value according to its holding-type branch.<br>src/nport/custodian.py:124 | Base value is positions.csv column swapFlag. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=swapFlag. Requirement: conditional - derivCat==SWP.           |
| terminationDt   | U.S. Bank custodian CSV                         | The legacy custodian transform copies or parses the value from the custody row.<br>src/nport/custodian.py:124        | Base value is positions.csv column terminationDt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=terminationDt. Requirement: conditional - derivCat==SWP. |
| upfrontPmnt     | Builder fallback, not a sourced legacy field    | builder.py emits 0 when the accepted holding column is blank.<br>src/nport/builder.py:497                            | Base value is positions.csv column upfrontPmnt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=upfrontPmnt. Requirement: never.                           |



|           |                                              |                                                                                                             |                                                                                                                                                          |
|-----------|----------------------------------------------|-------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| pmntCurCd | Builder fallback, not a sourced legacy field | builder.py uses the holding currency when the accepted holding column is blank.<br>src/nport/builder.py:498 | Base value is positions.csv column pmntCurCd. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntCurCd. Requirement: never. |
|-----------|----------------------------------------------|-------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|

## Swap (continued)

| Canonical field | Actual current/legacy origin                    | Transform and live code location                                                                                     | New independent workflow                                                                                                                                                           |
|-----------------|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| upfrontRcpt     | Builder fallback, not a sourced legacy field    | builder.py emits 0 when the accepted holding column is blank.<br>src/nport/builder.py:499                            | Base value is positions.csv column upfrontRcpt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=upfrontRcpt. Requirement: never.                       |
| rcptCurCd       | Builder fallback, not a sourced legacy field    | builder.py uses the holding currency when the accepted holding column is blank.<br>src/nport/builder.py:500          | Base value is positions.csv column rcptCurCd. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=rcptCurCd. Requirement: never.                           |
| notionalAmt     | U.S. Bank custodian CSV                         | The legacy custodian transform copies or parses the value from the custody row.<br>src/nport/custodian.py:124        | Base value is positions.csv column notionalAmt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=notionalAmt. Requirement: conditional - derivCat==SWP. |
| swapCurCd       | Tool constant or classification in custodian.py | The legacy custodian transform assigns the value according to its holding-type branch.<br>src/nport/custodian.py:124 | Base value is positions.csv column swapCurCd. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=swapCurCd. Requirement: never.                           |

## Swap (continued)

| Canonical field    | Actual current/legacy origin                        | Transform and live code location                                                                                                                            | New independent workflow                                                                                                                                                                                        |
|--------------------|-----------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| recFixedOrFloating | Seeded legacy human-review workbook overlay         | master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin.<br>src/nport/master_sheet.py:748 | Base value is positions.csv column recFixedOrFloating. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recFixedOrFloating. Requirement: conditional - derivCat==SWP.                |
| recFixedRt         | No verified automated writer in the legacy pipeline | The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it.<br>src/nport/models.py:181               | Base value is positions.csv column recFixedRt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recFixedRt. Requirement: conditional - recFixedOrFloating==Fixed.                    |
| recFloatingRtIndex | No verified automated writer in the legacy pipeline | The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it.<br>src/nport/models.py:182               | Base value is positions.csv column recFloatingRtIndex. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recFloatingRtIndex. Requirement: conditional - recFixedOrFloating==Floating. |

|                     |                                                     |                                                                                                                                               |                                                                                                                                                                                                                   |
|---------------------|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| recFloatingRtSpread | No verified automated writer in the legacy pipeline | The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it.<br>src/nport/models.py:183 | Base value is positions.csv column recFloatingRtSpread. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recFloatingRtSpread. Requirement: conditional - recFixedOrFloating==Floating. |
|---------------------|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### Swap (continued)

| Canonical field | Actual current/legacy origin                        | Transform and live code location                                                                                                              | New independent workflow                                                                                                                                       |
|-----------------|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| recPmntAmt      | No verified automated writer in the legacy pipeline | The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it.<br>src/nport/models.py:184 | Base value is positions.csv column recPmntAmt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recPmntAmt. Requirement: never.     |
| recCurCd        | No verified automated writer in the legacy pipeline | The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it.<br>src/nport/models.py:185 | Base value is positions.csv column recCurCd. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recCurCd. Requirement: never.         |
| recRateTenor    | No verified automated writer in the legacy pipeline | The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it.<br>src/nport/models.py:186 | Base value is positions.csv column recRateTenor. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recRateTenor. Requirement: never. |
| recRateUnit     | No verified automated writer in the legacy pipeline | The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it.<br>src/nport/models.py:187 | Base value is positions.csv column recRateUnit. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recRateUnit. Requirement: never.   |

### Swap (continued)

| Canonical field | Actual current/legacy origin                        | Transform and live code location                                                                                                                            | New independent workflow                                                                                                                                       |
|-----------------|-----------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| recResetDt      | No verified automated writer in the legacy pipeline | The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it.<br>src/nport/models.py:188               | Base value is positions.csv column recResetDt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recResetDt. Requirement: never.     |
| recResetUnit    | No verified automated writer in the legacy pipeline | The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it.<br>src/nport/models.py:189               | Base value is positions.csv column recResetUnit. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recResetUnit. Requirement: never. |
| recDesc         | Seeded legacy human-review workbook overlay         | master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin.<br>src/nport/master_sheet.py:748 | Base value is positions.csv column recDesc. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recDesc. Requirement: never.           |

|          |                                                     |                                                                                                                                                            |                                                                                                                                                        |
|----------|-----------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| pmntDesc | No verified automated writer in the legacy pipeline | The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it.<br><code>src/nport/models.py:192</code> | Base value is positions.csv column pmntDesc. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntDesc. Requirement: never. |
|----------|-----------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|

### Swap (continued)

| Canonical field      | Actual current/legacy origin                        | Transform and live code location                                                                                                                                         | New independent workflow                                                                                                                                                                                             |
|----------------------|-----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pmntFixedOrFloating  | Tool constant or classification in custodian.py     | The legacy custodian transform assigns the value according to its holding-type branch.<br><code>src/nport/custodian.py:127</code>                                        | Base value is positions.csv column pmntFixedOrFloating. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntFixedOrFloating. Requirement: conditional - derivCat==SWP.                   |
| pmntFixedRt          | No verified automated writer in the legacy pipeline | The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it.<br><code>src/nport/models.py:194</code>               | Base value is positions.csv column pmntFixedRt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntFixedRt. Requirement: conditional - pmntFixedOrFloating==Fixed.                      |
| pmntFloatingRtIndex  | Seeded legacy human-review workbook overlay         | master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin.<br><code>src/nport/master_sheet.py:748</code> | Base value is positions.csv column pmntFloatingRtIndex. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntFloatingRtIndex. Requirement: conditional - pmntFixedOrFloating==Floating.   |
| pmntFloatingRtSpread | Seeded legacy human-review workbook overlay         | master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin.<br><code>src/nport/master_sheet.py:748</code> | Base value is positions.csv column pmntFloatingRtSpread. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntFloatingRtSpread. Requirement: conditional - pmntFixedOrFloating==Floating. |

### Swap (continued)

| Canonical field | Actual current/legacy origin                        | Transform and live code location                                                                                                                                         | New independent workflow                                                                                                                                         |
|-----------------|-----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pmntPmntAmt     | No verified automated writer in the legacy pipeline | The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it.<br><code>src/nport/models.py:197</code>               | Base value is positions.csv column pmntPmntAmt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntPmntAmt. Requirement: never.     |
| pmntCurCdLeg    | Tool constant or classification in custodian.py     | The legacy custodian transform assigns the value according to its holding-type branch.<br><code>src/nport/custodian.py:128</code>                                        | Base value is positions.csv column pmntCurCdLeg. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntCurCdLeg. Requirement: never.   |
| pmntRateTenor   | Seeded legacy human-review workbook overlay         | master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin.<br><code>src/nport/master_sheet.py:748</code> | Base value is positions.csv column pmntRateTenor. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntRateTenor. Requirement: never. |

|              |                                             |                                                                                                                                                                 |                                                                                                                                                                |
|--------------|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pmntRateUnit | Seeded legacy human-review workbook overlay | master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin.<br>src/nport/<br>master_sheet.py:748 | Base value is positions.csv column pmntRateUnit. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntRateUnit. Requirement: never. |
|--------------|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Swap (continued)

| Canonical field | Actual current/legacy origin                        | Transform and live code location                                                                                                              | New independent workflow                                                                                                                                         |
|-----------------|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| pmntResetDt     | No verified automated writer in the legacy pipeline | The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it.<br>src/nport/models.py:201 | Base value is positions.csv column pmntResetDt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntResetDt. Requirement: never.     |
| pmntResetUnit   | No verified automated writer in the legacy pipeline | The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it.<br>src/nport/models.py:202 | Base value is positions.csv column pmntResetUnit. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntResetUnit. Requirement: never. |

## Forward

| Canonical field | Actual current/legacy origin                        | Transform and live code location                                                                                                              | New independent workflow                                                                                                                                                                         |
|-----------------|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| payoffProfDeriv | No verified automated writer in the legacy pipeline | The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it.<br>src/nport/models.py:204 | Base value is positions.csv column payoffProfDeriv. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=payoffProfDeriv. Requirement: conditional - derivCat in FWD/FUT. |

## Other Deriv

| Canonical field | Actual current/legacy origin                        | Transform and live code location                                                                                                              | New independent workflow                                                                                                                                                                 |
|-----------------|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| otherDerivDesc  | No verified automated writer in the legacy pipeline | The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it.<br>src/nport/models.py:206 | Base value is positions.csv column otherDerivDesc. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=otherDerivDesc. Requirement: conditional - derivCat==OTH. |

## Liquidity

| Canonical field             | Actual current/legacy origin                        | Transform and live code location                                                                                                              | New independent workflow                                                                                                                                                                                                   |
|-----------------------------|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| liquidityClassificationJson | No verified automated writer in the legacy pipeline | The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it.<br>src/nport/models.py:209 | Base value is positions.csv column liquidityClassificationJson. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=liquidityClassificationJs Requirement: conditional - fund policy requires C.7. |

---

|                            |                                                     |                                                                                                                                               |                                                                                                                                                                                        |
|----------------------------|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| liquidityCircumstancesJson | No verified automated writer in the legacy pipeline | The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it.<br>src/nport/models.py:210 | Base value is positions.csv column liquidityCircumstancesJson. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=liquidityCircumstances. Requirement: never. |
|----------------------------|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

---

## 13. Release decision

---

nport build <fund> <period> --from-inputs writes output only after every applicable XML value and policy/applicability input is resolved, all reconciliations pass, canonical validation passes, and XSD validation passes. Source metadata does not gate release. Explicit U.S. Bank/EagleSTAR/prepared-filing input references remain prohibited.

---

Generated from the repository field contracts and source controls on 2026-08-04.