

N-PORT In-House Runbook

A field-by-field operating guide showing what supplies each value, exactly where it is entered, how the input workflow runs, and what blocks release.

As of August 4, 2026 · Source-independent workflow

Controlling rule: no file, value, mapping, or pre-fill delivered by U.S. Bank may populate the in-house filing. Those artifacts are read-only comparison evidence.

1. Purpose and non-negotiable boundary

This runbook operates an N-PORT service built from independent sources. U.S. Bank custody exports, EagleSTAR attachments, prepared filings, email attachments, and prior master workbooks are benchmark outputs only. They may never be copied, merged, seeded, or used to clear a production exception.

Stop rule: if the only available answer comes from U.S. Bank, record the field as MISSING and keep the filing NOT READY.

2. Status language

Status	Use it when	Operator action
MISSING	A required XML value or policy/applicability input is unresolved.	Complete the exact FundFields or HoldingFields row.
NOT READY	One or more open inputs or validation errors remain.	Fix the exact workbook row or upstream file printed by build.
PROVIDED	A current or proposed value is ready for build.	Set status; sourceId is optional.
CLEAR	XML fields, applicability, validation, and reconciliation pass.	Retain the inputs and proceed.

3. What matters to the filing

Release rule: source labels do not appear in N-PORT XML. The build gates only XML values, policy/applicability inputs that change XML, reconciliation results, canonical validation, and XSD validation.

Item	Appears in XML	Where the human acts	Release effect
------	----------------	----------------------	----------------

XML value	Yes	FundFields or HoldingFields	Value/format/requiredness blocks build
Policy/applicability driver	Indirectly	FundFields targetFile=fund_config.txt	Blocks because it changes dates, form, or XML sections
Reconciliation control	No	ReconciliationInputs	Blocks only when the calculated difference exceeds tolerance
Item	Appears in XML	Where the human acts	Release effect
sourceId / Sources metadata	No	Optional	Never blocks XML; retained only for diagnostics
U.S. Bank/EagleSTAR reference	No	Do not input	Rejected as a prohibited comparison-output input

4. Exact operating workflow

Use this order every time. Do not skip ahead. If build reports an open input or validation error, correct the named workbook row or upstream file and rerun the same command.

Step 1 - Check the input format

Run:

```
Set-Location "C:\Users\damie\nportvalidation"
& ".\venv\Scripts\nport.exe" schema
```

System:

Prints the required and conditional `positions.csv` columns.

Human:

Export independent positions to `data/intake/<period>/<fund>/positions.csv`. If available, place the independent order file beside it as `create_redeem_orders.csv`.

Stop if:

Either file came from or was derived from U.S. Bank or EagleSTAR.

Step 2 - Run the preparation automation

Run:

```
$p = ".\data\intake\2026-06\fdrs\positions.csv"
$o = ".\data\intake\2026-06\fdrs\create_redeem_orders.csv"
& ".\venv\Scripts\nport.exe" prepare FDRS 2026-06 --positions $p --orders $o
```

System:

Creates `data/funds/fdrs/filings/2026-06/filing_inputs.xlsx`, calculates controls for the supplied files, and inserts Bloomberg formulas. Omit `--orders $o` when unavailable.

Pass when:

The command prints the expected workbook path.

Step 3 - Open and save on Bloomberg

Run:

Open `filing_inputs.xlsx` in Excel on a logged-in Bloomberg terminal.

System:

The Bloomberg Excel Add-In calculates the visible formulas on the `Bloomberg` sheet.

Human:

Wait until formulas show values or explicit Bloomberg errors, then save and close the workbook.

Pass when:

The workbook is saved with calculated values; unresolved Bloomberg errors remain visible and will block.

Step 4 - Complete the remaining inputs

Run:

Reopen `filing_inputs.xlsx`.

Human:

Ignore `Sources` for XML completion. Filter `FundFields` and `HoldingFields` to `MISSING`. For `PROVIDED`, set `status` and enter `proposedValue` only when the automated/current value is absent or must be corrected; fund-config rows require `proposedValue` when applicable. For `NOT_APPLICABLE`, leave `proposedValue` blank and enter `status` plus a factual `comment`. In `ReconciliationInputs`, enter `controlValue`, `tolerance`, `status`, and `comment`. `sourceId` is optional everywhere.

Pass when:

Build reports zero open XML inputs and validation/reconciliation errors.

Step 5 - Run the final automation

Run:

```
& ".\venv\Scripts\nport.exe" build FDRS 2026-06 --from-inputs
```

System:

Checks XML values, policy/applicability, and reconciliation; writes a clean bundle; generates XML; and runs XSD validation.

Human:

If `NOT READY`, correct the exact workbook row or upstream file printed by the command and rerun the same command.

Pass when:

The clean bundle and validated XML are written.

Step 6 - Optional aligned comparison

Run:

```
& ".\venv\Scripts\nport.exe" compare-reference --internal ".\output\FDRS_2026-06.xml" --reference "<aligned-reference.xml>"
```

System:

Writes a versioned clean bundle under `data/builds/fdrs/2026-06/<run-id>/`, writes XML under `output/`, and performs a read-only comparison.

Human:

Confirm the internal and reference outputs use the same fund identity and report date. Document gaps; never copy comparison values back into the filing.

Pass when:

The clean bundle, receipt, validated XML, and documented comparison all exist.

Run the workflow for every fund

Scope rule: the service is not limited to FDRS. Each fund has its own positions file, input workbook, clean bundle, and XML.

Phase A - generate one input workbook per intake folder. The folder name is the fund ticker.

```
$period = "2026-06"
$nport = ".\env\Scripts\nport.exe"
$intakeRoot = Join-Path ".\data\intake" $period

foreach ($fundFolder in Get-ChildItem -LiteralPath $intakeRoot -Directory) {
    $fund = $fundFolder.Name.ToLowerInvariant()
    $positions = Join-Path $fundFolder.FullName "positions.csv"
    $orders = Join-Path $fundFolder.FullName "create_redeem_orders.csv"
    if (-not (Test-Path -LiteralPath $positions)) {
        throw "Missing independent positions file for $fund: $positions"
    }
    $prepareArgs = @("prepare", $fund, $period, "--positions", $positions)
    if (Test-Path -LiteralPath $orders) {
        $prepareArgs += @("--orders", $orders)
    }
    & $nport @prepareArgs
    if ($LASTEXITCODE -ne 0) { throw "prepare failed for $fund" }
}
```

Phase B - Bloomberg and remaining inputs. Open, calculate, and save each workbook on Bloomberg; then fill each fund's remaining field rows and ReconciliationInputs control rows.

Phase C - build. The loop stops at the first fund that is not ready.

```
$period = "2026-06"
$nport = ".\env\Scripts\nport.exe"

foreach ($book in Get-ChildItem -Path ".\data\funds*\filings\$period\filing_inputs.xlsx" -File) {
    $fund = $book.Directory.Parent.Parent.Name.ToLowerInvariant()
    & $nport build $fund $period --from-inputs
    if ($LASTEXITCODE -ne 0) { throw "build failed for $fund" }
}
```

Complete command reference

Command	Stage	What it does	Writes data?
<code>nport schema</code>	Intake design	Prints every canonical positions.csv column, type, and applicability rule.	No

<code>nport prepare <fund> <period> --positions <file> [--orders <file>]</code>	Prepare	Creates filing_inputs.xlsx, gap rows, reconciliation inputs, and Bloomberg formulas.	Yes - filing_inputs.xlsx
<code>nport build <fund> <period> --from-inputs</code>	Validate and build	Prints exact open inputs/errors or writes the clean bundle and schema-valid XML.	Only when all inputs and validations clear
<code>nport compare-reference -- internal <xml> --reference <xml></code>	Post-build comparison	Performs a read-only structural comparison after dates and fund identity are aligned.	No filing inputs

Command	Stage	What it does	Writes data?
<code>nport check-schema</code>	Maintenance	Checks the local N-PORT schema files and version.	Cache only when applicable
<code>nport pull --ticker <ticker> --list</code>	External research	Lists recent EDGAR N-PORT filings; it is not an input adapter.	No, unless an explicit output download is requested

Disabled write paths: masters, split, mergehumanreview, enrich, merge, new-filing, build-master, split-master, build-filing-master, and split-filing-master. Do not use them for the independent service.

5. Post-automation human entry queue

Automation handoff: run `prepare`, open/save the workbook on Bloomberg, then work only in `filing_inputs.xlsx`. Filter `FundFields` and `HoldingFields` to `MISSING`. Work only the values, policy decisions, and reconciliation controls listed below. Do not complete Sources for XML release.

Sheet	Rows to work	What the reviewer types	What the system owns
FundFields	Filter status = MISSING	PROVIDED: proposedValue when no automated value exists, plus status. NOT_APPLICABLE: status and factual comment; leave proposedValue blank. sourceId is optional.	For targetFile=fund_config.txt, proposedValue is required whenever the field applies; currentValue is reference-only.
HoldingFields	Filter status = MISSING	PROVIDED: status; add proposedValue only when currentValue is blank or must be corrected. NOT_APPLICABLE: status and factual comment. sourceId is optional.	Enter only rows generated for the supplied positions. Do not add holdings or invent missing rows.

Sheet	Rows to work	What the reviewer types	What the system owns
ReconciliationInputs	Every generated checkId	PROVIDED: controlValue, tolerance, status, comment. A flow may be NOT_APPLICABLE only when its filed flow is N/A; then enter status and factual comment. sourceId is optional.	Never type actualBasis or the filed-side actual. Build calculates the actual and difference.
Sources	Optional only	Nothing is required for XML. Automation retains technical paths needed to reload supplied files; optional sourceId notes may be added for diagnostics.	Source labels, paths, hashes, counts, and as-of dates never serialize into N-PORT XML.

Exact field names that may remain after automation

Queue	When the reviewer acts	fieldName / checkId
Fund configuration - identity/static	Every generated row is a human confirmation from independent evidence	cik, ccc, regName, regFileNumber, regCik, regLei, regStreet1, regStreet2, regCity, regState, regCountry, regZipOrPostalCode, regPhone, seriesName, seriesId, seriesLei, classId, signerOrg, signerName, signerTitle
Fund configuration - policy	Confirm from the current policy record. policyEffectiveTo may remain blank when the policy is open-ended.	fiscalYearEndMMDD, derivativesRegimePolicy, liquidityRequired, cashB2fRequired, policyEffectiveFrom, policyEffectiveTo
Queue	When the reviewer acts	fieldName / checkId
Filing - accounting, signer, and core values	Enter only rows still MISSING	isFinalFiling, dateSigned, totAssets, totLiabs, netAssets, assetsAttrMiscSec, assetsInvested, amtPayOneYrBanksBorr, amtPayOneYrCtrlComp, amtPayOneYrOthAffil, amtPayOneYrOther, amtPayAftOneYrBanksBorr, amtPayAftOneYrCtrlComp, amtPayAftOneYrOthAffil, amtPayAftOneYrOther, delayDeliv, standByCommit, liquidPref, isNonCashCollateral, netRealizedGainMon1, netUnrealizedApprMon1, netRealizedGainMon2, netUnrealizedApprMon2, netRealizedGainMon3, netUnrealizedApprMon3, nameDesignatedIndex, indexIdentifier
Filing - monthly returns	Bloomberg normally populates these; enter only if still MISSING and another independent source supports them	rtn1, rtn2, rtn3
Queue	When the reviewer acts	fieldName / checkId
Filing - create/redeem flows	Orders may populate these; enter only the rows still MISSING	mon1Sales, mon1Redemption, mon1Reinvestment, mon2Sales, mon2Redemption, mon2Reinvestment, mon3Sales, mon3Redemption, mon3Reinvestment
Filing - conditional risk sections	Enter PROVIDED when applicable, or NOT_APPLICABLE with a factual comment when policy says the section does not apply	curMetricsJson, creditSprdRiskIgJson, creditSprdRiskNonigJson, cashNotReportedInCoRD, monthlyReturnCategoriesJson, derivExposurePct, derivCurrencyExposurePct, derivInterestRateExposurePct, derivDaysInExcess, medianDailyVarPct, medianVarRatioPct, backtestingExceptions
Queue	When the reviewer acts	fieldName / checkId

Holdings	The exact queue is dynamic: every generated HoldingFields row whose status remains MISSING. fieldName and recordKey identify exactly what and which holding.	Possible fields are listed by condition in the runbook's exhaustive holding trace; no hidden holding inputs exist.
Reconciliation	Every generated ReconciliationInputs check	POSITIONS_TO_GL, FLOW:mon1Sales, FLOW:mon1Redemption, FLOW:mon1Reinvestment, FLOW:mon2Sales, FLOW:mon2Redemption, FLOW:mon2Reinvestment, FLOW:mon3Sales, FLOW:mon3Redemption, FLOW:mon3Reinvestment, DERIVATIVE_MARKET_VALUE (when generated), DERIVATIVE_UNREALIZED (when generated)

Do not edit: Summary, Bloomberg formulas, GapGuide, Reconciliation, gapId, targetFile, recordKey, fieldName, currentValue, actualBasis, SYSTEM_DERIVED rows, or SYSTEM_CONTROL rows.

Permitted blanks: policyEffectiveTo may stay blank for an open-ended policy; nameDesignatedIndex and indexIdentifier are required only for relative VaR; holding isin and ticker may remain blank when another permitted identifier path is valid.

6. Filing input workbook

Sheet	Key	What the human edits	Result	Release rule
Summary	Fund + period	Nothing	Shows scope, stop rule, and next command	Read-only
Bloomberg	targetFile + recordKey + fieldName	Nothing; formulas calculate in Excel	Supported returns and security/reference values	Blank/error results remain MISSING
GapGuide	gapId	Nothing	Explains every tracked item, evidence template, and exact destination	Read-only
FundFields	targetFile + fieldName	PROVIDED: proposedValue if needed + status. N/A: status + factual comment. sourceId optional	Config and filing-level XML values	Candidate rows have status MISSING

Sheet	Key	What the human edits	Result	Release rule
HoldingFields	recordKey + fieldName	PROVIDED: status + proposedValue only to supply/correct. N/A: status + factual comment. sourceId optional	Holding XML exceptions	Only generated candidate rows
Sources	sourceId	Nothing required; optional trace only	Diagnostic sidecar metadata	Does not gate XML
ReconciliationInputs	checkId	controlValue, tolerance, status, comment; sourceId optional	Control side of position-to-GL, flows, and derivative checks	Every generated difference is within tolerance
Reconciliation	check	Nothing; correct upstream filed input or ReconciliationInputs	Build-calculated actual, control, difference, tolerance, and result	Every automated check passes

The workbook does not make data true. Enter only known values; never infer from comparison output. Source metadata is optional and does not validate a value.

Fund-configuration safeguard: for `targetFile=fund_config.txt`, enter `proposedValue`. The existing `currentValue` is reference-only and cannot be accepted by changing status alone.

7. Status rules

Value	Exact meaning	Required entry
MISSING	No usable value has been supplied.	The row remains an open input when applicable.
PROVIDED	A current or proposed value is ready for the build.	Resolved value and status. <code>sourceId</code> optional.
NOT_APPLICABLE	A conditional field does not apply to this fund/holding.	Status plus a factual reason in comment. <code>sourceId</code> optional.

Value	Exact meaning	Required entry
SYSTEM_DERIVED	The system calculates the value from validated period/policy inputs.	No manual override.
SYSTEM_CONTROL	The system owns the release-state value.	No manual override.

`sourceId`, `sourceAsOf`, hashes, and counts are optional diagnostic metadata. None appears in the XML.

8. Current input checklist and exact fix location

Centralized remediation: use only this fund-period's `filing_inputs.xlsx`. Enter XML values/dispositions in `FundFields` or `HoldingFields` and controls in `ReconciliationInputs`. Do not create gap-specific templates or complete Sources for release.

ID / status	What must be resolved	Single review destination
G-001 OPEN INPUT	Position population All Part C holdings	<code>filing_inputs.xlsx</code> CLI + <code>HoldingFields</code>
G-002 OPEN INPUT	Fund-accounting values Assets, liabilities, net assets, balance-sheet items, gains, returns, and cash	<code>filing_inputs.xlsx</code> <code>FundFields</code>
G-003 PARTLY AUTOMATED INPUT	Create/redeem flows Monthly sales, redemptions, and reinvestments	<code>filing_inputs.xlsx</code> CLI + <code>FundFields</code>
G-004 OPEN INPUT	Policy and static data Fiscal year-end, derivatives regime, applicability, identity, and signer fields	<code>filing_inputs.xlsx</code> <code>FundFields</code>

ID / status	What must be resolved	Single review destination
-------------	-----------------------	---------------------------

G-005 OPTIONAL	Source manifest Diagnostic provenance only; no XML element	filing_inputs.xlsx Sources
G-006 INPUT BOUNDARY	Prohibited comparison inputs U.S. Bank, EagleSTAR, and prepared filing outputs	filing_inputs.xlsx CLI + optional Sources
G-007 OPTIONAL	Manual provenance sourceId and provenance sidecars; no XML element	filing_inputs.xlsx FundFields + HoldingFields
G-008 CONDITIONAL OPEN INPUT	Swap economics Counterparty, LEI, notional, value, termination, and leg terms	filing_inputs.xlsx HoldingFields
ID / status	What must be resolved	Single review destination
G-009 CONDITIONAL OPEN INPUT	B.2.f / B.3 / B.5.c / B.9 / B.10 Cash outside C/D, risk metrics, monthly categories, derivatives exposure, or VaR	filing_inputs.xlsx FundFields
G-010 CONDITIONAL OPEN INPUT	C.7 liquidity Liquidity classification/circumstances by holding	filing_inputs.xlsx HoldingFields
G-011 CONDITIONAL OPEN INPUT	Option terms and delta Delta, exercise terms, expiry, and reference identity	filing_inputs.xlsx HoldingFields
G-012 ACCURACY GATE	Reconciliation Position-to-GL, monthly flows, derivative totals, and NAV equation	filing_inputs.xlsx ReconciliationInputs
ID / status	What must be resolved	Single review destination
G-013 OUT OF ACTIVE SCOPE	Origin assurance Source metadata cannot authenticate origin and does not affect XML	No workbook entry

Exact fix location and proof

ID	Sheet / entry point	Exact action	Owner	Completion test
G-001	CLI + HoldingFields	prepare <fund> <period> --positions <independent.csv>; then resolve MISSING HoldingFields rows.	Operations	The file loads and every required holding value validates
G-002	FundFields	Filter gapId G-002; enter proposedValue and status. Use a factual comment for NOT_APPLICABLE.	Fund Accounting	Every applicable XML value is present and the NAV equation passes
G-003	CLI + FundFields	Pass --orders to prepare; enter only unresolved G-003 proposedValue/status rows.	Capital Markets + Accounting	Every applicable flow value is present and reconciles
ID	Sheet / entry point	Exact action	Owner	Completion test

G-004	FundFields	For targetFile=fund_config.txt enter proposedValue/status; policyEffectiveTo may be blank if open-ended.	Compliance / Legal	Every XML-impacting policy/static value validates
G-005	Sources	No reviewer entry is required for XML release.	None	Never blocks XML generation
G-006	CLI + optional Sources	Remove any prohibited supplied path/reference. Never copy comparison values into the workbook.	Engineering + Operations	No prohibited comparison output is used as an input
ID	Sheet / entry point	Exact action	Owner	Completion test
G-007	FundFields + HoldingFields	No sourceId is required. For NOT_APPLICABLE, enter only a factual comment plus status.	None	Never blocks XML generation
G-008	HoldingFields	Filter gapId G-008 and enter proposedValue/status for each named recordKey.	Derivatives Operations	All required swap XML fields validate and valuation reconciles
G-009	FundFields	Filter gapId G-009; enter proposedValue/status or factual NOT_APPLICABLE comment.	Accounting + Risk	Policy determines applicability; every applicable XML section validates
ID	Sheet / entry point	Exact action	Owner	Completion test
G-010	HoldingFields	Filter gapId G-010 and enter proposedValue/status for each named recordKey.	Liquidity Risk	Every applicable holding has valid C.7 XML content
G-011	HoldingFields	Filter gapId G-011 and enter proposedValue/status for each named recordKey.	Derivatives Risk	Every required option XML field validates
G-012	ReconciliationInputs	Enter controlValue, tolerance, status, and comment. sourceId is optional. Build calculates actual and difference.	Accounting + Operations	Every calculated difference is within tolerance
ID	Sheet / entry point	Exact action	Owner	Completion test
G-013	No workbook entry	No action in this workflow.	None	Does not gate XML generation

9. How to read the field trace

Actual lineage is not authorization. The second column states what the current/legacy code really used, including Bloomberg formulas, U.S. Bank custody, EagleSTAR, seeded review workbooks, constants, and no-feed fields. Those legacy writers are disabled or prohibited for the new production build. The fourth column is the only production workflow.

The trace is generated from the canonical config, filing, and holding field maps. Generation stops if field counts change or the verified lineage anchors no longer resolve.

Verification performed: 72 rows: code anchor located for each; Bloomberg claims checked against BLOOMBERG_SPECS (10 cols) + risk sheet (4 cols); EagleSTAR claims checked against 17 writer keys; Human-review claims checked against 15 review value columns; Custodian claims checked against 67 transform-assigned keys; filing_master HEADER: 55 columns, 0 unmapped; Exhaustive canonical trace: 170 fields (30 config, 56 filing, 84 holding).

10. Exhaustive field trace - fund configuration

All 30 accepted fund-configuration fields are listed. `requiredSources`, `policySourceRef`, `policyApprovedBy`, and `policyApprovedAt` are compatibility/provenance keys: they are not requested by the workbook and do not affect XML.

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
<code>cik</code>	<code>fund_config.txt</code> (current static value)	Direct mapping; stable-identity reconciliation <code>src/nport/config.py:241</code>	FundFields: <code>targetFile=fund_config.txt</code> , <code>recordKey=FUND</code> , <code>fieldName=cik</code> . Enter <code>proposedValue</code> and <code>status=PROVIDED</code> ; <code>sourceId</code> is optional.
<code>ccc</code>	<code>fund_config.txt</code> (current); EDGAR filer administrator	Injected only at execution; never copied from comparison files <code>src/nport/config.py:241</code>	FundFields: <code>targetFile=fund_config.txt</code> , <code>recordKey=FUND</code> , <code>fieldName=ccc</code> . Enter <code>proposedValue</code> and <code>status=PROVIDED</code> ; <code>sourceId</code> is optional.
<code>regName</code>	<code>fund_config.txt</code> (current static value)	Direct mapping; stable-identity reconciliation <code>src/nport/config.py:241</code>	FundFields: <code>targetFile=fund_config.txt</code> , <code>recordKey=FUND</code> , <code>fieldName=regName</code> . Enter <code>proposedValue</code> and <code>status=PROVIDED</code> ; <code>sourceId</code> is optional.
<code>regFileNumber</code>	<code>fund_config.txt</code> (current static value)	Direct mapping; stable-identity reconciliation <code>src/nport/config.py:241</code>	FundFields: <code>targetFile=fund_config.txt</code> , <code>recordKey=FUND</code> , <code>fieldName=regFileNumber</code> . Enter <code>proposedValue</code> and <code>status=PROVIDED</code> ; <code>sourceId</code> is optional.

Fund configuration (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
<code>regCik</code>	<code>fund_config.txt</code> (current static value)	Direct mapping; stable-identity reconciliation <code>src/nport/config.py:241</code>	FundFields: <code>targetFile=fund_config.txt</code> , <code>recordKey=FUND</code> , <code>fieldName=regCik</code> . Enter <code>proposedValue</code> and <code>status=PROVIDED</code> ; <code>sourceId</code> is optional.
<code>regLei</code>	<code>fund_config.txt</code> (current static value)	Direct mapping; stable-identity reconciliation <code>src/nport/config.py:241</code>	FundFields: <code>targetFile=fund_config.txt</code> , <code>recordKey=FUND</code> , <code>fieldName=regLei</code> . Enter <code>proposedValue</code> and <code>status=PROVIDED</code> ; <code>sourceId</code> is optional.

regStreet1	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation <code>src/nport/config.py:241</code>	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regStreet1. Enter proposedValue and status=PROVIDED; sourceId is optional.
regStreet2	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation <code>src/nport/config.py:241</code>	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regStreet2. Enter proposedValue and status=PROVIDED; sourceId is optional.

Fund configuration (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
regCity	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation <code>src/nport/config.py:241</code>	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regCity. Enter proposedValue and status=PROVIDED; sourceId is optional.
regState	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation <code>src/nport/config.py:241</code>	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regState. Enter proposedValue and status=PROVIDED; sourceId is optional.
regCountry	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation <code>src/nport/config.py:241</code>	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regCountry. Enter proposedValue and status=PROVIDED; sourceId is optional.
regZipOrPostalCode	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation <code>src/nport/config.py:241</code>	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regZipOrPostalCode. Enter proposedValue and status=PROVIDED; sourceId is optional.

Fund configuration (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
regPhone	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation <code>src/nport/config.py:241</code>	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=regPhone. Enter proposedValue and status=PROVIDED; sourceId is optional.

seriesName	fund_config.txt (current static value)	Direct identifier mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=seriesName. Enter proposedValue and status=PROVIDED; sourceId is optional.
seriesId	fund_config.txt (current static value)	Direct identifier mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=seriesId. Enter proposedValue and status=PROVIDED; sourceId is optional.
seriesLei	fund_config.txt (current static value)	Direct identifier mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=seriesLei. Enter proposedValue and status=PROVIDED; sourceId is optional.

Fund configuration (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
classId	fund_config.txt (current static value)	Direct identifier mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=classId. Enter proposedValue and status=PROVIDED; sourceId is optional.
signerOrg	fund_config.txt (current static value)	Direct mapping; evidence retained with filing approval src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=signerOrg. Enter proposedValue and status=PROVIDED; sourceId is optional.
signerName	fund_config.txt (current static value)	Direct mapping; evidence retained with filing approval src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=signerName. Enter proposedValue and status=PROVIDED; sourceId is optional.
signerTitle	fund_config.txt (current static value)	Direct mapping; evidence retained with filing approval src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=signerTitle. Enter proposedValue and status=PROVIDED; sourceId is optional.

Fund configuration (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
-----------------	------------------------------	----------------------------------	--------------------------

fiscalYearEndMMDD	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=fiscalYearEndMMDD. Enter proposedValue and status=PROVIDED; sourceId is optional.
derivativesRegimePolicy	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=derivativesRegimePolic Enter proposedValue and status=PROVIDED; sourceId is optional.
liquidityRequired	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=liquidityRequired. Enter proposedValue and status=PROVIDED; sourceId is optional.
cashB2fRequired	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=cashB2fRequired. Enter proposedValue and status=PROVIDED; sourceId is optional.

Fund configuration (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
policyEffectiveFrom	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=policyEffectiveFrom. Enter proposedValue and status=PROVIDED; sourceId is optional.
policyEffectiveTo	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	FundFields: targetFile=fund_config.txt, recordKey=FUND, fieldName=policyEffectiveTo. Enter proposedValue and status=PROVIDED; sourceId is optional.
policyApprovedBy	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	Compatibility/provenance key; it is not requested and does not affect XML.
policyApprovedAt	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	Compatibility/provenance key; it is not requested and does not affect XML.

Fund configuration (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
policySourceRef	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	Compatibility/provenance key; it is not requested and does not affect XML.

requiredSources	fund_config.txt (current static value)	Direct mapping; stable-identity reconciliation src/nport/config.py:241	Optional provenance metadata; it is not requested and does not affect XML.
-----------------	--	---	--

11. Exhaustive field trace - filing-level data

All 56 accepted filing-level fields are listed. A legacy constant is reported as a constant; it is not silently reclassified as sourced data.

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
submissionType	Tool-derived filing period/default; future approved fund registry	filing_master.py derives the period; policy.py overrides from an approved registry when present src/nport/filing_master.py:66	SYSTEM_DERIVED after the period and supplied fund-policy rows pass validation.
liveTestFlag	Filing Operations and authorized signer workflow	Operator-controlled status/date with release gate src/nport/cli.py:1198	SYSTEM_CONTROL; remains TEST until all release controls pass.
repPdEnd	Tool-derived filing period/default; future approved fund registry	filing_master.py derives the period; policy.py overrides from an approved registry when present src/nport/custodian.py:808	SYSTEM_DERIVED after the period and supplied fund-policy rows pass validation.
repPdDate	Tool-derived filing period/default; future approved fund registry	filing_master.py derives the period; policy.py overrides from an approved registry when present src/nport/custodian.py:808	SYSTEM_DERIVED after the period and supplied fund-policy rows pass validation.

Filing-level data (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
isFinalFiling	Filing Operations and authorized signer workflow	Operator-controlled status/date with release gate src/nport/filing_master.py:66	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=isFinalFiling. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
dateSigned	Filing Operations and authorized signer workflow	Operator-controlled status/date with release gate src/nport/filing_master.py:118	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=dateSigned. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
totAssets	Gmail export - U.S. Bank EagleSTAR Trial Balance; custodian fallback	eaglestar.py overrides filing_master.py custody-derived fallback src/nport/eaglestar.py:310	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=totAssets. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.

totLiabs	Gmail export - U.S. Bank EagleSTAR Trial Balance; custodian fallback	eaglestar.py overrides filing_master.py custody-derived fallback src/nport/eaglestar.py:312	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=totLiabs. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
----------	--	---	--

Filing-level data (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
netAssets	Gmail export - U.S. Bank EagleSTAR Trial Balance; custodian fallback	eaglestar.py overrides filing_master.py custody-derived fallback src/nport/eaglestar.py:314	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=netAssets. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
assetsAttrMiscSec	Gmail export - U.S. Bank EagleSTAR Trial Balance; custodian fallback	eaglestar.py overrides filing_master.py custody-derived fallback src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=assetsAttrMiscSec. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
assetsInvested	Gmail export - U.S. Bank EagleSTAR Trial Balance; custodian fallback	eaglestar.py overrides filing_master.py custody-derived fallback src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=assetsInvested. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
amtPayOneYrBanksBorr	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayOneYrBanksBc. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.

Filing-level data (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
amtPayOneYrCtrlldComp	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayOneYrCtrlldCon. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.

amtPayOneYrOthAffil	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayOneYrOthAffil. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
amtPayOneYrOther	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:307	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayOneYrOther. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
amtPayAftOneYrBanksBorr	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayAftOneYrBanksBorr. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.

Filing-level data (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
amtPayAftOneYrCtrlldComp	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayAftOneYrCtrlldComp. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
amtPayAftOneYrOthAffil	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayAftOneYrOthAffil. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
amtPayAftOneYrOther	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=amtPayAftOneYrOther. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
delayDeliv	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=delayDeliv. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.

Filing-level data (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
standByCommit	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=standByCommit. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
liquidPref	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=liquidPref. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
isNonCashCollateral	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=isNonCashCollateral. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
rtn1	Bloomberg formula in filing_master.xlsx	BDP custom total-return formula for each reporting month src/nport/filing_master.py:48	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=rtn1. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.

Filing-level data (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
rtn2	Bloomberg formula in filing_master.xlsx	BDP custom total-return formula for each reporting month src/nport/filing_master.py:48	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=rtn2. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
rtn3	Bloomberg formula in filing_master.xlsx	BDP custom total-return formula for each reporting month src/nport/filing_master.py:48	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=rtn3. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
netRealizedGainMon1	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=netRealizedGainMon1. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.

netUnrealizedApprMon1	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=netUnrealizedApprMon Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
-----------------------	---	---	--

Filing-level data (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
netRealizedGainMon2	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=netRealizedGainMon2. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
netUnrealizedApprMon2	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=netUnrealizedApprMon Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
netRealizedGainMon3	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=netRealizedGainMon3. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
netUnrealizedApprMon3	Gmail export - U.S. Bank EagleSTAR Trial Balance, or tool constant where identified	eaglestar.py writes mapped accounting values; filing_master.py supplies explicit defaults src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=netUnrealizedApprMon Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.

Filing-level data (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
mon1Sales	Gmail export - EagleSTAR Trial Balance	eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon1Sales. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.

mon1Redemption	Gmail export - EagleSTAR Trial Balance	eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon1Redemption. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
mon1Reinvestment	No current feed; filing_master.py supplies N/A	Create/redeem orders do not contain reinvested distributions src/nport/models.py:84	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon1Reinvestment. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
mon2Sales	Gmail export - EagleSTAR Trial Balance	eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon2Sales. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.

Filing-level data (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
mon2Redemption	Gmail export - EagleSTAR Trial Balance	eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon2Redemption. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
mon2Reinvestment	No current feed; filing_master.py supplies N/A	Create/redeem orders do not contain reinvested distributions src/nport/models.py:87	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon2Reinvestment. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
mon3Sales	Gmail export - EagleSTAR Trial Balance	eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon3Sales. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
mon3Redemption	Gmail export - EagleSTAR Trial Balance	eaglestar.py writes subscriptions/redemptions; create/redeem order export is reconciliation-only src/nport/eaglestar.py:206	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon3Redemption. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.

Filing-level data (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
mon3Reinvestment	No current feed; filing_master.py supplies N/A	Create/redeem orders do not contain reinvested distributions src/nport/models.py:90	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=mon3Reinvestment. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
nameDesignatedIndex	Human-review workbook designated_index sheet (legacy 497K seed)	humanreview.py seed values merge through filing_master.py src/nport/ master_sheet.py:748	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=nameDesignatedIndex. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
indexIdentifier	Human-review workbook designated_index sheet (legacy 497K seed)	humanreview.py seed values merge through filing_master.py src/nport/ master_sheet.py:748	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=indexIdentifier. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
curMetricsJson	Bloomberg formulas plus U.S. Bank custodian market value	filing_master.py aggregates duration/rating fields after workbook calculation src/nport/ filing_master.py:40	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=curMetricsJson. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.

Filing-level data (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
creditSprdRiskIgJson	Bloomberg formulas plus U.S. Bank custodian market value	filing_master.py aggregates duration/rating fields after workbook calculation src/nport/ filing_master.py:40	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=creditSprdRiskIgJson. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
creditSprdRiskNonigJson	Bloomberg formulas plus U.S. Bank custodian market value	filing_master.py aggregates duration/rating fields after workbook calculation src/nport/ filing_master.py:40	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=creditSprdRiskNonigJs Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
cashNotReportedInCoRD	No current feed	Typed field exists; no Gmail, custodian, create/redeem, or Bloomberg writer src/nport/models.py:100	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=cashNotReportedInCO Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.

monthlyReturnCategoriesJson	No current feed	Typed field exists; no Gmail, custodian, create/redeem, or Bloomberg writer <code>src/nport/models.py:101</code>	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=monthlyReturnCategories Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
-----------------------------	-----------------	---	--

Filing-level data (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
derivativesRegime	No current populated source; future approved fund registry	policy.py derives it only when the registry exists <code>src/nport/filing_master.py:321</code>	SYSTEM_DERIVED after the period and supplied fund-policy rows pass validation.
derivExposurePct	No current feed	B.9/B.10 typed fields and preflight gates exist, but no writer populates them <code>src/nport/models.py:103</code>	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=derivExposurePct. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
derivCurrencyExposurePct	No current feed	B.9/B.10 typed fields and preflight gates exist, but no writer populates them <code>src/nport/models.py:104</code>	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=derivCurrencyExposurePct. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
derivInterestRateExposurePct	No current feed	B.9/B.10 typed fields and preflight gates exist, but no writer populates them <code>src/nport/models.py:105</code>	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=derivInterestRateExposurePct. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.

Filing-level data (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
derivDaysInExcess	No current feed	B.9/B.10 typed fields and preflight gates exist, but no writer populates them <code>src/nport/models.py:106</code>	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=derivDaysInExcess. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
medianDailyVarPct	No current feed	B.9/B.10 typed fields and preflight gates exist, but no writer populates them <code>src/nport/models.py:107</code>	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=medianDailyVarPct. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.

medianVarRatioPct	No current feed	B.9/B.10 typed fields and preflight gates exist, but no writer populates them <code>src/nport/models.py:108</code>	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=medianVarRatioPct. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.
backtestingExceptions	No current feed	B.9/B.10 typed fields and preflight gates exist, but no writer populates them <code>src/nport/models.py:109</code>	FundFields: targetFile=filing_data.txt, recordKey=FUND, fieldName=backtestingExceptions. Use PROVIDED, or NOT_APPLICABLE with a factual comment; sourceId is optional.

12. Exhaustive field trace - holdings

All 84 accepted holdings fields are listed and grouped by filing condition. Present base values remain tied to the independent POSITIONS source; missing required and exception-sensitive values are surfaced in HoldingFields.

Base

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
name	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. <code>src/nport/custodian.py:107</code>	Base value is positions.csv column name. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=name. Requirement: always.
lei	Bloomberg workbook formula for conventional securities; explicit constants on some derivative/UST paths	BDP enrichment owns conventional-security values; custodian code sets N/A/US or the U.S. Treasury LEI on identified special paths. <code>src/nport/master_sheet.py:128</code>	Base value is positions.csv column lei. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=lei. Requirement: always.
title	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. <code>src/nport/custodian.py:107</code>	Base value is positions.csv column title. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=title. Requirement: always.
cusip	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. <code>src/nport/custodian.py:107</code>	Base value is positions.csv column cusip. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=cusip. Requirement: always.

Base (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
isin	Bloomberg workbook formula for conventional securities; explicit constants on some derivative/UST paths	BDP enrichment owns conventional-security values; custodian code sets N/A/US or the U.S. Treasury LEI on identified special paths. <code>src/nport/master_sheet.py:128</code>	Base value is positions.csv column isin. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=isin. Requirement: never.
ticker	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. <code>src/nport/custodian.py:107</code>	Base value is positions.csv column ticker. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=ticker. Requirement: never.
balance	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. <code>src/nport/custodian.py:679</code>	Base value is positions.csv column balance. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=balance. Requirement: always.

units	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:680	Base value is positions.csv column units. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=units. Requirement: always.
-------	---	--	---

Base (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
curCd	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:662	Base value is positions.csv column curCd. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=curCd. Requirement: always.
valUSD	U.S. Bank custodian CSV for non-swaps; EagleSTAR PVal for swaps	MarketValue is used for non-swaps; swap value is replaced with matched unrealized PVal. src/nport/eaglestar.py:206	Base value is positions.csv column valUSD. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=valUSD. Requirement: always.
pctVal	Derived from filed valUSD and filed netAssets	The legacy transform recalculates the percentage after accounting overrides. src/nport/custodian.py:125	Base value is positions.csv column pctVal. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pctVal. Requirement: always.
payoffProfile	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:662	Base value is positions.csv column payoffProfile. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=payoffProfile. Requirement: always.

Base (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
assetCat	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:108	Base value is positions.csv column assetCat. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=assetCat. Requirement: always.
issuerCat	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:108	Base value is positions.csv column issuerCat. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=issuerCat. Requirement: always.
invCountry	Bloomberg workbook formula for conventional securities; explicit constants on some derivative/UST paths	BDP enrichment owns conventional-security values; custodian code sets N/A/US or the U.S. Treasury LEI on identified special paths. src/nport/master_sheet.py:157	Base value is positions.csv column invCountry. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=invCountry. Requirement: always.

isRestrictedSec	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:662	Base value is positions.csv column isRestrictedSec. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=isRestrictedSec. Requirement: always.
-----------------	---	--	---

Base (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
fairValLevel	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:662	Base value is positions.csv column fairValLevel. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=fairValLevel. Requirement: always.
isCashCollateral	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:662	Base value is positions.csv column isCashCollateral. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=isCashCollateral. Requirement: always.
isNonCashCollateral	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:662	Base value is positions.csv column isNonCashCollateral. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=isNonCashCollateral. Requirement: always.
isLoanByFund	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:662	Base value is positions.csv column isLoanByFund. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=isLoanByFund. Requirement: always.

Conditional

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
issuerConditionalDesc	Tool constant only on the legacy swap path; otherwise no verified writer	custodian.py sets N/A for swaps; other issuerCat=OTHER cases are not populated automatically. src/nport/custodian.py:662	Base value is positions.csv column issuerConditionalDesc. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=issuerConditionalDesc. Requirement: conditional - issuerCat==OTHER.
assetConditionalDesc	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:137	Base value is positions.csv column assetConditionalDesc. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=assetConditionalDesc. Requirement: conditional - assetCat==OTHER.
otherDesc	Tool-generated identifier only for legacy option/swap paths	custodian.py writes USER DEFINED plus an internally constructed option/swap identifier; other paths remain blank. src/nport/custodian.py:662	Base value is positions.csv column otherDesc. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=otherDesc. Requirement: never.

otherValue	Tool-generated identifier only for legacy option/swap paths	custodian.py writes USER DEFINED plus an internally constructed option/swap identifier; other paths remain blank. src/nport/custodian.py:662	Base value is positions.csv column otherValue. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=otherValue. Requirement: never.
------------	---	---	--

Conditional (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
exchangeRt	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:140	Base value is positions.csv column exchangeRt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=exchangeRt. Requirement: conditional - non-USD currency.

Debt

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
maturityDt	Bloomberg workbook formula; U.S. Treasury name parser exists in the direct custodian transform	Corporate/debt master enrichment uses BDP; the alternate direct Treasury path parses coupon and maturity from SecurityName. src/nport/master_sheet.py:101	Base value is positions.csv column maturityDt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=maturityDt. Requirement: conditional - debt security.
couponKind	Bloomberg workbook formula; U.S. Treasury name parser exists in the direct custodian transform	Corporate/debt master enrichment uses BDP; the alternate direct Treasury path parses coupon and maturity from SecurityName. src/nport/master_sheet.py:101	Base value is positions.csv column couponKind. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=couponKind. Requirement: conditional - maturityDt set.
annualizedRt	Bloomberg workbook formula; U.S. Treasury name parser exists in the direct custodian transform	Corporate/debt master enrichment uses BDP; the alternate direct Treasury path parses coupon and maturity from SecurityName. src/nport/master_sheet.py:101	Base value is positions.csv column annualizedRt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=annualizedRt. Requirement: conditional - maturityDt set.
isDefault	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:137	Base value is positions.csv column isDefault. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=isDefault. Requirement: conditional - maturityDt set.

Debt (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
areIntrstPmntsInArRs	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:137	Base value is positions.csv column areIntrstPmntsInArRs. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=areIntrstPmntsInArRs. Requirement: conditional - maturityDt set.

isPaidKind	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. <code>src/nport/custodian.py:137</code>	Base value is positions.csv column isPaidKind. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=isPaidKind. Requirement: conditional - maturityDt set.
------------	---	---	---

Deriv Common

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
derivCat	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. <code>src/nport/custodian.py:114</code>	Base value is positions.csv column derivCat. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=derivCat. Requirement: conditional - derivative holding.
counterpartyName	Seeded human-review overlay for swaps; OCC tool constant for options	Swap values come from the legacy counterparty sheet; option values use the OCC constants in custodian.py. <code>src/nport/master_sheet.py:776</code>	Base value is positions.csv column counterpartyName. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=counterpartyName. Requirement: conditional - derivCat set.
counterpartyLei	Seeded human-review overlay for swaps; OCC tool constant for options	Swap values come from the legacy counterparty sheet; option values use the OCC constants in custodian.py. <code>src/nport/master_sheet.py:776</code>	Base value is positions.csv column counterpartyLei. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=counterpartyLei. Requirement: conditional - derivCat set.
unrealizedAppr	Gmail export - U.S. Bank EagleSTAR PVal attachment	Matched by Primary Asset ID and written as the derivative unrealized amount. <code>src/nport/eaglestar.py:206</code>	Base value is positions.csv column unrealizedAppr. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=unrealizedAppr. Requirement: conditional - derivCat set.

Option

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
putOrCall	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. <code>src/nport/custodian.py:115</code>	Base value is positions.csv column putOrCall. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=putOrCall. Requirement: conditional - derivCat in OPT/SWO/WAR.
writtenOrPur	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. <code>src/nport/custodian.py:115</code>	Base value is positions.csv column writtenOrPur. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=writtenOrPur. Requirement: conditional - derivCat in OPT/SWO/WAR.

shareNo	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. <code>src/nport/custodian.py:662</code>	Base value is positions.csv column shareNo. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=shareNo. Requirement: never.
exercisePrice	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. <code>src/nport/custodian.py:115</code>	Base value is positions.csv column exercisePrice. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=exercisePrice. Requirement: conditional - derivCat in OPT/SWO/WAR.

Option (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
exercisePriceCurCd	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. <code>src/nport/custodian.py:115</code>	Base value is positions.csv column exercisePriceCurCd. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=exercisePriceCurCd. Requirement: never.
expDt	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. <code>src/nport/custodian.py:116</code>	Base value is positions.csv column expDt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=expDt. Requirement: conditional - derivCat in OPT/SWO/WAR.
delta	Manual value preserved in security_master.xlsx; no automated feed	The legacy master preserves the workbook cell; it does not calculate or source delta. <code>src/nport/models.py:160</code>	Base value is positions.csv column delta. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=delta. Requirement: conditional - derivCat in OPT/SWO/WAR.

Ref Instrument

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
refInstType	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. <code>src/nport/custodian.py:117</code>	Base value is positions.csv column refInstType. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refInstType. Requirement: never.
refIndexName	Seeded legacy human-review workbook overlay	master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin. <code>src/nport/master_sheet.py:789</code>	Base value is positions.csv column refIndexName. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refIndexName. Requirement: conditional - refInstType==indexBasket.
refIndexIdentifier	Seeded legacy human-review workbook overlay	master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin. <code>src/nport/master_sheet.py:789</code>	Base value is positions.csv column refIndexIdentifier. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refIndexIdentifier. Requirement: conditional - refInstType==indexBasket.

refIssuerName	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:129	Base value is positions.csv column refIssuerName. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refIssuerName. Requirement: conditional - refInstType==otherRefInst.
---------------	-------------------------	---	--

Ref Instrument (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
refIssueTitle	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:129	Base value is positions.csv column refIssueTitle. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refIssueTitle. Requirement: conditional - refInstType==otherRefInst.
refCusip	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:130	Base value is positions.csv column refCusip. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refCusip. Requirement: never.
refIsin	Bloomberg workbook formula on the reference security	BDP enrichment uses the reference CUSIP/security key. src/nport/master_sheet.py:129	Base value is positions.csv column refIsin. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refIsin. Requirement: never.
refTicker	Bloomberg workbook formula on the reference security	BDP enrichment uses the reference CUSIP/security key. src/nport/master_sheet.py:129	Base value is positions.csv column refTicker. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=refTicker. Requirement: never.

Swap

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
swapFlag	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:124	Base value is positions.csv column swapFlag. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=swapFlag. Requirement: conditional - derivCat==SWP.
terminationDt	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:124	Base value is positions.csv column terminationDt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=terminationDt. Requirement: conditional - derivCat==SWP.
upfrontPmnt	Builder fallback, not a sourced legacy field	builder.py emits 0 when the accepted holding column is blank. src/nport/builder.py:497	Base value is positions.csv column upfrontPmnt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=upfrontPmnt. Requirement: never.

pmntCurCd	Builder fallback, not a sourced legacy field	builder.py uses the holding currency when the accepted holding column is blank. src/nport/builder.py:498	Base value is positions.csv column pmntCurCd. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntCurCd. Requirement: never.
-----------	--	---	--

Swap (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
upfrontRcpt	Builder fallback, not a sourced legacy field	builder.py emits 0 when the accepted holding column is blank. src/nport/builder.py:499	Base value is positions.csv column upfrontRcpt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=upfrontRcpt. Requirement: never.
rcptCurCd	Builder fallback, not a sourced legacy field	builder.py uses the holding currency when the accepted holding column is blank. src/nport/builder.py:500	Base value is positions.csv column rcptCurCd. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=rcptCurCd. Requirement: never.
notionalAmt	U.S. Bank custodian CSV	The legacy custodian transform copies or parses the value from the custody row. src/nport/custodian.py:124	Base value is positions.csv column notionalAmt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=notionalAmt. Requirement: conditional - derivCat==SWP.
swapCurCd	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. src/nport/custodian.py:124	Base value is positions.csv column swapCurCd. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=swapCurCd. Requirement: never.

Swap (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
recFixedOrFloating	Seeded legacy human-review workbook overlay	master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin. src/nport/master_sheet.py:748	Base value is positions.csv column recFixedOrFloating. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recFixedOrFloating. Requirement: conditional - derivCat==SWP.
recFixedRt	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:181	Base value is positions.csv column recFixedRt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recFixedRt. Requirement: conditional - recFixedOrFloating==Fixed.
recFloatingRtIndex	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:182	Base value is positions.csv column recFloatingRtIndex. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recFloatingRtIndex. Requirement: conditional - recFixedOrFloating==Floating.

recFloatingRtSpread	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:183	Base value is positions.csv column recFloatingRtSpread. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recFloatingRtSpread. Requirement: conditional - recFixedOrFloating==Floating.
---------------------	---	---	---

Swap (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
recPmntAmt	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:184	Base value is positions.csv column recPmntAmt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recPmntAmt. Requirement: never.
recCurCd	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:185	Base value is positions.csv column recCurCd. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recCurCd. Requirement: never.
recRateTenor	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:186	Base value is positions.csv column recRateTenor. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recRateTenor. Requirement: never.
recRateUnit	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:187	Base value is positions.csv column recRateUnit. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recRateUnit. Requirement: never.

Swap (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
recResetDt	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:188	Base value is positions.csv column recResetDt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recResetDt. Requirement: never.
recResetUnit	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:189	Base value is positions.csv column recResetUnit. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recResetUnit. Requirement: never.
recDesc	Seeded legacy human-review workbook overlay	master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin. src/nport/master_sheet.py:748	Base value is positions.csv column recDesc. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=recDesc. Requirement: never.

pmntDesc	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:192</code>	Base value is positions.csv column pmntDesc. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntDesc. Requirement: never.
----------	---	--	--

Swap (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
pmntFixedOrFloating	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. <code>src/nport/custodian.py:127</code>	Base value is positions.csv column pmntFixedOrFloating. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntFixedOrFloating. Requirement: conditional - derivCat==SWP.
pmntFixedRt	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:194</code>	Base value is positions.csv column pmntFixedRt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntFixedRt. Requirement: conditional - pmntFixedOrFloating==Fixed.
pmntFloatingRtIndex	Seeded legacy human-review workbook overlay	master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin. <code>src/nport/master_sheet.py:748</code>	Base value is positions.csv column pmntFloatingRtIndex. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntFloatingRtIndex. Requirement: conditional - pmntFixedOrFloating==Floating.
pmntFloatingRtSpread	Seeded legacy human-review workbook overlay	master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin. <code>src/nport/master_sheet.py:748</code>	Base value is positions.csv column pmntFloatingRtSpread. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntFloatingRtSpread. Requirement: conditional - pmntFixedOrFloating==Floating.

Swap (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
pmntPmntAmt	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. <code>src/nport/models.py:197</code>	Base value is positions.csv column pmntPmntAmt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntPmntAmt. Requirement: never.
pmntCurCdLeg	Tool constant or classification in custodian.py	The legacy custodian transform assigns the value according to its holding-type branch. <code>src/nport/custodian.py:128</code>	Base value is positions.csv column pmntCurCdLeg. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntCurCdLeg. Requirement: never.
pmntRateTenor	Seeded legacy human-review workbook overlay	master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin. <code>src/nport/master_sheet.py:748</code>	Base value is positions.csv column pmntRateTenor. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntRateTenor. Requirement: never.

pmntRateUnit	Seeded legacy human-review workbook overlay	master_sheet.py copies the seeded legacy workbook value when present; that workflow does not establish independent origin. src/nport/ master_sheet.py:748	Base value is positions.csv column pmntRateUnit. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntRateUnit. Requirement: never.
--------------	---	---	--

Swap (continued)

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
pmntResetDt	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:201	Base value is positions.csv column pmntResetDt. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntResetDt. Requirement: never.
pmntResetUnit	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:202	Base value is positions.csv column pmntResetUnit. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=pmntResetUnit. Requirement: never.

Forward

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
payoffProfDeriv	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:204	Base value is positions.csv column payoffProfDeriv. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=payoffProfDeriv. Requirement: conditional - derivCat in FWD/FUT.

Other Deriv

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
otherDerivDesc	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:206	Base value is positions.csv column otherDerivDesc. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=otherDerivDesc. Requirement: conditional - derivCat==OTH.

Liquidity

Canonical field	Actual current/legacy origin	Transform and live code location	New independent workflow
liquidityClassificationJson	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:209	Base value is positions.csv column liquidityClassificationJson. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=liquidityClassificationJs Requirement: conditional - fund policy requires C.7.

liquidityCircumstancesJson	No verified automated writer in the legacy pipeline	The canonical model accepts the field and validation/builder may use it, but no legacy intake adapter supplies it. src/nport/models.py:210	Base value is positions.csv column liquidityCircumstancesJson. If missing or exception-sensitive, use HoldingFields: recordKey=, fieldName=liquidityCircumstances. Requirement: never.
----------------------------	---	---	--

13. Release decision

nport build <fund> <period> --from-inputs writes output only after every applicable XML value and policy/applicability input is resolved, all reconciliations pass, canonical validation passes, and XSD validation passes. Source metadata does not gate release. Explicit U.S. Bank/EagleSTAR/prepared-filing input references remain prohibited.

Generated from the repository field contracts and source controls on 2026-08-04.