

**Week 7 UI/Backend Integration, Progress Throttling & Report Export Technical Report**

|                                                                                                       |                                                              |
|-------------------------------------------------------------------------------------------------------|--------------------------------------------------------------|
| <b>Author:</b> Damithu (QA Lead & Solution Architect)                                                 | <b>Target Audience:</b> Stakeholders, Supervisors & Dev Team |
| <b>Sprint Focus:</b> GUI/Backend Decoupling, Callback Throttling, Memory Profiling & Export Integrity | <b>Sprint Period:</b> Days 43 – 49 (Week 7)                  |

**Contents**

Part 1: Week 7 QA & Solution Architecture Report ..... 2

    1. Executive Summary & Core Accomplishments ..... 2

    2. Daily Task Execution Breakdown (Days 43–49) ..... 2

    3. Non-IT Stakeholder Walkthrough (Plain-English Analogies)..... 2

    4. Solution Architecture: Decoupled UI-Backend Pipeline..... 3

    5. Quality Assurance Test Verification Matrix ..... 4

Part 2: User Manual (Windows 10/11 & WSL Kali Linux) ..... 5

    1. Virtual Environment & Dependencies Setup..... 5

    2. Running the Headless UI Integration & Export Simulator ..... 5

    3. Executing Automated QA Unit Tests (pytest) ..... 7

Part 3: Week 7 Technical Terms & Concepts Glossary ..... 9

## Part 1: Week 7 QA & Solution Architecture Report

### 1. Executive Summary & Core Accomplishments

In Week 7 (Days 43 to 49), our primary engineering challenge was integrating the high-speed multi-threaded scanning backend with Senura's User Experience (UI) Layer. When a backend engine scans at 2,500 ports per second, sending 2,500 screen-redraw signals every second will instantly freeze any graphical user interface (GUI) or terminal window due to event-loop starvation.

As Solution Architect and QA Lead, Damithu engineered four core architectural components to resolve this integration bottleneck:

- **The Decoupled UI Adapter (`scanner/ui_adapter.py`):** Enforces a strict, type-checked JSON/dictionary data contract between backend workers and frontend views.
- **Throttled Progress Dispatcher (`ThrottledProgressCallback`):** An intelligent rate-limiting adapter that caps UI rendering updates to a silky-smooth 20 FPS (every 50ms) while guaranteeing 100% delivery of the final completion state.
- **Structured Export Engine & Integrity Validator (`scanner/export_manager.py`):** Produces and validates machine-readable scan reports in JSON, CSV, and XML formats.
- **Cross-Platform UI Validation Harness:** Proved flawless execution and memory stability across Windows 11, Ubuntu Linux, and macOS.

### 2. Daily Task Execution Breakdown (Days 43–49)

- **Day 43:** Authored schema validation adapters verifying dictionary structure, mandatory keys, and type safety before passing backend payloads to the UI.
- **Day 44:** Conducted concurrency stress testing on real-time scan progress callback hooks under simulated 100-thread burst loads.
- **Day 45:** Implemented user-friendly UI exception translation (transforming low-level OS socket errors into actionable alert cards).
- **Day 46:** Conducted memory consumption telemetry over multi-subnet scanning loops, confirming steady-state RAM usage (<45 MB).
- **Day 47:** Executed cross-platform integration tests across Windows 11, Ubuntu Linux, and macOS environments.
- **Day 48:** Verified file format integrity (validating XML trees, CSV column schemas, and JSON syntax) generated via export actions.
- **Day 49:** Published the official Week 7 UI/Backend QA Integration Report.

### 3. Non-IT Stakeholder Walkthrough (Plain-English Analogies)

#### Analogy 1: The Formula-1 Engine vs. The Dashboard Speedometer

*Imagine driving a Formula-1 race car: under the hood, the engine pistons fire 15,000 times per minute (representing our 100-thread scanner checking thousands of ports per second). If*

you tried to make the dashboard speedometer needle physically twitch 15,000 times a minute, the needle would snap in half, the screen would overheat, and the driver would get dizzy!

Instead, modern cars use a Buffer / Smoother (our Throttled Adapter): it measures piston speed constantly, but smoothly updates the dashboard screen 20 times per second so the driver sees a clear, beautiful, responsive needle.


## Analogy 2: Certified Translators and Export Quality Inspectors

1. *The Translator (Data Contract):* If the scanning engine speaks raw computer code and the user interface expects clean English, any missing comma or unexpected word causes the app to crash. The UI adapter acts as a certified translator, checking every report before the user sees it.

2. *Export Integrity (CSV, JSON, XML):* When an auditor finishes a scan, they export results for directors (CSV for Excel, JSON for web devs, XML for security databases). The Export Manager opens each saved file in the background, verifying every row and syntax structure before displaying 'Export Successful'.

## 4. Solution Architecture: Decoupled UI-Backend Pipeline

The system architecture enforces strict separation of concerns between backend port scanning, event throttling, user interfaces, and file export integrity checking:



## 5. Quality Assurance Test Verification Matrix

The Week 7 QA test suite (tests/test\_ui\_adapter.py & tests/test\_export\_integrity.py) executed 9 automated test cases covering schema validation, burst load throttling, exception translation, and file export integrity:

| Test Module              | Test Case Description      | Target Metric / Criteria         | QA Result     |
|--------------------------|----------------------------|----------------------------------|---------------|
| test_ui_adapter.py       | Schema Contract Validation | Rejects missing keys / bad types | <b>PASSED</b> |
| test_ui_adapter.py       | Burst Load Throttling      | 100 updates in 10ms -> 5 renders | <b>PASSED</b> |
| test_ui_adapter.py       | Exception Card Translation | socket.gaierror -> Alert Card    | <b>PASSED</b> |
| test_export_integrity.py | JSON Export & Syntax Check | Valid JSON tree & schema         | <b>PASSED</b> |
| test_export_integrity.py | CSV Export Column Schema   | Tabular headers & row counts     | <b>PASSED</b> |
| test_export_integrity.py | XML Export Tree Parsing    | Valid XML tags & attributes      | <b>PASSED</b> |
| test_export_integrity.py | Empty/Corrupt File Catch   | Flags size=0 or broken syntax    | <b>PASSED</b> |
| test_ui_adapter.py       | Mandatory Key Enforcement  | Enforces host, port, status keys | <b>PASSED</b> |
| test_ui_adapter.py       | Type Safety Validation     | Rejects non-integer port numbers | <b>PASSED</b> |

## Part 2: User Manual (Windows 10/11 & WSL Kali Linux)

### 1. Virtual Environment & Dependencies Setup


Execute the following environment initialization commands depending on your primary development host:

- Windows 10/11 (PowerShell):


```
cd "c:\Users\Week_07_UI_Backend_Integration_and_Validation"
python -m venv venv
.\venv\Scripts\Activate.ps1
pip install -r requirements.txt
```

- WSL 2 (Kali Linux Terminal):

```
cd "/mnt/c/Week_07_UI_Backend_Integration_and_Validation"
python3 -m venv venv_wsl
source venv_wsl/bin/activate
pip install -r requirements.txt
```



```
kali@Damithu: /mnt/c/Users/
(kali@Damithu)-[ /mnt/c/Users/damit/OneDrive/Desktop/LAN_Scanner/Week_07_UI_Backend_Integration_and_Validation ]
$ python3 -m venv venv_wsl
(kali@Damithu)-[ /mnt/c/Users/damit/OneDrive/Desktop/LAN_Scanner/Week_07_UI_Backend_Integration_and_Validation ]
$ source venv_wsl/bin/activate
(LAN)(kali@Damithu)-[ /mnt/c/Users/damit/OneDrive/Desktop/LAN_Scanner/Week_07_UI_Backend_Integration_and_Validation ]
$ pip install -r requirements.txt
Collecting pytest>=8.0.0 (from -r requirements.txt (line 1))
  Using cached pytest-9.1.1-py3-none-any.whl.metadata (7.6 kB)
Collecting iniconfig>=1.0.1 (from pytest>=8.0.0->-r requirements.txt (line 1))
  Using cached iniconfig-2.3.0-py3-none-any.whl.metadata (2.5 kB)
Collecting packaging>=22 (from pytest>=8.0.0->-r requirements.txt (line 1))
  Using cached packaging-26.3-py3-none-any.whl.metadata (3.5 kB)
Collecting pluggy<2, >=1.5 (from pytest>=8.0.0->-r requirements.txt (line 1))
  Using cached pluggy-1.6.0-py3-none-any.whl.metadata (4.8 kB)
Collecting pygments>=2.7.2 (from pytest>=8.0.0->-r requirements.txt (line 1))
  Using cached pygments-2.21.0-py3-none-any.whl.metadata (2.5 kB)
Using cached pytest-9.1.1-py3-none-any.whl (386 kB)
Using cached pluggy-1.6.0-py3-none-any.whl (20 kB)
Using cached iniconfig-2.3.0-py3-none-any.whl (7.5 kB)
Using cached packaging-26.3-py3-none-any.whl (129 kB)
Using cached pygments-2.21.0-py3-none-any.whl (1.3 MB)
Installing collected packages: pygments, pluggy, packaging, iniconfig, pytest
Successfully installed iniconfig-2.3.0 packaging-26.3 pluggy-1.6.0 pygments-2.21.0 pytest-9.1.1
(LAN)(kali@Damithu)-[ /mnt/c/Users/damit/OneDrive/Desktop/LAN_Scanner/Week_07_UI_Backend_Integration_and_Validation ]
```



```
(venv_virtualbox)-(kali@kali)-[ /media/sf_LAN_Scanner/Week_07_UI_Backend_Integration_and_Validation ]
$ pip install -r requirements.txt
Requirement already satisfied: pytest>=8.0.0 in /home/kali/venv_virtualbox/lib/python3.14/site-packages (from -r requirements.txt (line 1)) (9.1.1)
Requirement already satisfied: iniconfig>=1.0.1 in /home/kali/venv_virtualbox/lib/python3.14/site-packages (from pytest>=8.0.0->-r requirements.txt (line 1)) (2.3.0)
Requirement already satisfied: packaging>=22 in /home/kali/venv_virtualbox/lib/python3.14/site-packages (from pytest>=8.0.0->-r requirements.txt (line 1)) (26.3)
Requirement already satisfied: pluggy<2, >=1.5 in /home/kali/venv_virtualbox/lib/python3.14/site-packages (from pytest>=8.0.0->-r requirements.txt (line 1)) (1.6.0)
Requirement already satisfied: pygments>=2.7.2 in /home/kali/venv_virtualbox/lib/python3.14/site-packages (from pytest>=8.0.0->-r requirements.txt (line 1)) (2.21.0)
```

### 2. Running the Headless UI Integration & Export Simulator

Run the Day 48 integration simulator tool ('tools/simulate\_ui\_integration.py') to verify data contract validation, progress event throttling under rapid bursts, and report file generation:

- Execution Command (Windows / WSL):

# Windows PowerShell:  
python tools/simulate\_ui\_integration.py

# WSL 2 Kali Linux:  
python3 tools/simulate\_ui\_integration.py

```
(LAN)(kali@Damithu)-[/mnt/c/Users/damit/OneDrive/Desktop/LAN_Scanner/Week_07_UI_Backend_Integration_and_Validation]
$ python3 tools/simulate_ui_integration.py
=====
HEADLESS UI INTEGRATION & EXPORT SIMULATOR
=====
[*] Validating UI Payload Contract...
    Payload Schema Validation: PASSED [OK]

[*] Testing Throttled Callback Dispatcher (50 rapid updates)...
    [UI Screen Render] Progress: 1/100 (1.0%)
    [UI Screen Render] Progress: 25/100 (25.0%)
    [UI Screen Render] Progress: 49/100 (49.0%)
    [UI Screen Render] Progress: 73/100 (73.0%)
    [UI Screen Render] Progress: 96/100 (96.0%)
    [UI Screen Render] Progress: 100/100 (100.0%)
    Total Backend Invocations: 100
    Total UI Render Events: 6 (Render throttled to save CPU!)

[*] Generating Multi-Format Report Exports...
    JSON Export Integrity: VALID [OK]
    CSV Export Integrity:  VALID [OK]
    XML Export Integrity:  VALID [OK]
=====
(LAN)(kali@Damithu)-[/mnt/c/Users/damit/OneDrive/Desktop/LAN_Scanner/Week_07_UI_Backend_Integration_and_Validation]
$
```

```
(venv_virtualbox)-(kali@kali)-[/media/sf_LAN_Scanner/Week_07_UI_Backend_Integration_and_Validation]
$ python3 tools/simulate_ui_integration.py
=====
HEADLESS UI INTEGRATION & EXPORT SIMULATOR
=====
[*] Validating UI Payload Contract...
    Payload Schema Validation: PASSED [OK]

[*] Testing Throttled Callback Dispatcher (50 rapid updates)...
    [UI Screen Render] Progress: 1/100 (1.0%)
    [UI Screen Render] Progress: 20/100 (20.0%)
    [UI Screen Render] Progress: 38/100 (38.0%)
    [UI Screen Render] Progress: 57/100 (57.0%)
    [UI Screen Render] Progress: 75/100 (75.0%)
    [UI Screen Render] Progress: 93/100 (93.0%)
    [UI Screen Render] Progress: 100/100 (100.0%)
    Total Backend Invocations: 100
    Total UI Render Events: 7 (Render throttled to save CPU!)

[*] Generating Multi-Format Report Exports...
    JSON Export Integrity: VALID [OK]
    CSV Export Integrity:  VALID [OK]
    XML Export Integrity:  VALID [OK]
=====
(venv_virtualbox)-(kali@kali)-[/media/sf_LAN_Scanner/Week_07_UI_Backend_Integration_and_Validation]
$
```

#### • Expected Simulator Output:

```
=====
HEADLESS UI INTEGRATION & EXPORT SIMULATOR
=====
[*] Validating UI Payload Contract...
    Payload Schema Validation: PASSED [OK]

[*] Testing Throttled Callback Dispatcher (50 rapid updates)...
    [UI Screen Render] Progress: 1/100 (1.0%)
    [UI Screen Render] Progress: 27/100 (27.0%)
    [UI Screen Render] Progress: 58/100 (58.0%)
```

```
[UI Screen Render] Progress: 89/100 (89.0%)
[UI Screen Render] Progress: 100/100 (100.0%)
Total Backend Invocations: 100
Total UI Render Events: 5 (Render throttled to save CPU!)
```

```
[*] Generating Multi-Format Report Exports...
JSON Export Integrity: VALID [OK]
CSV Export Integrity: VALID [OK]
XML Export Integrity: VALID [OK]
```

---

### 3. Executing Automated QA Unit Tests (pytest)

To run all 9 automated unit tests covering data contracts, burst callback throttling, and report file integrity:

```
# Windows PowerShell:
python -m pytest tests -v
```

```
# WSL 2 Kali Linux:
pytest tests -v
```

#### • Expected Test Verification Output:

```
tests/test_export_integrity.py::test_json_export_and_validation PASSED [ 11%]
tests/test_export_integrity.py::test_csv_export_and_validation PASSED [ 22%]
tests/test_export_integrity.py::test_xml_export_and_validation PASSED [ 33%]
tests/test_export_integrity.py::test_empty_or_corrupt_file_validation PASSED [ 44%]
tests/test_ui_adapter.py::test_valid_payload_contract PASSED [ 55%]
tests/test_ui_adapter.py::test_missing_mandatory_keys PASSED [ 66%]
tests/test_ui_adapter.py::test_invalid_field_types PASSED [ 77%]
tests/test_ui_adapter.py::test_throttled_callback_under_burst_load PASSED [ 88%]
tests/test_ui_adapter.py::test_ui_exception_card_generation PASSED [100%]

===== 9 passed in 0.12s
=====
```

```

(LAN)(kali@Damithu)-[/mnt/c/Users/damit/OneDrive/Desktop/LAN_Scanner/Week_07_UI_Backend_Integration_and_Validation]
$ pytest tests -v
===== test session starts =====
platform linux -- Python 3.14.7, pytest-9.1.1, pluggy-1.6.0 -- /mnt/c/Users/damit/OneDrive/Desktop/LAN_Scanner/Week_07_UI_Backend_Integration_and_Validation
/venv_wsl/bin/python3
cachedir: .pytest_cache
rootdir: /mnt/c/Users/damit/OneDrive/Desktop/LAN_Scanner/Week_07_UI_Backend_Integration_and_Validation
collected 9 items

tests/test_export_integrity.py::test_json_export_and_validation PASSED [ 11%]
tests/test_export_integrity.py::test_csv_export_and_validation PASSED [ 22%]
tests/test_export_integrity.py::test_xml_export_and_validation PASSED [ 33%]
tests/test_export_integrity.py::test_empty_or_corrupt_file_validation PASSED [ 44%]
tests/test_ui_adapter.py::test_valid_payload_contract PASSED [ 55%]
tests/test_ui_adapter.py::test_missing_mandatory_keys PASSED [ 66%]
tests/test_ui_adapter.py::test_invalid_field_types PASSED [ 77%]
tests/test_ui_adapter.py::test_throttled_callback_under_burst_load PASSED [ 88%]
tests/test_ui_adapter.py::test_ui_exception_card_generation PASSED [100%]

===== 9 passed in 0.14s =====
(LAN)(kali@Damithu)-[/mnt/c/Users/damit/OneDrive/Desktop/LAN_Scanner/Week_07_UI_Backend_Integration_and_Validation]
$

```

```

(venv_virtualbox)-(kali@kali)-[/media/sf_LAN_Scanner/Week_07_UI_Backend_Integration_and_Validation]
$ pytest tests -v
===== test session starts =====
platform linux -- Python 3.14.7, pytest-9.1.1, pluggy-1.6.0 -- /home/kali/venv_virtualbox/bin/python3
cachedir: .pytest_cache
rootdir: /media/sf_LAN_Scanner/Week_07_UI_Backend_Integration_and_Validation
plugins: cov-7.1.0
collected 9 items

tests/test_export_integrity.py::test_json_export_and_validation PASSED [ 11%]
tests/test_export_integrity.py::test_csv_export_and_validation PASSED [ 22%]
tests/test_export_integrity.py::test_xml_export_and_validation PASSED [ 33%]
tests/test_export_integrity.py::test_empty_or_corrupt_file_validation PASSED [ 44%]
tests/test_ui_adapter.py::test_valid_payload_contract PASSED [ 55%]
tests/test_ui_adapter.py::test_missing_mandatory_keys PASSED [ 66%]
tests/test_ui_adapter.py::test_invalid_field_types PASSED [ 77%]
tests/test_ui_adapter.py::test_throttled_callback_under_burst_load PASSED [ 88%]
tests/test_ui_adapter.py::test_ui_exception_card_generation PASSED [100%]

===== 9 passed in 0.55s =====
(venv_virtualbox)-(kali@kali)-[/media/sf_LAN_Scanner/Week_07_UI_Backend_Integration_and_Validation]
$

```

### Part 3: Week 7 Technical Terms & Concepts Glossary

This glossary provides formal technical definitions alongside intuitive, non-IT real-world analogies for key software architecture, UI event handling, and data integrity concepts introduced in Week 7:

#### 1. Decoupled Architecture

**Technical Definition:** A software engineering design pattern where components (such as the scanning backend engine and the graphical/CLI frontend interface) operate independently, communicating solely through well-defined data contracts without direct internal dependencies.

**Real-World Analogy:** A television and a remote control; as long as the infrared signal standard is maintained, you can replace or upgrade the remote control without rebuilding the inside of the television screen.

#### 2. Data Contract

**Technical Definition:** A formal, agreed-upon specification defining the structure, fields, data types, and constraints of data exchanged between distinct software subsystems or microservices.

**Real-World Analogy:** A standardized paper loan application form; both the customer and the bank agree that Box A must contain a name, Box B an income, and Box C a signature.

#### 3. Event Throttling & Debouncing

**Technical Definition:** Techniques used to limit the execution rate of an event handler. Throttling ensures a function executes at most once per specified time interval (e.g., maximum 20 times per second), regardless of how many times it was triggered.

**Real-World Analogy:** An elevator door button; even if an impatient person presses the button 50 times in 3 seconds, the elevator engine only processes one smooth door-close operation.

#### 4. Event Loop Starvation

**Technical Definition:** A condition in asynchronous or GUI applications where high-frequency CPU or I/O events monopolize the main execution thread, preventing the GUI framework from processing paint, redraw, or user-click events, causing the window to freeze.

**Real-World Analogy:** A bank teller bombarded with so many questions simultaneously that they freeze up and cannot serve anyone standing in line.

#### 5. Serialization & Deserialization

**Technical Definition:** Serialization is converting an in-memory object graph into a standardized stream of bytes or text (like JSON or XML) for storage. Deserialization is the reverse process of reconstructing an in-memory object from text.

**Real-World Analogy:** Disassembling a bicycle, packing the parts into a flat cardboard box for shipping (serialization), and reassembling the bicycle upon arrival (deserialization).

## 6. JSON (JavaScript Object Notation)

**Technical Definition:** A lightweight, text-based, language-independent data interchange format utilizing human-readable key-value pairs and ordered lists.

**Real-World Analogy:** A structured digital index card organized neatly with bullet points and clear category headings.

## 7. CSV (Comma-Separated Values)

**Technical Definition:** A simple, tabular text format where each line represents a data record and individual fields within the record are delimited by commas.

**Real-World Analogy:** A spreadsheet printed onto plain paper with clear columns and rows.

## 8. XML (Extensible Markup Language)

**Technical Definition:** A markup language defining a set of rules for encoding documents in a format that is both human-readable and machine-readable, utilizing nested tags with attributes.

**Real-World Analogy:** A Russian nesting doll where every box contains another neatly labeled box explaining what is inside.