


Packet Tracer Simulation - TCP and UDP Communications

Topology



Objectives

Part 1: Generate Network Traffic in Simulation Mode

Part 2: Examine the Functionality of the TCP and UDP Protocols

Background

This simulation activity is intended to provide a foundation for understanding the TCP and UDP in detail. Simulation mode provides the ability to view the functionality of the different protocols.

As data moves through the network, it is broken down into smaller pieces and identified in some fashion so that the pieces can be put back together. Each of these pieces is assigned a specific name (protocol data unit [PDU]) and associated with a specific layer. Packet Tracer Simulation mode enables the user to view each of the protocols and the associated PDU. The steps outlined below lead the user through the process of requesting services using various applications available on a client PC.

This activity provides an opportunity to explore the functionality of the TCP and UDP protocols, multiplexing and the function of port numbers in determining which local application requested the data or is sending the data.

Part 1: Generate Network Traffic in Simulation Mode

Step 1: Generate traffic to populate Address Resolution Protocol (ARP) tables.

Perform the following tasks task to reduce the amount of network traffic viewed in the simulation.

- Click **MultiServer** and click the **Desktop** tab > **Command Prompt**.
- Enter the **ping 192.168.1.255** command. This will take a few seconds as every device on the network responds to **MultiServer**.
- Close the **MultiServer** window.

Step 2: Generate web (HTTP) traffic.

- a. Switch to Simulation mode.
- b. Click **HTTP Client** and click the **Desktop** tab > **Web Browser**.
- c. In the URL field, enter **192.168.1.254** and click **Go**. Envelopes (PDUs) will appear in the simulation window.
- d. Minimize, but do not close, the **HTTP Client** configuration window.

Step 3: Generate FTP traffic.

- a. Click **FTP Client** and click the **Desktop** tab > **Command Prompt**.
- b. Enter the **ftp 192.168.1.254** command. PDUs will appear in the simulation window.
- c. Minimize, but do not close, the **FTP Client** configuration window.

Step 4: Generate DNS traffic.

- a. Click **DNS Client** and click the **Desktop** tab > **Command Prompt**.
- b. Enter the **nslookup multiserver.pt.ptu** command. A PDU will appear in the simulation window.
- c. Minimize, but do not close, the **DNS Client** configuration window.

Step 5: Generate Email traffic.

- a. Click **E-Mail Client** and click the **Desktop** tab > **E Mail** tool.
- b. Click **Compose** and enter the following information:
 - 1) **To:** user@multiserver.pt.ptu
 - 2) **Subject:** Personalize the subject line
 - 3) **E-Mail Body:** Personalize the Email
- c. Click **Send**.
- d. Minimize, but do not close, the **E-Mail Client** configuration window.

Step 6: Verify that the traffic is generated and ready for simulation.

Every client computer should have PDUs listed in the Simulation Panel.

Part 2: Examine Functionality of the TCP and UDP Protocols

Step 1: Examine multiplexing as all of the traffic crosses the network.

You will now use the **Capture/Forward** button and the **Back** button in the Simulation Panel.

- a. Click **Capture/Forward** once. All of the PDUs are transferred to the switch.
- b. Click **Capture/Forward** again. Some of the PDUs disappear. What do you think happened to them?
When we click Capture/Forward in Packet Tracer, some PDUs are disappearing. This happens because they've either reached their final destination or been processed by a network device like a router or switch.
- c. Click **Capture/Forward** six times. All clients should have received a reply. Note that only one PDU can cross a wire in each direction at any given time. What is this called?
When we click Capture/Forward six times, all clients should have received a reply. We might notice that only one PDU can travel in each direction on a wire at a time. This is called full-duplex communication, where data can move both ways at the same time, but only one packet is sent in each direction at any

- d. A variety of PDUs appears in the event list in the upper right pane of the simulation window. Why are they so many different colors?

The PDUs in the event list are shown in different colors because each color represents a specific protocol being used in the communication. This helps us quickly identify which protocol is handling each

- e. Click **Back** eight times. This should reset the simulation.

Note: Do not click **Reset Simulation** any time during this activity; if you do, you will need to repeat the steps in Part 1.

Step 2: Examine HTTP traffic as the clients communicate with the server.

- a. Filter the traffic that is currently displayed to display only **HTTP** and **TCP** PDUs filter the traffic that is currently displayed:
 - 1) Click **Edit Filters** and toggle the **Show All/None** check box.
 - 2) Select **HTTP** and **TCP**. Click anywhere outside of the Edit Filters box to hide it. The Visible Events should now display only **HTTP** and **TCP** PDUs.
- b. Click **Capture/Forward**. Hold your mouse above each PDU until you find one that originates from **HTTP Client**. Click the PDU envelope to open it.

- c. Click the **Inbound PDU Details** tab and scroll down to the last section. What is the section labeled?
TCP

Are these communications considered to be reliable?

As for whether the communications are reliable, the answer is yes. Since HTTP relies on TCP, the communication is considered reliable. TCP ensures that the data is sent correctly and in order. It does

- d. Record the **SRC PORT**, **DEST PORT**, **SEQUENCE NUM**, and **ACK NUM** values. What is written in the field to the left of the **WINDOW** field?
SRC PORT: 1025 , DEST PORT: 80, SEQUENCE NUM: 0, ACK NUM: 0 . URGENT POINTER: 0x0000

- e. Close the PDU and click **Capture/Forward** until a PDU returns to the **HTTP Client** with a checkmark.

- f. Click the PDU envelope and select **Inbound PDU Details**. How are the port and sequence numbers different than before?
the value of SRC PORT and DEST PORT is shift with each other. while the SEQUENCE NUM is same as before but the ACK NUM is change into 1

- g. There is a second **PDU** of a different color, which **HTTP Client** has prepared to send to **MultiServer**. This is the beginning of the HTTP communication. Click this second PDU envelope and select **Outbound PDU Details**.

- h. What information is now listed in the TCP section? How are the port and sequence numbers different from the previous two PDUs?
SRC PORT: 1025, DEST PORT: 80, SEQUENCE NUM: 1, ACK NUM: 1. it only different at the sequence number where it has value 1 while both previous two PDUs has 0.

- i. Click **Back** until the simulation is reset.

Step 3: Examine FTP traffic as the clients communicate with the server.

- a. In the Simulation Panel, change **Edit Filters** to display only **FTP** and **TCP**.
- b. Click **Capture/Forward**. Hold your cursor above each PDU until you find one that originates from **FTP Client**. Click that PDU envelope to open it.
- c. Click the **Inbound PDU Details** tab and scroll down to the last section. What is the section labeled?
TCP section

Are these communications considered to be reliable?

As for whether the communications are reliable, yes, FTP over TCP is considered reliable. This is because TCP ensures that all data sent during the FTP session is delivered correctly and in the proper order.

- d. Record the **SRC PORT**, **DEST PORT**, **SEQUENCE NUM**, and **ACK NUM** values. What is written in the field to the left of the **WINDOW** field?
SRC PORT: 1025, DEST PORT: 21, SEQUENCE NUM: 0, ACK NUM: 0. URGENT POINTER: 0x0000
- e. Close the PDU and click **Capture/Forward** until a PDU returns to the **FTP Client** with a checkmark.
- f. Click the PDU envelope and select **Inbound PDU Details**. How are the port and sequence numbers different than before?
values of SRC PORT and DEST PORT is switch with each other. while the SEQUENCE NUM is same as before but the ACK NUM is change into 1
- g. Click the **Outbound PDU Details** tab. How are the port and sequence numbers different from the previous two results?
SRC PORT: 1025, DEST PORT: 21, SEQUENCE NUM: 1, ACK NUM: 1. it only different at the sequence number where it has value 1 while both previous two PDUs has 0.
- h. Close the PDU and click **Capture/Forward** until a second PDU returns to the **FTP Client**. The PDU is a different color.
- i. Open the PDU and select **Inbound PDU Details**. Scroll down past the TCP section. What is the message from the server?
Message: Welcome to PT Ftp server
- j. Click **Back** until the simulation is reset.

Step 4: Examine DNS traffic as the clients communicate with the server.

- a. In the Simulation Panel, change **Edit Filters** to display only **DNS** and **UDP**.
- b. Click the PDU envelope to open it.
- c. Click the **Inbound PDU Details** tab and scroll down to the last section. What is the section labeled?
DNS Query

Are these communications considered to be reliable?
- d. Record the **SRC PORT** and **DEST PORT** values. Why is there no sequence and acknowledgement number?
SRC PORT: 1025, DEST PORT: 53. There are no sequence and acknowledgment numbers in DNS traffic because UDP does not use them. Unlike TCP, UDP is stateless, meaning that each packet is treated independently.
- e. Close the PDU and click **Capture/Forward** until a PDU returns to the **DNS Client** with a checkmark.
- f. Click the PDU envelope and select **Inbound PDU Details**. How are the port and sequence numbers different than before?
values of SRC PORT and DEST PORT is switch with each other.
- g. What is the last section of the PDU called?
DNS Answer
- h. Click **Back** until the simulation is reset.

Step 5: Examine email traffic as the clients communicate with the server.

- a. In the Simulation Panel, change **Edit Filters** to display only **POP3**, **SMTP** and **TCP**.

- b. Click **Capture/Forward**. Hold your cursor above each PDU until you find one that originates from **E-mail Client**. Click that PDU envelope to open it.
- c. Click the **Inbound PDU Details** tab and scroll down to the last section. What transport layer protocol does email traffic use?
TCP

Are these communications considered to be reliable?
Yes, email communications using POP3 and SMTP are considered reliable because they rely on TCP. TCP is a connection-oriented protocol that ensures the data is delivered accurately. It does this by:

d. Record the **SRC PORT**, **DEST PORT**, **SEQUENCE NUM**, and **ACK NUM** values. What is written in the field to the left of the **WINDOW** field?
SRC PORT: 1025, DEST PORT: 25, SEQUENCE NUM: 0, ACK NUM: 0. URGENT POINTER: 0x0000

e. Close the **PDU** and click **Capture/Forward** until a PDU returns to the **E-Mail Client** with a checkmark.

f. Click the PDU envelope and select **Inbound PDU Details**. How are the port and sequence numbers different than before?
value of SRC PORT and DEST PORT is switch with each other. while the SEQUENCE NUM is same as before but the ACK NUM is change into 1

g. Click the **Outbound PDU Details** tab. How are the port and sequence numbers different from the previous two results?
SRC PORT: 1025, DEST PORT: 25, SEQUENCE NUM: 1, ACK NUM: 1. it only different at the sequence number where it has value 1 while both previous two PDUs has 0.

h. There is a second **PDU** of a different color that **HTTP Client** has prepared to send to **MultiServer**. This is the beginning of the email communication. Click this second PDU envelope and select **Outbound PDU Details**.

i. How are the port and sequence numbers different from the previous two **PDUs**?
there is no different for the values of the ports and sequence number

j. What email protocol is associated with TCP port 25? What protocol is associated with TCP port 110?

k. Click **Back** until the simulation is reset.

Step 6: Examine the use of port numbers from the server.

- a. To see TCP active sessions, perform the following steps in quick succession:
 - 1) Switch back to **Realtime** mode.
 - 2) Click **MultiServer** and click the **Desktop** tab > **Command Prompt**.
- b. Enter the **netstat** command. What protocols are listed in the left column?
What port numbers are being used by the server?
TCP 192.168.1.254:21

c. What states are the sessions in?
ESTABLISHED

d. Repeat the **netstat** command several times until you see only one session still ESTABLISHED. For which service is this connection still open? TCP 192.168.1.254:21 192.168.1.254:1025

Why doesn't this session close like the other three? (Hint: Check the minimized clients)

The session doesn't close like the others because the client application is still running in the background, even if it's minimized. For example, a web browser might still be connected to a server, or an email client

Suggested Scoring Rubric

Activity Section	Question Location	Possible Points	Earned Points
Part 2: Examine Functionality of the TCP and UDP Protocols	Step 1	15	15
	Step 2	15	15
	Step 3	15	15
	Step 4	15	15
	Step 5	15	15
	Step 6	25	10
Total Score		100	85