

EMSOL is all about reducing emissions and improving performance from combustion of fossil fuels, be it Diesel, Petrol, Kerosene or Furnace Oil. In a nut shell, EMSOL helps in reducing Air Pollution and Fuel Costs while improving performance of vehicles, power generators and steam boilers and industrial equipment powered by liquid fossil fuels.

EMSOL offers specific products for Automobiles, Marine crafts and Generators powered by Diesel, Petrol & Kerosene fuels. Also for Diesel & Furnace Oil fired Steam Boilers, Industrial Driers & Heaters.

Air pollution is threatening the healthy existence of all creatures due to ever advancing human life style on earth. Transport Industry is known to be the single most contributing sector that pollutes air, adding highly toxic gases and particulate matter that leads to a number of respiratory system related illnesses in human beings. The cost of environmental air pollution is rather difficult to estimate, because the effects are multi factorial. Air Pollution has an impact on plant growth & food production, water resources, roads & buildings, metal corrosion and corrosion protection, industrial production processes and above all, has a direct impact on human & animal health, causing diseases, life-long suffering and premature deaths.

EMSOL gives you a smooth, trouble free and efficient operation, prolonging the life of your vehicle or the equipment, even if you disregard all the positive benefits of EMSOL towards the environment you live in.

EMSOL- (Fuel System Cleaner) for Diesel, Petrol & Kerosene powered Vehicles

FSC:



Colour: Light Green

Application: Designed for cleaning the fuel system in engines (Motor Vehicles and

Marine engines)and intended to be used in following conditions

1. High Smoke Emission (Black or White)& Emission test failure
2. Carburetor & EFI system clean-ups and engine tuning
3. Common Rail Diesel system Clean-up and engine tuning
4. Check Engine warning
5. Reduced pulling power

Use for the FIRST TIME only in vehicles done over 25,000 kms /

engines run over 1000 Hrs. or in the event of a condition stated above

Method: Add EMSOL-FSC to **full tank** (or on ½ tank minimum) and run the vehicle as usual until the next service. for 25-30 minutes or 25-30 kms would be sufficient for emission test/re-test for 90% of vehicles.The rest may need longer running to clear heavy deposits.

Dosage : @ 1:1000 (1ml per 1Litre ±25%).

Packing: Available in 5ml sachets, 20ml, 40ml & 100ml plastic bottles for retail markets. 1L, 2L & 5L containers for corporate clients.

NOTE: Using EMSOL-FSC at every service/5000kms would help

keeping the fuel system health. This is not required if you use EMSOL-FE or EMSOL-D regularly.

EMSOL – FE (Fuel Economizer)



EMSOL-FE: (Fuel Economizer) for Diesel, Petrol & Kerosene powered Vehicles

Colour: Light Blue

Application: Intended for improving fuel economy in motor vehicles and marine engines.

Method: Add EMSOL-FE to fuel tank before or after refueling.

Dosage : @ 1:1000 (1ml per 1Litre $\pm 25\%$). Use at every re-fuelling for best economy

Packing: Available in 5ml sachets, 20ml, 40ml & 100ml plastic bottles for retail markets. 1L, 2L & 5L containers are available on special orders for fleet owners and

EMSOL-D



EMSOL-D: (Concentrate) Diesel, Petrol & Kerosene powered Vehicles and equipment

Colour: Light Orange

Application: Treatment of bulk storage tanks for fuel economy in motor vehicles, Generators and/or marine craft

Method: Add EMSOL-D to the fuel tank or to bulk storage tank. (Recommend adding before filling the b
advised if heavy smoke is prevailing or faster cleaning is desired for emission test etc.

Dosage : @ 1:2500 to 1:3000 (1ml per 2.5 to 3 Litres)

Packing: 1L, 2L & 5L Containers.(Available in 20ml, 40ml & 100ml plastic bottles on special orders)
