

Scout App v8.33 Exact Setup Guide

For someone who only has the GitHub repositories and needs to make the app work from zero: Supabase, Vercel, Gmail OAuth, cron workers, app deploy, and extension install.

Important: run these steps on your own PC. ChatGPT does not need GitHub access. The app repo is <https://github.com/damolax/Scout-app.git> and the extension repo is <https://github.com/damolax/scout-extension.git>.

1. What you are setting up

- **Scout App:** Next.js app deployed to Vercel. It manages businesses, templates, sending, replies, notifications, operations, Auto Scout, and source capture.
- **Supabase:** database, auth, row-level security, workspace membership, and all tracking tables.
- **Gmail OAuth:** allows Scout to send through connected Gmail accounts and sync replies/bounces.
- **Extension:** captures Google/Bing dorking results and imports them into the app without copy/paste.
- **Workers/Cron:** keeps replies, bounces, due schedules, follow-ups, and Auto Scout running even if the browser page is closed.

2. Prerequisites

Requirement	Use
Node.js 24.x and npm 10.x	Install and build the Next.js app. Vercel should also use Node 24.
Git Bash	Clone, copy, commit, and push the repos.
Supabase project	Database tables, auth, RLS, service role key.
Vercel project	Deploy the app and run cron jobs.
Google Cloud project	Gmail OAuth client ID, secret, and redirect URI.
Chrome or Edge	Load the Scout extension unpacked.

3. Clone and deploy the app repo

After unzipping the generated Scout App package, copy the files into the GitHub repo on your PC.

```
cd ~/Desktop

git clone https://github.com/damolax/Scout-app.git Scout-app-v833
cd Scout-app-v833

SOURCE="/c/PATH/TO/scout_app_v833_final"
cp -R "$SOURCE"/. .
rm -rf node_modules .next .git tsconfig.tsbuildinfo

npm install
npm run typecheck
npm run build

git add .
git commit -m "Build v8.33 notifications and durable jobs"
git push origin main

vercel --prod
```

4. Environment variables

Add these in Vercel Project Settings -> Environment Variables. Use Production, Preview, and Development unless you intentionally separate them.

Variable	Purpose
NEXT_PUBLIC_SUPABASE_URL	Public Supabase project URL.
NEXT_PUBLIC_SUPABASE_ANON_KEY	Public Supabase anon key.
SUPABASE_SERVICE_ROLE_KEY	Server-only service role key for workers and protected writes.
NEXT_PUBLIC_SITE_URL	Your deployed Vercel app URL.
GOOGLE_CLIENT_ID	Google OAuth client ID.
NEXT_PUBLIC_GOOGLE_CLIENT_ID	Same client ID for browser OAuth start.
GOOGLE_CLIENT_SECRET	Google OAuth client secret.
CRON_SECRET	Shared secret for Vercel cron and internal workers.
SCHEDULE_WORKER_SECRET	Optional. Can be same as CRON_SECRET.
RUN_ALL_WORKER_SECRET	Optional. Can be same as CRON_SECRET.
AUTO_SCOUT_WORKER_SECRET	Optional. Can be same as CRON_SECRET.
NEXT_PUBLIC_BACKEND_URL	Optional external backend/email finder URL if you use one.
SCOUT_DEFAULT_WORKSPACE_ID	Default workspace ID, usually 00000000-0000-4000-8000-000000000001.

5. Supabase database setup

Run the migrations in Supabase SQL Editor. For a fresh setup, run the migration files in chronological order from the repo. For an existing v8.32 install, at minimum run the new v8.33 migration.

```
supabase/migrations/202607100833_notifications_durable_jobs.sql
```

- Creates **app_notifications** so replies and worker signals stay visible after refresh.
- Adds heartbeat/resume fields to **message_schedules**.
- Adds helper function **get_active_scout_jobs()**.
- Keeps RLS policies tied to workspace membership.

6. Supabase Auth

- Enable email/password sign-in in Supabase Authentication.
- Add the app URL to allowed redirect URLs if Supabase asks for it.
- The default workspace is created by the base migration.
- The user configured as admin in the migration is auto-approved. Other users need workspace membership/approval if you customize access.

7. Google OAuth setup

Step	Action
OAuth consent screen	Create/configure an external or internal app. Add Gmail scopes needed for send/read.
Credentials	Create OAuth Client ID -> Web application.
Authorized JavaScript origins	Add your Vercel URL, for example https://your-app.vercel.app .
Authorized redirect URI	Add https://your-app.vercel.app/api/gmail/oauth/callback .
Vercel env	Set <code>GOOGLE_CLIENT_ID</code> , <code>NEXT_PUBLIC_GOOGLE_CLIENT_ID</code> , and <code>GOOGLE_CLIENT_SECRET</code> .
Reconnect Gmail	Open Scout -> Settings -> connect each sender account.

8. Cron and durable jobs

The app has Vercel cron paths in `vercel.json`. The important one is the full autopilot worker. It runs hourly and handles inbox sync, bounces, due schedules, follow-ups, Auto Scout, and status repair.

```
/api/workers/run-all?workspaceId=00000000-0000-4000-8000-000000000001&includeSeedTest=false
```

- Manual sends from the Message page are saved as durable schedules before sending starts.
- If the browser page closes, the schedule still exists in Supabase.
- If a worker times out, a later worker can reset stale running schedules and continue with remaining Ready contacts.
- Auto Scout jobs live in `email_research_jobs`, so they remain queued/running even when you leave the page.

9. Deploy the extension repo

```
cd ~/Desktop

git clone https://github.com/damolax/scout-extension.git scout-extension-v65
cd scout-extension-v65

SOURCE="/c/PATH/T0/scout_extension_v65_package/chrome-extension"
cp -R "$SOURCE"/. .
rm -rf .git/*.lock

git add .
git commit -m "Build v6.5 autonomous dorking ingest"
git push origin main
```

10. Load and configure the extension

- Open chrome://extensions or edge://extensions.
- Enable Developer Mode.
- Click Load unpacked.
- Select the extension folder.
- Open the extension popup and add your Scout App URL plus workspace key.
- Run Google/Bing dorking and capture/import results directly to Scout.

11. Final validation checklist

Test	Expected result
Login	Dashboard opens with workspace name.
Settings -> Gmail	Connected Gmail account shows connected/ready.
Templates	Initial, follow-up, and reply templates are separated.
Source Scout / Extension	Google/Bing results import without copy/paste.
Auto Scout	Jobs appear as queued/running/done and continue after page leave.
Message -> Start Send	Creates a durable job in schedules instead of only a browser loop.
Operations -> Full Autopilot	Runs replies, bounces, schedules, and Auto Scout.
Replies	Real replies and auto replies appear after Gmail sync.
Notifications	Persistent notification appears for real replies and worker signals.