DAMON Requirements for (More) Access-aware MM of Future

SeongJae (SJ) Park <sj@kernel.org>

https://damonitor.github.io

Recent Proposals for (More) Access-aware MM of Future

- Workingset reporting
- CXL Hotness Monitoring Unit
- Promotion of unmapped page cache folios (or, folio_mark_accessed()-based pages promotion)
- PTE A bit-based pages promotion kernel thread (kmmscand)
- AMD IBS-based pages promotion kernel thread (kpromoted)
- MGLRU-based pages promotion kernel thread (klruscand)
- Memory tiering per-cgroup fairness

Requirements for (More) Access-aware MM of Future

- Multiple sources of access information
 - (MG)LRU, file I/O, Accessed bits, CXL HMU, AMD IBS, ...
- Fancy controls of management operations
 - Unblock main workloads' progress
 - Tasks/cgroups level fairness

How DAMON Could Help Multiple Sources Information Requirement

- DAMON Operations Set layer:
 - Address space/fundamental feature (A-bit, LRU activeness, IBS, ...) specific operations layer
 - Core layer pulls the information and distills those into DAMON-region abstraction
 - Get overhead/accuracy tradeoff
 - Use of DAMON-region is not mandated (hacky, though)
 - API callers can implement and use their operations set with the sources

```
/**
 * struct damon_operations - Monitoring operations for given use cases.
[...]
 * @prepare_access_checks should manipulate the monitoring regions to be
 * prepared for the next access check.
 * @check_accesses should check the accesses to each region that made after the
 * last preparation and update the number of observed accesses of each region.
[...]
    void (*prepare_access_checks)(struct damon_ctx *context);
    unsigned int (*check_accesses)(struct damon_ctx *context);
```

How DAMON Could Help Fancy Memory Management Operations

- DAMOS (auto-tuned) quotas for resource usages
 - Give quotas tuning feedback loop input with appropriate data
 - Users can provide arbitrary input or use DAMON self-retrievable metrics
- DAMOS filters for fine target pages selection

How DAMON in Future Could Better Help

- Be a better DAMON: less overhead and more accuracy
 - Efforts are ongoing: Page level monitoring, Intervals auto-tuning, ...
- Optimized API for access reporting (pushing information)
- Less hacky optional (dis)use of DAMON region abstraction
 - For both monitoring and memory management operations
- Direct folio-level use of controlled memory management operations engine
- DAMOS tuning goal metrics and filter for more use cases including per-cgroup per-node memory usages

DAMON API for Pushing Access Information

```
+/**
 * damon report access - Report identified access events to DAMON.
   @pid:
                       The PID of the virual address space of the address.
                       NULL if it is of the physical address.
   @addr:
                      The start address of the access made region
              Size of the region that the access events were made.
   @size:
   @nr_accesses: Number of detected accesses to the address range.
   @node_id:
              NUMA node that made the accesses.
 * Report access events to DAMON. Can be called from any context.
+void damon_report_access(struct pid *pid, unsigned long addr, unsigned long size,
               unsigned int nr_accesses, int node_id)
```

DAMOS API for Folio Level Async/Controlled Memory Operations

```
+/**
   damos add folios - Add a list of folios as highest priority target for given
                      damos.
   @scheme: DAMOS scheme for the specific access-aware operation.
   @folios: List of folios to apply the access-aware operation.
+ * If a kernel component finds folios that eligible for a specific memory
  * management operation (e.g., CXL-promotion or demotion), execution of the
 * operation can be requested to be done by DAMOS using this function. The
 * execution of the operation will be asynchronously done by DAMOS worker
+ * thread. DAMOS features for resource control (DAMOS quotas) will also be
 * applied.
+void damos_add_folios(struct damos *scheme, struct list_head *folios)
```

Current Plans

- damon_report_access() will be "RFC PATCH"-ed in near future
 - Use cases: per-CPU, write-only monitoring
 - Milestones: Page faults-based operations set, AMD IBS-based one, other h/w feature based ones
- damos_add_folios() plan is not clear
 - Not sure if there is a real use case, make your voice

Discussion Points

- We may need this first
- We ain't gonna need this
- You're missing this

Backup Slides

DAMON Stack, In a Future

