DAMON Updates and Plans:

Tiering, Monitoring, DAMON-X, and THP

SeongJae Park (SJ) <sj@kernel.org> <sjpark@crusoe.ai>

From: SJ, On Behalf Of damon@

Aaron Yang
Akinobu Mita
Alexandre Ghiti
Andrew Morton
Arnd Bergmann
Asier Gutierrez
Balbir Singh
Bijan Tabatabai
Bjorn Helgaas
Cheng-Han Wu
Dan Carpenter
Enze Li
Honggyu Kim
Jackie Liu
JaeJoon Jung
jianyun.gao
Josh Law
Kees Cook
Kevin Lourenco
Liew Rui Yan
Linus Torvalds
Li RongQing
Lokesh Gidra
Lorenzo Stoakes
Nathan Gao
Qianfeng Rong
qinyu
Quanmin Yan
Raul Pazemecxas De Andrade
Ravi Jonnalagadda
Sang-Heon Jeon
SeongJae Park
Shakeel Butt
Shu Anzai
Stanislav Fort
Su Hui
Swaraj Gaikwad
Taotao Chen
Thushara.M.S
Vineeth Pillai
Yueyang Pan
Yunjeong Mun

42 authors, 469 commits since 2025-03-26 (LSFMMBPF 2025)

DAMON in Nutshell

DAMON in One Sentence

“DAMON is a Linux kernel subsystem for efficient access monitoring and access-aware system operations.”

High Level Implementation

- Spawn a kernel thread that does
- See if each page is accessed, every 5ms
- Inform users the findings, every 100ms
- Time intervals can be [auto-]tuned

Providing Access Information

- Location
- Frequency
- Stability
- Recency



Access pattern heatmap of Splash2x/Raytrace

Design

- Goals: Accurate, Lightweight, Tunable and Automated
- Mechanisms: Sampling, Adaptive regions, Sysfs interface, Feedback loops
- Results
  - <0.1% CPU overhead on products

Availability and Usages

- Available on >=5.15 upstream kernels
- Enabled on most distro kernels
- Being used for products and researches

DAMOS: Second Face of DAMON

- DAMon-based Operation Schemes
  - “Page out cold memory”
  - “Migrate hot/cold pages to DRAM/CXL node”
- Turn DAMON into access-aware memory management system operations engine

Community

- Public channels
  - Mailing list: damon@lists.linux.dev
  - Project website: https://damonitor.github.io/
- Private channels
  - Maintainer email: sj@kernel.org
  - DAMON Beer/Coffee/Tea Meetup

DAMON in One Sentence

“DAMON is a Linux kernel subsystem for efficient access monitoring and access-aware system operations.”

Table Of Contents (55 mins)

- Updates from LSFMMBPF 25
  - Memory Tiering (10 mins)
  - Data Attributes Monitoring (10 mins)
- New for LSFMMBPF 26
  - Page Faults or Alternatives for DAMON (15 mins)
  - DAMON-X (5 mins)
  - Access-aware THP (15 mins)

Memory Tiering

LSFMMBPF’25 Recap

- SK hynix developed DAMOS_MIGRATE (6.11)
  - For CXL capacity extension of HMSDK
  - DAMOS_MIGRATE hot/cold data DRAM ↔ CXL
  - Static hot/cold threshold
- SJ was developing TPP-DAMON
  - Auto-tune thresholds for high DRAM utilization
  - Achieved ~4.42% Taobench score increase

Multi-thread Tiering (SK hynix)

- Per-subregion DAMON worker thread
  - Accelerate hot/cold pages finding
  - Accelerate migrations
- Achieves ~94% llama.cpp speedup

Dynamic Interleaving (Micron)

- Extend DAMOS_MIGRATE
  - Multiple destination nodes with their weights
  - For dynamic interleave weights
  - Works on virtual address only
- Achieves ~25% benchmark speedup
- Merged into 6.17

Interleaving Auto-tune (Micron)

- Add new DAMOS auto-tune goal
  - For physical address based dynamic interleaving
  - Example usage: x:y hot memory interleaving
    - Migrate hot data CXL→DRAM for X% hot data in DRAM
    - Migrate hot data DRAM→CXL for Y% hot data in CXL
- Merged into mm-new after 7.1-rc1

TPP-DAMON

- Merged into 6.16
- Cgroup-aware extension developed (6.19)
- Positive test results privately shared
- No more active development is planned (Support mode)

NUMA-TPP-DAMON

- Tiering: special case NUMA management
  - Single accessor (CPU node)
  - Single promotion/demotion path
- General NUMA: N Accessors
  - CPU, GPU, *PU
  - N promotion/demotion paths
  - Idea: run accessor-aware TPP for each path

NUMA-TPP-DAMON in Example

- TPP1 migrate CPU1-hot/cold memory
  - for DRAM1 ↔ CXL.mem1 ↔ DRAM2 ↔ CXL.mem2 path
- TPP2 migrate CPU2-hot/cold memory
  - for DRAM2 ↔ CXL.mem2 ↔ DRAM1 ↔ CXL.mem1 path



Possible NUMA topology

	CPU1	CPU2
DRAM1	10	50
CXL.mem1	20	60
DRAM2	50	10
CXL.mem2	60	20

Relative access speed from CPU to memory

NUMA-TPP-DAMON Status

- Brainstorming level early planning
  - Idea is shared on LPC’25 special-mm uconf
- Challenge: per-accessor monitoring

Inputs?

- ~10:15

Data Attributes Monitoring (was: light-weight cgroups monitoring)

LSFMMBPF’25 Recap

- Meta developed page level monitoring
  - Show how many bytes in each DAMON-region
    - Hugepage, belong to specific cgroup, etc
- Challenge: High Overhead
  - Filters are applied in folio level

Page Level Monitoring Updates

- Essential changes are merged into 6.15
- Meta extended hugepage support for virtual address spaces (merged into 6.18)
- Idea for fleet-wide monitoring is shared
  - Machine-level sampling

Data Attrs Monitoring

- Sampling-based page level monitoring
- Let users register multiple probes
  - Each probe is for each data attribute to monitor
  - Each probe constitutes DAMOS filter-like filters
- For each access-sample page, apply probes
- Count/expose per-region per-probe hits

Attrs Monitoring: Outcomes

- Lightweight, Scalable
  - Access sampling is reused
  - Region-adjustment is applied
- Accuracy is arguable
  - Usefulness depends on multiple factors
  - Page level monitoring could be used together

Attrs Monitoring: Status

- First RFC is shared
  - Supports page anonymity monitoring
- Aiming to drop RFC with
  - More stabilized user interface
  - Cgroup support

Attrs Monitoring: Future Plan

- Data access as a data attribute
  - Add pg_idle DAMON filter
  - Allow attr-based region merge/split
- Extend for richer access check primitives
  - Add DAMON filters for page faults, PMU, etc
  - Path forward to NUMA-TPP-DAMON

Inputs?

- ~10:25

Page Faults or Alternatives for DAMON

Motivation

- Per-NUMA/CPUs/threads monitoring
  - For cache-aware sched_ext
  - For NUMA-TPP-DAMON
- Per-reads/writes monitoring
  - For easiest live migration target VM finding
  - For easiest KSM merge candidates finding

Challenge: Lack of Information

- pg_idle: DAMON’s access check primitive
  - Lacks accessor, type of access information
- Solution: use other primitives
  - Page fault events
  - PMU (e.g., AMD IBS)

NUMA Hinting Faults

- NUMA balancing’s access check primitive
- Mark a page not exists (PTE) but accessible (vma)
- Page fault handler notifies faults on marked pages to NUMA balancing

NUMA Hinting for DAMON

- Prototype with (very dirty) hack exists
- Problems
  - Making page fault handling code dirty
  - Interference between DAMON and NUMA balancing

NUMA Hinting Cleanup

- Cleanup should come first
- Apparently no doubt todo
- Uffd workingset detection does a sort of cleanup

NUMA Hinting Interference

- NUMA balancing and DAMON can show faults that are caused by each other
- Intuitively odd behavior

Option 1: Build-time Isolation

- Disallow building NUMA balancing and page fault-mode DAMON together
- Advantage: simple
- Disadvantage: inflexible

Option 2: Runtime Isolation

- Let them exclusively enabled in runtime
- Ask them to uninstall installed marks before disabled

Option 3: Partial isolation

- Let them exclusively enabled in runtime
- Let them show each other-installed protections
  - In a sense, NUMA balancing interferes past/future enabled instances already

Option 4: Let Them Interfere

- Inform faults to both NUMA balancing and DAMON if they are enabled
- Any real problem from the interference?
  - No problem from DAMON’s perspective
- Concurrent usages would be rare anyway

Proposal

- Cleanup is must-do
- Start with option 1 (build time isolation)
  - Or option 4 (let them interfere)
- And revisit if users request changes

Alternative: Perf Events

- Multiple RFC implementations available
- perf maintainers show no concern (yet)
- Problem: Work on only specific h/w

Inputs?

- ~10:40

DAMON-X

Why: DAMON That Just Works

- DAMON goal: Tunable and Automated
- DAMON sysfs: For flexible user controls
- DAMON modules: For users who want it just works
  - E.g., DAMON_RECLAIM and DAMON_STAT
  - Should just work with 1-2 parameter setup

Problems in DAMON Modules

- Runs in exclusive manner
  - Cannot run >=2 modules at same time
- Inflexible
  - Flexible debugging/testing purpose interface is needed on production

Ideas

- Modules share monitoring params
  - The recommended intervals auto-tuning setup
  - Runs for the physical address space
- Differences are only DAMOS schemes
- Single DAMON context can run multiple schemes
- Online schemes [un]install is always supported

DAMON-X

- DAMON-Enabled Compute System
- Always run common setup DAMON
- Modules online-[un]install DAMOS schemes
- Support optional sysfs interface

Project Status

- Idea was shared on LPC’24 MM microconf
- Planning to POC-implement by Q3’26

Inputs?

- ~10:45

Access-aware THP

Motivation

- THP is known to be
  - Good: makes it faster (TLB miss reduction)
  - Bad: makes it larger (internal fragmentation)
- madvise() allows users wisely use THP
- Could DAMOS make it access-aware?

Initial Implementation and Test

- DAMOS_[NO]HUGEPAGE hot/cold pages
  - Hot: DAMON found any access
  - Cold: Region-sz >=2MiB, Unaccessed >=7 secs
- Test Results with PARSEC 3.0
  - Removes 80% memory bloat from THP
  - Preserves 46% THP performance gain
  - Numbers are not very stable

Productionizing Challenges

- Was unable to find good answers to
- Collapse? Split? Both?
- Virtual or physical address space?
- What is the ideal hot/cold thresholds?

Huawei’s Recent Approach

- Find three CPU hogger processes
  - Periodically change the list of processes
- Collapse hot memory in the processes
  - Auto-tune thresholds until make progress
- Good results on MySQL
- Still no good answers to the questions

Collapse or Split

- Should we collapse?
  - Or, enable THP=always?
- Should we split?
  - Or, rely on THP shrinkers?
    - Or, help or override THP shrinkers?
- Should we do both?
  - Or, rely on other mechanisms and do only one?

Virtual or Physical Address?

- Virtual addr is essential for collapsing
  - What processes to pick? Let users decide?
  - How to deal with DAMON-X (physical addr)?
- Physical addr can be used for splitting
  - Do not interfere with DAMON-X
  - Do not require users control

How to Set Thresholds?

- Quota goal-based autotune? What should be the goal?
  - huge:non-huge page ratio?
    - Huawei recently proposed this
  - TLB miss rate?
  - Memory bloat or pressure?

Thoughts At The Moment

- Collapsing for wise user makes sense
  - Huawei mm.git-merged DAMON_COLLAPSE
- Splitting for DAMON-X makes sense
- New DAMOS autotune goal makes sense for both

Better-help madvise()?

- DAMON is difficult to use
  - Require root permission
  - DAMON-X is for physical address space
- DAMON-X may better help

DAMON-X for easier madvise()

- User: request hotness of x-y address range of proc A
- DAMON-X: Sample-aggregate-output
  - pick N pages in the virtual address range
  - Find their physical addresses
  - Find hotness of the pages on its physical address-based snapshot
  - Aggregate their hotness and return to user

More Inputs?

- NUMA-TPP-DAMON
- Light-weight data attributes monitoring
- DAMON: Data Attributes Monitoring/Operations eNgine
- DAMON-X
- DAMON-THP

Backup Slides

Changes since LSFMMBPF’25

- 6.15-rc1 (2025-04-06)
  - DAMOS filters for hugepages, active, unmapped
  - DAMON intervals auto-tuning
- 6.16-rc1 (2025-07-08)
  - Self-tuned memory tiering
- 6.17-rc1 (2025-08-10)
  - DAMOS interleaving
  - DAMON_STAT
- 6.18-rc1 (2025-10-12)
  - 32bit PAE support
- 6.19-rc1 (2025-12-14)
  - Memcg-aware memory tiering
- 7.0-rc1 (2026-02-22)
  - DAMOS max_nr_snapshots
  - Active:inactive pages ratio based LRU sorting
- 7.1-rc1 (2026-04-26)
  - Quota goal tuner

TPP-DAMON in More Details

```
damo start \
    --numa_node 0 --monitoring_intervals_goal 4% 3 5ms 10s \
        --damos_action migrate_cold 1 --damos_access_rate 0% 0% \
        --damos_apply_interval 1s \
        --damos_quota_interval 1s --damos_quota_space 200MB \
        --damos_quota_goal node_mem_free_bp 0.5% 0 \
        --damos_filter reject young \
    --numa_node 1 --monitoring_intervals_goal 4% 3 5ms 10s \
        --damos_action migrate_hot 0 --damos_access_rate 5% max \
        --damos_apply_interval 1s \
        --damos_quota_interval 1s --damos_quota_space 200MB \
        --damos_quota_goal node_mem_used_bp 99.7% 0 \
        --damos_filter allow young \
        --damos_nr_quota_goals 1 1 --damos_nr_filters 1 1 \
    --nr_targets 1 1 --nr_schemes 1 1 --nr_ctxs 1 1
```

TPP-DAMON in More Details

```
damo start \
    --numa_node 0 --monitoring_intervals_goal 4% 3 5ms 10s \
        --damos_action migrate_cold 1 --damos_access_rate 0% 0% \
        --damos_apply_interval 1s \
        --damos_quota_interval 1s --damos_quota_space 200MB \
        --damos_quota_goal node_mem_free_bp 0.5% 0 \
        --damos_filter reject young \
    --numa_node 1 --monitoring_intervals_goal 4% 3 5ms 10s \
        --damos_action migrate_hot 0 --damos_access_rate 5% max \
        --damos_apply_interval 1s \
        --damos_quota_interval 1s --damos_quota_space 200MB \
        --damos_quota_goal node_mem_used_bp 99.7% 0 \
        --damos_filter allow young \
        --damos_nr_quota_goals 1 1 --damos_nr_filters 1 1 \
    --nr_targets 1 1 --nr_schemes 1 1 --nr_ctxs 1 1
```

Start DAMON in kernel.

Dear DAMON user-space tool,

TPP-DAMON in More Details

```
damo start \
    --numa_node 0 --monitoring_intervals_goal 4% 3 5ms 10s \
        --damos_action migrate_cold 1 --damos_access_rate 0% 0% \
        --damos_apply_interval 1s \
        --damos_quota_interval 1s                                  200MB \
        --damos_filter allow node_mem
        --damos_filter allow young
    --numa_node 1 --monitoring_intervals_goal 4% 3 5ms 10s \
        --damos_action migrate_hot 0 --damos_access_rate 5% max \
        --damos_apply_interval 1s \
        --damos_quota_interval 1s --damos_quota_space 200MB \
        --damos_quota_goal node_mem_used_bp 99.7% 0 \
        --damos_filter allow young \
        --damos_nr_quota_goals 1 1 --damos_nr_filters 1 1 \
    --nr_targets 1 1 --nr_schemes 1 1 --nr_ctxs 1 1
```

Create one DAMON worker thread, monitoring for node 0 (upper tier)

With auto-tuned monitoring intervals.

TPP-DAMON in More Details

```
damo start \
    --numa_node 0 --monitoring_intervals_goal 4% 3 5ms 10s \
        --damos_action migrate_cold 1 --damos_access_rate 0% 0% \
        --damos_apply_interval 1s \
        --damos_q[illegible] interval 1s --damos_quota_space 200MB \
        -[illegible] \
        -[illegible]
    --num[illegible] 5ms 10s \
        -[illegible]s_rate 5% max \
        --damos_apply_interval 1s \
        --damos_quota_interval 1s --damos_quota_space 200MB \
        --damos_quota_goal node_mem_used_bp 99.7% 0 \
        --damos_filter allow young \
        --damos_nr_quota_goals 1 1 --damos_nr_filters 1 1 \
    --nr_targets 1 1 --nr_schemes 1 1 --nr_ctxs 1 1
```

And ask it to *migrate* un-accessed (access_rate *0%*) memory to node *1* (lower tier), *cold*est one first.
IOW, **demote** cold memory.

TPP-DAMON in More Details

```
damo start \
    --numa_node 0 --monitoring_intervals_goal 4% 3 5ms 10s \
        --damos_action migrate_cold 1 --damos_access_rate 0% 0% \
        --damos_apply_interval 1s \
        --damos_quota_interval 1s --damos_quota_space 200MB \
        --damos_quota_goal node_mem_free_bp 0% 0 \
        --damos_filter reject young \
    --numa_node 1 --monitoring_intervals_goal 4% 3 5ms 10s \
        --damos_action migrate_hot 0 --damos_access_rate 5% max \
        --damos_apply_interval 1s \
        --damos_quota_interval 1s --damos_quota_space 200MB \
        --damos_quota_goal node_mem_used_bp 99.7% 0 \
        --damos_filter allow young \
        --damos_nr_quota_goals 1 1 --damos_nr_filters 1 1 \
    --nr_targets 1 1 --nr_schemes 1 1 --nr_ctxs 1 1
```

And do that once per second.

TPP-DAMON in More Details

```
damo start \
    --numa_node 0 --monitoring_intervals_goal 4% 3 5ms 10s \
        --damos_action migrate_cold 1 --damos_access_rate 0% 0% \
        --damos_apply_interval 1s \
        --damos_quota_interval 1s --damos_quota_space 200MB \
        --damos_quota_goal node_mem_free_bp 0.5% 0 \
        --damos_fi[illegible]ject young \
    --numa[illegible]
        --[illegible]x \
        --[illegible]
        --[illegible]
        --damos_quota_goal node_mem_used_bp 99.7% 0 \
        --damos_filter allow young \
        --damos_nr_quota_goals 1 1 --damos_nr_filters 1 1 \
    --nr_targets 1 1 --nr_schemes 1 1 --nr_ctxs 1 1
```

Within *one second*, do the migration only up to *200 MiB* of memory.

TPP-DAMON in More Details

```
damo start \
    --numa_node 0 --monitoring_intervals_goal 4% 3 5ms 10s \
        --damos_action migrate_cold 1 --damos_access_rate 0% 0% \
        --damos_apply_interval 1s \
        --damos_quota_interval 1s --damos_quota_space 200MB \
        --damos_quota_goal node_mem_free_bp 0.5% 0 \
        --damos_filter reject young \
    --numa_node 1 [illegible]ring_intervals_goal 4% 3 5ms 10s \
        --[illegible]x \
        --[illegible]
        --[illegible]
        --damos_quota_goal node_mem_used_bp 99.7% 0 \
        --damos_filter allow young \
        --damos_nr_quota_goals 1 1 --damos_nr_filters 1 1 \
    --nr_targets 1 1 --nr_schemes 1 1 --nr_ctxs 1 1
```

Under the 200MiB/1s hard limitation, auto-tune the real soft limitation to make node 0's free memory ratio becomes 0.5% soon.

TPP-DAMON in More Details

```
damo start \
    --numa_node 0 --monitoring_intervals_goal 4% 3 5ms 10s \
        --damos_action migrate_cold 1 --damos_access_rate 0% 0% \
        --damos_apply_interval 1s \
        --damos_quota_interval 1s --damos_quota_space 200MB \
        --damos_quota_goal node_mem_free_bp 0.5% 0 \
        --damos_filter reject young \
    --numa_node 1 --monitoring_intervals_goal 4% 3 5ms 10s \
        --damos_action migrate_hot 0 --damos_access_rate 5% max \
        --
        --
        --
        --damos_filter allow young \
        --damos_nr_quota_goals 1 1 --damos_nr_filters 1 1 \
    --nr_targets 1 1 --nr_schemes 1 1 --nr_ctxs 1 1
```

Btw, if the page is PG_Young, don’t do the migration.
DAMON might identify young page as not accessed.

TP

Create another DAMON worker thread that monitors *node 1* (lower tier) with auto-tuned monitoring intervals.
Ask it to migrate memory shown >=*5%* access rate to *node 0* (upper tier), *hot*test first. IOW, **promote** hot pages.
Do the migration once per second, up to 200 MiB of memory.
Under the *200 MiB/s* hard limit, adjust the real soft limit aiming *node 0* memory utilization ratio *99.7%*.
Btw, to that only if the page is PG_*Young*.

```
damo
-                                                                    % \
    --damos_                    node_mem_free_bp 0.5% 0 \
    --damos_filter reject young \
--numa_node 1 --monitoring_intervals_goal 4% 3 5ms 10s \
    --damos_action migrate_hot 0 --damos_access_rate 5% max \
    --damos_apply_interval 1s \
    --damos_quota_interval 1s --damos_quota_space 200MB \
    --damos_quota_goal node_mem_used_bp 99.7% 0 \
    --damos_filter allow young \
    --damos_nr_quota_goals 1 1 --damos_nr_filters 1 1 \
--nr_targets 1 1 --nr_schemes 1 1 --nr_ctxs 1 1
```