

Getting Started with the API

Welcome to the platform. This guide covers authentication, making your first request, and handling errors.

Prerequisites

Before you begin, ensure you have:

- An active account with API access enabled
- Your API key from the dashboard
- Python 3.9 or higher

Authentication

All requests require a Bearer token in the `Authorization` header.

```
GET /api/v1/data
Authorization: Bearer YOUR_API_KEY
Content-Type: application/json
```

 **TIP**

API keys are scoped to your organization. Do not share them across teams.

Your First Request

```
import requests

response = requests.get(
    "https://api.example.com/v1/data",
    headers={"Authorization": "Bearer YOUR_API_KEY"}
)

print(response.json())
```

 **PRO TIP**

Use environment variables to store your API key. Never hardcode credentials in source files.

Rate Limits

Plan	Requests/min	Burst
Free	60	100

Plan	Requests/min	Burst
Pro	600	1000
Enterprise	Unlimited	—

 **WARNING**

Exceeding the rate limit returns **429 Too Many Requests**. Implement exponential backoff in your client.

Error Handling

All errors follow a consistent structure:

```
{
  "error": {
    "code": "INVALID_TOKEN",
    "message": "The provided token has expired.",
    "docs": "https://docs.example.com/errors#INVALID_TOKEN"
  }
}
```

 **BREAKING CHANGE IN V2**

The `data.results` field was renamed to `data.items` in API v2. Update your client before migrating.

Next Steps

- [Authentication deep dive](#)
- [Webhooks setup](#)
- [SDK reference](#)