



# ER Model Diagram



# Final Project Database Schema Diagram



Note: The data is already in Third Normal Form (3NF). All tables have an attribute primary key upon which all non-primary attributes fully rely. There are no transitive dependencies, and all columns are atomic.

# Mapping Table

Requirement	Assumption/Reasoning	Representation in ER Model / Relational Schema
System retains Member information such as: firstName, lastName, phoneNumber, gender, and dateOfBirth.	Members self-register. Each email is unique.	<b>Entity: Member</b> — Attributes: memberID (PK), firstName, lastName, email, phoneNumber, gender, dateOfBirth.
A member can record many health metrics.	Each health metric belongs to exactly one member.	<b>Entity: HealthMetric</b> — Attributes: metricID (PK), memberID (FK), dateRecorded, timeRecorded, heightFeet, weightLBS, heartRateBpm, bodyFatPercentage, bloodPressure. <b>Relationship:</b> Member 1 to M HealthMetric.

Members create Fitness Goals and update status when completed.	A member has many fitness goals. A goal belongs to one member. Only the member can update goal status.	<p><b>Entity:</b> <b>FitnessGoals</b> — Attributes: goalID (PK), memberID (FK), goal, description, achieved, dateLogged, dateAchieved.</p> <p><b>Relationship:</b> Member 1 to M FitnessGoals.</p>
System stores Trainer information such as firstName, lastName, phoneNumber, email.	Trainers are created by Admin.	<p><b>Entity:</b> <b>Trainer</b> — Attributes: trainerID (PK), firstName, lastName, phoneNumber, email.</p>

Trainers creates availability.	Trainer availability cannot overlap with an availability they have already set for themselves.	<b>Entity:</b> TrainerAvailability — Attributes: availabilityID (PK), trainerID (FK), availabilityStartTime, availabilityEndTime. <b>Relationship:</b> Trainer 1 to M TrainerAvailability.
Members can enroll into group classes.	A member cannot enroll twice into the same class. Class capacity is based on room capacity.	<b>Entity:</b> Enrollment — Attributes: memberID (FK), classSessionID (FK), enrolledAt. <b>Relationships:</b> Member M to M ClassSession via Enrollment.

<p>Rooms are stored in the system containing building name, room number, and capacity.</p>	<p>Room capacity must be &gt; 0.</p>	<p><b>Entity: Room</b> — Attributes: roomID (PK), building, roomNumber, capacity.</p>
<p>Equipment's are in a room.</p>	<p>Equipment can exist on their own but should remain connected to a room.</p>	<p><b>Entity: Equipment</b> — Attributes: equipmentID (PK), roomID (FK), equipmentName, status.  <b>Relationship:</b> Room 1 to M Equipment.</p>
<p>Group Class Sessions (ClassSession) are created with a trainer, an available room, and a start/end time.</p>	<p>ClassSession cannot overlap another class in the same room or with the same trainer.</p>	<p><b>Entity: ClassSession</b> — Attributes: classSessionID (PK), sessionName, sessionStartTime, sessionEndTime, trainerID (FK), roomID (FK).  <b>Relationships:</b> Trainer 1 to M ClassSession; Room 1 to M ClassSession; Member M to M ClassSession (via Enrollment).</p>
<p>Admin can create trainers, add rooms, schedule classes, update classes, cancel classes, and manage equipment.</p>	<p>Admin only exists as a role and is not an entity stored in the database.   It acts upon the database but does not need to be represented within it.   I chose not to include Admin as an entity because entities represent persistent data, and the admin role does not have attributes that necessarily connect to other entities.</p>	

