

Metrics of successful websites and companies

Danai Avratoglou

January 2017

Contents

1	Introduction	3
2	Data gathering	4
2.1	Data Source - Fortune 500	4
2.2	Metrics	5
2.3	Python	7
2.4	Scripts	7
2.4.1	Fortune data - list download	8
2.4.2	Url validation	10
2.4.3	HTML download	11
2.4.4	Not downloadable pages	12
2.4.5	Readability index	13
2.4.6	Social media	14
2.4.7	Links - Internal and External	17
2.4.8	Loading time	18
2.4.9	Types and number of images	20
2.4.10	Size of images	22
2.4.11	Number of words - Unique and Total	28
2.4.12	HTML Validation	31
2.4.13	Fortune 500 - Metrics download	33
2.4.14	Merge data-frames and extract final csv file	38
3	Data Analysis	39
3.1	R and R-Studio	39
3.2	Scripts	39
3.2.1	Data cleansing	40
3.2.2	Variable analysis and correlation	40
3.2.3	Data manipulation	41
3.2.4	Logistic Regression	41
3.2.5	Comparisons and other methods	42
4	Conclusions	43
5	Bibliography	44
A	Appendix A: Fortune 500 Companies	45

1 Introduction

An on-line presence of a company was not an important factor of its success until a few years ago. Taking although into account the vast spread of the impact that internet has on consumers regarding their choices this hypothesis is not valid any more. Companies are obliged by the trends to be active on-line and to maintain a website that depicts the image they want their consumers to perceive. The purpose of this paper is to understand the relationship that exists between the website of a company and its success. Trying to comprehend this relationship a comparison will take place between specific metrics of the websites of the Fortune's 500 more successful companies and their financial status. By performing regression models and statistical analysis this paper will try to explore which metrics of a company's website influence its success.

2 Data gathering

The first step in order to contact this research is to conclude to the companies that are going to be examined. Since the purpose of this paper is to see if the website metrics that will be examined are influencing the success of the company it is a good idea to examine websites of some already successful companies and try to find out what they have in common.

2.1 Data Source - Fortune 500

The Fortune 500 is an annual list compiled and published by Fortune magazine that ranks 500 of the largest U.S. corporations by total revenue for their respective fiscal years. The list includes public companies, along with privately held companies for which revenues are publicly available.[1, 2]

For the purposes of this paper we will use this list of companies and we will examine their websites in order to understand if they indeed have something in common or if their success is irrelevant with their on-line presence.

The first thing that we will need is a list of the names that are include in the fortune 500. The easiest way to obtain this list is from the following article: <http://www.zyxware.com/articles/4344/list-of-fortune-500-companies-and-their-websites>. The way that we will obtain the list will be explained in the 2.4 Scripts section of this chapter. In the following table one can see the 50 most succesful companies that are included in the Fortune 500 during the period this paper is taking place. The rest of the list is available in the Appendix A.??

Table 1: Fortune 500 - 50 first companies

1. Walmart	2. Exxon Mobil	3. Apple
4. Berkshire Hathaway	5. McKesson	6. UnitedHealth Group
7. CVS Health	8. General Motors	9. Ford Motor
10. AT&T	11. General Electric	12. AmerisourceBergen
13. Verizon	14. Chevron	15. Costco
16. Fannie Mae	17. Kroger	18. Amazon.com
19. Walgreens Boots Alliance	20. HP	21. Cardinal Health
22. Express Scripts Holding	23. J.P. Morgan Chase	24. Boeing
25. Microsoft	26. Bank of America Corp.	27. Wells Fargo
28. Home Depot	29. Citigroup	30. Phillips 66
31. IBM	32. Valero Energy	33. Anthem
34. Procter & Gamble	35. State Farm Insurance Cos.	36. Alphabet
37. Comcast	38. Target	39. Johnson & Johnson
40. MetLife	41. Archer Daniels Midland	42. Marathon Petroleum
43. Freddie Mac	44. PepsiCo	45. United Technologies
46. Aetna	47. Lowe's	48. UPS
49. AIG	50. Prudential Financial	

2.2 Metrics

Now that we have declared the companies that we are going to use we will also need to decide which metrics are we going to examine for each site. Since we cannot have access to metrics such as traffic we will have to examine metrics that are more related to how the site is structure and what exactly does the initial page of each site includes. Initially we can divide the metrics in two major categories:

- What we see?
- What lays behind of what we see?

In the first category we are referring to metrics that can easily be conceived by the naked eye as well. For example the images that a website is using in its landing page. How many there are and if they are big or small.

The second category is not so obvious and it includes informations that usually is visible only to the web developer or the creator of the page. The information here are being given from the html code of a site. For instance we can see if the html code has any errors, that can lead to some malfunction in the site for example.

Now that we have a first understanding of the two main categories that the metrics we will use are divided in, we can see in detail the metrics that will be examined in this paper:

2.2.0.1 Loading time:

One aspect of a website that is crucial is the time it takes for it to load. Nowadays that the internet speed is going higher and higher most people do not have the patient to wait for a page to load. That is why we think that a metrics that should be definitely included in this research in the loading time of the initial page of a site.

2.2.0.2 Number of links:

When someone is browsing through the internet in many cases they are not completely sure what exactly they are looking for and that is why in a website it would be wise to have some links that can direct the user to find what he wants. These links can either direct the user in another page of the same site, in which case the link will be characterized as an internal link. Or they can lead the user to another site, where in that case the link is characterized as an external link. For the purpose of this paper since it is not so clear which type of links are more important to a user we will examine both the internal and the external links.

2.2.0.3 Social media:

Our era is marked by the social media wave that has changed our lifestyle and our daily habits. So it would be considered an overview if we didn't take

under consideration the number of social media that the company chooses to participate in. Even though they can also be considered as external links of the website we will examine them separately in order to see if any particular social medium effects the company's revenues.

2.2.0.4 Number and size of images:

Since the site is the first thing that a user will see for the company and there is a famous quote that says that "*First impressions counts*" we should also examine how the companies decide to visualize their landing page. In other words to see how many images they include in it and more on that what sizes are those images.

It is completely different to see only one huge image in the landing page of a site with not many words or descriptions than to see many small images with different information. The purpose is to examine if these type of diversities between the examined websites are actually related to how they are doing profit wise.

2.2.0.5 Type of images:

This kind of information is a little more complicated for a simple user to understand, but in many cases it plays a very important role. For example some websites are using specific type of images or banners that are not compatible with all the browsers, leading the user to see some break points in the website and even stop visiting it. That is why we believe is important to review this metric as well.

2.2.0.6 Number of words:

They say a picture worth a thousand words but that is not enough in our case. After exploring the number, sizes and type of pictures that a website is using we should also explore the number of words it is using to accompany the images and complete the outcome that a user will come across. The metrics we will use will be two. The first one will be the total words that are being used in the landing page and the other one will be the total unique words that are being used. When we are referring to unique words we mean words that are not so commonly use such as "a" or "and" and they give an air of individuality to the text. By using this metric we would try to see if the words that are being used are just as important as the actual content and if the words can make a difference.

2.2.0.7 Readability index:

In order for the previous metrics to be completed we will also have to take under consideration how comprehending is the text used in the websites for the users. This information can be obtained by calculating the readability index

of the website. How the readability index is being calculated will be further explained in another section.

2.2.0.8 HTML Validation:

Moreover we will have to check the quality of the html code behind the website we are seeing. Are there any mistakes in the code for example any brackets that opened and never closed or any links that do not work. We will examine again two different metrics here the number of errors and the number of warnings. The warnings are parts of the code that even though they work at the time there is a good chance to malfunction if any changes or additions are to be made to the html code.

2.3 Python

After having a first look into the variables/ metrics we will use in order to contact this research we should also see how we are going to obtain all this information.

Since all of this information can be subtracted from the html code of a company's website we should use a programming language in order to download the html pages and then to extract the specific metrics we want to examine from them. For the purposes of this paper the programming language that will be used for downloading the metrics from the websites is Python. More specifically the version of Python that will be used is the 2.7 one. Python is a widely used high-level programming language used for general-purpose programming, created by Guido van Rossum and first released in 1991. An interpreted language, Python has a design philosophy which emphasizes code readability (notably using white space indentation to delimit code blocks rather than curly braces or keywords), and a syntax which allows programmers to express concepts in fewer lines of code than possible in languages such as C++ or Java.

The language provides constructs intended to enable writing clear programs on both a small and large scale. Furthermore the way that Python allows a user to program is common to all users which gives this language a leverage as a program built in Python can be easily understood from another user without any difficulty.

The environment that is going to be used is from the Anaconda package which is a free open source distribution of the Python and R programming languages for large-scale data processing, predictive analytics, and scientific computing, that aims to simplify package management and deployment. To be more precise from this package we are going to use the Jupyter Notebook.[4]

2.4 Scripts

In order to gather all the needed metrics we had to create many small scripts so as to collect them. In this section we will present in detail the code that

was used in order to extract the information that later will help us contact the analysis of the relationship between those metrics and the company's status.

2.4.1 Fortune data - list download

The first step is to download and gather the names of the companies that we are going to examine and also the url of their websites and finally their ranking. Those information can be found in the following url as he have already mentioned in the beginning. <http://www.zyxware.com/articles/4344/list-of-fortune-500-companies-and-their-websites>.

The way to keep only the those three informations as separate variables is by separating from the html code of this page the needed information.

The first step is to create 3 empty lists where we will include the informations we are going to extract. The first list will contain the rank of each site, the second one will contain the name of the company and the 3rd one will contain the actual link of the company's site:

```
list_company_number = []
list_company_name = []
list_company_website = []
```

The second step is to upload some libraries that will help us create this function but also the ones that are going to follow.

```
import urllib
import urllib2
import time
import os
from bs4 import BeautifulSoup
import re
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
```

Finally the third step is to create the function that will firstly download the html code of the url at hand, secondly keep only the part of the code that we need to examine and thirdly save this part into the empty lists we created above. This function is called websites and takes as variable to work only the url of the site we need to examine:

```
def websites (url):
    from time import time
    start = time ()
    browser = urllib2.build_opener()
    browser.addheaders = [( 'User-agent ', 'Mozilla/5.0 ')]
    response = browser.open(url)
    myHTML = response.read()
    soup = BeautifulSoup(myHTML,"lxml")
    o = 0
```



```

td_list =[]
for row2 in soup.html.body.findAll('td'):
    td_list.insert(o, row2)
    o = o + 1
a = 0
b = 1
c = 2
list_numbering = 0
for i in range (0,500):
    num = str(td_list[a])
    company = str(td_list[b])
    site = str(td_list[c])
    c_num = re.findall('>(.*?)</td>', num)
    c_num = str(c_num[0])
    c_name = re.findall('>(.*?)</td>', company)
    c_name = str(c_name[0])
    c_site = re.findall('">(.*?)</a>', site)
    c_site = str(c_site[0])
    list_company_number.insert(list_numbering, c_num)
    list_company_name.insert(list_numbering, c_name)
    list_company_website.insert(list_numbering, c_site)
    a = a + 3
    b = b + 3
    c = c + 3
    list_numbering = list_numbering + 1
end = time ()
duration = round (end - start , 1)
minutes = round (duration /60, 1)
print 'The_lists_are_ready_in_', duration , '_seconds'
print 'The_lists_are_ready_in_', minutes , '_minutes'

```

The steps we followed to create the following function are the following:

2.4.1.1 Step 1

We create a fake browser that we are going to use in order to open the page and downloaded. The reason we do that is that many sites do not allow us to download their page because they are afraid of stealing important information. Since we are not using any private information we use this method to avoid issues while trying to open the html page at hand.

2.4.1.2 Step 2

We open the url and we read it while saving it in the variable "myHTML".

2.4.1.3 Step 3

With the help of the BeautifulSoup library we read the page as a lxml file and then for each row of this file we are looking for the "td" parts of the code where the informations we want are included.

2.4.1.4 Step 4

Since we need the names and the urls of all the 500 sites we created a loop from 0 to 500 where for each i we try to isolate the part of the code that contains the information that we want. Moreover even though it seems that with this loop we calculate 501 numbers since in Python the second bracket is always open we actually count from zero to 499.

2.4.1.5 Step 5

We use reg expressions¹ in order to state precisely what part of the already selected code we want to keep.

2.4.1.6 Step 6

We insert with a specific order the names, the ranking and the url to the corresponding lists and finally we create a text that will appear when the function is completed. Here we have also calculated the time that this function took to be completed and we will appear it as well along with the text.

2.4.2 Url validation

Now that we have saved in the three lists the names, the ranking and the urls of the companies that we are going to examine we first have to check whether or not those urls are valid in order to proceed with the download of the html code behind the initial web page of each one of those companies.

We first have to install the validators package in python so as to proceed with the validation of the url. In the command prompt window that opens when you open the Jupyter Notebook you have to write: "pip install validators" and then press enter in order for the package to be installed. This specific package currently supports python versions 2.7, 3.3, 3.4, 3.5 and PyPy.² The function that we are going to use from this package is called validators.url. This function returns True if the url at hand is a valid url or False if it is not.

Below one can see that we created a loop that will run as many times as the length of the list that we created in the previous section.

During this loop we create a string variable where we use the urls that we have saved in the list, one at each time, and we add the "http://" prefix.

Now that we have created the correct way that a url is supposed to be written we

¹A regular expression is a special sequence of characters that helps you match or find other strings or sets of strings, using a specialized syntax held in a pattern.

²<https://validators.readthedocs.io/en/latest>

will use the function of the validators package and we will create an if function that will check if the answer to a site is different from True and if it is it would add a unit in the variable nv so as to know at the end how many sites did not had valid urls.

Finally we ask from the programme to print the final result so as to know how many urls are not valid. The code that was created for this procedure is the following one:

```
nv = 0
for num in range(len(list_company_website)):
    line = 'http://' + str(list_company_website[num])
    x = validators.url(line)
    if x != True:
        nv = nv +1
print "The validation is complete! There were" , nv ,
    "not valid pages"
```

In our case all the urls where valid so we are eligible to proceed at the next part of the code.

2.4.3 HTML download

Download the actual html code of the initial pages of the 500 websites we will examine.

```
#def list_company_HTML (list_company_website , list_company_name , start , end):
import time
browser2 = urllib2.build_opener()
browser2.addheaders = [( 'User-agent' , 'Mozilla/5.0 ')]
for i in range (0,500):
    k = str(i + 1)
    lc = str(list_company_website[i])
    lc = lc.replace(" ", "")
    lc = lc.replace("[", "")
    lc = lc.replace("]", "")
    lcn = str(list_company_name[i])
    lcn = lcn.replace(" ", "")
    lcn = lcn.replace("[", "")
    lcn = lcn.replace("]", "")
    url2= 'http://' + lc
    #print (url2)
    list500_names.insert(i, lcn)
    list500_url.insert(i, lc)
    list500_num.insert(i, k)
    if i == 118 or i == 464: #The site 118(119) has a problem and the whole code
        #when I run it so we will thing of this site as a not downloadable
        list500_sites.insert(i, 0)
```

```

        #print ("The site " + k + " has NOT been downloaded!")
    else:
        #an exception might be thrown, so the code should be in a try-except block
        try:
            response2=browser2.open(url2)
        except Exception: # this describes what to do if an exception is thrown
            list500_sites.insert(i,0)
            print ("The_site_" + str(i) + "_has_NOT_been_downloaded!")
            continue
        #read the response in html format. This is essentially a long piece
        myHTML2=response2.read()
        list500_sites.insert(i,myHTML2)
        #wait for 2 seconds
        time.sleep(2)
        #print ("The site " + k + " has been downloaded!")
    #print "We saved: ",str(i + 1)," sites!"
    #print (len(list500_names),list500_names)

```

2.4.4 Not downloadable pages

By performing the previous code we could see that some pages could not be downloaded. In order to know from the beginning which companies sites will not be available for further exploration we created this part of the code which creates a list with the names of those companies.

```

#As we can see there is one site that hasn't been downloaded in order
#to keep track of the sites that we could not download
#we will create a new list that we will keep them all together there
not_d = []
not_d_n = []
num = []
def not_downloadables (list500_names,list500_sites):
    met = 0
    for i in range(len(list500_names)):
        if list500_sites[i] == 0:
            ct = list500_names[i]
            not_d.insert(met,ct)
            not_d_n.insert(met,str(i))
            num.insert(met,met)
            met = met + 1

```

#Now we will run the function to see which sites havent been downloaded

```

not_downloadables (list500_names, list500_sites)
d = { 'company' : pd.Series(not_d, index=[num]),
      'number' : pd.Series(not_d_n, index=[num]) }
nd = pd.DataFrame(d)
nd

```

2.4.5 Readability index

Now that we have downloaded the html code we would like to see how easy would be for someone to read this code. We will use a site that will help us evaluate and create the readability index.

*#Now we will perform a reliability test for the text that is
#included in the html code of the company's page*

```

from pattern import metrics
readability = []
rdb = []

```

```

def readable (list500_names, list500_sites):
    for i in range (len(list500_names)):
        myHTML = list500_sites[i]
        if myHTML == 0:
            readability.insert(i, "n/a")
            rdb.insert(i, "n/a")
        else:
            a = metrics.flesch_reading_ease(myHTML) * 100
            a = round (a, 1)
            if a > 90:
                readability.insert(i, "Very_easy")
                rdb.insert(i, 6)
            elif a > 80:
                readability.insert(i, "Easy")
                rdb.insert(i, 5)
            elif a > 70:
                readability.insert(i, "Fairly_easy")
                rdb.insert(i, 4)
            elif a > 60:
                readability.insert(i, "Standard")
                rdb.insert(i, 3)
            elif a > 50:
                readability.insert(i, "Fairly_difficult")
                rdb.insert(i, 2)
            elif a > 30:

```

```

        readability.insert(i,"Difficult")
        rdb.insert(i,1)
    else:
        readability.insert(i,"Very_Confusing")
        rdb.insert(i,0)
print "The_function_is_completed!"

```

```
readable (list500_names , list500_sites)
```

The function **is** completed!

```

d1 = { 'company' : pd.Series(list500_names , index=[list500_num]) ,
        'url' : pd.Series(list500_url , index=[list500_num]) ,
        'Readability' : pd.Series(readability , index=[list500_num]) ,
        'Readability_index' : pd.Series(rdb , index=[list500_num]) }
fre = pd.DataFrame(d1)
fre.tail(3) #we see the first 3 in the data frame

```

2.4.6 Social media

Now we will see how many and which companies include in their initial page the link to specific social media.

```

#Retreiving the social media from each site
#First create empty lists for the ones that
#we will need to calculate
sm_f = []
sm_t = []
sm_i = []
sm_p = []
sm_y = []
sm_l = []
sm_nm = []
nm = []
sm_url = []

```

```

#Then create a function that will feel in those
#lists so as to make the data frame later on
def socialmedia (list500_sites ,list500_names ,list500_url):
    from time import time
    # I used it to see how much time it does to run the function
    start = time ()
    for i in range(len(list500_names)):
        myHTML = list500_sites[i]
        sm = [ 'facebook.com', 'twitter.com',
                'instagram.com', 'pinterest.com',
                'youtube.com', 'linkedin.com' ]
        if myHTML == 0:
            #print(str(i), "no")
            sm_nm.insert(i, list500_names[i])
            nm.insert(i, i)
            sm_url.insert(i, list500_url[i])
            sm_f.insert(i, 'n/a')
            sm_t.insert(i, 'n/a')
            sm_i.insert(i, 'n/a')
            sm_p.insert(i, 'n/a')
            sm_y.insert(i, 'n/a')
            sm_l.insert(i, 'n/a')
        else:
            for index in range(len(sm)):
                x = sm[index]
                social = re.findall(x, myHTML)
                if (len(social) > 0):
                    if x == 'facebook.com':
                        answerf = 'TRUE'
                    if x == 'twitter.com':
                        answer_t = 'TRUE'
                    if x == 'instagram.com':
                        answer_i = 'TRUE'
                    if x == 'pinterest.com':
                        answer_p = 'TRUE'
                    if x == 'youtube.com':
                        answer_y = 'TRUE'
                    if x == 'linkedin.com':
                        answer_l = 'TRUE'
                else:
                    if x == 'facebook.com':
                        answerf = 'FALSE'
                    if x == 'twitter.com':
                        answer_t = 'FALSE'
                    if x == 'instagram.com':
                        answer_i = 'FALSE'

```

```

        if x == 'pinterest.com':
            answerp = 'FALSE'
        if x == 'youtube.com':
            answery = 'FALSE'
        if x == 'linkedin.com':
            answerl = 'FALSE'
    sm_nm.insert(i, list500_names[i])
    nm.insert(i, i)
    sm_url.insert(i, list500_url[i])
    sm_f.insert(i, answerf)
    sm_t.insert(i, answerl)
    sm_i.insert(i, answeri)
    sm_p.insert(i, answerp)
    sm_y.insert(i, answery)
    sm_l.insert(i, answerl)
end = time ()
duration = round (end - start , 3)
minutes = round (duration /60, 1)
print 'The_lists_are_completed_in_', minutes, '_minutes'
print 'The_lists_are_ready_in_', duration, '_seconds'

```

#Now we will run the function for the 25 first sites for starters
socialmedia (list500_sites ,list500_names ,list500_url)

```

The lists are completed in 0.0 minutes
The lists are ready in 0.259 seconds

```

#Finally we create the data frame with the elements we found

```

d2 = {'company' : pd.Series(sm_nm, index=[nm]) ,
      'facebook' : pd.Series(sm_f, index=[nm]) ,
      'twitter' : pd.Series(sm_t, index=[nm]) ,
      'instagram' : pd.Series(sm_i, index=[nm]) ,
      'pinterest' : pd.Series(sm_p, index=[nm]) ,
      'youtube' : pd.Series(sm_y, index=[nm]) ,
      'linkedin' : pd.Series(sm_l, index=[nm]) ,}
social_media = pd.DataFrame(d2)
social_media.tail(3) #we see the first 3 in the data frame

```


2.4.7 Links - Internal and External

Next step is to see how many internal, external and finally total links each html code has.

```
#Create the lists we will need for the data frame
l_nm = []
l_ex = []
l_in = []
l_t = []
nm = []
l_url = []

#create the function that will calculate the different type of links
def links (list500_sites ,list500_names ,list500_url):
    from time import time
    # I used it to see how much time it does to run the function
    start = time ()
    for num in range(len(list500_names)):
        myHTML = list500_sites [num]
        if myHTML == 0:
            l_nm.insert(num,list500_names [num])
            l_ex.insert(num,'n/a')
            l_t.insert(num,'n/a')
            l_in.insert(num,'n/a')
            nm.insert(num,num)
        else:
            href = re.findall('href',myHTML)
            external = re.findall('href="https:',myHTML)
            ex = (len(external))
            alllinks = (len(href))
            internal = (len(href) - len(external))
            l_nm.insert(num,list500_names [num])
            l_ex.insert(num,ex)
            l_t.insert(num,alllinks)
            l_in.insert(num,internal)
            nm.insert(num,num)
    end = time ()
    duration = round (end - start , 3)
    minutes = round (duration /60, 1)
    print 'The_lists_are_ready_in_', minutes , '_minutes'
    print 'The_lists_are_ready_in_', duration , '_seconds'
```

```

#Run the function in order to find the external,
#internal and total links of each site
#For now we are running for the first 25 sites only
links (list500_sites ,list500_names ,list500_url)

```

```

The lists are ready in 0.0 minutes
The lists are ready in 0.088 seconds

```

```

#Create a dataframe so as to be able to see
#the results of the function we run
d3 = {'company' : pd.Series(l_nm , index=[nm]) ,
      'external' : pd.Series(l_ex , index=[nm]) ,
      'internal' : pd.Series(l_in , index=[nm]) ,
      'total_links' : pd.Series(l_t , index=[nm])}
sites_links = pd.DataFrame(d3)
sites_links.tail(3) #we see the first 3 in the data frame

```

2.4.8 Loading time

One very important factor as we mentioned before is the time that the site does to be loaded and with this part of the code we will count exactly that.

```

#The initial lists we will need in order
#to calculate the loading time
lt_nm = []
lt_time = []
nm = []
lt_url = []

```

```

#the function that will calculate the loading time
def loadtime (list_company_website ,list500_names ,list500_url):
    from time import time
    browser2 = urllib2.build_opener()
    browser2.addheaders = [( 'User-agent' , 'Mozilla/5.0 ')]
    for num in range(len(list500_names)):
        lc = str(list_company_website[num])
        lc = lc.replace(" ","")

```

```

lc = lc.replace("[",",")
lc = lc.replace("]",",")
url2 = 'http://' + lc
if num == 118 or num == 464:
    #The site 118(119) has a problem and the whole code
    #is stacking when I run it so we will think of this
    #site as a not downloadable
    lt_nm.insert(num,list500_names[num])
    lt_time.insert(num,'n/a')
    nm.insert(num,num)
    lt_url.insert(num,list500_url[num])
    #print ("The site " + str(num) + " has NOT been loaded!")
else:
    try:
        response2 = browser2.open(url2)
    except Exception:
        lt_time.insert(num,'n/a')
        lt_nm.insert(num,list500_names[num])
        nm.insert(num,num)
        print ("The site " + str(num)+ " has NOT been loaded!")
        continue
    start_time = time()
    myHTML2 = response2.read()
    end_time = time()
    response2.close()
    l_t = round(end_time-start_time , 3)
    #in order to be more readable we rounded the time
    loadt = str(l_t)
    lt_nm.insert(num,list500_names[num])
    lt_time.insert(num,loadt)
    nm.insert(num,num)
    lt_url.insert(num,list500_url[num])
    #print ("The site " + str(num) + " has been loaded!")
print "The function is completed!"

```

```

#running the function for the first 25 sites
loadtime (list_company_website , list500_names , list500_url)

```

```

#creating the data frame with the loading times
d4 = { 'company' : pd.Series(lt_nm , index=[nm]) ,
        'loading_time' : pd.Series(lt_time , index=[nm]) }
loading_time = pd.DataFrame(d4)
loading_time.head(3) #we see the first 3 in the data frame

```

2.4.9 Types and number of images

There are many different types of images that can be used in a site. Here we will examine which ones are being preferred from the majority of the examined companies and in what amount. In other words we will count the number of each type of image and then calculate the total number of images appearing in this initial page.

```
#Find out how many and what type of images each site has  
#first we create the initially empty lists
```

```
p_p = []  
p_d = []  
p_jpg = []  
p_jpeg = []  
p_gif = []  
p_tif = []  
p_tiff = []  
p_bmp = []  
p_jpe = []  
p_nm = []  
p_tt = []  
nm = []  
p_url = []
```

```
#Then we create the function that will explore  
#the html pages and search for the images
```

```
def images (list500_sites ,list500_names ,list500_url):  
    from time import time # I used it to see  
    #how much time it does to run the function  
    start = time ()  
    for num in range(len(list500_names)):  
        myHTML = list500_sites[num]  
        image = [ '.png', '.dib', '.jpg', '.jpeg',  
                  '.bmp', '.jpe', '.gif', '.tif', '.tiff']  
        totalnumber = 0  
        if myHTML == 0:  
            p_nm.insert(num,list500_names[num])  
            p_p.insert(num, 'n/a')  
            p_d.insert(num, 'n/a')  
            p_jpg.insert(num, 'n/a')  
            p_jpeg.insert(num, 'n/a')  
            p_gif.insert(num, 'n/a')  
            p_tif.insert(num, 'n/a')  
            p_tiff.insert(num, 'n/a')
```

```

p_bmp.insert(num, 'n/a')
p_jpe.insert(num, 'n/a')
p_tt.insert(num, 'n/a')
nm.insert(num, num)
p_url.insert(num, list500_url[num])
else:
    for index in range(len(image)):
        x = image[index]
        photo = re.findall(x, myHTML)
        if x == '.png':
            p = str(len(photo))
        if x == '.dib':
            d = str(len(photo))
        if x == '.jpg':
            jpg = str(len(photo))
        if x == '.jpeg':
            jpeg = str(len(photo))
        if x == '.gif':
            gif = str(len(photo))
        if x == '.tif':
            tif = str(len(photo))
        if x == '.tiff':
            tiff = str(len(photo))
        if x == '.bmp':
            bmp = str(len(photo))
        if x == '.jpe':
            jpe = str(len(photo))
        totalnumber = len(photo) + totalnumber
    total = str(totalnumber)
    p_nm.insert(num, list500_names[num])
    p_p.insert(num, p)
    p_d.insert(num, d)
    p_jpg.insert(num, jpg)
    p_jpeg.insert(num, jpeg)
    p_gif.insert(num, gif)
    p_tif.insert(num, tif)
    p_tiff.insert(num, tiff)
    p_bmp.insert(num, bmp)
    p_jpe.insert(num, jpe)
    p_tt.insert(num, total)
    nm.insert(num, num)
    p_url.insert(num, list500_url[num])
end = time ()
duration = round (end - start , 3)
minutes = round (duration /60, 1)
print 'The_lists_are_ready_in_', minutes, '_minutes'

```

```
print 'The_lists_are_ready_in_', duration, '_seconds'
```

```
#Then we run the function for the first 20 sites for now
images (list500_sites ,list500_names ,list500_url)
```

```
The lists are ready in 0.1 minutes
The lists are ready in 3.341 seconds
```

```
#Finally we create a dataframe in order to see the results of the function
d5 = {'company' : pd.Series(p_nm, index=[nm]),
      '.png' : pd.Series(p_p, index=[nm]),
      '.dib' : pd.Series(p_d, index=[nm]),
      '.jpg' : pd.Series(p_jpg, index=[nm]),
      '.jpeg' : pd.Series(p_jpeg, index=[nm]),
      '.bmp' : pd.Series(p_bmp, index=[nm]),
      '.jpe' : pd.Series(p_jpe, index=[nm]),
      '.gif' : pd.Series(p_gif, index=[nm]),
      '.tif' : pd.Series(p_tif, index=[nm]),
      '.tiff' : pd.Series(p_tiff, index=[nm]),
      'total_images' : pd.Series(p_tt, index=[nm])}
images_types = pd.DataFrame(d5)
images_types.head(3) #we see the first 3 in the data frame
```

2.4.10 Size of images

Aside from the number of images another important factor is the size of each image. The following code will find the different sizes that are being used in the companies at hand and keep only the unique sizes.

```
#Now we will find the different dimensions that each site uses
#initially we create the empty lists we will need
nm = []
s_comp = []
s_dimensions = []
s_times = []
s_tt_dif_dim = []
ht = [] #list of different heights in each case
wt = [] #list of different widths in each case
```

```

h_w = [] # combinations of height and width
dif_size = []
un_size = []
s_url = []

```

```

#With the below function we will gather
#in a variable all the different dimensions
#and in another one all the times that each
#dimension occurs for each html code

```

```

def find_dif_sizes (list_company_website , list500_names , list500_url ):
    from time import time # I used it to see how much time it does to run the fu
    start = time ()
    for num in range(len(list500_names)):
        nm.insert(num,num)
        s_comp.insert(num,list500_names[num])
        s_url.insert(num,list500_url[num])
        myHTML = list500_sites[num]
        if myHTML == 0:
            s_dimensions.insert(num,0)
            s_times.insert(num,0)
        else:
            soup = BeautifulSoup(myHTML, "lxml")
            # we create 2 local variables so as to gather the
            #different dimensions and occurencies of each page seperately
            s_dimensions_local = []
            s_times_local = []
            hw = 0
            # we use it for the lists of height and width
            # find all the img in the first site html. Since in some
            #cases either the height or the width is missing we would
            #like to keep only the ones that have both dimensions
            for tag in soup.find_all('img'):
                h = tag.attrs.get('height', None)
                w = tag.attrs.get('width', None)
                #we use if to check which ones have both
                if h != None:
                    if w != None:
                        ht.insert(hw,h)
                        wt.insert(hw,w)
                        hw = hw + 1
            hw2 = 0
            for l in range(len(ht)):
                h_w_c = ht[l] + 'x' + wt[l]

```

```

#we create a str with the form (300x300)
#so as to be more easily to read later on
h_w.insert(hw2,h_w_c)
#we put it in a new list
hw2 = hw2 + 1
if h_w == []:#we check if there are not any dimensions available
    nm.insert(num,num)
    s_comp.insert(num,list500_names[num])
    s_dimensions.insert(num,0)
    s_times.insert(num,0)
if h_w != []:#now we continue with the cases
    #where the dimensions are indeed available
    from collections import Counter
    hw_unique = Counter(h_w)
    hw_unique2 = str(hw_unique)
    #the unique different dimensions for the specific site
    #Due to the fact that we are talking about
    #a list we have to split the parts we need
    split1 = hw_unique2.split('{')
    a = split1[1]
    split2 = a.split('}')
    b = split2[0]
    split3 = b.split(',')
    finalsplit = []
    fs = []
    z = 0
    m = 1
    j = 0
    z1 = 0
    m1 = 1
    #each of the items in split3 has a form '300x300 : 15'
    #and in order to create the dataframe we have
    #to split this form and keep the informations in different l
    for numb in split3:
        oldstring = numb
        newstring = oldstring.replace(" ", "")
        new = newstring.replace("'", "")
        string = new.replace("_", "")
        finalstring = string.split(':')
        #the finalstring is a list that contains the dimensions
        #and the occurencies in order toseperate in different
        #lists we create an additional loop
        for xx in range(len(finalstring)):
            ax = finalstring[xx]
            if 'x' in ax:
                s_dimensions_local.insert(z1,finalstring[xx])

```



```

        z1 = z1 + 1
    else:
        s_times_local.insert(ml,finalstring[xx])
        ml = ml + 1
    #Now we can add to the lists the parts we created so as
    #to have them all gathered together
    s_dimensions.insert(num,s_dimensions_local)
    s_times.insert(num,s_times_local)
end = time ()
duration = round (end - start , 3)
minutes = round (duration /60, 1)
print 'The_lists_are_ready_in_', minutes, '_minutes'
print 'The_lists_are_ready_in_', duration, '_seconds'

```

```

#Run the function for the first 20 sites
find_dif_sizes (list500_sites ,list500_names ,list500_url)

```

```

The lists are ready in 1.4 minutes
The lists are ready in 81.813 seconds

```

```

#Find the unique different image dimensions and put them on a list
def unique_dif_sizes (s_dimensions ,list500_names):
    ds = 0
    for num in range(len(list500_names)):
        asw = s_dimensions[num]
        if asw != 0 :
            for s in range(len(asw)):
                ss = asw[s]
                dif_size.insert(ds,ss)
                ds = ds + 1
    dsu = 0
    for i in dif_size:
        if i not in un_size:
            un_size.insert(dsu,i)
            dsu = dsu + 1
    print(un_size)

```

```

#Run the function unique_dif-sizes
unique_dif-sizes (s_dimensions ,list500_names)

#The lists we will need for the next function
t_f-s = []
ttf = []
nm = []
com = []

#Function in order to check whether or not each
#company has these dimensions
def dimensions_per_company (un_size ,list500_names):
    from time import time
    # I used it to see how much time it does to run the function
    start = time ()
    #t_f-s.insert(0,un_size)
    #ttf.insert(0,t_f-s)
    for num in range(len(list500_names)):
        #print(str(num))
        sla = s_dimensions[num]
        #dimensions of site num
        where = [] #empty list
        wh = 0
        haveornot = []
        for er in range (len(un_size)):
            if sla != 0 :
                for sizea in sla:
                    if sizea == un_size[er]:
                        where.insert(wh,str(er))
                        wh = wh +1
                    break
            if str(er) in where:
                haveornot.insert(er,True)
            else:
                haveornot.insert(er,False)

        t_f-s.insert(num,haveornot)
        ttf.insert(num,t_f-s)
        nm.insert(num,num)
        com.insert(num,list500_names[num])
    end = time ()
    duration = round (end - start , 3)

```

```

minutes = round (duration /60, 1)
print 'The_lists_are_ready_in_', minutes, '_minutes'
print 'The_lists_are_ready_in_', duration, '_seconds'

#Run the function dimensions_per_company
dimensions_per_company (un_size ,list500_names)

The lists are ready in 0.1 minutes
The lists are ready in 3.699 seconds

#Create an initial dataframe where we will add the sizes later on
d6 = {'company' : pd.Series(com, index=[nm])}
sizess = pd.DataFrame(d6)
sizess.head(3)

#####
#Now we want to break the variable t_f_s
#in order to add the columns to the dataframe
#Finally we create the data frame with the elements we found
def final_dimensions_dataframe (un_size ,t_f_s ,list500_names):
    from time import time
    # I used it to see how much time it does to run the function
    start = time ()
    for q in range(len(un_size)):
        names = un_size[q]
        var = []
        for num in range(len(list500_names)):
            a = t_f_s [num]
            var.insert(num,a[q])
        sizess[names] = pd.Series(var, index=sizess.index)
    end = time ()
    duration = round (end - start , 3)
    minutes = round (duration /60, 1)
    print 'The_lists_are_ready_in_', minutes, '_minutes'
    print 'The_lists_are_ready_in_', duration, '_seconds'

```

```
#Run the function final_dimensions_dataframe
final_dimensions_dataframe (un_size , t_f_s , list500_names)
```

```
The lists are ready in 0.0 minutes
The lists are ready in 0.414 seconds
```

```
sizess.tail(3)
```

2.4.11 Number of words - Unique and Total

As it was mentioned and before words are exactly as important in a html page as the images. So we have to calculate the number of unique words and the total words that are being appeared in each companies html code.

```
#Now we would like to find the words in the text
#and the unique words of each html page
#First of all we need to have a dictionary with which
#we would check if the word we found truly exists
#The dictionary is available in the internet from a
#github account from where we are going to read it
url_dictionary = "https://raw.githubusercontent.com/dwyl/english-words/master/wo
browser = urllib2.build_opener()
browser.addheaders = [( 'User-agent' , 'Mozilla/5.0' )]
response = browser.open(url_dictionary)
html_dictionary = response.read()
html_dictionary
dicti = str(html_dictionary)
#dicti
```

```
#dict_new = dicti.split("\\n")
dict_new = dicti.split("\n")
dict_new[49]
#the first 49 parts are not words so we have to remove them from the list
```

'a1'

```
dict_final = []
df = 0
for i in range (50,len(dict_new)):
    forfinal = dict_new[i]
    forfinal = forfinal.replace(" ",",")
    dict_final.insert(df,forfinal)
    df = df + 1
dict_final[0]
#This is the original dictionary with which we will check each word
```

'aa'

```
#And now we will find each html file which words has inside
empty = []
wordsin = []
ocin = []
def html_which_word (list500_names):
    from time import time
    # I used it to see how much time it does to run the function
    start_t = time()
    for num in range(len(list500_sites)):
        line = list500_sites[num]
        if line == 0:
            wordsin.insert(num,0)
            ocin.insert(num,0)
        else:
            wordcount={}
            simeiaastiksis = ["/", ".", ",", "=", ">", "<", "?", "|", ":",
                                "-", "]", "[", "$", "&", "%", "(", ")", "{",
                                "}", "'", ";", "\\", "_", "!", "+", "#", "=",
                                "@", "^", "*", " ' "]
            for ss in range(len(simeiaastiksis)):
```

```

simeio = simeiasiksis[ss]
line = line.replace(simeio, "_")
for word1 in line.split():
    word1 = word1.lower()
    if word1 in dict_final:
        if word1 not in wordcount:
            wordcount[word1] = 1
        else:
            wordcount[word1] += 1
wordsin_local = []
wl = 0
ocin_local = []
for k,v in wordcount.items():
    #print (k,v)
    wordsin_local.insert(wl, str(k))
    ocin_local.insert(wl, str(v))
    wl = wl + 1
wordsin.insert(num, wordsin_local)
# final list with all the words in each site
ocin.insert(num, ocin_local)
#final list with all the occurencies of the words in each site
#print('The site ', str(num +1), ' has been checked')
end_t = time()
total_t = round(end_t - start_t,3)
total_ = round(total_t / 60,1)
print('finished_', str(x) , '_sites_in:', str(total_), '_minutes')

```

```
html_which_word (list500_names)
```

```
('finished_', 'True', '_sites_in:', '197.6', '_minutes')
```

```

#Create the dataframe for the words and unique words
d7 = {'company' : pd.Series(list500_names , index=[mm])}
wordss = pd.DataFrame(d7)
wordss.head(3)

```

```

#####
#Create the two lists we will need in order to make the dataframe
l1 = []

```

```

l2 = []
for num in range(len(list500_names)):
    line = list500_sites[num]
    if wordsin[num] == 0 :
        l1.insert(num, 'n/a')
        l2.insert(num, 'n/a')
    else:
        total_words = len(wordsin[num])
        occurencies = ocin[num]
        l1.insert(num, total_words)
        count = 0
        for a in occurencies :
            if a == '1':
                count = count + 1
        l2.insert(num, count)
wordss['total_words'] = pd.Series(l1, index=sizess.index)
wordss['unique_words'] = pd.Series(l2, index=sizess.index)
wordss.head(3)

```

2.4.12 HTML Validation

Now that we have downloaded and kept in data frames the basic metrics that we will need for the analysis we should also check the quality of the html code.

```

#In order to validate the html code we will use the w3 validator
#We will validate each url and then we will open the url of the validation page
#so as to extract the errors, the info warnings and the non-document-error io in
#First we create the empty lists we would use later on
num_errors = []
num_info_warnings = []
num_non_doc = []
nm = []
num_open_page = []
empty = ""

```

```

#Then we create the function that will pull the informations we want
def html_validation (list500_url, list500_names):
    from time import time # I used it to see how much time it does to run the fu
    start = time ()
    for num in range(len(list500_names)):
        line = list500_url[num]
        url_check = "https://validator.w3.org/nu/?doc=https://" + line

```

```

browser = urllib2.build_opener()
browser.addheaders = [( 'User-agent', 'Mozilla/5.0' )]
response = browser.open(url_check)
html_check = response.read()
html_check
check = str(html_check)
er = 0
err = 0
errr = 0
e = False
if check != empty:
    e = True
    soup = BeautifulSoup(check,"lxml")
    o = 0
    keyf = []
    for row in soup.html.body.findAll('div'):
        keyf.insert(o,row)
        o = o + 1
    #print(len(keyf),list500_url[num], "site number: ", str(num))
    if len(keyf) != 0:
        keyfin = str(keyf[2])
        #the elements we need is in the 2nd div of the code
        dol= re.findall('class="error"',keyfin)
        er = er + len(dol)
        doll= re.findall('class="info_warning"',
                        ,keyfin)
        err = err + len(doll)
        dolll= re.findall('class="non-document-error_io"',
                        ,keyfin)
        errr = errr + len(dolll)
    num_errors.insert(num,er)
    num_info_warnings.insert(num,err)
    num_non_doc.insert(num,errr)
    nm.insert(num,num)
    num_open_page.insert(num,e)
end = time ()
duration = round (end - start , 3)
minutes = round (duration /60, 1)
print 'The lists are ready in ', minutes, ' minutes'

```

```

#Now we will run the function we created
html_validation (list500_url,list500_names)

```


The lists are ready in 37.0 minutes

```
#After the checks we will create the dataframe with the informations we want
d8 = {'company' : pd.Series(list500_names, index=[nm]),
      'The_page_opened' : pd.Series(num_open_page, index=[nm]),
      'number_of_errors' : pd.Series(num_errors, index=[nm]),
      'number_of_warning' : pd.Series(num_info_warnings, index=[nm]),
      'non-document-error' : pd.Series(num_non_doc, index=[nm])}
html_val = pd.DataFrame(d8)
html_val.head(3)
```

2.4.13 Fortune 500 - Metrics download

Just in order to have some metrics that will depict the status of the companies we are going to analyse we will also download some metrics from the fortune 500 sites for each company.

```
#The next step is to take some informations from the fortune 500 site for each c
#In order to achieve that we should open the pages for each one of the sites sep
#Since there is a pattern in the way the pages are named it shouldn't be difficu
#Firstly we should create the pattern with which we will download the pages
#By running the code we can see that the names of each comany are not
#written exactly as we have saved them
#So we do need to alter the names first in order for the below function to run
```

```
#creating a new list with alterations in order for the names
#to match the ones that fortune 500 uses so that we can download the html page
list_company_name_new = []
for num in range(0,500):
    cn = list_company_name[num]
    cn = cn.replace("_", "-")
    cn = cn.replace("&", "")
    cn = cn.replace(" ", "")
    cn = cn.replace(".", "-")
    cn = cn.replace("amp;", "")
    company = cn.lower()
    list_company_name_new.insert(num,cn)
```

```

fortune_pages = []
def fortune500 (list_company_name_new):
    from time import time # I used it to see how much time it does to run the fu
    start = time ()
    for num3 in range (0,500):
        i = str (num3 +1)
        companyname = list_company_name_new[num3]
        browser = urllib2.build_opener()
        #because i work from different computers with different
        #pyhton version some commands are not recognizable in each version
        browser.addheaders = [( 'User-agent', 'Mozilla/5.0' )]
        site_fortune = "http://beta.fortune.com/fortune500/"+companyname+"-"+i
        page_fortune = browser.open(site_fortune)
        html_fortune = page_fortune.read()
        #print("fortune page for company:", list_company_name_new[num3],i)
        fortune_pages.insert(num3, html_fortune)
    end = time ()
    duration = round (end - start , 3)
    minutes = round (duration /60, 1)
    print 'The_lists_are_ready_in_', minutes, '_minutes'
    print 'The_lists_are_ready_in_', duration, '_seconds'

```

```

#Run the function we created
fortune500 (list_company_name_new)

```

```

The lists are ready in 21.6 minutes
The lists are ready in 1295.917 seconds

```

```

#Now that we have opened the url we are going to extract
#some informations that we need from them
#In order to do that initially we have to create
#the variables we will need
keyf =[]
per =[]
rev_dol = []
rev_per = []
prof_dol = []

```

```

prof_per = []
assets_dol = []
assets_per = []
tse_dol = []
tse_per = []
mar_dol = []
mar_per = []
market = []
nm = []
ln = []
urln = []
empty = []

```

```

def fortune_metrics (list_company_name ,list_company_website):
    x = 0
    for n in range (0,500):    #we put 25 for testing
        nm.insert(x,x)
        ln.insert(x,list_company_name[n])
        urln.insert(x,list_company_website[n])
        files = fortune_pages[x]
        soup = BeautifulSoup( files ,"lxml")
        o=0
        for row in soup.html.body.findAll( 'tbody' ):
            keyf.insert(o,row)
            o=o+1
        keyfin = keyf[0]
        #the elements we need is in the first tbody of the code
        data = keyfin.findAll( 'td' )

        one = str(data[0])
        # revenue
        two = str(data[1])
        # revenue in dollars we need to extract this
        revdol= re.findall( '>\$(.+?)</td>' ,two)
        #we keep only the numbers
        if revdol[0] != empty:
            w = revdol[0]
            a = w.replace(" ", "")
            r = a.replace(",","")
            rev_dol.insert(x,r)
        else:
            rev_dol.insert(x,'not_available')
        tria = str(data[2])

```

```

# revenue in percentage we need to extract this as well
revper= re.findall( '>(.*?)%</td>',tria)
#we keep only the numbers
if revper != empty:
    w = revper[0]
    a = w.replace(" ", "")
    r1 = a.replace("]", "")
    rev_per.insert(x,r1)
else:
    rev_per.insert(x,'not_available')
four = str(data[3]) # profit
five = str(data[4])
# profit in dollars we need to extract this
profdol= re.findall( '>\$(.*?)</td>',five)
#we keep only the numbers
if profdol != empty:
    w = profdol[0]
    a = w.replace(" ", "")
    p = a.replace("]", "")
    prof_dol.insert(x,p)
else:
    prof_dol.insert(x,'not_available')
six = str(data[5])
# profit in percentage we need to extract this as well
profper = re.findall( '>(.*?)%</td>',six)
#we keep only the numbers
if profper != empty:
    w = profper[0]
    a = w.replace(" ", "")
    p1 = a.replace("]", "")
    prof_per.insert(x,p1)
else:
    prof_per.insert(x,'not_available')
seven = str(data[6]) #assets
eight = str(data[7]) #assets in dollars we need to extract this
assetsdol= re.findall( '>\$(.*?)</td>',eight)
#we keep only the numbers
if assetsdol != empty:
    w = assetsdol[0]
    a = w.replace(" ", "")
    ass = a.replace("]", "")
    assets_dol.insert(x,ass)
else:
    assets_dol.insert(x,'not_available')
ten = str(data[9]) #Total Stockholder Equity ($M)
eleven = str(data[10])

```

```

#Total Stockholder Equity ($M) in dollars we need to extract this
tsedol= re.findall( '>\$(.+?)</td>',eleven)
#we keep only the numbers
if tsedol != empty:
    w = tsedol[0]
    a = w.replace(" ", "")
    ts = a.replace("]", "")
    tse_dol.insert(x,ts)
else:
    tse_dol.insert(x,'not_available')
thirteen = str(data[12]) # market value
fourteen = str(data[13])
# market value in dollars we need to extract this
mardol= re.findall( '>\$(.+?)</td>',fourteen)
#we keep only the numbers
if mardol != empty:
    w = mardol[0]
    a = w.replace(" ", "")
    mar = a.replace("]", "")
    mar_dol.insert(x,mar)
else:
    mar_dol.insert(x,'not_available')
x = x + 1
print "The_function_is_complete!"

```

```
fortune_metrics (list_company_name ,list_company_website)
```

The function **is** complete!

```

d9 = { 'company' : pd.Series(ln , index=[nm]) ,
       'Revenues_$' : pd.Series(rev_dol , index=[nm]) ,
       'Revenues_%' : pd.Series(rev_per , index=[nm]) ,
       'Assets_$' : pd.Series(assets_dol , index=[nm]) ,
       'Total_Stockholder_Equity_$' : pd.Series(tse_dol , index=[nm]) ,
       'Market_value_$' : pd.Series(mar_dol , index=[nm])}
fort500 = pd.DataFrame(d9)
fort500.head(3)

```

2.4.14 Merge data-frames and extract final csv file

The final step of the code is to create a final data frame which will include all the information gathered and then create a csv file that will be used for the further analysis that will be take place with the use of the program language R.

```
fort500.merge(html_val, left_on='company', right_on='company',
how='outer')
fort500.head(3)
result = pd.merge(fort500, html_val, how='inner', on=['company', 'company'])
result2 = pd.merge(social_media, fre, how='inner', on=['company', 'company'])
result3 = pd.merge(wordss, sizess, how='inner', on=['company', 'company'])
result4 = pd.merge(images_types, loading_time, how='inner',
on=['company', 'company'])
result5 = pd.merge(result, sites_links, how='inner', on=['company', 'company'])
result6 = pd.merge(result5, result2, how='inner', on=['company', 'company'])
result7 = pd.merge(result6, result3, how='inner', on=['company', 'company'])
final3 = pd.merge(result7, result4, how='inner', on=['company', 'company'])
final3.head(3)
final3.to_csv('total_500.csv', sep=';')

data500 = pd.read_csv("total_500.csv", sep=';')
data500.head(3)
```

3 Data Analysis

Now that we have gathered all the information needed the next step is to proceed to their analysis. For the purposes of this assignment we will use the programming language R to perform this analysis.

3.1 R and R-Studio

R is a programming language and software environment for statistical computing and graphics supported by the R Foundation for Statistical Computing. The R language is widely used among statisticians and data miners for developing statistical software and data analysis.

Furthermore R is freely available under the GNU General Public License, and pre-compiled binary versions are provided for various operating systems. While R has a command line interface, there are several graphical front-ends available. For the purpose of this paper we will use the R-Studio which is a free and open-source integrated development environment (IDE) for R.

3.2 Scripts

In this chapter we are going to present the scripts that we used throughout the analysis and we will explain elaborately how we reached to the conclusions. The analysis that we are going to perform will be explained by the following order as we performed it:

1. Data cleansing
2. Variable analysis and correlation
 - (a) Fortune variables correlation
 - (b) Social media analysis and correlation
 - (c) Links analysis and correlations
 - (d) Words analysis and correlation
 - (e) HTML validation variables analysis and correlation
 - (f) Image types analysis and correlation
3. Data manipulation
 - (a) Image sizes variables reconstruction
 - (b) Remove variables
4. Logistic Regression
 - (a) Training and test set creation
 - (b) Null and Full model creation
 - (c) Lasso Method

- (d) Both Method
 - (e) Predictions and comparison of models
5. Comparisons and other methods
- (a) Correlation testing
 - (b) Clustering testing
 - (c) Final testing
 - (d) Final model

3.2.1 Data cleansing

The first step in order to perform the analysis is to upload the final csv we have created and then change any miss fitted value or type of variable so as to be easier for us to examine them.

3.2.2 Variable analysis and correlation

Now that the variables are cleansed we can perform the first step of the analysis. We should see how the prices are distributed and get a first look of what we are examining.

3.2.2.1 Fortune variables correlation

The first step is to determine the variable with which we will compare all the other ones. Obviously this variable will be one of the metrics we downloaded from the fortune 500 site so as to have an actual variable that shows the status of the company and compare the rest of the variables with it.

3.2.2.2 Social media analysis and correlation

Now that we have reach to the conclusion that the metric we will use from the Fortune 500 is the Revenues we will proceed with analysing the social media variables to see how they are distributed and then to see how they are correlated with the chosen variable.

3.2.2.3 Links analysis and correlations

Next step is to analyse the distribution of the internal, external and total links and of course their correlation with each other and with the Revenues.

3.2.2.4 Words analysis and correlation

Continuing with the analysis of the unique words and the total words with correlation to the readability index.

3.2.2.5 HTML validation variables analysis and correlation

During the extraction of the html validation variables we created 4 different metrics: the number of errors, the number of warnings the non document error and the page not opened one. In this chapter we are going to analyse the distributions of those variables and also their correlation with the Revenues.

3.2.2.6 Image types analysis and correlation

Last but not least we should analyse the distribution of the different types of images that are being used on the websites that we are examining and also compare the total images with the Revenues to see the correlation.

3.2.3 Data manipulation

In this chapter we are going to change some of the variables that we have created in order to make them more easy to be analysed and explained in relationship to the Revenues.

3.2.3.1 Image sizes variables reconstruction

After implementing the python code for the size images (2.4.10) we created almost 700 different variables. This number is almost prohibited when it comes to regression models especially when the actual number of the examined cases are a lot fewer (500). That is why we decide to group this 700 variables to 5 new ones that we will be able to incorporate to this analysis.

3.2.3.2 Remove variables

Now that we have created and analysed all the needed variables we can subtract from the data frame the variables that we have decide not to include in the regression analysis that will follow.

3.2.4 Logistic Regression

In this chapter we will perform logistic regression to the chosen data frame in order to determine the variables that affect most the price of the Revenues of a company

3.2.4.1 Training and test set creation

Before we begin with the regression we have to divide the data frame to 2 data frames so as to be able to test the model we will create. We will make a training set and a test set.

3.2.4.2 Null and Full model creation

The first step is by using the training set to create a null model (that includes only the Revenues) and a full model (that includes all the variables)

3.2.4.3 Lasso Method

The next step is to implement the Lasso method

3.2.4.4 Both Method

We will continue by applying the both method of the logistic regression in order to see if the variables that will be kept are the same or less than the lasso method.

3.2.4.5 Predictions and comparison of models

Now we will make the predictions using the test set in order to compare how well do the model that we created work in practise.

3.2.5 Comparisons and other methods

Now that we have a first idea of the metrics that are considered more important it would be wise to use other methods to double check the results.

3.2.5.1 Correlation testing

By seeing the correlations of the chosen variables we could create models by subtracting some of them to see if the results will be improved.

3.2.5.2 Clustering testing

We will use the clustering method to see how the variables are being group together. And which variables play the most important role.

3.2.5.3 Final testing

Now we will compare the results to see if we can test any other theory so as to be sure about the final results.

3.2.5.4 Final model

After completing the analysis we can conclude that the most important variable of the websites that can play a crucial role to the actual revenues of a company are the images. More specifically the sizes and the type of the images along with the external links.

4 Conclusions

This conclusion can be easily explained from the fact that the eye is drawn to specific stimulations. There are many studies that show that where the eye is going in the first seconds that a user is visiting a page can be crucial. So the right type of image with a correct structure and use of specific image sizes can make a site more likeable and friendly to the users.

Example - Testing of where does the eye drop first

Example - Images and the importance to the psychology

Example - Type of images more easily and rapid loading

Example - Information that the user is looking for not confined only inside the same website

5 Bibliography

References

- [1] *<https://en.wikipedia.org/wiki/Fortune500>*
- [2] *<http://beta.fortune.com/fortune500>*
- [3] *<http://www.tablesgenerator.com/>*
- [4] *<https://www.continuum.io/downloads>*
- [5] *<https://validator.w3.org/>*
- [6] Rui Miguel Forte, Mastering Predictive Analytics with R, Packt Publishing Ltd., June 2015

A Appendix A: Fortune 500 Companies

Table 2: Fortune 500 - Companies Ranked: 51 - 100

51. Intel	52. Humana	53. Disney
54. Cisco Systems	55. Pfizer	56. Dow Chemical
57. Sysco	58. FedEx	59. Caterpillar
60. Lockheed Martin	61. N.Y. Life Insurance	62. Coca-Cola
63. HCA Holdings	64. Ingram Micro	65. Energy Transfer Equity
66. Tyson Foods	67. American Airlines Group	68. Delta Air Lines
69. Nationwide	70. Johnson Controls	71. Best Buy
72. Merck	73. Liberty Mutual I.G.	74. Goldman Sachs Group
75. Honeywell International	76. Massachusetts Mutual L.I.	77. Oracle
78. Morgan Stanley	79. Cigna	80. U.C. Holdings
81. Allstate	82. TIAA	83. INTL FCStone
84. CHS	85. American Express	86. Gilead Sciences
87. Publix Super Markets	88. General Dynamics	89. TJX
90. ConocoPhillips	91. Nike	92. World Fuel Services
93. 3M	94. Mondelez International	95. Exelon
96. Twenty-First Century Fox	97. Deere	98. Tesoro
99. Time Warner	100. Northwestern Mutual	

Table 3: Fortune 500 - Companies Ranked: 101 - 150

101. DuPont	102. Avnet	103. Macy's
104. Enterprise Products Partners	105. Travelers Cos.	106. Philip Morris International
107. Rite Aid	108. Tech Data	109. McDonald's
110. Qualcomm	111. Sears Holdings	112. Capital One Financial
113. EMC	114. USAA	115. Duke Energy
116. Time Warner Cable	117. Halliburton	118. Northrop Grumman
119. Arrow Electronics	120. Raytheon	121. Plains GP Holdings
122. US Foods Holding	123. AbbVie	124. Centene
125. Community Health Systems	126. Alcoa	127. International Paper
128. Emerson Electric	129. Union Pacific	130. Amgen
131. U.S. Bancorp	132. Staples	133. Danaher
134. Whirlpool	135. Aflac	136. AutoNation
137. Progressive	138. Abbott Laboratories	139. Dollar General
140. Tenet Healthcare	141. Eli Lilly	142. Southwest Airlines
143. Penske Automotive Group	144. ManpowerGroup	145. Kohl's
146. Starbucks	147. Paccar	148. Cummins
149. Altria Group	150. Xerox	

Table 4: Fortune 500 - Companies Ranked: 151 - 200

151. Kimberly-Clark	152. Hartford F.S.G.	153. Kraft Heinz
154. Lear	155. Fluor	156. AECOM
157. Facebook	158. Jabil Circuit	159. CenturyLink
160. Supervalu	161. General Mills	162. Southern
163. NextEra Energy	164. Thermo Fisher Scientific	165. American Electric Power
166. PG&E Corp.	167. NGL Energy Partners	168. Bristol-Myers Squibb
169. Goodyear Tire & Rubber	170. Nucor	171. PNC F.S.G.
172. Health Net	173. Micron Technology	174. Colgate-Palmolive
175. Freeport-McMoRan	176. ConAgra Foods	177. Gap
178. Baker Hughes	179. Bank of N.Y. Mellon C.	180. Dollar Tree
181. Whole Foods Market	182. PPG Industries	183. Genuine Parts
184. Icahn Enterprises	185. Performance Food Group	186. Omnicom Group
187. DISH Network	188. FirstEnergy	189. Monsanto
190. AES	191. CarMax	192. National Oilwell Varco
193. NRG Energy	194. Western Digital	195. Marriott International
196. Office Depot	197. Nordstrom	198. Kinder Morgan
199. Aramark	200. DaVita HealthCare Partners	

Table 5: Fortune 500 - Companies Ranked: 201 - 250

201. Molina Healthcare	202. WellCare Health Plans	203. CBS
204. Visa	205. Lincoln National	206. Ecolab
207. Kellogg	208. C.H. Robinson Worldwide	209. Textron
210. Loews	211. Illinois Tool Works	212. Synnex
213. Viacom	214. HollyFrontier	215. Land O'Lakes
216. Devon Energy	217. PBF Energy	218. Yum Brands
219. Texas Instruments	220. CDW	221. Waste Management
222. Marsh & McLennan	223. Chesapeake Energy	224. Parker-Hannifin
225. Occidental Petroleum	226. Guardian Life I.C.A.	227. Farmers Ins. Exchange
228. J.C. Penney	229. Consolidated Edison	230. Cognizant Tech. Solutions
231. VF	232. Ameriprise Financial	233. Computer Sciences
234. L Brands	235. Jacobs Engineering Group	236. Principal Financial
237. Ross Stores	238. Bed Bath & Beyond	239. CSX
240. Toys R Us	241. Las Vegas Sands	242. Leucadia National
243. Dominion Resources	244. United States Steel	245. L-3 Communications
246. Edison International	247. Entergy	248. ADP
249. First Data	250. BlackRock	

Table 6: Fortune 500 - Companies Ranked: 251 - 300

251. WestRock	252. Voya Financial	253. Sherwin-Williams
254. Hilton Worldwide Holdings	255. R.R. Donnelley & Sons	256. Stanley Black & Decker
257. Xcel Energy	258. Murphy USA	259. CBRE Group
260. D.R. Horton	261. Estee Lauder	262. Praxair
263. Biogen	264. State Street Corp.	265. Unum Group
266. Reynolds American	267. Group 1 Automotive	268. Henry Schein
269. Hertz Global Holdings	270. Norfolk Southern	271. Reinsurance G. of America
272. Public Service E. G.	273. BB&T Corp.	274. DTE Energy
275. Assurant	276. Global Partners	277. Huntsman
278. Becton Dickinson	279. Semptra Energy	280. AutoZone
281. Navistar International	282. Precision Castparts	283. Discover F. S.
284. Liberty Interactive	285. W.W. Grainger	286. Baxter International
287. Stryker	288. Air Products & Chemicals	289. Western Refining
290. Universal Health Services	291. Owens & Minor	292. Charter Communications
293. Advance Auto Parts	294. MasterCard	295. Applied Materials
296. Eastman Chemical	297. Sonic Automotive	298. Ally Financial
299. CST Brands	300. eBay	

Table 7: Fortune 500 - Companies Ranked: 301 - 350

301. Lennar	302. GameStop	303. Reliance Steel & Aluminum
304. Hormel Foods	305. Celgene	306. Genworth Financial
307. PayPal Holdings	308. Priceline Group	309. MGM Resorts International
310. Autoliv	311. Fidelity National Financial	312. Republic Services
313. Corning	314. Peter Kiewit Sons'	315. Univar
316. Mosaic	317. Core-Mark Holding	318. Thrivent F. for Lutherans
319. Cameron International	320. HD Supply Holdings	321. Crown Holdings
322. EOG Resources	323. Veritiv	324. Anadarko Petroleum
325. Laboratory C. of A.	326. Pacific Life	327. News Corp.
328. Jarden	329. SunTrust Banks	330. Avis Budget Group
331. Broadcom	332. American Family I. G.	333. Level 3 Communications
334. Tenneco	335. United Natural Foods	336. Dean Foods
337. Campbell Soup	338. Mohawk Industries	339. BorgWarner
340. PVH	341. Ball	342. O'Reilly Automotive
343. Eversource Energy	344. Franklin Resources	345. Masco
346. Lithia Motors	347. KKR	348. Oneok
349. Newmont Mining	350. PPL	

Table 8: Fortune 500 - Companies Ranked: 351 - 400

351. SpartanNash	352. Quanta Services	353. XPO Logistics
354. Ralph Lauren	355. Interpublic Group	356. Steel Dynamics
357. WESCO International	358. Quest Diagnostics	359. Boston Scientific
360. AGCO	361. Foot Locker	362. Hershey
363. CenterPoint Energy	364. Williams	365. Dick's Sporting Goods
366. Live Nation Entertainment	367. Mutual of Omaha Ins.	368. W.R. Berkley
369. LKQ	370. Avon Products	371. Darden Restaurants
372. Kindred Healthcare	373. Weyerhaeuser	374. Casey's General Stores
375. Sealed Air	376. Fifth Third Bancorp	377. Dover
378. Huntington Ingalls Industries	379. Netflix	380. Dillard's
381. EMCOR Group	382. Jones Financial	383. AK Steel Holding
384. UGI	385. Expedia	386. salesforce.com
387. Targa Resources	388. Apache	389. Spirit AeroSystems H.
390. Expeditors Inter. of Washington	391. Anixter International	392. Fidelity N. Inf. S.
393. Asbury Automotive Group	394. Hess	395. Ryder System
396. Terex	397. Coca-Cola Eur. P.	398. Auto-Owners Insurance
399. Cablevision Systems	400. Symantec	

Table 9: Fortune 500 - Companies Ranked: 401 - 450

401. Charles Schwab	402. Calpine	403. CMS Energy
404. Alliance Data Systems	405. JetBlue Airways	406. Discovery Communic.
407. Trinity Industries	408. Sanmina	409. NCR
410. FMC Technologies	411. Erie Insurance Group	412. Rockwell Automation
413. Dr Pepper Snapple Group	414. iHeartMedia	415. Tractor Supply
416. J.B. Hunt Transport Services	417. Commercial Metals	418. Owens-Illinois
419. Harman Inter. Ind.	420. Baxalta	421. American F. G.
422. NetApp	423. Graybar Electric	424. Oshkosh
425. Ameren	426. A-Mark Precious Metals	427. Barnes & Noble
428. Dana Holding	429. Constellation Brands	430. LifePoint Health
431. Zimmer Biomet H.	432. Harley-Davidson	433. PulteGroup
434. Newell Brands	435. Avery Dennison	436. Jones Lang LaSalle
437. WEC Energy Group	438. Marathon Oil	439. TravelCenters of A.
440. United Rentals	441. HRG Group	442. Old Republic Inter.
443. Windstream Holdings	444. Starwood Hotels & Resorts	445. Delek US Holdings
446. Packaging Corp. of A.	447. Quintiles Transnational H.	448. Hanesbrands
449. Realogy Holdings	450. Mattel	

Table 10: Fortune 500 - Companies Ranked: 451 - 500

451. Motorola Solutions	452. J.M. Smucker	453. Regions Financial
454. Celanese	455. Clorox	456. Ingredion
457. Genesis Healthcare	458. Peabody Energy	459. Alaska Air Group
460. Seaboard	461. Frontier Communic.	462. Amphenol
463. Lansing Trade Group	464. SanDisk	465. St. Jude Medical
466. Wyndham Worldwide	467. Kelly Services	468. Western Union
469. Envision Healthcare H.	470. Visteon	471. Arthur J. Gallagher
472. Host Hotels & Resorts	473. Ashland	474. Insight Enterprises
475. Energy Future Holdings	476. Markel	477. Essendant
478. CH2M Hill	479. Western & Southern F.G.	480. Owens Corning
481. S&P Global	482. Raymond James Financial	483. NiSource
484. Airgas	485. ABM Industries	486. Citizens F.G.
487. Booz Allen Hamilton H.	488. Simon Property Group	489. Domtar
490. Rockwell Collins	491. Lam Research	492. Fiserv
493. Spectra Energy	494. Navient	495. Big Lots
496. Telephone & Data Systems	497. First American Financial	498. NVR
499. Cincinnati Financial	500. Burlington Stores	
