



set:
architectural
status:
concept issue
file name:
176 Bellevue Road - Duplex Development_Lot 11.pln
drawn by:



East / ROW Elevation





CL4

Factory Painted 0.55 Steel Flashing Colour to Match Cladding

CL2

James Hardies Stria Vertical Cladding on 20mm Cavity

CL5

Framed Glass Balustrade 'Full Height Top Fix' , with Glazing as per NZS4331

CL4

Factory Painted 0.55 Steel Flashing Colour to Match Cladding

CL2

James Hardies Stria Vertical Cladding on 20mm Cavity

set: architectur status:

status: concept issue file name: 176 Bellevue Road - Duplex Development_Lot 11.pln 176 Bellevue Road





job no:
set:
architectural
status:
concept issue
file name:
176 Bellevue Road - Duplex Development_Lot 11.pln
drawn by:


| Content of the cont

FRAMING FIXING KEY:

All lintel fixings have been designed as per NZS3604:2011. 8.6.1.8, Fig 8.12 & Table 8.14

F1 = Lintel to trimming stud, fixed with 3/90x3.15mm power-driven nails (end nailed), or 2/100x3.75mm hand-driven nails (end nailed).

F2 = Lintel fixing for uplift, fixed as per NZS3604 Fig 8.12 (refer to NZS Requirements Detail page),or alternative fixing of 7.5 kN capacity in tension along the line of the trimming stud.



S1 = 90 x 45mm SG8 H1.2 Framing @ 400 centres

S2 = 70 x 45mm SG8 H1.2 Framing @ 600 centres

S3 = 90 x 45mm x (1200h x 600w) SG8 H1.2 Framing @ 400 centres

S4 = 90 x 45mm SG8 H1.2 Framing @ 400 centres

job no: set: architectural status: concept issue file name: 176 Bellevue Road - Duplex Development_Lot 11,pln drawn by:

176 Bellevue Road

FRAMING NOTATION:

All studs have been calculated as per NZS 3604:2011 Table 8.2.

All new timber framing shown to be 'SG8' & 'H1.2'.

All lintels shown are to be 'SG8' & 'H1.2' (apart from HySpan lintels).

All timber lintels to be supported with 2/90x45mm SG8 timber studs (at each end) as per NZS3604:2011 Figure 8.5.

All timber lintels to be fixed in accordance with NZS3604:2011 Figure 8.12, for fixing of lintels to prevent uplift.

Ensure D.P.C. or approved equivalent to be placed between all timber members & concrete substrates.

All new structural members & lintels to be positioned within roof space or as high as possible, due to flush ceiling finish.

LOAD BEARING STUD REQUIREMENTS:

All framing to be H1.2 SG8 timber framing as per NZS 3604:2011.

Designed for Very High Wind Zone Table 8.2 NOTE: Studs 70mm and 90mm thick may be substituted with built-up members, nailed together in accordance with 2.4.4.7

90x45mm SG8 H1.2 wall framing

- studs @ 400mm crs. to max. 2.4m high
- studs @ 300mm crs. to max. 3.0m high


90x70mm SG8 H1.2 wall framing

- studs @ 600mm crs. to max. 2,7m high

NON-LOAD BEARING STUD REQUIREMENTS: NZS3604 Table 8.4 Internal Walls all wind zones

70x45mm SG8 H1.2 wall framing


- studs @ 600mm crs. to max. 2.4m high
- studs @ 400mm crs. to max. 2.7m high




S1 Note: Load Bearing Exterior Wall. 90 x 45mm SG8 H1.2 Framing @ 400 centres


S2 Note: Non Loadbearing Wall.70 x 45mm SG8 H1.2 Framing @ 600 centres


set:
architectural
status:
concept issue
file name:
176 Bellevue Road - Duplex Development_Lot 11.pln





set:
architectural
status:
concept issue
file name:
176 Bellevue Road - Duplex Development_Lot 11.pln





Bearers: Dwelling H3.2 SG8 140x70

Deck H3.2 SG8 140 x 90

Piles:


125x125 H5 Timber Piles. Length & Embedment Varies

Joists: Dwelling H3.2 SG8 190x45 @ 400 Centres

Deck H3.2 SG8 190 x 45 @ 400 Centres

job no:
set:
architectural
status:
concept issue
file name:
176 Bellevue Road - Duplex Development_Lot 11.pln
drawn by:

Note: All Fixings, Connections & Flashings to comply with NZBC, E2/AS1 & NZS3604 for Very High Wind Zone



job no:
set:
architectural
status:
concept issue
file name:
176 Bellevue Road - Duplex Development_Lot 11.pln
drawn br.