



Lesson 11. Cluster Analysis

- What is Cluster Analysis?
- Types of Data in Cluster Analysis
- A Categorization of Major Clustering Methods
- Partitioning Methods
- Hierarchical Methods
- Density-Based Methods
- Grid-Based Methods
- Model-Based Clustering Methods
- Outlier Analysis
- Summary




What is Cluster Analysis?

- Cluster: a collection of data objects
 - Similar to one another within the same cluster
 - Dissimilar to the objects in other clusters
- Cluster analysis
 - Grouping a set of data objects into clusters
- Clustering is **unsupervised classification**: no predefined classes
- Typical applications
 - As a **stand-alone tool** to get insight into data distribution
 - As a **preprocessing step** for other algorithms

Examples of Clustering Applications

- **Information retrieval:** document clustering
- **Land use:** Identification of areas of similar land use in an earth observation database
- **Marketing:** Develop targeted marketing programs
- **City planning:** Identifying groups of houses according to their house type, value, and geographical location
- **Earthquake studies:** Observe earthquake epicenters
- **Climate:** understanding earth climate, find patterns of atmospheric and ocean





What Is Good Clustering?

- A good clustering method will produce high quality clusters with
 - high intra-class similarity
 - low inter-class similarity
- The quality of a clustering result depends on both the similarity measure used by the method and its implementation.
- The quality of a clustering method is also measured by its ability to discover some or all of the hidden patterns.



Requirements of Clustering in Data Mining

- Scalability (**Big Data**)
- Ability to deal with different types of attributes
- Discovery of clusters with arbitrary shape
- Minimal requirements for domain knowledge to determine input parameters
- Able to deal with noise and outliers
- Incremental clustering and insensitivity to input order
- High dimensionality
- Incorporation of user-specified constraints
- Interpretability and usability



Lesson 12. Cluster Analysis

- What is Cluster Analysis?
- Types of Data in Cluster Analysis
- A Categorization of Major Clustering Methods
 - Partitioning Methods
 - Hierarchical Methods
 - Density-Based Methods
 - Grid-Based Methods
 - Model-Based Clustering
 - Outlier Analysis
- Summary

Data Structures

■ Data matrix

- p – number of variables
- n – number of objects
- x_{if} – value of variable i in record f

$$\begin{bmatrix} x_{11} & \dots & x_{1f} & \dots & x_{1p} \\ \dots & \dots & \dots & \dots & \dots \\ x_{i1} & \dots & x_{if} & \dots & x_{ip} \\ \dots & \dots & \dots & \dots & \dots \\ x_{n1} & \dots & x_{nf} & \dots & x_{np} \end{bmatrix}$$

■ Dissimilarity matrix

- $d(i,j)$ – distance between objects i and j

$$\begin{bmatrix} 0 & & & & \\ d(2,1) & 0 & & & \\ d(3,1) & d(3,2) & 0 & & \\ \vdots & \vdots & \vdots & & \\ d(n,1) & d(n,2) & \dots & \dots & 0 \end{bmatrix}$$

Attribute Types in Clustering Analysis

- **Nominal:** categories, states, or “names of things”
 - *Hair_color* = {auburn, black, blond, brown, grey, red, white}
 - marital status, occupation, ID numbers, zip codes
- **Binary**
 - Nominal attribute with only 2 states (0 and 1)
 - Symmetric binary: both outcomes equally important
 - e.g., gender
 - Asymmetric binary: outcomes not equally important.
 - e.g., medical test (positive vs. negative), TF
 - Convention: assign 1 to most important outcome (e.g., HIV positive)
- **Ordinal**
 - Values have a meaningful order (ranking) but magnitude between successive values is not known.
 - *Size* = {small, medium, large}, grades, army rankings





Numeric Attribute Types

- Quantity (integer or real-valued)
- **Interval**
 - Measured on a scale of **equal-sized units**
 - Values have order
 - E.g., *temperature in C° or F° , calendar dates*
 - No true zero-point
- **Ratio**
 - Inherent **zero-point**
 - We can speak of values as being an order of magnitude larger than the unit of measurement (10 K° is twice as high as 5 K°).
 - e.g., *temperature in Kelvin, length, counts, monetary quantities*



Interval-scaled variables

- Goal: give all variables (age (years), height (cm), etc.) an equal weight
- Standardize data (n – number of objects)
 - Calculate the mean absolute deviation for variable f :

$$s_f = \frac{1}{n}(|x_{1f} - m_f| + |x_{2f} - m_f| + \dots + |x_{nf} - m_f|)$$

- Where the mean value of f is $m_f = \frac{1}{n}(x_{1f} + x_{2f} + \dots + x_{nf})$.
- Calculate the standardized measurement (z-score)

$$z_{if} = \frac{x_{if} - m_f}{s_f}$$

- Using mean absolute deviation is more robust than using standard deviation, since deviations are not squared



Similarity and Dissimilarity Between Objects

- Distances are normally used to measure the similarity or dissimilarity between two data objects

- Requirements

- *Non-negativity*: $d(i,j) \geq 0$
- *Distance to itself*: $d(i,i) = 0$
- *Symmetry*: $d(i,j) = d(j,i)$
- *Triangular inequality*: $d(i,j) \leq d(i,k) + d(k,j)$

- Some popular ones include: Minkowski distance:

$$d(i,j) = \sqrt[q]{(|x_{i1} - x_{j1}|^q + |x_{i2} - x_{j2}|^q + \dots + |x_{ip} - x_{jp}|^q)}$$

- where $i = (x_{i1}, x_{i2}, \dots, x_{ip})$ and $j = (x_{j1}, x_{j2}, \dots, x_{jp})$ are two p -dimensional data objects, and q is a positive integer



Similarity and Dissimilarity Between Objects (Cont.)

- If $q = 1$, d is Manhattan distance

$$d(i, j) = |x_{i_1} - x_{j_1}| + |x_{i_2} - x_{j_2}| + \dots + |x_{i_p} - x_{j_p}|$$

- If $q = 2$, d is Euclidean distance:

$$d(i, j) = \sqrt{(|x_{i_1} - x_{j_1}|^2 + |x_{i_2} - x_{j_2}|^2 + \dots + |x_{i_p} - x_{j_p}|^2)}$$

- Other dissimilarity measures are available



Binary Variables

- A contingency table for binary data
 - p – number of variables
- Distance measure for symmetric binary variables:
- Distance measure for asymmetric binary variables:
- Jaccard coefficient (*similarity* measure for asymmetric binary variables):

		Object j		
		1	0	sum
Object i	1	a	b	$a+b$
	0	c	d	$c+d$
sum		$a+c$	$b+d$	p

$$d(i, j) = \frac{b+c}{a+b+c+d}$$

$$d(i, j) = \frac{b+c}{a+b+c}$$

$$sim_{Jaccard}(i, j) = \frac{a}{a+b+c}$$

Dissimilarity between Binary Variables

Example

Name	Gender	Fever	Cough	Test-1	Test-2	Test-3	Test-4
Jack	M	Y	N	P	N	N	N
Mary	F	Y	N	P	N	P	N
Jim	M	Y	P	N	N	N	N

- gender is a symmetric attribute
- the remaining attributes are asymmetric binary
- let the values *Y* and *P* be set to 1, and the value *N* be set to 0

$$d(i, j) = \frac{b + c}{a + b + c}$$

$$d(jack, mary) = \frac{0 + 1}{2 + 0 + 1} = 0.33$$

$$d(jack, jim) = \frac{1 + 1}{1 + 1 + 1} = 0.67$$

$$d(jim, mary) = \frac{1 + 2}{1 + 1 + 2} = 0.75$$

	Jack			sum
	1	0		
Mary	1	2	1	3
	0	0	3	3
sum	2	4		6



Nominal Variables

- A generalization of the binary variable in that it can take more than 2 states, e.g., red, yellow, blue, green
- Method 1: Simple matching
 - m : # of matches, p : total # of variables

$$d(i, j) = \frac{p - m}{p}$$

- Method 2: use a large number of binary variables
 - creating a new binary variable for each of the M nominal states



Ordinal Variables

- An ordinal variable can be discrete or continuous
- Order is important, e.g., rank
- Can be treated like interval-scaled
 - replace x_{if} by their rank
 - map the range of each variable onto $[0, 1]$ by replacing $r_{if} \in \{1, \dots, M_f\}$ i -th object in the f -th variable by

$$z_{if} = \frac{r_{if} - 1}{M_f - 1}$$

- Example: academic ranks in Israel
- compute the dissimilarity using methods for interval-scaled variables



Ratio-Scaled Variables

- Ratio-scaled variable: a positive measurement on a nonlinear scale, approximately at exponential scale, such as Ae^{Bt} or Ae^{-Bt}
 - Examples: salaries, web links
- Methods:
 - treat them like interval-scaled variables—*not a good choice!* (why?—the scale can be distorted)
 - apply logarithmic transformation
$$y_{if} = \log(x_{if})$$
 - treat them as continuous ordinal data treat their rank as interval-scaled

Variables of Mixed Types

- A database may contain all the six types of variables
 - symmetric binary, asymmetric binary, nominal, ordinal, interval and ratio
- One may use a weighted formula to combine their effects

$$d(i, j) = \frac{\sum_{f=1}^P \delta_{ij}^{(f)} d_{ij}^{(f)}}{\sum_{f=1}^P \delta_{ij}^{(f)}}$$

- $\delta_{ij}(f)$ – binary indicator ($\delta_{ij}(f) = 0$ if a variable f should be skipped)
- $d_{ij}^{(f)}$ – contribution of variable f to dissimilarity between i and j
- *Variable f* is binary or nominal:
 - $d_{ij}^{(f)} = 0$ if $x_{if} = x_{jf}$, or $d_{ij}^{(f)} = 1$ otherwise
- *Variable f* is interval-based: use the normalized distance
- *Variable f* is ordinal or ratio-scaled
 - compute ranks r_{if} and
 - and treat z_{if} as interval-scaled

$$z_{if} = \frac{r_{if} - 1}{M_f - 1}$$



Vector Objects

- Vector objects: keywords in documents, gene features in micro-arrays, etc.
- Broad applications: information retrieval, biologic taxonomy, etc.
- Cosine measure

$$s(\vec{X}, \vec{Y}) = \frac{\vec{X}^t \cdot \vec{Y}}{|\vec{X}| |\vec{Y}|},$$

\vec{X}^t is a transposition of vector \vec{X} , $|\vec{X}|$ is the Euclidean normal of vector \vec{X} ,



Lesson 12. Cluster Analysis

- What is Cluster Analysis?
- Types of Data in Cluster Analysis
- A Categorization of Major Clustering Methods
- Partitioning Methods
- Hierarchical Methods
- Density-Based Methods
- Grid-Based Methods
- Model-Based Clustering Methods
- Outlier Analysis
- Summary

Major Clustering Approaches (I)

- Partitioning approach:
 - Construct various partitions and then evaluate them by some criterion, e.g., minimizing the sum of square errors
 - Typical methods: k-means, k-medoids, CLARANS
- Hierarchical approach:
 - Create a hierarchical decomposition of the set of data (or objects) using some criterion
 - Typical methods: Diana, Agnes, BIRCH, CAMELEON
- Density-based approach:
 - Based on connectivity and density functions
 - Typical methods: DBSACN, OPTICS, DenClue
- Grid-based approach:
 - based on a multiple-level granularity structure
 - Typical methods: STING, WaveCluster, CLIQUE



Major Clustering Approaches (II)

- Model-based:

- A model is hypothesized for each of the clusters and tries to find the best fit of that model to each other
- Typical methods: EM, SOM, COBWEB

- Frequent pattern-based:

- Based on the analysis of frequent patterns
- Typical methods: p-Cluster

- User-guided or constraint-based:

- Clustering by considering user-specified or application-specific constraints
- Typical methods: COD (obstacles), constrained clustering

- Link-based clustering:

- Objects are often linked together in various ways
- Massive links can be used to cluster objects: SimRank, LinkClus



Typical Alternatives to Calculate the Distance between Clusters

- Single link: smallest distance between an element in one cluster and an element in the other, i.e., $dis(K_i, K_j) = \min(t_{ip}, t_{jq})$
- Complete link: largest distance between an element in one cluster and an element in the other, i.e., $dis(K_i, K_j) = \max(t_{ip}, t_{jq})$
- Average: avg distance between an element in one cluster and an element in the other, i.e., $dis(K_i, K_j) = avg(t_{ip}, t_{jq})$
- Centroid: distance between the centroids of two clusters, i.e., $dis(K_i, K_j) = dis(C_i, C_j)$
- Medoid: distance between the medoids of two clusters, i.e., $dis(K_i, K_j) = dis(M_i, M_j)$
 - Medoid: one chosen, centrally located object in the cluster



Centroid, Radius and Diameter of a Cluster (for numerical data sets)

- Centroid: the “middle” of a cluster
$$C_m = \frac{\sum_{i=1}^N (t_{ip})}{N}$$

- Radius: square root of average distance from any point of the cluster to its centroid

$$R_m = \sqrt{\frac{\sum_{i=1}^N (t_{ip} - c_m)^2}{N}}$$

- Diameter: square root of average mean squared distance between all pairs of points in the cluster

$$D_m = \sqrt{\frac{\sum_{i=1}^N \sum_{q=1}^N (t_{ip} - t_{iq})^2}{N(N-1)}}$$



Lesson 12. Cluster Analysis

- What is Cluster Analysis?
- Types of Data in Cluster Analysis
- A Categorization of Major Clustering Methods
- **Partitioning Methods**
- Hierarchical Methods
- Density-Based Methods
- Grid-Based Methods
- Model-Based Clustering Methods
- Outlier Analysis
- Summary



Partitioning Algorithms: Basic Concept

- Partitioning method: Partitioning a database ***D*** of ***n*** objects into a set of ***k*** clusters, such that the sum of squared distances is minimized (where c_i is the centroid or medoid of cluster C_i)

$$E = \sum_{i=1}^k \sum_{p \in C_i} (p - c_i)^2$$


- Given k , find a partition of k *clusters* that optimizes the chosen partitioning criterion
 - Global optimal: exhaustively enumerate all partitions
 - Heuristic methods: *k-means* and *k-medoids* algorithms
 - *k-means* (MacQueen'67, Lloyd'57/'82): Each cluster is represented by the center of the cluster
 - *k-medoids* or PAM (Partition around medoids) (Kaufman & Rousseeuw'87): Each cluster is represented by one of the objects in the cluster



The *K-Means* Clustering Method

- Given k , the *k-means* algorithm is implemented in four steps:
 - Partition objects into k nonempty subsets
 - Compute seed points as the centroids of the clusters of the current partitioning (the centroid is the center, i.e., *mean point*, of the cluster)
 - Assign each object to the cluster with the nearest seed point
 - Go back to Step 2, stop when the assignment does not change

An Example of *K-Means* Clustering



- Partition objects into k nonempty subsets
- Repeat
 - Compute centroid (i.e., mean point) for each partition
 - Assign each object to the cluster of its nearest centroid
- Until no change



K-Means Example ($k = 2$)

Iteration 1

Cluster 1

Rec No	X1	X2	X3	X4	X5
1	0	0	0	0	0
2	0	0	0	0	0
3	1	1	1	1	1
Mean	0.33	0.33	0.33	0.33	0.33

Cluster 2

Rec No	X1	X2	X3	X4	X5
4	1	0	1	0	1
5	0	1	0	1	0
6	1	0	1	1	1
7	1	1	1	1	1
Mean	0.75	0.5	0.75	0.75	0.75

Objects Re-assignment

Rec No	Old	to Cluster 1	to Cluster 2	Min	New
1	1	0.745	1.581	0.745	1
2	1	0.745	1.581	0.745	1
3	1	1.491	0.707	0.707	2
4	2	1.247	1.000	1.000	2
5	2	1.106	1.414	1.106	1
6	2	1.374	0.707	0.707	2
7	2	1.491	0.707	0.707	2



K-Means Example ($k = 2$)

Iteration 2

Cluster 1

Rec No	X1	X2	X3	X4	X5
1	0	0	0	0	0
2	0	0	0	0	0
5	0	1	0	1	0
Mean	0.00	0.33	0.00	0.33	0.00

Cluster 2

Rec No	X1	X2	X3	X4	X5
3	1	1	1	1	1
4	1	0	1	0	1
6	1	0	1	1	1
7	1	1	1	1	1
Mean	1	0.5	1	0.75	1

Objects Re-assignment

Rec No	Old	to Cluster 1	to Cluster 2	Min	New
1	1	0.471	1.953	0.471	1
2	1	0.471	1.953	0.471	1
3	2	1.972	0.559	0.559	2
4	2	1.795	0.901	0.901	2
5	1	0.943	1.820	0.943	1
6	2	1.886	0.559	0.559	2
7	2	1.972	0.559	0.559	2

Comments on the *K-Means* Method

- Strength: *Efficient*: $O(tkn)$, where n is # objects, k is # clusters, and t is # iterations. Normally, $k, t \ll n$.
 - Comparing: PAM: $O(k(n-k)^2)$, CLARA: $O(ks^2 + k(n-k))$
- Comment: Often terminates at a *local optimal*.
- Weakness
 - Applicable only to objects in a continuous n -dimensional space
 - Using the k-modes method for categorical data
 - In comparison, k-medoids can be applied to a wide range of data
 - Need to specify k , the *number* of clusters, in advance (there are ways to automatically determine the best k (see Hastie et al., 2009))
 - Sensitive to noisy data and *outliers*
 - Not suitable to discover clusters with *non-convex shapes*




Variations of the *K-Means* Method

- A few variants of the *k-means* which differ in
 - Selection of the initial *k* means
 - Dissimilarity calculations
 - Strategies to calculate cluster means
- Handling categorical data: *k-modes* (Huang'98)
 - Replacing means of clusters with modes
 - Using new dissimilarity measures to deal with categorical objects
 - Using a frequency-based method to update modes of clusters
 - A mixture of categorical and numerical data: *k-prototype* method


What is the problem of k-Means Method?

- The k-means algorithm is sensitive to outliers !
 - Since an object with an extremely large value may substantially distort the distribution of the data.
- K-Medoids: Instead of taking the **mean** value of the object in a cluster as a reference point, **medoids** can be used, which is the **most centrally located** object in a cluster.




PAM: A Typical K-Medoids Algorithm


Total Cost = 20



Arbitrary
choose k
objects
as initial
medoids



Assign
each
remaining
object to
nearest
medoids




K=2


Do loop
Until no
change

Swapping O
and O_{random}
If quality is
improved.

Total Cost = 26



Compute
total cost of
swapping



The K-Medoid Clustering Method

- *K-Medoids* Clustering: Find *representative* objects (medoids) in clusters
 - *PAM* (Partitioning Around Medoids, Kaufmann & Rousseeuw 1987)
 - Starts from an initial set of medoids and iteratively replaces one of the medoids by one of the randomly selected non-medoids if it decreases the total distance of the resulting clustering
 - Each object is assigned to a cluster represented by the nearest medoid
 - *PAM* works effectively for small data sets, but does not scale well for large data sets (due to the computational complexity)
 - Efficiency improvement on PAM
 - *CLARA* (Kaufmann & Rousseeuw, 1990): PAM on samples
 - *CLARANS* (Ng & Han, 1994): Randomized re-sampling




Lesson 12. Cluster Analysis

- What is Cluster Analysis?
- Types of Data in Cluster Analysis
- A Categorization of Major Clustering Methods
- Partitioning Methods
- **Hierarchical Methods**
- Density-Based Methods
- Grid-Based Methods
- Model-Based Clustering Methods
- Outlier Analysis
- Summary




Hierarchical Clustering

- Use distance matrix as clustering criteria. This method does not require the number of clusters k as an input, but needs a termination condition



AGNES (Agglomerative Nesting)


- Introduced in Kaufmann and Rousseeuw (1990)
- Implemented in statistical analysis packages, e.g., Splus
- Use the Single-Link method and the dissimilarity matrix.
- Merge nodes that have the least dissimilarity
- Go on in a non-descending fashion
- Eventually all nodes belong to the same cluster



Dendrogram: Shows How the Clusters are Merged

Decompose data objects into a several levels of nested partitioning (tree of clusters), called a dendrogram.

A clustering of the data objects is obtained by cutting the dendrogram at the desired level, then each connected component forms a cluster.





Agglomerative Clustering Example


Data Objects:

Rec No	X1	X2	X3	X4	X5
1	0	0	0	0	0
2	0	0	0	0	0
3	1	1	1	1	1
4	1	0	1	0	1
5	0	1	0	1	0
6	1	0	1	1	1
7	1	1	1	1	1

Dissimilarity
Matrix
(Euclidean
Distances):

Rec No	Dist1	Dist2	Dist3	Dist4	Dist5	Dist6	Dist7
1							
2	0.000						
3	2.236	2.236					
4	1.732	1.732	1.414				
5	1.414	1.414	1.732	2.236			
6	2.000	2.000	1.000	1.000	2.000		
7	2.236	2.236	0.000	1.414	1.732	1.000	

Agglomerative Clustering Example (cont.)



More on Hierarchical Clustering Methods

- Major weakness of agglomerative clustering methods
 - do not scale well: time complexity of at least $O(n^2)$, where n is the number of total objects
 - can never undo what was done previously
- Integration of hierarchical with distance-based clustering
 - BIRCH (1996): uses CF-tree and incrementally adjusts the quality of sub-clusters
 - CURE (1998): selects well-scattered points from the cluster and then shrinks them towards the center of the cluster by a specified fraction
 - CHAMELEON (1999): hierarchical clustering using dynamic modeling



Summary

- **Cluster analysis** groups objects based on their **similarity** and has wide applications
- Measure of similarity can be computed for **various types of data**
- Clustering algorithms can be **categorized** into partitioning methods, hierarchical methods, density-based methods, grid-based methods, and model-based methods
- **Outlier detection** and analysis are very useful for fraud detection, etc. and can be performed by statistical, distance-based or deviation-based approaches
- There are still lots of research issues on cluster analysis, such as **efficient clustering in big data environment**



References (1)

- R. Agrawal, J. Gehrke, D. Gunopulos, and P. Raghavan. Automatic subspace clustering of high dimensional data for data mining applications. SIGMOD'98
- M. R. Anderberg. Cluster Analysis for Applications. Academic Press, 1973.
- M. Ankerst, M. Breunig, H.-P. Kriegel, and J. Sander. Optics: Ordering points to identify the clustering structure, SIGMOD'99.
- Beil F., Ester M., Xu X.: "Frequent Term-Based Text Clustering", KDD'02
- M. M. Breunig, H.-P. Kriegel, R. Ng, J. Sander. LOF: Identifying Density-Based Local Outliers. SIGMOD 2000.
- M. Ester, H.-P. Kriegel, J. Sander, and X. Xu. A density-based algorithm for discovering clusters in large spatial databases. KDD'96.
- M. Ester, H.-P. Kriegel, and X. Xu. Knowledge discovery in large spatial databases: Focusing techniques for efficient class identification. SSD'95.
- D. Fisher. Knowledge acquisition via incremental conceptual clustering. Machine Learning, 2:139-172, 1987.
- D. Gibson, J. Kleinberg, and P. Raghavan. Clustering categorical data: An approach based on dynamic systems. VLDB'98.
- V. Ganti, J. Gehrke, R. Ramakrishan. CACTUS Clustering Categorical Data Using Summaries. KDD'99.



References (2)

- D. Gibson, J. Kleinberg, and P. Raghavan. Clustering categorical data: An approach based on dynamic systems. In Proc. VLDB'98.
- S. Guha, R. Rastogi, and K. Shim. Cure: An efficient clustering algorithm for large databases. SIGMOD'98.
- S. Guha, R. Rastogi, and K. Shim. ROCK: A robust clustering algorithm for categorical attributes. In *ICDE'99*, pp. 512-521, Sydney, Australia, March 1999.
- A. Hinneburg, D. I. A. Keim: An Efficient Approach to Clustering in Large Multimedia Databases with Noise. KDD'98.
- A. K. Jain and R. C. Dubes. Algorithms for Clustering Data. Printice Hall, 1988.
- G. Karypis, E.-H. Han, and V. Kumar. CHAMELEON: A Hierarchical Clustering Algorithm Using Dynamic Modeling. *COMPUTER*, 32(8): 68-75, 1999.
- L. Kaufman and P. J. Rousseeuw. Finding Groups in Data: an Introduction to Cluster Analysis. John Wiley & Sons, 1990.
- E. Knorr and R. Ng. Algorithms for mining distance-based outliers in large datasets. VLDB'98.



References (3)

- G. J. McLachlan and K.E. Bkasford. Mixture Models: Inference and Applications to Clustering. John Wiley and Sons, 1988.
- R. Ng and J. Han. Efficient and effective clustering method for spatial data mining. VLDB'94.
- L. Parsons, E. Haque and H. Liu, Subspace Clustering for High Dimensional Data: A Review, SIGKDD Explorations, 6(1), June 2004
- E. Schikuta. Grid clustering: An efficient hierarchical clustering method for very large data sets. Proc. 1996 Int. Conf. on Pattern Recognition
- G. Sheikholeslami, S. Chatterjee, and A. Zhang. WaveCluster: A multi-resolution clustering approach for very large spatial databases. VLDB'98.
- A. K. H. Tung, J. Han, L. V. S. Lakshmanan, and R. T. Ng. Constraint-Based Clustering in Large Databases, ICDT'01.
- A. K. H. Tung, J. Hou, and J. Han. Spatial Clustering in the Presence of Obstacles, ICDE'01
- H. Wang, W. Wang, J. Yang, and P.S. Yu. Clustering by pattern similarity in large data sets, SIGMOD'02
- W. Wang, Yang, R. Muntz, STING: A Statistical Information grid Approach to Spatial Data Mining, VLDB'97
- T. Zhang, R. Ramakrishnan, and M. Livny. BIRCH : An efficient data clustering method for very large databases. SIGMOD'96
- X. Yin, J. Han, and P. S. Yu, "LinkClus: Efficient Clustering via Heterogeneous Semantic Links", VLDB'06