



SCHOOL OF COMPUTATION, INFORMATION
AND TECHNOLOGY — INFORMATICS

TECHNISCHE UNIVERSITÄT MÜNCHEN

Master's Thesis in Informatics

An Overlay for Social Networks based on Directed Acyclic Graphs on the Edge

Dan Bachar





SCHOOL OF COMPUTATION, INFORMATION
AND TECHNOLOGY — INFORMATICS

TECHNISCHE UNIVERSITÄT MÜNCHEN

Master's Thesis in Informatics

An Overlay for Social Networks based on Directed Acyclic Graphs on the Edge

**Ein Overlay für soziale Netzwerke auf der
Grundlage gerichteter azyklischer Graphen auf
der Kante**

Author:	Dan Bachar
Examiner:	Prof. Dr.-Ing. Jörg Ott
Supervisor:	Prof. Dr. Idit Keidar
Advisor:	Dr. David Guzman
Submission Date:	15.8.2026



I confirm that this master's thesis in informatics is my own work and I have documented all sources and material used.

Munich, 15.8.2026

Dan Bachar

Acknowledgments

Abstract

Recent crises, natural disasters, and large-scale protests have highlighted the significant reliance of people on online social networks and instant messaging platforms for communication. During crises, consolidated communication systems can become strained, partially or wholly destroyed, censored, or otherwise monitored. Permissionless distributed overlays are alternatives to consolidated communication realizations. System designers consider these overlays to be more resilient, since they distribute power and content control among many equal peers. These overlays introduce a massive performance overhead, as they rely on gossip and constant chatter between peers to disseminate the correct system state by reaching consensus, through many rounds of communication. This performance overhead poses a risk to usability of such systems in disaster zones, as peer devices often have limited connectivity and power supply, which together with the gossip protocol, can severely limit the peers' ability to communicate. In this paper, we propose a system architecture for unstructured peer-to-peer networks that achieves grassroots constitutional consensus based on efficient geometrical overlay design that trade achieve a higher throughput by using more edge computing. We use this system architecture to evaluate a decentralized social network deployed on smartphones using BLE connectivity, where users have total control of their data and privacy.

Kurzfassung

Recent crises, natural disasters, and large-scale protests have highlighted the significant reliance of people on online social networks and instant messaging platforms for communication. During crises, consolidated communication systems can become strained, partially or wholly destroyed, censored, or otherwise monitored. Permissionless distributed overlays are alternatives to consolidated communication realizations. System designers consider these overlays to be more resilient, since they distribute power and content control among many equal peers. These overlays introduce a massive performance overhead, as they rely on gossip and constant chatter between peers to disseminate the correct system state by reaching consensus, through many rounds of communication. This performance overhead poses a risk to usability of such systems in disaster zones, as peer devices often have limited connectivity and power supply, which together with the gossip protocol, can severely limit the peers' ability to communicate. In this paper, we propose a system architecture for unstructured peer-to-peer networks that achieves grassroots constitutional consensus based on efficient geometrical overlay design that trade achieve a higher throughput by using more edge computing. We use this system architecture to evaluate a decentralized social network deployed on smartphones using BLE connectivity, where users have total control of their data and privacy.

Contents

Acknowledgments	iii
Abstract	iv
Kurzfassung	v
1. Introduction	1
2. State-of-the-Art	4
2.1. Peer-to-peer Communication Technologies	4
2.2. Opportunistic Networking Systems	6
2.3. Routing in Opportunistic Networks	6
2.4. Decentralized Social Networks	6
2.5. Grassroots Social Networks	6
3. Problem Analysis	7
3.1. Assumptions	7
3.2. Design Goals	7
4. Architecture	8
4.1. System Architecture	8
5. Testbed	10
6. Evaluation	11
7. Discussion	12
8. Conclusion	13
A. General Addenda	14
A.1. Detailed Addition	14
B. Figures	15
B.1. Example 1	15
B.2. Example 2	15
List of Figures	16

List of Tables

17

1. Introduction

The decentralized administration of the Internet is one of the basic enablers of the rapid growth of the Internet as a whole, thanks to the autonomous nature of different network systems [**why-internet-works**]. Different Internet Service Providers (ISPs) play a critical role in the functionality of the Internet, as they connect their end customers (Internet users) to the Internet backhaul. The power dynamic of this system inherently gives control over shaping consumption patterns to the ISPs: consolidation of power at the hands of a few gives the ISPs the unique ability to control, throttle, or monitor the flow of information, in addition to enabling oppressive practices such as censorship and surveillance of end users. Governmental control of the telecommunication infrastructure often leads to the repression of communities during times of political unrest [**digital-repression-palestine, internet-shutdown-human-rights**], severely limiting the possibility for social actors to dissent and organize themselves. In addition to policial repression engaged by the government, physical distruptions can also limit free speech. Most recently, communication disruptions due to airstrikes on main fiber optic lines, and the depletion of fuel for generators, have severely limited the information flow to the population of Gaza since the start of the Israel-Hamas war in October 2023, halting humanitarian coordination, and leaving the affected population entirely cut off from life-saving information and assistance [**gaza-brief, gaza-report**].

Together, the aforementioned practices have led to a growing interest in peer-to-peer (p2p) messaging platforms, decentralized social networks [**bluesky, mastodon**], and distributed ledger-based applications [**bitcoin, ethereum**]. To guarantee free speech in disaster zones, during protests, and for citizens living under oppressive regimes, we decide to focus on unstructured p2p networks, as they inherently exhibit a higher level of resilience to topology changes and churn, in comparison to structured p2p networks. Structured p2p networks usually require an expensive randomized approach to establish resilient topologies, as they need to spread information across random peers to prevent dependence on any single peer [**guzman22, guzman25, kademlia**]. Additionally, iterative diffusion of the information causes data plane overhead [**guzman25**], which increases the message propagation latency [**guzman22, guzman23**]. Popular blockchains, which use a structured p2p overlay, employ concentration of services in a few highly available nodes, poses a threat to resilience despite a high reliability of those nodes, as a single network partition can prevent the entire network from communicating [**guzman24**]. Unstructured p2p networks, on the other hand, are more suitable for highly-dynamic alternative communication methods, often necessary to guarantee free decentralized communication means, as they usually do not distribute central information amongst the participating nodes. Most notably, the rise of unstructured p2p messaging platforms like Firechat [**firechat**], Briar [**briar**], bitchat [**bitchat**], and Amigo [**amigo**], have proven that there is a growing shift in user interest patterns away from traditional

Centralized Social Networks towards diverse p2p social networks.

After exploring the different types of p2p overlay networks, we discuss the choice of the communication protocol, which dictates the limited physical device communication radius. We chose to focus on a stable protocol that most modern devices support and the populace is most likely to use in disaster zones: Bluetooth, and more specifically Bluetooth Low Energy (BLE) [bt-spec]. We decided to focus on Bluetooth Low Energy (BLE) as it is more power efficient, over classic Basic Rate/Enhanced Data Rate (BR/EDR), as BLE conserves device battery life, it allows users to communicate over short ranges over a longer period of time than comparable communication protocols e.g. WiFi Direct [wifi-ble-power],

Next, we discuss the bottleneck of unstructured p2p networks: the communication algorithm. Most unstructured p2p networks rely on gossip protocols to disseminate information across the network, which reduces its performance and poses a threat to resilience (cite guided research paper?). Gossip protocols usually require constant chatter between peers to reach consensus about the system state, which introduces a massive performance overhead. This performance overhead poses a risk to usability of such systems in disaster zones, as peer devices often have limited connectivity and power supply, which together with the gossip protocol, can severely limit the peers' ability to communicate. The introduction of permissioned peers, such as high-availability bootstrapping nodes or signaling servers, improves the network's overall ability to communicate, bootstrap new communication links as well as maintain existing ones. However, those nodes pose an inherent tradeoff between performance and resilience to failure or surveillance, as relying on such nodes in disaster zones poses a risk with the infrastructure being oftentimes affected by network partitions, political censorship, or physical disruptions which halts the entire network from communicating. While such bootstrapping nodes ease the process of joining the network, discovering peers, and (potentially) disseminating and ordering state, they weaken the peers' ability to function without their presence, which is, as we show in this paper, oftentimes unnecessary. Instead of using permissioned nodes to facilitate communication by achieving total order of transactions, we suggest that using a partial ordering of transactions using a distributed Directed Acyclic Graph Conflict Free Replicated Data Types (DAG-CRDT), in which each node contains blocks of data, as well as edges which reference previous blocks, lends itself well to storing persistent communication data needed for social networking. This knowledge base, also known as the block frontier, provides proof to the local state of the node which created it, and iteratively ordering it on each participants' local device using a total order, achieves an eventual total order without extra communication between the peers [keidar23].

In this research paper, we deal mainly with the following three axes of distributed systems: security, decentralization, and resilience. In the first axis, security, we discuss the security of an open distributed system, its permission model, anonymity, confidentiality, and encryption. Following the security axis, we explore decentralization as a way to circumvent centralized control and avoid single points of failure. Several design decisions in our system architecture influence the system's decentralization: a pure p2p system completely resides on the peer devices; while this approach highlights communication which is independent from any existing networking architecture, it introduces limitations on the range of communication, as

it only allows for communication based on proximity due to the physical device constraints. Finally, we discuss resilience, which in our context refers to network survivability under duress. These communication issues include Byzantine behavior, which is independent of the communication. These issues include reachability, bandwidth limitations, and coverage loss.

This paper proposes a system architecture for resilient unstructured p2p networks, based on a wireless dual communication stack that leverages both a short-range city-scale relation as well as as Internet-scale relation, when available, to facilitate effective communication. For this, in section 2, we present the p2p communication protocols we used: BLE and UDX 2.1, as well as related works which lay at the foundation of this research paper: Peer-to-Peer Opportunistic Networking 2.2, Routing in Opportunistic Networking 2.3, Decentralized Social Networks (DSNs) 2.4, and finally, Grassroots Social Networks, and what sets them apart from DSNs 2.5. Finally, the State-of-the-Art chapter positions this research work contrastingly. To formalize the setting, goals, and environment for this research paper, section 3 will introduce our basic environment assumptions, an analysis of the concrete problem at hand, and the design goals of the system. Elaborating on the approach introduced in chapter 3, section 4 introduces the system architecture designed to support a permissionless, unstructured p2p social network, emphasizing the base algorithms, system components, and different communication layers. The 5 section introduces the testbed we used to evaluate the performance of the system architecture introduced in 4. Next, chapter 6 evaluates the results of the experiment conducted on the testbed, which proves the possibility of our design. Chapter 7 discusses the implications of the results introduced in the previous chapter, and finally, chapter 8 concludes the paper.

2. State-of-the-Art

The State-of-the-Art section presents the papers that lay at the foundation at this research work, and positions it adverserally. The sections in this chapter range will provide an overview over the communication mediums that we considered for this work: Bluetooth Classic, Bluetooth Low Energy, Bluetooth Mesh, Wi-Fi ad-hoc and Direct, and others. Next, this section continues with elaborating the networking assumptions that make this work possible, primarily discussing the difference between traditional packet-switching and the Store-Carry-Forward paradigm, that enables Delay-Tolerant Networking, while also presenting similar systems that have been developed using this paradigm. Followingly, we present main approaches that enable packet propagation in Delay Tolerant Networks (DTNs), explain each one of them, and show which one we used. Then, we present leading Decentralized Social Networks, and discuss whether they could have been used in our scenarios, showing that they actually cannot, and finally present the pinnacle: Grassroots Social Networks. Grassroots Social Networks lay at the core of this research work, and the networking layer presented here is a core work that lays at its foundation.

2.1. Peer-to-peer Communication Technologies

To create the peer-to-peer communication platform, different technologies were evaluated based on the following criteria:

- Spread of the protocol: As a user-facing tool, the communication medium had to be present in virtually all smartphones used today; thus, technologies that are supported by a handful of flagship smartphones, while being an interesting point for future work, are out of the question for this work.
- Low power: the communication protocol should not use a high amount of power to propagate packets
- Target: the communication protocol should be able to carry text messages efficiently, so a text message should be received within a short time in close range (e.g. 200KB in 1 second).
- Mobility: protocols need to support a high node mobility stemming from the mobility patterns of the users
- Infrastructure: there can be no external infrastructure necessary for the normal operation of the technology

Mobile Ad-Hoc Networks (MANETs) are infrastructure-less networks established using an array of battery-powered mobile devices that use the ad-hoc mode of their wireless network adapter to establish a spontaneous end-to-end connected, packet-switched network [Liu2026, Kindt2018]. In these networks, nodes act both as routers and hosts for data packets. MANETs, as well as Vehicle Ad-Hoc Networks (VANETs) and Smartphone Ad-Hoc Networks (SPANs), have been extensively studied, with research going back to DARPA's usage of radio to transmit data packets [Stotts2008]. These elements were bulky, expensive, provided poor data rates, and handled node mobility poorly. Since their onset, MANETs have advanced to VANETs, which deal with rapid topology changes arising due to a network established between fast-moving vehicles such as drone nets [Liu2026], and SPANs, which focus on establishing networks around humans utilizing a commonly available resource, the smartphone. SPANs utilize commonly available infrastructure in normal commercial-grade smartphones to connect users without external infrastructure, by leveraging technologies like Wi-Fi Aware, Wi-Fi Direct ??, Bluetooth Classic, and Bluetooth Low Energy ??, to facilitate critical communication during natural disasters, wars, protests, or Internet outages. Because they rely on no external infrastructure, SPANs are oftentimes proposed as the foundation to serverless grassroots social networks such as Bitchat ??, and indeed the idea behind SPANs and is tangential to the core of this research work: MANETs today offer a generally higher data rate than DTNs, but their requirement of a continuously-connected end-to-end path between source and destination make it impossible here, as oftentimes users suffer from offline periods due to emergencies. To route packets, MANETs usually relay on protocols that use topological knowledge of the nodes to efficiently route between them, being reactive to changes or working proactively to evaluate link states, and use out-of-band information like geological location [CMB-MANET]. An alternative to MANETs, DTNs have been proposed in communication-challenged regions where end-to-end path connectivity is lacking: research on DTNs was propelled by NASA for interplanetary travel; the Curiosity rover on Mars, a resource-constrained robot that has been travelling the surface of the red planet since 2012, has been using a DTN to convey pictures to Earth through a satellite orbiting the planet. Instead of wasting precious power on beaming a transmission directly to Earth, the Curiosity rover stores the transmission until the satellite is optimally located orthogonally over it, before sending the satellite its data packets. The satellite then carries the packets until it is at an optimal orbit to Earth. The final transmission between the satellite and Earth completes the communication cycle, enabling the rover to continue to explore Mars for ten years after the end of its intended two-year mission. The concept that thus lies at the core of DTNs is the Store-Carry-Forward paradigm, which stands in stark contrast to the immediacy requirements of normal packet routing: in standard packet routing, all nodes participating in a transmission between source and destination need to be connected and online concurrently; in DTN routing, the networking graph can be partially offline for extensive periods of time while nodes carry the transmissions. Similarly to MANETs, DTNs also suffer from communication overheads that arise due to control messages, and are especially exacerbated by dense environments with many participants. In addition to space travel, DTNs have also enabled nomadic populace in northern Scandinavia the access to communication: the Sami people.

MANET, Wifi Adhoc, Wifi Direct, Wifi Aware, Bluetooth BDR, Bluetooth Low Energy, Power usage of BLE vs. Direct, NAT, Hole-punching

2.2. Opportunistic Networking Systems

(MANET BATMAN) vs. Twimight, Emergency Broadcast, COVID contact tracing, Wifi-Opp

2.3. Routing in Opportunistic Networks

Flooding, Spray-and-Pray, PRoPHET

2.4. Decentralized Social Networks

Bluesky, Mastodon, Briar, Nostr, SBB, Bitchat

2.5. Grassroots Social Networks

Shapiro

3. Problem Analysis

3.1. Assumptions

- Disaster struck zone: Partially down communications, BLE first, mesh
- Politically oppressive regimes: various trust levels, edge rendezvous points, p2p
- Online monitoring: encryption through Noise handshake for key exchange
- More?

3.2. Design Goals


- Prefer local over remote communication
- When available, use the Internet-scale relation to relay messages over long distances
- Reduce attack interface for surveillance and monitoring as much as possible: expose the minimum amount of required information to facilitate communication
- Store-carry-forward: cache packets for unavailable recipients until a possible delivery attempt can be made
- Do not ignore existing mobile infrastructure to facilitate Internet-scale communication: edge rendezvous points and hole-punching
- Because the application may be used in various circumstances, let the user decide on various security-critical settings (i.e. use cloud RV point, friends, introduction facilitation)

4. Architecture

A demo chat app deployed on phones, which serves as the foundation to the blocklace-based future grassroots social network: argue why exactly these functions are needed.

4.1. System Architecture

The stack is organised into four layers. The lower two (transport + protocol) constitute the reusable library ('lib/src/'); the coordinator sits above them as the public façade; the topmost layer is the consuming application (in this repo, a demonstrator chat app under 'lib/*.dart').



- Ed25519 identity
- Two transport protocols, one interface
- Message types: announce, message, friendship
- Friend vs. Stranger
- Trust Levels: cold calls
- Facilitation opt-in: edge RV points
- Always-on cloud RV points: optionally use RVs to facilitate connections
- Signaling over BT or mutual friends: hole-punching

- Simple messaging: text and media
- Blocks: ACK, NACK

5. Testbed

To evaluate the system architecture, we deployed it as a mobile application on a limited testbed of Android and iOS devices. During the deployment, usage statistics were recorded and uploaded to a secure TUM server on an opt-in basis.

6. Evaluation

7. Discussion

8. Conclusion

A. General Addenda

If there are several additions you want to add, but they do not fit into the thesis itself, they belong here.

A.1. Detailed Addition

Even sections are possible, but usually only used for several elements in, e.g. tables, images, etc.

B. Figures

B.1. Example 1

✓

B.2. Example 2

✗

List of Figures

List of Tables

bibliography.bib