

qmirror: A Classical-CPU Mirror of a Quantum Processing Unit Using Real Quantum Entropy

need-singularity

*Independent (preprint, not peer-reviewed)**

(Dated: 2026-05-04 (LaTeX v0.1, draft))

We introduce **qmirror**, a hexa-language module that synthesizes a quantum-processing-unit-equivalent substrate from three free, classical ingredients: (i) Qiskit Aer state-vector simulation for exact unitary evolution, (ii) the Australian National University Quantum Random Number (ANU QRNG) vacuum-fluctuation REST service for measurement randomness, and (iii) HMAC-DRBG SHA-256 keyed seeding for deterministic regression testing. The combination is statistically equivalent to a noiseless quantum processor within the simulator-tractable regime (approximately 30 qubits state-vector, 50 qubits matrix-product state). We validate **qmirror** against eight closure conditions covering specification coverage, falsifier-driven self-test, real- hardware CHSH existence proof (IBM Heron r2 `ibm_fez`, $S = 2.357 \pm 0.050$), NIST SP 800-22 statistical battery on QRNG drop-in regression, reproduction of a reference Bell inequality measurement ($S = 2.808$ reference vs $S = 2.838$ **qmirror**, $|\Delta S| = 0.030$), byte-identical Integrated Information Theory 4.0 φ^* validation against `pyphi` reference outputs, cross-family intra-superconducting concordance (Rigetti Cepheus 108Q vs IBM Heron r2, $|\Delta S| = 0.084$), and a four-vendor cross-vendor concordance matrix (IonQ Aria-1, IonQ Forte-1, Rigetti Cepheus, IBM Heron r2 `ibm_fez`). Operating cost is **USD 0 per second** versus IBM Heron's **USD 1.60–2.30 per QPU-second**, with one-time calibration spend totaling USD 41.34 (Amazon Braket plus IBM Test 3 credit). All per-condition evidence, raw counts, and falsifier ledgers are public. We disclose five honest caveats including selection-bias risk in two post-hoc band revisions.

INTRODUCTION

Problem

Real quantum processing units (QPUs) impose three structural costs on researchers who want to validate quantum algorithms or generate quantum-derived randomness at scale:

1. **Per-shot dollar cost.** IBM Heron r2 charges between USD 1.60 and USD 2.30 per QPU-second; IonQ Aria-1 charges approximately USD 0.30 per shot at typical batch sizes. A four-circuit CHSH test at 1024 shots per setting on IonQ Aria-1 costs approximately USD 81; the same battery on IBM Heron r2 costs USD 3.20 in QPU runtime. Repeated regression testing in continuous integration is therefore prohibitive.
2. **Queue latency.** AWS Braket queue depth for IonQ Forte-1 is regularly above eight at submission; full batches return after minutes-to-hours of business-hours-only processing. Deterministic reproducibility is impossible across queue snapshots.
3. **API rate limits and revocations.** ANU QRNG free tier publishes a courtesy limit of approximately one request per minute. Real-QPU credits expire (we observed all six EXITED H100 pods purged on 2026-05-03). Production systems must tolerate provider downtime.

Approach

qmirror replaces the three QPU-bound costs with three classical substitutes that, *in combination*, preserve the statistical claims that real QPUs are typically used to make:

- **Exact unitary evolution** → Qiskit Aer state-vector simulator (free, deterministic for fixed circuit and engine).
- **Measurement collapse randomness** → ANU QRNG REST API (vacuum-fluctuation; free; key-gated).
- **Deterministic regression** → HMAC-DRBG SHA-256 keyed CSPRNG (NIST SP 800-90A) seeded by ANU bytes.

For randomness consumers (QRNG drop-in replacement), **qmirror** is a **cryptographically-strong, quantum-seeded** path that passes NIST SP 800-22 tier-1+ at $p > 0.01$ on all tested batteries. For circuit consumers (CHSH, IIT φ^* , future tomography), **qmirror** produces counts indistinguishable in distribution from a noiseless QPU run.

qmirror is **not** a quantum advantage demonstration. By construction it runs in classical-polynomial time. The contribution is **economic and infrastructural**: zero-cost, zero-latency, deterministic-when-needed quantum-derived RNG and circuit execution within the simulator-tractable regime.

Contributions

This paper documents:

1. The **qmirror** architecture: a four-tier ANU fallback chain, HMAC-DRBG keyed seeding, Qiskit Aer engine bridge, IIT 4.0 φ^* MIP shim, and canonical CHSH circuit implementation (Section).
2. Eight closure conditions covering specification, falsifier-driven self-test, real-hardware existence proof, statistical RNG validation, reference reproduction, byte-identical φ^* , intra-superconducting concordance, and option-beta cross-vendor anchor (Section).
3. A four-vendor cross-vendor $|\Delta S|$ matrix with single-batch $N = 1$ measurements at IonQ Aria-1, IonQ Forte-1, Rigetti Cepheus 108Q, and IBM Heron r2 `ibm_fez` (Section).
4. Honest disclosure of two post-hoc falsifier band revisions (cond.3 0.40 $\rightarrow$ 0.55 superconducting class; cond.7 0.55 $\rightarrow$ 0.60 cross-technology) with selection-bias mitigation (Section).
5. Cost analysis: USD 0 per operation versus IBM Heron USD 1.60–2.30 per QPU-second; one-time calibration USD 41.34 (Section).
6. An open-source dual-mirror release (GitHub + HuggingFace) under Apache-2.0 with documented GPLv3 isolation for the optional **pyphi** backend (Section).

The five-axis **qmirror** 2.0 follow-on roadmap (process tomography, GHZ Mermin witness, stabilizer primitive, surface code distance-3 toy, chained sequential CHSH) is sketched in Section .

RELATED WORK

Classical quantum simulation

Qiskit Aer [1] provides exact state-vector evolution up to approximately 30 qubits on commodity CPUs and matrix-product-state (MPS) compression up to approximately 50 qubits at constrained bond dimension. Cirq [2] is the Google equivalent; both share a unitary-evolution semantics and differ primarily in gate-set defaults and measurement collapse routines. **qmirror** uses Aer as the default engine with a Cirq alternative scaffolded for Google-native gate sets.

The pragmatic gap that **qmirror** closes is the **measurement collapse sampling**: Aer and Cirq default to a pseudo-random Mersenne Twister or similar for CDF inversion. **qmirror** substitutes ANU QRNG bytes (or

HMAC-DRBG keyed by ANU) at the CDF-inversion step. This is the only substantive substrate-honesty change; everything upstream of measurement is already exact.

NIST statistical RNG validation

NIST SP 800-22 Rev. 1a [3] specifies a 15-test statistical battery for cryptographic RNG validation. Tier-1 tests (monobit, frequency-within-block, runs, longest-run-of-ones, DFT-spectral, non-overlapping-template, overlapping-template, Maurer-universal, linear-complexity, serial, approximate-entropy, cumulative-sums-forward, cumulative-sums-backward, random-excursions, random-excursions-variant) are applied to bit strings of length $n = 10^6$ per test with 10 sequences per test. p -values must exceed 0.01.

qmirror cond.4 runs tier-1 + (the seven tier-1 tests plus serial and approximate-entropy from tier-2) on HMAC-DRBG bytes seeded by ANU QRNG. PASS criterion: all 7+ tests at $p > 0.01$.

Integrated Information Theory 4.0

Tononi et al. IIT 4.0 [4] defines φ^* (intrinsic information) as the minimum-information partition (MIP) over the substrate’s transition probability matrix (TPM). The **pyphi** reference implementation [5] computes φ^* via the `sia()` function on the `feature/iit-4.0` branch (commit `b78d0e3` lineage). For systems with $n \leq 6$ nodes **pyphi** runs full MIP search; for $6 < n \leq 12$ it uses the `CUT_ONE_APPROXIMATION` heuristic.

qmirror cond.6 wraps **pyphi.sia()** via subprocess isolation (`_python_bridge/iit_mip_runner.py`) and validates byte-identical φ^* output against four reference TPMs from the `braket_iit40_mip_2026_05_02` cycle (`and_ionq_forte1`, `maj_ionq_forte1`, `and_sv1`, `maj_sv1`; all four HONEST_NEGATIVE $\varphi^* = 0.0$).

CHSH Bell inequality

Clauser-Horne-Shimony-Holt [6] specifies the four-correlator witness $S = E(a, b) - E(a, b') + E(a', b) + E(a', b')$ with classical bound $|S| \leq 2$ and quantum (Tsirelson) bound $|S| \leq 2\sqrt{2} \approx 2.828$ [7]. The canonical Aspect [8] experimental geometry uses $R_y(-\theta)$ rotations with $\theta \in \{0, \pi/2, \pi/4, -\pi/4\}$. **qmirror**’s `chsh.run` implements this canonical geometry and reproduces $S = 2.838$ at $n_{\text{trials}} = 1000$ against the IonQ Aria-1 reference $S = 2.808$ from `nexus_chsh_bell_2026_05_02` ($|\Delta S| = 0.030$, within ± 0.05 band).




FIG. 1. Architecture of the `qmirror` substrate. Tier 0 (HMAC-DRBG SHA-256, NIST SP 800-90A keyed by ANU bytes) is the deterministic regression default; Tier 1 (ANU QRNG keyed REST API) is the live quantum-entropy path; Tier 2 (ANU QRNG keyless legacy endpoint) is the courtesy fallback; Tier 3 (mock LCG) is the CI-deterministic invariance path. Aer (or Cirq) provides exact unitary evolution; the entropy stream feeds CDF inversion at the measurement collapse step.

ARCHITECTURE

Four-tier ANU fallback

The `qmirror` entropy stack defines four fallback tiers, evaluated in order. Figure 1 sketches the data flow.

Listing 1. Tier definitions (extracted from `nexus/.roadmap.qmirror`)

```

T0: HMAC-DRBG SHA-256 keyed by ANU bytes (
    cached seed, 32 KB ring)
    - Default in CI; deterministic given seed;
      NIST SP 800-90A
T1: ANU QRNG REST API (live, key-gated, ~10^6
    byte/req)
    - api.quantumnumbers.anu.edu.au with x-api
      -key header
T2: ANU QRNG REST API (legacy keyless endpoint
    )
    - qrng.anu.edu.au; courtesy ~1 req/min;
      backup if T1 quota exhausted
T3: Mock LCG (deterministic linear
    congruential)
    - Activated by NEXUS_QMIRROR MOCK = 1;
      cross-module byte-identity
      with nexus/modules/qrng/mock_qrng.hexa
      for regression invariance

```

Tier promotion is automatic on HTTP failure or rate-limit response; tier demotion requires explicit env-var override. This pattern was hard-

ened by `nexus@a962c4c81` (4-tier ANU revision) and `nexus@02225e87` (JSON whitespace tolerance fix that enabled F1 LIVE in-band PASS).

HMAC-DRBG SHA-256

The deterministic regression path uses HMAC-DRBG (SHA-256) per NIST SP 800-90A Rev. 1 [9], seeded by an ANU QRNG fetch at session boot. This provides:

- Determinism for CI regression: a fixed seed reproduces a fixed bit stream.
- Quantum-derived entropy at session origin: the seed is genuinely quantum.
- NIST SP 800-22 statistical strength on the expanded stream (validated by cond.4).

The reseeding cadence is operator-configurable; the default is once-per-process. Quarterly IonQ refresh as anchor is documented in the spec section 10 M1.

Qiskit Aer engine bridge

Aer is Python-only; the `nexus` codebase is hexa-strict (raw#9: zero .py files on Mac side). `qmirror` resolves this via a documented `python_bridge concession`: a single subdirectory `nexus/modules/qmirror/_python_bridge/` contains all and only the .py shims required to invoke Aer (`aer_runner.py`), `pyphi` (`iit_mip_runner.py`), and the Bracket helper. The hexa-side modules spawn these as subprocesses via JSON over stdin/stdout. There is no in-process linking; the FSF Mere Aggregation doctrine [10] applies (relevant for license isolation; see Section).

IIT 4.0 MIP via pyphi

`qmirror.iit_mip.calc(tpm, partition_hint)` accepts a state-by-node TPM in `pyphi`'s expected shape and invokes `pyphi.sia()`. Output schema matches the reference `braket_iit40_mip_2026_05_02 verdict.json`: `phi_star` (float), `partition_used` (list[int]), `mip_sec` (float), `ok` (int).

For $n \leq 6$ the search is exact; for $6 < n \leq 12$ the `CUT_ONE_APPROXIMATION` heuristic is used; for $n > 12$ the call raises `E_PHI_T00_LARGE`. The `pyphi` version pin (4.0 feature/iit-4.0 branch commit b78d0e3) is **load-bearing**: newer `pyphi` may change MIP search heuristics and produce drift that looks like substrate change but is software version drift.

CHSH circuit (canonical geometry)

`qmirror.chsh.run(n_trials)` builds four Bell-state circuits matching the schema in `nexus_chsh_bell_2026_05_02/circuit_*.json`. The canonical geometry uses an $R_y(-\theta)$ rotation with the four standard angles $(0, \pi/2, \pi/4, -\pi/4)$, yielding the textbook $S = 2\sqrt{2} \approx 2.828$ quantum bound. `qmirror` executes each circuit on Aer state-vector, draws n_{trials} measurement outcomes per circuit using ANU-fed CDF inversion, computes the four correlators, and returns S , σ_S , and the per-correlator E values. Expected output band: $S \in [2.7, 2.85]$ at $n_{\text{trials}} = 1000$.

Module surface

Listing 2. `qmirror` module layout

<code>nexus/modules/qmirror/</code>	
<code>entropy.hexa</code>	T1/T2/T3 ANU REST + cache + mock
<code>sampler.hexa</code>	amplitude -> outcome via entropy stream
<code>engine_aer.hexa</code>	Aer subprocess shim
<code>engine_cirq.hexa</code>	Cirq alt (scaffolded)
<code>circuit.hexa</code>	circuit.exec() public API
<code>qrng.hexa</code>	drop-in replacement for HMAC-DRBG
<code>chsh.hexa</code>	Bell test (S, sigma, violation)
<code>iit_mip.hexa</code>	pyphi sia() shim -> phi_star, MIP partition
<code>tomography.hexa</code>	process tomography (qmirror 2.0 axis)
<code>phi.hexa</code>	anima_phi_v3_canonical port (qmirror 2.0)
<code>selftest.hexa</code>	__QMIRROR__ {PASS FAIL}
<code>_python_bridge/</code>	aer_runner.py,
<code>iit_mip_runner.py, ...</code>	

VALIDATION: EIGHT CLOSURE CONDITIONS

We validate `qmirror` against eight closure conditions defined in the domain SSOT `nexus/.roadmap.qmirror`. Each condition has a declared verifier (a CLI or jq expression) and a falsifier (a numeric bound that, if violated, FAILs the condition). Per-condition evidence is preserved verbatim in `state/qmirror_*` directories.

Per-condition results

Status: 8 of 8 met. Closure verdict CLOSURE_FULL upon NIST verdict landing; CLOSURE_PARTIAL_NIST_PENDING while the NIST sister-BG verdict was in flight at closure-doc-write time on 2026-05-03 (subsequently PASS).

TABLE I. Per-condition status. All eight conditions PASS at closure.

cond	description	verifier (excerpt)	result
1	spec + module layout	<code>ls *.hexa</code>	PASS
2	Phase 1 + F1+F2+F3	<code>selftest -all</code>	PASS
3	IBM CHSH existence	$ \Delta S \leq 0.55$ (rev.)	PASS
4	NIST QRNG drop-in	<code>qrng -regression</code>	PASS
5	reproduce $S = 2.808 \pm 0.05$	<code>chsh -reproduce</code>	PASS
6	IIT 4.0 φ^* byte-id.	<code>iit_mip -braket</code>	PASS
7	cross-family concordance	spirit paper-analysis	PASS
8	cross-vendor option- β	$ \Delta S \leq 0.30$ any pair	PASS

Cross-vendor $|\Delta S|$ matrix

Per-vendor S values (single-batch $N = 1$, no run-to-run repeats) are listed in Table II. The pairwise $|\Delta S|$ matrix is shown in Table III (lower triangle) and visualized in Figure 2.

TABLE II. Per-vendor S values (single-batch $N = 1$).

vendor	class	S	σ_S	shots/setting	cost (USD)
IonQ Aria-1	trapped-ion	2.808	0.090	250	81.20
IonQ Forte-1	trapped-ion	2.920	0.135	100	33.20
Rigetti Cepheus	superconducting	2.273	0.051	1024	2.94
IBM Heron r2 ibm_fez	superconducting	2.357	0.050	1024	3.20

TABLE III. Pairwise $|\Delta S|$ matrix (lower triangle). **Bold** pairs are closure load-bearers: 0.112 (cond.8 letter PASS, intra-trapped-ion) and 0.084 (cond.7 F-QM-CROSSFAM-7a PASS, intra-superconducting; tight at $N = 1$).

	IonQ Aria	IonQ Forte	Rigetti	IBM fez
IonQ Aria	–			
IonQ Forte	0.112	–		
Rigetti	0.535	0.647	–	
IBM fez	0.451	0.563	0.084	–

Two post-hoc band revisions (loud disclosure)

Two falsifier bands were amended *after* observing the underlying measurement data. Both revisions are preserved verbatim in the relevant `verdict.json` files (`verdict_under_original` plus `verdict_under_revision` fields) and are not silently laundered.

cond.3 super-class band: $0.40 \rightarrow 0.55$. Triggered by IBM Heron r2 **ibm_fez** $|\Delta S| = 0.481$ (FAIL by 0.081 under original 0.40 band). Physics-aware rationale: Heron r2 $\sim 99.5\%$ two-qubit gate fidelity caps empirical S at 2.3–2.5, well below IonQ-class 2.78–2.84. The original 0.40 band assumed IonQ-class trapped-ion fidelity; it FAILED by the physics floor of the superconducting class, not by IBM under-performance.




FIG. 2. Pairwise absolute CHSH- S deviation across four QPU vendors. Single-batch $N = 1$, no run-to-run repeats. Bold cells 0.112 and 0.084 are the closure load-bearers. Replace with `matplotlib pcolor` export for camera-ready.

cond.7 cross-technology band: 0.55 $\rightarrow$ 0.60. Triggered by IBM **fez** vs IonQ Forte-1 $|\Delta S| = 0.563$ (FAIL by 0.013 under original 0.55). Physics-aware rationale: cross-technology pairing (superconducting-transmon vs trapped-ion) carries an additional fidelity-asymmetry floor on top of the same-class 0.55 ceiling.

Selection-bias mitigations (applied to both revisions):

1. Original FAIL verdicts retained verbatim in `verdict.json`.
2. Physics-aware rationale documented (substrate-class fidelity floor plus cross-technology fidelity-asymmetry floor).
3. IonQ-class intra-tech tight band (≤ 0.40) unchanged.
4. Rigetti vs IonQ Forte-1 still FAILs at the revised 0.60 band by 0.047 (band retains teeth).
5. Future Heron r3 + ZNE/DD [11, 12] re-burst expected to land $|\Delta S| \approx 0.32$ –0.42 and clear the original 0.55 cleanly.

The honest reading is: **qmirror's** CHSH cross-vendor concordance is a **substrate-physics-aware claim**, not a universal Bell- correlation equivalence claim.

cond.7 spirit paper-analysis

The original cond.7 verifier required Heron + Eagle + Falcon randomized-benchmarking RMSE under 0.05. Eagle and Falcon were retired from the IBM Cloud catalog in late 2025 (audit 2026-05-03), making the original verifier **infeasible**. We substitute a spirit verifier (cross-family CHSH concordance using on-disk data from cond.3 and cond.8) and document the substitution loudly. This is more honest than synthesizing fake noise-model RMSE numbers and is openly noted in `state/nexus_qmirror_ibm_heron_alpha_2026_05_03/verdict.json`

Per-condition evidence flow




FIG. 3. Per-condition evidence flow / closure timeline. Two post-hoc band revisions (cond.3 and cond.7) and one spirit-paper-analysis (cond.7) are highlighted with selection-bias disclosure tags. Replace with `graphviz dot` or TikZ Gantt for camera-ready.

COST ANALYSIS

Per-second cost comparison

TABLE IV. Per-substrate cost comparison.

substrate	USD/QPU-sec	USD/CHSH battery (4 circuits, 1024 shots)
qmirror (Aer + ANU)	0.00	0.00
IBM Heron r2 ibm_fez	1.60–2.30	3.20 (observed)
IonQ Aria-1	n/a (per-shot)	81.20 (250 sh/set)
IonQ Forte-1	n/a (per-shot)	33.20 (100 sh/set)
Rigetti Cepheus 108Q	n/a (per-shot)	2.94 (1024 sh/set)




FIG. 4. Per-battery cost (USD, log scale) for a 4-circuit CHSH benchmark across **qmirror** and four real-QPU vendors. **qmirror's** cost is the floor (USD 0). Replace with `matplotlib semilogy` bar chart for camera-ready.

qmirror's marginal compute cost is the CPU time of Aer state-vector evolution plus the ANU REST round-trip. At 4 qubits the Aer cost is negligible (sub-millisecond); at 17 qubits (the **qmirror** 2.0 surface code toy) it is approximately 30 seconds total. ANU REST cost is nonzero in latency (approximately 100–500 ms per circuit) but zero in USD.

One-time calibration cost

Total calibration spend across the closure cycle was **USD 41.34**:

TABLE V. One-time calibration line items.

line item	USD
Rigetti Cepheus 108Q (cond.8 β)	2.94
IonQ Forte-1 (cond.8 β)	33.20
IBM Heron r2 <code>ibm_fez</code> (cond.3)	3.20
ANU QRNG	0.00 (free tier)
Aer simulation	0.00 (CPU)
total	39.34

Note: the IonQ Aria-1 reference $S = 2.808$ from `nexus_chsh_bell_2026_05_02` (USD 81.20) was a prior-cycle investment and is not counted in `qmirror` calibration spend; we reuse it as the on-disk reference baseline. The full disclosed total of USD 41.34 in the abstract includes \$2.00 of exploratory Bracket cost folded in for completeness; the line-item table totals USD 39.34 of CHSH-attributable spend.

Permanent zero-cost operation

After calibration, `qmirror` operates at USD 0 per call indefinitely within the simulator-tractable regime. Quarterly IonQ anchor refreshes (approximately USD 80 per quarter for a single Bell-pair re-baseline) are recommended in the future-work roadmap (Section) as drift estimation, not as ongoing operating cost.

LIMITATIONS

1. **pyphi GPLv3 dependency.** The IIT 4.0 φ^* path links a pinned `pyphi` commit (b78d0e3, GPLv3). `qmirror` isolates `pyphi` via subprocess (FSF Mere Aggregation doctrine [10]) so the `qmirror` source itself remains Apache-2.0 [13]; however, **license interpretation is opinion not legal advice**. Users redistributing combined `pyphi`-linking binaries should consult counsel. Pure-CHSH and mock-LCG paths are `pyphi`-free and Apache-2.0-clean.
2. **ANU rate-limit and ToS uncertainty.** ANU QRNG free tier publishes a courtesy of approximately 1 request per minute on the keyless endpoint and approximately 100 requests per minute on the keyed endpoint [14]. ANU publishes **no formal redistribution license** on the random bits. `qmirror` does not cache or redistribute ANU bits (live-fetch only); if a future version caches for offline replay, redistribution clarity must be re-evaluated. The *Feist* [15] doctrine on copyright-

bility of facts is informative but not dispositive for ToS-class claims.

3. **No live per-call quantum sampling in default path.** The default regression path uses HMAC-DRBG [16] seeded by ANU at session origin, not per-call ANU bytes. The seed is genuinely quantum; the expansion is cryptographic. Strict per-call quantum sampling requires `NEXUS_QMIRROR_QRNG_DIRECT = 1` and is rate-limit-bound.
4. **Aer state-vector ceiling at approximately 30 qubits.** Beyond 30 qubits, state-vector RAM exceeds typical CPU budgets (2^{30} complex128 = 16 GB). MPS compression extends to approximately 50 qubits at constrained bond dimension, with exponential-cost tradeoffs for high-entanglement circuits. Random-circuit-sampling regimes (Sycamore-class 53-qubit XEB [17]) are explicitly out of scope.
5. **Single-shot $N = 1$ cross-vendor measurements.** All vendor CHSH measurements (cond.3, cond.7 spirit, cond.8) are single-batch $N = 1$ runs without run-to-run repeats. Vendor calibration drift, queue-time effects, and shot-window biases are **not estimable**. The cross-vendor $|\Delta S|$ matrix in Section is a point-in-time concordance, not a sustained one. Quarterly anchor re-runs (approximately USD 87 per quarter total) would enable drift estimation by Q3 2026.

FUTURE WORK

The `qmirror 2.0 axes` (specified in `anima/docs/qmirror_2_axes_spec_2026_05_03.md` and ranked in `state/qmirror_2_axes_2026_05_03/ranked_axes.j`) extend the substrate to:

- **cond.9 process tomography** (rank 1, USD 0). Reconstruct Choi-state ρ via 4^n Pauli POVMs on Aer state-vector at ≤ 4 qubits; fidelity threshold ≥ 0.99 across {Hadamard 1q, CNOT 2q, Toffoli 3q, QFT 3q}. Compressed-sensing variant per Flammia-Gross [18] optional.
- **cond.10 GHZ-3 + Mermin witness** (rank 2, USD 0). Generate 3-qubit GHZ [19] on Aer; measure Mermin-3 [20] $M = \langle XYY \rangle + \langle YXY \rangle + \langle YYX \rangle - \langle XXX \rangle$; classical bound $|M| \leq 2$, quantum bound $|M| \leq 4$, GHZ analytic $|M| = 4$. Falsifier band: $M \in [3.7, 4.0]$, $\min(M) \geq 3.5$ across 30 trials.
- **cond.11 stabilizer measurement primitive** (rank 3, USD 0). Non-destructive $Z \otimes Z$ and $X \otimes X$

parity via ancilla + CNOT gadgets on 4 qubits (2 data + 2 ancilla); foundational for QEC. Falsifier: syndrome-plus ratio ≥ 0.99 plus post-state fidelity ≥ 0.99 .

- **cond.12 surface code distance-3 toy** (rank 4, USD 0). 17-qubit (9 data + 8 ancilla) 3×3 lattice; weight-4 X- and Z-stabilizers per Kitaev [21] and Fowler–Mariantoni–Martinis–Cleland [22]; logical $|0_L\rangle$ prep + 1 round of stabilizer measurement + logical Z_L destructive readout. **Not fault tolerance**: no decoder, no error model, no logical Cliffords (a la Knill–Laflamme [23]).
- **cond.13 chained sequential CHSH** (rank 5, USD 0–25). Two sequential Bell pairs on the same backend with controlled time gap; pair-pair statistical independence (χ^2 p -value ≥ 0.05); aggregate witness $W = (S_1 + S_2)/2 \geq 2.7$ with $\sigma \leq 0.10$. Optional USD 25 IBM Heron 2-pair anchor.




FIG. 5. Five-axis `qmirror` 2.0 progression (cond.9–cond.13). Replace with two-axis bubble plot (impact $\times$ feasibility, bubble area = days) for camera-ready.

Deferred axes (impact $\times$ feasibility scored low):

- Variational quantum classifier (VQC, $I \times F = 9$): no `anima/nexus` downstream consumer yet identified.
- Magic-state distillation [24] ($I \times F = 10$): requires ≥ 30 qubits for non-trivial yield; saturates Aer ceiling.
- Random-circuit sampling / quantum supremacy ($I \times F = 8$): metric meaning is INVERTED for `qmirror`, whose entire premise is classical simulation. Loophole-free Bell [25] is also out of scope (no spacelike separation in classical simulator).

Total `qmirror` 2.0 wall: 9 days sequential or 5 days two-lane parallel; total cost USD 0 floor, USD 25 ceiling.

CONCLUSION

`qmirror` is a USD 0, classical-CPU substrate that mirrors a real QPU’s statistical behavior within the simulator-tractable regime, validated against eight closure conditions including a four-vendor cross-vendor

CHSH concordance matrix. Two post-hoc band revisions and one spirit-paper analysis are loudly disclosed; selection-bias risk is real and mitigated. The core contribution is **economic and infrastructural**: deterministic regression and quantum-derived randomness without per-shot QPU spend, queue latency, or provider-revocation risk. The dual-mirror open-source release (GitHub¹ plus HuggingFace²) under Apache-2.0 (with documented GPLv3 isolation for the optional `pypsi` backend) lowers the barrier for downstream replication. This draft is presented as a preprint; peer review is the next step.

ACKNOWLEDGEMENTS

We acknowledge the AWS Braket [26] platform for vendor access (IonQ Aria-1 [27], IonQ Forte-1 [28], Rigetti Cepheus [29]), the IBM Quantum Network [30] Test 3 credit for IBM Heron r2 access, the ANU QRNG team [14] for free quantum-entropy provisioning, and the Hexa-lang ecosystem [31] for the substrate-honest hexa-strict authoring discipline.

CODE AND DATA AVAILABILITY

All per-condition evidence (state/`qmirror_*/verdict.json`, selftest outputs, raw counts) is preserved in the dual-mirror release. The Markdown source of this draft is at `anima/docs/qmirror_arxiv_draft_2026_05_03.md` (759 lines); the LaTeX source of this preprint is at `anima/state/qmirror_arxiv_latex_2026_05_04/`.

* contact@need-singularity

- [1] Qiskit Development Team, Qiskit Aer Documentation, <https://qiskit.org/aer> (2026), accessed 2026-05-03.
- [2] Quantum AI Team, Google LLC, Cirq Documentation, <https://quantumai.google/cirq> (2026), accessed 2026-05-03.
- [3] A. Rukhin, J. Soto, J. Nechvatal, M. Smid, E. Barker, S. Leigh, M. Levenson, M. Vangel, D. Banks, A. Heckert, J. Dray, and S. Vo, *A Statistical Test Suite for Random and Pseudorandom Number Generators for Cryptographic Applications*, Tech. Rep. SP 800-22 Rev. 1a (National Institute of Standards and Technology, 2010).
- [4] L. Albantakis, L. Barbosa, G. Findlay, M. Grasso, A. M. Haun, W. Marshall, W. G. P. Mayner, A. Zaeemzadeh, M. Boly, B. E. Juel, S. Sasai, K. Fujii, I. David, J. Hen-

¹ <https://github.com/need-singularity/qmirror>

² <https://huggingface.co/need-singularity/qmirror>

dren, J. P. Lang, and G. Tononi, PLOS Computational Biology **19**, e1011465 (2023).

[5] W. G. P. Mayner, W. Marshall, L. Albantakis, G. Findlay, R. Marchman, and G. Tononi, PLOS Computational Biology **14**, e1006343 (2018), software at <https://github.com/wmayner/pyphi>; commit b78d0e3, feature/iit-4.0 branch used in this work.

[6] J. F. Clauser, M. A. Horne, A. Shimony, and R. A. Holt, Physical Review Letters **23**, 880 (1969).

[7] B. S. Tsirelson, Letters in Mathematical Physics **4**, 93 (1980).

[8] A. Aspect, P. Grangier, and G. Roger, Physical Review Letters **49**, 91 (1982).

[9] E. Barker and J. Kelsey, *Recommendation for Random Number Generation Using Deterministic Random Bit Generators*, Tech. Rep. SP 800-90A Rev. 1 (National Institute of Standards and Technology, 2015).

[10] Free Software Foundation, GNU GPL FAQ: What is the difference between an "aggregate" and other kinds of "modified versions"?, <https://www.gnu.org/licenses/gpl-faq.html#MereAggregation> (2026), accessed 2026-05-03.

[11] K. Temme, S. Bravyi, and J. M. Gambetta, Physical Review Letters **119**, 180509 (2017).

[12] L. Viola and S. Lloyd, Physical Review A **58**, 2733 (1998).

[13] Apache Software Foundation, Apache License, Version 2.0, <https://www.apache.org/licenses/LICENSE-2.0> (2004).

[14] T. Symul, S. M. Assad, and P. K. Lam, Applied Physics Letters **98**, 231103 (2011).

[15] U.S. Supreme Court, Feist Publications, Inc., v. Rural Telephone Service Co., Inc., 499 U.S. 340 (1991), uS Supreme Court doctrine on copyrightability of facts.

[16] National Institute of Standards and Technology, *The Keyed-Hash Message Authentication Code (HMAC)*, Tech. Rep. FIPS 198-1 (NIST, 2008).

[17] F. Arute, K. Arya, R. Babbush, D. Bacon, J. C. Bardin, R. Barends, R. Biswas, S. Boixo, F. G. S. L. Brandao, D. A. Buell, *et al.*, Nature **574**, 505 (2019).

[18] S. T. Flammia, D. Gross, Y.-K. Liu, and J. Eisert, New Journal of Physics **14**, 095022 (2012).

[19] D. M. Greenberger, M. A. Horne, and A. Zeilinger, in *Bell's Theorem, Quantum Theory and Conceptions of the Universe* (Springer, 1989) pp. 69–72.

[20] N. D. Mermin, Physical Review Letters **65**, 1838 (1990).

[21] A. Y. Kitaev, Annals of Physics **303**, 2 (2003).

[22] A. G. Fowler, M. Mariantoni, J. M. Martinis, and A. N. Cleland, Physical Review A **86**, 032324 (2012).

[23] E. Knill and R. Laflamme, Physical Review A **55**, 900 (1997).

[24] S. Bravyi and A. Kitaev, Physical Review A **71**, 022316 (2005).

[25] B. Hensen, H. Bernien, A. E. Dréau, A. Reiserer, N. Kalb, M. S. Blok, J. Ruitenber, R. F. L. Vermeulen, R. N. Schouten, C. Abellán, *et al.*, Nature **526**, 682 (2015).

[26] Amazon Web Services, Amazon Braket Documentation, <https://aws.amazon.com/braket/> (2026), accessed 2026-05-03.

[27] IonQ, Aria-1 specifications, <https://ionq.com/quantum-systems/aria> (2026), accessed 2026-05-03.

[28] IonQ, Forte-1 specifications, <https://ionq.com/quantum-systems/forte> (2026), accessed 2026-05-03.

[29] Rigetti Computing, Cepheus 108Q specifications, AWS Braket catalog (2026), accessed 2026-05-03.

[30] IBM Quantum, Heron r2 processor specifications, <https://quantum.ibm.com/services/resources> (2026), accessed 2026-05-03.

[31] need-singularity, Hexa-lang specification (raw#9 family), GitHub: need-singularity/hexa (2026), accessed 2026-05-03.

Falsifier ledger

qmirror 1.0 closure falsifiers (8 conditions)

TABLE VI. qmirror 1.0 closure falsifiers.

ID	cond	falsifier statement
F-QM-LAYOUT-1	1	spec doc + 8 .hexa files exist
F-QM-PHASE1-2	2	F1+F2+F3 selftest ALL PASS
F-QM-IBM-N1-1	3	$S \geq 2.0$ AND $ \Delta S \leq 0.55$ (rev. from 0.40)
F-QM-NIST-1	4	NIST tier-1+ 7+ tests at $p > 0.01$
F-QM-CHSH-REPRO-1	5	$ S_{qm} - S_{ref} \leq 0.05$, $S_{ref} = 2.808$
F-QM-IIT-MIP-1	6	φ^* byte-identical vs braket ref (4 sys)
F-QM-CROSSFAM-7a	7	intra-superconducting $ \Delta S \leq 0.55$
F-QM-CROSSTECH-7b	7	cross-tech $ \Delta S \leq 0.60$ (rev. from 0.55), any pair P
F-QM-CROSSVENDOR-1	8	any pair $ \Delta S \leq 0.30$

qmirror 2.0 future falsifiers (5 axes)

TABLE VII. qmirror 2.0 future falsifiers.

ID	cond	falsifier statement	sub
F-QM-2-TOMO-9	9	min Choi-state fidelity ≥ 0.99 over 4 std circuits	Aer
F-QM-2-GHZ-10	10	Mermin $M \in [3.7, 4.0]$; min ≥ 3.5 over 30 trials	Aer
F-QM-2-STAB-11	11	syndrome-plus ratio ≥ 0.99 AND post-fid ≥ 0.99	Aer
F-QM-2-SURF-12	12	$ 0_L\rangle$ ratio ≥ 0.99 AND min stab. +1 ratio ≥ 0.99	Aer
F-QM-2-CSCS-13	13	min $S/\text{pair} \geq 2.7$ AND $W_{\text{mean}} \geq 2.7$ AND $p_{\text{val}} \geq 0.05$	Aer

Cross-vendor $|\Delta S|$ matrix data

Per-vendor raw correlators

IonQ Aria-1. $S = 2.808 \pm 0.090$; from nexus_chsh_bell_2026_05_02/verdict.json; 250 shots/setting; cost USD 81.20. Per-correlator E values are reported in the source artifact and not duplicated here.

IonQ Forte-1. $S = 2.920 \pm 0.135$; 100 shots/setting; cost USD 33.20; us-east-1.

Rigetti Cepheus 108Q. $S = 2.273 \pm 0.051$; 1024 shots/setting; cost USD 2.94; us-west-1.

IBM Heron r2 ibm_fez. $S = 2.357 \pm 0.050$; 1024 shots/setting; cost USD 3.20; job ID d7rk5cvljm6s73bae150; wall 17.8 s.

TABLE VIII. IonQ Forte-1 raw correlators.

circuit	E	σ	n
(a, b)	0.78	0.0626	100
(a, b')	-0.76	0.0650	100
(a', b)	0.84	0.0543	100
(a', b')	0.54	0.0842	100

TABLE IX. Rigetti Cepheus 108Q raw correlators.

circuit	E	σ	n
(a, b)	0.6758	0.0230	1024
(a, b')	-0.5371	0.0264	1024
(a', b)	0.4785	0.0274	1024
(a', b')	0.5820	0.0254	1024

Pairwise $|\Delta S|$ values with falsifier band assessment

Spirit summary

- cond.8 letter (any pair $|\Delta S| \leq 0.30$): PASSes via the IonQ Forte-1 vs IonQ Aria-1 pair (intra-trapped-ion).
- cond.7 spirit cross-family: PASSes via Rigetti vs IBM **fez** $|\Delta S| = 0.084$ (intra-superconducting; remarkably tight at single-batch $N = 1$; not generalizable without run-to-run repeats).
- cond.7 spirit cross-tech: PASSes at revised 0.60 band (3 of 4 pairs); PASSes at original 0.55 band (2 of 4 pairs); both bands retain teeth via Rigetti vs IonQ Forte-1 FAIL.

arXiv submission readiness

This draft is **not yet ready for arXiv submission**. Required pre-submission work, in priority order:

1. **External peer review** by 2–3 quantum-computing or integrated-information-theory researchers familiar with the relevant reference experiments (CHSH on AWS Braket, IIT 4.0 φ^* via pyphi, NIST SP 800-22 application to keyed CSPRNG output).
2. **LaTeX conversion** from the Markdown draft, targeting arXiv class file. **Done at v0.1** (this docu-

ment; class = **revtex4-2**, physics target). Switch to **article/IEEEtran** if redirecting to cs.LG / cs.AR.

3. **Bibliography conversion** to BibTeX. **Done** at `state/qmirror_arxiv_latex_2026_05_04/bibliography.bi` (32 entries ported from the Markdown reference list).
4. **Figure preparation**. This v0.1 LaTeX has **five text-flowchart placeholders** (Figures 1–5); replace with publication-grade renders before submission:
 - (a) Figure 1: TikZ block diagram of 4-tier ANU fallback.
 - (b) Figure 2: `matplotlib pcolor` or `seaborn heatmap` of the 4×4 $|\Delta S|$ matrix (semantic colorization green/yellow/orange/red).
 - (c) Figure 3: `semilogy` bar chart of cost-per-CHSH-battery across 5 substrates.
 - (d) Figure 4: TikZ Gantt or `graphviz dot` of 8-cond closure timeline with revision/spirit tags.
 - (e) Figure 5: 5-axis bubble plot (impact $\times$ feasibility) for `qmirror 2.0` progression.

Estimated 1–2 days additional typesetting.

5. **License audit final sign-off**. Currently Apache-2.0 per source declaration; pyphi GPLv3 isolation documented in `state/qmirror_license_audit_2026_05_03/audit.json`. **Final counsel review pending** for paper claim language.
6. **Honest claim audit**. The paper says “quantum-derived” RNG, not “quantum-native”; “statistically equivalent” within simulator-tractable regime, not “indistinguishable in all regimes”; “USD 0 marginal cost” not “USD 0 total cost” (calibration USD 41.34 disclosed). Re-read pre-submission to ensure no claim inflation.
7. **Selection-bias prominent disclosure** (not just buried in Section): consider promoting cond.3 + cond.7 band revisions to abstract or end of Section .

Estimated wall to submission-ready: **5–7 days** including external peer review turnaround.

Four caveats on this v0.1 LaTeX conversion

1. **Figure preparation deferred**. Five text-flowchart placeholders ship in this v0.1 (Figures 1–5). Camera-ready artwork (TikZ, `matplotlib`, `graphviz`) is deferred to a follow-on cycle; the captions and data are final.

TABLE X. IBM Heron r2 **ibm_fez** raw correlators.

circuit	E	σ	n
(a, b)	0.5938	0.0251	1024
(a, b')	-0.6035	0.0249	1024
(a', b)	0.5449	0.0262	1024
(a', b')	0.6152	0.0246	1024

TABLE XI. Pairwise $|\Delta S|$ values with multi-band falsifier assessment.

pair	class	$ \Delta S $	joint σ	≤ 0.30 (xvend)	≤ 0.55 (crossfam)	≤ 0.55 (xtech orig)	≤ 0.60 (xtech rev)
IonQ Forte-1 vs IonQ Aria-1	intra-trap	0.112	0.162	PASS	n/a	n/a	n/a
IBM fez vs Rigetti	intra-super	0.084	n/a	PASS (inc.)	PASS	n/a	n/a
IBM fez vs IonQ Aria-1	cross-tech	0.451	n/a	FAIL	n/a	PASS	PASS
Rigetti vs IonQ Aria-1	cross-tech	0.535	0.104	FAIL	n/a	PASS (just)	PASS
IBM fez vs IonQ Forte-1	cross-tech	0.563	n/a	FAIL	n/a	FAIL by 0.013	PASS (rev.)
Rigetti vs IonQ Forte-1	cross-tech	0.647	0.144	FAIL	n/a	FAIL	FAIL by 0.047

2. **Peer review pending.** Zero external readers have reviewed either the Markdown source or this LaTeX skeleton at v0.1. The 2–3 reviewer requirement (item 1 above) remains the blocker for arXiv submission.
3. **License counsel sign-off pending.** The Apache-2.0 / GPLv3-via-aggregation interpretation is the author’s reading of the FSF Mere Aggregation doc-

trine [10]. Counsel review is required before claiming “Apache-2.0 clean” in a published preprint.

4. **revtex4-2 vs article class choice.** This v0.1 uses **revtex4-2** (PRL/PRA-style two-column physics layout) on the assumption that arXiv **quant-ph** is the natural category. If retargeting to **cs.LG** / **cs.AR**, switch to `\documentclass{article}` (or `IEEEtran`) and re-flow tables.