

	<h1>GENYUS</h1>	SPECIFICATIONS
		Rev. 0 – Ed. 1

SPECIFICATIONS AND FIELDS OF EMPLOYMENT

Extra-washable wall water paint for interior and exterior use, easily applicable and retouchable thanks to its roller anti-drop and to its brush self-expanding effect . It is completely mat and perfectly white and presents an excellent covering power.

It can be applied on all types of supports such as: plaster, plasterboard, lime and/or cement-based pargets, old water paints (after proper preparation).

COMPOSITION

GENIUS SPECIAL contains titanium dioxide, alkalis-resistant polyacetovinyl copolymers in emulsion, flatting charges, special reinforcing fillers and non-toxic additives. It does not contain any noxious substance such as lead and chrome-based solvents and pigments.

METHODS OF APPLICATION

Sand, clean out, plaster over any imperfection with STUCCOMURO or with POLISTICK (depending on the thickness of the imperfection). Apply a coat of FISSATIVO UNIVERSALE diluted in water from a ratio of 1 to 5 to a ratio of 1 to 10, according to the absorption degree of the support.

Let it dry for at least 4 hours and apply two coats of water paint GENIUS, opportunely diluted, (see the technical data) at a distance of 4/5 hours after the application of the first coat.

TECHNICAL DATA

SPECIFIC WEIGHT:	1400 +/- 30 grams/litres
FILM ASPECT:	MAT
COLOURS:	white (other colours by request)
VISCOSITY:	thixotropic aspect
YIELD:	7-8 m ² /litres (by two coats)
DILUTION:	40-50% in water for paintbrush and roller application 60% in water for spray application
PACKAGE:	14-litres tin-plated cases available 5/ 2,5 litres polyethylene cases available
DRYING:	to the touch 30 minutes, completely 24 hours at 20°C
APPLICATION:	paintbrush, roller, spray
PRESERVATION:	36 months in the intact packages, away from temperature changes

ITEM OF SPECIFICATIONS

Painting of indoor walls using mat water paint like the GENIUS produced by SPIVER Ltd., applied by two paintbrush, roller or spray coats with an average consumption of 0.150 litres/m², previous application of a coat of FISSATIVO UNIVERSALE, produced by SPIVER Ltd., diluted in water from a ratio of 1 to 5 to a ratio of 1 to 10, according to the absorption degree of the support.

Price inclusive of the material and implementation, except the scaffoldings per square metre: £.....

NB The above-mentioned data are susceptible of variations. Spiver Ltd. is not responsible for any negative result depending on the application of the product out of the Company's control and on the agents unrelated to the product quality.