

Revision nr.9 Dated 27/01/2010 Printed on 28/01/2010 Page n. 1 / 4 EN

Safety Data Sheet

1. Identification of the substance / preparation and the Company

1.1 Identification of the substance or preparation

Product name COCCIO PESTO

1.2 Use of the substance / preparation

Intended use decorative internal coating

1.3 Company identification

Name SPIVER S.r.I.

Full address Contrada Babbaurra SS 122

District and Country 93100 CALTANISSETTA (CL)

ITALY

Tel. +39 0934 577791 Fax +39 0934 588795

e-mail address of the competent person responsible for the Safety Data Sheet

info@spiver.it

1.4 Emergency telephone

For urgent inquiries refer to +39 0934 577791

2. Hazards Identification.

2.1 Substance/Preparation Classification.

This product is dangerous under 67/548/EEC and 1999/45/EC directives and subsequent amendments. Therefore, this product requires a safety data sheet according to the Regulation (EC) 1907/2006 and subsequent amendments. Further information on health and/or environmental hazards can be found in sections 11 and 12 of this sheet.

Danger Symbols: Xi

R phrases: 41

2.2 Danger Identification.

RISK OF SERIOUS DAMAGE TO EYES.

3. Composition / Information on ingredients.

Contains:

Name. Concentration % (C). Classification.

CALCE IDRATA 21<= C <22,5 Xi R 41

C.A.S. number 1305-62-0 EC number 215-137-3

The complete text of -R- phrases is specified in section 16.

4. First aid measures.

EYES: Wash immediately with plenty of water for at least 15 minutes and seek medical advice at once.

SKIN: Immediately take off all contaminated clothing and have a shower. Seek medical advice.

INGESTION: Have the patient drink water as much as possible and seek medical advice immediately. Do not induce vomiting before consulting a doctor.

INHALATION: Immediately seek medical advice. In the meantime, remove the patient to open air, far from the contaminated premises; if respiration stops or is difficult, give an artificial respiration adopting the proper measure for the helper.





Revision nr.9 Dated 27/01/2010 Printed on 28/01/2010 Page n. 2 / 4

5. Fire-fighting measures.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SUITABLE EXTINGUISHING MEDIA

The extinction equipment should be of the conventional kind: carbon dioxide, foam, powder and nebulised water.

EXTINGUISHING MEDIA WHICH SHALL NOT BE USED FOR SAFETY REASONS

None in particular.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products (carbon oxide, toxic pyrolysis products, etc).

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Hardhat with visor, fireproof clothing (fireproof jacket and trousers with straps around arms, legs and waist), work gloves (fireproof, cut proof and dielectric), a depressurised mask with facemask covering the whole of the operator's face or a self-respirator (self-protector) in the event of large quantities of fume.

6. Accidental release measures.

PERSONAL PRECAUTIONS

Wear appropriate protective equipment. Send away individuals who are not suitably equipped. Use breathing equipment if fumes or powders are released into the air. Block the leakage if there is no hazard. Do not handle damaged containers or the leaked product before donning appropriate protective gear. For information on risks for the environmental and health, respiratory tract protection, ventilation and personal protection equipment, refer to the other sections of this sheet.

ENVIRONMENTAL PRECAUTIONS

The product must not penetrate the sewers, surface water, ground water and neighbouring areas. Dilute the product well with water after collection.

METHODS FOR CLEANING UP

Suck the liquid into a suitable container (made of material not incompatible with the product) and soak up any leaked product with absorbent inert material (sand, vermiculite, diatomeous earth, Kieselguhr, tripoli powder, universal cement, etc). Neutralise remaining material. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

7. Handling and storage.

Make sure that equipment is available for cooling the vessels, to prevent the danger of overpressure and overheating in the event of fire in the vicinity. Refer to the other sections of this data sheet for information relating to health and environmental risks.

8. Exposure control / personal protection.

8.1 Exposure limit values.

| Name | Туре | Country | y TWA/8h | | STEL/15min | | |
|--------------|-----------|---------|----------|-----|------------|-----|--|
| | | | mg/m3 | ppm | mg/m3 | ppm | |
| | | | | | | | |
| CALCE IDRATA | TLV-ACGIH | | 5 | 0 | 0 | 0 | |
| | | | | | | | |

8.2 Exposure controls.

As the use of adequate technical equipment must always take priority over personal protection equipment, make sure that the workplace is well aired through effective local aspiration or bad air vent. If such operations do not make it possible to keep the concentration of the product below the permitted workplace exposure thresholds a suitable respiratory tract protection must be used. See product label for hazard details during use. Ask your chemical substance suppliers for advice when choosing personal protection equipment. Personal protection equipment must comply with the rules in force indicated below.

HAND PROTECTION

Protect hands with category I (ref. Directive 89/686/EEC and standard EN 374) work gloves, such as those in latex, PVC or equivalent. The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves' limit depends on the duration of exposure.

EYE PROTECTION

Wear hood visor or protective visor together with airtight goggles (ref. standard EN 166).

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (ref. Directive 89/686/CEE and standard EN 344). Wash body with soap and water after removing overalls.

RESPIRATORY PROTECTION

If the threshold value for one or more of the substances present in the preparation for daily exposure in the workplace or to a fraction established by the company's prevention and protection service is exceeded, wear a mask with an B or universal filter, the class (1, 2 or 3) of which must be chosen according to the limit concentration of use (ref. standard EN 141).



Revision nr.9 Dated 27/01/2010 Printed on 28/01/2010 Page n. 3 / 4 ΕN

The use of breathing protection equipment, such as masks with organic vapour and dust/mist cartridges, is necessary in the absence of technical measures limiting worker exposure. The protection provided by masks is in any case limited.

If the substance in question is odourless or its olfactory threshold is higher than the relative exposure limit and in the event of an emergency, or when exposure levels are unknown or the concentration of oxygen in the workplace is less than 17% volume, wear self-contained, open-circuit compressed air breathing apparatus (ref. standard EN 137) or fresh air hose breathing apparatus for use with full face mask, half mask or mouthpiece (ref. standard EN 138).

An emergency eye washing and shower system must be provided.

9. Physical and chemical properties.

Colour WHITISH
Odour ODORLESS
Appearance PASTE

Solubility MISCIBLE IN WATER

Viscosity Not available. Vapour density Not available. **Evaporation Rate** Not available. Reactive Properties Not available. Partition coefficient: n-octanol/water Not available. pH. 13 - 13,5 Boiling point. Not available. Flash point. 61 °C. Explosive properties. Not available.

Vapour pressure. Not available.

Specific gravity. 1,600 - 1,700 VOC (Directive 1999/13/EC) : 0

VOC (Directive 1999/13/EC): 0
VOC (volatile carbon): 0

10. Stability and reactivity.

The product is stable in normal conditions of use and storage. In the event of thermal decomposition or fire, vapours potentially dangerous to health may be released.

Kg/I

11. Toxicological information.

This product may cause serious ocular lesions, cornea opacity, iris lesions, irreversible eye coloration.

CALCIUM CARBONATE: oral LD50 (mg/kg) 6450 (RAT). CALCIUM HYDROXIDE: oral LD50 (mg/kg) 7340 (RAT).

12. Ecological information.

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

13. Disposal consideration.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information.

This product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

15. Regulatory information.



MSDS EPY 0801



Revision nr.9 Dated 27/01/2010 Printed on 28/01/2010 Page n. 4/4

ΕN

RISK OF SERIOUS DAMAGE TO EYES. R 41

S 25 AVOID CONTACT WITH EYES.

IN CASE OF CONTACT WITH EYES, RINSE IMMEDIATELY WITH PLENTY OF WATER AND SEEK MEDICAL S 26

ADVICE

S 39 WEAR EYE/FACE PROTECTION.

Danger labelling under directives 67/548/EEC and 1999/45/EC and following amendments and adjustments.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC):

Decorative effect coatings.

VOC given in g/litre of product in a ready-to-use condition : Limit value: 200,00 (2010)

VOC of product: 0.00

16. Other information.

Text of (R) phrases quoted in section 3 of the sheet.

RISK OF SERIOUS DAMAGE TO EYES. R 41

GENERAL BIBLIOGRAPHY

- 1. Directive 1999/45/EC and following amendments;
- 2. Directive 67/548/EEC and following amendments and adjustments (technical adjustment XXIX);
- 3. Regulation (EC) 1272/2008 (CLP) of the European Parliament;
- 4. Regulation (EC) 1907/2006 (REACH) of the European Parliament;
- 5. The Merck Index. 10th Edition;
- 6. Handling Chemical Safety;
- 7. Niosh Registry of Toxic Effects of Chemical Substances;
- 8. INRS Fiche Toxicologique (toxicological sheet);
- 9. Patty Industrial Hygiene and Toxicology;
- 10. N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition;

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product .

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Changes to previous review.

The following sections were modified:

01 / 08 / 09 / 13

MSDS EPY 0801