

# ARTHE CERA

SCHEDA TECNICA

Rev. 0 - Ed. 1

### SPECIFICATION AND FIELDS OF EMPLOYMENT

Transparent water paste wax which is especially for the protection of Venetian stucco both synthetic and lime. It produces a greater brightness of the stucco and it improves the wash ability and gives greater uniformity of final colour.ARTHE CERA is colourable with ARTHE CONCENTRATO / or dyes of our GLOBAL Tinting SYSTEM.

### **COMPOSITION**

Special water emulsion wax, non-toxic additives.

### **METHOD OF APPLICATION:**

SURFACE PREPERATION

- Apply directly on polished finished plaster with a very thin stainless float.
- Leave to absorb and dry for at least 2 hours
- Proceed to the final levelling with stainless float.

#### **TECHNICAL DATA**

SPECIFIC WEIGHT 0,90 Kg./Lt. +/- 1% VISCOSITY thixotropic aspect DRYING TO THE TOUCH 2 hours at 20℃ COMPLETELY DRY 24 hours at 20℃ TEMPERATURE PF APPLICATION between 5℃ and 30℃ YIELD 20 - 25 mg./Lt.**COLOURS** transparent **PACKAGE** cans of ml. 750 and Lt. 4

PRESERVATION 24 months in the intact packages, away from temperature changes

## ITEM OF SPECIFICATION

Protecting walls or surfaces with surfaces Venetian stucco with a paste wax water type of ARTHE CERA Spiver Inc. , Based on special wax emulsion water, non-toxic additives.

The price includes the equipment and implementation, excluding the scaffolding sqm. €.....

NB The above-mentioned data are susceptible of variations. Spiver Ltd. Is not responsible for any negative result depending on the application of the product out of the company's control and on the agents unrelated to the product quality.