Research vision


Danel Ahman

University of Ljubljana

Balliol College, 12.11.2018


Programming Languages

```
let r = alloc 0 in r := !r + 1; r
```




Programming Languages

let r = alloc 0 in r := !r + 1; r




Typed Programming Languages


let r = alloc 0 in r := !r + 1; r : ref Nat



let r = alloc 0 in r := !r + 1; r : ref Nat



But what about behaviour?



State of affairs in type-based reasoning

State of affairs in type-based reasoning

Values

Well-understood, uniform, and thoroughly studied!:)

Refinement types

Dependent types

```
Vec a n = \Sigma l:List A.(len l = n)
```

- Homogeneous implementations
 - Agda, Coq, Idris, F*, L.Haskell, ...

State of affairs in type-based reasoning

Values

Well-understood, uniform, and thoroughly studied!:)

Refinement types

Dependent types

```
Vec a n = \Sigma l:List A.(len l = n)
```

- Homogeneous implementations
 - Agda, Coq, Idris, F*, L.Haskell, ...

Effects and behaviour

Scattered landscape, effectspecific, little uniformity! :(

• Hoare Type Theory (state)

```
M : \Psi.X.\{P\}x:A\{Q\}
```

F* (state, exceptions, but no I/O)

```
M : ST A wp<sub>st</sub>

M : 10 A wp<sub>10</sub>
```

Session Types (I/O & channels)

```
c: ?Nat.!String.!Nat.T
```

• Graded monads, param. monads

- Goal: a general, uniform framework for reasoning about effects
 - wide range of effects (state, I/O, exceptions, probability, ...)
 - primitive and user-defined effects
 - combinations of effects

- Goal: a general, uniform framework for reasoning about effects
 - wide range of effects (state, I/O, exceptions, probability, ...)
 - primitive and user-defined effects
 - combinations of effects
- Answer: algebraic effects and effect handlers (rather than just monads)
 - operations and equations
 - reveal the fundamental underlying tree-like structure of effects
 - effect handlers are algebras; handling is homomorphism application

Goal: a general, uniform
 - wide range of effects (see and user-defined)
 - primitive and user-defined
 - combinations of effect
 Answer: algebraic effect
 - operations and equation

- reveal the fundamental underlying tree-like structure of effects
- effect handlers are algebras; handling is homomorphism application

Goal: a general, uniform
 wide range of effects (
 primitive and user-defi
 combinations of effect
 Answer: algebraic effect

read

 write₀
 write₀
 write₀
 write₀
 x
 x

Answer: algebraic effect

- reveal the fundamental underlying tree-like structure of effects

- operations and equation


- effect handlers are algebras; handling is homomorphism application

Goal: a general, uniform
 wide range of effects (read

- primitive and user-defi


combinations of effect

- Answer: algebraic effect
 - operations and equation




- reveal the fundamental underlying tree-like structure of effects
- effect handlers are algebras; handling is homomorphism application


- Goal: a general, uniform :
 - wide range of effects (
 - primitive and user-defi
 - combinations of effect
- Answer: algebraic effect
 - operations and equation




- reveal the fundamental underlying tree-like structure of effects
- effect handlers are algebras; handling is homomorphism application



- Goal: a general, uniform
 - wide range of effects (
 - primitive and user-defi
 - combinations of effect
- Answer: algebraic effect
 - operations and equation



- reveal the fundamental underlying tree-like structure of effects
- effect handlers are algebras; handling is homomorphism application



- Goal: a general, uniform framework for reasoning about effects
 - wide range of effects (state, I/O, exceptions, probability, ...)
 - primitive and user-defined effects
 - combinations of effects
- Answer: algebraic effects and effect handlers (rather than just monads)
 - operations and equations
 - reveal the fundamental underlying tree-like structure of effects
 - effect handlers are algebras; handling is homomorphism application

- Goal: a general, uniform framework for reasoning about effects
 - wide range of effects (state, I/O, exceptions, probability, ...)
 - primitive and user-defined effects
 - combinations of effects
- Answer: algebraic effects and effect handlers (rather than just monads)
 - operations and equations
 - reveal the fundamental underlying tree-like structure of effects
 - effect handlers are algebras; handling is homomorphism application
- State of the art: very popular (!) but effect systems too coarse grained (!)
 - concurrency, probability, delimited control, monadic reflection, ...
 - Multicore OCaml, Uber's Pyro tool, Eff, Koka, Frank, ...
 - -M : A ! { read , write, throw }

- Simple idea: exploit the underlying tree-like structure of effects!
 - <op>(ψ₁,..., ψ_n) for each n-ary <u>operation symbol</u> (cf TYPES'15)

- Simple idea: exploit the underlying tree-like structure of effects!
 - <op>(ψ₁,..., ψ_n) for each n-ary <u>operation symbol</u> (cf TYPES'15)

$$\langle op \rangle (\psi_1, ..., \psi_n) = \left\{ \begin{array}{c} op \\ \downarrow \\ t_1 \end{array} \right. \quad t_n \left[\begin{array}{c} t_1 \in \psi_1 \land \cdots \land t_n \in \psi_n \end{array} \right\}$$

M : A ! 4

- Simple idea: exploit the underlying tree-like structure of effects!
 - <op>(ψ₁,..., ψ_n) for each n-ary <u>operation symbol</u> (cf TYPES'15)

- Simple idea: exploit the underlying tree-like structure of effects!
 - <op>(ψ₁,..., ψ_n) for each n-ary <u>operation symbol</u> (cf TYPES'15)

Major pros:

- uniform across all algebraic effects
- can already encode Hoare Logic, Session Types, HL ⊗ ST, ...

- Simple idea: exploit the underlying tree-like structure of effects!
 - <op>(ψ₁,..., ψ_n) for each n-ary <u>operation symbol</u> (cf TYPES'15)

Major pros:

- uniform across all algebraic effects
- can already encode Hoare Logic, Session Types, HL ⊗ ST, ...

```
\{\{1\}\}\} A \{Q\} = A ! V_{i\in\{0,1\},q\in Q} <rd>(<wr<sub>i</sub>>(ret),<wr<sub>q</sub>>(ret))
```

- Simple idea: exploit the underlying tree-like structure of effects!
 - <op>(ψ₁,..., ψ_n) for each n-ary <u>operation symbol</u> (cf TYPES'15)

Major pros:

- uniform across all algebraic effects
- can already encode Hoare Logic, Session Types, HL ⊗ ST, ...

- Simple idea: exploit the underlying tree-like structure of effects!
 - <op>(ψ₁,..., ψ_n) for each n-ary <u>operation symbol</u> (cf TYPES'15)

Major pros:

- uniform across all algebraic effects
- can already encode Hoare Logic, Session Types, HL ⊗ ST, ...

Challenges:

- lifting non-linear effect equations (read x x = x)
- operations with value params. and variable binding
- effect instances, generativity, and locality (my current focus in LJ)
- dynamic nature of handlers

- Separation Logic (state, I/O, state ⊗ I/O, ...)
 - HL + generative instances and locality

- Separation Logic (state, I/O, state ⊗ I/O, ...)
 - HL + generative instances and locality
- Big Data Computations
 - commutative monoid structure (an algebraic effect)
 - partitioning, spatial layout, ...

- Separation Logic (state, I/O, state ⊗ I/O, ...)
 - HL + generative instances and locality
- Big Data Computations
 - commutative monoid structure (an algebraic effect)
 - partitioning, spatial layout, ...
- Concurrency
 - (multi-)handlers based concurrency
 - Scala's promises and futures as a monotonic state effect

- Separation Logic (state, I/O, state ⊗ I/O, ...)
 - HL + generative instances and locality
- Big Data Computations
 - commutative monoid structure (an algebraic effect)
 - partitioning, spatial layout, ...
- Concurrency
 - (multi-)handlers based concurrency
 - Scala's promises and futures as a monotonic state effect
- Probabilistic programming
 - sample as an algebraic effect; condition as a handler (cf Pyro)

Temporal view

- Year 1
 - modal logic (design, model and proof theory)
 - instances, generativity, locality
 - case studies and applications
- Year 2
 - declarative PL design (type-and-effect system)
 - meta-theory (denotational and operational)
 - case studies and applications
- Year 3
 - algorithmic PL design (type-and-effect inference)
 - implementation
 - case studies and applications

Temporal view

Year 1

- modal logic (design, model and proof theory)
- instances, generativity, locality
- case studies and applications

Year 2

- declarative PL design (type-and-effect system)
- meta-theory (denotational and operational)
- case studies and applications

Year 3

- algorithmic
- implementa
- case studies

In parallel

- continue collaborations with the F* team
- continue collaborations on container datatypes
- forge new collaborations in Oxford (and elsewhere)

Conclusions

- Software is everywhere!
- We had better know what it does!

- General and uniform frameworks already exist for values!
- But only scattered, effect-specific frameworks for behaviour!

- My research will seek to rectify this situation
 - a uniform and widely applicable approach
 - inspired by <u>algebraic effects</u> and <u>effect handlers</u>
 - both <u>foundational theory</u> and <u>exciting applications</u>