

# Embracing monotonicity in



Danel Ahman @ INRIA Paris

based on a joint POPL 2018 paper with

Cătălin Hrițcu and Kenji Maillard @ INRIA Paris

Cédric Fournet, Aseem Rastogi, and Nikhil Swamy @ MSR

Software Science Departmental Seminar, TUT

February 12, 2018



# and embracing monotonicity (in it)

Danel Ahman @ INRIA Paris

based on a joint POPL 2018 paper with

Cătălin Hrițcu and Kenji Maillard @ INRIA Paris

Cédric Fournet, Aseem Rastogi, and Nikhil Swamy @ MSR

Software Science Departmental Seminar, TUT

February 12, 2018

# Outline

- \* F\* overview
- Monotonic state by example
- Key ideas behind our general extension to Hoare-style logics
- Accommodating monotonic state in F\*
- Some examples of monotonic state at work
- Glimpse of meta-theory and correctness results
- More examples of monotonic state at work (see our paper)
- Monadic reification and reflection (see our paper)

# Outline

- \*  $F^*$  overview
- Monotonic state by example
- Key ideas behind our general extension to Hoare-style logics
- Accommodating monotonic state in  $F^*$
- Some examples of monotonic state at work
- Glimpse of meta-theory and correctness results
- More examples of monotonic state at work (see our paper)
- Monadic reification and reflection (see our paper)

- **F\*** is
  - a **functional programming language**
    - ML, OCaml, F#, Haskell, ...
    - extracted to OCaml or F#; subset compiled to efficient C code
  - an **interactive proof assistant**
    - Agda, Coq, Lean, Isabelle/HOL, ...
    - interactive modes for Emacs and Atom
  - a **semi-automated verifier** of imperative programs
    - Dafny, Why3, FramaC, ...
    - Z3-based SMT-automation; tactics and metaprogramming (WIP)
- **Application-driven development**
  - Project Everest [project-everest.github.io]
  - miTLS, HACL\*, Vale, ...
  - Microsoft Research (US, UK, India), INRIA (Paris), ...

- **F\*** is
  - a **functional programming language**
    - ML, OCaml, F#, Haskell, ...
    - extracted to OCaml or F#; subset compiled to efficient C code
  - an **interactive proof assistant**
    - Agda, Coq, Lean, Isabelle/HOL, ...
    - interactive modes for Emacs and Atom
  - a **semi-automated verifier** of imperative programs
    - Dafny, Why3, FramaC, ...
    - Z3-based SMT-automation; tactics and metaprogramming (WIP)
- **Application-driven** development
  - Project Everest [project-everest.github.io]
  - miTLS, HACl\*, Vale, ...
  - Microsoft Research (US, UK, India), INRIA (Paris), ...



```
module Talk

// Dependent (inductive) types

type vector 'a : nat -> Type =
| Nil : vector 'a 0
| Cons : #n:nat -> 'a -> vector 'a n -> vector 'a (n + 1)
```



```

module Talk

// Dependent (inductive) types

type vector 'a : nat -> Type =
| Nil : vector 'a 0
| Cons : #n:nat -> 'a -> vector 'a n -> vector 'a (n + 1)

// Dependently typed (recursive, total) functions

val append : #a:Type -> #n:nat -> #m:nat -> vector a n -> vector a m -> Tot (vector a (n + m))
let rec append #a #n #m xs ys =
  match xs with
  | Nil -> ys
  | Cons #n x xs' -> Cons x (append xs' ys)

```

```

module Talk

// Dependent (inductive) types

type vector 'a : nat -> Type =
| Nil : vector 'a 0
| Cons : #n:nat -> 'a -> vector 'a n -> vector 'a (n + 1)

// Dependently typed (recursive, total) functions

val append : #a:Type -> #n:nat -> #m:nat -> vector a n -> vector a m -> Tot (vector a (n + m))
let rec append #a #n #m xs ys =
  match xs with
  | Nil -> ys
  | Cons #n x xs' -> Cons x (append xs' ys)

// Refinement types

let in_range_index (min:nat) (max:nat) = i:nat{min <= i /\ i <= max}

val lkp : #a:Type -> #n:nat -> vector a n -> in_range_index 1 n -> Tot a
let rec lkp #a #n xs i =
  match xs with
  | Cons x xs' -> if i = 1 then x else lkp xs' (i - 1)

```

```

module Talk

// Dependent (inductive) types

type vector 'a : nat -> Type =
| Nil : vector 'a 0
| Cons : #n:nat -> 'a -> vector 'a n -> vector 'a (n + 1)

// Dependently typed (recursive, total) functions

val append : #a:Type -> #n:nat -> #m:nat -> vector a n -> vector a m -> Tot (vector a (n + m))
let rec append #a #n #m xs ys =
  match xs with
  | Nil -> ys
  | Cons #n x xs' -> Cons x (append xs' ys)

// Refinement types

let in_range_index (min:nat) (max:nat) = i:nat{min <= i /\ i <= max}

val lkp : #a:Type -> #n:nat -> vector a n -> in_range_index 1 n -> Tot a
let rec lkp #a #n xs i =
  match xs with
  | Cons x xs' -> if i = 1 then x else lkp xs' (i - 1)

// First-class predicates (for which Type0 behaves like (classical) Prop)

type is_prefix_of (#a:Type) (#n:nat) (#m:nat) (xs:vector a n) (zs:vector a m{n <= m}) : Type0 =
  forall (i:nat) . (1 <= i /\ i <= n) ==> lkp xs i == lkp zs i

```

```

module Talk

// Dependent (inductive) types

type vector 'a : nat -> Type =
| Nil : vector 'a 0
| Cons : #n:nat -> 'a -> vector 'a n -> vector 'a (n + 1)

// Dependently typed (recursive, total) functions

val append : #a:Type -> #n:nat -> #m:nat -> vector a n -> vector a m -> Tot (vector a (n + m))
let rec append #a #n #m xs ys =
  match xs with
  | Nil -> ys
  | Cons #n x xs' -> Cons x (append xs' ys)

// Refinement types

let in_range_index (min:nat) (max:nat) = i:nat{min <= i /\ i <= max}

val lkp : #a:Type -> #n:nat -> vector a n -> in_range_index 1 n -> Tot a
let rec lkp #a #n xs i =
  match xs with
  | Cons x xs' -> if i = 1 then x else lkp xs' (i - 1)

// First-class predicates (for which Type0 behaves like (classical) Prop)

type is_prefix_of (#a:Type) (#n:nat) (#m:nat) (xs:vector a n) (zs:vector a m{n <= m}) : Type0 =
  forall (i:nat) . (1 <= i /\ i <= n) ==> lkp xs i == lkp zs i

// Extrinsic reasoning (using separate lemmas)

val lemma : #a:Type -> #n:nat -> #m:nat -> xs:vector a n -> ys:vector a m -> Lemma (requires (True))
                                                    (ensures (xs `is_prefix_of` (append xs ys)))

let rec lemma #a #n #m xs ys =
  match xs with
  | Nil -> ()
  | Cons x xs' -> lemma xs' ys

```

```

module Talk

// Dependent (inductive) types

type vector 'a : nat -> Type =
| Nil : vector 'a 0
| Cons : #n:nat -> 'a -> vector 'a n -> vector 'a (n + 1)

// Dependently typed (recursive, total) functions

val append : #a:Type -> #n:nat -> #m:nat -> vector a n -> vector a m -> Tot (vector a (n + m))
let rec append #a #n #m xs ys =
  match xs with
  | Nil -> ys
  | Cons #n x xs' -> Cons x (append xs' ys)

// Refinement types

let in_range_index (min:nat) (max:nat) = i:nat{min <= i /\ i <= max}

val lkp : #a:Type -> #n:nat -> vector a n -> in_range_index 1 n -> Tot a
let rec lkp #a #n xs i =
  match xs with
  | Cons x xs' -> if i = 1 then x else lkp xs' (i - 1)

// First-class predicates (for which Type0 behaves like (classical) Prop)

type is_prefix_of (#a:Type) (#n:nat) (#m:nat) (xs:vector a n) (zs:vector a m{n <= m}) : Type0 =
  forall (i:nat) . (1 <= i /\ i <= n) ==> lkp xs i == lkp zs i

// Extrinsic reasoning (using separate lemmas)

val lemma : #a:Type -> #n:nat -> #m:nat -> xs:vector a n -> ys:vector a m -> Lemma (requires (True))
                                                    (ensures (xs `is_prefix_of` (append xs ys)))

let rec lemma #a #n #m xs ys =
  match xs with
  | Nil -> ()
  | Cons x xs' -> lemma xs' ys

// Intrinsic reasoning (making lemmas part of definitions, e.g., using Hoare-style pre- and postconditions)

val take : #a:Type -> n:nat -> #m:nat -> zs:vector a m -> Pure (vector a n) (requires (n <= m))
                                                    (ensures (fun xs -> xs `is_prefix_of` zs))

let rec take #a n #m zs =
  if n > 0 then match zs with
  | Cons z zs' -> let n':nat = n - 1 in Cons z (take n' zs')
  else Nil

```

```
// Heaps, ML-style typed references, and Hoare logic
```

```
open FStar.Heap  
open FStar.ST
```

```
let rec program n =  
  let r = alloc 0 in  
  sum_loop 1 n r;  
  r  
  
and sum_loop i n r =  
  if i < n then (r := !r + i; sum_loop (i + 1) n r)  
  else (r := !r + n)
```

```
// Heaps, ML-style typed references, and Hoare logic
```

```
open FStar.Heap
```

```
open FStar.ST
```

```
val sum : i:nat -> n:nat{i <= n} -> Tot nat (decreases (n - i))
```

```
let rec sum i n =  
  if i < n then i + sum (i + 1) n  
  else n
```

```
val program : n:nat -> ST (ref nat) (requires (fun h0 -> 1 <= n))  
  (ensures (fun h0 r h1 -> fresh r h0 h1 ∧  
    modifies (Set.empty) h0 h1 ∧  
    sel h1 r = sum 1 n))
```

```
let rec program n =  
  let r = alloc 0 in  
  sum_loop 1 n r;  
  r
```

```
and sum_loop i n r =  
  if i < n then (r := !r + i; sum_loop (i + 1) n r)  
  else (r := !r + n)
```

```
// Heaps, ML-style typed references, and Hoare logic
```

```
open FStar.Heap
open FStar.ST
```

```
val sum : i:nat -> n:nat{i <= n} -> Tot nat (decreases (n - i))
```

```
let rec sum i n =
  if i < n then i + sum (i + 1) n
  else n
```

```
val program : n:nat -> ST (ref nat) (requires (fun h0 -> 1 <= n))
  (ensures (fun h0 r h1 -> fresh r h0 h1 ∧
    modifies (Set.empty) h0 h1 ∧
    sel h1 r = sum 1 n))
```

```
val sum_loop : i:nat -> n:nat -> r:ref nat -> ST unit (requires (fun h0 -> 1 <= i ∧ i <= n ∧
  sel h0 r = sum 0 (i - 1)))
  (ensures (fun h0 _ h1 -> modifies (Set.singleton (addr_of r)) h0 h1 ∧
    sel h1 r = sum 1 n))
```

```
let rec program n =
  let r = alloc 0 in
  sum_loop 1 n r;
  r
```

```
and sum_loop i n r =
  if i < n then (r := !r + i; sum_loop (i + 1) n r)
  else (r := !r + n)
```



```

// Heaps, ML-style typed references, and Hoare logic

open FStar.Heap
open FStar.ST

val sum : i:nat -> n:nat{i <= n} -> Tot nat (decreases (n - i))

let rec sum i n =
  if i < n then i + sum (i + 1) n
  else n

val sum_plus_lemma : i:nat -> n:nat -> Lemma (requires (i <= n))
  (ensures (sum i (n + 1) = sum i n + (n + 1)))
  (decreases (n - i))
  [SMTPat (sum i n)]

let rec sum_plus_lemma i n =
  if i < n then sum_plus_lemma (i + 1) n
  else ()

val program : n:nat -> ST (ref nat) (requires (fun h0 -> 1 <= n))
  (ensures (fun h0 r h1 -> fresh r h0 h1 /\
    modifies (Set.empty) h0 h1 /\
    sel h1 r = sum 1 n))

val sum_loop : i:nat -> n:nat -> r:ref nat -> ST unit (requires (fun h0 -> 1 <= i /\ i <= n /\
  sel h0 r = sum 0 (i - 1)))
  (ensures (fun h0 _ h1 -> modifies (Set.singleton (addr_of r)) h0 h1 /\
    sel h1 r = sum 1 n))

let rec program n =
  let r = alloc 0 in
  sum_loop 1 n r;
  r

and sum_loop i n r =
  if i < n then (r := !r + i; sum_loop (i + 1) n r)
  else (r := !r + n)

```

# F\* – not just a pure programming language

- Tot, Lemma, Pure, ... are just some **effects** amongst many
  - Tot  $t$
  - Lemma (requires  $\text{pre}_{\text{Lemma}}$ ) (ensures  $\text{post}_{\text{Lemma}}$ )
  - Pure  $t$  (requires  $\text{pre}_{\text{Pure}}$ ) (ensures  $\text{post}_{\text{Pure}}$ )
  - Div  $t$  (requires  $\text{pre}_{\text{Div}}$ ) (ensures  $\text{post}_{\text{Div}}$ )
  - Exc  $t$  (requires  $\text{pre}_{\text{Exc}}$ ) (ensures  $\text{post}_{\text{Exc}}$ )
  - ST  $t$  (requires  $\text{pre}_{\text{ST}}$ ) (ensures  $\text{post}_{\text{ST}}$ )
  - ...
- **Monad morphs.**  $\text{Pure} \rightsquigarrow \{\text{Div}, \text{Exc}, \text{ST}\}; \text{Exc} \rightsquigarrow \text{STExc}; \dots$
- Systematically derived from **WP-calculi**

[POPL 2017]

# Outline

\*  $F^*$  overview

- Monotonic state by example
- Key ideas behind our general extension to Hoare-style logics
- Accommodating monotonic state in  $F^*$
- Some examples of monotonic state at work
- Glimpse of meta-theory and correctness results
- More examples of monotonic state at work (see our paper)
- Monadic reification and reflection (see our paper)

# Monotonicity in program verification

- Consider a program operating on **set-valued state**

`insert v; complex_procedure(); assert (v ∈ get())`

- To prove the assertion (say, in a Floyd-Hoare style logic), we could prove that the code maintains a **stateful invariant**

$\{\lambda s. v \in s\}$  `complex_procedure()`  $\{\lambda s. v \in s\}$

- likely that we have to **carry**  $\lambda s. v \in s$  **through** the proof of `c_p`
- does not guarantee** that  $\lambda s. v \in s$  holds at every point in `c_p`
- sensitive** to proving that `c_p` maintains  $\lambda s. w \in s$  for some `w`
- However, if `c_p` **never removes**, then  $\lambda s. v \in s$  is **stable**, and we would like the program logic to give us `v ∈ get()` “for free”

# Monotonicity in program verification

- Consider a program operating on **set-valued state**

insert v; complex\_procedure(); **assert** ( $v \in \text{get}()$ )

- To prove the assertion (say, in a Floyd-Hoare style logic), we could prove that the code maintains a **stateful invariant**

$\{\lambda s. v \in s\}$  complex\_procedure()  $\{\lambda s. v \in s\}$

- likely that we have to carry  $\lambda s. v \in s$  through the proof of c\_p
- does not guarantee that  $\lambda s. v \in s$  holds at every point in c\_p
- sensitive to proving that c\_p maintains  $\lambda s. w \in s$  for some w
- However, if c\_p never removes, then  $\lambda s. v \in s$  is stable, and we would like the program logic to give us  $v \in \text{get}()$  “for free”

# Monotonicity in program verification

- Consider a program operating on **set-valued state**

insert v; complex\_procedure(); **assert** ( $v \in \text{get}()$ )

- To prove the assertion (say, in a Floyd-Hoare style logic), we could prove that the code maintains a **stateful invariant**

$\{\lambda s. v \in s\}$  complex\_procedure()  $\{\lambda s. v \in s\}$

- likely that we have to **carry**  $\lambda s. v \in s$  **through** the proof of c\_p
- does not guarantee** that  $\lambda s. v \in s$  holds at every point in c\_p
- sensitive** to proving that c\_p maintains  $\lambda s. w \in s$  for some w
- However, if c\_p **never removes**, then  $\lambda s. v \in s$  is **stable**, and we would like the program logic to give us  $v \in \text{get}()$  “for free”

# Monotonicity in program verification

- Consider a program operating on **set-valued state**

`insert v; complex_procedure(); assert (v ∈ get())`

- To prove the assertion (say, in a Floyd-Hoare style logic), we could prove that the code maintains a **stateful invariant**

$\{\lambda s. v \in s\}$  `complex_procedure()`  $\{\lambda s. v \in s\}$

- likely that we have to **carry**  $\lambda s. v \in s$  **through** the proof of `c_p`
- does not guarantee** that  $\lambda s. v \in s$  holds at every point in `c_p`
- sensitive** to proving that `c_p` maintains  $\lambda s. w \in s$  for some `w`
- However, if `c_p` **never removes**, then  $\lambda s. v \in s$  is **stable**, and we would like the program logic to give us `v ∈ get()` “for free”

# Monotonicity in programming

- **Programming** also relies on **monotonicity**, even if you don't realise it!
- Consider ML-style typed references  $r:\text{ref } a$ 
  - $r$  is a **proof of existence** of an  $a$ -typed value in the heap
- Correctness relies on **monotonicity**!
  - 1) Allocation **stores** an  $a$ -typed value in the heap
  - 2) Writes **don't change type** and there is **no deallocation**
  - 3) So, given a ref.  $r$ , it is **guaranteed to point** to an  $a$ -typed value
- Baked into the memory models of most languages
- We derive them from **global state** + **general monotonicity**



# Monotonicity in programming

- **Programming** also relies on **monotonicity**, even if you don't realise it!
- Consider ML-style typed **references**  $r:\text{ref } a$ 
  - $r$  is a **proof of existence** of an  $a$ -typed value in the heap
- Correctness relies on **monotonicity**!
  - 1) Allocation stores an  $a$ -typed value in the heap
  - 2) Writes **don't change type** and there is **no deallocation**
  - 3) So, given a ref.  $r$ , it is **guaranteed to point** to an  $a$ -typed value
- Baked into the memory models of most languages
- We derive them from **global state** + **general monotonicity**

# Monotonicity in programming

- **Programming** also relies on **monotonicity**, even if you don't realise it!
- Consider ML-style typed **references**  $r:\text{ref } a$ 
  - $r$  is a **proof of existence** of an  $a$ -typed value in the heap
- Correctness relies on **monotonicity**!
  - 1) Allocation **stores** an  $a$ -typed value in the heap
  - 2) Writes **don't change type** and there is **no deallocation**
  - 3) So, given a ref.  $r$ , it is **guaranteed to point** to an  $a$ -typed value
- Baked into the memory models of most languages
- We derive them from **global state + general monotonicity**

# Monotonicity in programming

- **Programming** also relies on **monotonicity**, even if you don't realise it!
- Consider ML-style typed **references**  $r:\text{ref } a$ 
  - $r$  is a **proof of existence** of an  $a$ -typed value in the heap
- Correctness relies on **monotonicity**!
  - 1) Allocation **stores** an  $a$ -typed value in the heap
  - 2) Writes **don't change type** and there is **no deallocation**
  - 3) So, given a ref.  $r$ , it is **guaranteed to point** to an  $a$ -typed value
- Baked into the memory models of most languages
- We derive them from **global state** + **general monotonicity**

# Monotonicity is really useful!

- In this talk, we will see how monotonicity gives us
  - our **motivating example** and **monotonic counters**
  - **typed references** (`ref t`) and **untyped references** (`uref`)
  - more flexibility with **monotonic references** (`mref t rel`)
- See our POPL 2018 paper for more
  - temporarily **violating monotonicity** via snapshots
  - two substantial case studies in  $F^*$ 
    - a **secure file-transfer** application
    - Ariadne **state continuity** protocol [Strackx, Piessens 2016]
  - pointers to other works in  $F^*$  relying on monotonicity for
    - sophisticated **region-based memory models** [fstar-lang.org]
    - **crypto** and **TLS verification** [project-everest.github.io]

# Monotonicity is really useful!

- In this talk, we will see how monotonicity gives us
  - our **motivating example** and **monotonic counters**
  - **typed references** (`ref t`) and **untyped references** (`uref`)
  - more flexibility with **monotonic references** (`mref t rel`)
- See our POPL 2018 paper for more
  - temporarily **violating monotonicity** via snapshots
  - two substantial case studies in  $F^*$ 
    - a **secure file-transfer** application
    - Ariadne **state continuity** protocol [Strackx, Piessens 2016]
  - pointers to other works in  $F^*$  relying on monotonicity for
    - sophisticated **region-based memory models** [fstar-lang.org]
    - **crypto** and **TLS verification** [project-everest.github.io]

# Monotonicity is really useful!

- In this talk, we will see how monotonicity gives us
  - our **motivating example** and **monotonic counters**
  - **typed references** (`ref t`) and **untyped references** (`uref`)
  - more flexibility with **monotonic references** (`mref t rel`)
- See our POPL 2018 paper for more
  - temporarily **violating monotonicity** via snapshots
  - two substantial case studies in  $F^*$ 
    - a **secure file-transfer** application
    - Ariadne **state continuity** protocol [Strackx, Piessens 2016]
  - pointers to other works in  $F^*$  relying on monotonicity for
    - sophisticated **region-based memory models** [fstar-lang.org]
    - **crypto** and **TLS verification** [project-everest.github.io]

# Outline

- \*  $F^*$  overview
- Monotonic state by example
- Key ideas behind our general extension to Hoare-style logics
- Accommodating monotonic state in  $F^*$
- Some examples of monotonic state at work
- Glimpse of meta-theory and correctness results
- More examples of monotonic state at work (see our paper)
- Monadic reification and reflection (see our paper)

# Key ideas behind our general framework

- Based on **monotonic programs** and **stable predicates**
  - per verification task, we **choose a preorder  $\text{rel}$**  on states
    - set inclusion, heap inclusion, increasing counter values, ...
  - a stateful program  $e$  is **monotonic** (wrt.  $\text{rel}$ ) when
$$\forall s e' s'. (e, s) \rightsquigarrow^* (e', s') \implies \text{rel } s s'$$
  - a stateful predicate  $p$  is **stable** (wrt.  $\text{rel}$ ) when
$$\forall s s'. p \ s \wedge \text{rel } s s' \implies p \ s'$$
- **Our solution:** extend Hoare-style program logics (e.g.,  $F^*$ ) with
  - $a$  means to **witness** the validity of  $p \ s$  in some state  $s$
  - $a$  means for turning a  $p$  into a **state-independent proposition**
  - $a$  means to **recall** the validity of  $p \ s'$  in any future state  $s'$
- Provides a **unifying account** of the existing *ad hoc* uses in  $F^*$



# Key ideas behind our general framework

- Based on **monotonic programs** and **stable predicates**
  - per verification task, we **choose a preorder** **rel** on states
    - set inclusion, heap inclusion, increasing counter values, ...
  - a stateful program  $e$  is **monotonic** (wrt. **rel**) when
$$\forall s e' s'. (e, s) \rightsquigarrow^* (e', s') \implies \text{rel } s \ s'$$
  - a stateful predicate  $p$  is **stable** (wrt. **rel**) when
$$\forall s s'. p \ s \wedge \text{rel } s \ s' \implies p \ s'$$
- **Our solution:** extend Hoare-style program logics (e.g.,  $F^*$ ) with
  - $a$  means to **witness** the validity of  $p \ s$  in some state  $s$
  - $a$  means for turning a  $p$  into a **state-independent proposition**
  - $a$  means to **recall** the validity of  $p \ s'$  in any future state  $s'$
- Provides a **unifying account** of the existing *ad hoc* uses in  $F^*$

# Key ideas behind our general framework

- Based on **monotonic programs** and **stable predicates**
  - per verification task, we **choose a preorder  $\text{rel}$**  on states
    - set inclusion, heap inclusion, increasing counter values, ...
  - a stateful program  $e$  is **monotonic** (wrt.  $\text{rel}$ ) when
$$\forall s e' s'. (e, s) \rightsquigarrow^* (e', s') \implies \text{rel } s s'$$
  - a stateful predicate  $p$  is **stable** (wrt.  $\text{rel}$ ) when
$$\forall s s'. p \ s \wedge \text{rel } s s' \implies p \ s'$$
- **Our solution:** extend Hoare-style program logics (e.g.,  $F^*$ ) with
  - $a$  means to **witness** the validity of  $p \ s$  in some state  $s$
  - $a$  means for turning a  $p$  into a **state-independent proposition**
  - $a$  means to **recall** the validity of  $p \ s'$  in any future state  $s'$
- Provides a **unifying account** of the existing *ad hoc* uses in  $F^*$

# Key ideas behind our general framework

- Based on **monotonic programs** and **stable predicates**
  - per verification task, we **choose a preorder** **rel** on states
    - set inclusion, heap inclusion, increasing counter values, ...

- a stateful program  $e$  is **monotonic** (wrt. **rel**) when

$$\forall s e' s'. (e, s) \rightsquigarrow^* (e', s') \implies \text{rel } s s'$$

- a stateful predicate  $p$  is **stable** (wrt. **rel**) when

$$\forall s s'. p s \wedge \text{rel } s s' \implies p s'$$

- **Our solution:** extend Hoare-style program logics (e.g.,  $F^*$ ) with
  - $a$  means to **witness** the validity of  $p s$  in some state  $s$
  - $a$  means for turning a  $p$  into a **state-independent proposition**
  - $a$  means to **recall** the validity of  $p s'$  in any future state  $s'$
- Provides a **unifying account** of the existing *ad hoc* uses in  $F^*$

# Key ideas behind our general framework

- Based on **monotonic programs** and **stable predicates**
  - per verification task, we **choose a preorder** **rel** on states
    - set inclusion, heap inclusion, increasing counter values, ...

- a stateful program  $e$  is **monotonic** (wrt. **rel**) when

$$\forall s e' s'. (e, s) \rightsquigarrow^* (e', s') \implies \text{rel } s s'$$

- a stateful predicate  $p$  is **stable** (wrt. **rel**) when

$$\forall s s'. p \ s \wedge \text{rel } s s' \implies p \ s'$$

- **Our solution:** extend Hoare-style program logics (e.g.,  $F^*$ ) with
  - $a$  means to **witness** the validity of  $p \ s$  in some state  $s$
  - $a$  means for turning a  $p$  into a **state-independent proposition**
  - $a$  means to **recall** the validity of  $p \ s'$  in any future state  $s'$
- Provides a **unifying account** of the existing *ad hoc* uses in  $F^*$

# Key ideas behind our general framework

- Based on **monotonic programs** and **stable predicates**
  - per verification task, we **choose a preorder** **rel** on states
    - set inclusion, heap inclusion, increasing counter values, ...
  - a stateful program  $e$  is **monotonic** (wrt. **rel**) when
$$\forall s e' s'. (e, s) \rightsquigarrow^* (e', s') \implies \text{rel } s s'$$
  - a stateful predicate  $p$  is **stable** (wrt. **rel**) when
$$\forall s s'. p \ s \wedge \text{rel } s s' \implies p \ s'$$
- **Our solution:** extend Hoare-style program logics (e.g.,  $F^*$ ) with
  - a means to **witness** the validity of  $p \ s$  in some state  $s$
  - a means for turning a  $p$  into a **state-independent proposition**
  - a means to **recall** the validity of  $p \ s'$  in any future state  $s'$
- Provides a **unifying account** of the existing *ad hoc* uses in  $F^*$

# Key ideas behind our general framework

- Based on **monotonic programs** and **stable predicates**
  - per verification task, we **choose a preorder** **rel** on states
    - set inclusion, heap inclusion, increasing counter values, ...
  - a stateful program  $e$  is **monotonic** (wrt. **rel**) when
$$\forall s e' s'. (e, s) \rightsquigarrow^* (e', s') \implies \text{rel } s s'$$
  - a stateful predicate  $p$  is **stable** (wrt. **rel**) when
$$\forall s s'. p \ s \wedge \text{rel } s s' \implies p \ s'$$
- **Our solution:** extend Hoare-style program logics (e.g.,  $F^*$ ) with
  - a means to **witness** the validity of  $p \ s$  in some state  $s$
  - a means for turning a  $p$  into a **state-independent proposition**
  - a means to **recall** the validity of  $p \ s'$  in any future state  $s'$
- Provides a **unifying account** of the existing *ad hoc* uses in  $F^*$

# Outline

- \*  $F^*$  overview
- Monotonic state by example
- Key ideas behind our general extension to Hoare-style logics
- Accommodating monotonic state in  $F^*$
- Some examples of monotonic state at work
- Glimpse of meta-theory and correctness results
- More examples of monotonic state at work (see our paper)
- Monadic reification and reflection (see our paper)

# Recap: Ordinary global state in F\*

- F\* supports Hoare-style reasoning about state via the **comp. type**

$ST \#state\ t\ (\text{requires}\ pre)\ (\text{ensures}\ post)$

where

$pre : state \rightarrow Type$        $post : state \rightarrow t \rightarrow state \rightarrow Type$

- ST is an abstract pre-postcondition refinement of

$st\ t \stackrel{\text{def}}{=} state \rightarrow t * state$

- The global state **actions** have types

$get : unit \rightarrow ST\ state\ (\text{requires}\ (\lambda \_ . \top))\ (\text{ensures}\ (\lambda s_0\ s\ s_1 . s_0 = s = s_1))$

$put : s : state \rightarrow ST\ unit\ (\text{requires}\ (\lambda \_ . \top))\ (\text{ensures}\ (\lambda \_ \_ s_1 . s_1 = s))$

- Refs.** and **local state** are defined in F\* using **monotonicity**



# Recap: Ordinary global state in F\*

- F\* supports Hoare-style reasoning about state via the **comp. type**

$ST \#_{\text{state}} t \text{ (requires pre) (ensures post)}$

where

$\text{pre} : \text{state} \rightarrow \text{Type} \quad \text{post} : \text{state} \rightarrow t \rightarrow \text{state} \rightarrow \text{Type}$

- ST is an abstract pre-postcondition refinement of

$\text{st } t \stackrel{\text{def}}{=} \text{state} \rightarrow t * \text{state}$

- The global state **actions** have types

$\text{get} : \text{unit} \rightarrow ST \text{ state (requires } (\lambda \_ . \top) \text{) (ensures } (\lambda s_0 \ s \ s_1 . s_0 = s = s_1))$

$\text{put} : s : \text{state} \rightarrow ST \text{ unit (requires } (\lambda \_ . \top) \text{) (ensures } (\lambda \_ \ s_1 . s_1 = s))$

- Refs. and local state are defined in F\* using **monotonicity**

# Recap: Ordinary global state in F\*

- F\* supports Hoare-style reasoning about state via the **comp. type**

$$ST \#_{state} t \text{ (requires pre) (ensures post)}$$

where

$$\text{pre} : state \rightarrow Type \quad \text{post} : state \rightarrow t \rightarrow state \rightarrow Type$$

- ST is an abstract pre-postcondition refinement of

$$st\ t \stackrel{\text{def}}{=} state \rightarrow t * state$$

- The global state **actions** have types

$$\text{get} : unit \rightarrow ST\ state \text{ (requires } (\lambda \_ . \top) \text{) (ensures } (\lambda s_0\ s\ s_1 . s_0 = s = s_1) \text{)}$$
$$\text{put} : s : state \rightarrow ST\ unit \text{ (requires } (\lambda \_ . \top) \text{) (ensures } (\lambda \_ \_ s_1 . s_1 = s) \text{)}$$

- Refs. and local state are defined in F\* using monotonicity

# Recap: Ordinary global state in F\*

- F\* supports Hoare-style reasoning about state via the **comp. type**

$$ST \#_{state} t \text{ (requires pre) (ensures post)}$$

where

$$pre : state \rightarrow Type \qquad post : state \rightarrow t \rightarrow state \rightarrow Type$$

- ST is an abstract pre-postcondition refinement of

$$st\ t \stackrel{def}{=} state \rightarrow t * state$$

- The global state **actions** have types

$$get : unit \rightarrow ST\ state \text{ (requires } (\lambda \_ . \top) \text{) (ensures } (\lambda s_0\ s\ s_1 . s_0 = s = s_1) \text{)}$$
$$put : s : state \rightarrow ST\ unit \text{ (requires } (\lambda \_ . \top) \text{) (ensures } (\lambda \_ \_ s_1 . s_1 = s) \text{)}$$

- Refs.** and **local state** are defined in F\* using **monotonicity**

## New: Monotonic global state in $F^*$

# New: Monotonic global state in F\*

- We capture monotonic state with a new **computational type**

`MST #state #rel t (requires pre) (ensures post)`

- The `get` action is typed as in ST

`get : unit → MST state (requires (λ_.T))  
(ensures (λ s0 s s1 . s0 = s = s1))`

- To ensure **monotonicity**, the `put` action gets a precondition

`put : s:state → MST unit (requires (λ s0 . rel s0 s))  
(ensures (λ _ s1 . s1 = s))`

- So intuitively, MST is an **abstract** pre-postcondition refinement of

$\text{mst } t \stackrel{\text{def}}{=} s_0:\text{state} \rightarrow t * s_1:\text{state} \{ \text{rel } s_0 \ s_1 \}$

## New: Monotonic global state in $F^*$

- We capture monotonic state with a new **computational type**

MST #state #rel t (requires pre) (ensures post)

- The **get** action is typed as in **ST**

$$\text{get} : \text{unit} \rightarrow \text{MST state} \left( \text{requires } (\lambda \_ . \top) \right) \\ \left( \text{ensures } (\lambda s_0 \ s \ s_1 . s_0 = s = s_1) \right)$$

# New: Monotonic global state in F\*

- We capture monotonic state with a new **computational type**

`MST #state #rel t (requires pre) (ensures post)`

- The **get** action is typed as in `ST`

`get : unit → MST state (requires (λ_.T))  
(ensures (λ s0 s s1 . s0 = s = s1))`

- To ensure **monotonicity**, the **put** action gets a precondition

`put : s:state → MST unit (requires (λ s0 . rel s0 s))  
(ensures (λ _ _ s1 . s1 = s))`

- So intuitively, `MST` is an **abstract** pre-postcondition refinement of

`mst t  $\stackrel{\text{def}}{=} s_0:\text{state} \rightarrow t * s_1:\text{state} \{ \text{rel } s_0 s_1 \}$`

## New: Monotonic global state in $F^*$

- We capture monotonic state with a new **computational type**

MST #state **#red** t (requires pre) (ensures post)

- The **get** action is typed as in **ST**

$$\text{get} : \text{unit} \rightarrow \text{MST state} \left( \text{requires } (\lambda \_ . \top) \right) \\ \left( \text{ensures } (\lambda s_0 \ s \ s_1 . s_0 = s = s_1) \right)$$

- To ensure **monotonicity**, the **put** action gets a precondition

$$\text{put} : \text{s:state} \rightarrow \text{MST unit } (\text{requires } (\lambda s_0. \text{rel } s_0 \text{ s})) \\ (\text{ensures } (\lambda \_ s_1. s_1 = \text{s}))$$

- So intuitively, **MST** is an **abstract** pre-postcondition refinement of

$$\text{mst } t \stackrel{\text{def}}{=} s_0:\text{state} \rightarrow t * s_1:\text{state} \{\text{rel } s_0 \ s_1\}$$



# New: Recalling a Witness

- We extend  $F^*$  with a **logical capability**

$\text{witnessed} : (\text{state} \rightarrow \text{Type}) \rightarrow \text{Type}$

together with a **weakening principle** (functoriality)

$\text{wk} : p, q : (\text{state} \rightarrow \text{Type}) \rightarrow \text{Lemma} (\text{requires } (\forall s. p\ s \implies q\ s))$   
 $(\text{ensures } (\text{witnessed } p \implies \text{witnessed } q))$

- Intuitively, think of it as a **necessity modality**

$$\begin{aligned} \llbracket \text{witnessed } p \rrbracket (s) &\stackrel{\text{def}}{=} p \text{ 'stable\_from' } s \\ &\stackrel{\text{def}}{=} \forall s'. \text{rel } s\ s' \implies \llbracket p\ s' \rrbracket (s) \end{aligned}$$

- As usual, for natural deduction, need **world-indexed sequents**
- But, wait a minute ...

# New: Recalling a Witness

- We extend  $F^*$  with a **logical capability**

$\text{witnessed} : (\text{state} \rightarrow \text{Type}) \rightarrow \text{Type}$

together with a **weakening principle (functoriality)**

$\text{wk} : p, q : (\text{state} \rightarrow \text{Type}) \rightarrow \text{Lemma } (\text{requires } (\forall s. p\ s \implies q\ s))$   
 $(\text{ensures } (\text{witnessed } p \implies \text{witnessed } q))$

- Intuitively, think of it as a **necessity modality**

$$\begin{aligned} \llbracket \text{witnessed } p \rrbracket(s) &\stackrel{\text{def}}{=} p \text{ 'stable\_from' } s \\ &\stackrel{\text{def}}{=} \forall s'. \text{rel } s\ s' \implies \llbracket p\ s' \rrbracket(s) \end{aligned}$$

- As usual, for natural deduction, need **world-indexed sequents**
- But, wait a minute ...

# New: Recalling a Witness

- We extend  $F^*$  with a **logical capability**

$\text{witnessed} : (\text{state} \rightarrow \text{Type}) \rightarrow \text{Type}$

together with a **weakening principle (functoriality)**

$\text{wk} : p, q : (\text{state} \rightarrow \text{Type}) \rightarrow \text{Lemma } (\text{requires } (\forall s. p\ s \implies q\ s))$   
 $(\text{ensures } (\text{witnessed } p \implies \text{witnessed } q))$

- Intuitively, think of it as a **necessity modality**

$$\begin{aligned} \llbracket \text{witnessed } p \rrbracket(s) &\stackrel{\text{def}}{=} p \text{ 'stable\_from' } s \\ &\stackrel{\text{def}}{=} \forall s'. \text{rel } s\ s' \implies \llbracket p\ s' \rrbracket(s) \end{aligned}$$

- As usual, for natural deduction, need **world-indexed sequents**
- But, wait a minute ...

# New: Recalling a Witness

- We extend  $F^*$  with a **logical capability**

$$\text{witnessed} : (\text{state} \rightarrow \text{Type}) \rightarrow \text{Type}$$

together with a **weakening principle (functoriality)**

$$\text{wk} : p, q : (\text{state} \rightarrow \text{Type}) \rightarrow \text{Lemma} \left( \text{requires } (\forall s. p \ s \implies q \ s) \right) \\ \left( \text{ensures } (\text{witnessed } p \implies \text{witnessed } q) \right)$$

- Intuitively, think of it as a **necessity modality**

$$\llbracket \text{witnessed } p \rrbracket(s) \stackrel{\text{def}}{=} p \text{ 'stable\_from' } s \\ \stackrel{\text{def}}{=} \forall s'. \text{rel } s \ s' \implies \llbracket p \ s' \rrbracket(s)$$

- As usual, for natural deduction, need **world-indexed sequents**
- But, wait a minute ...

# New: Recalling a Witness

- We extend  $F^*$  with a **logical capability**

$$\text{witnessed} : (\text{state} \rightarrow \text{Type}) \rightarrow \text{Type}$$

together with a **weakening principle (functoriality)**

$$\text{wk} : p, q : (\text{state} \rightarrow \text{Type}) \rightarrow \text{Lemma} \left( \text{requires } (\forall s. p \ s \implies q \ s) \right) \\ \left( \text{ensures } (\text{witnessed } p \implies \text{witnessed } q) \right)$$

- Intuitively, think of it as a **necessity modality**

$$\llbracket \text{witnessed } p \rrbracket(s) \stackrel{\text{def}}{=} p \text{ 'stable\_from' } s \\ \stackrel{\text{def}}{=} \forall s'. \text{rel } s \ s' \implies \llbracket p \ s' \rrbracket(s)$$

- As usual, for natural deduction, need **world-indexed sequents**
- But, wait a minute ...

# New: Recalling a Witness

- ... Hoare-style logics are essentially **world/state-indexed**, so
- we include a **stateful introduction rule** for witnessed

```
witness : p:(state  $\rightarrow$  Type0)  
          $\rightarrow$  MST unit (requires ( $\lambda s_0. p$  'stable_from'  $s_0$ ))  
                   (ensures ( $\lambda s_0 - s_1. s_0 = s_1 \wedge$  witnessed  $p$ )))
```

- and a **stateful elimination rule** for witnessed

```
recall : p:(state  $\rightarrow$  Type0)  
         $\rightarrow$  MST unit (requires ( $\lambda \_.$  witnessed  $p$ ))  
                  (ensures ( $\lambda s_0 - s_1. s_0 = s_1 \wedge p$  'stable_from'  $s_1$ )))
```

# New: Recalling a Witness

- ... Hoare-style logics are essentially **world/state-indexed**, so
- we include a **stateful introduction rule** for witnessed

```
witness : p:(state  $\rightarrow$  Type0)  
          $\rightarrow$  MST unit (requires ( $\lambda s_0.$  p 'stable_from' s0))  
                   (ensures ( $\lambda s_0 - s_1. s_0 = s_1 \wedge$  witnessed p))
```

- and a **stateful elimination rule** for witnessed

```
recall : p:(state  $\rightarrow$  Type0)  
         $\rightarrow$  MST unit (requires ( $\lambda ..$  witnessed p))  
                  (ensures ( $\lambda s_0 - s_1. s_0 = s_1 \wedge$  p 'stable_from' s1))
```

# New: Recalling a Witness

- ... Hoare-style logics are essentially **world/state-indexed**, so
- we include a **stateful introduction rule** for witnessed

```
witness : p:(state → Type0)  
        → MST unit (requires (λ s0. p 'stable_from' s0))  
                   (ensures (λ s0 - s1. s0 = s1 ∧ witnessed p))
```

- and a **stateful elimination rule** for witnessed

```
recall : p:(state → Type0)  
        → MST unit (requires (λ -. witnessed p))  
                   (ensures (λ s0 - s1. s0 = s1 ∧ p 'stable_from' s1))
```



# Outline

- \*  $F^*$  overview
- Monotonic state by example
- Key ideas behind our general extension to Hoare-style logics
- Accommodating monotonic state in  $F^*$
- Some examples of monotonic state at work
- Glimpse of meta-theory and correctness results
- More examples of monotonic state at work (see our paper)
- Monadic reification and reflection (see our paper)

# The motivating example revisited

- Recall the program operating on the **set-valued state**

```
insert v; complex_procedure(); assert (v ∈ get())
```

- We pick **set inclusion**  $\subseteq$  as our preorder rel on states
- We **prove the assertion** by inserting a witness and recall

```
insert v; witness ( $\lambda s. v \in s$ ); c_p(); recall ( $\lambda s. v \in s$ ); assert (v ∈ get())
```

- For any other w, wrapping

```
insert w; [ ]; assert (w ∈ get())
```

around the program is handled **similarly easily** by

```
insert w; witness ( $\lambda s. w \in s$ ); [ ]; recall ( $\lambda s. w \in s$ ); assert (w ∈ get())
```

- Monotonic counters** are analogous, by picking  $\mathbb{N}$  and  $\leq$ , e.g.,  

```
create 0; incr(); witness ( $\lambda c. c > 0$ ); c_p(); recall ( $\lambda c. c > 0$ )
```

# The motivating example revisited

- Recall the program operating on the **set-valued state**

```
insert v; complex_procedure(); assert (v ∈ get())
```

- We pick **set inclusion**  $\subseteq$  as our preorder rel on states
- We **prove the assertion** by inserting a witness and recall

```
insert v; witness ( $\lambda s. v \in s$ ); c_p(); recall ( $\lambda s. v \in s$ ); assert (v ∈ get())
```

- For any other w, wrapping

```
insert w; [ ]; assert (w ∈ get())
```

around the program is handled **similarly easily** by

```
insert w; witness ( $\lambda s. w \in s$ ); [ ]; recall ( $\lambda s. w \in s$ ); assert (w ∈ get())
```

- Monotonic counters** are analogous, by picking  $\mathbb{N}$  and  $\leq$ , e.g.,  

```
create 0; incr(); witness ( $\lambda c. c > 0$ ); c_p(); recall ( $\lambda c. c > 0$ )
```

# The motivating example revisited

- Recall the program operating on the **set-valued state**

```
insert v; complex_procedure(); assert (v ∈ get())
```

- We pick **set inclusion**  $\subseteq$  as our preorder rel on states
- We **prove the assertion** by inserting a witness and recall

```
insert v; witness ( $\lambda s. v \in s$ ); c_p(); recall ( $\lambda s. v \in s$ ); assert (v ∈ get())
```

- For any other w, wrapping

```
insert w; [ ]; assert (w ∈ get())
```

around the program is handled **similarly easily** by

```
insert w; witness ( $\lambda s. w \in s$ ); [ ]; recall ( $\lambda s. w \in s$ ); assert (w ∈ get())
```

- Monotonic counters** are analogous, by picking  $\mathbb{N}$  and  $\leq$ , e.g.,  

```
create 0; incr(); witness ( $\lambda c. c > 0$ ); c_p(); recall ( $\lambda c. c > 0$ )
```

# The motivating example revisited

- Recall the program operating on the **set-valued state**

```
insert v; complex_procedure(); assert (v ∈ get())
```

- We pick **set inclusion**  $\subseteq$  as our preorder  $\text{rel}$  on states
- We **prove the assertion** by inserting a witness and recall

```
insert v; witness ( $\lambda s. v \in s$ ); c_p(); recall ( $\lambda s. v \in s$ ); assert (v ∈ get())
```

- For **any other**  $w$ , wrapping

```
insert w; [ ]; assert (w ∈ get())
```

around the program is handled **similarly easily** by

```
insert w; witness ( $\lambda s. w \in s$ ); [ ]; recall ( $\lambda s. w \in s$ ); assert (w ∈ get())
```

- Monotonic counters are analogous, by picking  $\mathbb{N}$  and  $\leq$ , e.g.,  

```
create 0; incr(); witness ( $\lambda c. c > 0$ ); c_p(); recall ( $\lambda c. c > 0$ )
```

# The motivating example revisited

- Recall the program operating on the **set-valued state**

```
insert v; complex_procedure(); assert (v ∈ get())
```

- We pick **set inclusion**  $\subseteq$  as our preorder  $\text{rel}$  on states
- We **prove the assertion** by inserting a witness and recall

```
insert v; witness ( $\lambda s. v \in s$ ); c_p(); recall ( $\lambda s. v \in s$ ); assert (v ∈ get())
```

- For **any other**  $w$ , wrapping

```
insert w; [ ]; assert (w ∈ get())
```

around the program is handled **similarly easily** by

```
insert w; witness ( $\lambda s. w \in s$ ); [ ]; recall ( $\lambda s. w \in s$ ); assert (w ∈ get())
```

- Monotonic counters** are analogous, by picking  $\mathbb{N}$  and  $\leq$ , e.g.,  

```
create 0; incr(); witness ( $\lambda c. c > 0$ ); c_p(); recall ( $\lambda c. c > 0$ )
```

# ML-style typed references (local state)

- First, we define a type of **heaps** as a finite map

```
type heap =
```

```
| H : h : (N → cell) → ctr : N { ∀ n. ctr ≤ n ⇒ h n = Unused } → heap
```

where

```
type cell =
```

```
| Unused : cell
```

```
| Used : a : Type → v : a → cell
```

- Next, we define a **preorder** on heaps (**heap inclusion**)

```
let heap_inclusion (H h0 _) (H h1 _) = ∀ id. match h0 id, h1 id with
```

```
| Used a _, Used b _ → a = b
```

```
| Unused, Used _ _ → ⊤
```

```
| Unused, Unused → ⊤
```

```
| Used _ _, Unused → ⊥
```

# ML-style typed references (local state)

- First, we define a type of **heaps** as a finite map

```
type heap =
```

```
| H : h:( $\mathbb{N} \rightarrow \text{cell}$ )  $\rightarrow$  ctr: $\mathbb{N}\{\forall n. \text{ctr} \leq n \implies h\ n = \text{Unused}\}$   $\rightarrow$  heap
```

where

```
type cell =
```

```
| Unused : cell
```

```
| Used : a:Type  $\rightarrow$  v:a  $\rightarrow$  cell
```

- Next, we define a preorder on heaps (**heap inclusion**)

```
let heap_inclusion (H h0 _) (H h1 _) =  $\forall \text{id}. \text{match } h_0\ \text{id}, h_1\ \text{id} \text{ with}$ 
```

```
| Used a _, Used b _  $\rightarrow$  a = b
```

```
| Unused, Used _ _  $\rightarrow$   $\top$ 
```

```
| Unused, Unused  $\rightarrow$   $\top$ 
```

```
| Used _ _, Unused  $\rightarrow$   $\perp$ 
```



# ML-style typed references (local state)

- First, we define a type of **heaps** as a finite map

`type heap =`

`| H : h:( $\mathbb{N} \rightarrow \text{cell}$ )  $\rightarrow$  ctr: $\mathbb{N}\{\forall n. \text{ctr} \leq n \implies h\ n = \text{Unused}\}$   $\rightarrow$  heap`

where

`type cell =`

`| Unused : cell`

`| Used : a:Type  $\rightarrow$  v:a  $\rightarrow$  cell`

- Next, we define a **preorder** on heaps (**heap inclusion**)

`let heap_inclusion (H h0 _) (H h1 _) =  $\forall \text{id}. \text{match } h_0\ \text{id}, h_1\ \text{id} \text{ with}$`

`| Used a _, Used b _  $\rightarrow$  a = b`

`| Unused, Used _ _  $\rightarrow$   $\top$`

`| Unused, Unused  $\rightarrow$   $\top$`

`| Used _ _, Unused  $\rightarrow$   $\perp$`

# ML-style typed references (local state)

- As a result, we can define new **local state effect**

$$\text{MLST } t \text{ pre post} \stackrel{\text{def}}{=} \text{MST } \# \text{heap } \# \text{heap\_inclusion } t \text{ pre post}$$

- Next, we define the type of **references** using monotonicity

```
abstract type ref a = id:N{witnessed ( $\lambda h$ . contains h id a)}
```

where

```
let contains (H h _) id a =  
  match h id with  
  | Used b _  $\rightarrow$  a = b  
  | Unused  $\rightarrow \perp$ 
```

- Important: contains is **stable** wrt. heap\_inclusion

# ML-style typed references (local state)

- As a result, we can define new **local state effect**

$$\text{MLST } t \text{ pre post} \stackrel{\text{def}}{=} \text{MST } \# \text{heap } \# \text{heap\_inclusion } t \text{ pre post}$$

- Next, we define the type of **references** using monotonicity

```
abstract type ref a = id:N{witnessed ( $\lambda h$ . contains h id a)}
```

where

```
let contains (H h _) id a =
```

```
  match h id with
```

```
    | Used b _ → a = b
```

```
    | Unused → ⊥
```

- Important: contains is **stable** wrt. heap\_inclusion

# ML-style typed references (local state)

- As a result, we can define new **local state effect**

$$\text{MLST } t \text{ pre post} \stackrel{\text{def}}{=} \text{MST } \# \text{heap } \# \text{heap\_inclusion } t \text{ pre post}$$

- Next, we define the type of **references** using monotonicity

`abstract type` `ref a = id:N{witnessed ( $\lambda h$ . contains h id a)}`

where

`let` `contains (H h _) id a =`

`match h id with`

`| Used b _  $\rightarrow$  a = b`

`| Unused  $\rightarrow \perp$`

- Important: `contains` is **stable** wrt. `heap_inclusion`

# ML-style typed references (local state)

- Finally, we define **MLST's actions** using **MST's actions**

- `let alloc (#a:Type) (v:a) : MLST (ref a) ... = ...`
  - get the current heap
  - create a fresh ref., and add it to the heap
  - put the updated heap back
  - witness that the created ref. is in the heap
- `let ! (r:ref a) : MLST a (req. ( $\top$ )) (ens. (...)) = ...`
  - recall that the given ref. is in the heap
  - get the current heap
  - select the given reference from the heap
- `let := (r:ref a) (v:a) : MLST unit ... = ...`
  - recall that the given ref. is in the heap
  - get the current heap
  - update the heap with the given value at the given ref.
  - put the updated heap back

# ML-style typed references (local state)

- Finally, we define **MLST**'s **actions** using **MST**'s actions
  - **let alloc** ( $\#a:\text{Type}$ ) ( $v:a$ ) : **MLST** (ref a) ... = ...
    - **get** the current heap
    - **create** a fresh ref., and **add** it to the heap
    - **put** the updated heap back
    - **witness** that the created ref. is in the heap
  - **let !** ( $r:\text{ref } a$ ) : **MLST** a (**req.** ( $\top$ )) (**ens.** (...)) = ...
    - **recall** that the given ref. is in the heap
    - **get** the current heap
    - **select** the given reference from the heap
  - **let :=** ( $r:\text{ref } a$ ) ( $v:a$ ) : **MLST** unit ... = ...
    - **recall** that the given ref. is in the heap
    - **get** the current heap
    - **update** the heap with the given value at the given ref.
    - **put** the updated heap back

# ML-style typed references (local state)

- Finally, we define **MLST**'s **actions** using **MST**'s actions
  - **let alloc** ( $\#a:\text{Type}$ ) ( $v:a$ ) : **MLST** (ref a) ... = ...
    - **get** the current heap
    - **create** a fresh ref., and **add** it to the heap
    - **put** the updated heap back
    - **witness** that the created ref. is in the heap
  - **let !** ( $r:\text{ref a}$ ) : **MLST** a (**req.** ( $\top$ )) (**ens.** (...)) = ...
    - **recall** that the given ref. is in the heap
    - **get** the current heap
    - **select** the given reference from the heap
  - **let :=** ( $r:\text{ref a}$ ) ( $v:a$ ) : **MLST** unit ... = ...
    - **recall** that the given ref. is in the heap
    - **get** the current heap
    - **update** the heap with the given value at the given ref.
    - **put** the updated heap back

# ML-style typed references (local state)

- Finally, we define **MLST**'s **actions** using **MST**'s actions
  - **let alloc** ( $\#a:\text{Type}$ ) ( $v:a$ ) : **MLST** (ref a) ... = ...
    - **get** the current heap
    - **create** a fresh ref., and **add** it to the heap
    - **put** the updated heap back
    - **witness** that the created ref. is in the heap
  - **let !** ( $r:\text{ref } a$ ) : **MLST** a (**req.** ( $\top$ )) (**ens.** (...)) = ...
    - **recall** that the given ref. is in the heap
    - **get** the current heap
    - **select** the given reference from the heap
  - **let :=** ( $r:\text{ref } a$ ) ( $v:a$ ) : **MLST** unit ... = ...
    - **recall** that the given ref. is in the heap
    - **get** the current heap
    - **update** the heap with the given value at the given ref.
    - **put** the updated heap back



# Adding untyped and monotonic references

- Untyped references (`uref`) with strong updates

- Used heap cells are extended with **tags**

where 
$$| \text{Used} : a:\text{Type} \rightarrow v:a \rightarrow \text{t:tag} \rightarrow \text{cell}$$

$$\text{type tag} = \text{Typed} : \text{tag} \mid \text{Untyped} : \text{tag}$$

- actions corresponding to urefs have **weaker types** than for refs

- Monotonic references (`mref a rel`)

- Used heap cells are extended with **typed tags**

where 
$$| \text{Used} : a:\text{Type} \rightarrow v:a \rightarrow \text{t:tag } a \rightarrow \text{cell}$$

$$\text{type tag } a = \text{Typed} : \text{rel:preorder } a \rightarrow \text{tag } a \mid \text{Untyped} : \text{tag } a$$

- `mrefs` provide **more flexibility** with ref.-wise monotonicity
- Further, all three can be extended with **manually managed** refs.

# Adding untyped and monotonic references

- **Untyped references** (`uref`) with strong updates

- Used heap cells are extended with **tags**

|  $\text{Used} : a:\text{Type} \rightarrow v:a \rightarrow \text{t:tag} \rightarrow \text{cell}$

where

`type tag` = `Typed : tag` | `Untyped : tag`

- actions corresponding to urefs have **weaker types** than for refs

- **Monotonic references** (`mref a rel`)

- Used heap cells are extended with **typed tags**

|  $\text{Used} : a:\text{Type} \rightarrow v:a \rightarrow \text{t:tag } a \rightarrow \text{cell}$

where

`type tag a` = `Typed : rel:preorder a  $\rightarrow$  tag a` | `Untyped : tag a`

- `mrefs` provide **more flexibility** with ref.-wise monotonicity

- Further, all three can be extended with **manually managed** refs.

# Adding untyped and monotonic references

- **Untyped references** (`uref`) with strong updates

- Used heap cells are extended with **tags**

where 
$$| \text{Used} : a:\text{Type} \rightarrow v:a \rightarrow \text{t:tag} \rightarrow \text{cell}$$

$$\text{type tag} = \text{Typed} : \text{tag} \mid \text{Untyped} : \text{tag}$$

- actions corresponding to urefs have **weaker types** than for refs

- **Monotonic references** (`mref a rel`)

- Used heap cells are extended with **typed tags**

where 
$$| \text{Used} : a:\text{Type} \rightarrow v:a \rightarrow \text{t:tag } a \rightarrow \text{cell}$$

$$\text{type tag } a = \text{Typed} : \text{rel:preorder } a \rightarrow \text{tag } a \mid \text{Untyped} : \text{tag } a$$

- mrefs provide **more flexibility** with ref.-wise monotonicity

- Further, all three can be extended with **manually managed** refs.

# Adding untyped and monotonic references

- **Untyped references** (`uref`) with strong updates

- Used heap cells are extended with **tags**

where 
$$| \text{Used} : a:\text{Type} \rightarrow v:a \rightarrow \text{t:tag} \rightarrow \text{cell}$$

$$\text{type tag} = \text{Typed} : \text{tag} \mid \text{Untyped} : \text{tag}$$

- actions corresponding to urefs have **weaker types** than for refs

- **Monotonic references** (`mref a rel`)

- Used heap cells are extended with **typed tags**

where 
$$| \text{Used} : a:\text{Type} \rightarrow v:a \rightarrow \text{t:tag } a \rightarrow \text{cell}$$

$$\text{type tag } a = \text{Typed} : \text{rel:preorder } a \rightarrow \text{tag } a \mid \text{Untyped} : \text{tag } a$$

- `mrefs` provide **more flexibility** with ref.-wise monotonicity
- Further, all three can be extended with **manually managed** refs.

# Outline

- \*  $F^*$  overview
- Monotonic state by example
- Key ideas behind our general extension to Hoare-style logics
- Accommodating monotonic state in  $F^*$
- Some examples of monotonic state at work
- Glimpse of meta-theory and correctness results
- More examples of monotonic state at work (see our paper)
- Monadic reification and reflection (see our paper)

# Glimpse of meta-theory

- A small **dependently typed**  $\lambda$ -calculus with **Tot** and **MST** effects
- **Logical consistency** shown via cut elimination

- Using an **instrumented operational semantics**, where

$$(\text{witness } p, s, W) \rightsquigarrow (\text{return } (), s, W \cup \{p\})$$
$$(\text{recall } p, s, W) \rightsquigarrow (\text{return } (), s, W)$$

- **Strong normalisation** shown via type-erasure and TT-lifting
- Hoare-style **total correctness** via SN, progress, and preservation

if  $\vdash e : \text{MST } t$  *pre post* and

$\vdash (s, W) \text{ wf}$  and witnessed  $W \vdash$  *pre s*

then  $(e, s, W) \rightsquigarrow^* (\text{return } v, s', W')$  and  $\vdash v : t$  and

witnessed  $W' \vdash$  *rel s s'* and  $W \subseteq W'$  and

witnessed  $W' \vdash$  *post s v s'*

# Glimpse of meta-theory

- A small **dependently typed**  $\lambda$ -calculus with **Tot** and **MST** effects
- **Logical consistency** shown via cut elimination

- Using an **instrumented operational semantics**, where

$$(\text{witness } p, s, W) \rightsquigarrow (\text{return } (), s, W \cup \{p\})$$
$$(\text{recall } p, s, W) \rightsquigarrow (\text{return } (), s, W)$$

- **Strong normalisation** shown via type-erasure and TT-lifting
- Hoare-style **total correctness** via SN, progress, and preservation

if  $\vdash e : \text{MST } t$  *pre post* and

$\vdash (s, W) \text{ wf}$  and witnessed  $W \vdash$  *pre s*

then  $(e, s, W) \rightsquigarrow^* (\text{return } v, s', W')$  and  $\vdash v : t$  and

witnessed  $W' \vdash$  *rel s s'* and  $W \subseteq W'$  and

witnessed  $W' \vdash$  *post s v s'*

# Glimpse of meta-theory

- A small **dependently typed**  $\lambda$ -calculus with **Tot** and **MST** effects
- **Logical consistency** shown via cut elimination
- Using an **instrumented operational semantics**, where

$$(\text{witness } p, s, W) \rightsquigarrow (\text{return } (), s, W \cup \{p\})$$

$$(\text{recall } p, s, W) \rightsquigarrow (\text{return } (), s, W)$$

- **Strong normalisation** shown via type-erasure and TT-lifting
- Hoare-style **total correctness** via SN, progress, and preservation

if  $\vdash e : \text{MST } t$  *pre post* and

$\vdash (s, W) \text{ wf}$  and witnessed  $W \vdash$  *pre s*

then  $(e, s, W) \rightsquigarrow^* (\text{return } v, s', W')$  and  $\vdash v : t$  and

witnessed  $W' \vdash$  *rel s s'* and  $W \subseteq W'$  and

witnessed  $W' \vdash$  *post s v s'*



# Glimpse of meta-theory

- A small **dependently typed**  $\lambda$ -calculus with **Tot** and **MST** effects
- **Logical consistency** shown via cut elimination
- Using an **instrumented operational semantics**, where

$$(\text{witness } p, s, W) \rightsquigarrow (\text{return } (), s, W \cup \{p\})$$

$$(\text{recall } p, s, W) \rightsquigarrow (\text{return } (), s, W)$$

- **Strong normalisation** shown via type-erasure and TT-lifting
- Hoare-style **total correctness** via SN, progress, and preservation

if  $\vdash e : \text{MST } t$  *pre post* and

$\vdash (s, W) \text{ wf}$  and witnessed  $W \vdash$  *pre s*

then  $(e, s, W) \rightsquigarrow^* (\text{return } v, s', W')$  and  $\vdash v : t$  and

witnessed  $W' \vdash$  *rel s s'* and  $W \subseteq W'$  and

witnessed  $W' \vdash$  *post s v s'*

# Glimpse of meta-theory

- A small **dependently typed**  $\lambda$ -calculus with **Tot** and **MST** effects
- **Logical consistency** shown via cut elimination
- Using an **instrumented operational semantics**, where

$$(\text{witness } p, s, W) \rightsquigarrow (\text{return } (), s, W \cup \{p\})$$

$$(\text{recall } p, s, W) \rightsquigarrow (\text{return } (), s, W)$$

- **Strong normalisation** shown via type-erasure and TT-lifting
- Hoare-style **total correctness** via SN, progress, and preservation

if  $\vdash e : \text{MST } t \text{ } \textit{pre post}$  and

$\vdash (s, W) \text{ wf}$  and witnessed  $W \vdash \textit{pre } s$

then  $(e, s, W) \rightsquigarrow^* (\text{return } v, s', W')$  and  $\vdash v : t$  and

witnessed  $W' \vdash \textit{rel } s \ s'$  and  $W \subseteq W'$  and

witnessed  $W' \vdash \textit{post } s \ v \ s'$

# Conclusion

- Monotonicity
  - can be distilled into a **simple** and **general** framework
  - is **useful** for **programming** (refs.) and **verification** (Prj. Everest)
- See our POPL 2018 paper for
  - further **examples** and **case studies**
  - details of **meta-theory** for [MST](#)
  - first steps towards **monadic reification** for [MST](#) (rel. reasoning)
- Ongoing: taking the **modality** aspect of witnessed seriously
  - to remove instrumentation from op. sem., and
  - to improve support for monadic reification

# Thank you for your attention!

## Questions?

D. Ahman, C. Fournet, C. Hrițcu, K. Maillard, A. Rastogi, N. Swamy.

**Recalling a Witness: Foundations and Applications of Monotonic State**

*Proc. ACM Program. Lang.*, volume 2, issue POPL, article 65, 2018.