

# Embracing monotonicity in



Danel Ahman @ INRIA Paris

(based on a joint POPL 2018 paper with)

Cătălin Hrițcu and Kenji Maillard @ INRIA Paris

Cédric Fournet, Aseem Rastogi, and Nikhil Swamy @ MSR

Software Science Departmental Seminar, TUT

February 12, 2018

# Outline

- \* F\* overview
- Monotonic state by example
- Key ideas behind our general extension to Hoare-style logics
- Accommodating monotonic state in F\*
- Some examples of monotonic state at work
- Glimpse of meta-theory and correctness results
- More examples of monotonic state at work (see our paper)
- Monadic reification and reflection (see our paper)

# Outline

- \*  $F^*$  overview
- Monotonic state by example
- Key ideas behind our general extension to Hoare-style logics
- Accommodating monotonic state in  $F^*$
- Some examples of monotonic state at work
- Glimpse of meta-theory and correctness results
- More examples of monotonic state at work (see our paper)
- Monadic reification and reflection (see our paper)

- **F\*** is
  - a **functional programming language**
    - ML, OCaml, F#, Haskell, ...
    - extracted to OCaml or F#; subset compiled to efficient C code
  - an **interactive proof assistant**
    - Agda, Coq, Lean, Isabelle/HOL, ...
    - interactive modes for Emacs and Atom
  - a **semi-automated verifier** of imperative programs
    - Dafny, Why3, FramaC, ...
    - Z3-based SMT-automation; tactics and metaprogramming (WIP)
- **Application-driven development**
  - Project Everest [project-everest.github.io]
  - Microsoft Research (US, UK, India), INRIA (Paris), ...
  - miTLS, HACl\*, Vale, ...

- **F\*** is
  - a **functional programming language**
    - ML, OCaml, F#, Haskell, ...
    - extracted to OCaml or F#; subset compiled to efficient C code
  - an **interactive proof assistant**
    - Agda, Coq, Lean, Isabelle/HOL, ...
    - interactive modes for Emacs and Atom
  - a **semi-automated verifier** of imperative programs
    - Dafny, Why3, FramaC, ...
    - Z3-based SMT-automation; tactics and metaprogramming (WIP)
- **Application-driven** development
  - Project Everest [project-everest.github.io]
  - Microsoft Research (US, UK, India), INRIA (Paris), ...
  - miTLS, HACL\*, Vale, ...

```

module Talk

// Dependent (inductive) types

type vector 'a : nat -> Type =
  | Nil : vector 'a 0
  | Cons : #n:nat -> 'a -> vector 'a n -> vector 'a (n + 1)

// Dependently typed (recursive, total) functions

val append : #a:Type -> #n:nat -> #m:nat -> vector a n -> vector a m -> Tot (vector a (n + m))
let rec append #a #n #m xs ys =
  match xs with
  | Nil -> ys
  | Cons #n x xs -> Cons x (append xs ys)

// Refinement types

let in_range_index (min:nat) (max:nat) = i:nat{min <= i /\ i <= max}

val lkp : #a:Type -> #n:nat -> vector a n -> in_range_index 1 n -> Tot a
let rec lkp #a #n xs i =
  match xs with
  | Cons x xs -> if i = 1 then x else lkp xs (i - 1)

// First-class predicates (for which Type0 behaves like (classical) Prop)

type is_prefix_of (#a:Type) (#n:nat) (#m:nat) (xs:vector a n) (zs:vector a m{n <= m}) : Type0 =
  forall (i:nat) . (1 <= i /\ i <= n) ==> lkp xs i == lkp zs i

// Extrinsic reasoning (using separate lemmas)

val lemma : #a:Type -> #n:nat -> #m:nat -> xs:vector a n -> ys:vector a m -> Lemma (requires (True))
  (ensures (xs `is_prefix_of` (append xs ys)))

let rec lemma #a #n #m xs ys =
  match xs with
  | Nil -> ()
  | Cons x xs -> lemma xs ys

// Intrinsic reasoning (making lemmas part of definitions)

val take : #a:Type -> #n:nat -> zs:vector a n -> m:nat -> Pure (vector a m) (requires (m <= n))
  (ensures (fun xs -> xs `is_prefix_of` zs))

let rec take #a #n zs m =
  if m > 0 then match zs with | Cons z zs -> let m' : nat = m - 1 in Cons z (take zs m')
  else Nil

```

# F\* – not just a pure programming language

- Tot, Lemma, Pure, ... are just some **effects** amongst many
  - Tot  $t$
  - Lemma (requires  $\text{pre}_{\text{Lemma}}$ ) (ensures  $\text{post}_{\text{Lemma}}$ )
  - Pure  $t$  (requires  $\text{pre}_{\text{Pure}}$ ) (ensures  $\text{post}_{\text{Pure}}$ )
  - Div  $t$  (requires  $\text{pre}_{\text{Div}}$ ) (ensures  $\text{post}_{\text{Div}}$ )
  - Exc  $t$  (requires  $\text{pre}_{\text{Exc}}$ ) (ensures  $\text{post}_{\text{Exc}}$ )
  - ST  $t$  (requires  $\text{pre}_{\text{ST}}$ ) (ensures  $\text{post}_{\text{ST}}$ )
  - ...
- **Monad morphs.**  $\text{Pure} \rightsquigarrow \{\text{Div}, \text{Exc}, \text{ST}\}; \text{Exc} \rightsquigarrow \text{STExc}; \dots$
- Systematically derived from **WP-calculi** (see POPL'17 paper)

# Outline

\*  $F^*$  overview

- Monotonic state by example
- Key ideas behind our general extension to Hoare-style logics
- Accommodating monotonic state in  $F^*$
- Some examples of monotonic state at work
- Glimpse of meta-theory and correctness results
- More examples of monotonic state at work (see our paper)
- Monadic reification and reflection (see our paper)



# Monotonicity in program verification

- Consider a program operating on **set-valued state**

```
insert v; complex_procedure(); assert (v ∈ get())
```

- To prove the assertion (say, in a Floyd-Hoare style logic), we could prove that the code maintains a **stateful invariant**

$$\{\lambda s.v \in s\} \text{ complex\_procedure() } \{\lambda s.v \in s\}$$

- likely that we have to **carry**  $\lambda s.v \in s$  **through** the proof of `c_p`
- does not guarantee** that  $\lambda s.v \in s$  holds at every point in `c_p`
- sensitive** to proving that `c_p` maintains  $\lambda s.w \in s$  for some `w`
- However, if `c_p` **never removes**, then  $\lambda s.v \in s$  is **stable**, and we would like the program logic to give us `v ∈ get()` “for free”

# Monotonicity in program verification

- Consider a program operating on **set-valued state**

insert v; complex\_procedure(); **assert** ( $v \in \text{get}()$ )

- To prove the assertion (say, in a Floyd-Hoare style logic), we could prove that the code maintains a **stateful invariant**

$\{\lambda s. v \in s\}$  complex\_procedure()  $\{\lambda s. v \in s\}$

- likely that we have to carry  $\lambda s. v \in s$  through the proof of c\_p
- does not guarantee that  $\lambda s. v \in s$  holds at every point in c\_p
- sensitive to proving that c\_p maintains  $\lambda s. w \in s$  for some w
- However, if c\_p never removes, then  $\lambda s. v \in s$  is stable, and we would like the program logic to give us  $v \in \text{get}()$  “for free”

# Monotonicity in program verification

- Consider a program operating on **set-valued state**

`insert v; complex_procedure(); assert (v ∈ get())`

- To prove the assertion (say, in a Floyd-Hoare style logic), we could prove that the code maintains a **stateful invariant**

$\{\lambda s.v \in s\}$  `complex_procedure()`  $\{\lambda s.v \in s\}$

- likely that we have to **carry**  $\lambda s.v \in s$  **through** the proof of `c_p`
- does not guarantee** that  $\lambda s.v \in s$  holds at every point in `c_p`
- sensitive** to proving that `c_p` maintains  $\lambda s.w \in s$  for some `w`
- However, if `c_p` **never removes**, then  $\lambda s.v \in s$  is **stable**, and we would like the program logic to give us `v ∈ get()` “for free”

# Monotonicity in program verification

- Consider a program operating on **set-valued state**

`insert v; complex_procedure(); assert (v ∈ get())`

- To prove the assertion (say, in a Floyd-Hoare style logic), we could prove that the code maintains a **stateful invariant**

$\{\lambda s.v \in s\}$  `complex_procedure()`  $\{\lambda s.v \in s\}$

- likely that we have to **carry**  $\lambda s.v \in s$  **through** the proof of `c_p`
- does not guarantee** that  $\lambda s.v \in s$  holds at every point in `c_p`
- sensitive** to proving that `c_p` maintains  $\lambda s.w \in s$  for some `w`
- However, if `c_p` **never removes**, then  $\lambda s.v \in s$  is **stable**, and we would like the program logic to give us  $v \in \text{get}()$  “for free”

# Monotonicity in programming

- **Programming** also relies on **monotonicity**, even if you don't realise it!
- Consider ML-style typed references  $r:\text{ref } a$ 
  - $r$  is a **proof of existence** of an  $a$ -typed value in the heap
- Correctness relies on **monotonicity**!
  - 1) Allocation **stores** an  $a$ -typed value in the heap
  - 2) Writes **don't change type** and there is **no deallocation**
  - 3) So, given a ref.  $r$ , it is **guaranteed to point** to an  $a$ -typed value
- Baked into the memory models of most languages
- We derive them from **global state** + **general monotonicity**

# Monotonicity in programming

- **Programming** also relies on **monotonicity**, even if you don't realise it!
- Consider ML-style typed **references**  $r:\text{ref } a$ 
  - $r$  is a **proof of existence** of an  $a$ -typed value in the heap
- Correctness relies on **monotonicity**!
  - 1) Allocation stores an  $a$ -typed value in the heap
  - 2) Writes **don't change type** and there is **no deallocation**
  - 3) So, given a ref.  $r$ , it is **guaranteed to point** to an  $a$ -typed value
- Baked into the memory models of most languages
- We derive them from **global state** + **general monotonicity**

# Monotonicity in programming

- **Programming** also relies on **monotonicity**, even if you don't realise it!
- Consider ML-style typed **references**  $r:\text{ref } a$ 
  - $r$  is a **proof of existence** of an  $a$ -typed value in the heap
- Correctness relies on **monotonicity**!
  - 1) Allocation **stores** an  $a$ -typed value in the heap
  - 2) Writes **don't change type** and there is **no deallocation**
  - 3) So, given a ref.  $r$ , it is **guaranteed to point** to an  $a$ -typed value
- Baked into the memory models of most languages
- We derive them from **global state** + **general monotonicity**

# Monotonicity in programming

- **Programming** also relies on **monotonicity**, even if you don't realise it!
- Consider ML-style typed **references**  $r:\text{ref } a$ 
  - $r$  is a **proof of existence** of an  $a$ -typed value in the heap
- Correctness relies on **monotonicity**!
  - 1) Allocation **stores** an  $a$ -typed value in the heap
  - 2) Writes **don't change type** and there is **no deallocation**
  - 3) So, given a ref.  $r$ , it is **guaranteed to point** to an  $a$ -typed value
- Baked into the memory models of most languages
- We derive them from **global state** + **general monotonicity**



# Monotonicity is really useful!

- In this talk, we will see how monotonicity gives us
  - our **motivating example** and **monotonic counters**
  - **typed references** (`ref t`) and **untyped references** (`uref`)
  - more flexibility with **monotonic references** (`mref t rel`)
- See our POPL 2018 paper for more
  - temporarily **violating monotonicity** via snapshots
  - two substantial case studies in  $F^*$ 
    - a **secure file-transfer** application
    - Ariadne **state continuity** protocol [Strackx, Piessens 2016]
  - pointers to other works in  $F^*$  relying on monotonicity for
    - sophisticated **region-based memory models** [fstar-lang.org]
    - **crypto** and **TLS verification** [project-everest.github.io]

# Monotonicity is really useful!

- In this talk, we will see how monotonicity gives us
  - our **motivating example** and **monotonic counters**
  - **typed references** (`ref t`) and **untyped references** (`uref`)
  - more flexibility with **monotonic references** (`mref t rel`)
- See our POPL 2018 paper for more
  - temporarily **violating monotonicity** via snapshots
  - two substantial case studies in  $F^*$ 
    - a **secure file-transfer** application
    - Ariadne **state continuity** protocol [Strackx, Piessens 2016]
  - pointers to other works in  $F^*$  relying on monotonicity for
    - sophisticated **region-based memory models** [fstar-lang.org]
    - **crypto** and **TLS verification** [project-everest.github.io]

# Monotonicity is really useful!

- In this talk, we will see how monotonicity gives us
  - our **motivating example** and **monotonic counters**
  - **typed references** (`ref t`) and **untyped references** (`uref`)
  - more flexibility with **monotonic references** (`mref t rel`)
- See our POPL 2018 paper for more
  - temporarily **violating monotonicity** via snapshots
  - two substantial case studies in  $F^*$ 
    - a **secure file-transfer** application
    - Ariadne **state continuity** protocol [Strackx, Piessens 2016]
  - pointers to other works in  $F^*$  relying on monotonicity for
    - sophisticated **region-based memory models** [fstar-lang.org]
    - **crypto** and **TLS verification** [project-everest.github.io]

# Outline

- \*  $F^*$  overview
- Monotonic state by example
- Key ideas behind our general extension to Hoare-style logics
- Accommodating monotonic state in  $F^*$
- Some examples of monotonic state at work
- Glimpse of meta-theory and correctness results
- More examples of monotonic state at work (see our paper)
- Monadic reification and reflection (see our paper)

# Key ideas behind our general framework

- Based on **monotonic programs** and **stable predicates**
  - per verification task, we **choose a preorder  $\text{rel}$**  on states
    - set inclusion, heap inclusion, increasing counter values, ...
  - a stateful program  $e$  is **monotonic** (wrt.  $\text{rel}$ ) when
$$\forall s e' s'. (e, s) \rightsquigarrow^* (e', s') \implies \text{rel } s s'$$
  - a stateful predicate  $p$  is **stable** (wrt.  $\text{rel}$ ) when
$$\forall s s'. p \ s \wedge \text{rel } s s' \implies p \ s'$$
- **Our solution:** extend Hoare-style program logics (e.g.,  $F^*$ ) with
  - $a$  means to **witness** the validity of  $p \ s$  in some state  $s$
  - $a$  means for turning a  $p$  into a **state-independent proposition**
  - $a$  means to **recall** the validity of  $p \ s'$  in any future state  $s'$
- Provides a **unifying account** of the existing *ad hoc* uses in  $F^*$

# Key ideas behind our general framework

- Based on **monotonic programs** and **stable predicates**
  - per verification task, we **choose a preorder** **rel** on states
    - set inclusion, heap inclusion, increasing counter values, ...
  - a stateful program  $e$  is **monotonic** (wrt. **rel**) when
$$\forall s e' s'. (e, s) \rightsquigarrow^* (e', s') \implies \text{rel } s \ s'$$
  - a stateful predicate  $p$  is **stable** (wrt. **rel**) when
$$\forall s s'. p \ s \wedge \text{rel } s \ s' \implies p \ s'$$
- **Our solution:** extend Hoare-style program logics (e.g.,  $F^*$ ) with
  - $a$  means to **witness** the validity of  $p \ s$  in some state  $s$
  - $a$  means for turning a  $p$  into a **state-independent proposition**
  - $a$  means to **recall** the validity of  $p \ s'$  in any future state  $s'$
- Provides a **unifying account** of the existing *ad hoc* uses in  $F^*$

# Key ideas behind our general framework

- Based on **monotonic programs** and **stable predicates**
  - per verification task, we **choose a preorder  $\text{rel}$**  on states
    - set inclusion, heap inclusion, increasing counter values, ...
  - a stateful program  $e$  is **monotonic** (wrt.  $\text{rel}$ ) when
$$\forall s e' s'. (e, s) \rightsquigarrow^* (e', s') \implies \text{rel } s s'$$
  - a stateful predicate  $p$  is **stable** (wrt.  $\text{rel}$ ) when
$$\forall s s'. p \ s \wedge \text{rel } s s' \implies p \ s'$$
- **Our solution:** extend Hoare-style program logics (e.g.,  $F^*$ ) with
  - $a$  means to **witness** the validity of  $p \ s$  in some state  $s$
  - $a$  means for turning a  $p$  into a **state-independent proposition**
  - $a$  means to **recall** the validity of  $p \ s'$  in any future state  $s'$
- Provides a **unifying account** of the existing *ad hoc* uses in  $F^*$

# Key ideas behind our general framework

- Based on **monotonic programs** and **stable predicates**
  - per verification task, we **choose a preorder  $\text{rel}$**  on states
    - set inclusion, heap inclusion, increasing counter values, ...

- a stateful program  $e$  is **monotonic** (wrt.  $\text{rel}$ ) when

$$\forall s e' s'. (e, s) \rightsquigarrow^* (e', s') \implies \text{rel } s s'$$

- a stateful predicate  $p$  is **stable** (wrt.  $\text{rel}$ ) when

$$\forall s s'. p s \wedge \text{rel } s s' \implies p s'$$

- **Our solution:** extend Hoare-style program logics (e.g.,  $F^*$ ) with
  - $a$  means to **witness** the validity of  $p s$  in some state  $s$
  - $a$  means for turning a  $p$  into a **state-independent proposition**
  - $a$  means to **recall** the validity of  $p s'$  in any future state  $s'$
- Provides a **unifying account** of the existing *ad hoc* uses in  $F^*$



# Key ideas behind our general framework

- Based on **monotonic programs** and **stable predicates**
  - per verification task, we **choose a preorder *rel*** on states
    - set inclusion, heap inclusion, increasing counter values, ...
  - a stateful program  $e$  is **monotonic** (wrt. *rel*) when

$$\forall s e' s'. (e, s) \rightsquigarrow^* (e', s') \implies \text{rel } s s'$$

- a stateful predicate  $p$  is **stable** (wrt. *rel*) when

$$\forall s s'. p \ s \ \wedge \ \text{rel } s s' \implies p \ s'$$

- **Our solution:** extend Hoare-style program logics (e.g.,  $F^*$ ) with
  - $a$  means to **witness** the validity of  $p \ s$  in some state  $s$
  - $a$  means for turning a  $p$  into a **state-independent proposition**
  - $a$  means to **recall** the validity of  $p \ s'$  in any future state  $s'$
- Provides a **unifying account** of the existing *ad hoc* uses in  $F^*$

# Key ideas behind our general framework

- Based on **monotonic programs** and **stable predicates**
  - per verification task, we **choose a preorder** **rel** on states
    - set inclusion, heap inclusion, increasing counter values, ...
  - a stateful program  $e$  is **monotonic** (wrt. **rel**) when
$$\forall s e' s'. (e, s) \rightsquigarrow^* (e', s') \implies \text{rel } s s'$$
  - a stateful predicate  $p$  is **stable** (wrt. **rel**) when
$$\forall s s'. p \ s \ \wedge \ \text{rel } s s' \implies p \ s'$$
- **Our solution:** extend Hoare-style program logics (e.g.,  $F^*$ ) with
  - $a$  means to **witness** the validity of  $p \ s$  in some state  $s$
  - $a$  means for turning a  $p$  into a **state-independent proposition**
  - $a$  means to **recall** the validity of  $p \ s'$  in any future state  $s'$
- Provides a **unifying account** of the existing *ad hoc* uses in  $F^*$

# Key ideas behind our general framework

- Based on **monotonic programs** and **stable predicates**
  - per verification task, we **choose a preorder** **rel** on states
    - set inclusion, heap inclusion, increasing counter values, ...
  - a stateful program  $e$  is **monotonic** (wrt. **rel**) when
$$\forall s e' s'. (e, s) \rightsquigarrow^* (e', s') \implies \text{rel } s s'$$
  - a stateful predicate  $p$  is **stable** (wrt. **rel**) when
$$\forall s s'. p \ s \ \wedge \ \text{rel } s s' \implies p \ s'$$
- **Our solution:** extend Hoare-style program logics (e.g.,  $F^*$ ) with
  - a means to **witness** the validity of  $p \ s$  in some state  $s$
  - a means for turning a  $p$  into a **state-independent proposition**
  - a means to **recall** the validity of  $p \ s'$  in any future state  $s'$
- Provides a **unifying account** of the existing *ad hoc* uses in  $F^*$

# Outline

- \*  $F^*$  overview
- Monotonic state by example
- Key ideas behind our general extension to Hoare-style logics
- Accommodating monotonic state in  $F^*$
- Some examples of monotonic state at work
- Glimpse of meta-theory and correctness results
- More examples of monotonic state at work (see our paper)
- Monadic reification and reflection (see our paper)

# Recap: Ordinary global state in F\*

- F\* supports Hoare-style reasoning about state via the **comp. type**

$$\text{ST}_{\text{state}}\ t\ (\text{requires}\ \text{pre})\ (\text{ensures}\ \text{post})$$

where

$$\text{pre} : \text{state} \rightarrow \text{Type} \qquad \text{post} : \text{state} \rightarrow t \rightarrow \text{state} \rightarrow \text{Type}$$

- ST is an abstract pre-postcondition refinement of

$$\text{st}\ t \stackrel{\text{def}}{=} \text{state} \rightarrow t * \text{state}$$

- The global state **actions** have types

$$\text{get} : \text{unit} \rightarrow \text{ST}\ \text{state}\ (\text{requires}\ (\lambda \_.\top))\ (\text{ensures}\ (\lambda\ s_0\ s\ s_1.\ s_0 = s = s_1))$$
$$\text{put} : s:\text{state} \rightarrow \text{ST}\ \text{unit}\ (\text{requires}\ (\lambda \_.\top))\ (\text{ensures}\ (\lambda \_ \_ s_1.\ s_1 = s))$$

- Refs. and local state** are defined in F\* using **monotonicity**

# Recap: Ordinary global state in F\*

- F\* supports Hoare-style reasoning about state via the **comp. type**

$$ST_{\text{state}}\ t\ (\text{requires}\ \text{pre})\ (\text{ensures}\ \text{post})$$

where

$$\text{pre} : \text{state} \rightarrow \text{Type} \qquad \text{post} : \text{state} \rightarrow t \rightarrow \text{state} \rightarrow \text{Type}$$

- ST is an abstract pre-postcondition refinement of

$$\text{st}\ t \stackrel{\text{def}}{=} \text{state} \rightarrow t * \text{state}$$

- The global state **actions** have types

$$\text{get} : \text{unit} \rightarrow ST\ \text{state}\ (\text{requires}\ (\lambda\_.\top))\ (\text{ensures}\ (\lambda\ s_0\ s\ s_1.\ s_0 = s = s_1))$$

$$\text{put} : s:\text{state} \rightarrow ST\ \text{unit}\ (\text{requires}\ (\lambda\_.\top))\ (\text{ensures}\ (\lambda\ _\ _\ s_1.\ s_1 = s))$$

- Refs. and local state are defined in F\* using **monotonicity**

# Recap: Ordinary global state in F\*

- F\* supports Hoare-style reasoning about state via the **comp. type**

$$\text{ST}_{\text{state}} \, t \, (\text{requires } \text{pre}) \, (\text{ensures } \text{post})$$

where

$$\text{pre} : \text{state} \rightarrow \text{Type} \qquad \text{post} : \text{state} \rightarrow t \rightarrow \text{state} \rightarrow \text{Type}$$

- ST is an abstract pre-postcondition refinement of

$$\text{st } t \stackrel{\text{def}}{=} \text{state} \rightarrow t * \text{state}$$

- The global state **actions** have types

$$\text{get} : \text{unit} \rightarrow \text{ST } \text{state} \, (\text{requires } (\lambda \_ . \top)) \, (\text{ensures } (\lambda s_0 \, s \, s_1 . s_0 = s = s_1))$$

$$\text{put} : s : \text{state} \rightarrow \text{ST } \text{unit} \, (\text{requires } (\lambda \_ . \top)) \, (\text{ensures } (\lambda \_ \_ s_1 . s_1 = s))$$

- Refs. and local state are defined in F\* using monotonicity

# Recap: Ordinary global state in F\*

- F\* supports Hoare-style reasoning about state via the **comp. type**

$$ST_{\text{state}} \ t \ (\text{requires } \text{pre}) \ (\text{ensures } \text{post})$$

where

$$\text{pre} : \text{state} \rightarrow \text{Type} \qquad \text{post} : \text{state} \rightarrow t \rightarrow \text{state} \rightarrow \text{Type}$$

- ST is an abstract pre-postcondition refinement of

$$st \ t \stackrel{\text{def}}{=} \text{state} \rightarrow t * \text{state}$$

- The global state **actions** have types

$$\text{get} : \text{unit} \rightarrow ST \ \text{state} \ (\text{requires } (\lambda \_ . \top)) \ (\text{ensures } (\lambda s_0 \ s \ s_1 . s_0 = s = s_1))$$

$$\text{put} : s : \text{state} \rightarrow ST \ \text{unit} \ (\text{requires } (\lambda \_ . \top)) \ (\text{ensures } (\lambda \_ \_ s_1 . s_1 = s))$$

- Refs.** and **local state** are defined in F\* using **monotonicity**



# New: Monotonic global state in F\*

- We capture monotonic state with a new **computational type**

$\text{MST}_{\text{state}, \text{rel}}\ t\ (\text{requires}\ \text{pre})\ (\text{ensures}\ \text{post})$

- The **get** action is typed as in ST

$\text{get} : \text{unit} \rightarrow \text{MST}\ \text{state}\ (\text{requires}\ (\lambda \_.\text{T}))$   
 $(\text{ensures}\ (\lambda\ s_0\ s\ s_1.\ s_0 = s = s_1))$

- To ensure **monotonicity**, the **put** action gets a precondition

$\text{put} : \text{s}:\text{state} \rightarrow \text{MST}\ \text{unit}\ (\text{requires}\ (\lambda\ s_0.\ \text{rel}\ s_0\ s))$   
 $(\text{ensures}\ (\lambda\ \_.\ s_1.\ s_1 = s))$

- So intuitively, MST is an **abstract** pre-postcondition refinement of

$\text{mst}\ t \stackrel{\text{def}}{=} \text{s}_0:\text{state} \rightarrow t * \text{s}_1:\text{state}\{\text{rel}\ \text{s}_0\ \text{s}_1\}$

# New: Monotonic global state in F\*

- We capture monotonic state with a new **computational type**

$\text{MST}_{\text{state}, \text{rel}} \ t \ (\text{requires} \ \text{pre}) \ (\text{ensures} \ \text{post})$

- The **get** action is typed as in ST

$\text{get} : \text{unit} \rightarrow \text{MST state} \ (\text{requires} \ (\lambda \_ . \top))$   
 $(\text{ensures} \ (\lambda s_0 \ s \ s_1 . s_0 = s = s_1))$

- To ensure **monotonicity**, the **put** action gets a precondition

$\text{put} : s:\text{state} \rightarrow \text{MST unit} \ (\text{requires} \ (\lambda s_0 . \text{rel } s_0 \ s))$   
 $(\text{ensures} \ (\lambda \_ \ s_1 . s_1 = s))$

- So intuitively, MST is an **abstract** pre-postcondition refinement of

$\text{mst } t \stackrel{\text{def}}{=} s_0:\text{state} \rightarrow t * s_1:\text{state} \{ \text{rel } s_0 \ s_1 \}$

# New: Monotonic global state in F\*

- We capture monotonic state with a new **computational type**

$\text{MST}_{\text{state}, \text{rel}} \ t \ (\text{requires} \ \text{pre}) \ (\text{ensures} \ \text{post})$

- The **get** action is typed as in **ST**

$\text{get} : \text{unit} \rightarrow \text{MST} \ \text{state} \ (\text{requires} \ (\lambda \_ . \top))$   
 $(\text{ensures} \ (\lambda s_0 \ s \ s_1 . s_0 = s = s_1))$

- To ensure **monotonicity**, the **put** action gets a precondition

$\text{put} : s : \text{state} \rightarrow \text{MST} \ \text{unit} \ (\text{requires} \ (\lambda s_0 . \text{rel} \ s_0 \ s))$   
 $(\text{ensures} \ (\lambda \_ \ s_1 . s_1 = s))$

- So intuitively, **MST** is an **abstract** pre-postcondition refinement of

$\text{mst} \ t \stackrel{\text{def}}{=} s_0 : \text{state} \rightarrow t * s_1 : \text{state} \{ \text{rel} \ s_0 \ s_1 \}$

# New: Monotonic global state in F\*

- We capture monotonic state with a new **computational type**

$\text{MST}_{\text{state}, \text{rel}} \ t \ (\text{requires} \ \text{pre}) \ (\text{ensures} \ \text{post})$

- The **get** action is typed as in **ST**

$\text{get} : \text{unit} \rightarrow \text{MST} \ \text{state} \ (\text{requires} \ (\lambda \_ . \top))$   
 $(\text{ensures} \ (\lambda s_0 \ s \ s_1 . s_0 = s = s_1))$

- To ensure **monotonicity**, the **put** action gets a precondition

$\text{put} : \text{s} : \text{state} \rightarrow \text{MST} \ \text{unit} \ (\text{requires} \ (\lambda s_0 . \text{rel} \ s_0 \ s))$   
 $(\text{ensures} \ (\lambda \_ \ s_1 . s_1 = s))$

- So intuitively, MST is an **abstract** pre-postcondition refinement of

$\text{mst} \ t \stackrel{\text{def}}{=} \text{s}_0 : \text{state} \rightarrow t * \text{s}_1 : \text{state} \{ \text{rel} \ s_0 \ s_1 \}$

# New: Monotonic global state in F\*

- We capture monotonic state with a new **computational type**

$$\text{MST}_{\text{state}, \text{rel}} \, t \, (\text{requires} \, \text{pre}) \, (\text{ensures} \, \text{post})$$

- The **get** action is typed as in ST

$$\begin{aligned} \text{get} : \text{unit} \rightarrow \text{MST} \, \text{state} \, (\text{requires} \, (\lambda \_ . \top)) \\ (\text{ensures} \, (\lambda s_0 \, s \, s_1 . s_0 = s = s_1)) \end{aligned}$$

- To ensure **monotonicity**, the **put** action gets a precondition

$$\begin{aligned} \text{put} : \text{s} : \text{state} \rightarrow \text{MST} \, \text{unit} \, (\text{requires} \, (\lambda s_0 . \text{rel} \, s_0 \, s)) \\ (\text{ensures} \, (\lambda \_ \_ s_1 . s_1 = s)) \end{aligned}$$

- So intuitively, MST is an **abstract** pre-postcondition refinement of

$$\text{mst} \, t \stackrel{\text{def}}{=} \text{s}_0 : \text{state} \rightarrow t * \text{s}_1 : \text{state} \{ \text{rel} \, \text{s}_0 \, \text{s}_1 \}$$

# New: Recalling a Witness

- We extend  $F^*$  with a **logical capability**

$\text{witnessed} : (\text{state} \rightarrow \text{Type}) \rightarrow \text{Type}$

together with a **weakening principle** (functoriality)

$\text{wk} : p, q : (\text{state} \rightarrow \text{Type}) \rightarrow \text{Lemma} (\text{requires } (\forall s. p\ s \implies q\ s))$   
 $(\text{ensures } (\text{witnessed } p \implies \text{witnessed } q))$

- Intuitively, think of it as a **necessity modality**

$$\llbracket \text{witnessed } p \rrbracket(s) \stackrel{\text{def}}{=} \forall s'. \text{rel } s\ s' \implies \llbracket p\ s' \rrbracket(s)$$

- As usual, for natural deduction, need **world-indexed sequents**
- But, wait a minute ...

# New: Recalling a Witness

- We extend  $F^*$  with a **logical capability**

$\text{witnessed} : (\text{state} \rightarrow \text{Type}) \rightarrow \text{Type}$

together with a **weakening principle (functoriality)**

$\text{wk} : p, q : (\text{state} \rightarrow \text{Type}) \rightarrow \text{Lemma } (\text{requires } (\forall s. p\ s \implies q\ s))$   
 $(\text{ensures } (\text{witnessed } p \implies \text{witnessed } q))$

- Intuitively, think of it as a **necessity modality**

$$\llbracket \text{witnessed } p \rrbracket(s) \stackrel{\text{def}}{=} \forall s'. \text{rel } s\ s' \implies \llbracket p\ s' \rrbracket(s)$$

- As usual, for natural deduction, need **world-indexed sequents**
- But, wait a minute ...

# New: Recalling a Witness

- We extend  $F^*$  with a **logical capability**

$\text{witnessed} : (\text{state} \rightarrow \text{Type}) \rightarrow \text{Type}$

together with a **weakening principle (functoriality)**

$\text{wk} : p, q : (\text{state} \rightarrow \text{Type}) \rightarrow \text{Lemma } (\text{requires } (\forall s. p\ s \implies q\ s))$   
 $(\text{ensures } (\text{witnessed } p \implies \text{witnessed } q))$

- Intuitively, think of it as a **necessity modality**

$$\llbracket \text{witnessed } p \rrbracket(s) \stackrel{\text{def}}{=} \forall s'. \text{rel } s\ s' \implies \llbracket p\ s' \rrbracket(s)$$

- As usual, for natural deduction, need **world-indexed sequents**
- But, wait a minute ...



# New: Recalling a Witness

- We extend  $F^*$  with a **logical capability**

$\text{witnessed} : (\text{state} \rightarrow \text{Type}) \rightarrow \text{Type}$

together with a **weakening principle (functoriality)**

$\text{wk} : p, q : (\text{state} \rightarrow \text{Type}) \rightarrow \text{Lemma} \left( \text{requires } (\forall s. p\ s \implies q\ s) \right)$   
 $\quad \quad \quad \left( \text{ensures } (\text{witnessed } p \implies \text{witnessed } q) \right)$

- Intuitively, think of it as a **necessity modality**

$$\llbracket \text{witnessed } p \rrbracket (s) \stackrel{\text{def}}{=} \forall s'. \text{rel } s\ s' \implies \llbracket p\ s' \rrbracket (s)$$

- As usual, for natural deduction, need **world-indexed sequents**
- But, wait a minute ...

# New: Recalling a Witness

- We extend  $F^*$  with a **logical capability**

$\text{witnessed} : (\text{state} \rightarrow \text{Type}) \rightarrow \text{Type}$

together with a **weakening principle (functoriality)**

$\text{wk} : p, q : (\text{state} \rightarrow \text{Type}) \rightarrow \text{Lemma} \left( \text{requires } (\forall s. p\ s \implies q\ s) \right)$   
 $\left( \text{ensures } (\text{witnessed } p \implies \text{witnessed } q) \right)$

- Intuitively, think of it as a **necessity modality**

$$\llbracket \text{witnessed } p \rrbracket (s) \stackrel{\text{def}}{=} \forall s'. \text{rel } s\ s' \implies \llbracket p\ s' \rrbracket (s)$$

- As usual, for natural deduction, need **world-indexed sequents**
- But, wait a minute ...

# New: Recalling a Witness

- ... Hoare-style logics are essentially **world/state-indexed**, so
- we include a **stateful introduction rule** for witnessed

```
witness : p:(state  $\rightarrow$  Type0)  
          $\rightarrow$  MST unit (requires ( $\lambda s_0. p \text{ 'stable\_from' } s_0$ ))  
                     (ensures ( $\lambda s_0 - s_1. s_0 = s_1 \wedge \text{witnessed } p$ )))
```

- and a **stateful elimination rule** for witnessed

```
recall : p:(state  $\rightarrow$  Type0)  
         $\rightarrow$  MST unit (requires ( $\lambda \_. \text{witnessed } p$ ))  
                    (ensures ( $\lambda s_0 - s_1. s_0 = s_1 \wedge p \text{ 'stable\_from' } s_1$ )))
```

# New: Recalling a Witness

- ... Hoare-style logics are essentially **world/state-indexed**, so
- we include a **stateful introduction rule** for witnessed

```
witness : p:(state  $\rightarrow$  Type0)  
          $\rightarrow$  MST unit (requires ( $\lambda s_0.$  p 'stable_from' s0))  
                   (ensures ( $\lambda s_0 - s_1. s_0 = s_1 \wedge$  witnessed p))
```

- and a **stateful elimination rule** for witnessed

```
recall : p:(state  $\rightarrow$  Type0)  
         $\rightarrow$  MST unit (requires ( $\lambda ..$  witnessed p))  
                  (ensures ( $\lambda s_0 - s_1. s_0 = s_1 \wedge$  p 'stable_from' s1))
```

# New: Recalling a Witness

- ... Hoare-style logics are essentially **world/state-indexed**, so
- we include a **stateful introduction rule** for witnessed

```
witness : p:(state  $\rightarrow$  Type0)  
          $\rightarrow$  MST unit (requires ( $\lambda s_0$ . p 'stable_from' s0))  
                     (ensures ( $\lambda s_0 - s_1$ . s0 = s1  $\wedge$  witnessed p)))
```

- and a **stateful elimination rule** for witnessed

```
recall : p:(state  $\rightarrow$  Type0)  
         $\rightarrow$  MST unit (requires ( $\lambda \_$ . witnessed p))  
                    (ensures ( $\lambda s_0 - s_1$ . s0 = s1  $\wedge$  p 'stable_from' s1)))
```

# Outline

- \*  $F^*$  overview
- Monotonic state by example
- Key ideas behind our general extension to Hoare-style logics
- Accommodating monotonic state in  $F^*$
- Some examples of monotonic state at work
- Glimpse of meta-theory and correctness results
- More examples of monotonic state at work (see our paper)
- Monadic reification and reflection (see our paper)

# The motivating example revisited

- Recall the program operating on the **set-valued state**

```
insert v; complex_procedure(); assert (v ∈ get())
```

- We pick **set inclusion**  $\subseteq$  as our preorder rel on states
- We **prove the assertion** by inserting a witness and recall

```
insert v; witness ( $\lambda s. v \in s$ ); c_p(); recall ( $\lambda s. v \in s$ ); assert (v ∈ get())
```

- For any other w, wrapping

```
insert w; [ ]; assert (w ∈ get())
```

around the program is handled **similarly easily** by

```
insert w; witness ( $\lambda s. w \in s$ ); [ ]; recall ( $\lambda s. w \in s$ ); assert (w ∈ get())
```

- Monotonic counters** are analogous, by picking  $\mathbb{N}$  and  $\leq$ , e.g.,  

```
create 0; incr(); witness ( $\lambda c. c > 0$ ); c_p(); recall ( $\lambda c. c > 0$ )
```

# The motivating example revisited

- Recall the program operating on the **set-valued state**

```
insert v; complex_procedure(); assert (v ∈ get())
```

- We pick **set inclusion**  $\subseteq$  as our preorder rel on states
- We **prove the assertion** by inserting a witness and recall

```
insert v; witness ( $\lambda s. v \in s$ ); c_p(); recall ( $\lambda s. v \in s$ ); assert (v ∈ get())
```

- For any other w, wrapping

```
insert w; [ ]; assert (w ∈ get())
```

around the program is handled **similarly easily** by

```
insert w; witness ( $\lambda s. w \in s$ ); [ ]; recall ( $\lambda s. w \in s$ ); assert (w ∈ get())
```

- Monotonic counters** are analogous, by picking  $\mathbb{N}$  and  $\leq$ , e.g.,  

```
create 0; incr(); witness ( $\lambda c. c > 0$ ); c_p(); recall ( $\lambda c. c > 0$ )
```



# The motivating example revisited

- Recall the program operating on the **set-valued state**

```
insert v; complex_procedure(); assert (v ∈ get())
```

- We pick **set inclusion**  $\subseteq$  as our preorder rel on states
- We **prove the assertion** by inserting a witness and recall

```
insert v; witness ( $\lambda s. v \in s$ ); c_p(); recall ( $\lambda s. v \in s$ ); assert (v ∈ get())
```

- For any other w, wrapping

```
insert w; [ ]; assert (w ∈ get())
```

around the program is handled **similarly easily** by

```
insert w; witness ( $\lambda s. w \in s$ ); [ ]; recall ( $\lambda s. w \in s$ ); assert (w ∈ get())
```

- Monotonic counters** are analogous, by picking  $\mathbb{N}$  and  $\leq$ , e.g.,  

```
create 0; incr(); witness ( $\lambda c. c > 0$ ); c_p(); recall ( $\lambda c. c > 0$ )
```

# The motivating example revisited

- Recall the program operating on the **set-valued state**

```
insert v; complex_procedure(); assert (v ∈ get())
```

- We pick **set inclusion**  $\subseteq$  as our preorder `rel` on states
- We **prove the assertion** by inserting a witness and recall

```
insert v; witness ( $\lambda s. v \in s$ ); c_p(); recall ( $\lambda s. v \in s$ ); assert (v ∈ get())
```

- For **any other** `w`, wrapping

```
insert w; [ ]; assert (w ∈ get())
```

around the program is handled **similarly easily** by

```
insert w; witness ( $\lambda s. w \in s$ ); [ ]; recall ( $\lambda s. w \in s$ ); assert (w ∈ get())
```

- Monotonic counters are analogous, by picking  $\mathbb{N}$  and  $\leq$ , e.g.,  
`create 0; incr(); witness ( $\lambda c. c > 0$ ); c_p(); recall ( $\lambda c. c > 0$ )`

# The motivating example revisited

- Recall the program operating on the **set-valued state**

```
insert v; complex_procedure(); assert (v ∈ get())
```

- We pick **set inclusion**  $\subseteq$  as our preorder rel on states
- We **prove the assertion** by inserting a witness and recall

```
insert v; witness ( $\lambda s. v \in s$ ); c_p(); recall ( $\lambda s. v \in s$ ); assert (v ∈ get())
```

- For **any other** w, wrapping

```
insert w; [ ]; assert (w ∈ get())
```

around the program is handled **similarly easily** by

```
insert w; witness ( $\lambda s. w \in s$ ); [ ]; recall ( $\lambda s. w \in s$ ); assert (w ∈ get())
```

- Monotonic counters** are analogous, by picking  $\mathbb{N}$  and  $\leq$ , e.g.,  
create 0; incr(); **witness** ( $\lambda c. c > 0$ ); c\_p(); **recall** ( $\lambda c. c > 0$ )

# ML-style typed references (local state)

- First, we define a type of **heaps** as a finite map

```
type heap =
```

```
| H : h : (N → cell) → ctr : N { ∀ n. ctr ≤ n ⇒ h n = Unused } → heap
```

where

```
type cell =
```

```
| Unused : cell
```

```
| Used : a : Type → v : a → cell
```

- Next, we define a **preorder** on heaps (**heap inclusion**)

```
let heap_inclusion (H h0 _) (H h1 _) = ∀ id. match h0 id, h1 id with
```

```
| Used a _, Used b _ → a = b
```

```
| Unused, Used _ _ → ⊥
```

```
| Unused, Unused → ⊤
```

```
| Used _ _, Unused → ⊥
```

# ML-style typed references (local state)

- First, we define a type of **heaps** as a finite map

```
type heap =
```

```
| H : h:( $\mathbb{N} \rightarrow \text{cell}$ )  $\rightarrow$  ctr: $\mathbb{N}\{\forall n. \text{ctr} \leq n \implies h\ n = \text{Unused}\} \rightarrow \text{heap}$ 
```

where

```
type cell =
```

```
| Unused : cell
```

```
| Used : a:Type  $\rightarrow$  v:a  $\rightarrow$  cell
```

- Next, we define a preorder on heaps (**heap inclusion**)

```
let heap_inclusion (H h0 _) (H h1 _) =  $\forall \text{id}. \text{match } h_0\ \text{id}, h_1\ \text{id} \text{ with}$ 
```

```
| Used a _, Used b _  $\rightarrow$  a = b
```

```
| Unused, Used _ _  $\rightarrow$   $\top$ 
```

```
| Unused, Unused  $\rightarrow$   $\top$ 
```

```
| Used _ _, Unused  $\rightarrow$   $\perp$ 
```

# ML-style typed references (local state)

- First, we define a type of **heaps** as a finite map

`type heap =`

`| H : h:( $\mathbb{N} \rightarrow \text{cell}$ )  $\rightarrow$  ctr: $\mathbb{N}\{\forall n. \text{ctr} \leq n \implies h\ n = \text{Unused}\} \rightarrow \text{heap}$`

where

`type cell =`

`| Unused : cell`

`| Used : a:Type  $\rightarrow$  v:a  $\rightarrow$  cell`

- Next, we define a **preorder** on heaps (**heap inclusion**)

`let heap_inclusion (H h0 _) (H h1 _) =  $\forall \text{id}. \text{match } h_0\ \text{id}, h_1\ \text{id} \text{ with}$`

`| Used a _, Used b _  $\rightarrow a = b$`

`| Unused, Used _ _  $\rightarrow \top$`

`| Unused, Unused  $\rightarrow \top$`

`| Used _ _, Unused  $\rightarrow \perp$`

# ML-style typed references (local state)

- As a result, we can define new **local state effect**

$$\text{MLST } t \text{ pre post} \stackrel{\text{def}}{=} \text{MST}_{\text{heap, heap\_inclusion}} t \text{ pre post}$$

- Next, we define the type of **references** using monotonicity

abstract type ref a = id:N{witnessed ( $\lambda h.$  contains h id a)}

where

let contains (H h \_) id a =

match h id with

| Used b \_  $\rightarrow$  a = b

| Unused  $\rightarrow \perp$

- Important: contains is **stable** wrt. heap\_inclusion

# ML-style typed references (local state)

- As a result, we can define new **local state effect**

$$\text{MLST } t \text{ pre post} \stackrel{\text{def}}{=} \text{MST}_{\text{heap, heap\_inclusion}} t \text{ pre post}$$

- Next, we define the type of **references** using monotonicity

```
abstract type ref a = id:N{witnessed ( $\lambda h$ . contains h id a)}
```

where

```
let contains (H h _) id a =
```

```
  match h id with
```

```
    | Used b _  $\rightarrow$  a = b
```

```
    | Unused  $\rightarrow \perp$ 
```

- Important: contains is **stable** wrt. heap\_inclusion



# ML-style typed references (local state)

- As a result, we can define new **local state effect**

$$\text{MLST } t \text{ pre post} \stackrel{\text{def}}{=} \text{MST}_{\text{heap, heap\_inclusion}} t \text{ pre post}$$

- Next, we define the type of **references** using monotonicity

```
abstract type ref a = id:ℕ{witnessed (λh. contains h id a)}
```

where

```
let contains (H h _) id a =  
  match h id with  
  | Used b _ → a = b  
  | Unused → ⊥
```

- Important: contains is **stable** wrt. heap\_inclusion

# ML-style typed references (local state)

- Finally, we define **MLST**'s **actions** using **MST**'s actions

- `let alloc (a:Type) (v:a) : MLST (ref a) ... = ...`
  - get the current heap
  - create a fresh ref., and add it to the heap
  - put the updated heap back
  - witness that the created ref. is in the heap
- `let read (r:ref a) : MLST a (req. ( $\top$ )) (ens. (...)) = ...`
  - recall that the given ref. is in the heap
  - get the current heap
  - select the given reference from the heap
- `let write (r:ref a) (v:a) : MLST unit ... = ...`
  - recall that the given ref. is in the heap
  - get the current heap
  - update the heap with the given value at the given ref.
  - put the updated heap back

# ML-style typed references (local state)

- Finally, we define **MLST**'s **actions** using **MST**'s actions
  - **let alloc** ( $a:\text{Type}$ ) ( $v:a$ ) : **MLST** ( $\text{ref } a$ ) ... = ...
    - **get** the current heap
    - **create** a fresh ref., and **add** it to the heap
    - **put** the updated heap back
    - **witness** that the created ref. is in the heap
  - **let read** ( $r:\text{ref } a$ ) : **MLST**  $a$  ( $\text{req. } (\top)$ ) ( $\text{ens. } (...)$ ) = ...
    - **recall** that the given ref. is in the heap
    - **get** the current heap
    - **select** the given reference from the heap
  - **let write** ( $r:\text{ref } a$ ) ( $v:a$ ) : **MLST**  $\text{unit}$  ... = ...
    - **recall** that the given ref. is in the heap
    - **get** the current heap
    - **update** the heap with the given value at the given ref.
    - **put** the updated heap back

# ML-style typed references (local state)

- Finally, we define **MLST**'s **actions** using **MST**'s actions
  - **let alloc**  $(a:\text{Type}) (v:a) : \text{MLST} (\text{ref } a) \dots = \dots$ 
    - **get** the current heap
    - **create** a fresh ref., and **add** it to the heap
    - **put** the updated heap back
    - **witness** that the created ref. is in the heap
  - **let read**  $(r:\text{ref } a) : \text{MLST } a (\text{req. } (\top)) (\text{ens. } (\dots)) = \dots$ 
    - **recall** that the given ref. is in the heap
    - **get** the current heap
    - **select** the given reference from the heap
  - **let write**  $(r:\text{ref } a) (v:a) : \text{MLST unit } \dots = \dots$ 
    - **recall** that the given ref. is in the heap
    - **get** the current heap
    - **update** the heap with the given value at the given ref.
    - **put** the updated heap back

# ML-style typed references (local state)

- Finally, we define **MLST**'s **actions** using **MST**'s actions
  - **let alloc**  $(a:\text{Type}) (v:a) : \text{MLST} (\text{ref } a) \dots = \dots$ 
    - **get** the current heap
    - **create** a fresh ref., and **add** it to the heap
    - **put** the updated heap back
    - **witness** that the created ref. is in the heap
  - **let read**  $(r:\text{ref } a) : \text{MLST } a (\text{req. } (\top)) (\text{ens. } (\dots)) = \dots$ 
    - **recall** that the given ref. is in the heap
    - **get** the current heap
    - **select** the given reference from the heap
  - **let write**  $(r:\text{ref } a) (v:a) : \text{MLST} \text{ unit } \dots = \dots$ 
    - **recall** that the given ref. is in the heap
    - **get** the current heap
    - **update** the heap with the given value at the given ref.
    - **put** the updated heap back

# Adding untyped and monotonic references

- Untyped references (`uref`) with strong updates

- Used heap cells are extended with **tags**

where 
$$\text{Used} : a:\text{Type} \rightarrow v:a \rightarrow \text{t:tag} \rightarrow \text{cell}$$

$$\text{type tag} = \text{Typed} : \text{tag} \mid \text{Untyped} : \text{tag}$$

- actions corresponding to urefs have **weaker types** than for refs

- Monotonic references (`mref a rel`)

- Used heap cells are extended with **typed tags**

where 
$$\text{Used} : a:\text{Type} \rightarrow v:a \rightarrow \text{t:tag } a \rightarrow \text{cell}$$

$$\text{type tag } a = \text{Typed} : \text{rel:preorder } a \rightarrow \text{tag } a \mid \text{Untyped} : \text{tag } a$$

- `mrefs` provide **more flexibility** with ref.-wise monotonicity

- Further, all three can be extended with **manually managed** refs.

# Adding untyped and monotonic references

- **Untyped references** (`uref`) with strong updates

- Used heap cells are extended with **tags**

where 
$$| \text{Used} : a:\text{Type} \rightarrow v:a \rightarrow \text{t:tag} \rightarrow \text{cell}$$

$$\text{type tag} = \text{Typed} : \text{tag} \mid \text{Untyped} : \text{tag}$$

- actions corresponding to urefs have **weaker types** than for refs

- **Monotonic references** (`mref a rel`)

- Used heap cells are extended with **typed tags**

where 
$$| \text{Used} : a:\text{Type} \rightarrow v:a \rightarrow \text{t:tag } a \rightarrow \text{cell}$$

$$\text{type tag } a = \text{Typed} : \text{rel:preorder } a \rightarrow \text{tag } a \mid \text{Untyped} : \text{tag } a$$

- `mrefs` provide **more flexibility** with ref.-wise monotonicity

- Further, all three can be extended with **manually managed** refs.

# Adding untyped and monotonic references

- **Untyped references** (`uref`) with strong updates

- Used heap cells are extended with **tags**

where 
$$| \text{Used} : a:\text{Type} \rightarrow v:a \rightarrow \text{t:tag} \rightarrow \text{cell}$$

$$\text{type tag} = \text{Typed} : \text{tag} \mid \text{Untyped} : \text{tag}$$

- actions corresponding to urefs have **weaker types** than for refs

- **Monotonic references** (`mref a rel`)

- Used heap cells are extended with **typed tags**

where 
$$| \text{Used} : a:\text{Type} \rightarrow v:a \rightarrow \text{t:tag } a \rightarrow \text{cell}$$

$$\text{type tag } a = \text{Typed} : \text{rel:preorder } a \rightarrow \text{tag } a \mid \text{Untyped} : \text{tag } a$$

- mrefs provide **more flexibility** with ref.-wise monotonicity

- Further, all three can be extended with **manually managed** refs.



# Adding untyped and monotonic references

- **Untyped references** (`uref`) with strong updates

- Used heap cells are extended with **tags**

where 
$$| \text{Used} : a:\text{Type} \rightarrow v:a \rightarrow \text{t:tag} \rightarrow \text{cell}$$

$$\text{type tag} = \text{Typed} : \text{tag} \mid \text{Untyped} : \text{tag}$$

- actions corresponding to urefs have **weaker types** than for refs

- **Monotonic references** (`mref a rel`)

- Used heap cells are extended with **typed tags**

where 
$$| \text{Used} : a:\text{Type} \rightarrow v:a \rightarrow \text{t:tag } a \rightarrow \text{cell}$$

$$\text{type tag } a = \text{Typed} : \text{rel:preorder } a \rightarrow \text{tag } a \mid \text{Untyped} : \text{tag } a$$

- `mrefs` provide **more flexibility** with ref.-wise monotonicity
- Further, all three can be extended with **manually managed** refs.

# Outline

- \*  $F^*$  overview
- Monotonic state by example
- Key ideas behind our general extension to Hoare-style logics
- Accommodating monotonic state in  $F^*$
- Some examples of monotonic state at work
- Glimpse of meta-theory and correctness results
- More examples of monotonic state at work (see our paper)
- Monadic reification and reflection (see our paper)

# Glimpse of meta-theory

- A small **dependently typed**  $\lambda$ -calculus with **Tot** and **MST** effects
- Using an **instrumented operational semantics**, where

$$\begin{aligned}(\text{witness } p, s, W) &\rightsquigarrow (\text{return } (), s, W \cup \{p\}) \\(\text{recall } p, s, W) &\rightsquigarrow (\text{return } (), s, W)\end{aligned}$$

- **Strong normalisation** shown via type-erasure and TT-lifting
- Hoare-style **total correctness** via SN, progress, and preservation

if  $\vdash e : \text{MST } t \text{ } \textit{pre post}$  and

$\vdash (s, W) \text{ wf}$  and witnessed  $W \vdash \textit{pre } s$

then  $(e, s, W) \rightsquigarrow^* (\text{return } v, s', W')$  and  $\vdash v : t$  and

witnessed  $W' \vdash \textit{rel } s s'$  and  $W \subseteq W'$  and

witnessed  $W' \vdash \textit{post } s v s'$

# Glimpse of meta-theory

- A small **dependently typed**  $\lambda$ -calculus with **Tot** and **MST** effects
- Using an **instrumented operational semantics**, where

$$\begin{aligned}(\text{witness } p, s, W) &\rightsquigarrow (\text{return } (), s, W \cup \{p\}) \\(\text{recall } p, s, W) &\rightsquigarrow (\text{return } (), s, W)\end{aligned}$$

- **Strong normalisation** shown via type-erasure and TT-lifting
- Hoare-style **total correctness** via SN, progress, and preservation

if  $\vdash e : \text{MST } t \text{ } \textit{pre post}$  and

$\vdash (s, W) \text{ wf}$  and witnessed  $W \vdash \textit{pre } s$

then  $(e, s, W) \rightsquigarrow^* (\text{return } v, s', W')$  and  $\vdash v : t$  and

witnessed  $W' \vdash \textit{rel } s s'$  and  $W \subseteq W'$  and

witnessed  $W' \vdash \textit{post } s v s'$

# Glimpse of meta-theory

- A small **dependently typed**  $\lambda$ -calculus with **Tot** and **MST** effects
- Using an **instrumented operational semantics**, where

$$(\text{witness } p, s, W) \rightsquigarrow (\text{return } (), s, W \cup \{p\})$$

$$(\text{recall } p, s, W) \rightsquigarrow (\text{return } (), s, W)$$

- **Strong normalisation** shown via type-erasure and TT-lifting
- Hoare-style **total correctness** via SN, progress, and preservation

if  $\vdash e : \text{MST } t \text{ } \textit{pre post}$  and

$\vdash (s, W) \text{ wf}$  and witnessed  $W \vdash \textit{pre } s$

then  $(e, s, W) \rightsquigarrow^* (\text{return } v, s', W')$  and  $\vdash v : t$  and

witnessed  $W' \vdash \textit{rel } s s'$  and  $W \subseteq W'$  and

witnessed  $W' \vdash \textit{post } s v s'$

# Glimpse of meta-theory

- A small **dependently typed**  $\lambda$ -calculus with **Tot** and **MST** effects
- Using an **instrumented operational semantics**, where

$$\begin{aligned}(\text{witness } p, s, W) &\rightsquigarrow (\text{return } (), s, W \cup \{p\}) \\(\text{recall } p, s, W) &\rightsquigarrow (\text{return } (), s, W)\end{aligned}$$

- **Strong normalisation** shown via type-erasure and TT-lifting
- Hoare-style **total correctness** via SN, progress, and preservation

**if**  $\vdash e : \text{MST } t \text{ } \textit{pre post}$  **and**

$\vdash (s, W) \text{ wf}$  **and** witnessed  $W \vdash \textit{pre } s$

**then**  $(e, s, W) \rightsquigarrow^* (\text{return } v, s', W')$  **and**  $\vdash v : t$  **and**

witnessed  $W' \vdash \textit{rel } s s'$  **and**  $W \subseteq W'$  **and**

witnessed  $W' \vdash \textit{post } s v s'$

# Conclusion

- Monotonicity
  - can be distilled into a **simple** and **general** framework
  - is **useful** for **programming** (refs.) and **verification** (Prj. Everest)
- See our POPL 2018 paper for
  - further **examples** and **case studies**
  - details of **meta-theory** for MST
  - first steps towards **monadic reification** for MST (rel. reasoning)
- Ongoing: taking the **modality** aspect of witnessed seriously
  - to remove instrumentation from op. sem., and
  - to improve support for monadic reification

# Conclusion

- Monotonicity
  - can be distilled into a **simple** and **general** framework
  - is **useful** for **programming** (refs.) and **verification** (Prj. Everest)
- See our POPL 2018 paper for
  - further **examples** and **case studies**
  - details of **meta-theory** for [MST](#)
  - first steps towards **monadic reification** for [MST](#) (rel. reasoning)
- Ongoing: taking the **modality** aspect of witnessed seriously
  - to remove instrumentation from op. sem., and
  - to improve support for monadic reification



# Thank you for your attention!

## Questions?

D. Ahman, C. Fournet, C. Hrițcu, K. Maillard, A. Rastogi, N. Swamy.

**Recalling a Witness: Foundations and Applications of Monotonic State**

*Proc. ACM Program. Lang.*, volume 2, issue POPL, article 65, 2018.

# Appendix: Mon. reification and reflection

- In  $F^*$  every **abstract ST computation**

$$e : \text{ST } t \text{ (requires pre) (ensures post)}$$

can be **reified** into its **underlying Pure representation**

$$\text{reify } e : s_0 : \text{state} \rightarrow \text{Pure } (t * \text{state}) \text{ (requires (pre } s_0)) \\ \text{(ensures } (\lambda (x, s_1). \text{post } s_0 \ x \ s_1))$$

and vice versa using **reflection** (see our POPL 2017 paper)

- Useful for **extrinsic reasoning**, e.g., for relational properties
- We also need it for **MST**!

# Appendix: Mon. reification and reflection

- In  $F^*$  every **abstract ST computation**

$$e : \text{ST } t \text{ (requires pre) (ensures post)}$$

can be **reified** into its **underlying Pure representation**

$$\text{reify } e : s_0 : \text{state} \rightarrow \text{Pure } (t * \text{state}) \text{ (requires (pre } s_0)) \\ \text{(ensures } (\lambda (x, s_1). \text{post } s_0 \ x \ s_1))$$

and vice versa using **reflection** (see our POPL 2017 paper)

- Useful for **extrinsic reasoning**, e.g., for relational properties
- We also need it for MST!

# Appendix: Mon. reification and reflection

- In  $F^*$  every **abstract ST computation**

$$e : \text{ST } t \text{ (requires pre) (ensures post)}$$

can be **reified** into its **underlying Pure representation**

$$\text{reify } e : s_0 : \text{state} \rightarrow \text{Pure } (t * \text{state}) \text{ (requires (pre } s_0)) \\ \text{(ensures } (\lambda (x, s_1). \text{post } s_0 \ x \ s_1))$$

and vice versa using **reflection** (see our POPL 2017 paper)

- Useful for **extrinsic reasoning**, e.g., for relational properties
- We also need it for **MST**!

# Appendix: Mon. reification and reflection

- We cannot simply turn an **abstract MST computation**

$e : \text{MST } t \text{ (requires pre) (ensures post)}$

into a **state-passing function**

$s_0 : \text{state} \rightarrow \text{Pure } (t * s_1 : \text{state} \{ \text{rel } s_0 \ s_1 \}) \text{ (req. (pre } s_0))$   
 $\text{(ens. } (\lambda (x, s_1). \text{post } s_0 \ x \ s_1))$

- For example, consider the **recalling** action

$\text{recall} : p : (\text{state} \rightarrow \text{Type}) \rightarrow \text{MST unit (requires } (\lambda \_. \text{witnessed } p))$   
 $\text{(ensures } (\lambda s_0 \ s_1. s_0 = s_1 \wedge p \ s_1))$

which we would like to **reduce** as

$\text{reify (recall } p) \rightsquigarrow \lambda s_0. \text{return } ((), s_0)$

but we cannot prove  $p \ s_0$  from **witnessed**  $p$  in the pure logic

# Appendix: Mon. reification and reflection

- We cannot simply turn an **abstract MST computation**

$$e : \text{MST } t \text{ (requires pre) (ensures post)}$$

into a **state-passing function**

$$s_0 : \text{state} \rightarrow \text{Pure } (t * s_1 : \text{state} \{ \text{rel } s_0 \ s_1 \}) \text{ (req. (pre } s_0))$$
$$(\text{ens. } (\lambda (x, s_1). \text{post } s_0 \ x \ s_1))$$

- For example, consider the **recalling** action

$$\text{recall} : p : (\text{state} \rightarrow \text{Type}) \rightarrow \text{MST unit (requires } (\lambda \_. \text{witnessed } p))$$
$$(\text{ensures } (\lambda s_0 \ s_1. s_0 = s_1 \wedge p \ s_1))$$

which we would like to **reduce** as

$$\text{reify (recall } p) \rightsquigarrow \lambda s_0. \text{return } ((), s_0)$$

but we cannot prove  $p \ s_0$  from **witnessed**  $p$  in the pure logic

# Appendix: Mon. reification and reflection

- We cannot simply turn an **abstract MST computation**

$$e : \text{MST } t \text{ (requires pre) (ensures post)}$$

into a **state-passing function**

$$s_0 : \text{state} \rightarrow \text{Pure } (t * s_1 : \text{state} \{ \text{rel } s_0 \ s_1 \}) \text{ (req. (pre } s_0)) \\ \text{(ens. } (\lambda (x, s_1). \text{post } s_0 \ x \ s_1))$$

- For example, consider the **recalling** action

$$\text{recall} : p : (\text{state} \rightarrow \text{Type}) \rightarrow \text{MST unit (requires } (\lambda \_ . \text{witnessed } p)) \\ \text{(ensures } (\lambda s_0 - s_1 . s_0 = s_1 \wedge p \ s_1))$$

which we would like to **reduce** as

$$\text{reify (recall } p) \rightsquigarrow \lambda s_0 . \text{return } ((), s_0)$$

but we cannot prove  $p \ s_0$  from  $\text{witnessed } p$  in the pure logic

# Appendix: Mon. reification and reflection

- In our POPL 2018 paper, we support reification and reflection by
  - indexing  $\text{MST}_{\text{state}, \text{rel}, \mathbf{b}}$  with a **boolean flag**  $\mathbf{b}$  (reifiable?), and
  - **guarding** the pre-postconditions of witness and recall with  $\mathbf{b}$so if  $\mathbf{b} = \text{true}$  then witness and recall are **logically no-ops**.
- This works but leads to **duplication** of pre- and postconditions!
- Instead, ongoing work is taking (hybrid) **modal logic** seriously

$$\mathbf{s}_0:\text{state} \rightarrow \text{Pure } (t * \mathbf{s}_1:\text{state}\{\text{rel } \mathbf{s}_0 \ \mathbf{s}_1\}) \ (\text{req. } (\text{pre } \mathbf{s}_0 \ @ \ \mathbf{s}_0)) \\ (\text{ens. } (\lambda (x, \mathbf{s}_1). \text{post } \mathbf{s}_0 \ x \ \mathbf{s}_1 \ @ \ \mathbf{s}_1))$$

where  $@$  is the **standard translation** of modal logic



# Appendix: Mon. reification and reflection

- In our POPL 2018 paper, we support reification and reflection by
  - indexing  $\text{MST}_{\text{state}, \text{rel}, \mathbf{b}}$  with a **boolean flag**  $\mathbf{b}$  (reifiable?), and
  - **guarding** the pre-postconditions of witness and recall with  $\mathbf{b}$so if  $\mathbf{b} = \text{true}$  then witness and recall are **logically no-ops**.
- This **works** but leads to **duplication** of pre- and postconditions!
- Instead, ongoing work is taking (hybrid) **modal logic** seriously

$$\mathbf{s}_0:\text{state} \rightarrow \text{Pure } (t * \mathbf{s}_1:\text{state}\{\text{rel } \mathbf{s}_0 \ \mathbf{s}_1\}) \ (\text{req. } (\text{pre } \mathbf{s}_0 \ @ \ \mathbf{s}_0)) \\ (\text{ens. } (\lambda (x, \mathbf{s}_1). \text{post } \mathbf{s}_0 \ x \ \mathbf{s}_1 \ @ \ \mathbf{s}_1))$$

where  $@$  is the **standard translation** of modal logic

# Appendix: Mon. reification and reflection

- In our POPL 2018 paper, we support reification and reflection by
  - indexing  $\text{MST}_{\text{state}, \text{rel}, \mathbf{b}}$  with a **boolean flag**  $\mathbf{b}$  (reifiable?), and
  - **guarding** the pre-postconditions of witness and recall with  $\mathbf{b}$so if  $\mathbf{b} = \text{true}$  then witness and recall are **logically no-ops**.
- This **works** but leads to **duplication** of pre- and postconditions!
- Instead, ongoing work is taking (hybrid) **modal logic** seriously

$$\mathbf{s}_0:\text{state} \rightarrow \text{Pure} \left( \mathbf{t} * \mathbf{s}_1:\text{state} \{ \text{rel } \mathbf{s}_0 \ \mathbf{s}_1 \} \right) \left( \text{req. } (\text{pre } \mathbf{s}_0 \ @ \ \mathbf{s}_0) \right) \\ \left( \text{ens. } (\lambda (x, \mathbf{s}_1). \text{post } \mathbf{s}_0 \ x \ \mathbf{s}_1 \ @ \ \mathbf{s}_1) \right)$$

where  $@$  is the **standard translation** of modal logic