

The following table explains each field on this display.

Table 10. Work with Source Overlay File display fields

Field Name	Description
Library	<p>Specifies the library that contains source overlay files you want to list and work with. Choose from the following:</p> <p>library name Specifies the name of the library that contains the source overlay files you want to work with.</p> <p>*USRLIBL Only libraries in the user portion of the job's library list are searched.</p> <p>*LIBL All the libraries in the user and system portions of the job's library list are searched. Note: This value may cause a long response time until the Work with Source Overlay Files display appears.</p> <p>*CURLIB The current library for the job is searched. If no current entry exists in the library list, library QGPL is used.</p> <p>*ALLUSR All "user-defined" libraries are searched. "User-defined" libraries include library QGPL, but exclude all other libraries with names that begin with the letter "Q." Note: This value may cause a long response time until the Work with Source Overlay Files display appears.</p> <p>*ALL All libraries in the system, including QSYS, are searched. Note: This value may cause a long response time until the Work with Source Overlay Files display appears.</p>
File	<p>Specifies that you want to work with all source overlay files in the library or a subset of source overlay files in the library. Choose from the following:</p> <p>source overlay file name Specifies a source overlay file name for a display with only that source overlay name in the list.</p> <p>generic name Specifies a partial name of the source overlay file name qualified by an asterisk (*) to display a specific subset of source overlay files. The generic name is the following format:</p> <p>ABC* Display a list of all source overlay files that begin with the characters ABC. For example, ABC, ABCD, or ABCTEST.</p> <p>*ALL Specifies *ALL to display all the source overlays in the specified library.</p>