Step 1 - Starting the Overlay Utility

Example Actions:

- 1. Type STRAFPU on the command line.
- 2. Press the Enter key.

The IBM Advanced Function Printing Utilities for iSeries menu appears.

```
IBM Advanced Function Printing Utilities for iSeries
Select one of the following:
  Overlay Utility
    1. Work with source overlays
    2. Work with source overlay files
  Print Format Utility
    11. Work with PFD definitions
   12. Work with PFD definition files
   13. Print database file member
   14. Print AFP Utilities tutorial
  Resource Management Utility
   21. Convert to page segment \  \  \, 
   22. Work with overlays
   23. Work with page segments
Selection or command
===> 2
F3=Exit F4=Prompt F9=Retrieve F12=Cancel F16=System main menu
(C) COPYRIGHT IBM CORP. 1991, 1996
```

From this display, you can select any function of AFP Utilities for iSeries.

The overlay utility functions are:

Option	Function
1	Work with source overlays
2	Work with source overlay files

Before you create a source overlay, you must create a source overlay file to store it.

Note: You need a library to create a source overlay. OVLLIB is used in the following example, but you may use the name of your library instead. If you do not have any libraries, create a library by typing CRTLIB OVLLIB on the command line and pressing the Enter key.