2028 MY MEDIUM DUTY F-650/F-750

September 14, 2026

Note to Medium Duty Order Guide users. The F-650/F-750 Order Guide is designed as a comparative featue code reference. The Medium Duty CANNOT be ordered via CONCEPS nor WEBDO. Ford Medium Duty MUST be ordered via the AccuQuote (AQ) software program.

For assistance with F-650/F-750 specifications, technical questions, order support or to obtain CVT software, please contact the Commercial Vehicle Hotline at 877-TRK-LINE (877-875-5463).

For additional sales support information be sure to use:

Ford Upfit Site: www.fordupfits.com/commercial
Ford E-Source Book: www.esourcebook.dealerconnection.com
Ford Body Builder: ***https://www.fordpro.com/en-us/upfit/bbas/***



2028 MY MEDIUM DUTY F-650 / F-750
ORDER GUIDE
September 14, 2026
PEP CODE 600A

MODEL INDEX

MAJOR PRODUCT CHANGES III

STANDARD EQUIPMENT ..... 1 - 4

OPTIONAL EQUIPMENT ..... 5 - 20

TIRE REFERENCE ..... 21 - 24

2028 MEDIUM DUTY F-650 / F-750
MAJOR PRODUCT CHANGES
September 14, 2026

MECHANICAL

- The TorqShift 10-speed transmission is now standard on gas F-650 and F-750 models. The TorqShift transmission will also come standard with a PTO Provision.
- The 7.3L gasoline engine will now include, as standard equipment, Hardened Engine Intake Valves, Exhaust Valves and Valve Seats previously included in the Gaseous Fuel Prep Pack. This means that any MY28 gas engine can be modified for CNG or LPG.
- The Gaseous Fuel Prep Package is removed from the program.
- The 7.3L engine will now come standard with water cooled manifolds. The 7.3L engine exhaust will now include two additional catalytic converters in line after the exhaust manifolds. The VIN engraving theft-deterrent option (62B) will inlcude the additional catalytic converter housings.
- **New rating for the 7.3L V8 gas engine for MY28 is 304Hp and 441 ft.-lbs. of torque**
- **Diesel engine models will be late availability.**

EXTERIOR

- The electric Back-Up Alarm (17M) now requires that the standard tail lamps are included on the vehicle.

OPTIONS CHANGED

- 19.5: X 7.5” wheels, both steel and aluminum (order codes 646, 64D 666, 66B, 66D and 60X), have been dropped from the program

INTERIOR / COMFORT

SAFETY / SECURITY

DRIVER ASSIST

FUNCTIONAL

- The four body builder switches, previously optional on gas models will now be standard.

PACKAGES

LATEST ORDER GUIDE UPDATES

- ***Medium Duty vehicles will no longer be equipped with an embedded modem. Customers who need connectivity for vehicle data can purchase a plug-in device from FordPro Intelligence.***
- **Ford Motor Company will not provide any exhaust or evaporative emissions certificate for 7.3L engines converted to use CNG or Propane fuel. Ford does not represent that a vehicle converted to use CNG will comply with all applicable U.S. or Canadian safety standards. It is the responsibility of either the mid-stage engine modifier or the final stage manufacturer (body-builder, installer, alterer or subsequent stage manufacturer) to determine that any vehicle converted to use CNG complies with U.S. Federal, California or Canadian exhaust and evaporative emission requirements, Federal fuel economy standards, U.S. and Canadian safety standards, labeling and any other requirements. Furthermore, once a 7.3L engine has been converted then the onus of support falls upon the engine modifier, not Ford.**
- **★Starting with MY28, F-650 and F-750 models will be available for commercial sale to Puerto Rico.**

PLEASE NOTE: Ongoing discussions with the California Air Resource Board has resulted in the continuation of the temporary suspension of the ban on diesel sales in the State of California for the 2027 calendar year. All diesel units, built after January 1, 2027 will be certified as 50-State Emission units and will be eligible to be sold and registered in California through the end of year. However, MY27 units built BEFORE August 3, 2026 (as well as MY25 and MY26 units) ARE NOT Eligible for sale in California.

★ = New for this model year

Ford PRO	Former Order Code	New Order Code	F-650 DIESEL STRAIGHT (Dock Height)	F-650 GAS STRAIGHT (Dock Height)	F-750 DIESEL STRAIGHT (Dock Height)	F-750 GAS STRAIGHT (Dock Height)
Standard Equipment by Model and Engine						
FRAME, GVWR AND GCWR						
Single Channel–Straight 'C' 12.64 SM, 50,000 PSI 632,000 RBM. High strength low alloy steel; 10.125" x 3.062" x 0.312" (257.2mm x 77.8mm x 8.0mm)	534	CWABM	•	•	—	—
Single Channel–Straight 'C' 15.14 SM, 80,000 PSI 1,211,200 RBM. High strength low alloy steel. 10.250" x 3.092" x 0.375" (260.4mm x 78.5mm x 9.5mm).	535	CWABP	—	—	•	•
Bumper Front–Black Full Width	766	CLFAD	•	•	•	•
Square Cut Frame Ends			•	•	•	•
26,000 Lbs. GVWR (may be optioned up to 29,000 Lbs.)			•	•	—	—
31,000 Lbs. GVWR (may be optioned up to 37,000 Lbs. with diesel engine or UP TO 33,000 Lbs. with gas engine)			—	—	•	•
37,000 Lbs. GCWR maximum			—	•	—	•
50,000 Lbs. GCWR maximum			•	—	•	—
FRONT AXLE AND SUSPENSION						
Axle, Front Non-Driving Dana D-850F 8,500 lb. Cap. (Includes Integral Power Steering)	43A	DYFBU	•	•	—	—
Axle, Front Non-Driving Dana E-1002I 10,000 lb. Cap. (Includes Integral Power Steering)	43N	DYFCC	—	—	•	•
8,500 lb. Parabolic Taper-leaf Springs (Includes Shock Absorbers)	61B	DYDBH	•	•	—	—
10,000 lb. Parabolic Taper Leaf Spring	61C	DYDBK	—	—	•	•
Shock Absorbers, Dual Front–Standard Duty, Double Acting			•	•	•	•
Wheel Seals, Front–Oil Lubricated, SKF ScotSeal® PlusXL seals			•	•	•	•
REAR AXLE AND SUSPENSION						
17,500 lb. Rear Axle Assembly–Single-Speed (Dana S17-140) Single Reduction	472	YFCAB	•	•	—	—
21,000 lb. Rear Axle Assembly–Single Speed, (Dana 21060S), Single Reduction	475	YFCAE	—	—	•	•
Spr Capacity-Rear 19,000 lb. Multi Leaf	68M	DZJEF	•	•	—	—
Spr Cap-Rear 21,000 lb. Multi Leaf	68P	DZJEH	—	—	•	•
Wheel Seals, Rear–Oil Lubricated, SKF ScotSeal® PlusXL seals			•	•	•	•
BRAKES AND BRAKE EQUIPMENT						
Hydraulic Brake System–Bosch HydroMax® w/Traction Control. Includes hand operated park brake lever.	67H	FDAAC	•	•	•	•
Electronic Stability Control - STANDARD: ***WITH STANDARD Hydraulic Brakes:*** Special Build sales code in support of ESC is not necessary for hydraulic brake units. ***WITH OPTIONAL Air Brakes:***. Requires the ADDITIONAL selection of a Special Build Requirement sales code (listed in OPTIONAL Section under Brakes). Final Upfit center of gravity sales code is necessary. ***Note: ESC may be deleted with option code 18A. See Brake Section in Options.***			•	•	•	•
Hill Start Assist – Requires Hydraulic Brakes			•	•	•	•
ENGINE AND ENGINE EQUIPMENT						
6.7L Power Stroke® V8 Turbo Diesel 270 Hp @ 2400 RPM, 800 lb.-ft. Torque @ 1500 RPM ***LATE AVAILABILTY**	99C	EN-YE	•	—	•	—
50-U.S. GALLON – Single, Left-hand, aluminum, rectangular (Standard on Regular Cab)	65B	GBGFJ	•	—	•	—
65-U.S. GALLON – Single, Left-hand, aluminum, rectangular (Standard on SuperCab and Crew Cab)	65E	GBGBK	•	—	•	—
Diesel Fuel–Cold Weather Anti-Gel Additive–Gold Eagle #2106			•	—	•	—
7.3L 2V DEVCT NA PFI V8 GAS – 441 ft-lbs @ 3750 rpm, and 304 hp @ 3750 rpm	99N	EN-JO	—	•	—	•
50-U.S. GALLON – Single, Left-hand, Steel (Regular Cab and SuperCab Only)	65A	GBGAR	—	•	—	•
60-U.S. GALLON – Single, Left-hand, Steel (Crew Cab Only)	65D	GBGBA	—	•	—	•
TRANSMISSION						
Ford TorqShift® HD 10-Speed Automatic WITH PTO Provision and Tow/Haul	44D	TR-GG	•	•	•	•
EXHAUST						
Under Cab, Right Side Outlet, Switchback-Style	91G	F2AAM	•	—	•	—
Single, Horizontal Muffler - Frame Mounted Right Side Back of Cab w/Catalytic Converter	91H	F2ABB	—	•	—	•
ELECTRICAL SYSTEM						
Extra Heavy-Duty Alternator – 12 Volt, 195 Amp			•	—	•	—
Battery – Two 12 Volt, 750 CCA (1500 CCA total), includes standard Steel Battery Box, RH Side under cab			•	—	•	—
Heavy-Duty Alternator – 12 Volt, 210 Amp			—	•	—	•
Battery – One 12-Volt 900 CCA, includes standard Steel Battery Box, RH Side under cab			—	•	—	•
Emergency Flasher–Four Way			•	•	•	•
Fuses, SAE–Blade-Type Smart Fuse Box			•	•	•	•
Aero Headlamps–High series, includes side marker lights with reflectors (front)			•	•	•	•
Taillamps–Two w/Integral Stop, Turn, Backup and License Plate bracket			•	•	•	•

Ford PRO	Former Order Code	New Order Code	F-650		F-750	
			DIESEL	GAS	DIESEL	GAS
			STRAIGHT (Dock Height)		STRAIGHT (Dock Height)	
Standard Equipment by Model and Engine						
ELECTRICAL SYSTEM continued						
Body Builder Wiring - At Back of Cab at Frame (includes sealed connectors for 2 ground circuits, with combined left/stop, combined right/stop, stop lamps, park lamps, back up lamps) (also includes 2 additional pass through wires to cab			•	•	•	•
FUEL TANKS						
50-U.S. Gallon Diesel – Single, Left-hand, aluminum, rectangular (Standard on Regular Cab)	65B	GBGFJ	•	—	•	—
65-U.S. Gallon Diesel – Single, Left-hand, aluminum, rectangular (Standard on SuperCab and Crew Cab)	65E	GBGBK	•	—	•	—
Diesel Fuel–Cold Weather Anti-Gel Additive–Gold Eagle #2106			•	—	•	—
50-U.S. Gallon Gas – Single, Left-hand, Steel (Regular Cab and SuperCab Only)	65A	GBGAR	—	•	—	•
60-U.S. Gallon Gas – Single, Left-hand, Steel (Crew Cab Only)	65D	GBGBA	—	•	—	•
SEATS						
30/0/30–Fixed Driver and Fixed Passenger with Consolette–Vinyl	88A	YCMEJ	•	•	•	•
SUPERCAB–REAR SEAT						
60/40–Rear Bench Seat with Bolster and Flip-up Cushion–Trim will match selected Driver seat material	87B	BYBBX	•	•	•	•
CREW CAB–REAR SEAT						
60/40–Rear Bench Seat with Flip-up Cushion and Fold-down Back–Trim will match selected Driver seat material	87C	BYBA9	•	•	•	•
CAB EQUIPMENT						
CAB EXTERIOR						
Doors–Two (Four with Super Cab or Crew Cab)			•	•	•	•
Front End Tilting Fiberglass Hood & Fenders Assembly – Tilt Type, Frame Mounted, Torsion Bar Assist (Incl. Integral noise & Inner splash shields and mud flaps)			•	•	•	•
Glass–Laminated Windshield, Solar Tint All-Around			•	•	•	•
Painted Grille – Composite	86A	BLDAC	•	•	•	•
Horn–Dual Note Electric–Level 2			•	•	•	•
Roof Mounted Clearance Lights – Amber Lenses, Clear bulbs			•	•	•	•
Tow Hooks, Front (2)–Frame Mounted, painted black			•	•	•	•
Window, Rear–Fixed			•	•	•	•
Windshield Wiper Control–Two-Speed Electric Intermittent w/Windshield Washers			•	•	•	•
MIRRORS						
Mirrors, Heated Dual Rectangular XL2020 Intergral Mirror, Sail Type, 96” Width, Manual Fold, Solid Black Finish	54M	BSHEK	•	•	•	•
CAB INTERIOR						
Air Conditioning, Manual–Includes Integral Heater and Defroster	572	AC--B	•	•	•	•
Air Registers–Molded-in-color with Positive Shut-Off, color coordinated trim			•	•	•	•
Assist Handles, Interior A Pillars–Driver and Passenger; All Cabs			•	•	•	•
Assist Handles, Interior B Pillars–Grab Handle, Driver and Passenger; Crew Cab Only			•	•	•	•
Auxiliary Power Point – In Instrument Panel, Two: One Dual USB, one 12V			•	•	•	•
4 Body Builder Switches–mounted in Center I/P With connector access located in engine compartment; Amperages vary by switch: Inlcudes 10, 15, 25, 25	59F	JZJAC	•	•	•	•
Back Panel Trim Cover			•	•	•	•
Coat Hook–RH/LH Color Keyed			•	•	•	•
Cruise Control–Steering Wheel Mounted Controls			•	•	•	•
Demisters–LH & RH Side Windows			•	•	•	•
Dome Lamp–Rear Mounted with integral map reading lights Auxiliary Power Point – In Instrument Panel, Two			•	•	•	•
Door Trim – Color Coordinated Molded w/Grab Handle	59F	JZJAC	•	•	•	•
Armrest/grab handleBack Panel Trim Cover			•	•	•	•
Floor Covering–Black VinylCoat Hook–RH/LH Color Keyed			•	•	•	•
Gauge Cluster, Diesel–with electronic speedometer (MPH/KPH), includes oil pressure, coolant temperature, DEF gauge, fuel gauge, tachometer, and indicator lights. Also included is enhanced 3-button Message Center with odometer, trip odometer, distance to empty for fuel, average fuel economy, hour meter and warning messages. Transmission temperature in message center.Cruise Control–Steering Wheel Mounted Controls			•	—	•	—
Gauge Cluster, Gas–with electronic speedometer (MPH/KPH) includes oil pressure, coolant temperature, fuel gauge, tachometer and indicator lights. Also included is enhanced 3-button Message Center with odometer, trip odometer, distance to empty for fuel, average fuel economy, hour meter, and warning messages. Transmission temperature in message center.Demisters–LH & RH Side Windows			—	•	—	•
Glove Box–Instrument Panel, RH			•	•	•	•
Headliner–Color Coordinated, Molded, Cloth			•	•	•	•
Instrument Panel–Color Coordinated With Color Coordinated Accents			•	•	•	•
Oil Maintenance Minder			•	•	•	•
Radio AM/FM Stereo–With 2 speakers, includes USB input, clock display, and Bluetooth	588	IBAAF	•	•	•	•
Safety Belts–Belt Minder (Chime & Flashing Warning Light on Instrument Panel if Belts Not Buckled)			•	•	•	•

Ford PRO	Former Order Code	New Order Code	F-650		F-750	
			DIESEL	GAS	DIESEL	GAS
			STRAIGHT (Dock Height)		STRAIGHT (Dock Height)	
Standard Equipment by Model and Engine						
CAB INTERIOR continued						
Safety Belts–Color Coordinated, All Position, Includes Fixed D-Rings (Regular Cab)			●	●	●	●
Safety Belts–Color Coordinated, All Position, Includes Front Seat Adjustable D-Rings (SuperCab or Crew Cab)			●	●	●	●
Scuff Plates			●	●	●	●
Speedometer – Non Metric (MPH) – US Market			●	●	●	●
Metric Speedometer – (KPH) - Canada market			●	●	●	●
Steering Column – Tilt / Telescoping			●	●	●	●
Steering Wheel–Black PVC with integral cruise control switches, includes audio controls			●	●	●	●
Tachometer – Electric			●	●	●	●
Turn Signal–Multifunction Switch with Windshield Wiper (1-7 Variable Speed, Hi, Low), Windshield Washer, L/R Turn Signal; Self Cancel, L/R Lane Change, Hazard, Flash-To-Pass, High Beam			●	●	●	●
Automatic Head Lamps / Running Lamp Activation			●	●	●	●
Turn Signal Switch, Self-Canceling–Multifunction Switch			●	●	●	●
Turn Signal Switch, Signal Stat, Non-Canceling			●	●	●	●
Sunvisor, Single Driver–Vinyl			●	●	●	●
Sunvisor, Single Passenger–Vinyl With Mirror			●	●	●	●
WHEELS, FRONT						
22.5x8.25–Steel disc, 10-hole–hub piloted, 5 hand hold, powder-coated white	643	D2HAU	●	●	●	●
TIRES, FRONT						
11R22.5H Goodyear® Fuel Max RSA	T2A	YDJCQ	●	●	●	●
WHEELS, REAR						
22.5x8.25–Steel disc, 10-hole–hub piloted, 5 hand hold, powder-coated white	663	D4PCE	●	●	●	●
TIRES, REAR						
11R22.5H Goodyear Fuel Max RSA	R2A	YDKDX	●	●	●	●
PAINT						
Body Color Available–Agate Black (UM), Oxford White (YZ), Race Red (PQ), School Bus Yellow (B1), Iconic Silver (JS)			●	●	●	●
Chassis Color – Black			●	●	●	●
Paint Process (cab body)–Environmentally friendly,"3-Wet System"			●	●	●	●

2028 MEDIUM DUTY F-650/F-750
OPTIONAL EQUIPMENT

Ford PRO	Former Order Code	New Order Code	F-650 DIESEL STRAIGHT (Dock Height)	F-650 GAS STRAIGHT (Dock Height)	F-750 DIESEL STRAIGHT (Dock Height)	F-750 GAS STRAIGHT (Dock Height)
		Regular Cab	F6D	F6A	F7D	F7A
		Super Cab	X6D	X6A	X7D	X7A
		Crew Cab	W6D	W6A	W7D	W7A
01- FRAME, FRAME EQUIPMENT AND GVWR DERATES						
Single Channel–Straight 'C' 12.64 SM, 50,000 PSI, 632,000 RBM. High strength low alloy steel; 10.125" x 3.062" x 0.312" (257.2mm x 77.8mm x 8.0mm)	534	CWABM	S	S	—	—
Single Channel–Straight 'C' 10.75 SM, 80,000 PSI, 860,000 RBM. High strength low alloy steel; 9.125" x 3.062" x 0.312" (232.8mm x 77.8mm x 7.9mm).	533	CWABL	O	O	—	—
Single Channel–Straight 'C' 14.18 SM, 120,000 PSI, 1,701,600 RBM. Heat treated alloy steel; 10.125" x 3.580" x 0.312" (257.2mm x 90.9mm x 8.0mm)	536	CWABN	O	O	O	O
Single Channel–Straight 'C' 15.14 SM, 80,000 PSI, 1,211,200 RBM. High strength low alloy steel. 10.250" x 3.092" x 0.375" (260.4mm x 78.5mm x 9.5mm).	535	CWABP	O	O	S	S
Single Channel–Straight 'C' 16.98 SM, 120,000 PSI, 2,037,600 RBM. Heat treated alloy steel; 10.250" x 3.610" x 0.375" (260.4mm x 91.66mm x 9.5mm). ***Not available with Crew Cab and requires 281" Wheelbase.**	538	CWAAH	O*	O*	O	O
Single Channel–Straight 'C' 20.11 SM, 120,000 PSI, 2,413,200 RBM. Heat treated alloy steel; 10.375" x 3.705" x 0.438" (263.5mm x 94.1mm x 11.1mm).	539	CWABQ	—	—	O	O
FRAME REINFORCEMENT–Outer "C" Channel Reinforcement–120,000 PSI. 29.84 SM; 3,580,800 RBM (combined RBM rating). Heat treated alloy steel; 10.813" x 3.892" x 0.312"; (274.6 mm x 98.9 mm x 8.0 mm). Requires Frame 536	41R	CWEAB	—	—	O	O
Frame Rail Drilling–Factory pre-drilled holes in Frame Rails to support Special Fuel Tanks for a ***Roush*** CNG/LPG Gaseous Prep Conversion. Saves time, cost, transportation while providing accuracy for the mount.	19C	CWBAD	—	O	—	O
Frame Rail Drilling–Factory pre-drilled holes in frame rails to support aftermarket install of Hydraulic pump system for EZ-TRAC 4x4 conversion. **Not available with Super Cab** ***Not available with 19.5 tires / wheels**	19D	CWBAF	O*	—	O	—
Frame Rail Drilling–Factory pre-drilled holes in frame rails to support aftermarket install of transfer case brackets for a Meritor 4x4 conversion. **Not available with SUPER CAB** ***Not available with 19.5 tires / wheels** Requires under cab exhaust (91G) **Not available with FRAME REINFORCEMENT (41R)** **Not available with 115 dual tank (65F)** **Not available with 10.75 S/M-80K PSI frame (533)**	19E	CWBAE	O*	—	O	—
Integral Front Frame Extension, 20" in front of grille–Requires Frame 536 on 650 Straight Frame or Frame 536, 538, 539 or 536 with 41R on 750 Straight Frame. Includes (76X) Bumper Delete and Includes Fixed Grille (86B).	532	CWLAB	O	O	O	O
Bumper, Front–Full Width, Chrome Plated Steel. Included with Exterior Appearance Group (90E)	765	CLFAE	O/I	O/I	O/I	O/I
Bumper, Front Delete (Standard with Front Frame Extension 532) Also Deletes the Mounting Brackets	76X	CLFAA	O	O	O	O
Bumper Extension, Front – 3" Extension	76F	CLHAB	O	O	O	O
Tow Hooks -Delete	76Y	C1UAA	O	O	O	O
Special Rating GVWR – Limited to 25,999 lb. Only Available to GAWR Combinations that EXCEED 26,000 lbs	18D	AA3BM	O	O	O	O
Special Rating GVWR – Limited to 33,000 lb. GVWR, Only Available to GAWR Combinations that EXCEED 33,000 lbs. Not Available when 43P Front Axle and 47X Rear Axle are used together.	18G	AA3BP	—	—	O	—
Special Rating GVWR – 22,000 lb. GVWR. Only available with F-650 models with combination of 10.75 SM frame (533), 8,500 lb. Front Axle (43A), 17,500 lb. Rear Axle (472), 19,500 lb. spring suspension (68M) and 19.5" wheels and tires.	18B	AA3BQ	O	O	—	—
Special Rating GVWR – 24,000 Lb. GVWR. Only available with F-650 models with combination of 10.75 SM frame (533), 8,500 lb. Front Axle (43A), 17,500 lb. Rear Axle (472), 19,500 lb. spring suspension (68M) and 19.5" wheels and tires.	18R	AA3BR	O	O	—	—
02 – FRONT AXLE AND SUSPENSION						
Axle, Front Non-Driving Dana D-850F 8,500 lb. Cap. (Includes Integral Power Steering)	43A	DYFBU	S	S	—	—
Axle, Front Non-Driving Dana E-1002I 10,000 lb. Cap. (Includes Integral Power Steering)	43N	DYFCC	O	O	S	S
Axle, Front Non-Driving (Dana E-1202I), I-Beam-Type, 12,000# Capacity	43P	DYFCJ	—	—	O	O
Axle, Front Non-Driving Dana 14,000# Capacity	43D	DYFCQ	—	—	O	—
TAPER-LEAF SPRINGS, PARABOLIC (INCLUDES SHOCK ABSORBERS)						
8,500 lb., Parabolic Taper-Leaf Springs (Available with 43A Only)	61B	DYDBH	S	S	—	—
10,000 lb., Parabolic Taper Leaf Spring (Available with 43A or 43N)	61C	DYDBK	O	O	S	S
12,000 lb., Parabolic Taper-Leaf Springs (Available with 43N and 43P)	61D	DYDBL	O	O	O	O
13,200 lb., Parabolic Taper Leaf Springs (Available on 43P and 43D)	61E	DYDBQ	—	—	O	O
14,000 lb., Parabolic Taper Leaf Springs (Available on 43D)	61F	DYDCB	—	—	O	—
Stabilizer Bar, Front	15S	DYKAB	O	O	O	O
Lube, Front Axle–EmGard 50W, Synthetic Oil	60A	DYLAD	O	O	O	O

2028 MEDIUM DUTY F-650/F-750
OPTIONAL EQUIPMENT

Ford PRO	Former Order Code	New Order Code	F-650 DIESEL STRAIGHT (Dock Height)	F-650 GAS STRAIGHT (Dock Height)	F-750 DIESEL STRAIGHT (Dock Height)	F-750 GAS STRAIGHT (Dock Height)
		Regular Cab	F6D	F6A	F7D	F7A
		Super Cab	X6D	X6A	X7D	X7A
		Crew Cab	W6D	W6A	W7D	W7A
03 – REAR AXLE AND SUSPENSION						
17,500 lb. Dana S17-140 Single-Speed Open–Gentech Quiet Gears	472	YFCAB	S	S	—	—
19,000 lb. Dana S19-140 Single-Speed Open–Gentech Quiet Gears	474	YFCAC	O	O	—	—
21,000 lb. Dana 21060S Single-Speed Open–Hypoid Gear	475	YFCAE	—	—	S	S
21,000 lb. Dana 21060D Single-Speed Locking–Pneumatic Driver Controlled	476	YFCAF	—	—	O	—
23,000 lb. Dana S23-172 Single-Speed Open–Hypoid Gear	479	YFCAH	—	—	O	—
23,000 lb. Dana S23-172D Single-Speed Locking–Pneumatic Driver Controlled	47P	YFCAJ	—	—	O	—
26,000 lb. Dana S26-190 Single-Speed Open–Hypoid Gear **Not Available with (43N) 10,000# Front Axle**	47X	YFCAK	—	—	O	—
MULTI-LEAF SPRINGS – VARI-RATE SUSPENSION						
19,000 lb. Cap for 17,500 lb. and 19,000 lb. Rear Axles (Includes 4500 lb. Auxiliary Rubber Spring)	68M	DZJEF	S	S	—	—
21,000 lb. Cap for 19,000 and 21,000 lb. Rear Axles (Includes 4500 lb. Auxiliary Rubber Spring)	68P	DZJEH	O	O	S	S
23,000 lb. Cap for 21,000 lb., 23,000 lb. and 26,000 Rear Axles (Includes 4500 lb. Auxiliary Rubber Spring)	68R	DZJEL	—	—	O	O
31,000 lb. Cap for 23,000 lb. and 26,000 lb. Rear Axles (Includes 4500 lb. Auxiliary Rubber Spring)	68T	DZJE9	—	—	O	—
SHOCKS AND LUBRICATION						
Shock Absorbers, Rear–Double Acting (Included in Air Ride Suspension) **Not Available with Relocated Brake Chambers 62F**	961	D1GAI	O	O	O	O
Lube, Rear Axle–EmGard 75W-90, Synthetic Oil	607	EJ2AC	O	O	O	O
04 – BRAKES – BRAKE EQUIPMENT						
Air Brakes (4 WHEEL DRUM) with Traction Control–Straight Truck with 16.5"x7.0" " / 15.0"x8.63"* Rear Pads–22.5" / 19.5"* Wheels; Meritor Q-Plus with ABS (Bendix Anti-Lock Brake System) (4-Channel) (Includes 15" x 4" Front Brakes, Dual Direct Reading Air Pressure Gauges, Brake Lines Color Coded Nylon, Bendix 13.2 CFM Capacity Air Compressor, Instrument Panel Mounted Yellow Knob Parking Brake Control Valve, Automatic Slack Adjusters Front and Rear, Two Rear Spring Parking Air Brake Chambers Mounted on Front of Rear Axle, Three Drain Valve(s) and Two Air Tanks. (Not recommended with Hi-Rail Train System applications) -- Includes 62D Air Dryer (Bendix AD/IS) with Heater–Mounted Inboard Left Frame Rail *Requires RNDM (Less Park on gear shift), Deletes hand operated park brake lever **#158" wheel base not available with 19.5" tires combined with airbrakes**	67A	FDAAB	O*#	—	O	—
Air Brakes (4 WHEEL DISC) with Traction Control – Includes 62D Air Dryer (Bendix AD/IS) with Heater–Mounted Inboard Left Frame Rail -- Deletes hand operated park brake lever	67D	FBAAD	—	—	O	—
Air Brakes (FRONT DISC / REAR DRUM) with Traction Control–Straight Truck xxx, Bendix 13.2 CFM Capacity Air Compressor, Instrument Panel Mounted Yellow Knob Parking Brake Control Valve, Includes 62D Air Dryer (Bendix AD/IS) with Heater–Mounted Inboard Left Frame Rail *Requires RNDM (Less Park on gear shift) -- Deletes hand operated park brake lever #Requires 10K front axle ***Not available with 19.5" tires**	67C	FBAAC	O*#	—	O	—
Electronic Stability Control DELETE. Deletes the standard ESC feature **Not available with Driver Assist Technology (87H or 87A)**	18A	FENAA	O	O	O	O
Special Build Requirement–LOW–38" to 48" Center of Gravity (Requires Air Brakes). **Not available with ESC Delete (18A)**	98B	AADAB	O	—	O	—
Special Build Requirement–MEDIUM–48" to 58" Center of Gravity (Requires Air Brakes). **Not available with ESC Delete (18A)**	98C	AADAC	O	—	O	—
Special Build Requirement –HIGH–58"–68" Center of Gravity (Requires Air Brakes). **Not available with ESC Delete (18A)**	98E	AADAE	O	—	O	—
Special Build Requirement- TANKER HIGH–58" to 68" Center of Gravity (Requires Air Brakes). **Not available with ESC Delete (18A)**	98F	AADAF	O	—	O	—
Special Build Requirement-–TANKER MEDIUM–48" to 58" Center of Gravity (Requires Air Brakes). **Not available with ESC Delete (18A)**	98J	AADAJ	O	—	O	—
Air Brake Chambers, Spring–Relocated to Rear of Axle for Maximum Ground Clearance **Not available with 961 Rear Shock Absorbers** *(Standard with 158" and 176" WB Regular Cab when Air Brakes [67A] are ordered with 91B Torpedo-style exhaust–Not Available with Hydraulic Brakes) ** Required with 158" WB Regular Cab or 167" WB Super Cab when using 91B Torpedo-style Exhaust **(not availble with Air Disc Brakes 67D)**	62F	FALAC	O*	—	O*	—
Air Dryer (Bendix AD/IS) with Heater–Mounted Left Frame Rail (for Hydraulic brake applications that include stand alone engine air compressor)	62D	FDVAC	O	—	O	—
Trailer Connection Socket – Hydraulic Brake – Combinbed Stop / Turn lamp wiring; 7-way–Mounted at Rear of Frame For Combined Trailer Stop, Tail, Turn, Marker Light Circuits; Includes Electric Trailer Brake Accommodation Package with Cab Connections for Mounting Customer Installed Electric Brake Unit. Available with (Standard) Combined Back of Cab Body Builder Wiring or available with (59C) Combined End of Frame Body Builder Wiring. ***Not Available with 281" WB.**	152	C2BAS	O*	O*	O	O

2028 MEDIUM DUTY F-650/F-750
OPTIONAL EQUIPMENT

Ford PRO	Former Order Code	New Order Code	F-650		F-750	
			DIESEL	GAS	DIESEL	GAS
			STRAIGHT (Dock Height)		STRAIGHT (Dock Height)	
		Regular Cab	F6D	F6A	F7D	F7A
		Super Cab	X6D	X6A	X7D	X7A
		Crew Cab	W6D	W6A	W7D	W7A
04 – BRAKES – BRAKE EQUIPMENT continued						
Trailer Connection Socket – Hydraulic Brake – Separate Stop / Turn lamp wiring; 7-way – Mounted at Rear of Frame For Separate Trailer Stop, Tail, Turn, Marker Light Circuits; Includes Electric Trailer Brake Accommodation Package with Cab Connections for Mounting Customer Installed Electric Brake Unit (Available with Hydraulic Brake Straight Truck) Available with (59D) Separate Back of Cab Body Builder Wiring or available with (59E) Separate End of Frame Body Builder Wiring. *Not Available with 281" WB.	154	C2BAT	O *	O *	O	O
Trailer Air Brake Package–Includes Air Lines to rear of frame, Hand Control Valve and Tractor Protection Valve (Requires Trailer Connection Socket 7-Way, Code 159 or 157) (Requires Air Brakes). Requires 18A ESC Delete.	158	C1MAC	O	—	O	—
Trailer Connection Socket – Air Brake – Comined Stop / Turn lamp wiring; 7-way– Mounted at Rear of Frame, for Combined Trailer Stop, Tail, Turn; Available with Air Brake Straight Truck. Available with Standard Combined Back of Cab Body Builder Wiring or available with (59C) Combined End of Frame Body Builder Wiring. Requires 18A ESC Delete. ***Not Available with 281" WB**	159	C2BAU	O*	—	O	—
Trailer Connection Socket – Air Brake – Seperate Stop / Turn lamp wiring; 7-way – Mounted at Rear of Frame, for Separate Trailer Stop, Tail, Turn, Marker Light Circuits; Compatible with Trailers that have Amber or Side Turn Lights with Separate Stop/Turn wiring. Available with Air Brakes Straight Truck. Available with (59D) Back of Cab Body Builder Wiring or available with (59E) Separate End of Frame Body Builder Wiring. Requires 18A ESC Delete. ***Not Available with 281" WB**	157	C2BAV	O*	—	O	—
05 – ENGINES – ENGINE EQUIPMENT						
6.7L Power Stroke® V8 Turbo Diesel 270 Horsepower @ 2400 RPM, 800 lb.-ft. Torque @ 1500 RPM **LATE AVAILABILITY**	99C	EN-YE	S	—	S	—
6.7L Power Stroke® V8 Turbo Diesel 300 Horsepower @ 2500 RPM, 850 lb.-ft. Torque @ 1500 RPM **LATE AVAILABILITY**	99E	EN-YF	O	—	O	—
6.7L Power Stroke® V8 Turbo Diesel 330 Horsepower @ 2600 RPM, 900 lb.-ft. Torque @ 1500 RPM **LATE AVAILABILITY**	99X	EN-YG	O	—	O	—
50-State Emissions Certification (for California registry, includes Clean Idle lable on vehicle and "Certified For Sale In California" typed on COV	425	DGAAE	S	—	S	—
7.3L 2V DEVCT NA PFI V8 GAS – 441 ft-lbs @ 3750 rpm, and 304 hp @ 3750 rpm	99N	EN-JO	—	S	—	S
Air Compressor Bendix–13.2 CFM Capacity – Required stand-alone air source with options that require air source with Hydraulic Brakes *Required with seats 88N, 88P, 88G, 88H, 88E, 88Fwhen ordered without air brakes.	62G	FDSAW	O*	—	O*	—
Engine Block Heater (Phillips) (120 Volt/750 Watt) / (Diesel engine block heaters will also come with a removable grill cover, this option includes a front grille cover to be used in cold weather situations.)	41H	DEBAF	O	O	O	O
Active Regen Control – Allows Driver to Inhibit Automatic Regen until Regen can be performed in a Safe location.	98R	A6YAC	O	—	O	—
Speed Limiter–65 mph	916	GTCAM	O	O	O	O
Speed Limiter–70 mph	917	GTCAH	O	O	O	O
Timer–Engine Idle Shutdown, 5 minutes	94A	DCEAE	O	O	O	O
Timer–Engine Idle Shutdown, 10 minutes	94B	DCEAF	O	O	O	O
Timer–Engine Idle Shutdown, 15 minutes	94C	DCEAG	O	O	O	O
Timer–Engine Idle Shutdown, 20 minutes	94D	DCEAH	O	O	O	O
06 – TRANSMISSION						
Ford TorqShift® HD 10-Speed Automatic WITH PTO Provision and Tow/Haul	44D	TR-GG	S	S	S	S
07 – EXHAUST						
Exhaust System**–**Single Horizontal Muffler, Catalytic Converter, Frame-Mounted, Right-Hand, Back of Cab, Between Frame Rails. Downward Facing Outlet Tip	91H	F2ABB	—	S	—	S
Exhaust System–Switchback-Style Under Cab Outside Frame Rails, Right Side Outlet–Single, Horizontal Muffler, Rear Facing Downward Discharge	91G	F2AAM	S	—	S	—
Exhaust System–Torpedo-Style Back Of Cab, Right-Side Outlet**–**Single, Horizontal Muffler/Pipe, Inline, Right-Side Exhaust with Underbody Exit in Front of Axle Restricted to Regular Cab only **Not Available with Hydraulic Brakes or Air Brakes on 158" or 176"WB Regular Cab**.	91B	F2AAQ	O	—	O	—
Exhaust System–Switchback-Style Under Cab, Vertical Outlet, Right Side–Single, Horizontal Muffler, Right Side, Under Cab, Outside of Frame Rail with Vertical Exhaust, Passenger Side Rear Corner with Heat Shield and Turn-Out. Not Available with 54F Trailer Tow mirror ***Intrudes 2" into clean CA***	91D	F2ABE	O	—	O	—

2028 MEDIUM DUTY F-650/F-750
OPTIONAL EQUIPMENT

	Former Order Code	New Order Code	F-650		F-750	
			DIESEL	GAS	DIESEL	GAS
			STRAIGHT (Dock Height)		STRAIGHT (Dock Height)	
Regular Cab			F6D	F6A	F7D	F7A
Super Cab			X6D	X6A	X7D	X7A
Crew Cab			W6D	W6A	W7D	W7A
08 – ELECTRICAL – ALTERNATOR–BATTERY						
ALTERNATOR (12-VOLT)						
Dual Heavy Duty Alternators–357 Amp. Capacity (200+157 Amp Alternators)	17D	HUACA	O	—	O	—
Dual Heavy Duty Alternators–397 Amp. Capacity (240+157 Amp Alternators)	17B	HUACB	—	O	—	O
Alternator–Extra Heavy Duty 12-volt, 240-amp.	17A	HUAA4	O	—	O	—
Alternator–Extra/Extra Heavy Duty 12-volt, 240-amp.	17E	HUAAE	—	O	—	O
Jump Start Stud–Remote Mounted (Not Available with Temporary Mount batteries)	55M	DEGAE	O	O	O	O
BATTERY (12-VOLT)						
Battery, 12-volt, Motorcraft (includes steel battery box) Single, 900 CCA		HTBBS	—	S	—	S
Two, 750 CCA (1500 CCA Total)		HTBBT	S	—	S	—
Two, 900 CCA (1800 CCA Total)	63B	HTBBR	O	O	O	O
Three, 900 CCA (2700 CCA Total)	63D	HTBBQ	O	—	O	—
LIGHTING						
Roof Marker/Clearance Lights–Clear Lenses, Amber Bulbs, 5 Lights **Note:** Cab is equiped with amber lens with clear bulb lamps standard. Use this option for clear lense fleet requirements.	164	JBPAJ	O	O	O	O
Tail Lights Delete–Deletes Stop, Turn, Tail and Backup Lights (Does Not Omit Cable Harness to End of Frame)	55X	JDAAA	O	O	O	O
Daytime Running Lamps (not configurable) (Standard in Canada)	962	JBCAB	O/S	O/S	O/S	O/S
BODY BUILDER WIRING						
Body Builder Wiring–At Back of Cab (Includes Sealed Connectors for 2 Ground Circuits with Combined Left/Stop, Combined Right/Stop, Stop Lamps, Park Lamps, Back Up Lamps) (Also Includes 2 Additional Pass Through Wires to Cab) (Available with Hydraulic Brakes or Air Brakes) ***Not Available with (154) Hydraulic Brake Trailer Connection** ****Not available with (157) Air Brake Trailer Connection**		J1AAB	S**	S*	S**	S*
Body Builder Wiring–At End of Frame (Includes Sealed Connectors for 2 Ground Circuits with Combined Left/Stop, Combined Right/Stop, Stop Lamps, Back Up Lamps) (Also Includes 2 Additional Pass Through Wires to Cab). ***Not Available with (19B) Beverage Package or (154) Hydraulic Brake Trailer Connection** ****Not available with (157) Air Brake Trailer Connection**	59C	J1AAC	O**	O*	O**	O*
Body Builder Wiring–At Back of Cab Includes Sealed Connectors for 2 Ground Circuits, with Separate Left/Stop, Separate Right/Stop, Stop Lamps, Backup Lamps) (Also Includes 2 Additional Pass Through Wires to Cab) ***Not Available with (19B) Beverage Package or (152) Hydraulic Brake Trailer Connection** ****Not availabel with (159) Air Brake Trailer Connection**	59D	J1AAF	O**	O*	O**	O*
Body Builder Wiring–At End of Frame (Includes Sealed Connectors for 2 Ground Circuits, with Separate Left/Stop, Separate Right/Stop, Stop Lamps, Backup Lamps) (Also Includes 2 Additional Pass Through Wires to Cab) ***Not Available with (19B) Beverage Package or (152) Hydraulic Brake Trailer Connection** ****Not availabel with (159) Air Brake Trailer Connection**	59E	J1AAG	O**	O*	O**	O*
Back-up Alarm–Electric, 102 dBA	17M	HLDAB	O	O	O	O
Voltmeter	16V	HFCAB	O	O	O	O
Vehicle Integration System 1.0	86M	JRSAB	O	O	O	O
09–FUEL TANKS						
GASOLINE ENGINE						
50-U.S. GALLON – Single, Left-hand, Steel (Regular Cab and SuperCab Only)	65A	GBGAR	—	S	—	S
60-U.S. GALLON – Single, Left-hand, Steel (Standard on Crew Cab)	65D	GBGBA	—	S/O	—	S/O
DIESEL ENGINE						
50-U.S. GALLON–Left-hand, aluminum, rectangular (Regular Cab Only)	65B	GBGFJ	S	—	S	—
65-U.S. GALLON–Left-hand, aluminum, rectangular (Standard on SuperCab and Crew Cab Only; Optional on Regular Cab Only)	65E	GBGBK	S/O	—	S/O	—
115-U.S. GALLON–Left-hand 65-gal.; right-hand 50-gal., aluminum, rectangular	65F	GBGA4	O	—	O	—

OPTIONAL EQUIPMENT

	Former Order Code	New Order Code	F-650 DIESEL STRAIGHT (Dock Height)	F-650 GAS STRAIGHT (Dock Height)	F-750 DIESEL STRAIGHT (Dock Height)	F-750 GAS STRAIGHT (Dock Height)
Regular Cab			F6D	F6A	F7D	F7A
Super Cab			X6D	X6A	X7D	X7A
Crew Cab			W6D	W6A	W7D	W7A
10–SEATS						
30/0/30–Fixed Driver and Fixed Passenger with Consolette–Vinyl	88A	YCMEJ	S	S	S	S
30/0/30–Fixed Driver and Fixed Passenger with Consolette–Cloth	88B	YCMD2	O	O	O	O
30/70–Fixed Driver and Fixed 2-Passenger Bench–Vinyl	881	YCMEV	O	O	O	O
30/70–Fixed Driver and Fixed 2-Passenger Bench–Cloth	882	YCMEH	O	O	O	O
30/0/30–Air Ride Driver (integral air pump) and Fixed Passenger with Consolette – Vinyl **Not Available with SuperCab** **Not Available with Air Brakes or Air Compressor (62G)**	88R	YCMER	O	O	O	O
30/0/30–Air Ride Driver (integral air pump) and Fixed Passenger with Consolette – Cloth **Not Available with SuperCab or Crew Cab** **Not Available with Air Brakes or Air Compressor (62G)**	88S	YCMED	O	O	O	O
30/70–Air Ride Driver (integral air pump) and Fixed 2-Passenger Bench – Vinyl **Not Available with SuperCab** **Not Available with Air Brakes or Air Compressor (62G)**	88L	YCMEP	O	O	O	O
30/70–Air Ride Driver (integral air pump) and Fixed 2-Passenger Bench – Cloth **Not Available with SuperCab** **Not Available with Air Brakes or Air Compressor (62G)**	88M	YCMEB	O	O	O	O
30/0/30–Air Ride Driver (integral air pump) and Air Ride Passenger (integral air pump) with Consolette – Vinyl **Not Available with SuperCab or Crew Cab** **Not Available with Air Brakes or Air Compressor (62G)**	88J	YCMEN	O	O	O	O
30/0/30–Air Ride Driver (integral air pump) and Air Ride Passenger (integral air pump) with Consolette – Cloth **Not Available with SuperCab or Crew Cab** **Not Available with Air Brakes or Air Compressor (62G)**	88K	YCMEA	O	O	O	O
30/0/30–Air Ride Driver (external air source) and Fixed Passenger with Consolette – Vinyl **Not Available with SuperCab or Crew Cab** Requires either Air Brakes or Air Compressor (62G)	88N	YCMEQ	O	—	O	—
30/0/30–Air Ride Driver (external air source) and Fixed Passenger with Consolette – Cloth **Not Available with SuperCab or Crew Cab** Requires either Air Brakes or Air Compressor (62G)	88P	YCMEC	O	—	O	—
30/70–Air Ride Driver (external air source) and Fixed 2-Passenger Bench – Vinyl **Not Available with SuperCab** Requires either Air Brakes or Air Compressor (62G)	88G	YCMEM	O	—	O	—
30/70–Air Ride Driver (external air source) and Fixed 2-Passenger Bench – Cloth **Not Available with SuperCab** Requires either Air Brakes or Air Compressor (62G)	88H	YCMD8	O	—	O	—
30/0/30–Air Ride Driver (external air source) and Air Ride Passenger (external air source) with Consolette – Vinyl **Not Available with SuperCab and CrewCab** Requires either Air Brakes or Air Compressor (62G)	88E	YCMEL	O	—	O	—
30/0/30–Air Ride Driver (external air source) and Air Ride Passenger (external air source) with Consolette – Cloth **Not Available with SuperCab and CrewCab** Requires either Air Brakes or Air Compressor (62G)	88F	YCMD4	O	—	O	—
40/20/40–Fixed Driver and Fixed Passenger with unique 20% Fold-Down Console–Vinyl	88Y	YCMEU	O	O	O	O
40/20/40–Fixed Driver and Fixed Passenger with unique 20% Fold-Down Console–Cloth	88Z	YCMEG	O	O	O	O
SUPERCAB OR CREW CAB–REAR SEAT						
Rear Seat–Delete	87X	BYBAA	O	O	O	O
11 – CAB EQUIPMENT						
SAFETY / ANTI-THEFT						
Driver Assist Technology Package, Hydraulic Brake. Includes Forward Collision Warning, Lane Departure Warning, Auto High Beam Control **Not available with 18A ESC Delete** **Not available with 20" frame extension (532) or bumper delete (76X)**	87H	FBFAC	O	O	O	O
Driver Assist Technology Package, Air Brake. (w/Bendix Wingman Advanced™). Includes Forward Collision Warning, Lane Departure Warning, Adaptive Cruise Control, Auto High Beam Control **Not available with 18A ESC Delete** **Not available with Radio Delete (58B) or Radio Prep Package (58P) or20" frame extension (532) or bumper delete (76X)**	87A	J4ZAB	O	—	O	—

Ford PRO	Former Order Code	New Order Code	F-650 DIESEL STRAIGHT (Dock Height)	F-650 GAS STRAIGHT (Dock Height)	F-750 DIESEL STRAIGHT (Dock Height)	F-750 GAS STRAIGHT (Dock Height)
		Regular Cab	F6D	F6A	F7D	F7A
		Super Cab	X6D	X6A	X7D	X7A
		Crew Cab	W6D	W6A	W7D	W7A
11 – CAB EQUIPMENT Continued						
SAFETY / FUNCTIONAL Continued						
Driver Assistance – FLEET SETTINGS Requires Valid Code and Driver Assist Technology Package (87H). Note: Settings are locked and cannot be changed by driver or fleet administrator. Includes: Driver Alert Set to ON Collision Assist - Alert Sensitivity Set to NORMAL Distance Indication is set to ON Active Braking set to ON Pre Collision Warning set to ON Lane Keeping set to ON Sensitivity set to NORMAL Auto Lamp Delay set to 20 sec Auto High Beam Set to ON Daytime Lights set to ON	55D	J5TAF	O	O	O	O
Fleet Safety Kit 5 lb Fire Extinguisher CLASS A,B, and C with mounting brackets. Triangle Reflector and Vehicle Fuse Kit (shipped loose not installed at plant)	87S	AHQAD	O	O	O	O
REAR VIEW CAMERA WITH MIRROR DISPLAY *Rear View Mirror Video with Full Length Display included in kit. To be installed by Upfitter(not available with roof clearance light delete)*	61M	J3KAM	O	O	O	O
VIN Stamping on Catalytic Converter Housing Theft-deterrent measure, full vehicle VIN stamped on catalytic converter housings, specific to individual vehicles. Gas models only.	62B	F4EAB	—	O	—	O
INTERIOR APPEARANCE GROUP						
Appearance Group–Front-mounted Overhead Console with Dual Sunglass Bins and Integral Front Map Reading Lights, Door Trim Panel, Chrome Air Registers, Second Row Bench Seat (Crew Cab) or Two-Row High Series Flip-Up Seats with Cushion and Bolster (SuperCab). Includes Power Equipment Group (90P)	90A	AB2BA	O	O	O	O
INTERIOR						
Gauge Cluster, Diesel with enhanced cluster with High-Level 8-Inch display at center cluster. Electronic speedometer (MPH/KPH), includes oil pressure, coolant temperature, DEF gauge, fuel gauge, tachometer, and indicator lights. Also included is enhanced 3-button Message Center with odometer, trip odometer, distance to empty for fuel, average fuel economy, hour meter and warning messages. Transmission temperature in message center.	92J	HKAAJ	O	—	O	—
Gauge Cluster, Gas with enhanced cluster with High-Level 8-Inch display at center of cluster. Electronic speedometer (MPH/KPH) includes oil pressure, coolant temperature, fuel gauge, tachometer and indicator lights. Also included is enhanced 3-button Message Center with odometer, trip odometer, distance to empty for fuel, average fuel economy, hour meter, and warning messages. Transmission temperature in message center.	92K	HKAAK	—	O	—	O
Rapid-Heat Supplemental Cab Heater (Optional in all states with 6.7L Power Stroke® Diesel engine) Requires Air Conditioning Required with Canada and these states Alaska, Colorado, Idaho, Iowa, Maine, Michigan, Minnesota, Montana, New Hampshire, New York, North Dakota, South Dakota, Vermont, Wisconsin, Wyoming	86H	GZAAH	O	—	O	—
Cup Holder–Instrument Panel Mounted, Pull out Cup Holder for two cups. **Not Available with Air Brakes** **Not available with 110 A/C Outlet 55P**	96C	B5QAB	O	O	O	O
110 A/C Outlet–In Lower Center Finish Panel *Requires 59F 4 Body Builders Switches	55P	HUKAC	O	O*	O	O*
4 speaker option for 588 radio	214	IDBAC	O	O	O	O
Radio Delete Package–Deletes radio, speakers, antenna and antenna cable. Includes radio instrument panel cover and aux audio jack cover and speaker locations for future radio upfit if owner desires	58B	IBAAA	O	O	O	O
Keyed Alike–Not Available with Anti-Theft System (85A); requires multiple-unit order (N/A with 90P)	85B	CAUAH	O	O	O	O
Keyed Alike–Option #1 NA with Anti-Theft System (85A); requires multiple-unit order (NA with 90P)	85L	CAUAL	O	O	O	O
Keyed Alike–Option #2 NA with Anti-Theft System (85A); requires multiple-unit order (NA with 90P)	85M	CAUAM	O	O	O	O
Keyed Alike–Option #3 NA with Anti-Theft System (85A); requires multiple-unit order (NA with 90P)	85N	CAUAN	O	O	O	O
Keyed Alike–Option #4 NA with Anti-Theft System (85A); requires multiple-unit order (NA with 90P)	85P	CAUAP	O	O	O	O

2028 MEDIUM DUTY F-650/F-750
OPTIONAL EQUIPMENT

Ford PRO	Former Order Code	New Order Code	F-650 DIESEL STRAIGHT (Dock Height)	F-650 GAS STRAIGHT (Dock Height)	F-750 DIESEL STRAIGHT (Dock Height)	F-750 GAS STRAIGHT (Dock Height)
		Regular Cab	F6D	F6A	F7D	F7A
		Super Cab	X6D	X6A	X7D	X7A
		Crew Cab	W6D	W6A	W7D	W7A
11 – CAB EQUIPMENT (continued)						
EXTERIOR						
Exterior Appearance Group–Includes (765) Full-Width Chrome-Plated Front Bumper and Chromed Fender Badge and (86C) Chrome Grille Surround	90E	ABFAK	O	O	O	O
Interior Rear View Mirror	90M	BSAAB	O	O	O	O
Tamper-proof Odometer	94T	HDGAD	O	O	O	O
Grille–Chrome Surround (Included in Exterior Appearance Group 90E)	86C	BLDAB	O/I	O/I	O/I	O/I
Grille, Fixed–Black/Grey (Included with Front Frame Extension 532)	86B	BLDAU	O/I	O/I	O/I	O/I
Horn, Air–Black, Single Trumpet, Air Solenoid Operated, Chassis Mounted on rail back of Bumper Requires Air Brakes or Air Compressor	59A	HIEAD	O	—	O	—
Mirrors, Heated Dual Rectangular XL2020 Intergral Mirror, Sail Type, 96" Width, Manual Fold, Solid Black Finish	54M	BSHEK	S	S	S	S
Mirrors–Dual Rectangular XL2020 with Integral Spot Mirror, Sail Type, 96" Width, Heated and Motorized, Solid Black Finish (Requires Power Equipment Group, 90P)	54P	BSHEA	O	O	O	O
Mirrors–Dual Rectangular XL2020 with Integral Spot Mirror, Sail Type, 96" Width, Heated and Motorized, Chrome Cap (Requires Power Equipment Group, 90P)	54A	BSHEB	O	O	O	O
Mirrors, Heated–Dual Rectangular XL2020 Integral Spot Mirror, Sail Type, 102" Width, Manual Fold, Solid Black Finish	54C	BSHEM	O	O	O	O
Mirrors–Dual Rectangular XL2020 with Integral Spot Mirror, Sail Type, 102" Width, Heated and Motorized, Solid Black Finish (Requires Power Equipment Group, 90P)	54R	BSHEC	O	O	O	O
Mirrors–Dual Rectangular XL2020 with Integral Spot Mirror, Sail Type, 102" Width, Heated and Motorized, Chrome Cap (Requires Power Equipment Group, 90P)	54K	BSHED	O	O	O	O
Mirrors, Trailer Tow, Powered–Power Telescoping, Power Folding with Power Heated Glass, Heated Convex spotter & Integrated Clearance Lights / Turn Signals (Sail Mount) (Requires Power Equipment Group, 90P) (Heat controls Dash Mounted). and requires radio **Not Available with Vertical Exhaust (91D)**	54F	BSHEG	O	O	O	O
Power Equipment Group–Power Front Side Windows, Power Rear Side Windows (Crew Cab) Power Door Locks and Door Trim Panel and Remote Keyless Entry. Includes Manual Rear Side Windows with SuperCab. Included in Appearance Group	90P	ABKAB	O/I	O/I	O/I	O/I
Aux Spot Mirrors–Front Fender Mounted–(2) Driver Side and Passenger Side	63F	BSJAB	O	O	O	O
Aux Spot Mirror–Front Fender Mounted–(1) Passenger Side Only	63G	BSJAG	O	O	O	O
Mud Flaps Holder without Flaps	165	A4XAB	O	O	O	O
Mud Flap Holder with Flaps *Available with 22.5" Wheels Only	166	A4XAC	O*	O*	O	O
12–FRONT WHEELS – HUB PILOT MOUNT						
22.5" X 8.25" Aluminum wheels, 10-hole Alcoa® Bright Polished w/Dura-Bright® seal on both sides	64H	D2HBN	O	O	O	O
19.5" x 6.75", White Powder-Coated Steel, 8-Hole **Not Available with Air Brakes**	645	D2ZAB	O	O	—	—
19.5" x 6.75", Aluminum wheels, 8-hole, Alcoa® Clean Buff w/Dura-Bright® seal on both sides Requires 668 Rear Wheels **Not available wih Air Brakes**	648	D2ZAM	O	O	—	—
22.5x8.25, Black Wheel Requires 669 Rear Wheels	649	D2HBM	O	O	O	O
13–REAR WHEELS – HUB PILOT MOUNT						
22.5" X 8.25" Aluminum wheels, 10-hole Alcoa® Bright Polished w/Dura-Bright® seal on both sides, outside mount, with white steel wheels inside mount. Requires 64H Front Wheels	66H	D4PBA	O	O	O	O
22.5" X 8.25" Aluminum wheels, 10-hole Alcoa® Bright Polished w/Dura-Bright® seal on both sides - Inside and outside mount aluminium Requires 64H Front Wheels	66C	D4PBC	O	O	O	O
19.5" x 6.75", White Powder-Coated Steel, 8-Hole **Not Available with Air Brakes**	665	D4NAC	O	O	—	—
19.5" x 6.75", Aluminum wheels, 8-hole, Alcoa® Clean Buff w/Dura-Bright® seal both sides **Not available with Air Brakes** Requires 648 Front Wheels	668	D4NAF	O	O	—	—
19.5" x 6.75", DRW Aluminum wheels, 8-hole, Alcoa® Clean Buff w/Dura-Bright® seal on both sides - Inside and outside mount aluminium **Not available with Air Brakes** Requires 648 Front Wheels	66A	D4NAL	O	O	—	—
22.5" x 8.25", Black Wheel Requires 649 Front Wheels	669	D4PCY	O	O	O	O
13A–SPARE WHEELS (rim only) – One Only						
19.5" x 6.75", 8-hole Requires Hydraulic Brakes	60W	D17BH	O	O	—	—
22.5" x 8.25", White Powder-Coated Steel, 10-Hole. Requires 22.5" x 8.25"–Steel disc on chassis **Not Available with 649/669 Black Wheels**	60Z	D17HB	O	O	O	O

2028 MEDIUM DUTY F-650/F-750
OPTIONAL EQUIPMENT

Ford PRO	Former Order Code	New Order Code	F-650 DIESEL STRAIGHT (Dock Height)	F-650 GAS STRAIGHT (Dock Height)	F-750 DIESEL STRAIGHT (Dock Height)	F-750 GAS STRAIGHT (Dock Height)
		Regular Cab	F6D	F6A	F7D	F7A
		Super Cab	X6D	X6A	X7D	X7A
		Crew Cab	W6D	W6A	W7D	W7A
14 – PAINT						
RPO Body Colors Available:						
Agate Black	UM	PN4GM	O	O	O	O
Oxford White	YZ	PNYW3	O	O	O	O
Race Red	PQ	PN4A7	O	O	O	O
School Bus Yellow	B1	PNAJF	O	O	O	O
Iconic Silver	JS	PN4HJ	O	O	O	O
15–MISCELLANEOUS						
Ambulance Prep Package–Special EPA Calibration approved for special Emergency vehicles. System includes (17D) Dual Heavy Duty Alternators @ 357 Amps. Total, and (63D) 3–900CCA Battery System for 2700 Total CCA output	19A	AALAF	O	—	O	—
Beverage Delivery Package–Contains Body Builder Wiring at back of cab at frame (includes sealed connectors for 2 ground circuits with combined Left/Stop, Combined Right/Stop, Stop Lamps, Park Lamps, Backup Lamps) Also Includes 2 Additional Pass Through Wires to Cab) with 6 feet additional length to accommodate drop frame beverage body application. **Not available with 59C, 59D or 59E Body Builder Wiring**	19B	AAEDB	O	O	O	O
Fire/Rescue Prep Package–Special EPA Calibration approved for special Emergency vehicles. System includes (17D) Dual Heavy Duty Alternators @ 357 Amps. Total, and (63D) 3–900CCA Battery System for 2700 Total CCA output	19F	AALAR	O	—	O	—
Pre-Delivery Inspection – Selection requires that you also choose either (314) or (31F) to have Pre-Delivery Inspection Performed **Required with any final Ship To that is not to a dealer**	21A	A2UAB	O	O	O	O
Ship-Thru Manning – MAY be selected without adding (21A) for MODIFICATIONS ONLY – Dealer must make arrangements directly with Manning (please use CVT Resources for additional information)	314		O	O	O	O
Ship-Thru NFS National Fleet Services – MAY be selected without adding (21A) for MODIFICATIONS ONLY – Dealer must make arrangements directly with NFS (please use CVT Resources for additional information)	31F		O	O	O	O
COV Required - Send a paper Certificate of Origin for a Vehicle (COV) for those states that file electronically - CA or MI	79V		O	O	O	O
16–TIRES						
22.5" Tires, Front (Requires 22.5" Wheel)						
11R22.5H Goodyear Fuel MAX RSA (497 rev/mile) Requires either: R2A, R2H,	T2A	YDJCQ	S	S	S	S
11R22.5H Michelin X Multi Energy Z2 (501 rev/mile) Requires either: R2E, RMB	T2E	YDJCX	O	O	O	O
255/70R22.5H Goodyear Endurance RSA (566 rev/mile) Requires either: RCH, R2K **Not available with 14,000# front axle (43D)**	TCH	YDJBX	O	O	O	O
275/80R22.5H Michelin X Multi Energy Z (515 rev/mile) Requires either: R2J,R2M **Not available with 23,000# rear axle (479 or 47P) or 26,000# rear axle (47X)**	T2M	YDJDB	O	O	O	O
295/75R22.5H Continental HSR3 (514 rev/mile) Requires: RRA, RRD, R2H, RMB	TRA	YDJCZ	O	O	O	O
19.5" Tires, Front (Requires 19.5" Wheel)						
245/70R 19.5G Hankook AH35 (628 rev/mile) Requires either: R9A, R9C **Not available with 19,000# rear axle (474)**	T9A	YDJCS	O	O	—	—
245/70R19.5H Michelin AGILIS HDZ (619 rev/mile) Requires: RGK **Not available with 19,000# rear axle (474)**	TGK	YDJDA	O	O	—	—
245/70R19.5H Hankook AH35 (628 rev/mile) Requires either: R9E, R9F **Not available with 19,000# rear axle (474)**	T9F	YDJCW	O	O	—	—
265/70R19.5G Hankook AH35 (613 rev/mile) Requires either: R9B, R9D	T9B	YDJCV	O	O	—	—

..

Ford PRO	Former Order Code	New Order Code	F-650 DIESEL STRAIGHT (Dock Height)	F-650 GAS STRAIGHT (Dock Height)	F-750 DIESEL STRAIGHT (Dock Height)	F-750 GAS STRAIGHT (Dock Height)
		Regular Cab	F6D	F6A	F7D	F7A
		Super Cab	X6D	X6A	X7D	X7A
		Crew Cab	W6D	W6A	W7D	W7A
16–TIRES Continued						
22.5 Tires, Rear (Requires 22.5 Wheel)						
11R22.5H Goodyear Fuel Max RSA (497 rev/mile) Requires either: T2A	R2A	YDKDX	S	S	S	S
11R22.5H Goodyear Fuel Max RTD (493 rev/mile) Requires either: T2A, TRA	R2H	YDKDW	O	O	O	O
11R22.5H Michelin X Multi Energy Z2 (501 rev/mile) Requires either: T2E	R2E	YDKFK	O	O	O	O
11R22.5H Michelin X Multi D (494 rev/mile) Requires either: T2E, TRA	RMB	YDKFJ	O	O	O	O
255/70R22.5H Goodyear Fuel Max RTD (563 rev/mile) Requires: TCH	R2K	YDKFG	O	O	O	O
255/70R22.5H Goodyear Fuel MAX RSA (563 rev/mile) Requires: TCH	RCH	YDKDN	O	O	O	O
275/80R22.5H Michelin X Multi Energy D (514 rev/mile) Requires: T2M	R2J	YDKDZ	O	O	O	O
275/80R22.5H Michelin X Multi Energy Z (515 rev/mile) Requires: T2M	R2M	YDKFQ	O	O	O	O
295/75R22.5H Continental HDR2 ECO PLUS (514 rev/mile) Requires: TRA	RRD	YDKFR	O	O	O	O
295/75R22.5H Continental HSR3 (514 rev/mile) Requires: TRA	RRA	YDKFM	O	O	O	O
19.5 Tires, Rear						
245/70R 19.5G Hankook AH35 (621 rev/mile) Requires: T9A	R9A	YDKFB	O	O	—	—
245/70R19.5G Hankook DH35 (632 rev/mile) Requires: T9A	R9C	YDKFC	O	O	—	—
265/70R19.5G Hankook AH35 (613 rev/mile) Requires: T9B	R9B	YDKFB	O	O	—	—
265/70R19.5G Hankook DH35 (614 rev/mile) Requires: T9B	R9D	YDKFE	O	O	—	—
245/70R19.5H Hankook AH35 (621 rev/mile) Requires T9F	R9F	YDKFF	O	O	—	—
245/70R19.5H Hankook DH35 (632 rev/mile) Requires: T9F	R9E	YDKFH	O	O	—	—
245/70R19.5H Michelin AGILIS HDZ (619 rev/mile) Requires: TGK	RGK	YDKFP	O	O	—	—
AXLE RATIOS						
4.88–Available with axle: 472474475, 476 *Requires 475 or 476 axle	X4G	EGAML	O	—	O*	—
5.29–Available with axle: 472474475, 476 *Available with 19.5 tires only	X5B	EGAPD	O	O*	O	—
5.57–Available with axle: 472, 474, 475, 479, 47X, 476, 47P * Available with 19.5 tires only	X5D	EGAPH	O	O*	O	—
6.14–Available with axle: 472, 474, 479, 47P *Available with 22.5 tires only	X6A	EGAGE	O	O*	O	—
6.17–Available with axle: 475, 476	X6B	EGAQD	—	—	O	O
6.50–Available with axle: 472, 474, 475, 476 *Excludes: 255/70R/22.5 tires **Available with 22.5 tires only	X6D	EGAQJ	O*	O**	O*	O
6.83–Available with axle: 47X *Available with all 11R 22.5 tires or Hankook 275/80R/22.5 tire	X6E	EGAQG	—	—	O*	—
7.17–Available with axle: 475 *Excludes: 255/70R/22.5 tires	X7A	EGARB	—	—	—	O*
REGULAR CAB: Available WB (CA / AF / OAL Dimensions)						
WB 158” (CA 84” / AF 49” / OAL 246”)	158	AA5I8	S	S	S	S
WB 176” (CA 102” / AF 70” / OAL 285”)	176	AA5K6	O	O	O	O
WB 182” (CA 108” / AF 70” / OAL 291”)	182	AA5A3	O	O	O	O
WB 194” (CA 120” / AF 75” / OAL 308”)	194	AA5A4	O	O	O	O
WB 200” (CA 126” / AF 75” / OAL 314”)	200	AA5MP	O	O	O	O
WB 212” (CA 138” / AF 81” / OAL 332”)	212	AA5A5	O	O	O	O
WB 218” (CA 144” / AF 81” / OAL 338”)	218	AA5A6	O	O	O	O
WB 224” (CA 150” / AF 87” / OAL 350”)	224	AA5A7	O	O	O	O
WB 230” (CA 156” / AF 87” / OAL 356”)	230	AA5A8	O	O	O	O
WB 242” (CA 168” / AF 100” / OAL 381”)	242	AA5RK	O	O	O	O
WB 260” (CA 186” / AF 120” / OAL 419”) *Not Available with 533 Frame	260	AA5A9	O*	O*	O	O
WB 281” / CA 207” / AF 120” / OAL 440” *Requires 538 frame **Requires 538 or 539 frame or 536 frame with 41R reinforcement	281	AA5BA	O*	O*	O**	O**

2028 MEDIUM DUTY F-650/F-750
OPTIONAL EQUIPMENT

Ford PRO	Former Order Code	New Order Code	F-650 DIESEL STRAIGHT (Dock Height)	F-650 GAS STRAIGHT (Dock Height)	F-750 DIESEL STRAIGHT (Dock Height)	F-750 GAS STRAIGHT (Dock Height)
		Regular Cab	F6D	F6A	F7D	F7A
		Super Cab	X6D	X6A	X7D	X7A
		Crew Cab	W6D	W6A	W7D	W7A
SUPER CAB: Available WB (CA / AF / OAL Dimensions)						
WB 179” / CA 84” / AF 49” / OAL 267”	179	AA5K9	S	S	S	S
WB 203” / CA 108” / AF 70” / OAL 312”	203	AA5AR	O	O	O	O
WB 215” / CA 120” / AF 75” / OAL 329”	215	AA5BC	O	O	O	O
WB 221” / CA 126” / AF 75” / OAL 335”	221	AA5BD	O	O	O	O
WB 239” / CA 144” / AF 81” / OAL 359”	239	AA5BF	O	O	O	O
WB 245” / CA 150” / AF 87” / OAL 371”	245	AA5BG	O	O	O	O
WB 251” / CA 156” / AF 87” / OAL 377”	251	AA5RQ	O	O	O	O
WB 281” / CA 207” / AF 120” / OAL 440 *Requires 538 frame **Requires 538/539 frame or 536 with 41R reinforcement	281	AA5BA	O*	O*	O**	O**
CREW CAB: Available WB / CA / AF / OAL Dimensions						
WB 194” / CA 84” / AF 49” / OAL 282”	194	AA5A4	O	O	O	O
WB 212” / CA 102” / AF 70” / OAL 321”	212	AA5A5	O	O	O	O
WB 218” / CA 108” / AF 70” / OAL 327”	218	AA5A6	O	O	O	O
WB 230” / CA 120” / AF 75” / OAL 344”	230	AA5A8	O	O	O	O
WB 236” / CA 126” / AF 75” / OAL 350”	236	AA5BL	O	O	O	O
WB 248” / CA 136” / AF 81” / OAL 368”	248	AA5BM	O	O	O	O
WB 260” / CA 150” / AF 87” / OAL 386” ***Not Available with frame 533 and W6D or W6A Body Code**	260	AA5A9	O*	O*	O	O
WB 266” / CA 156” / AF 87” / OAL 386” ***Not Available with frame 533 and W6D or W6A Body Code**	266	AA5BP	O*	O*	O	O
WB 278” / CA 168” / AF 100” / OAL 417” ***Not Available with 533 Frame**	278	AA5S5	O*	O*	—	—

WHEEL AND TIRE REFERENCE – FRONT AND REAR COMBINED (NOTE: REFER TO WHEEL SECTION FOR RESTRICTIONS)

Available Wheels		
643 / D2HAU  Front 22.5x8.25 White Powder Coated Steel, 10-Hole	64H / D2ZAB  Front 22.5x8.25 Bright Polished w/Dura-Bright® seal on both sides, 10-Hole	645 / D2ZAB  Front 19.5x6.75 White Powder Coated Steel, 8-Hole
648 / D2ZAM  Front 19.5x6.75 Clean Buff w/Dura-Bright® seal on both sides, 8-Hole	649 / D2HBM  Front 22.5x8.25 Black Wheel	66H / D4PBA  Rear 22.5x8.25 10-Hole Bright Polished w/Dura-Bright® outer mount, White Powder Coated Steel (steel inner wheel)
663 / D4PCE  Rear 22.5x8.25 White Powder Coated Steel, 10-Hole	66C / D4PBC  Rear 22.5x8.25 Bright Polished w/Dura-Bright® seal on both sides, 10-Hole (steel inner wheel)	665 / D4NAC  Rear 19.5x6.75 White Powder Coated Steel, 8-Hole
66A / D4NAL (Dual) 668 / D4NAF(Outside Only)  Rear 19.5x6.75 Clean Buff w/Dura-Bright® seal on both sides, 8-Hole	669 / D4PCY  Rear 22.5x8.25 Black Wheel (front shown)	

OPTIONAL EQUIPMENT

Available Front Tires		
T2E / YDJCX  Front Two 11R22.5H Michelin X Multi Energy Z2 (501 rev/mile)	T2A / YDJCQ  Front Two 11R22.5H Goodyear Fuel Max RSA (497 rev/mile)	TRA / YDJCZ  Front Two 295/75R22.5H Continental HSR3 (514 rev/mile)
TCH / YDJBX  Front Two 255/70R22.5H Goodyear Endurance RSA (566 rev/mile)	T9A / YDJCS  Front Two 245/70R19.5G Hankook AH35 (628 rev/mile)	TGK / YDJDA  Front Two 245/70R19.5H Michelin AGILIS HDZ (619 rev/mile)
T2M / YDJDB  Front Two 275/80R22.5H Michelin X Multi Energy Z (515 rev/mile)	T9F / YDJCW  Front Two 245/70R19.5H Hankook AH35 (628 rev/mile)	T9B / YDJCV  Front Two 265/70R19.5G Hankook AH35 (613 rev/mile)

OPTIONAL EQUIPMENT

Available Rear Tires		
R2E / YSKFK  Rear Four 11R22.5H Michelin X Multi Energy Z2 (501 rev/mile)	R2H / YDKDW  Rear Four 11R22.5H Goodyear Fuel Max RTD (493 rev/mile)	R2A / YDKDX  Rear Four 11R22.5H Goodyear Fuel Max RSA (497 rev/mile)
RRD / YDKFR  Rear Four 295/75R22.5H Continental HDL3 (514 rev/mile)	RRA / YDKFM  Rear Four 295/75R22.5H Continental HSR3 (514 rev/mile)	R9E / YDKFH  Rear Four 245/70R19.5H Hankook DH35 (632 rev/mile)
RCH / YDKDN  Rear Four 255/70R22.5H Goodyear Fuel Max RTD (563 rev/mile)	R9A / YDKFB  Rear Four 245/70R19.5G Hankook AH35 (621 rev/mile)	R9C / YDKFC  Rear Four 245/70R19.5G Hankook DH35 (632 rev/mile)
R9F / YDKFF  Rear Four 245/70R19.5H Hankook AH35 (621 rev/mile)	R2K / YDKFG  Rear Four 255/70R22.5H Goodyear Fuel Max RTD (563 rev/mile)	RGK / YDKFP  Rear Four 245/70R19.5H Michelin AGILIS HDZ (619 rev/mile)
R2M / YDKFQ  Rear Four 275/80R22.5H Michelin X Multi Energy Z (515 rev/mile)	RMB / YDKFJ  Rear Four 11R22.5H Michelin X Multi D(494 rev/mile)	R2J / YDKDZ  Rear Four 275/80R22.5G Michelin X Multi Energy D (514 rev/mile)

OPTIONAL EQUIPMENT

Available Rear Tires Continued		
R9B / YDKFD  Rear Four 265/70R19.5G Hankook AH35 (613 rev/mile)	R9D / YDKFE  Rear Four 265/70R19.5G Hankook DH35 (614 rev/mile)	