

CSC12107 – Information Systems for Business Intelligence

Chapter 3

DATA MODELING



KHOA CÔNG NGHỆ THÔNG TIN
TRƯỜNG ĐẠI HỌC KHOA HỌC TỰ NHIÊN



Learning Objectives

- After complete this chapter, student can:
 - Define the meaning of the facts and dimensional attributes
 - Define the data hierarchies , slowly changing dimension
 - Design a Star or Snowflake data model diagram from analytical business requirements and OLTP system



Main topic

- Designing the Dimensional Data Store
 - Star schema
 - Snowflake schema
- Designing the Normalize Data Store





Introduction

Building a data warehouse system to make sure that the system will help users achieve the business objectives:

1. gather functional and nonfunctional requirements
2. find out business issues and challenges
3. identify the business areas that would benefit from a data warehouse system
4. dive into each of these areas and learn about the business operations within that area
5. define what the data warehouse system does
6. find out whether the data that we need is available in the source systems and whether it is accessible





Understanding Business Operations

- understand the business operations, we will define the **functional requirements** → define what the data warehouse system does:
 - the questions or issues that a data warehouse system will be able to answer
 - the data that will be stored in the data warehouse
 - the analysis the users will be performing
- **Nonfunctional requirements** guide and constrain the architecture
 - security, availability, and performance...



Understanding Business Operations

- An **event** is an activity that happens repeatedly every few seconds or minutes. Or it could be every few hours or days.
 - Ex:
 - in the purchasing area, we have a document called a purchase order.
 - a customer buys a record from the online store
- A **level** is a quantitative measurement of an object at a particular point in time
- **Roles** are the who, whom, and what involved in the event.



Understanding Business Operations

Amadeus Entertainment Data Warehouse System Functional Requirements

- **EX1:** The business users need to be able to analyze “product sales” (that’s when a High customer is buying a product rather than subscribing to a package) over time by geographic area, by customer demographic, by stores and sales territory, and by product hierarchy. The users also need to know the revenues, the costs, and the margin in U.S. dollars. Local currencies will be converted to U.S. dollars.
- **EX2:** The business users will be able to analyze “supplier performance,” which is the Low weighted average of the totals spent, costs, value of returns, value of rejects, title and format availability, stock outages, lead time, and promptness



Dimensional modeling (DM)

- DM is a logical design technique. The purpose of DM is to enable BI reporting, query, and analysis
- The key concepts in DM are **facts**, **dimensions**, and **attributes**
- Facts, dimensions, and attributes can be organized in several ways, called schemas:
 - Star schema
 - Snowflake schema
 - Multidimensional/galaxy schema
- The choice of schema depends on variables such as the type of reporting that the model needs to facilitate and the type of BI tool being used



4.0

A DIMENSIONAL MODEL

when those
products were sold



Date


Product Sales



Customer

who bought
the products

what products
were sold



Product

| |
|---|
| sales_date_key customer_key product_key store_key |
| order_id line_number quantity unit_price unit_cost sales_value sales_cost margin |



Store

Where those products
were bought

- **Fact table:** tbl_Fact_Sales
- **Measure:** Quantity, sales_value, sales_cost, unit_price, unit_cost, margin
- **Fact table keys:** sales_date_key, customer_key, product_key, store_key
- **Dimension:** Date, Customer, Product, Store



Dimension

- A dimension is an entity that establishes the business context for the measures (facts) used by an enterprise
- Dimensions define the who, what, where, and why of the dimensional model, and group similar attributes into a category or subject area
- Ex: product, geography, customers, employees, time....
- Key purpose of dimensions:
 - use their attributes to filter and analyze data based on performance measures



Dimension keys

- A key concept in constructing dimensions is that each row of a dimension table is unique
- **Surrogate keys**
 - Is often generated by the database system
 - is an integer whose value is meaningless
 - to provide an identifier that is consistent and unique across source systems and time, and independent of business systems
 - is a great data type to index and join in a relational model

DimProduct

ProductKey

ProductAlternateKey
WeightUnitMeasureCode
SizeUnitMeasureCode
EnglishProductName
StandardCost
FinishedGoodsFlag
Color
SafetyStockLevel
ReorderPoint
ListPrice
Size
SizeRange

DimGeography

GeographyKey

PostalCode
City
StateProvinceCode
StateProvinceName
CountryRegionCode



Dimension keys

- Best practice:
 - maintain the source system's primary key as an alternate key in the dimension (also called source system's natural key)
- Ex: Dim_Customers
 - CustomerNK is the natural key in the dimension and primary key in the source system
 - SOR_NK:

| Dim_Customers | |
|---------------|--------------------------|
| PK | <u>CustomerSK</u> |
| U1 | CustomerNK |
| | SOR_NK |
| | Title |
| | FirstName |
| | MiddleName |
| | LastName |



Dimension hierarchy

- Group things together in ways that an enterprise would measure itself
- These hierarchies represent many-to-one relationships
- EX:
 - DimProduct: Product → Product subcategory → Product category
 - DimDate: Day → month → quarter → Year
 - DimGeography: City → State → Country

Dimension hierarchy


Users drill/roll up and down dimensional hierarchies to obtain more or less detail about the business



| Year | Region | Sales |
|------|---------|--------|
| 1996 | Asia | 1,000 |
| | Europe | 50,000 |
| | America | 20,000 |
| 1997 | Asia | 1,500 |
| | | |

Dimension hierarchy

Users drill/roll up and down dimensional hierarchies to obtain more or less detail about the business




| Year | Quarter | Vùng miền | Doanh thu |
|-------|---------|-----------|-----------|
| 1996 | Q1 | Asia | 200 |
| | Q2 | Asia | 200 |
| | Q3 | Asia | 250 |
| 1997 | Q4 | Asia | 350 |
| | Q1 | Europe | 10,000 |
| ----- | ----- | ----- | ----- |



Date dimension


- Important
- Several levels in the dimension table → recorded all the time levels needed for analysis and in accordance with the content
- Example:
 - Analysis financial data of an enterprise: day, week, month, quarter, year, holiday...

Modeling the calendar




**Gregorian
calendar**

Modeling the calendar



Fiscal Calendar

Modeling the calendar





Slowly Changing Dimension (SCD)

- SCD: is a technique used to store the ***historical value*** of dimension attributes
- Three types of SCD:
 - overwrite the old values with the new ones (SCD type 1)
 - Preserve the old value:
 - store the old values as rows (SCD type 2)
 - store them as columns (SCD type 3)



Slowly Changing Dimension (SCD)

- Store 7 was in region 1, but it is now in region 2

| key | store | region | status |
|-----|-------|--------|---------|
| 1 | 7 | 1 | expired |
| 2 | 7 | 2 | active |

what if store 7 moves region again, to region 3, for example?

Storing Historical Information As a Row

| key | store | current_region | old_region | effective_date |
|-----|-------|----------------|------------|----------------|
| 1 | 7 | 2 | 1 | 11/18/2007 |

Storing Historical Information As a Column





Rapidly changing dimension (RCD)

- Ex: a customer dimension with ten attributes.
 - Attributes 1 to 9 change once a year.
 - Attribute 10 changes every day

→ How do we store the historical information?






Degenerate dimension

- Context that is insignificant for analysis such as invoice no, ticket no, ...in an transaction
- Has an informative role, is stored in a fact table



Rapidly changing dimension (RCD)





- **A fact is a measurement** of a business activity, such as a business event or transaction, and is generally numeric
 - Fact: sales
 - Numeric measurements: counts, dollar amounts, percentages, or ratios
- Facts can be aggregated or derived
 - Ex: sum up the total revenue or calculate the profitability of a set of sales transactions
- Facts provide the measurements of how well or how poorly the business is performing
- Fact tables are normalized and contain little redundancy



FACT TABLE

- Fact tables are composed of two types of columns:
 - Keys
 - a group of foreign keys (FK) that point to the primary keys of dimensional tables
 - Measures
 - actual measures of the business activity
 - Every measurement has a grain, which is the level of detail in the measurement of an event



FACT TABLE KEYS


- **Key column:** consists of a group of foreign keys (FK) that point to the primary keys of dimensional tables that are associated with this fact table to enable business analysis.
- The primary key of a fact table is typically a multipart key consisting of the combination of foreign keys that can uniquely identify the fact table row.
 - primary key is a surrogate key.
 - primary key with degenerative dimensions



4.0

FACT TABLE KEYS

- The relationships between fact tables and the dimensions are **one-to-many**
- If combining a subset of foreign keys creates uniqueness, then this multipart key will become the primary key




Fact keys:

(DateKey, StoreKey, ProductKey, CustomerKey)



Fact table—primary key is a surrogate key

- if you cannot identify unique rows with any of the methods discussed so far, create a primary key based on a **surrogate key**:
 - is often generated by the database system using an **IDENTITY** data type
 - is an integer whose value is meaningless
- **OnlineSalesKey**: is the surrogate key that was created as the PK





FACT TABLE MEASURES

- Every measurement has a grain, which is the level of detail in the measurement of an event
- Granularity is determined by its data source, indicates the level of detail stored in a table. Example:
 - Each Time record represents a day
 - Each Product record represents a product
 - Each Organization record represents one branch➔ then the grain of a sales Fact table with these dimensions is sales per product per day per branch
- Granularity at **too high** a level severely limits the ability of users to obtain additional detail
- Granularity at **too low** a level results in an exponential increase in the size requirements of the DW



FACT TABLE MEASURES

- **Type of fact measure:**

- Additive Facts

- can be summed across any of the dimensions associated with the fact table.

- Semi-additive Facts

- can be summed across some dimensions, but not all


- Non-additive Facts

- can't be added across any dimensions



FACT MEASURES - Additive Facts


- is the easiest to define and manage, can be added across all dimensions
 - Ex: the quantity of items (number of books)





FACT MEASURES - SemiAdditive Facts


- Can be added across some dimensions but not others
- Ex: bank account balances, the number of students attending a class, or inventory levels





FACT MEASURES – NonAdditive Facts

- Can't be added across any dimensions
- Ex: ratios, and temperatures;



The logo features the letters 'ft' in a stylized blue font, with a teal circular graphic containing the number '4.0' to its right.


SCHEMA

- which schema should use when building the dimensional model?
 - What kind of analysis are you trying to perform on that data and how complex is it?
 - What are the analytical requirements and restrictions?
 - How consistent is the data you want to query and analyze?
 - What BI tool do you plan to use?



Star Schema


- is the most common schema for dimensional models
- It is a fact table surrounded by multiple **denormalized** dimension tables
- a dimension does not have a subtable (a subdimension)
- easier for the ETL processes to load the data into DDS





Snowflake schema


- a dimension can have a subdimension → is to minimize redundant data
- The fact table stores the foreign key to the lowest level of the dimensional hierarchy.





4.0

Galaxy schema



- This schema specifies two fact tables, *sales* and *shipping*
 - allows dimension tables to be shared between fact tables.
 - For example, the dimensions tables for *time*, *item*, and *location* are shared between the *sales* and *shipping* fact tables
 - A fact table may be in relationship with some (not all) dimension table



Exercises

- steps for data warehouse dimensional modeling example:
 - Step 1: Chose Business Objective
 - how many paracetamol and diclofenac tablets sold from single MedPlus store every day
 - Step 2: Identify Granularity
 - MedPlus shop sells 1,000 paracetamol tablets on a specific day then granularity is daily and 10,000 on specific month then granularity would be monthly
 - Step 3: Identify Dimension and its attributes
 - Shop”, “Medicine”, and “Day”
 - Step 4: Identify Fact
 - number of tablets sold is a measure