

Drivetrain Torque Settings - 2018 Stelvio 2.0T (Q4 AWD, ZF 8HP)

VIN ZASFAPN5J7B88115 | transmission, transfer case, differentials, driveline, mounts | from cuore, 2026-09-26

Only CONFIRMED is manufacturer data (here: ZF 8HP pan/filter bolts and fill window, from ZF/FCA text). SINGLE = one forum/aggregator source; UNKNOWN = use the FCA service manual (TechAuthority). Rows marked [BMW G30...] are the same ZF 8HP in a BMW, for reference only. Fact-checked 2026-09-26: the propshaft flange figure seen online (72-101 lb-ft) is from a 1970s Alfa manual and must not be used.

TRANSMISSION (ZF 8HP)

Fastener	Torque	Conf.	Note
ZF 8HP pan/filter assembly bolts (13x)	10 Nm (7.4 lb-ft)	CONFIRM.	Integrated pan/filter assembly, not separately serviceable; gasket...
ZF 8HP transmission fluid drain plug	UNKNOWN	UNKNOWN	Giorgio-specific value not found. use the service manual...
ZF 8HP transmission fluid fill/level plug	UNKNOWN	UNKNOWN	Giorgio-specific value not found; the 4th-gen 8HP fill/level check...
BMW G30 reference: mechatronics-to-transmission bolts M6x59/M6x20	8 Nm (5.9 lb-ft)	CORROB.	[BMW G30, not Alfa-specific.] SINGLE-USE. Sequence 1->17; screws...
BMW G30 reference: output speed sensor	4 Nm (3.0 lb-ft) + +12 deg	CORROB.	[BMW G30, not Alfa-specific.] BMW 8HP family -- NOT independently...
BMW G30 reference: pan bolts M6 (13x)	10 Nm (7.4 lb-ft)	CORROB.	[BMW G30, not Alfa-specific.] SINGLE-USE. Sequence 1->13; pan itself...
BMW G30 reference: drain plug M18	8 Nm (5.9 lb-ft)	CORROB.	[BMW G30, not Alfa-specific.] BMW 8HP family -- NOT independently...
Fluid / capacity / interval			
ZF 8HP transmission fluid	ZF LifeguardFluid 8 / Mopar '8 & 9 Speed ATF, P/N 68218925AA -- NOT compatible with...	CORROB.	Fluid identity/incompatibility...
ZF 8HP owner/service-manual capacity, 2.0 AWD	9.3 (9.8 qt) L	SINGLE	Close to but not reconciled with the...
ZF 8HP fill/level-check temperature window	30-50 (86-122 F) °C	CONFIRM.	General 8HP family window; matches...
ZF 8HP service interval, FCA position	no FCA-published mileage number found this pass	UNKNOWN	use the service manual (TechAuthority)
ZF 8HP service interval, ZF generic guidance	50000-75000 mi	SINGLE	Forum-attributed to ZF; not...

TRANSFER CASE (Q4)

Fastener	Torque	Conf.	Note
Transfer case (Q4) drain plug	UNKNOWN	UNKNOWN	A stelvioforum thread asking this exact question cites the rear...
Transfer case (Q4) fill plug	UNKNOWN	UNKNOWN	Same open question as transfer_case_drain_plug. use the service...
Fluid / capacity / interval			
Q4 transfer case fluid	Petronas Tutela Transmission Transfer Case (Q4) -- Tutela Transmission Hypoide Gear Oil,...	CORROB.	Do not substitute ATF or generic 75W...
Q4 transfer case capacity	conflicting: ~1 L (repo doc) vs 0.7 L (giuliatech.com) L	SINGLE	Unreconciled -- confirm exact fill...
Q4 transfer case service interval	not found	UNKNOWN	use the service manual (TechAuthority)

DIFFERENTIALS (FRONT AND REAR)

Fastener	Torque	Conf.	Note
Front differential drain plug	UNKNOWN	UNKNOWN	Not found. use the service manual (TechAuthority)
Front differential fill plug	UNKNOWN	UNKNOWN	Not found. use the service manual (TechAuthority)
Rear differential (rear axle) drain plug	26 Nm (19.2 lb-ft)	SINGLE	Stated as known/given by the original poster in a thread actually...
Rear differential (rear axle) fill plug	26 Nm (19.2 lb-ft)	SINGLE	Same source as rear_diff_drain_plug; drain and fill plugs are...
Fluid / capacity / interval			
Front differential fluid	SAE 75W-80, API GL-5, synthetic, FIAT approval 9.55550-DA10	SINGLE	
Front differential capacity, 2.0T	0.5 L	SINGLE	
Front differential service interval	anecdotally lasts to ~100000 km without visible wear km	SINGLE	Not an OEM schedule.
Rear differential fluid, 2.0T variants (195 open / 230-LSD / 210-eLSD)	SAE 75W-85, synthetic, FIAT approval 9.55550-DA9	SINGLE	
Rear differential capacity, 2.0T variants	0.9-1.1 (varies by internal type: 195 / 230-LSD / 210-eLSD) L	SINGLE	
Rear differential service interval	~50000-60000 (rear wears faster than front per forum guidance) km	SINGLE	Not an OEM schedule.

DRIVELINE

Fastener	Torque	Conf.	Note
Propshaft flange/centre-carrier nut	UNKNOWN - use service manual	UNKNOWN	DO NOT USE the 72-101 lb-ft figure that circulates online:...
Central M14 bolt, Q4 (4x4) versions	124-136 Nm	SINGLE	Location not independently confirmed -- possibly a front-driveline...
Front/rear axle (hub) nut	52 lb-ft + +47 deg	SINGLE	SINGLE-USE. Torque-then-angle procedure; always fit a NEW nut.
Front/rear hub mounting bolts	74 lb-ft	SINGLE	
Wheel lug bolts (reference only, not a drivetrain fastener)	89 lb-ft	SINGLE	Included for completeness only; see service_specs.py's own wheel_lug...

MOUNTS

Fastener	Torque	Conf.	Note
Engine mount bolts into aluminium block	22-27 Nm	SINGLE	
Longitudinal mount (torque strut / dogbone) bolts	25-31 Nm	SINGLE	SINGLE-USE. Alfa Romeo specifies the mount itself must be replaced...
Central M14 bolt, Q4 versions (mounts-context duplicate)	124-136 Nm	SINGLE	Same figure and same unresolved-location caveat as driveline's...
Transmission-bracket-to-transmission-case fasteners	UNKNOWN	SINGLE	SINGLE-USE. Fasteners reported one-time-use per a referenced TSB for...

Also relevant: TSB 21-035-20 (TCM flash, shift quality) applies to this VIN. After a transmission fluid service run the adaptation relearn; fill/level check only in the 30-50 C fluid window.