

# Brakes, Wheels & Tyres - 2018 Alfa Romeo Stelvio 2.0T

VIN ZASFAKPN5J7B88115 | about 142,290 km / 88,415 mi | cuore, 2026-09-26

## Rotors & pads

|                          | Front                                              | Rear                                | Conf.   |
|--------------------------|----------------------------------------------------|-------------------------------------|---------|
| Rotor, new               | 28 mm (330 mm dia.)                                | 22 mm (320 mm dia.)                 | SINGLE  |
| Rotor, minimum (discard) | 25.5 mm                                            | UNKNOWN -- read cast MIN TH marking | SINGLE  |
| Pad minimum thickness    | UNKNOWN -- electronic pad-wear sensor on inner pad | UNKNOWN                             | UNKNOWN |

**EPB service mode required before rear pad service:** Rear brakes use an electric parking brake (EPB) with a motorized caliper piston. Reported procedure: infotainment Settings > Passive Safety > Brake Service Mode, ignition on/engine off, in Park with the foot brake released; the screen confirms once the actuators retract. No wiTECH/scan tool is reported as required for a routine pad change via this menu path; MultiEcuScan's own coverage of an equivalent routine was not confirmed in this research pass. Never force the rear piston back mechanically without service mode active -- it can strip the actuator's gears/spindle. Press pistons straight back (do not rotate -- tears the seal); if the battery is disconnected while the caliper is off, pump the brake pedal before reconnecting to avoid setting fault codes.

## Fluid & tyres

| Item                    | Value                                                                                                                       | Conf.    |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------|----------|
| Brake fluid             | DOT 4, FCA spec MS.90039 -- capacity 0.9 L (reservoir + lines)                                                              | CONFIRM. |
| Change interval         | Every 2 years, regardless of mileage                                                                                        | CONFIRM. |
| Tyre size, base 18in    | 235/60R18                                                                                                                   | CORROB.  |
| Tyre size, Ti 19in      | 235/55R19, load/speed index 101V                                                                                            | CORROB.  |
| Pressure (19in fitment) | Front 207 kPa / 30 psi; rear 228 kPa / 33 psi -- READ THE DOOR-JAMB PLACARD                                                 | SINGLE   |
| Rotation                | Square (non-staggered) fitments: standard front-to-rear. Staggered (Quadrifoglio or any mismatched fitment): DO NOT ROTATE. | SINGLE   |

## Torques

| Fastener                                             | Torque  | Conf.   | Note                                                                                            |
|------------------------------------------------------|---------|---------|-------------------------------------------------------------------------------------------------|
| Wheel lug bolts                                      | 121 Nm  | CORROB. | Bolts threaded into the hub, NOT nuts on studs -- confirmed by all sources. Two independent...  |
| Brake caliper guide/slide pin bolt, front            | 30 Nm   | CORROB. | Reported consistently (~22 ft-lb / 30 Nm) for the single guide-pin bolt (between the...         |
| Brake caliper bracket/carrier-to-knuckle bolt, front | UNKNOWN | UNKNOWN | Conflicting forum reports: one 2018 2.0L thread settled on ~57 ft-lb (~77 Nm) with...           |
| Brake caliper guide/slide pin bolt, rear             | 27 Nm   | SINGLE  | From one 2018 2.0L thread (~20 ft-lb / 27 Nm), read via a search-engine summary only -- the...  |
| Brake caliper bracket/carrier-to-knuckle bolt, rear  | UNKNOWN | UNKNOWN | Not distinguished from the rear guide-pin figure in any source found. use the service manual... |
| Rotor retaining screw                                | UNKNOWN | UNKNOWN | Confirmed as an M10 x 1.25 thread (~16.4mm length) from parts listings, but no torque value...  |
| Wheel bearing/hub retaining nut or bolts             | UNKNOWN | UNKNOWN | SINGLE-USE. No sourced torque value found. Hub nuts on many AWD platforms are single-use,...    |

**UNKNOWN values above must come from the service manual (TechAuthority)** -- never substitute a guessed number. Wheel lug bolts thread into the hub (not nuts on studs); torque in a star pattern, snug then final torque. This is a safety-critical fastener.

## Four-corner record

|                                | FL | FR | RL | RR |
|--------------------------------|----|----|----|----|
| Pad thickness (mm) inner/outer |    |    |    |    |
| Rotor thickness (mm)           |    |    |    |    |
| Tread depth (32nds / mm)       |    |    |    |    |
| Pressure (psi/kPa)             |    |    |    |    |
| Tyre DOT date code             |    |    |    |    |