

Transmission and Drivetrain - 2018 Stelvio 2.0T (Q4 AWD, ZF 8HP)

VIN ZASFAPN5J7B88115 | about 142,290 km / 88,415 mi | transmission, transfer case, differentials, driveline, mounts | cuore, 2026-09-26

DUE: transfer case oil, 80000 mi (128000 km) / 8 years (CONFIRM., owner's manual). This car is past that mileage (about 142,290 km / 88,415 mi) -- replace unless records show it was already done. Do not substitute ATF or generic 75W GL-5 -- friction characteristics are matched to the Q4 clutch pack.

TSB 21-035-20 (2020-05-08) applies to this VIN: Flash: TCM Update. Applies explicitly to 2018 (GU) Stelvio, 2.0L I4 DI Turbo (EC2), North America. Fixes MIL w/ P0002-00, P026E-00, P1066-00, P26E4-00, P2B61-00, P2BC1-00, U1008-00; transmission shift-quality improvements; turbo coolant-pump after-run update. Labor op 18-19-05-MX, 0.3 hr. PCM must also be updated to...

Only CONFIRMED is manufacturer data (ZF 8HP pan/filter bolts and fill window; transfer case interval, from the owner's manual). SINGLE/CORROB. = one or two non-manufacturer sources; UNKNOWN = use the FCA service manual (TechAuthority). The propshaft flange figure seen online (72-101 lb-ft) is from a 1970s Alfa manual and must not be used on this car.

TRANSMISSION (ZF 8HP)

Fluid / capacity / interval		Conf.
ZF 8HP transmission fluid: ZF LifeguardFluid 8 / Mopar '8 & 9 Speed ATF', P/N 68218925AA -- NOT compatible with ATF+4 or any...		CORROB.
ZF 8HP owner/service-manual capacity, 2.0 AWD: 9.3 (9.8 qt)		SINGLE
ZF 8HP fill/level-check temperature window: 30-50 (86-122 F)		CONFIRM.
ZF 8HP service interval, ZF generic guidance: 50000-75000		SINGLE
Fastener	Torque	Conf.
ZF 8HP pan/filter assembly bolts (13x) Integrated pan/filter assembly, not separately serviceable; gasket reusable if...	10 Nm	CONFIRM.
ZF 8HP transmission fluid drain plug Giorgio-specific value not found. use the service manual (TechAuthority)	UNKNOWN	UNKNOWN
ZF 8HP transmission fluid fill/level plug Giorgio-specific value not found; the 4th-gen 8HP fill/level check requires an OEM...	UNKNOWN	UNKNOWN

TRANSFER CASE (MAGNA Q4)

Fluid / capacity / interval		Conf.
Q4 transfer case fluid: Petronas Tutela Transmission Transfer Case (Q4) -- Tutela Transmission Hypoide Gear Oil, Synthetic...		CORROB.
Q4 transfer case capacity: conflicting: ~1 L (repo doc) vs 0.7 L (giuliatech.com)		SINGLE
Q4 transfer case service interval: 80000 mi (128000 km) / 8 years		CONFIRM.
DTCM ADJ routine: hypothesis: actuator position / clutch-clearance learn, drives to mechanical end stops and records...		UNKNOWN
Fastener	Torque	Conf.
Transfer case (Q4) drain plug A stelvioforum thread asking this exact question cites the rear differential's 26 Nm...	UNKNOWN	UNKNOWN
Transfer case (Q4) fill plug Same open question as transfer_case_drain_plug. use the service manual (TechAuthority)	UNKNOWN	UNKNOWN

DIFFERENTIALS (FRONT AND REAR)

Fluid / capacity / interval		Conf.
Front differential fluid: SAE 75W-80, API GL-5, synthetic, FIAT approval 9.55550-DA10		SINGLE
Front differential capacity, 2.0T: 0.5		SINGLE
Rear differential fluid, 2.0T variants (195 open / 230-LSD / 210-eLSD): SAE 75W-85, synthetic, FIAT approval 9.55550-DA9		SINGLE
Rear differential capacity, 2.0T variants: 0.9-1.1 (varies by internal type: 195 / 230-LSD / 210-eLSD)		SINGLE
Rear differential trim/option (which unit is fitted to this VIN): depends on trim/options: open 195 / mechanical-LSD 230-LSD / electronic 210-eLSD; Ti Sport and...		UNKNOWN
Fastener	Torque	Conf.
Front differential drain plug Not found. use the service manual (TechAuthority)	UNKNOWN	UNKNOWN
Front differential fill plug Not found. use the service manual (TechAuthority)	UNKNOWN	UNKNOWN
Rear differential (rear axle) drain plug Stated as known/given by the original poster in a thread actually asking about the...	26 Nm	SINGLE
Rear differential (rear axle) fill plug Same source as rear_diff_drain_plug; drain and fill plugs are commonly the same...	26 Nm	SINGLE

DRIVELINE

Fluid / capacity / interval		Conf.
Propshaft material/construction: referenced as a carbon-fibre driveshaft on 2017-2025 Giulia/Stelvio by an aftermarket parts vendor...		SINGLE
Front flex disc / coupling: bolts possibly torque-to-yield, requiring replacement		SINGLE
Fastener	Torque	Conf.
Propshaft flange/centre-carrier nut DO NOT USE the 72-101 lb-ft figure that circulates online: fact-check (2026-09-26)...	UNKNOWN - use service manual	UNKNOWN
Front/rear axle (hub) nut SINGLE-USE. Torque-then-angle procedure; always fit a NEW nut.	52 lb-ft	SINGLE
Front/rear hub mounting bolts	74 lb-ft	SINGLE

MOUNTS

Fastener	Torque	Conf.
Engine mount bolts into aluminium block	22-27 Nm	SINGLE
Longitudinal mount (torque strut / dogbone) bolts SINGLE-USE. Alfa Romeo specifies the mount itself must be replaced on removal, not...	25-31 Nm	SINGLE
Transmission-bracket-to-transmission-case fasteners SINGLE-USE. Fasteners reported one-time-use per a referenced TSB for the 2021 Stelvio;...	UNKNOWN	SINGLE

Relearn: Fast Filling Adaptation + Standard Clutch Filling Adaptation via wiTECH; MES: QUICK LEARN / STATIC ADAPTATION (STADA) + separate RESET ADAPTIVE VALUES
Not required for a routine fluid+filter change or after a TCM/TCMA re-flash alone; not lost on battery disconnect (non-volatile EEPROM).