EXT: Front End User Registration

Extension Key: sr_feuser_register
Language: en
Keywords: forAdmins, forIntermediates, front end user, registration, newsletter, subscription, login
Copyright 2000-2023, Stanislas Rolland, <typo3AAAA(arobas)sjbr.ca>

This document is published under the Open Content License
available from http://www.opencontent.org/opl.shtml

The content of this document is related to TYPO3
- a GNU/GPL CMS/Framework available from www.typo3.org

Table of Contents

EXT: Front End User Registration.....1
Introduction.....3
What does it do?.....3
What's new in Version 12.....3
What's new in Version 10.....3
What's new in Version 7.....3
What's new in Version 6.....3
What's new in Version 5.....4
Sponsors.....4
Support.....4
Users Manual.....5
Registration Process.....5
Invitation.....5
Administrative Review.....5
Administration.....6
Front End Rendering.....6
Localization.....9
Configuration.....10
Configuration steps.....10
Upgrading to version 12.4.1+.....11
Upgrading from version 5+ to version 6+.....11
Upgrading from version 4+ to version 5+.....11
Extension configuration variables.....11
TypoScript Constants.....11
TypoScript Setup.....16
Display mode specific.....17
Registration process.....18
Registration processes:.....18
Table configuration.....19
Sending invitations.....19
Using frames.....19
Using available hooks.....19
Reducing the length of URL's.....20
Front End Login for Website Users.....20
Configure the extension to use the email address as user name.....20
Wrap for Select, Check Boxes and Radio Buttons.....21
Display of Front End User Data.....21
Using Captcha.....22
Make the user name changeable.....23
Tutorial: Adding fields to the registration form...24
Extend the fe_users table.....24
Add the fields in the HTML template.....24
Modify the TS template Constants and Setup.....25
Add the language labels for the new fields.....25
Troubleshooting.....26

Introduction

What does it do?

The Front End User Registration plugin is a front end user self-registration variant of Kasper Skårhøj's Front End User Admin extension. The Front End User Registration extension features include:

- Use of standard TYPO3 CMS facilities and tools: localization, alternate languages, TypoLink URLs, constant editor, database access;
- Use of country codes, country subdivision codes and language codes of the Static Info Tables;
- Addition of the following fields: gender, status, date of birth, comments, cnum (customer number), terms acknowledged and usergroup;
- Compatibility with extension "Direct Mail" in the use of field 'Receive HTML emails?' (module_sys_dmail_html), 'Receive newsletter?' (module_sys_dmail_newsletter) and of "Direct Mail Categories" (module_sys_dmail_category);
- Sending HTML emails;
- Optional attachment to HTML confirmation emails;
- Optional use of email address as username;
- Optional selection of user group on registration;
- Optional administrative review process for approval of registrations;
- User upload and maintenance of a set of images;
- Validation of the user's Internet site URL;
- Sending an invitation to register;
- Switching salutation mode;
- CSS-styled HTML5 template and optional Zurb Foundation variant;
- Seven optional hooks.

What's new in Version 12

- Requires TYPO3 12 LTS.
- Compatibility with Content Security Policy.
- Default templates were moved to Resources/Public/Templates direcory
- See section on upgrading.

What's new in Version 10

- Requires TYPO3 10 LTS.
- Enabled in TYPO3 11 LTS.
- New TypoScript constant 'allowHtmlInLabels'.
- Render select field as checkboxes relying on TCA renderType rather than renderMode

What's new in Version 7

- Enabled in TYPO3 10 LTS.
- Dependency on extension RSA authentication for TYPO3 (rsaauth) removed.
- New optional Zurb Foundation HTML template variant.

What's new in Version 6

- Requires TYPO3 9 LTS.
- Requires extension RDCT Frontend redirects (rdct).
- Version 5.1.2 is the last version that will work with TYPO3 7 LTS or TYPO3 8 LTS.

- Table fe_groups_language_overlay is dropped. Localization fields are added to the fe_groups table allowing to localize the title and description of frontend groups. No automated migration is offered.

What's new in Version 5

- Requires TYPO3 CMS 7 LTS.
- Is enabled in TYPO3 CMS 8 LTS.
- With TYPO3 CMS 8 LTS, the extension assumes that the image field (and any other user-defined file-referencing field) of the Frontend User (fe_users) record was migrated to FAL; the default upload folder is **2:/tx_srfeuserregister/** in TYPO3 CMS 8 LTS and **uploads/tx_srfeuserregister** in TYPO3 CMS 7 LTS.
- Also with TYPO3 CMS 8 LTS, the extension uses the TYPO3 Doctrine-based database API.
- In version 5.1.0, HTML5 input types are supported and the default HTML template is modified accordingly. In order to support the date input type, the following changes are introduced:
  - the TS constants and setup variables dateFormat and dateSplit are dropped;
  - the rendering format of dates in input forms is left to the browser;
  - the rendering format of dates in other contexts is specified in the locallang.xlf file as index dateFormat, thus allowing for varying formats depending on language.

Sponsors

Development of this extension was sponsored in part by Michael Lang, Marketing Factory Consulting GmbH, Pete Sonderskov, Wild Wild Web, Webspinnerij and Alexander Maringer.

You may sponsor further development of this extension by contacting Stanislas Rolland.

Support

Please see or report bugs on Codeberg: https://codeberg.org/sjbr/sr-feuser-register/issues

Users Manual

First, the extension must be installed and configured: see the Configuration section.

Second, the HTML template needs to be tailored to your site: see the Administration section.

Then, visitors can start registering as front end users.

Registration Process

The default procedure is the following:

- Just below the login box, the visitor is presented a link to a registration form or, if the user is already logged in, a link to a profile editing form;
- The first time visitor completes the registration form and clicks on the submit button. He is presented with a preview form in order to verify the registration information before creating the account. Hitting 'Cancel', he may go back to the form to make any desired correction; he will have to re-enter his password. Upon submitting the verified registration information, the new user is informed that an email is being sent to him to complete the registration process and his account is assigned to a user group preventing any special access;
- An email is sent to the registering visitor. The message contains two links. One link allows the visitor to confirm the registration and the other link cancels the registration (in case somebody has used his email address);
- Clicking on either link brings the visitor to a message page displayed in his browser. If he has confirmed his registration, he is presented with a login box and may log into the site. When the user confirms his registration, his account is assigned a user group allowing him to access whatever pages are targeted at registered users;
- When logged in, the user may edit his account information or delete his account;
- Upon each event (registration, confirmation, cancellation, update, or deletion), an email may be sent to the user to confirm the action. An email notification may also be sent to the administrator of the site. The email to the user may be in HTML format, if desired (the email will always include a plain text version).

Invitation

The extension may also be configured so that a front end user can create an account for another person and send an invitation to register. The invitation email allows the invited person to accept or decline the invitation. If the invited person accepts the invitation, she will be presented a form and requested to enter twice the same password.

Administrative Review

The extension may also be configured so that an email is sent to the site administrator when a visitor confirms his(her) registration.

In such case, the visitor is informed by email that his(her) registration needs to be reviewed and accepted by the site administration before he(she) may login.

The email sent to the site administrator contains all the information provided by the visitor (except the password). It also contains two links allowing the site administrator to accept or refuse the registration.

When the site administrator accepts or refuses the registration, an email is sent to inform the visitor of the decision of the site administration. The visitor may login only after the registration has been accepted by the site administrator.

The administrative review is bypassed when the registration was made by invitation.

Administration

Front End Rendering

HTML Template

The default HTML template provided with the plugin is:

`EXT:sr_feuser_register/Resources/Private/Templates/RegisterHtmlTemplate.html`

CSS Styles

Default CSS styles are defined in file in EXT:sr_feuser_register/Resources/Public/StyleSheets/default.css. They may be included in the frontend by including TS template 'FE User Registration CSS Styles'.

HTML Template Markers

The following is the list of global and main subparts markers used in the example HTML template.

Global markers:

- ###CHARSET### = config.metaCharset or 'utf-8'.

Main subparts markers:

- ###TEMPLATE_CREATE### : template used to display the initial registration form.
- ###TEMPLATE_CREATE_PREVIEW### : template used to display the (optional) registration preview form.
- ###TEMPLATE_CREATE_LOGIN### : template used to display a link to the edit form when the front end user is already logged in.
- ###TEMPLATE_CREATE_SAVED### : when email confirmation request is disabled, template used to display confirmation that the account was created.
- ###TEMPLATE_CREATE_SAVED_REVIEW### : when email confirmation request is disabled, but administrative review is enabled, template used to display confirmation that the account was created and that an administrative review is required.
- ###TEMPLATE_SETFIXED_CREATE### : when email confirmation request is enabled and administrative review is disabled, template used to display confirmation that the account was created but that an email is being sent to the user to complete the registration process.
- ###TEMPLATE_SETFIXED_CREATE_REVIEW### : when administrative review is enabled, template used to display confirmation that the account was created but that an email is being sent to the user to complete the registration process.
- ###TEMPLATE_INVITE### : template used to display the initial account creation form in the case of an invitation.
- ###TEMPLATE_INVITE_PREVIEW### : template used to display the (recommended) account creation preview form, in the case of an invitation.
- ###TEMPLATE_SETFIXED_INVITE### : template used to display confirmation that an account was created and that an invitation email has been sent to the user to complete the registration process or decline the invitation.
- ###TEMPLATE_SETFIXED_OK_APPROVE_INVITE###: template used to display a password update form when the invited person accepts the invitation.
- ###TEMPLATE_EDIT### : template used to display the account or profile editing form.
- ###TEMPLATE_EDIT_PREVIEW### : template used to display the (optional) editing preview form.
- ###TEMPLATE_EDIT_SAVED### : template used to display confirmation that the account was updated.
- ###TEMPLATE_DELETE_PREVIEW### : template used to display the deletion confirmation form.
- ###TEMPLATE_DELETE_SAVED### : template used to display confirmation that the account was deleted.
- ###TEMPLATE_SETFIXED_OK### : when administrative review is disabled, template used to display confirmation that the registration process was completed.

- ###TEMPLATE_SETFIXED_OK_APPROVE_REVIEW### : when administrative review is enabled, template used to display confirmation that the registration was completed, but that the registration must be accepted by the site administrator.
- ###TEMPLATE_SETFIXED_OK_ACCEPT### : when administrative review is enabled, template used to display the response page when the administrator accepts the account registration.
- ###TEMPLATE_SETFIXED_OK_ENTER### : when administrative review is enabled, template used to display the response page when the user clicks on the link in the acceptation email (without auto-login).
- ###TEMPLATE_SETFIXED_OK_REFUSE### : when administrative review is enabled, template used to display the response page when the administrator refuses the account registration.
- ###TEMPLATE_SETFIXED_OK_DELETE### : template used to display confirmation that the registration process was canceled.
- ###TEMPLATE_SETFIXED_OK_UNSUBSCRIBE###: template used to diaplsy the response page when a user was unsubscribed by following a link of a mailing application.
- ###TEMPLATE_SETFIXED_FAILED### : template used to display a message when the registration or cancellation process could not be completed.
- ###TEMPLATE_AUTH#### : template used to display a link to the registration form.
- ###TEMPLATE_NO_PERMISSIONS### : template used to display a message when some illegal access is attempted.
- ###EMAIL_TEMPLATE_CREATE_SAVED_HTML### : when email confirmation request is disabled, template for the HTML message sent to the user when he has created an account.
- ###EMAIL_TEMPLATE_CREATE_SAVED### : when email confirmation request is disabled, template for the plain text message sent to the user when he has created an account.
- ###EMAIL_TEMPLATE_CREATE_SAVED_ADMIN### : when email confirmation request is disabled, template for the plain text notification sent to the site administrator when a user has created an account.
- ###EMAIL_TEMPLATE_EDIT_SAVED_HTML### : template for the HTML message sent to the user when he has updated his account.
- ###EMAIL_TEMPLATE_EDIT_SAVED### : template for the plain text message sent to the user when he has updated his account.
- ###EMAIL_TEMPLATE_EDIT_SAVED_ADMIN### : template for the plain text notification sent to the site administrator when a user has updated his account.
- ###EMAIL_TEMPLATE_SETFIXED_CREATE_HTML### : when email confirmation request is enabled and administrative review is disabled, template for the HTML message sent to the user when he has created an account and need to confirm his registration.
- ###EMAIL_TEMPLATE_SETFIXED_CREATE### : when email confirmation request is enabled and administrative review is disabled, template for the plain text message sent to the user when he has created an account and needs to confirm his registration.
- ###EMAIL_TEMPLATE_SETFIXED_CREATE_ADMIN### : when email confirmation request is enabled and administrative review is disabled, template for the plain text notification sent to the site administrator when a user has created an account and needs to confirm his registration.
- ###EMAIL_TEMPLATE_SETFIXED_CREATE_REVIEW_HTML### : when administrative review is enabled, template for the HTML message sent to the user when he has created and he needs to confirm his registration, and administrative review will be required.
- ###EMAIL_TEMPLATE_SETFIXED_CREATE_REVIEW### : when administrative review is enabled, template for the plain text message sent to the user when he has created and he needs to confirm his registration, and administrative review will be required.
- ###EMAIL_TEMPLATE_SETFIXED_CREATE_REVIEW_ADMIN### : when administrative review is enabled, template for the plain text notification sent to the site administrator when a user has created an account and needs to confirm his registration.
- ###EMAIL_TEMPLATE_SETFIXED_REVIEW_ADMIN_HTML### : when administrative review is enabled, template for the HTML message sent to the site administrator when a user has approved his/her registration and a decision to accept or refuse the registration is required.
- ###EMAIL_TEMPLATE_SETFIXED_REVIEW_ADMIN### : when administrative review is enabled, template for the plain text message sent to the site administrator when a user has approved his/her registration and a decision to accept or refuse the registration is required.

- ###EMAIL_TEMPLATE_SETFIXED_INVITE_HTML### : template for the HTML invitation message sent to a person for whom an account has been created and requesting the invitation be accepted to confirm registration, or to decline the invitation (or ignore the message).
- ###EMAIL_TEMPLATE_SETFIXED_INVITE### : template for the plain text invitation message sent to a person for whom an account has been created and requesting the invitation be accepted to confirm registration, or to decline the invitation (or ignore the message).
- ###EMAIL_TEMPLATE_SETFIXED_INVITE_ADMIN### : template for the plain text notification sent to the site administrator when an invitation to register has been sent and the invited person needs to confirm his/her registration.
- ###EMAIL_TEMPLATE_SETFIXED_APPROVE_HTML### : when email confirmation request is enabled and administrative review is disabled, template for the HTML message sent to the user when he has confirmed the registration.
- ###EMAIL_TEMPLATE_SETFIXED_APPROVE### : when email confirmation request is enabled and administrative review is disabled, template for the plain text message sent to the user when he has confirmed the registration.
- ###EMAIL_TEMPLATE_SETFIXED_APPROVE_ADMIN### : when email confirmation request is enabled and administrative review is disabled, template for the plain text notification sent to the site administrator when a user has confirmed his registration.
- ###EMAIL_TEMPLATE_SETFIXED_APPROVE_REVIEW_HTML### : when administrative review is enabled, template for the HTML message sent to the user when he has confirmed the registration.
- ###EMAIL_TEMPLATE_SETFIXED_APPROVE_REVIEW### : when administrative review is enabled, template for the plain text message sent to the user when he has confirmed the registration.
- ###EMAIL_TEMPLATE_SETFIXED_APPROVE_REVIEW_ADMIN### : when administrative review is enabled, template for the plain text notification sent to the site administrator when a user has confirmed his registration.
- ###EMAIL_TEMPLATE_SETFIXED_ACCEPT_HTML### : when administrative review is enabled, template for the HTML welcome message sent to the user when the registration was accepted.
- ###EMAIL_TEMPLATE_SETFIXED_ACCEPT### : when administrative review is enabled, template for the plain text welcome message sent to the user when the registration was accepted.
- ###EMAIL_TEMPLATE_SETFIXED_ACCEPT_ADMIN### : when administrative review is enabled, template for the plain text notification sent to the site administrator when a registration was accepted.
- ###EMAIL_TEMPLATE_SETFIXED_REFUSE_HTML### : when administrative review is enabled, template for the HTML message sent to the user when the registration was refused.
- ###EMAIL_TEMPLATE_SETFIXED_REFUSE### : when administrative review is enabled, template for the plain text message sent to the user when the registration was refused.
- ###EMAIL_TEMPLATE_SETFIXED_REFUSE_ADMIN### : when administrative review is enabled, template for the plain text notification sent to the site administrator when a registration was refused.
- ###EMAIL_TEMPLATE_SETFIXED_DELETE_HTML### : template for the HTML message sent to the user when he has canceled his registration.
- ###EMAIL_TEMPLATE_SETFIXED_DELETE### : template for the plain text message sent to the user when he has canceled his registration.
- ###EMAIL_TEMPLATE_SETFIXED_DELETE_ADMIN### : template for the plain text notification sent to the site administrator when a user has canceled his registration.
- ###EMAIL_TEMPLATE_DELETE_SAVED_HTML### : template for the HTML message sent to the user when he has deleted his account.
- ###EMAIL_TEMPLATE_DELETE_SAVED### : template for the plain text message sent to the user when he has deleted his account.
- ###EMAIL_TEMPLATE_DELETE_SAVED_ADMIN### : template for the plain text notification sent to the site administrator when a user has deleted his account.
- ###EMAIL_TEMPLATE_SETFIXED_UNSUBSCRIBE_HTML###: template for the HTML message sent to the user to confirm that he/she was unsubscribed, but that his account is still active.
- ###EMAIL_TEMPLATE_SETFIXED_UNSUBSCRIBE###: template for the plain text message sent to the user to confirm that he/she was unsubscribed, but that his account is still active.

Localization

Adapting labels

You may adapt labels to your needs and languages.

Any label may be overridden by inserting the appropriate assignment in your TS template setup:

```
plugin.tx_srfeuserregister._LOCAL_LANG.languageCode.labelName = overridingValue
```

You can find the name of the label you want to modify (or translate) by inspecting the extension file EXT:sr_feuser_register/Resources/Private/Language/locallang.xlf.

Overriding labels specified in TCA

You may also override by the same method labels from other files when they are referenced by the TCA definition of a field (see the tutorial section on Adding fields to the registration form). This is done as follows:

```
plugin.tx_srfeuserregister._LOCAL_LANG.languageCode.tableName.fieldName = overridingValue
```

Switching salutation mode

You may also switch the salutation mode used in these labels when this is relevant for the language being used and when the labels are either available in file EXT:sr_feuser_register/Resources/Private/Language/locallang.xlf or provided by TypoScript setup. See the TypoScript Reference section.

v_dear_male or v_dear_female markers will be used instead of v_dear if a gender has been entered by the user.

Localization of user group title

This extension adds table **fe_groups_language_overlay** in order to allow localization of the user group title.

Labels with variables

Some labels in EXT:sr_feuser_register/Resources/Private/Language/locallang.xlf have names starting with 'v_'. In those labels, the following variables may be used:

- %1$s : the title of the pid containing the front end user records created by the extension;
- %2$s : the user name of the front end user;
- %3$s : the name of the front end user;
- %4$s : the email address of the front end user.

Special functions can be inserted. They will be replaced by the result of the function.

- {data:<field>}: value of this field of the FE user record
- {tca:<field>}: value of the marker ###TCA_INPUT_*field*###'
- {meta:<stuff>}: extra stuff functions:

  title: page title

Adding extra labels

Property extraLabels in TS setup may specify a list of extra labels that may be used in the HTML template.

The values of these labels are specified in TS setup with the same type of assignment as when overriding localized labels:

```
plugin.tx_srfeuserregister._LOCAL_LANG.languageCode.extraLabelName = extraLabelValue
```

Configuration

Configuration steps

These are the steps to configuring the Front End User Registration extension:

1. Install the extension using the Extension Manager. If not already installed, it is required that you install the extensions Frontend Login for Website Users (felogin), RDCT Frontend redirects (rdct) and Static Info Tables (static_info_tables).
2. The extension always uses character set utf-8 by default.
3. Use the status report in Admin Tools->Reports to check for possible problems with the installation of the extension.
4. Add the following static template to your TypoScript template: 'FE User Registration Setup'.
5. Create a folder page that will contain the records of front end users. Set the TS template constant **pid** to the page id of this folder. In the folder, create two Front End User Groups. Set the TS template constant **userGroupUponRegistration** to the uid of the first group and constant **userGroupAfterConfirmation** to the uid of the second group. The second group gives access to the pages targeted at the registered front end users, while the first group does not. If you use the generation of the user group from an XML file then the user groups will be filled in from uid values in the setfixed setup array.
6. Insert the login box plugin on any page. Then, on the same page, after the login box, insert the Front End User Registration extension, using the default (DE: 'normal') display mode, but setting the Record Storage Page to the folder that will contain the front end user records. Set the TS template constant **loginPID** to the page id of this page.
7. Create a second page after the previous one and set the access general options to "**Hide at login**". Insert the Front End User Registration extension, setting the display mode to Create (DE: 'Anlegen'), and the Record Storage Page to the folder that will contain the front end user records. Note that the access restriction should be set on the page, not on the content elements. Set the TS template constant **registerPID** to the page id of this page.
8. Create a third page limiting access to this page to the second user group you created. Insert the Front End User Registration extension, setting the display mode to Edit, and the Record Storage Page to the folder that will contain the front end user records. Note that the access restriction should be set on the page, not on the content elements. Set the TS template constant **editPID** to the page id of this page.
9. Create a fourth page and click the checkbox "**Hide in menu**". Insert the Front End User Registration plugin, using the Default display mode and setting the Record Storage Page to the folder that will contain the front end user records. Note that no access restriction should be set on this page, because otherwise unregistered users cannot see the confirmation page, and they cannot click on the confirmation link. Set the TS template constant **confirmPID** to the page id of this page.
10. Decide which fields you want included on the registration form and, among those, which ones you want to be required in order to register. Set TS template constants **formFields** and **requiredFields**.
11. Review the extension constants described below. All these properties may be conveniently edited using the Constant Editor TS template tool. If you do not use the Constant Editor to configure the extension, please note the form of the constants assignments in the constants section of your TS template:

    ```
    plugin.tx_srfeuserregister_pi1.property = value
    ```
    or if you assign multiple values:
    ```
    plugin.tx_srfeuserregister_pi1 {
     property = value
    ...
    }
    ```

Upgrading to version 12.4.1+

When you upgrade to version 12.4.1+:

- You need to first upgrade to TYPO3 12 LTS.
- Default HTML templates are moved to Resources/Public/Templates directory.
- HTML templates are modified : all onclick attributes must be removed; in template part ###TEMPLATE_DELETE_PREVIEW###, attribute id="tx_srfeuserregister_pi1_delete_doNotSave" must be added to the input tag with name="tx_srfeuserregister_pi1[doNotSave]".
- TS Constant onChangeAttribute is modified : the value is now inserted in the body of a JS event handler. See the default value.

Upgrading from version 5+ to version 6+

When you upgrade from version 5+ to version 6+:

- You need to first upgrade to TYPO3 9 LTS.
- You should run the TYPO3 database analalysis tool in order to add the localization columns to table fe_groups.
- If you localized frontend groups using record overlays, you will have to translate the frontend groups records manually. No automated migration tool is offered by the extension.

Upgrading from version 4+ to version 5+

When you upgrade from version 4+ to version 5+:

- With TYPO3 CMS 7 LTS, there is nothing special to do.
- With TYPO3 CMS 8 LTS, the image field (and any other user-defined file-referencing field) of the Frontend User (fe_users) record must be migrated to FAL.
- With TYPO3 CMS 8 LTS, the default upload folder is **2:/tx_srfeuserregister/**.

Extension configuration variables

The Extension Manager installation dialog allows you to set the following extension configuration variables:

- **Image upload folder**: this is the name of the upload folder for images uploaded by front end users. The default value is **2:/tx_srfeuserregister/** in TYPO3 CMS 8 LTS and **uploads/tx_srfeuserregister** in TYPO3 CMS 7 LTS. In some configurations, you may prefer to set it to **uploads/pics –** changes will update the TCA-definition of the image column of the fe_users table;
- **Maximum image size:** this is the maximum size in kBytes an image may be to be uploaded by front end users. The default value is **250 –** changes will update the TCA-definition of the image column of the fe_users table;
- **Allowed image types:** this is the list of accepted file extensions for uploaded images. The default value is **png, jpg, jpeg, gif, tif, tiff –** changes will update the TCA-definition of the image column of the fe_users table.

TypoScript Constants

Please note that the following properties refer to TS template constants, not to TS template setup.

If you do not use the constant module_sys_dmail_categoryEditor to configure the extension, please note the form of the constants assignments in the constants section of your TS template: **plugin.tx_srfeuserregister_pi1.*property* = *value***

Property:	Data type:	Description:	Default:
file.templateFile	string	File name of the HTML template	EXT:sr_feuser_register/Resources/Private/Templates/RegisterHtmlTemplate.html

Property:	Data type:	Description:	Default:
file.attachmentFile	string	File name of a file to be attached to the registration confirmation email.	EXT:sr_feuser_register/Resources/Private/TextFiles/attachment.txt
file.termsFile	string	File name of the terms of usage file. Note: This is used in conjunction with the field 'terms_acknowledged'.	EXT:sr_feuser_register/Resources/Public/TextFiles/terms.txt
termsUrl	string	Page (id or id,type) or url where the terms of usage are shown. Note: If set, overrides file.termsFile. Note: This is used in conjunction with the field 'terms_acknowledged'.	
enableHTMLMail	boolean	If set, emails sent to the front end user will be sent in HTML format. A plain text version will always be included in the emails.	1
enableEmailAttachment	boolean	If set, and if enableHTMLMail is also set, the attachment file - specified by file.attachmentFile - will be attached to the registration confirmation HTML email.	0
enableAutoLoginOnCreate	boolean	Enable auto-login on account creation: if set and if email confirmation is not set, the user will be automatically logged in upon creation of his(her) account.	0
enableAutoLoginOnConfirmation	boolean	If set, the user will be automatically logged in upon confirmation of his registration.	0
autoLoginRedirect_url	string	When auto login is enabled, URL to which the user may be redirected upon login.	
allowHtmlInLabels	boolean	Enable HTML in labels (HTML characters will not be converted).	0
HTMLMailCSS	string	File name of the HTML emails style sheet. If HTML emails are enabled, this file contains the CSS style sheet to be incorporated in these emails.	EXT:sr_feuser_register/Resources/Public/StyleSheets/htmlmail.css
email	string	Administration email address. This email address will be the sender email address and the recipient of administrator notifications.	MyTypo3Site@mydomain.org
siteName	string	Name of the registering site. If set, this will be used as the email address name in all sent emails and may be used as a signature on the mails.	My Typo3 Site
formFields	string	List of fields to be included on the front end user registration form. Should be a subset of the columns of the 'fe_users' table. Note: If Direct Mail (direct_mail) extension is not installed, fields module_sys_dmail_newsletter, module_sys_dmail_category and module_sys_dmail_html are ignored (removed from the list). Note: The default HTML template contains markers for the following fields: username, password, gender, name, first_name, middle_name, last_name, date_of_birth, status, address, city, zone, static_info_country, zip, telephone, fax, email, usergroup, terms_acknowledged, language, title, company, www, image, comments, module_sys_dmail_newsletter, module_sys_dmail_category, module_sys_dmail_html, captcha_response	username, password, gender, first_name, last_name, status, date_of_birth, email, address, city, zone, static_info_country, zip, telephone, fax, language, title, company, www, module_sys_dmail_html, module_sys_dmail_newsletter, module_sys_dmail_category, image, comments, terms_acknowledged, disable

Property:	Data type:	Description:	Default:
requiredFields	string	List of fields that must be filled in on the front end user registration form. Should be a subset of the list specified on the 'formFields' property. Note: captcha_response should not be set as a required field.	username, password, first_name, last_name, email
doNotEnforceUsername	boolean	If set, field username is not forced to be part of formFields and requiredFields.	0
unsubscribeAllowedFields	string	Unsubscribe allowed fields: List of fields that are allowed to be updated by an UNSUBSCRIBE link without any login. Note: Applies to setfixed links from mailing applications with the following query string values: &tx_srfeuserregister_pi1[cmd]=setfixed&sFK=UNSUBSCRIBE. A value for a field listed may be specified with a string of the form: &fD[fieldName]=value. The value of the field of the will be updated when the link is processed.	module_sys_dmail_newsletter
codeLength	int	Length of the authentication codes. Note: Direct Mail extension uses only 8 in its calculations.	8
formName	string	Name of the HTML form. The name is also referenced on the onChangeCountryAttribute. See below.	fe_users_form
onChangeCountryAttribute	string	Javascript to execute when the selected country is changed in the country selector box.	event.target.form.elements.namedItem('tx_srfeuserregister_pi1[countryChange]').value = 1; event.target.form.submit();
defaultCODE	string	Default CODE, when not specified on the inserted plugin record. May be CREATE or EDIT or empty.	None
pid	list of page_id's	List of pid's containing Front end user records. If the records edited/created are located on page(s) other than the 'current', enter the list of pages here. The first page in the list is used for creation.	None
userGroupsPidList	list of page_id's	User groups records PID list: List of page id's on which user groups records are located. Note: If specified, user groups records will be assumed to be located on one of the specified pages, rather than on the page specified by 'pid'.	None
module_sys_dmail_category_PIDLIST	string	PID list for Direct Mail categories. The Direct mail categories used by the plugin will be restricted to those found on the pages identified by the PID's in this list.	None
pidTitleOverride	string	The specified string will override the title of the System Folder page specified by the pid property. The title of the System Folder is used in some online and email messages in the default HTML template.	None
registerPID	page_id	Registration page PID: PID of the page on which the extension is inserted with the intent of serving as the front end user registration page. If not set, will default to 'current' page.	None
editPID	page_id	Profile editing page PID: PID of the page on which the extension is inserted with the intent of serving as the front end user profile editing page. If not set, will default to 'current' page.	None
linkToPID	page_id	Link to after edit PID: PID of a page to be linked to after the user has completed the editing of his/her profile. See also linkToPIDAddButton.	None
linkToPIDAddButton	boolean	Add a button to link to after edit. If set, an additional button is displayed on the profile editing page, or on the profile editing preview page, to save the changes and link to the page specified by linkToPID.	0
confirmPID	page_id	Confirmation page PID: PID of the page on which the extension is inserted with the intent of serving as the front end user confirmation page (or setfixed page!). Meaningful only if email confirmation request is enabled.	None

Property:	Data type:	Description:	Default:
confirmInvitationPID	page_id	Confirmation of invitation page PID: PID of the page on which the extension is inserted with the intent of serving as the front end user confirmation page (or setfixed page!) when replying to an invitation. Meaningful only if email confirmation request is enabled. Note: If not set, will take the same value as confirmPID.	None
confirmType	int	Confirmation page Type: Type (or pageNum) of the confirmation page. Meaningful only if email confirmation request is enabled.	0
loginPID	page_id	Login page PID: PID of the page on which the New login box extension is inserted with the intent of serving as the front end user login page. If not set, will default to 'current' page.	None
enablePreviewRegister	boolean	Enable preview on registration. If set, the registration dialog will include a preview of the front end user data before it is saved.	1
enablePreviewEdit	boolean	Enable preview on profile update. If set, the profile update dialog will include a preview of the front end user data before it is saved.	1
enableAdminReview	boolean	Enable administrative review. If set, the site administrator will be asked to accept the registration before it becomes enabled.	0
enableEmailConfirmation	boolean	Enable email confirmation request: If set, an email will be sent to the prospective front end user requesting a confirmation of registration.	1
useEmailAsUsername	boolean	Enable the use of the email address as username. Note: If enableEmailConfirmation is also set, the email field will NOT be included in the front end user profile editing form.	0
generateUsername	boolean	Generate the username. If set, the username is assumed to be generated. Note: Hook registrationProcess_beforeConfirmCreate must be configured.	0
allowUserGroupSelection	boolean	Allow selection of usergroup on registration. If set, the user may select to adhere to user group(s) when registering. Note: The selectable usergroups must be located in the page identified by the **pid** constant. Note: If constants **userGroupUponRegistration** and **userGroupAfterConfirmation** are set, the usergroups they specify are not selectable. Note: Field **usergroup** must be included in the list specified by constant **formFields**.	0
allowUserGroupUpdate	boolean	Allow selection of usergroup on editing. If set, the user may edit the list of user groups to which he(she) belongs. Note: See also constant **allowUserGroupSelection**.	0
allowMultipleUserGroupSelection	boolean	Allow selection of multiple usergroups. If set, the user may select to adhere to multiple user groups. Note: See also constants **allowUserGroupSelection** and **allowUserGroupUpdate**.	0
allowedUserGroups	string	Comma separated list of user groups to be selectable. If 'ALL', then all groups are allowed. Note: See also constant **allowUserGroupSelection**.	
allowedSubgroups	string	Comma separated list of subgroups from which all user groups shall be selectable. The user groups from allowedUserGroups shall be added also. Note: See also constant **allowedUserGroups**.	
deniedUserGroups	string	Comma separated list of user groups to be never selectable. These usegroups supersede the resulted user grous from allowedUserGroups and allowedSubgroups. Note: See also the constants **allowedUserGroups**. and **allowedSubgroups**	

Property:	Data type:	Description:	Default:
keepUnselectableUserGroups	boolean	If set and if a FE user is changing his FE user group then all the other FE user groups which are not shown in the select box will remain. If unset then the user will only keep the user group selected by himself and the reserved user groups which consist of the temporal user groups from the registration process: userGroupUponRegistration, userGroupAfterConfirmation, userGroupAfterAcceptation This is only useful if allowUserGroupUpdate has been set, too. Note: See also the constants **allowedUserGroups**., **allowedSubgroups** and **deniedUserGroups**	0
enableEmailOnApprove	boolean	Enable email on approval. If set, an email will be sent to the front end user when he confirms his registration. Effective only if email confirmation request is enabled.	1
enableEmailOnRefuse	boolean	Enable email on refusal: If set, an email will be sent to the prospective front end user when he refuses to confirm his registration. Effective only if email confirmation request is enabled.	1
enableEmailOnAdminRefuse	boolean	Enable email on denial: If set, an email will be sent to the prospective front end user when the site administrator refuses to confirm his(her) registration.	1
enableEmailOnRegister	boolean	Enable email on registration: If set, an email will be sent to the front end user confirming his registration. Ignored if email confirmation request is enabled.	1
enableEmailOnUpdate	int	Enable email on profile update. If set to 1, an email will be sent to the front end user to confirm the update of his profile.	1
enableEmailOnDelete	boolean	Enable email on delete. If set, an email will be sent to the front end user to confirm the deletion of his account.	1
enableEmailOnUnsubscribe	boolean	Enable email on unsubscribe: If set, an email will be sent to the front end user end its subscription to newsletters through a link from a mailing application.	1
enableAdminNotifyConfirmation	boolean	Enable admin notification on confirmation request. If set, an email will be sent to the site administrator when a request for confirmation of registration is sent to a user.	1
enableAdminNotifyOnApprove	boolean	Enable admin notification on approval: If set, an email will be sent to the site administrator when a user confirms his registration.	1
enableAdminNotifyOnRefuse	boolean	Enable admin notification on refusal. If set, an email will be sent to the site administrator when a user refuses to confirm his registration.	1
enableAdminNotifyOnRegister	boolean	Enable admin notification on registration. If set, an email will be sent to the site administrator when a user registers. This is ignored if email confirmation request is enabled.	1
enableAdminNotifyOnUpdate	boolean	Enable admin notification on update: If set, an email will be sent to the site administrator when a user updates his profile. If set to 2, only the changed fields will be sent.	1
enableAdminNotifyOnDelete	boolean	Enable admin notification on deletion: If set, an email will be sent to the site administrator when a user deletes his account.	1
enableAdminNotifyOnEnter	boolean	Enable admin notification on entering: If set, an email will be sent to the site administration when a user clicks on the link to log in.	0
enableAdminNotifyOnAdminAccept	boolean	Enable admin notification on approval by admin: If set, an email will be sent to the site administration when a registration is accepted by the administration.	1
enableAdminNotifyOnAdminRefuse	boolean	Enable admin notification on refusal by admin: If set, an email will be sent to the site administration when a registration is refused by the administration.	1
dmailCheckedUponRegistration	boolean	Check all the checkboxes for Direct Mail categories in creation dialogues.	0
userGroupUponRegistration	string	User group(s) upon registration: The value of the user group field. Must be a list of integers WITHOUT spaces between the comma separated values! Furthermore, these integers MUST point to actual fe_groups records!	None
userGroupAfterConfirmation	string	User group(s) after confirmation: The value of the user group(s) assigned to the front end user after receipt of his confirmation.	None

Property:	Data type:	Description:	Default:
userGroupAfterAcceptation	string	User group(s) after acceptation: The value of the user group(s) assigned to the front end user after acceptation of his(her) registration, when the administrative review is enabled. Note: If administrative review is not enabled, this property is ignored.	None
passwordAtLeast	int	Minimum password length: The minimum number of characters that the password must contain.	5
passwordAtMost	int	Maximum password length: The maximum number of characters that the password may contain.	40
usernameAtLeast	int	Minimum username length: The minimum number of characters that the username must contain.	6
usernameAtMost	int	Maximum username length: The maximum number of characters that the username may contain.	50
nameAtMost	int	Maximum name length: The maximum number of characters that the name of the front end user may contain.	80
forceFileDelete	boolean	If set, on record deletion, related images and files will be deleted even if the record in the database is only marked 'deleted.'	1
maxImages	int	Number of images that may be uploaded. Value: An integer larger than 0 and smaller than 7. Note: Has no effect if the field 'image' is not in the list formFields.	6
salutation	string	If set, should be either 'formal' or 'informal'. Note: This property will change the salutation mode used in the labels displayed in the front end, provided that this is meaningful in the language being displayed and that translators have provided the informal version.	None
useShortUrls	boolean	Enable the use of short URLs in email messages sent to users is enabled.	1
useLocalization	boolean	Enable the localization for selectable items.	0
useLocalCountry	boolean	Show the country names in their local languages.	0
shortUrlLife	int+	Short URL cache lifespan. This is the number of days that short URL's will be kept in the DB. After this delay, the short URL's will be removed. Confirmation URL's included in email messages older than this number of days will not work.	30

TypoScript Setup

Please note that the following properties refer to TS template setup, not to TS template constants.

When installing this extension, you should NOT use the following setting:

```
config.disableAllHeaderCode = 1
```

This setting will prevent the inclusion of Javascript essential to the correct behavior of the profile editing features.

Property:	Data type:	Description:	Default:
extraLabels	string	Comma-separated list of additional labels to use in the HTML template. See section Labels and localisation about adding extra labels.	None
templateFile	string	Same as file.templateFile from Constants. This is needed under Setup for language specific template files only.	

where.static_countries	string	Set a SQL WHERE condition to follow for the selected country in the static_countries table of the static_info_tables extension. Maybe you want to see only users from EU countries on your site.
		
		Example:
		`plugin.plugin.tx_srfeuserregister_pi1 {`
		`  where.static_countries = cn_eu_member = 1`
		`}`	

evalFunc	function-name	additional evaluation function for the records eg "user_myfunction" or "user_myclass->main"	

Property:	Data type:	Description:	Default:
userFunc_updateArray	function-name	User function to update the records	

displayRequired	cObject	Use this cOject for the display of required fields. By default the required fields are printed with an asterisk (*).
		
		Example:
		`displayRequired = COA`
		`displayRequired {`
		`  10 = TEXT`
		`  10.value = You must fill this in!`
		`  10.wrap = <b>Attention:</b> | *`
		`}`	

email.admin	string	Administration email address : the recipient of administrator notifications.	Defaults to the value of constant 'email'
email.from	string	This email address will be the sender email address for all mails.	Defaults to the value of constant 'email'
email.replyToAdmin	string	This email address will be the reply-to address of emails sent to the user.	Defaults to the value of constant 'email'
email.replyTo	string	This email address will be the reply-to address of emails sent to the administration. Possible values are : - 'user' : the reply-to adress will be the address of the user - an email : the reply-to address of emails sent to the administration.	

Display mode specific

Use the display mode (lower case) as the first parameter.

Example:

```
edit.overrideValues.usergroup = 3
```

Property:	Data type:	Description:	Default:
fields	string	List of fields to be included on the front end user registration form. Should be a subset of the columns of the 'fe_users' table. Allows to specify a different list of fields for each CODE.	See TS constant formFields
required	string	List of fields that must be filled in on the front end user registration form. Should be a subset of the list specified on the 'formFields' property. Allows to specify a different list of required fields for each CODE.	See TS constant requiredFields
defaultValues	array of strings	Default values for the fields.	

overrrideValues	array of strings/stdWrap	Array of field names for which a fixed value or stdWrap function shall be applied.
		The stdWrap e.g. can be used when FE Users should not be able to change a field, which they must fill out only at registration.
		
		Example:
		`overrideValues {`
		`  username =`
		`  usergroup >`
		`  disable = 0`
		`  by_invitation >`
		`  user_myfield = {TSFE:fe_user|user|user_myfield}`
		`  user_myfield.insertData = 1`
		`}`
			None

Property:	Data type:	Description:	Default:

evalValues	array of strings	Array with field names as keys and lists of validation functions as values. The validation functions should to be applied to the values entered in the named fields. Possible functions are:
		• uniqueLocal : the entered value must be unique for the field among all records in the configured pid's;
		• uniqueDeletedLocal : the entered value must be unique for the field among all records in the configured pid's, including deleted or disabled records;
		• uniqueGlobal : the entered value must be unique for the field among all records in the table;
		• uniqueDeletedGlobal : the entered value must be unique for the field among all records in the table, including deleted or disabled records;
		• twice : the same value should be entered in the field and the field named *fieldName_again;*
		• unsetEmpty : the value is unset if the entered value is empty;
		• email : the entered value must be a valid email address;
		• required : a value must be entered;
		• atLeast[*numberOfCharacters*] : the minimum number of characters to be entered;
		• atMost[*numberOfCharacters*]: the maximum number of characters to be entered;
		• wwwURL : a valid url must be entered;
		• date : a date must be entered in HTML5 format (Y-m-d);
		• upload[*numberOfFiles*] : the field allows to upload files;
		• preg[*regularExpression*] : the regular expression is applied to the entered value and a match must be found;
		• hook : function *evalValues* of the configured hooks are applied to the entered value;
		• captcha_response : freecap
		
		Example:
		`evalValues {`
		`password = twice, atLeast[5], atMost[40]`
		`username = uniqueLocal, atLeast[6], atMost[50]`
		`email = email,atMost[255],uniqueLocal`
		`date_of_birth = date`
		`image = upload[6]`
		`}`	

Registration process

Use 'setfixed' as the first and the registration process name (upper case) as the second parameter.

Example:

```
setfixed.ACCEPT {
   _FIELDLIST = uid,pid,usergroup
   usergroup = {$plugin.tx_srfeuserregister_pi1.userGroupAfterAcceptation}
   disable = 0
}
```

Registration processes:

- APPROVE: It starts after the user clicks the confirmation link in the email.
- ACCEPT: It starts after the admin clicks the acceptation confirmation link in the email.
- DELETE: It starts when the user starts the deletion process.
- REFUSE: It starts after the admin clicks the refusal link in the email
- ENTER: It starts after the user clicks the login link in the email.

Property:	Data type:	Description:	Default:
_FIELDLIST	string	List of fields to be used by the generated links. The encoding and decoding process wil consider these fields. Allows to specify a different list of fields for each PROCESS.	uid,pid,usergroup

Property:	Data type:	Description:	Default:
fieldname	string	Replace 'fieldname' with the database's field name of the table fe_users or tt_address resp. . The listed table field names will get a new value after the registration process.	

Table configuration

The last but one/two value will be the name of the view. It can be 'ALL', if it is valid for all views..

Views correspond to the display mode in upper case:

EDIT, CREATE

Example:

```
plugin.tx_srfeuserregister_pi1.conf.sys_dmail_category.ALL.sys_language_uid = 0
```

Property:	Data type:	Description:	Default:
sys_language_uid	integer	The system language uid as in config.sys_language_uid. You can override this on the extension level for each table and field to use Dmail categories in multiple languages under all website languages. Do not set it if you want to use the settings from config.sys_language_uid in the case when the Dmail categories are translated.	

Sending invitations

Create a page, limiting access to this page to front end user groups who will be authorized to send invitations to register. Insert the Front End User Registration plugin, setting the display mode to 'Invite' and the Starting Point to the System Folder that will contain the front end user records created.

When an account is created through this page, an invitation message will be sent to the email address specified on the account. The invited person may accept or decline the invitation.

Using frames

If the registration confirmation page (confirmPID) is designed to be displayed within frames, then add the following lines to your TS template setup:

[globalVar = TSFE:id = {$plugin.tx_srfeuserregister_pi1.confirmPID}]

config.page.frameReloadIfNotInFrameset = 1

config.linkVars >

config.linkVars = L,tx_srfeuserregister_pi1,fD,cmd,rU,aC

config.no_cache = 1

[global]

after setting plugin.tx_srfeuserregister_pi1.confirmPID in your TS template constants.

Note that cmd, rU and aC are in the list for compatibility with the Direct mail extension.

Using available hooks

Two sets of hooks may be used by the extension.

The first set of hooks is named **confirmRegistrationClass** and offers the possibility of the following two hooks:

- **confirmRegistrationClass_preProcess**: this hook is invoked just BEFORE the registration confirmation (or so-called setfixed) is processed;
- **confirmRegistrationClass_postProcess**: this hook is invoked just AFTER the registration confirmation (or so-called setfixed) is processed.

The second set of hooks is named **registrationProcess** and offers the possibility of the following four hooks:

- **registrationProcess_beforeConfirmCreate**: this hook is invoked just BEFORE the front end user record is filled

for preview by the user;

- **registrationProcess_afterSaveCreate**: this hook is invoked just AFTER the front end user record has been created and saved;
- **registrationProcess_afterSaveEdit**: this hook is invoked just AFTER the front end user record has been edited and saved;
- **registrationProcess_beforeSaveDelete**: this hook is invoked just BEFORE the front end user record is deleted.
- **addGlobalMarkers**: this hook is invoked in the init function of the marker object.

Each set of hooks must be defined within a class, each hook being a method of this class. However, all seven hooks could be defined as methods of the same class.

Some of the hooks receive two parameters: the current front end user record (or marker array, in the case of addGlobalMarkers) and a reference to the invoking object. In the case of **confirmRegistrationClass_preProcess** and of **registrationProcess_beforeConfirmCreate,** the first parameter is also passed as a reference so that some action may be taken on the content of the record.

The hooks are configured by the following assignments which could be included in the ext_localconf.php file of the extension providing the hooks:

```
$TYPO3_CONF_VARS['EXTCONF']['sr_feuser_register']['tx_srfeuserregister_pi1']['confirmRegistrationClass'][] = classReference;
$TYPO3_CONF_VARS['EXTCONF']['sr_feuser_register']['tx_srfeuserregister_pi1']['registrationProcess'][] = classReference;
```

Note that these are arrays, therefore you could configure multiple hooks of each type for various purposes.

File hooks/class.tx_srfeuserregister_hooksHandler.php of this extension provides a simple example class containing seven hooks doing nothing but provinding the interface you must use. File ext_localconf.php also contains example statements for configuring these example hooks. They are commented out. If you uncomment them, you should see the hooks being invoked when the extension is used in the front end. You must enter some PHP echo lines into the example hooks.

In the case of the **confirmRegistrationClass,** if the confirmation page is configured to be redirected to auto-login, you may not notice on the front end that the example hooks are being invoked.

In the case of the **registrationProcess_beforeConfirmCreate** example hook, if the plugin is configured to generate a username, a username is generated based on the first and last names of the user.

Reducing the length of URL's

You may find that the URL's sent in emails to the front end user are too long and may be broken when using plain text emails.

Using plain text emails and notification_email_urlmode

If you are using plain text emails (**enableHTMLMail** is set to 0):

- In your TS template setup, set config.notification_email_urlmode = 76 or config.notification_email_urlmode = all . See TSRef for information about this CONFIG setup property.

Using the short URL feature

This approach is compatible with both HTML and plain text emails. Simply enable the feature by setting the TS constant **useShortUrls** = 1 in your TS template. You should also review the default value of TS constant **shortUrlLife** and set it to a value that fits your needs.

Front End Login for Website Users

Use the page for login or a top level page, setting the Page "General Storage Storage" to the System Folder that will contain the front end user records created by the extension.

Configure the extension to use the email address as user name

1. Use the Constant editor to set the constant **useEmailAsUsername** to 1;
2. You may want to change the relative position of the email field in the following subparts of the HTML template: ###TEMPLATE_CREATE###, ###TEMPLATE_INVITE### and ###TEMPLATE_EDIT###.

Note that if you have set constant **enableEmailConfirmation**, the email field will not appear on the editing form because no confirmation request is sent when the email address is modified.

Also in tt_products the email addresses are used as user names.

Wrap for Select, Check Boxes and Radio Buttons

You can have different select boxes defined in TCA, which can also be shown as checkboxes in FE. You will need this for DirectMail or overwritten topics. The configuration needs the activity ('create', 'edit', 'email' for email, 'preview' for preview, 'input' for the page with input fields) and the field name of fe_users.

activities: EMAIL

Example Setup:

```
plugin.tx_srfeuserregister_pi1 {
      select {
            email {
                  module_sys_dmail_category.item.wrap = | <br/>
            }
      }
}
```

Property:	Data type:	Description:	Default:
item	stdWrap	Wrap around each single item. additional property: notLast: if set the last item will not be wrapped	
list	stdWrap	Wrap around the list of items.	

Display of Front End User Data

If you want to display the FE users data without any edit functionality, you can use TypoScript for setting this up.

by Peter Klein

Example Setup:

```
lib.userinfo = COA_INT
lib.userinfo {
  10 = TEXT
  10.data = TSFE:fe_user|user|username
  10.wrap = Username: |<br />
  10.required = 1

  # Use "first_name" and "last_name", if present,
  # otherwise use the "name" field
  20 = COA
  20.1 = TEXT
  20.1.data = TSFE:fe_user|user|first_name
  20.1.required = 1
  20.2 = TEXT
  20.2.data = TSFE:fe_user|user|last_name
  20.2.wrap =  |
  20.2.required = 1
  20.stdWrap.ifEmpty.data = TSFE:fe_user|user|name
  20.stdWrap.wrap = Name: |<br />
  20.stdWrap.required = 1

  30 <.10
  30.data = TSFE:fe_user|user|address
  30.wrap = Address: |<br />

  40 <.10
  40.data = TSFE:fe_user|user|city
  40.wrap = City: |<br />

  50 <.10
  50.data = TSFE:fe_user|user|zip
  50.wrap = Zip: |<br />

  60 <.10
  60.data = TSFE:fe_user|user|country
  60.wrap = Country: |<br />

  70 <.10
  70.data = TSFE:fe_user|user|company
  70.wrap = Company: |<br />

  80 <.10
  80.data = TSFE:fe_user|user|telephone
  80.wrap = Telephone: |<br />
```

```
  90 <.10
  90.data = TSFE:fe_user|user|fax
  90.wrap = Fax: |<br />

  100 <.10
  100.data = TSFE:fe_user|user|email
  100.typolink.parameter.data = TSFE:fe_user|user|email
  100.wrap = Email: |<br />

  110 <.10
  110.data = TSFE:fe_user|user|www
  110.typolink.parameter.data = TSFE:fe_user|user|www
  110.typolink.extTarget = _blank
  110.wrap = WWW: |<br />

  200 < .10
  200.data = TSFE:fe_user|user|usergroup
  200.split {
    token = ,
    cObjNum = 1 || 2
    1 {
     10 = CONTENT
     10.table = fe_groups
      # ID 13 is the folder where I store my FE users and FE groups.
      # Remember to change it to the ID of the folder
      # where YOU store your FE data!!
     10.select.pidInList = 13
     10.select.andWhere.current = 1
     10.select.andWhere.wrap = uid=|
     10.renderObj = TEXT
     10.renderObj.field = title
     10.renderObj.wrap = |,
    }
    2 < .1
    2.10.renderObj.wrap >
  }
  200.wrap = Member of group(s): |<br />

  300 < .10
  300.data = TSFE:fe_user|user|image
  300.split {
    token = ,
    cObjNum = 1
    1 {
     10 = IMAGE
     10.file.import.current = 1
     10.file.import = uploads/tx_srfeuserregister/
     10.file.width = 100
    }
  }
  300.wrap = Image(s): |<br />

}
page.100 < lib.userinfo
```

Using Captcha

It is possible to activate the display of a captcha image and a text field where the user must enter the text displayed on the image.

Extension sr_freecap must have been installed. The captcha_response field should not be specified as a required field.

Set in TS Constants:

```
formFields := addToList(captcha_response)

or, using the TS Constant Editor, add captcha_response to the list of fields
```

and in TS Setup:

```
plugin.tx_srfeuserregister_pi1 {
  create.evalValues.captcha_response = freecap
}
```

Make the user name changeable

Use the following setup.

Example:

```
plugin.tx_srfeuserregister_pi1 {
      edit {
            overrideValues {
                  username >
            }
      }
}
```

Tutorial: Adding fields to the registration form

Extend the fe_users table

The simplest way to extend the fe_users table is to create a small extension that will define the required fields in the database and the TCA. Your small extension will not contain any plugin or other processing.

Once your extension is created, install it. This will make the fields you have defined available to the TYPO3 backend. In this tutorial the name of the extension is *mynewext.*

Add the fields in the HTML template

You need to update the HTML template in order to include the fields you have defined in the proper subparts. The subparts of interest are:

###TEMPLATE_CREATE###

###TEMPLATE_CREATE_PREVIEW###

###TEMPLATE_INVITE###

###TEMPLATE_INVITE_PREVIEW###

###TEMPLATE_EDIT###

###TEMPLATE_EDIT_PREVIEW###

and perhaps some of the email subparts.

Have a look at how the predefined fields are included in each of the subparts, and do the same for the fields you are adding.

The HTML for a field named myNewFieldName in the CREATE, INVITE and EDIT subparts would look like:

```
<!-- ###SUB_INCLUDED_FIELD_myNewFieldName### -->
<dt>
      <label for="tx-srfeuserregister-pi1-myNewFieldName">###LABEL_MYNEWFIELDNAME###</label>
      <span class="tx-srfeuserregister-pi1-required">###REQUIRED_MYNEWFIELDNAME###</span>
</dt>
<dd>
      <!-- ###SUB_ERROR_FIELD_myNewFieldName### -->
      <p class="tx-srfeuserregister-pi1-error">###EVAL_ERROR_FIELD_myNewFieldName###</p>
      <!-- ###SUB_ERROR_FIELD_myNewFieldName### -->
      <!-- ###SUB_REQUIRED_FIELD_myNewFieldName### -->
      <p class="tx-srfeuserregister-pi1-error">###MISSING_MYNEWFIELDNAME###</p>
      <!-- ###SUB_REQUIRED_FIELD_myNewFieldName### -->
      <input id="tx-srfeuserregister-pi1-myNewFieldName" type="text" size="40" maxlength="50"
title="###TOOLTIP_MYNEWFIELDNAME###" name="###NAME_MYNEWFIELDNAME###" class="tx-srfeuserregister-pi1-
text" />
</dd>
<!-- ###SUB_INCLUDED_FIELD_myNewFieldName### -->
```

In the case of a field of type textarea, check, radio and select, the HTML for the field should rather look like the following:

```
<!-- ###SUB_INCLUDED_FIELD_myNewFieldName### -->
<dt>
      <label for="tx-srfeuserregister-pi1-myNewFieldName">###LABEL_MYNEWFIELDNAME###</label>
      <span class="tx-srfeuserregister-pi1-required">###REQUIRED_MYNEWFIELDNAME###</span>
</dt>
<dd>
      <!-- ###SUB_ERROR_FIELD_myNewFieldName### -->
      <p class="tx-srfeuserregister-pi1-error">###EVAL_ERROR_FIELD_myNewFieldName###</p>
      <!-- ###SUB_ERROR_FIELD_myNewFieldName### -->
      <!-- ###SUB_REQUIRED_FIELD_myNewFieldName### -->
      <p class="tx-srfeuserregister-pi1-error">###MISSING_MYNEWFIELDNAME###</p>
      <!-- ###SUB_REQUIRED_FIELD_myNewFieldName### -->
      ###TCA_INPUT_myNewFieldName###
</dd>
<!-- ###SUB_INCLUDED_FIELD_myNewFieldName### →
```

In each PREVIEW subpart, you need to add lines like:

```
<!-- ###SUB_INCLUDED_FIELD_myNewFieldName### -->
<dt>###LABEL_MYNEWFIELDNAME###</dt>
<dd>###FIELD_MYNEWFIELDNAME###</dd>
<!-- ###SUB_INCLUDED_FIELD_myNewFieldName### -->
```

or

```
<!-- ###SUB_INCLUDED_FIELD_myNewFieldName### -->
```

```
<dt>###LABEL_MYNEWFIELDNAME###</dt>
<dd>###TCA_INPUT_myNewFieldName###</dd>
<!-- ###SUB_INCLUDED_FIELD_myNewFieldName### -->
```

Modify the TS template Constants and Setup

Using the Constant Editor, modify the value of the following constants of plugin tx_srfeuserregister_pi1:

- **formFields**: add to the list of fields the names of the fields you have defined and want to be displayed in the front end form. If the field is not in this list, the subpart

  <!--###SUB_INCLUDED_FIELD_*myNewFieldName*###--> will be deleted;

- **requiredFields**: add to the list of fields the names of the fields you have defined and want to be treated as required fields. If the field is not in the list OR if the field is in this list and is correctly filled, the subpart

  <!--###SUB_REQUIRED_FIELD_*myNewFieldName*###--> will be deleted.

You may also specify in the TS template Setup some default values and validation rules to be applied by the extension to the additional fields.

If there are no validation rules, you should set:

```
plugin.tx_srfeuserregister_pi1.create.evalValues.myNewFieldName =
```

If your field is a select field and if you wish to enable multiple selection, you should also set:

```
plugin.tx_srfeuserregister_pi1.parseValues.myNewFieldName  = multiple
```

Add the language labels for the new fields

The language labels for the additional database fields should be added in Step1 above. These will be used by the Backend forms.

The language labels used by the front end plugin should be added in the TS template setup using the method described in the Localization section of this document. For each language of interest to you with *languageCode* , which must be replaced by 'de', 'default' or others. All cursive letters in the following examples must be replaced with your field names and texts.

You may need the following statements for each additional field with *myNewFieldName*:

The basic field label:

```
plugin.tx_srfeuserregister._LOCAL_LANG.languageCode.myNewFieldName = myNewFieldLabel
```

The message displayed when the field is required but missing:

```
plugin.tx_srfeuserregister._LOCAL_LANG.languageCode.missing_myNewFieldName = missingRequiredFieldMessage
```

Same as previous but for the invitation form:

```
plugin.tx_srfeuserregister._LOCAL_LANG.languageCode.missing_invitation_myNewFieldName =
missingRequiredFieldMessageOnInvitationForm
```

The following message displayed when a validation rule *evalRuleName* applicable to the field is not satisfied:

```
plugin.tx_srfeuserregister._LOCAL_LANG.languageCode.evalErrors_evalRuleName_myNewFieldName =
errorMessageForEvalRule
```

Troubleshooting

Please see/report problems on Codeberg: https://codeberg.org/sjbr/sr-feuser-register/issues

1. The confirmation link does not work. It shows just the site url *www.mydomain* without any parameters needed to confirm the registration on the confirmation page.

   Solution:
   You have set access restrictions on the page for the confirmation (confirmPID). The link to this page could not be generated for the email, because the user has no rights to see it. So remove the page restrictions (Edit page properties – Access).

2. An error message is shown:
   Internal error in the FE user registration. No text replacement has been found for
   missing_tx_myextension_my_tablefield

   Solution:
   You have to add the marker replacements for the user-defined fields into the setup. Follow the steps in chapter "Add the language labels for the new fields"

3. Form's token is empty (randomly)

   Solution: Use the TYPO3 CMS install tool to set

   ```
   $GLOBALS['TYPO3_CONF_VARS']['FE']['cookieDomain'] = my.domain.com
   ```