

REINFORCE algorithms, was introduced back in 1992¹¹ by Ronald Williams. Here is one common variant:

1. First, let the neural network policy play the game several times, and at each step, compute the gradients that would make the chosen action even more likely—but don’t apply these gradients yet.
2. Once you have run several episodes, compute each action’s advantage (using the method described in the previous section).
3. If an action’s advantage is positive, it means that the action was probably good, and you want to apply the gradients computed earlier to make the action even more likely to be chosen in the future. However, if the action’s advantage is negative, it means the action was probably bad, and you want to apply the opposite gradients to make this action slightly *less* likely in the future. The solution is simply to multiply each gradient vector by the corresponding action’s advantage.
4. Finally, compute the mean of all the resulting gradient vectors, and use it to perform a Gradient Descent step.

Let’s use `tf.keras` to implement this algorithm. We will train the neural network policy we built earlier so that it learns to balance the pole on the cart. First, we need a function that will play one step. We will pretend for now that whatever action it takes is the right one so that we can compute the loss and its gradients (these gradients will just be saved for a while, and we will modify them later depending on how good or bad the action turned out to be):

```
def play_one_step(env, obs, model, loss_fn):
    with tf.GradientTape() as tape:
        left_proba = model(obs[np.newaxis])
        action = (tf.random.uniform([1, 1]) > left_proba)
        y_target = tf.constant([[1.]]) - tf.cast(action, tf.float32)
        loss = tf.reduce_mean(loss_fn(y_target, left_proba))
        grads = tape.gradient(loss, model.trainable_variables)
        obs, reward, done, info = env.step(int(action[0, 0].numpy()))
    return obs, reward, done, grads
```

Let’s walk through this function:

- Within the `GradientTape` block (see [Chapter 12](#)), we start by calling the model, giving it a single observation (we reshape the observation so it becomes a batch containing a single instance, as the model expects a batch). This outputs the probability of going left.

¹¹ Ronald J. Williams, “Simple Statistical Gradient-Following Algorithms for Connectionist Reinforcement Learning,” *Machine Learning* 8 (1992) : 229–256.

- Next, we sample a random float between 0 and 1, and we check whether it is greater than `left_proba`. The action will be `False` with probability `left_proba`, or `True` with probability `1 - left_proba`. Once we cast this Boolean to a number, the action will be 0 (left) or 1 (right) with the appropriate probabilities.
- Next, we define the target probability of going left: it is 1 minus the action (cast to a float). If the action is 0 (left), then the target probability of going left will be 1. If the action is 1 (right), then the target probability will be 0.
- Then we compute the loss using the given loss function, and we use the tape to compute the gradient of the loss with regard to the model's trainable variables. Again, these gradients will be tweaked later, before we apply them, depending on how good or bad the action turned out to be.
- Finally, we play the selected action, and we return the new observation, the reward, whether the episode is ended or not, and of course the gradients that we just computed.

Now let's create another function that will rely on the `play_one_step()` function to play multiple episodes, returning all the rewards and gradients for each episode and each step:

```
def play_multiple_episodes(env, n_episodes, n_max_steps, model, loss_fn):
    all_rewards = []
    all_grads = []
    for episode in range(n_episodes):
        current_rewards = []
        current_grads = []
        obs = env.reset()
        for step in range(n_max_steps):
            obs, reward, done, grads = play_one_step(env, obs, model, loss_fn)
            current_rewards.append(reward)
            current_grads.append(grads)
            if done:
                break
        all_rewards.append(current_rewards)
        all_grads.append(current_grads)
    return all_rewards, all_grads
```

This code returns a list of reward lists (one reward list per episode, containing one reward per step), as well as a list of gradient lists (one gradient list per episode, each containing one tuple of gradients per step and each tuple containing one gradient tensor per trainable variable).

The algorithm will use the `play_multiple_episodes()` function to play the game several times (e.g., 10 times), then it will go back and look at all the rewards, discount them, and normalize them. To do that, we need a couple more functions: the first will compute the sum of future discounted rewards at each step, and the second will

normalize all these discounted rewards (returns) across many episodes by subtracting the mean and dividing by the standard deviation:

```
def discount_rewards(rewards, discount_factor):
    discounted = np.array(rewards)
    for step in range(len(rewards) - 2, -1, -1):
        discounted[step] += discounted[step + 1] * discount_factor
    return discounted

def discount_and_normalize_rewards(all_rewards, discount_factor):
    all_discounted_rewards = [discount_rewards(rewards, discount_factor)
                               for rewards in all_rewards]
    flat_rewards = np.concatenate(all_discounted_rewards)
    reward_mean = flat_rewards.mean()
    reward_std = flat_rewards.std()
    return [(discounted_rewards - reward_mean) / reward_std
            for discounted_rewards in all_discounted_rewards]
```

Let's check that this works:

```
>>> discount_rewards([10, 0, -50], discount_factor=0.8)
array([-22, -40, -50])
>>> discount_and_normalize_rewards([[10, 0, -50], [10, 20]],
...                               discount_factor=0.8)
...
...
array([-0.28435071, -0.86597718, -1.18910299]),
array([1.26665318, 1.0727777 ])]
```

The call to `discount_rewards()` returns exactly what we expect (see [Figure 18-6](#)). You can verify that the function `discount_and_normalize_rewards()` does indeed return the normalized action advantages for each action in both episodes. Notice that the first episode was much worse than the second, so its normalized advantages are all negative; all actions from the first episode would be considered bad, and conversely all actions from the second episode would be considered good.

We are almost ready to run the algorithm! Now let's define the hyperparameters. We will run 150 training iterations, playing 10 episodes per iteration, and each episode will last at most 200 steps. We will use a discount factor of 0.95:

```
n_iterations = 150
n_episodes_per_update = 10
n_max_steps = 200
discount_factor = 0.95
```

We also need an optimizer and the loss function. A regular Adam optimizer with learning rate 0.01 will do just fine, and we will use the binary cross-entropy loss function because we are training a binary classifier (there are two possible actions: left or right):

```
optimizer = keras.optimizers.Adam(lr=0.01)
loss_fn = keras.losses.binary_crossentropy
```

We are now ready to build and run the training loop!

```
for iteration in range(n_iterations):
    all_rewards, all_grads = play_multiple_episodes(
        env, n_episodes_per_update, n_max_steps, model, loss_fn)
    all_final_rewards = discount_and_normalize_rewards(all_rewards,
                                                       discount_factor)

    all_mean_grads = []
    for var_index in range(len(model.trainable_variables)):
        mean_grads = tf.reduce_mean(
            [final_reward * all_grads[episode_index][step][var_index]
             for episode_index, final_rewards in enumerate(all_final_rewards)
             for step, final_reward in enumerate(final_rewards)], axis=0)
        all_mean_grads.append(mean_grads)
    optimizer.apply_gradients(zip(all_mean_grads, model.trainable_variables))
```

Let's walk through this code:

- At each training iteration, this loop calls the `play_multiple_episodes()` function, which plays the game 10 times and returns all the rewards and gradients for every episode and step.
- Then we call the `discount_and_normalize_rewards()` to compute each action's normalized advantage (which in the code we call the `final_reward`). This provides a measure of how good or bad each action actually was, in hindsight.
- Next, we go through each trainable variable, and for each of them we compute the weighted mean of the gradients for that variable over all episodes and all steps, weighted by the `final_reward`.
- Finally, we apply these mean gradients using the optimizer: the model's trainable variables will be tweaked, and hopefully the policy will be a bit better.

And we're done! This code will train the neural network policy, and it will successfully learn to balance the pole on the cart (you can try it out in the "Policy Gradients" section of the Jupyter notebook). The mean reward per episode will get very close to 200 (which is the maximum by default with this environment). Success!



Researchers try to find algorithms that work well even when the agent initially knows nothing about the environment. However, unless you are writing a paper, you should not hesitate to inject prior knowledge into the agent, as it will speed up training dramatically. For example, since you know that the pole should be as vertical as possible, you could add negative rewards proportional to the pole's angle. This will make the rewards much less sparse and speed up training. Also, if you already have a reasonably good policy (e.g., hardcoded), you may want to train the neural network to imitate it before using policy gradients to improve it.

The simple policy gradients algorithm we just trained solved the CartPole task, but it would not scale well to larger and more complex tasks. Indeed, it is highly *sample inefficient*, meaning it needs to explore the game for a very long time before it can make significant progress. This is due to the fact that it must run multiple episodes to estimate the advantage of each action, as we have seen. However, it is the foundation of more powerful algorithms, such as *Actor-Critic* algorithms (which we will discuss briefly at the end of this chapter).

We will now look at another popular family of algorithms. Whereas PG algorithms directly try to optimize the policy to increase rewards, the algorithms we will look at now are less direct: the agent learns to estimate the expected return for each state, or for each action in each state, then it uses this knowledge to decide how to act. To understand these algorithms, we must first introduce *Markov decision processes*.

Markov Decision Processes

In the early 20th century, the mathematician Andrey Markov studied stochastic processes with no memory, called *Markov chains*. Such a process has a fixed number of states, and it randomly evolves from one state to another at each step. The probability for it to evolve from a state s to a state s' is fixed, and it depends only on the pair (s, s') , not on past states (this is why we say that the system has no memory).

Figure 18-7 shows an example of a Markov chain with four states.




Figure 18-7. Example of a Markov chain

Suppose that the process starts in state s_0 , and there is a 70% chance that it will remain in that state at the next step. Eventually it is bound to leave that state and never come back because no other state points back to s_0 . If it goes to state s_1 , it will then most likely go to state s_2 (90% probability), then immediately back to state s_1

(with 100% probability). It may alternate a number of times between these two states, but eventually it will fall into state s_3 and remain there forever (this is a *terminal state*). Markov chains can have very different dynamics, and they are heavily used in thermodynamics, chemistry, statistics, and much more.

Markov decision processes were first described in the 1950s by Richard Bellman.¹² They resemble Markov chains but with a twist: at each step, an agent can choose one of several possible actions, and the transition probabilities depend on the chosen action. Moreover, some state transitions return some reward (positive or negative), and the agent's goal is to find a policy that will maximize reward over time.

For example, the MDP represented in Figure 18-8 has three states (represented by circles) and up to three possible discrete actions at each step (represented by diamonds).




Figure 18-8. Example of a Markov decision process

If it starts in state s_0 , the agent can choose between actions a_0 , a_1 , or a_2 . If it chooses action a_1 , it just remains in state s_0 with certainty, and without any reward. It can thus decide to stay there forever if it wants to. But if it chooses action a_0 , it has a 70% probability of gaining a reward of +10 and remaining in state s_0 . It can then try again and again to gain as much reward as possible, but at one point it is going to end up instead in state s_1 . In state s_1 it has only two possible actions: a_0 or a_2 . It can choose to stay put by repeatedly choosing action a_0 , or it can choose to move on to state s_2 and get a negative reward of -50 (ouch). In state s_2 it has no other choice than to take action a_1 , which will most likely lead it back to state s_0 , gaining a reward of +40 on the

¹² Richard Bellman, "A Markovian Decision Process," *Journal of Mathematics and Mechanics* 6, no. 5 (1957): 679–684.

way. You get the picture. By looking at this MDP, can you guess which strategy will gain the most reward over time? In state s_0 it is clear that action a_0 is the best option, and in state s_2 the agent has no choice but to take action a_1 , but in state s_1 it is not obvious whether the agent should stay put (a_0) or go through the fire (a_2).

Bellman found a way to estimate the *optimal state value* of any state s , noted $V^*(s)$, which is the sum of all discounted future rewards the agent can expect on average after it reaches a state s , assuming it acts optimally. He showed that if the agent acts optimally, then the *Bellman Optimality Equation* applies (see [Equation 18-1](#)). This recursive equation says that if the agent acts optimally, then the optimal value of the current state is equal to the reward it will get on average after taking one optimal action, plus the expected optimal value of all possible next states that this action can lead to.

Equation 18-1. Bellman Optimality Equation

$$V^*(s) = \max_a \sum_{s'} T(s, a, s') [R(s, a, s') + \gamma \cdot V^*(s')] \quad \text{for all } s$$

In this equation:

- $T(s, a, s')$ is the transition probability from state s to state s' , given that the agent chose action a . For example, in [Figure 18-8](#), $T(s_2, a_1, s_0) = 0.8$.
- $R(s, a, s')$ is the reward that the agent gets when it goes from state s to state s' , given that the agent chose action a . For example, in [Figure 18-8](#), $R(s_2, a_1, s_0) = +40$.
- γ is the discount factor.

This equation leads directly to an algorithm that can precisely estimate the optimal state value of every possible state: you first initialize all the state value estimates to zero, and then you iteratively update them using the *Value Iteration* algorithm (see [Equation 18-2](#)). A remarkable result is that, given enough time, these estimates are guaranteed to converge to the optimal state values, corresponding to the optimal policy.

Equation 18-2. Value Iteration algorithm

$$V_{k+1}(s) \leftarrow \max_a \sum_{s'} T(s, a, s') [R(s, a, s') + \gamma \cdot V_k(s')] \quad \text{for all } s$$

In this equation, $V_k(s)$ is the estimated value of state s at the k^{th} iteration of the algorithm.



This algorithm is an example of *Dynamic Programming*, which breaks down a complex problem into tractable subproblems that can be tackled iteratively.

Knowing the optimal state values can be useful, in particular to evaluate a policy, but it does not give us the optimal policy for the agent. Luckily, Bellman found a very similar algorithm to estimate the optimal *state-action values*, generally called *Q-Values* (Quality Values). The optimal Q-Value of the state-action pair (s, a) , noted $Q^*(s, a)$, is the sum of discounted future rewards the agent can expect on average after it reaches the state s and chooses action a , but before it sees the outcome of this action, assuming it acts optimally after that action.

Here is how it works: once again, you start by initializing all the Q-Value estimates to zero, then you update them using the *Q-Value Iteration* algorithm (see [Equation 18-3](#)).

Equation 18-3. Q-Value Iteration algorithm

$$Q_{k+1}(s, a) \leftarrow \sum_{s'} T(s, a, s') \left[R(s, a, s') + \gamma \cdot \max_{a'} Q_k(s', a') \right] \quad \text{for all } (s', a')$$

Once you have the optimal Q-Values, defining the optimal policy, noted $\pi^*(s)$, is trivial: when the agent is in state s , it should choose the action with the highest Q-Value for that state: $\pi^*(s) = \underset{a}{\operatorname{argmax}} Q^*(s, a)$.

Let's apply this algorithm to the MDP represented in [Figure 18-8](#). First, we need to define the MDP:

```
transition_probabilities = [ # shape=[s, a, s']
    [[0.7, 0.3, 0.0], [1.0, 0.0, 0.0], [0.8, 0.2, 0.0]],
    [[0.0, 1.0, 0.0], None, [0.0, 0.0, 1.0]],
    [None, [0.8, 0.1, 0.1], None]]
rewards = [ # shape=[s, a, s']
    [[+10, 0, 0], [0, 0, 0], [0, 0, 0]],
    [[0, 0, 0], [0, 0, 0], [0, 0, -50]],
    [[0, 0, 0], [+40, 0, 0], [0, 0, 0]]]
possible_actions = [[0, 1, 2], [0, 2], [1]]
```

For example, to know the transition probability from s_2 to s_0 after playing action a_1 , we will look up `transition_probabilities[2][1][0]` (which is 0.8). Similarly, to get the corresponding reward, we will look up `rewards[2][1][0]` (which is +40). And to get the list of possible actions in s_2 , we will look up `possible_actions[2]` (in this case, only action a_1 is possible). Next, we must initialize all the Q-Values to 0 (except for the impossible actions, for which we set the Q-Values to $-\infty$):


```

Q_values = np.full((3, 3), -np.inf) # -np.inf for impossible actions
for state, actions in enumerate(possible_actions):
    Q_values[state, actions] = 0.0 # for all possible actions

```

Now let's run the Q-Value Iteration algorithm. It applies Equation 18-3 repeatedly, to all Q-Values, for every state and every possible action:

```

gamma = 0.90 # the discount factor

for iteration in range(50):
    Q_prev = Q_values.copy()
    for s in range(3):
        for a in possible_actions[s]:
            Q_values[s, a] = np.sum([
                transition_probabilities[s][a][sp]
                * (rewards[s][a][sp] + gamma * np.max(Q_prev[sp]))
            ])
        for sp in range(3)]])

```

That's it! The resulting Q-Values look like this:

```

>>> Q_values
array([[18.91891892, 17.02702702, 13.62162162],
       [ 0.          , -inf, -4.87971488],
       [-inf, 50.13365013, -inf]])

```

For example, when the agent is in state s_0 and it chooses action a_1 , the expected sum of discounted future rewards is approximately 17.0.

For each state, let's look at the action that has the highest Q-Value:

```

>>> np.argmax(Q_values, axis=1) # optimal action for each state
array([0, 0, 1])

```

This gives us the optimal policy for this MDP, when using a discount factor of 0.90: in state s_0 choose action a_0 ; in state s_1 choose action a_0 (i.e., stay put); and in state s_2 choose action a_1 (the only possible action). Interestingly, if we increase the discount factor to 0.95, the optimal policy changes: in state s_1 the best action becomes a_2 (go through the fire!). This makes sense because the more you value future rewards, the more you are willing to put up with some pain now for the promise of future bliss.

Temporal Difference Learning

Reinforcement Learning problems with discrete actions can often be modeled as Markov decision processes, but the agent initially has no idea what the transition probabilities are (it does not know $T(s, a, s')$), and it does not know what the rewards are going to be either (it does not know $R(s, a, s')$). It must experience each state and each transition at least once to know the rewards, and it must experience them multiple times if it is to have a reasonable estimate of the transition probabilities.

The *Temporal Difference Learning* (TD Learning) algorithm is very similar to the Value Iteration algorithm, but tweaked to take into account the fact that the agent has

only partial knowledge of the MDP. In general we assume that the agent initially knows only the possible states and actions, and nothing more. The agent uses an *exploration policy*—for example, a purely random policy—to explore the MDP, and as it progresses, the TD Learning algorithm updates the estimates of the state values based on the transitions and rewards that are actually observed (see [Equation 18-4](#)).

Equation 18-4. TD Learning algorithm

$$V_{k+1}(s) \leftarrow (1 - \alpha)V_k(s) + \alpha(r + \gamma \cdot V_k(s'))$$

or, equivalently:

$$V_{k+1}(s) \leftarrow V_k(s) + \alpha \cdot \delta_k(s, r, s')$$

$$\text{with } \delta_k(s, r, s') = r + \gamma \cdot V_k(s') - V_k(s)$$

In this equation:

- α is the learning rate (e.g., 0.01).
- $r + \gamma \cdot V_k(s')$ is called the *TD target*.
- $\delta_k(s, r, s')$ is called the *TD error*.

A more concise way of writing the first form of this equation is to use the notation $a \xleftarrow{\alpha} b$, which means $a_{k+1} \leftarrow (1 - \alpha) \cdot a_k + \alpha \cdot b_k$. So, the first line of [Equation 18-4](#) can be rewritten like this: $V(s) \xleftarrow{\alpha} r + \gamma \cdot V(s')$.



TD Learning has many similarities with Stochastic Gradient Descent, in particular the fact that it handles one sample at a time. Moreover, just like Stochastic GD, it can only truly converge if you gradually reduce the learning rate (otherwise it will keep bouncing around the optimum Q-Values).

For each state s , this algorithm simply keeps track of a running average of the immediate rewards the agent gets upon leaving that state, plus the rewards it expects to get later (assuming it acts optimally).

Q-Learning

Similarly, the Q-Learning algorithm is an adaptation of the Q-Value Iteration algorithm to the situation where the transition probabilities and the rewards are initially unknown (see [Equation 18-5](#)). Q-Learning works by watching an agent play (e.g., randomly) and gradually improving its estimates of the Q-Values. Once it has

accurate Q-Value estimates (or close enough), then the optimal policy is choosing the action that has the highest Q-Value (i.e., the greedy policy).

Equation 18-5. Q-Learning algorithm

$$Q(s, a) \leftarrow_{\alpha} r + \gamma \cdot \max_{a'} Q(s', a')$$

For each state-action pair (s, a) , this algorithm keeps track of a running average of the rewards r the agent gets upon leaving the state s with action a , plus the sum of discounted future rewards it expects to get. To estimate this sum, we take the maximum of the Q-Value estimates for the next state s' , since we assume that the target policy would act optimally from then on.

Let's implement the Q-Learning algorithm. First, we will need to make an agent explore the environment. For this, we need a step function so that the agent can execute one action and get the resulting state and reward:

```
def step(state, action):
    probas = transition_probabilities[state][action]
    next_state = np.random.choice([0, 1, 2], p=probas)
    reward = rewards[state][action][next_state]
    return next_state, reward
```

Now let's implement the agent's exploration policy. Since the state space is pretty small, a simple random policy will be sufficient. If we run the algorithm for long enough, the agent will visit every state many times, and it will also try every possible action many times:

```
def exploration_policy(state):
    return np.random.choice(possible_actions[state])
```

Next, after we initialize the Q-Values just like earlier, we are ready to run the Q-Learning algorithm with learning rate decay (using power scheduling, introduced in [Chapter 11](#)):

```
alpha0 = 0.05 # initial learning rate
decay = 0.005 # learning rate decay
gamma = 0.90 # discount factor
state = 0 # initial state

for iteration in range(10000):
    action = exploration_policy(state)
    next_state, reward = step(state, action)
    next_value = np.max(Q_values[next_state])
    alpha = alpha0 / (1 + iteration * decay)
    Q_values[state, action] *= 1 - alpha
    Q_values[state, action] += alpha * (reward + gamma * next_value)
    state = next_state
```

This algorithm will converge to the optimal Q-Values, but it will take many iterations, and possibly quite a lot of hyperparameter tuning. As you can see in [Figure 18-9](#), the Q-Value Iteration algorithm (left) converges very quickly, in fewer than 20 iterations, while the Q-Learning algorithm (right) takes about 8,000 iterations to converge. Obviously, not knowing the transition probabilities or the rewards makes finding the optimal policy significantly harder!




Figure 18-9. The Q-Value Iteration algorithm (left) versus the Q-Learning algorithm (right)

The Q-Learning algorithm is called an *off-policy* algorithm because the policy being trained is not necessarily the one being executed: in the previous code example, the policy being executed (the exploration policy) is completely random, while the policy being trained will always choose the actions with the highest Q-Values. Conversely, the Policy Gradients algorithm is an *on-policy* algorithm: it explores the world using the policy being trained. It is somewhat surprising that Q-Learning is capable of learning the optimal policy by just watching an agent act randomly (imagine learning to play golf when your teacher is a drunk monkey). Can we do better?

Exploration Policies

Of course, Q-Learning can work only if the exploration policy explores the MDP thoroughly enough. Although a purely random policy is guaranteed to eventually visit every state and every transition many times, it may take an extremely long time to do so. Therefore, a better option is to use the *ϵ -greedy policy* (ϵ is epsilon): at each step it acts randomly with probability ϵ , or greedily with probability $1-\epsilon$ (i.e., choosing the action with the highest Q-Value). The advantage of the ϵ -greedy policy (compared to a completely random policy) is that it will spend more and more time exploring the interesting parts of the environment, as the Q-Value estimates get better and better, while still spending some time visiting unknown regions of the MDP. It is quite common to start with a high value for ϵ (e.g., 1.0) and then gradually reduce it (e.g., down to 0.05).

Alternatively, rather than relying only on chance for exploration, another approach is to encourage the exploration policy to try actions that it has not tried much before. This can be implemented as a bonus added to the Q-Value estimates, as shown in Equation 18-6.

Equation 18-6. Q-Learning using an exploration function

$$Q(s, a) \leftarrow r + \gamma \cdot \max_{a'} f(Q(s', a'), N(s', a'))$$

In this equation:

- $N(s', a')$ counts the number of times the action a' was chosen in state s' .
- $f(Q, N)$ is an *exploration function*, such as $f(Q, N) = Q + \kappa/(1 + N)$, where κ is a curiosity hyperparameter that measures how much the agent is attracted to the unknown.

Approximate Q-Learning and Deep Q-Learning

The main problem with Q-Learning is that it does not scale well to large (or even medium) MDPs with many states and actions. For example, suppose you wanted to use Q-Learning to train an agent to play *Ms. Pac-Man* (see Figure 18-1). There are about 150 pellets that *Ms. Pac-Man* can eat, each of which can be present or absent (i.e., already eaten). So, the number of possible states is greater than $2^{150} \approx 10^{45}$. And if you add all the possible combinations of positions for all the ghosts and *Ms. Pac-Man*, the number of possible states becomes larger than the number of atoms in our planet, so there's absolutely no way you can keep track of an estimate for every single Q-Value.

The solution is to find a function $Q_\theta(s, a)$ that approximates the Q-Value of any state-action pair (s, a) using a manageable number of parameters (given by the parameter vector θ). This is called *Approximate Q-Learning*. For years it was recommended to use linear combinations of handcrafted features extracted from the state (e.g., distance of the closest ghosts, their directions, and so on) to estimate Q-Values, but in 2013, **DeepMind** showed that using deep neural networks can work much better, especially for complex problems, and it does not require any feature engineering. A DNN used to estimate Q-Values is called a *Deep Q-Network* (DQN), and using a DQN for Approximate Q-Learning is called *Deep Q-Learning*.

Now, how can we train a DQN? Well, consider the approximate Q-Value computed by the DQN for a given state-action pair (s, a) . Thanks to Bellman, we know we want this approximate Q-Value to be as close as possible to the reward r that we actually observe after playing action a in state s , plus the discounted value of playing optimally

from then on. To estimate this sum of future discounted rewards, we can simply execute the DQN on the next state s' and for all possible actions a' . We get an approximate future Q-Value for each possible action. We then pick the highest (since we assume we will be playing optimally) and discount it, and this gives us an estimate of the sum of future discounted rewards. By summing the reward r and the future discounted value estimate, we get a target Q-Value $y(s, a)$ for the state-action pair (s, a) , as shown in [Equation 18-7](#).

Equation 18-7. Target Q-Value

$$Q_{\text{target}}(s, a) = r + \gamma \cdot \max_{a'} Q_{\theta}(s', a')$$

With this target Q-Value, we can run a training step using any Gradient Descent algorithm. Specifically, we generally try to minimize the squared error between the estimated Q-Value $Q(s, a)$ and the target Q-Value (or the Huber loss to reduce the algorithm's sensitivity to large errors). And that's all for the basic Deep Q-Learning algorithm! Let's see how to implement it to solve the CartPole environment.

Implementing Deep Q-Learning

The first thing we need is a Deep Q-Network. In theory, you need a neural net that takes a state-action pair and outputs an approximate Q-Value, but in practice it's much more efficient to use a neural net that takes a state and outputs one approximate Q-Value for each possible action. To solve the CartPole environment, we do not need a very complicated neural net; a couple of hidden layers will do:

```
env = gym.make("CartPole-v0")
input_shape = [4] # == env.observation_space.shape
n_outputs = 2 # == env.action_space.n

model = keras.models.Sequential([
    keras.layers.Dense(32, activation="elu", input_shape=input_shape),
    keras.layers.Dense(32, activation="elu"),
    keras.layers.Dense(n_outputs)
])
```

To select an action using this DQN, we pick the action with the largest predicted Q-Value. To ensure that the agent explores the environment, we will use an ϵ -greedy policy (i.e., we will choose a random action with probability ϵ):

```
def epsilon_greedy_policy(state, epsilon=0):
    if np.random.rand() < epsilon:
        return np.random.randint(2)
    else:
        Q_values = model.predict(state[np.newaxis])
        return np.argmax(Q_values[0])
```

Instead of training the DQN based only on the latest experiences, we will store all experiences in a *replay buffer* (or *replay memory*), and we will sample a random training batch from it at each training iteration. This helps reduce the correlations between the experiences in a training batch, which tremendously helps training. For this, we will just use a deque list:

```
from collections import deque

replay_buffer = deque(maxlen=2000)
```



A *deque* is a linked list, where each element points to the next one and to the previous one. It makes inserting and deleting items very fast, but the longer the deque is, the slower random access will be. If you need a very large replay buffer, use a circular buffer; see the “Deque vs Rotating List” section of the notebook for an implementation.

Each experience will be composed of five elements: a state, the action the agent took, the resulting reward, the next state it reached, and finally a Boolean indicating whether the episode ended at that point (done). We will need a small function to sample a random batch of experiences from the replay buffer. It will return five NumPy arrays corresponding to the five experience elements:

```
def sample_experiences(batch_size):
    indices = np.random.randint(len(replay_buffer), size=batch_size)
    batch = [replay_buffer[index] for index in indices]
    states, actions, rewards, next_states, dones = [
        np.array([experience[field_index] for experience in batch])
        for field_index in range(5)]
    return states, actions, rewards, next_states, dones
```

Let’s also create a function that will play a single step using the ϵ -greedy policy, then store the resulting experience in the replay buffer:

```
def play_one_step(env, state, epsilon):
    action = epsilon_greedy_policy(state, epsilon)
    next_state, reward, done, info = env.step(action)
    replay_buffer.append((state, action, reward, next_state, done))
    return next_state, reward, done, info
```

Finally, let’s create one last function that will sample a batch of experiences from the replay buffer and train the DQN by performing a single Gradient Descent step on this batch:

```
batch_size = 32
discount_factor = 0.95
optimizer = keras.optimizers.Adam(lr=1e-3)
loss_fn = keras.losses.mean_squared_error
```

```

def training_step(batch_size):
    experiences = sample_experiences(batch_size)
    states, actions, rewards, next_states, dones = experiences
    next_Q_values = model.predict(next_states)
    max_next_Q_values = np.max(next_Q_values, axis=1)
    target_Q_values = (rewards +
                       (1 - dones) * discount_factor * max_next_Q_values)
    mask = tf.one_hot(actions, n_outputs)
    with tf.GradientTape() as tape:
        all_Q_values = model(states)
        Q_values = tf.reduce_sum(all_Q_values * mask, axis=1, keepdims=True)
        loss = tf.reduce_mean(loss_fn(target_Q_values, Q_values))
    grads = tape.gradient(loss, model.trainable_variables)
    optimizer.apply_gradients(zip(grads, model.trainable_variables))

```

Let's go through this code:

- First we define some hyperparameters, and we create the optimizer and the loss function.
- Then we create the `training_step()` function. It starts by sampling a batch of experiences, then it uses the DQN to predict the Q-Value for each possible action in each experience's next state. Since we assume that the agent will be playing optimally, we only keep the maximum Q-Value for each next state. Next, we use [Equation 18-7](#) to compute the target Q-Value for each experience's state-action pair.
- Next, we want to use the DQN to compute the Q-Value for each experienced state-action pair. However, the DQN will also output the Q-Values for the other possible actions, not just for the action that was actually chosen by the agent. So we need to mask out all the Q-Values we do not need. The `tf.one_hot()` function makes it easy to convert an array of action indices into such a mask. For example, if the first three experiences contain actions 1, 1, 0, respectively, then the mask will start with `[[0, 1], [0, 1], [1, 0], ...]`. We can then multiply the DQN's output with this mask, and this will zero out all the Q-Values we do not want. We then sum over axis 1 to get rid of all the zeros, keeping only the Q-Values of the experienced state-action pairs. This gives us the `Q_values` tensor, containing one predicted Q-Value for each experience in the batch.
- Then we compute the loss: it is the mean squared error between the target and predicted Q-Values for the experienced state-action pairs.
- Finally, we perform a Gradient Descent step to minimize the loss with regard to the model's trainable variables.

This was the hardest part. Now training the model is straightforward:


```

for episode in range(600):
    obs = env.reset()
    for step in range(200):
        epsilon = max(1 - episode / 500, 0.01)
        obs, reward, done, info = play_one_step(env, obs, epsilon)
        if done:
            break
    if episode > 50:
        training_step(batch_size)

```

We run 600 episodes, each for a maximum of 200 steps. At each step, we first compute the epsilon value for the ϵ -greedy policy: it will go from 1 down to 0.01, linearly, in a bit under 500 episodes. Then we call the `play_one_step()` function, which will use the ϵ -greedy policy to pick an action, then execute it and record the experience in the replay buffer. If the episode is done, we exit the loop. Finally, if we are past the 50th episode, we call the `training_step()` function to train the model on one batch sampled from the replay buffer. The reason we play 50 episodes without training is to give the replay buffer some time to fill up (if we don't wait enough, then there will not be enough diversity in the replay buffer). And that's it, we just implemented the Deep Q-Learning algorithm!

Figure 18-10 shows the total rewards the agent got during each episode.




Figure 18-10. Learning curve of the Deep Q-Learning algorithm

As you can see, the algorithm made no apparent progress at all for almost 300 episodes (in part because ϵ was very high at the beginning), then its performance suddenly skyrocketed up to 200 (which is the maximum possible performance in this environment). That's great news: the algorithm worked fine, and it actually ran much faster than the Policy Gradient algorithm! But wait... just a few episodes later, it forgot everything it knew, and its performance dropped below 25! This is called

catastrophic forgetting, and it is one of the big problems facing virtually all RL algorithms: as the agent explores the environment, it updates its policy, but what it learns in one part of the environment may break what it learned earlier in other parts of the environment. The experiences are quite correlated, and the learning environment keeps changing—this is not ideal for Gradient Descent! If you increase the size of the replay buffer, the algorithm will be less subject to this problem. Reducing the learning rate may also help. But the truth is, Reinforcement Learning is hard: training is often unstable, and you may need to try many hyperparameter values and random seeds before you find a combination that works well. For example, if you try changing the number of neurons per layer in the preceding from 32 to 30 or 34, the performance will never go above 100 (the DQN may be more stable with one hidden layer instead of two).



Reinforcement Learning is notoriously difficult, largely because of the training instabilities and the huge sensitivity to the choice of hyperparameter values and random seeds.¹³ As the researcher Andrej Karpathy put it: “[Supervised learning] wants to work. [...] RL must be forced to work.” You will need time, patience, perseverance, and perhaps a bit of luck too. This is a major reason RL is not as widely adopted as regular Deep Learning (e.g., convolutional nets). But there are a few real-world applications, beyond AlphaGo and Atari games: for example, Google uses RL to optimize its data-center costs, and it is used in some robotics applications, for hyperparameter tuning, and in recommender systems.

You might wonder why we didn’t plot the loss. It turns out that loss is a poor indicator of the model’s performance. The loss might go down, yet the agent might perform worse (e.g., this can happen when the agent gets stuck in one small region of the environment, and the DQN starts overfitting this region). Conversely, the loss could go up, yet the agent might perform better (e.g., if the DQN was underestimating the Q-Values, and it starts correctly increasing its predictions, the agent will likely perform better, getting more rewards, but the loss might increase because the DQN also sets the targets, which will be larger too).

The basic Deep Q-Learning algorithm we’ve been using so far would be too unstable to learn to play Atari games. So how did DeepMind do it? Well, they tweaked the algorithm!

¹³ A great 2018 post by Alex Irpan nicely lays out RL’s biggest difficulties and limitations.

Deep Q-Learning Variants

Let's look at a few variants of the Deep Q-Learning algorithm that can stabilize and speed up training.

Fixed Q-Value Targets

In the basic Deep Q-Learning algorithm, the model is used both to make predictions and to set its own targets. This can lead to a situation analogous to a dog chasing its own tail. This feedback loop can make the network unstable: it can diverge, oscillate, freeze, and so on. To solve this problem, in their 2013 paper the DeepMind researchers used two DQNs instead of one: the first is the *online model*, which learns at each step and is used to move the agent around, and the other is the *target model* used only to define the targets. The target model is just a clone of the online model:

```
target = keras.models.clone_model(model)
target.set_weights(model.get_weights())
```

Then, in the `training_step()` function, we just need to change one line to use the target model instead of the online model when computing the Q-Values of the next states:

```
next_Q_values = target.predict(next_states)
```

Finally, in the training loop, we must copy the weights of the online model to the target model, at regular intervals (e.g., every 50 episodes):

```
if episode % 50 == 0:
    target.set_weights(model.get_weights())
```

Since the target model is updated much less often than the online model, the Q-Value targets are more stable, the feedback loop we discussed earlier is dampened, and its effects are less severe. This approach was one of the DeepMind researchers' main contributions in their 2013 paper, allowing agents to learn to play Atari games from raw pixels. To stabilize training, they used a tiny learning rate of 0.00025, they updated the target model only every 10,000 steps (instead of the 50 in the previous code example), and they used a very large replay buffer of 1 million experiences. They decreased `epsilon` very slowly, from 1 to 0.1 in 1 million steps, and they let the algorithm run for 50 million steps.

Later in this chapter, we will use the TF-Agents library to train a DQN agent to play *Breakout* using these hyperparameters, but before we get there, let's take a look at another DQN variant that managed to beat the state of the art once more.

Double DQN

In a 2015 paper,¹⁴ DeepMind researchers tweaked their DQN algorithm, increasing its performance and somewhat stabilizing training. They called this variant *Double DQN*. The update was based on the observation that the target network is prone to overestimating Q-Values. Indeed, suppose all actions are equally good: the Q-Values estimated by the target model should be identical, but since they are approximations, some may be slightly greater than others, by pure chance. The target model will always select the largest Q-Value, which will be slightly greater than the mean Q-Value, most likely overestimating the true Q-Value (a bit like counting the height of the tallest random wave when measuring the depth of a pool). To fix this, they proposed using the online model instead of the target model when selecting the best actions for the next states, and using the target model only to estimate the Q-Values for these best actions. Here is the updated `training_step()` function:

```
def training_step(batch_size):
    experiences = sample_experiences(batch_size)
    states, actions, rewards, next_states, dones = experiences
    next_Q_values = model.predict(next_states)
    best_next_actions = np.argmax(next_Q_values, axis=1)
    next_mask = tf.one_hot(best_next_actions, n_outputs).numpy()
    next_best_Q_values = (target.predict(next_states) * next_mask).sum(axis=1)
    target_Q_values = (rewards +
                      (1 - dones) * discount_factor * next_best_Q_values)
    mask = tf.one_hot(actions, n_outputs)
    [...] # the rest is the same as earlier
```

Just a few months later, another improvement to the DQN algorithm was proposed.

Prioritized Experience Replay

Instead of sampling experiences *uniformly* from the replay buffer, why not sample important experiences more frequently? This idea is called *importance sampling* (IS) or *prioritized experience replay* (PER), and it was introduced in a 2015 paper¹⁵ by DeepMind researchers (once again!).

More specifically, experiences are considered “important” if they are likely to lead to fast learning progress. But how can we estimate this? One reasonable approach is to measure the magnitude of the TD error $\delta = r + \gamma \cdot V(s') - V(s)$. A large TD error indicates that a transition (s, r, s') is very surprising, and thus probably worth learning

¹⁴ Hado van Hasselt et al., “Deep Reinforcement Learning with Double Q-Learning,” *Proceedings of the 30th AAAI Conference on Artificial Intelligence* (2015): 2094–2100.

¹⁵ Tom Schaul et al., “Prioritized Experience Replay,” arXiv preprint arXiv:1511.05952 (2015).

from.¹⁶ When an experience is recorded in the replay buffer, its priority is set to a very large value, to ensure that it gets sampled at least once. However, once it is sampled (and every time it is sampled), the TD error δ is computed, and this experience's priority is set to $p = |\delta|$ (plus a small constant to ensure that every experience has a non-zero probability of being sampled). The probability P of sampling an experience with priority p is proportional to p^ζ , where ζ is a hyperparameter that controls how greedy we want importance sampling to be: when $\zeta = 0$, we just get uniform sampling, and when $\zeta = 1$, we get full-blown importance sampling. In the paper, the authors used $\zeta = 0.6$, but the optimal value will depend on the task.

There's one catch, though: since the samples will be biased toward important experiences, we must compensate for this bias during training by downweighting the experiences according to their importance, or else the model will just overfit the important experiences. To be clear, we want important experiences to be sampled more often, but this also means we must give them a lower weight during training. To do this, we define each experience's training weight as $w = (n P)^{-\beta}$, where n is the number of experiences in the replay buffer, and β is a hyperparameter that controls how much we want to compensate for the importance sampling bias (0 means not at all, while 1 means entirely). In the paper, the authors used $\beta = 0.4$ at the beginning of training and linearly increased it to $\beta = 1$ by the end of training. Again, the optimal value will depend on the task, but if you increase one, you will usually want to increase the other as well.

Now let's look at one last important variant of the DQN algorithm.

Dueling DQN

The *Dueling DQN* algorithm (DDQN, not to be confused with Double DQN, although both techniques can easily be combined) was introduced in yet another 2015 paper¹⁷ by DeepMind researchers. To understand how it works, we must first note that the Q-Value of a state-action pair (s, a) can be expressed as $Q(s, a) = V(s) + A(s, a)$, where $V(s)$ is the value of state s and $A(s, a)$ is the *advantage* of taking the action a in state s , compared to all other possible actions in that state. Moreover, the value of a state is equal to the Q-Value of the best action a^* for that state (since we assume the optimal policy will pick the best action), so $V(s) = Q(s, a^*)$, which implies that $A(s, a^*) = 0$. In a Dueling DQN, the model estimates both the value of the state and the advantage of each possible action. Since the best action should have an advantage of 0, the model subtracts the maximum predicted advantage from all pre-

16 It could also just be that the rewards are noisy, in which case there are better methods for estimating an experience's importance (see the paper for some examples).

17 Ziyu Wang et al., "Dueling Network Architectures for Deep Reinforcement Learning," arXiv preprint arXiv:1511.06581 (2015).

dicted advantages. Here is a simple Dueling DQN model, implemented using the Functional API:

```
K = keras.backend
input_states = keras.layers.Input(shape=[4])
hidden1 = keras.layers.Dense(32, activation="elu")(input_states)
hidden2 = keras.layers.Dense(32, activation="elu")(hidden1)
state_values = keras.layers.Dense(1)(hidden2)
raw_advantages = keras.layers.Dense(n_outputs)(hidden2)
advantages = raw_advantages - K.max(raw_advantages, axis=1, keepdims=True)
Q_values = state_values + advantages
model = keras.Model(inputs=[input_states], outputs=[Q_values])
```

The rest of the algorithm is just the same as earlier. In fact, you can build a Double Dueling DQN and combine it with prioritized experience replay! More generally, many RL techniques can be combined, as DeepMind demonstrated in a [2017 paper](#).¹⁸ The paper’s authors combined six different techniques into an agent called *Rainbow*, which largely outperformed the state of the art.

Unfortunately, implementing all of these techniques, debugging them, fine-tuning them, and of course training the models can require a huge amount of work. So instead of reinventing the wheel, it is often best to reuse scalable and well-tested libraries, such as TF-Agents.

The TF-Agents Library

The **TF-Agents library** is a Reinforcement Learning library based on TensorFlow, developed at Google and open sourced in 2018. Just like OpenAI Gym, it provides many off-the-shelf environments (including wrappers for all OpenAI Gym environments), plus it supports the PyBullet library (for 3D physics simulation), DeepMind’s DM Control library (based on MuJoCo’s physics engine), and Unity’s ML-Agents library (simulating many 3D environments). It also implements many RL algorithms, including REINFORCE, DQN, and DDQN, as well as various RL components such as efficient replay buffers and metrics. It is fast, scalable, easy to use, and customizable: you can create your own environments and neural nets, and you can customize pretty much any component. In this section we will use TF-Agents to train an agent to play *Breakout*, the famous Atari game (see [Figure 18-11](#)¹⁹), using the DQN algorithm (you can easily switch to another algorithm if you prefer).

18 Matteo Hessel et al., “Rainbow: Combining Improvements in Deep Reinforcement Learning,” arXiv preprint arXiv:1710.02298 (2017): 3215–3222.

19 If you don’t know this game, it’s simple: a ball bounces around and breaks bricks when it touches them. You control a paddle near the bottom of the screen. The paddle can go left or right, and you must get the ball to break every brick, while preventing it from touching the bottom of the screen.




Figure 18-11. The famous Breakout game

Installing TF-Agents

Let's start by installing TF-Agents. This can be done using pip (as always, if you are using a virtual environment, make sure to activate it first; if not, you will need to use the `--user` option, or have administrator rights):

```
$ python3 -m pip install -U tf-agents
```



At the time of this writing, TF-Agents is still quite new and improving every day, so the API may change a bit by the time you read this—but the big picture should remain the same, as well as most of the code. If anything breaks, I will update the Jupyter notebook accordingly, so make sure to check it out.

Next, let's create a TF-Agents environment that will just wrap OpenAI GGym's Breakout environment. For this, you must first install OpenAI Gym's Atari dependencies:

```
$ python3 -m pip install -U 'gym[atari]'
```

Among other libraries, this command will install `atari-py`, which is a Python interface for the Arcade Learning Environment (ALE), a framework built on top of the Atari 2600 emulator Stella.

TF-Agents Environments

If everything went well, you should be able to import TF-Agents and create a Breakout environment:

```
>>> from tf_agents.environments import suite_gym
>>> env = suite_gym.load("Breakout-v4")
>>> env
<tf_agents.environments.wrappers.TimeLimit at 0x10c523c18>
```

This is just a wrapper around an OpenAI Gym environment, which you can access through the `gym` attribute:

```
>>> env.gym
<gym.envs.atari.atari_env.AtariEnv at 0x24dcab940>
```

TF-Agents environments are very similar to OpenAI Gym environments, but there are a few differences. First, the `reset()` method does not return an observation; instead it returns a `TimeStep` object that wraps the observation, as well as some extra information:

```
>>> env.reset()
TimeStep(step_type=array(0, dtype=int32),
         reward=array(0., dtype=float32),
         discount=array(1., dtype=float32),
         observation=array([[0., 0., 0.], [0., 0., 0.],...]], dtype=float32))
```

The `step()` method returns a `TimeStep` object as well:

```
>>> env.step(1) # Fire
TimeStep(step_type=array(1, dtype=int32),
         reward=array(0., dtype=float32),
         discount=array(1., dtype=float32),
         observation=array([[0., 0., 0.], [0., 0., 0.],...]], dtype=float32))
```

The reward and observation attributes are self-explanatory, and they are the same as for OpenAI Gym (except the reward is represented as a NumPy array). The `step_type` attribute is equal to 0 for the first time step in the episode, 1 for intermediate time steps, and 2 for the final time step. You can call the time step's `is_last()` method to check whether it is the final one or not. Lastly, the `discount` attribute indicates the discount factor to use at this time step. In this example it is equal to 1, so there will be no discount at all. You can define the discount factor by setting the `discount` parameter when loading the environment.



At any time, you can access the environment's current time step by calling its `current_time_step()` method.

Environment Specifications

Conveniently, a TF-Agents environment provides the specifications of the observations, actions, and time steps, including their shapes, data types, and names, as well as their minimum and maximum values:


```
>>> env.observation_spec()
BoundedArraySpec(shape=(210, 160, 3), dtype=dtype('float32'), name=None,
                  minimum=[[0. 0. 0.], [0. 0. 0.],...]],
                  maximum=[[255., 255., 255.], [255., 255., 255.], ...]])
>>> env.action_spec()
BoundedArraySpec(shape=(), dtype=dtype('int64'), name=None,
                  minimum=0, maximum=3)
>>> env.time_step_spec()
TimeStep(step_type=ArraySpec(shape=(), dtype=dtype('int32'), name='step_type'),
         reward=ArraySpec(shape=(), dtype=dtype('float32'), name='reward'),
         discount=BoundedArraySpec(shape=(), ..., minimum=0.0, maximum=1.0),
         observation=BoundedArraySpec(shape=(210, 160, 3), ...))
```

As you can see, the observations are simply screenshots of the Atari screen, represented as NumPy arrays of shape [210, 160, 3]. To render an environment, you can call `env.render(mode="human")`, and if you want to get back the image in the form of a NumPy array, just call `env.render(mode="rgb_array")` (unlike in OpenAI Gym, this is the default mode).

There are four actions available. Gym's Atari environments have an extra method that you can call to know what each action corresponds to:

```
>>> env.gym.get_action_meanings()
['NOOP', 'FIRE', 'RIGHT', 'LEFT']
```



Specs can be instances of a specification class, nested lists, or dictionaries of specs. If the specification is nested, then the specified object must match the specification's nested structure. For example, if the observation spec is `{"sensors": ArraySpec(shape=[2]), "camera": ArraySpec(shape=[100, 100])}`, then a valid observation would be `{"sensors": np.array([1.5, 3.5]), "camera": np.array(...)}`. The `tf.nest` package provides tools to handle such nested structures (a.k.a. *nest*s).

The observations are quite large, so we will downsample them and also convert them to grayscale. This will speed up training and use less RAM. For this, we can use an *environment wrapper*.

Environment Wrappers and Atari Preprocessing

TF-Agents provides several environment wrappers in the `tf_agents.environments.wrappers` package. As their name suggests, they wrap an environment, forwarding every call to it, but also adding some extra functionality. Here are some of the available wrappers:

ActionClipWrapper

Clips the actions to the action spec.

ActionDiscretizeWrapper

Quantizes a continuous action space to a discrete action space. For example, if the original environment's action space is the continuous range from -1.0 to $+1.0$, but you want to use an algorithm that only supports discrete action spaces, such as a DQN, then you can wrap the environment using `discrete_env = ActionDiscretizeWrapper(env, num_actions=5)`, and the new `discrete_env` will have a discrete action space with five possible actions: 0, 1, 2, 3, 4. These actions correspond to the actions -1.0 , -0.5 , 0.0 , 0.5 , and 1.0 in the original environment.

ActionRepeat

Repeats each action over n steps, while accumulating the rewards. In many environments, this can speed up training significantly.

RunStats

Records environment statistics such as the number of steps and the number of episodes.

TimeLimit

Interrupts the environment if it runs for longer than a maximum number of steps.

VideoWrapper

Records a video of the environment.

To create a wrapped environment, you must create a wrapper, passing the wrapped environment to the constructor. That's all! For example, the following code will wrap our environment in an `ActionRepeat` wrapper so that every action is repeated four times:

```
from tf_agents.environments.wrappers import ActionRepeat

repeating_env = ActionRepeat(env, times=4)
```

OpenAI Gym has some environment wrappers of its own in the `gym.wrappers` package. They are meant to wrap Gym environments, though, not TF-Agents environments, so to use them you must first wrap the Gym environment with a Gym wrapper, then wrap the resulting environment with a TF-Agents wrapper. The `suite_gym.wrap_env()` function will do this for you, provided you give it a Gym environment and a list of Gym wrappers and/or a list of TF-Agents wrappers. Alternatively, the `suite_gym.load()` function will both create the Gym environment and wrap it for you, if you give it some wrappers. Each wrapper will be created without any arguments, so if you want to set some arguments, you must pass a `lambda`. For example, the following code creates a Breakout environment that will run for a maximum of 10,000 steps during each episode, and each action will be repeated four times:

```

from gym.wrappers import TimeLimit

limited_repeating_env = suite_gym.load(
    "Breakout-v4",
    gym_env_wrappers=[lambda env: TimeLimit(env, max_episode_steps=10000)],
    env_wrappers=[lambda env: ActionRepeat(env, times=4)])

```

For Atari environments, some standard preprocessing steps are applied in most papers that use them, so TF-Agents provides a handy `AtariPreprocessing` wrapper that implements them. Here is the list of preprocessing steps it supports:

Grayscale and downsampling

Observations are converted to grayscale and downsampled (by default to 84×84 pixels).

Max pooling

The last two frames of the game are max-pooled using a 1×1 filter. This is to remove the flickering that occurs in some Atari games due to the limited number of sprites that the Atari 2600 could display in each frame.

Frame skipping

The agent only gets to see every n frames of the game (by default $n = 4$), and its actions are repeated for each frame, collecting all the rewards. This effectively speeds up the game from the perspective of the agent, and it also speeds up training because rewards are less delayed.

End on life lost

In some games, the rewards are just based on the score, so the agent gets no immediate penalty for losing a life. One solution is to end the game immediately whenever a life is lost. There is some debate over the actual benefits of this strategy, so it is off by default.

Since the default Atari environment already applies random frame skipping and max pooling, we will need to load the raw, nonskipping variant called "BreakoutNoFrameskip-v4". Moreover, a single frame from the *Breakout* game is insufficient to know the direction and speed of the ball, which will make it very difficult for the agent to play the game properly (unless it is an RNN agent, which preserves some internal state between steps). One way to handle this is to use an environment wrapper that will output observations composed of multiple frames stacked on top of each other along the channels dimension. This strategy is implemented by the `FrameStack4` wrapper, which returns stacks of four frames. Let's create the wrapped Atari environment!

```

from tf_agents.environments import suite_atari
from tf_agents.environments.atari_preprocessing import AtariPreprocessing
from tf_agents.environments.atari_wrappers import FrameStack4

max_episode_steps = 27000 # <=> 108k ALE frames since 1 step = 4 frames
environment_name = "BreakoutNoFrameskip-v4"

env = suite_atari.load(
    environment_name,
    max_episode_steps=max_episode_steps,
    gym_env_wrappers=[AtariPreprocessing, FrameStack4])

```

The result of all this preprocessing is shown in [Figure 18-12](#). You can see that the resolution is much lower, but sufficient to play the game. Moreover, frames are stacked along the channels dimension, so red represents the frame from three steps ago, green is two steps ago, blue is the previous frame, and pink is the current frame.²⁰ From this single observation, the agent can see that the ball is going toward the lower-left corner, and that it should continue to move the paddle to the left (as it did in the previous steps).




Figure 18-12. Preprocessed Breakout observation

Lastly, we can wrap the environment inside a `TFPyEnvironment`:

```

from tf_agents.environments.tf_py_environment import TFPyEnvironment

tf_env = TFPyEnvironment(env)

```

This will make the environment usable from within a TensorFlow graph (under the hood, this class relies on `tf.py_function()`, which allows a graph to call arbitrary

²⁰ Since there are only three primary colors, you cannot just display an image with four color channels. For this reason, I combined the last channel with the first three to get the RGB image represented here. Pink is actually a mix of blue and red, but the agent sees four independent channels.

Python code). Thanks to the `TFPyEnvironment` class, TF-Agents supports both pure Python environments and TensorFlow-based environments. More generally, TF-Agents supports and provides both pure Python and TensorFlow-based components (agents, replay buffers, metrics, and so on).

Now that we have a nice Breakout environment, with all the appropriate preprocessing and TensorFlow support, we must create the DQN agent and the other components we will need to train it. Let's look at the architecture of the system we will build.

Training Architecture

A TF-Agents training program is usually split into two parts that run in parallel, as you can see in [Figure 18-13](#): on the left, a *driver* explores the *environment* using a *collect policy* to choose actions, and it collects *trajectories* (i.e., experiences), sending them to an *observer*, which saves them to a *replay buffer*; on the right, an *agent* pulls batches of trajectories from the replay buffer and trains some *networks*, which the collect policy uses. In short, the left part explores the environment and collects trajectories, while the right part learns and updates the collect policy.




Figure 18-13. A typical TF-Agents training architecture

This figure begs a few questions, which I'll attempt to answer here:

- Why are there multiple environments? Instead of exploring a single environment, you generally want the driver to explore multiple copies of the environment in parallel, taking advantage of the power of all your CPU cores, keeping

the training GPUs busy, and providing less-correlated trajectories to the training algorithm.

- What is a *trajectory*? It is a concise representation of a *transition* from one time step to the next, or a sequence of consecutive transitions from time step n to time step $n + t$. The trajectories collected by the driver are passed to the observer, which saves them in the replay buffer, and they are later sampled by the agent and used for training.
- Why do we need an observer? Can't the driver save the trajectories directly? Indeed, it could, but this would make the architecture less flexible. For example, what if you don't want to use a replay buffer? What if you want to use the trajectories for something else, like computing metrics? In fact, an observer is just any function that takes a trajectory as an argument. You can use an observer to save the trajectories to a replay buffer, or to save them to a TFRecord file (see [Chapter 13](#)), or to compute metrics, or for anything else. Moreover, you can pass multiple observers to the driver, and it will broadcast the trajectories to all of them.



Although this architecture is the most common, you can customize it as you please, and even replace some components with your own. In fact, unless you are researching new RL algorithms, you will most likely want to use a custom environment for your task. For this, you just need to create a custom class that inherits from the `PyEnvironment` class in the `tf_agents.environments.py_environment` package and overrides the appropriate methods, such as `action_spec()`, `observation_spec()`, `_reset()`, and `_step()` (see the “Creating a Custom TF-Agents Environment” section of the notebook for an example).

Now we will create all these components: first the Deep Q-Network, then the DQN agent (which will take care of creating the collect policy), then the replay buffer and the observer to write to it, then a few training metrics, then the driver, and finally the dataset. Once we have all the components in place, we will populate the replay buffer with some initial trajectories, then we will run the main training loop. So, let's start by creating the Deep Q-Network.

Creating the Deep Q-Network

The TF-Agents library provides many networks in the `tf_agents.networks` package and its subpackages. We will use the `tf_agents.networks.q_network.QNetwork` class:

```

from tf_agents.networks.q_network import QNetwork

preprocessing_layer = keras.layers.Lambda(
    lambda obs: tf.cast(obs, np.float32) / 255.)
conv_layer_params=[(32, (8, 8), 4), (64, (4, 4), 2), (64, (3, 3), 1)]
fc_layer_params=[512]

q_net = QNetwork(
    tf_env.observation_spec(),
    tf_env.action_spec(),
    preprocessing_layers=preprocessing_layer,
    conv_layer_params=conv_layer_params,
    fc_layer_params=fc_layer_params)

```

This QNetwork takes an observation as input and outputs one Q-Value per action, so we must give it the specifications of the observations and the actions. It starts with a preprocessing layer: a simple Lambda layer that casts the observations to 32-bit floats and normalizes them (the values will range from 0.0 to 1.0). The observations contain unsigned bytes, which use 4 times less space than 32-bit floats, which is why we did not cast the observations to 32-bit floats earlier; we want to save RAM in the replay buffer. Next, the network applies three convolutional layers: the first has $32\ 8 \times 8$ filters and uses a stride of 4, the second has $64\ 4 \times 4$ filters and a stride of 2, and the third has $64\ 3 \times 3$ filters and a stride of 1. Lastly, it applies a dense layer with 512 units, followed by a dense output layer with 4 units, one per Q-Value to output (i.e., one per action). All convolutional layers and all dense layers except the output layer use the ReLU activation function by default (you can change this by setting the `activation_fn` argument). The output layer does not use any activation function.

Under the hood, a QNetwork is composed of two parts: an encoding network that processes the observations, followed by a dense output layer that outputs one Q-Value per action. TF-Agent's `EncodingNetwork` class implements a neural network architecture found in various agents (see [Figure 18-14](#)).

It may have one or more inputs. For example, if each observation is composed of some sensor data plus an image from a camera, you will have two inputs. Each input may require some preprocessing steps, in which case you can specify a list of Keras layers via the `preprocessing_layers` argument, with one preprocessing layer per input, and the network will apply each layer to the corresponding input (if an input requires multiple layers of preprocessing, you can pass a whole model, since a Keras model can always be used as a layer). If there are two inputs or more, you must also pass an extra layer via the `preprocessing_combiner` argument, to combine the outputs from the preprocessing layers into a single output.

Next, the encoding network will optionally apply a list of convolutions sequentially, provided you specify their parameters via the `conv_layer_params` argument. This must be a list composed of 3-tuples (one per convolutional layer) indicating the

number of filters, the kernel size, and the stride. After these convolutional layers, the encoding network will optionally apply a sequence of dense layers, if you set the `fc_layer_params` argument: it must be a list containing the number of neurons for each dense layer. Optionally, you can also pass a list of dropout rates (one per dense layer) via the `dropout_layer_params` argument if you want to apply dropout after each dense layer. The `QNetwork` takes the output of this encoding network and passes it to the dense output layer (with one unit per action).




Figure 18-14. Architecture of an encoding network



The `QNetwork` class is flexible enough to build many different architectures, but you can always build your own network class if you need extra flexibility: extend the `tf_agents.networks.Network` class and implement it like a regular custom Keras layer. The `tf_agents.networks.Network` class is a subclass of the `keras.layers.Layer` class that adds some functionality required by some agents, such as the possibility to easily create shallow copies of the network (i.e., copying the network's architecture, but not its weights). For example, the `DQNAgent` uses this to create a copy of the online model.

Now that we have the DQN, we are ready to build the DQN agent.

Creating the DQN Agent

The TF-Agents library implements many types of agents, located in the `tf_agents.agents` package and its subpackages. We will use the `tf_agents.agents.dqn.dqn_agent.DqnAgent` class:


```

from tf_agents.agents.dqn.dqn_agent import DqnAgent

train_step = tf.Variable(0)
update_period = 4 # train the model every 4 steps
optimizer = keras.optimizers.RMSprop(lr=2.5e-4, rho=0.95, momentum=0.0,
                                     epsilon=0.00001, centered=True)
epsilon_fn = keras.optimizers.schedules.PolynomialDecay(
    initial_learning_rate=1.0, # initial  $\epsilon$ 
    decay_steps=250000 // update_period, #  $\Leftrightarrow$  1,000,000 ALE frames
    end_learning_rate=0.01) # final  $\epsilon$ 
agent = DqnAgent(tf_env.time_step_spec(),
                 tf_env.action_spec(),
                 q_network=q_net,
                 optimizer=optimizer,
                 target_update_period=2000, #  $\Leftrightarrow$  32,000 ALE frames
                 td_errors_loss_fn=keras.losses.Huber(reduction="none"),
                 gamma=0.99, # discount factor
                 train_step_counter=train_step,
                 epsilon_greedy=lambda: epsilon_fn(train_step))
agent.initialize()

```

Let's walk through this code:

- We first create a variable that will count the number of training steps.
- Then we build the optimizer, using the same hyperparameters as in the 2015 DQN paper.
- Next, we create a PolynomialDecay object that will compute the ϵ value for the ϵ -greedy collect policy, given the current training step (it is normally used to decay the learning rate, hence the names of the arguments, but it will work just fine to decay any other value). It will go from 1.0 down to 0.01 (the value used during in the 2015 DQN paper) in 1 million ALE frames, which corresponds to 250,000 steps, since we use frame skipping with a period of 4. Moreover, we will train the agent every 4 steps (i.e., 16 ALE frames), so ϵ will actually decay over 62,500 training steps.
- We then build the DQNAgent, passing it the time step and action specs, the QNet work to train, the optimizer, the number of training steps between target model updates, the loss function to use, the discount factor, the train_step variable, and a function that returns the ϵ value (it must take no argument, which is why we need a lambda to pass the train_step).

Note that the loss function must return an error per instance, not the mean error, which is why we set reduction="none".

- Lastly, we initialize the agent.

Next, let's build the replay buffer and the observer that will write to it.

Creating the Replay Buffer and the Corresponding Observer

The TF-Agents library provides various replay buffer implementations in the `tf_agents.replay_buffers` package. Some are purely written in Python (their module names start with `py_`), and others are written based on TensorFlow (their module names start with `tf_`). We will use the `TfUniformReplayBuffer` class in the `tf_agents.replay_buffers.tf_uniform_replay_buffer` package. It provides a high-performance implementation of a replay buffer with uniform sampling:²¹

```
from tf_agents.replay_buffers import tf_uniform_replay_buffer

replay_buffer = tf_uniform_replay_buffer.TfUniformReplayBuffer(
    data_spec=agent.collect_data_spec,
    batch_size=tf_env.batch_size,
    max_length=1000000)
```

Let's look at each of these arguments:

`data_spec`

The specification of the data that will be saved in the replay buffer. The DQN agent knows what the collected data will look like, and it makes the data spec available via its `collect_data_spec` attribute, so that's what we give the replay buffer.

`batch_size`

The number of trajectories that will be added at each step. In our case, it will be one, since the driver will just execute one action per step and collect one trajectory. If the environment were a *batched environment*, meaning an environment that takes a batch of actions at each step and returns a batch of observations, then the driver would have to save a batch of trajectories at each step. Since we are using a TensorFlow replay buffer, it needs to know the size of the batches it will handle (to build the computation graph). An example of a batched environment is the `ParallelPyEnvironment` (from the `tf_agents.environments.parallel_py_environment` package): it runs multiple environments in parallel in separate processes (they can be different as long as they have the same action and observation specs), and at each step it takes a batch of actions and executes them in the environments (one action per environment), then it returns all the resulting observations.

²¹ At the time of this writing, there is no prioritized experience replay buffer yet, but one will likely be open sourced soon.

`max_length`

The maximum size of the replay buffer. We created a large replay buffer that can store one million trajectories (as was done in the 2015 DQN paper). This will require a lot of RAM.



When we store two consecutive trajectories, they contain two consecutive observations with four frames each (since we used the `FrameStack4` wrapper), and unfortunately three of the four frames in the second observation are redundant (they are already present in the first observation). In other words, we are using about four times more RAM than necessary. To avoid this, you can instead use a `PyHashedReplayBuffer` from the `tf_agents.replay_buffers.py_hashed_replay_buffer` package: it deduplicates data in the stored trajectories along the last axis of the observations.

Now we can create the observer that will write the trajectories to the replay buffer. An observer is just a function (or a callable object) that takes a trajectory argument, so we can directly use the `add_method()` method (bound to the `replay_buffer` object) as our observer:

```
replay_buffer_observer = replay_buffer.add_batch
```

If you wanted to create your own observer, you could write any function with a trajectory argument. If it must have a state, you can write a class with a `__call__(self, trajectory)` method. For example, here is a simple observer that will increment a counter every time it is called (except when the trajectory represents a boundary between two episodes, which does not count as a step), and every 100 increments it displays the progress up to a given total (the carriage return `\r` along with `end=""` ensures that the displayed counter remains on the same line):

```
class ShowProgress:
    def __init__(self, total):
        self.counter = 0
        self.total = total
    def __call__(self, trajectory):
        if not trajectory.is_boundary():
            self.counter += 1
        if self.counter % 100 == 0:
            print("\r{}/{}".format(self.counter, self.total), end="")
```

Now let's create a few training metrics.

Creating Training Metrics

TF-Agents implements several RL metrics in the `tf_agents.metrics` package, some purely in Python and some based on TensorFlow. Let's create a few of them in order

to count the number of episodes, the number of steps taken, and most importantly the average return per episode and the average episode length:

```
from tf_agents.metrics import tf_metrics

train_metrics = [
    tf_metrics.NumberOfEpisodes(),
    tf_metrics.EnvironmentSteps(),
    tf_metrics.AverageReturnMetric(),
    tf_metrics.AverageEpisodeLengthMetric(),
]
```



Discounting the rewards makes sense for training or to implement a policy, as it makes it possible to balance the importance of immediate rewards with future rewards. However, once an episode is over, we can evaluate how good it was overall by summing the *undiscounted* rewards. For this reason, the `AverageReturnMetric` computes the sum of undiscounted rewards for each episode, and it keeps track of the streaming mean of these sums over all the episodes it encounters.

At any time, you can get the value of each of these metrics by calling its `result()` method (e.g., `train_metrics[0].result()`). Alternatively, you can log all metrics by calling `log_metrics(train_metrics)` (this function is located in the `tf_agents.eval.metric_utils` package):

```
>>> from tf_agents.eval.metric_utils import log_metrics
>>> import logging
>>> logging.getLogger().set_level(logging.INFO)
>>> log_metrics(train_metrics)
[...]
NumberOfEpisodes = 0
EnvironmentSteps = 0
AverageReturn = 0.0
AverageEpisodeLength = 0.0
```

Next, let's create the collect driver.

Creating the Collect Driver

As we explored in [Figure 18-13](#), a driver is an object that explores an environment using a given policy, collects experiences, and broadcasts them to some observers. At each step, the following things happen:

- The driver passes the current time step to the collect policy, which uses this time step to choose an action and returns an *action step* object containing the action.

- The driver then passes the action to the environment, which returns the next time step.
- Finally, the driver creates a trajectory object to represent this transition and broadcasts it to all the observers.

Some policies, such as RNN policies, are stateful: they choose an action based on both the given time step and their own internal state. Stateful policies return their own state in the action step, along with the chosen action. The driver will then pass this state back to the policy at the next time step. Moreover, the driver saves the policy state to the trajectory (in the `policy_info` field), so it ends up in the replay buffer. This is essential when training a stateful policy: when the agent samples a trajectory, it must set the policy's state to the state it was in at the time of the sampled time step.

Also, as discussed earlier, the environment may be a batched environment, in which case the driver passes a *batched time step* to the policy (i.e., a time step object containing a batch of observations, a batch of step types, a batch of rewards, and a batch of discounts, all four batches of the same size). The driver also passes a batch of previous policy states. The policy then returns a *batched action step* containing a batch of actions and a batch of policy states. Finally, the driver creates a *batched trajectory* (i.e., a trajectory containing a batch of step types, a batch of observations, a batch of actions, a batch of rewards, and more generally a batch for each trajectory attribute, with all batches of the same size).

There are two main driver classes: `DynamicStepDriver` and `DynamicEpisodeDriver`. The first one collects experiences for a given number of steps, while the second collects experiences for a given number of episodes. We want to collect experiences for four steps for each training iteration (as was done in the 2015 DQN paper), so let's create a `DynamicStepDriver`:

```
from tf_agents.drivers.dynamic_step_driver import DynamicStepDriver

collect_driver = DynamicStepDriver(
    tf_env,
    agent.collect_policy,
    observers=[replay_buffer_observer] + training_metrics,
    num_steps=update_period) # collect 4 steps for each training iteration
```

We give it the environment to play with, the agent's collect policy, a list of observers (including the replay buffer observer and the training metrics), and finally the number of steps to run (in this case, four). We could now run it by calling its `run()` method, but it's best to warm up the replay buffer with experiences collected using a purely random policy. For this, we can use the `RandomTFPolicy` class and create a second driver that will run this policy for 20,000 steps (which is equivalent to 80,000 simulator frames, as was done in the 2015 DQN paper). We can use our `ShowProgress` observer to display the progress:

```

from tf_agents.policies.random_tf_policy import RandomTFPolicy

initial_collect_policy = RandomTFPolicy(tf_env.time_step_spec(),
                                         tf_env.action_spec())

init_driver = DynamicStepDriver(
    tf_env,
    initial_collect_policy,
    observers=[replay_buffer.add_batch, ShowProgress(20000)],
    num_steps=20000) # <=> 80,000 ALE frames
final_time_step, final_policy_state = init_driver.run()

```

We're almost ready to run the training loop! We just need one last component: the dataset.

Creating the Dataset

To sample a batch of trajectories from the replay buffer, call its `get_next()` method. This returns the batch of trajectories plus a `BufferInfo` object that contains the sample identifiers and their sampling probabilities (this may be useful for some algorithms, such as PER). For example, the following code will sample a small batch of two trajectories (subepisodes), each containing three consecutive steps. These subepisodes are shown in [Figure 18-15](#) (each row contains three consecutive steps from an episode):

```

>>> trajectories, buffer_info = replay_buffer.get_next(
...     sample_batch_size=2, num_steps=3)
...
>>> trajectories._fields
('step_type', 'observation', 'action', 'policy_info',
 'next_step_type', 'reward', 'discount')
>>> trajectories.observation.shape
TensorShape([2, 3, 84, 84, 4])
>>> trajectories.step_type.numpy()
array([[1, 1, 1],
       [1, 1, 1]], dtype=int32)

```

The `trajectories` object is a named tuple, with seven fields. Each field contains a tensor whose first two dimensions are 2 and 3 (since there are two trajectories, each with three steps). This explains why the shape of the `observation` field is `[2, 3, 84, 84, 4]`: that's two trajectories, each with three steps, and each step's observation is $84 \times 84 \times 4$. Similarly, the `step_type` tensor has a shape of `[2, 3]`: in this example, both trajectories contain three consecutive steps in the middle of an episode (types 1, 1, 1). In the second trajectory, you can barely see the ball at the lower left of the first observation, and it disappears in the next two observations, so the agent is about to lose a life, but the episode will not end immediately because it still has several lives left.




Figure 18-15. Two trajectories containing three consecutive steps each

Each trajectory is a concise representation of a sequence of consecutive time steps and action steps, designed to avoid redundancy. How so? Well, as you can see in [Figure 18-16](#), transition n is composed of time step n , action step n , and time step $n + 1$, while transition $n + 1$ is composed of time step $n + 1$, action step $n + 1$, and time step $n + 2$. If we just stored these two transitions directly in the replay buffer, the time step $n + 1$ would be duplicated. To avoid this duplication, the n^{th} trajectory step includes only the type and observation from time step n (not its reward and discount), and it does not contain the observation from time step $n + 1$ (however, it does contain a copy of the next time step's type; that's the only duplication).




Figure 18-16. Trajectories, transitions, time steps, and action steps

So if you have a batch of trajectories where each trajectory has $t + 1$ steps (from time step n to time step $n + t$), then it contains all the data from time step n to time step $n + t$, except for the reward and discount from time step n (but it contains the reward and discount of time step $n + t + 1$). This represents t transitions (n to $n + 1$, $n + 1$ to $n + 2$, ..., $n + t - 1$ to $n + t$).

The `to_transition()` function in the `tf_agents.trajectories.trajectory` module converts a batched trajectory into a list containing a batched `time_step`, a batched `action_step`, and a batched `next_time_step`. Notice that the second dimension is 2 instead of 3, since there are t transitions between $t + 1$ time steps (don't worry if you're a bit confused; you'll get the hang of it):

```
>>> from tf_agents.trajectories.trajectory import to_transition
>>> time_steps, action_steps, next_time_steps = to_transition(trajectories)
>>> time_steps.observation.shape
TensorShape([2, 2, 84, 84, 4]) # 3 time steps = 2 transitions
```



A sampled trajectory may actually overlap two (or more) episodes! In this case, it will contain *boundary transitions*, meaning transitions with a `step_type` equal to 2 (end) and a `next_step_type` equal to 0 (start). Of course, TF-Agents properly handles such trajectories (e.g., by resetting the policy state when encountering a boundary). The trajectory's `is_boundary()` method returns a tensor indicating whether each step is a boundary or not.

For our main training loop, instead of calling the `get_next()` method, we will use a `tf.data.Dataset`. This way, we can benefit from the power of the Data API (e.g., parallelism and prefetching). For this, we call the replay buffer's `as_dataset()` method:

```
dataset = replay_buffer.as_dataset(
    sample_batch_size=64,
    num_steps=2,
    num_parallel_calls=3).prefetch(3)
```

We will sample batches of 64 trajectories at each training step (as in the 2015 DQN paper), each with 2 steps (i.e., 2 steps = 1 full transition, including the next step's observation). This dataset will process three elements in parallel, and prefetch three batches.



For on-policy algorithms such as Policy Gradients, each experience should be sampled once, used from training, and then discarded. In this case, you can still use a replay buffer, but instead of using a `Dataset`, you would call the replay buffer's `gather_all()` method at each training iteration to get a tensor containing all the trajectories recorded so far, then use them to perform a training step, and finally clear the replay buffer by calling its `clear()` method.

Now that we have all the components in place, we are ready to train the model!

Creating the Training Loop

To speed up training, we will convert the main functions to TensorFlow Functions. For this we will use the `tf_agents.utils.common.function()` function, which wraps `tf.function()`, with some extra experimental options:

```
from tf_agents.utils.common import function

collect_driver.run = function(collect_driver.run)
agent.train = function(agent.train)
```

Let's create a small function that will run the main training loop for `n_iterations`:

```
def train_agent(n_iterations):
    time_step = None
    policy_state = agent.collect_policy.get_initial_state(tf_env.batch_size)
    iterator = iter(dataset)
    for iteration in range(n_iterations):
        time_step, policy_state = collect_driver.run(time_step, policy_state)
        trajectories, buffer_info = next(iterator)
        train_loss = agent.train(trajectories)
        print("\r{} loss: {:.5f}".format(
            iteration, train_loss.loss.numpy()), end="")
    if iteration % 1000 == 0:
        log_metrics(train_metrics)
```

The function first asks the collect policy for its initial state (given the environment batch size, which is 1 in this case). Since the policy is stateless, this returns an empty tuple (so we could have written `policy_state = ()`). Next, we create an iterator over the dataset, and we run the training loop. At each iteration, we call the driver's `run()` method, passing it the current time step (initially `None`) and the current policy state. It will run the collect policy and collect experience for four steps (as we configured earlier), broadcasting the collected trajectories to the replay buffer and the metrics. Next, we sample one batch of trajectories from the dataset, and we pass it to the agent's `train()` method. It returns a `train_loss` object which may vary depending on the type of agent. Next, we display the iteration number and the training loss, and every 1,000 iterations we log all the metrics. Now you can just call `train_agent()` for some number of iterations, and see the agent gradually learn to play *Breakout*!

```
train_agent(10000000)
```

This will take a lot of computing power and a lot of patience (it may take hours, or even days, depending on your hardware), plus you may need to run the algorithm several times with different random seeds to get good results, but once it's done, the agent will be superhuman (at least at *Breakout*). You can also try training this DQN agent on other Atari games: it can achieve superhuman skill at most action games, but it is not so good at games with long-running storylines.²²

Overview of Some Popular RL Algorithms

Before we finish this chapter, let's take a quick look at a few popular RL algorithms:

Actor-Critic algorithms

A family of RL algorithms that combine Policy Gradients with Deep Q-Networks. An Actor-Critic agent contains two neural networks: a policy net and a DQN. The DQN is trained normally, by learning from the agent's experiences. The policy net learns differently (and much faster) than in regular PG: instead of estimating the value of each action by going through multiple episodes, then summing the future discounted rewards for each action, and finally normalizing them, the agent (actor) relies on the action values estimated by the DQN (critic). It's a bit like an athlete (the agent) learning with the help of a coach (the DQN).

*Asynchronous Advantage Actor-Critic*²³ (A3C)

An important Actor-Critic variant introduced by DeepMind researchers in 2016, where multiple agents learn in parallel, exploring different copies of the environ-

22 For a comparison of this algorithm's performance on various Atari games, see figure 3 in DeepMind's [2015 paper](#).

23 Volodymyr Mnih et al., "Asynchronous Methods for Deep Reinforcement Learning," *Proceedings of the 33rd International Conference on Machine Learning* (2016): 1928–1937.

ment. At regular intervals, but asynchronously (hence the name), each agent pushes some weight updates to a master network, then it pulls the latest weights from that network. Each agent thus contributes to improving the master network and benefits from what the other agents have learned. Moreover, instead of estimating the Q-Values, the DQN estimates the advantage of each action (hence the second A in the name), which stabilizes training.

Advantage Actor-Critic (A2C)

A variant of the A3C algorithm that removes the asynchronicity. All model updates are synchronous, so gradient updates are performed over larger batches, which allows the model to better utilize the power of the GPU.

Soft Actor-Critic²⁴ (SAC)

An Actor-Critic variant proposed in 2018 by Tuomas Haarnoja and other UC Berkeley researchers. It learns not only rewards, but also to maximize the entropy of its actions. In other words, it tries to be as unpredictable as possible while still getting as many rewards as possible. This encourages the agent to explore the environment, which speeds up training, and makes it less likely to repeatedly execute the same action when the DQN produces imperfect estimates. This algorithm has demonstrated an amazing sample efficiency (contrary to all the previous algorithms, which learn very slowly). SAC is available in TF-Agents.

Proximal Policy Optimization (PPO)²⁵

An algorithm based on A2C that clips the loss function to avoid excessively large weight updates (which often lead to training instabilities). PPO is a simplification of the previous *Trust Region Policy Optimization²⁶* (TRPO) algorithm, also by John Schulman and other OpenAI researchers. OpenAI made the news in April 2019 with their AI called OpenAI Five, based on the PPO algorithm, which defeated the world champions at the multiplayer game *Dota 2*. PPO is also available in TF-Agents.

24 Tuomas Haarnoja et al., “Soft Actor-Critic: Off-Policy Maximum Entropy Deep Reinforcement Learning with a Stochastic Actor,” *Proceedings of the 35th International Conference on Machine Learning* (2018): 1856–1865.

25 John Schulman et al., “Proximal Policy Optimization Algorithms,” arXiv preprint arXiv:1707.06347 (2017).

26 John Schulman et al., “Trust Region Policy Optimization,” *Proceedings of the 32nd International Conference on Machine Learning* (2015): 1889–1897.

*Curiosity-based exploration*²⁷

A recurring problem in RL is the sparsity of the rewards, which makes learning very slow and inefficient. Deepak Pathak and other UC Berkeley researchers have proposed an exciting way to tackle this issue: why not ignore the rewards, and just make the agent extremely curious to explore the environment? The rewards thus become intrinsic to the agent, rather than coming from the environment. Similarly, stimulating curiosity in a child is more likely to give good results than purely rewarding the child for getting good grades. How does this work? The agent continuously tries to predict the outcome of its actions, and it seeks situations where the outcome does not match its predictions. In other words, it wants to be surprised. If the outcome is predictable (boring), it goes elsewhere. However, if the outcome is unpredictable but the agent notices that it has no control over it, it also gets bored after a while. With only curiosity, the authors succeeded in training an agent at many video games: even though the agent gets no penalty for losing, the game starts over, which is boring so it learns to avoid it.

We covered many topics in this chapter: Policy Gradients, Markov chains, Markov decision processes, Q-Learning, Approximate Q-Learning, and Deep Q-Learning and its main variants (fixed Q-Value targets, Double DQN, Dueling DQN, and prioritized experience replay). We discussed how to use TF-Agents to train agents at scale, and finally we took a quick look at a few other popular algorithms. Reinforcement Learning is a huge and exciting field, with new ideas and algorithms popping out every day, so I hope this chapter sparked your curiosity: there is a whole world to explore!

Exercises

1. How would you define Reinforcement Learning? How is it different from regular supervised or unsupervised learning?
2. Can you think of three possible applications of RL that were not mentioned in this chapter? For each of them, what is the environment? What is the agent? What are some possible actions? What are the rewards?
3. What is the discount factor? Can the optimal policy change if you modify the discount factor?
4. How do you measure the performance of a Reinforcement Learning agent?
5. What is the credit assignment problem? When does it occur? How can you alleviate it?
6. What is the point of using a replay buffer?

²⁷ Deepak Pathak et al., “Curiosity-Driven Exploration by Self-Supervised Prediction,” *Proceedings of the 34th International Conference on Machine Learning* (2017): 2778–2787.

7. What is an off-policy RL algorithm?
8. Use policy gradients to solve OpenAI Gym's LunarLander-v2 environment. You will need to install the Box2D dependencies (`python3 -m pip install -U gym[box2d]`).
9. Use TF-Agents to train an agent that can achieve a superhuman level at SpaceInvaders-v4 using any of the available algorithms.
10. If you have about \$100 to spare, you can purchase a Raspberry Pi 3 plus some cheap robotics components, install TensorFlow on the Pi, and go wild! For an example, check out this [fun post](#) by Lukas Biewald, or take a look at GoPiGo or BrickPi. Start with simple goals, like making the robot turn around to find the brightest angle (if it has a light sensor) or the closest object (if it has a sonar sensor), and move in that direction. Then you can start using Deep Learning: for example, if the robot has a camera, you can try to implement an object detection algorithm so it detects people and moves toward them. You can also try to use RL to make the agent learn on its own how to use the motors to achieve that goal. Have fun!

Solutions to these exercises are available in [Appendix A](#).

Training and Deploying TensorFlow Models at Scale

Once you have a beautiful model that makes amazing predictions, what do you do with it? Well, you need to put it in production! This could be as simple as running the model on a batch of data and perhaps writing a script that runs this model every night. However, it is often much more involved. Various parts of your infrastructure may need to use this model on live data, in which case you probably want to wrap your model in a web service: this way, any part of your infrastructure can query your model at any time using a simple REST API (or some other protocol), as we discussed in [Chapter 2](#). But as time passes, you need to regularly retrain your model on fresh data and push the updated version to production. You must handle model versioning, gracefully transition from one model to the next, possibly roll back to the previous model in case of problems, and perhaps run multiple different models in parallel to perform *A/B experiments*.¹ If your product becomes successful, your service may start to get plenty of *queries per second* (QPS), and it must scale up to support the load. A great solution to scale up your service, as we will see in this chapter, is to use TF Serving, either on your own hardware infrastructure or via a cloud service such as Google Cloud AI Platform. It will take care of efficiently serving your model, handle graceful model transitions, and more. If you use the cloud platform, you will also get many extra features, such as powerful monitoring tools.

Moreover, if you have a lot of training data, and compute-intensive models, then training time may be prohibitively long. If your product needs to adapt to changes quickly, then a long training time can be a showstopper (e.g., think of a news

¹ An A/B experiment consists in testing two different versions of your product on different subsets of users in order to check which version works best and get other insights.

recommendation system promoting news from last week). Perhaps even more importantly, a long training time will prevent you from experimenting with new ideas. In Machine Learning (as in many other fields), it is hard to know in advance which ideas will work, so you should try out as many as possible, as fast as possible. One way to speed up training is to use hardware accelerators such as GPUs or TPUs. To go even faster, you can train a model across multiple machines, each equipped with multiple hardware accelerators. TensorFlow's simple yet powerful Distribution Strategies API makes this easy, as we will see.

In this chapter we will look at how to deploy models, first to TF Serving, then to Google Cloud AI Platform. We will also take a quick look at deploying models to mobile apps, embedded devices, and web apps. Lastly, we will discuss how to speed up computations using GPUs and how to train models across multiple devices and servers using the Distribution Strategies API. That's a lot of topics to discuss, so let's get started!

Serving a TensorFlow Model

Once you have trained a TensorFlow model, you can easily use it in any Python code: if it's a `tf.keras` model, just call its `predict()` method! But as your infrastructure grows, there comes a point where it is preferable to wrap your model in a small service whose sole role is to make predictions and have the rest of the infrastructure query it (e.g., via a REST or gRPC API).² This decouples your model from the rest of the infrastructure, making it possible to easily switch model versions or scale the service up as needed (independently from the rest of your infrastructure), perform A/B experiments, and ensure that all your software components rely on the same model versions. It also simplifies testing and development, and more. You could create your own microservice using any technology you want (e.g., using the Flask library), but why reinvent the wheel when you can just use TF Serving?

Using TensorFlow Serving

TF Serving is a very efficient, battle-tested model server that's written in C++. It can sustain a high load, serve multiple versions of your models and watch a model repository to automatically deploy the latest versions, and more (see [Figure 19-1](#)).

2 A REST (or RESTful) API is an API that uses standard HTTP verbs, such as GET, POST, PUT, and DELETE, and uses JSON inputs and outputs. The gRPC protocol is more complex but more efficient. Data is exchanged using protocol buffers (see [Chapter 13](#)).




Figure 19-1. TF Serving can serve multiple models and automatically deploy the latest version of each model

So let's suppose you have trained an MNIST model using `tf.keras`, and you want to deploy it to TF Serving. The first thing you have to do is export this model to TensorFlow's *SavedModel* format.

Exporting SavedModels

TensorFlow provides a simple `tf.saved_model.save()` function to export models to the *SavedModel* format. All you need to do is give it the model, specifying its name and version number, and the function will save the model's computation graph and its weights:

```
model = keras.models.Sequential([...])
model.compile([...])
history = model.fit([...])

model_version = "0001"
model_name = "my_mnist_model"
model_path = os.path.join(model_name, model_version)
tf.saved_model.save(model, model_path)
```

Alternatively, you can just use the model's `save()` method (`model.save(model_path)`): as long as the file's extension is not `.h5`, the model will be saved using the *SavedModel* format instead of the *HDF5* format.

It's usually a good idea to include all the preprocessing layers in the final model you export so that it can ingest data in its natural form once it is deployed to production. This avoids having to take care of preprocessing separately within the application that uses the model. Bundling the preprocessing steps within the model also makes it simpler to update them later on and limits the risk of mismatch between a model and the preprocessing steps it requires.



Since a SavedModel saves the computation graph, it can only be used with models that are based exclusively on TensorFlow operations, excluding the `tf.py_function()` operation (which wraps arbitrary Python code). It also excludes dynamic tf.keras models (see [Appendix G](#)), since these models cannot be converted to computation graphs. Dynamic models need to be served using other tools (e.g., Flask).

A SavedModel represents a version of your model. It is stored as a directory containing a *saved_model.pb* file, which defines the computation graph (represented as a serialized protocol buffer), and a *variables* subdirectory containing the variable values. For models containing a large number of weights, these variable values may be split across multiple files. A SavedModel also includes an *assets* subdirectory that may contain additional data, such as vocabulary files, class names, or some example instances for this model. The directory structure is as follows (in this example, we don't use assets):

```
my_mnist_model
├── 0001
│   ├── assets
│   ├── saved_model.pb
│   └── variables
│       ├── variables.data-00000-of-00001
│       └── variables.index
```

As you might expect, you can load a SavedModel using the `tf.saved_model.load()` function. However, the returned object is not a Keras model: it represents the SavedModel, including its computation graph and variable values. You can use it like a function, and it will make predictions (make sure to pass the inputs as tensors of the appropriate type):

```
saved_model = tf.saved_model.load(model_path)
y_pred = saved_model(tf.constant(X_new, dtype=tf.float32))
```

Alternatively, you can load this SavedModel directly to a Keras model using the `keras.models.load_model()` function:

```
model = keras.models.load_model(model_path)
y_pred = model.predict(tf.constant(X_new, dtype=tf.float32))
```

TensorFlow also comes with a small `saved_model_cli` command-line tool to inspect SavedModels:

```
$ export ML_PATH="$HOME/ml" # point to this project, wherever it is
$ cd $ML_PATH
$ saved_model_cli show --dir my_mnist_model/0001 --all
MetaGraphDef with tag-set: 'serve' contains the following SignatureDefs:
signature_def['__saved_model_init_op']:
[...]
```