SystemC: Co-specification and Embedded System Modeling

Overview:

- Hardware-Software Co-Specification
- SystemC and Co-specification
- Introduction to SystemC for Co-specification
- A SystemC Primer

Hardware-Software Codesign

Co-design of Embedded Systems consists of the following parts:

- **Co-Specification**

  Developing system specification that describes hardware, software modules and relationship between the hardware and software

- **Co-Synthesis**

  Automatic and semi-automatic design of hardware and software modules to meet the specification

- **Co-Simulation and Co-verification**

  Simultaneous simulation of hardware and software

HW/SW Co-Specification

- Model the Embedded system functionality from an abstract level.
- No concept of hardware or software yet.
- Common environment

  SystemC: based on C++.
- Specification is analyzed to generate a task graph representation of the system functionality.

Co-Specification

- A system design language is needed to describe the functionality of both software and hardware.
- The system is first defined without making any assumptions about the implementation.
- A number of ways to define new specification standards grouped in three categories:

➢ SystemC An open source library in C^{++} that provides a modeling platform for systems with hardware and software components.

SystemC for Co-specification

Open SystemC Initiative (OSCI) 1999 by EDA venders including Synopsys, ARM, CoWare, Fujitsu, etc.

- A C++ based modeling environment containing a class library and a standard ANSI C++ compiler.
- SystemC provides a C++ based modeling platform for exchange and co-design of system-level intellectual property (SoC-IP) models.

- SystemC is not an extension to C++

  SystemC 1.0 and 2.1, 2.2 and 2.3 versions

  It has a new C++ class library

SystemC Library Classes

SystemC classes enable the user to

- Define modules and processes
- Add inter-process/module communication through ports and signals.

Modules/processes can handle a multitude of data types:
Ranging from bits to bit-vectors, standard C++ types to user define types like structures

Modules and processes also introduce timing, concurrency and reactive behavior.

- Using SystemC requires knowledge of C/C++

SystemC 2.0 Language Architecture



SystemC 2.0 Language Architecture

- All of SystemC builds on C++
- Upper layers are cleanly built on top of the lower layers
- The SystemC core language provides a minimal set of modeling constructs for structural description, concurrency, communication, and synchronization.
- Data types are separate from the core language and user-defined data types are fully supported.
- Commonly used communication mechanisms such as signals and FIFOs can be built on top of the core language.

  The MOCs can also be built on top of the core language.
- If desired, lower layers can be used without needing the upper layers.

SystemC Benefits

SystemC 2.x allows the following tasks to be performed within a single language:

- Complex system specifications can be developed and simulated
- System specifications can be refined to mixed software and hardware implementations
- Hardware implementations can be accurately modeled at all the levels.
- Complex data types can be easily modeled, and a flexible fixed-point numeric type is supported
- The extensive knowledge, infrastructure and code base built around C and C++ can be leveraged

SystemC for Co-Specification

Multiple abstraction levels:

- SystemC supports untimed models at different levels of abstraction,
  - ranging from high-level functional models to detailed clock cycle accurate RTL models.

Communication protocols:

- SystemC provides multi-level communication semantics that enable you to describe the system I/O protocols at different levels of abstraction.

Waveform tracing:

- SystemC supports tracing of waveforms in VCD, WIF, and ISDB formats.

SystemC Development Environment



SystemC Features

Rich set of data types:

- **to support multiple design domains and abstraction levels.**
  - The fixed precision data types allow for fast simulation,
  - Arbitrary precision types can be used for computations with large numbers.
  - the fixed-point data types can be used for DSP applications.

Variety of port and signal types:

- **To support modeling at different levels of abstraction, from the functional to the RTL.**

Clocks:

- **SystemC has the notion of clocks (as special signals).**
- **Multiple clocks, with arbitrary phase relationship, are supported.**

Cycle-based simulation:

- **SystemC includes an ultra light-weight cycle-based simulation kernel that allows high-speed simulation.**

SystemC Data types

- SystemC supports:
  - all C/C++ native types
  - plus specific SystemC types

- SystemC types:
  - Types for systems modeling
  - 2 values (‘0’,’1’)
  - 4 values (‘0’,’1’,’Z’,’X’)
  - Arbitrary size integer (Signed/Unsigned)
  - Fixed point types

SC_Logic, SC_int types

SC_Logic: More general than ***bool***, 4 values :

('0' (false), '1' (true), 'X' (undefined) , 'Z'(high-impedance))

Assignment like ***bool***

my_logic = '0';
my_logic = 'Z';

Operators like bool but Simulation time bigger than ***bool***

Declaration

sc_logic my_logic;

Fixed precision Integer: Used when arithmetic operations need fixed size arithmetic operands

- INT can be converted in UINT and vice-versa
- 1-64 bits integer in SystemC

sc_int<n> -- signed integer with n-bits
sc_uint<n> -- unsigned integer with n-bits

Other SystemC types

Bit Vector

- ***sc_bv<n>***
  - 2-valued vector (0/1)
  - Not used in arithmetics operations
  - Faster simulation than ***sc_lv***

Logic Vector

- ***sc_lv<n>***
  - Vector of the 4-valued sc_logic type

Assignment operator (=)

- my_vector = “XZ01”
- Conversion between vector and integer (int or uint)
- Assignment between ***sc_bv*** and ***sc_lv***
- Additional Operators:

Reduction --	***and_reduction()***	***or_reduction()***	***xor_ reduction()***
Conversion --	***to_string()***		

SystemC Data types

Type	Description
sc_logic	Simple bit with 4 values(0/1/X/Z)
sc_int	Signed Integer from 1-64 bits
sc_uint	Unsigned Integer from 1-64 bits
sc_bigint	Arbitrary size signed integer
sc_biguint	Arbitrary size unsigned integer
sc_bv	Arbitrary size 2-values vector
sc_lv	Arbitrary size 4-values vector
sc_fixed	templated signed fixed point
sc_ufixed	templated unsigned fixed point
sc_fix	untemplated signed fixed point
sc_ufix	untemplated unsigned fixed point

SystemC types

Operators of fixed precision types

Bitwise	~	&	|	^	>>	<<			
Arithmetics	+	-	*	/	%				
Assignement	=	+=	-=	*=	/=	%=	&=	|=	^=
Equality	==	!=							
Relational	<	<=	>	> =					
Auto-Inc/Dec	++	--							
Bit selection	[*x*]		*e.g.* mybit = myint[7]						
Part select	range()		*e.g.* myrange = myint.range(7,4)						
Concatenation	(,)		*e.g.* intc = (inta, intb);						

Usage of SystemC types

```
sc_bit y, sc_bv<8> x;
y = x[6];

sc_bv<16> x, sc_bv<8> y;
y = x.range(0,7);

sc_bv<64> databus, sc_logic result;
result = databus.or_reduce();

sc_lv<32> bus2;
cout << "bus = " << bus2.to_string();
```

SystemC Specific Features

- Modules:
  - **A class called a module: A hierarchical entity that can have other modules or processes contained in it.**
- Ports:
  - **Modules have ports through which they connect to other modules.**
  - **Single-direction and bidirectional ports.**
- Signals:
  - **SystemC supports resolved and unresolved signals.**
- Processes:
  - **used to describe functionality.**
  - **contained inside modules.**

Modules

The basic building block in SystemC to partition a design.

- Modules are similar to „*entity*“ in VHDL
- Modules allow designers to hide internal data representation and algorithms from other modules.

Declaration

- Using the macro SC_MODULE

  SC_MODULE(*modulename***) {**

- Using typical C++ struct or class declaration:

  struct *modulename* **: sc_module {**

Elements:

Ports, local signals, local data, other modules, processes, and constructors

SystemC Constructor

Constructor: Each module should include a constructor that identifies processes as methods using the SC_METHOD macro.

SC_METHOD (funct) ; Identifies the function or process funct

Methods are called similar to C++ as:

function_type module_name::function_name(data_type var_name) { … }

- SC_METHOD process is triggered by events and executes all the statements in it before returning control to the SystemC kernel.
- A Method needs to be made sensitive to some internal or external signal. e.g. sensitive_pos << clock *or* sensitive_neg << clock
- Process and threads get executed automatically in the constrcutor even if an event in sensitivity list does not occur. To prevent this un-intentional execution, *dont_initialize()* function is used.

SystemC Module

```
SC_MODULE(module_name) {
// Ports declaration
// Signals declaration
// Module constructor : SC_CTOR
// Process constructors and sensibility list
//          SC_METHOD
// Sub-Modules creation and port mappings
// Signals initialization
}
```



Signals and Ports

Ports of a module are the external interfaces that pass information to and from a module.

```
sc_inout<data_type>  port_name;
```

- Create an input-output port of 'data_type' with name 'port_name'.
- **sc_in** and **sc_out** create input and output ports respectively.

Signals are used to connect module ports allowing modules to communicate.

```
sc_signal<data_type>  sig_name ;
```

- Create a signal of type 'data_type' and name it 'sig_name'.
- hardware module has its own *input* and *output ports* to which these signals are mapped or bound.

For example:

```
in_tmp = in.read( );
out.write(out_temp);
```

2-to-1 Mux Modules

Module constructor – SC_CTOR is Similar to an "*architecture*" in VHDL

```
SC_MODULE( Mux21 ) {
   sc_in< sc_uint<8> >   in1;
   sc_in< sc_uint<8> >   in2;
   sc_in< bool >         selection;
   sc_out< sc_uint<8> >  out;

   void MuxImplement( void );
   SC_CTOR( Mux21 ) {
      SC_METHOD( MuxImplement );
         sensitive << selection;
         sensitive << in1;
         sensitive << in2;
   }
}
```

SystemC Counter Code

```
struct counter : sc_module {    // the counter module
    sc_inout<int> in; // the input/output port of int type
    sc_in<bool> clk; // Boolean input port for clock
    void counter_fn(); // counter module function
    SC_CTOR( counter ) {
            SC_METHOD( counter_fn ); // declare the counter_fn as a method
            dont_initialize(); // don't run it at first execution
            sensitive_pos << clk; // make it sensitive to +ve clock edge
    }
}

// software block that check/reset the counter value, part of sc_main
void check_for_10(int *counted) {
            if (*counted == 10) {
               printf("Max count (10) reached ... Reset count to Zero\n");
               *counted = 0;
            }
}
```

BCD Counter Example Main Code

```
void check_for_10(int *counted);
 int sc_main(int argc, char *argv[]) {
    sc_signal<int> counting; // the signal for the counting variable
    sc_clock clock("clock",20, 0.5); // clock period = 20 duty cycle = 50%
    int counted; // internal variable, to store the value in counting signal
    counting.write(0); // reset the counting signal to zero at start
    counter COUNT("counter"); // call counter module
    COUNT.in(counting); // map the ports by name
    COUNT.clk(clock);     // map the ports by name
    for (unsigned char i = 0; i < 21; i++) {
            counted = counting.read(); // copy the signal onto the variable
            check_for_10(&counted); // call the software block & check for 10
            counting.write(counted);     // copy the variable onto the signal
            sc_start(20);                // run the clock for one period
    } return 0;
}
```

Counter Main Code with Tracing

```
int sc_main(int argc, char *argv[]) {
    sc_signal<int> counting; // the signal for the counting variable
    sc_clock clock("clock", 20, 0.5); // clock; time period = 20 duty cycle = 50%
    int counted; // internal variable, to stores the value in counting signal
                    // create the trace- file by the name of "counter_tracefile.vcd“
   sc_trace_file *tf = sc_create_vcd_trace_file("counter_tracefile");
                    // trace the clock and the counting signals
    sc_trace(tf, clock.signal(), "clock");
    sc_trace(tf, counting, "counting");
    counting.write(0); // reset the counting signal to zero at start
    counter COUNT("counter"); // call counter module. COUNT is just a temp var
    COUNT.in(counting); // map the ports by name
    COUNT.clk(clock);     // map the ports by name
    for (unsigned char i = 0; i < 21; i++) {
            .....
    }
    sc_close_vcd_trace_file(tf); // close the tracefile
 return 0;
}
```

SystemC Counter Module

```
#include "systemc.h"
#define COUNTER
struct counter : sc_module {    // the counter module
    sc_inout<int> in; // the input/output port of int type
    sc_in<bool> clk; // Boolean input port for clock
    void counter_fn(); // counter module function
    SC_CTOR( counter ) { // counter constructor
      SC_METHOD( counter_fn ); // declare the counter_fn as a method
      dont_initialize(); // don't run it at first execution
      sensitive_pos << clk; // make it sensitive to +ve clock edge
    }
} ;
 void counter :: counter_fn() {
    in.write(in.read() + 1);
    printf("in=%d\n", in.read());
}
```

Module Instantiation

- Instantiate module

  Module_type Inst_module (“*label*”);

- Instantiate module as a pointer

  *Module_type *pInst_module*;

  // Instantiate at the module constructor SC_CTOR

  pInst_module = new *module_type* (“*label*”);

  Inst_module.a(s);
  Inst_module.b(c);
  Inst_module.q(q);

  pInst_module -> a(s);
  pInst_module -> b(c);
  pInst_module -> q(q);

Sub-module Connections

Signals

```
sc_signal<type > q, s, c;
```

- **Positional Connection**
- **Named Connection**



Named and Positional Connections

```
SC_MODULE(filter) {
  // Sub-modules: "components
  sample *s1;
  coeff  *c1;
  mult   *m1;
  sc_signal<sc_uint <32> > q,s,c;
   // Constructor :"architecture"
   SC_CTOR(filter) {
   //Sub-modules instantiation/mapping
     s1 = new sample ("s1");
     s1->din(q);    // named mapping
     s1->dout(s);
     c1 = new coeff("c1");
     c1->out(c);    // named mapping
     m1 = new mult ("m1");
     (*m1)(s, c, q)//positional mapping
  }
}
```



Communication and Synchronization

- SystemC 2.0 and higher has general-purpose
  - Channel
    - A mechanism for communication and synchronization
    - They implement one or more *interfaces*
  - Interface
    - Specify a set of access methods to the channel

      But it does not implement those methods
  - Event
    - Flexible, low-level synchronization primitive
    - Used to construct other forms of synchronization

Communication and Synchronization



Interfaces

- Interface is purely functional and does not provide the implementation of the methods.
  - Interface only provides the method's signature.
- Interfaces are bound to ports.
  - They define what can be done through a particular port.



- The implementation is done inside a channel.

Channels

- Channel implements an interface
  - It must implement all of its defined methods.
- Channel are used for communication between processes inside of modules and between modules.
- Inside of a module a process may directly access a channel.
- If a channel is connected to a port of a module, the process accesses the channel through the port.



Channels


Module
Module Instance
Channel
Module Instance
Ports
Channel
Process
Channel
Process
Process
Module body
Module instances
concurrent processes

Channels

Two types of Channels: Primitive and Hierarchical

- Primitive Channels:
  - They have no visible structure and no processes
  - Theye cannot directly access other primitive channels.
    - sc_signal
    - sc_signal_rv
    - sc_fifo
    - sc_mutex
    - sc_semaphore
    - sc_buffer
- Hierarchical Channels:
  - These are modules themselves,
  - may contain processes, other modules etc.
  - may directly access other hierarchical channels.

Channel Usage

Use Primitive Channels:

- when you need to use the request-update semantics.
- when channels are atomic and cannot reasonably be chopped into smaller pieces.
- when speed is absolutely crucial.
  - Using primitive channels can often reduce the number of delta cycles.
- when it doesn't make any sense i.e. trying to build a channel out of processes and other channels such as a semaphore or a mutex.

Use Hierarchical Channels:

- when you would want to be able to explore the underlying structure,
- when channels contain processes or ports,
- when channels contain other channels.

A Communication Modeling FIFO Example



Problem definition: FIFO communication channel with blocking read and write operation

Source available in SystemC installation, under "examples\systemc" subdirectory

Processes

Processes are functions identified to the SystemC kernel and called if a signal of the sensitivity list changes.

- Processes implement the funcionality of modules.
- Similar to C++ functions or methods

Three types of Processes: Methods, Threads and Cthreads

- Methods : When activated, executes and returns
  SC_METHOD(process_name)
- Threads: can be suspended and reactivated
  - wait( ) -> suspends
  - one sensitivity list event -> activates

  SC_THREAD(process_name)
- Cthreads: are activated by the clock pulse
  SC_CTHREAD(process_name, clock value);

Processes

Type	SC_METHOD	SC_THREAD	SC_CTHREAD
Activates Exec.	Event in sensit. list	Event in sensit. List	Clock pulse
Suspends Exec.	NO	YES	YES
Infinite Loop	NO	YES	YES
suspended/ reactivated by	N.D.	wait()	wait() wait_until()

Constructor & Sensibility definition	SC_METHOD(*call_back*);
	sensitive(*signals*);
	sensitive_pos(*signals*);
	sensitive_neg(*signals*);
		SC_THREAD(*call_back*);
		sensitive(*signals*);
		sensitive_pos(*signals*);
		sensitive_neg(*signals*);
			SC_CTHREAD(
			call_back,
			clock.pos());
			SC_CTHREAD(
			call_back,
			clock.neg());

Sensitivity List of a Process

- sensitive with the ( ) operator
  Takes a single port or signal as argument
  ```
  sensitive(s1);sensitive(s2);sensitive(s3)
  ```
- sensitive with the stream notation
  Takes an arbitrary number of arguments
  ```
  sensitive << s1 << s2 << s3;
  ```
- sensitive_pos with either ( ) or << operator
  Defines sensitivity to positive edge of Boolean signal or clock
  ```
  sensitive_pos << clk;
  ```
- sensitive_neg with either ( ) or << operator
  Defines sensitivity to negative edge of Boolean signal or clock
  ```
  sensitive_neg << clk;
  ```

Multiple Process Example

```
SC_MODULE(ram) {
  sc_in<int> addr;
  sc_in<int> datain;
  sc_in<bool> rwb;
  sc_out<int> dout;
  int memdata[64];
      // local memory storage
  int i;
  void ramread(); // process-1
  void ramwrite();// process-2
  SC_CTOR(ram){
    SC_METHOD(ramread);
    sensitive << addr << rwb;
    SC_METHOD(ramwrite);
    sensitive << addr << datain << rwb;
    for (i=0; i++; i<64) {
      memdata[i] = 0;
  } }
};
```

Thread Process and wait() function

- *wait( )* may be used in both SC_THREAD and SC_CTHREAD processes but not in SC_METHOD process block
- *wait( )* suspends execution of the process until the process is invoked again
- *wait(<pos_int>)* may be used to wait for a certain number of cycles (SC_CTHREAD only)

In Synchronous process (SC_CTHREAD)

- Statements before the *wait( )* are executed in one cycle
- Statements after the *wait( )* executed in the next cycle

In Asynchronous process (SC_THREAD)

- Statements before the *wait( )* are executed in the last event
- Statements after the *wait( )* are executed in the next event

Thread Process and wait() function

```
void do_count() {
  while(1) {
    if(reset) {
      value = 0;
    }
    else if (count) {
      value++;
      q.write(value);
    }
    wait(); // wait till next event !
  }
}
```

Example Code

```
void wait_example:: my_thread_process(void)
{
        wait(10, SC_NS);
        cout << "Now at " << sc_time_stamp() << endl;
        sc_time t_DELAY(2, SC_MS);
        t_DELAY *= 2;
        cout << "Delaying " << t_DELAY<< endl;
        wait(t_DELAY);
        cout << "Now at " << sc_time_stamp()<< endl;
}
```

OUTPUT

Thread Example

```
SC_MODULE(my_module) {
  sc_in<bool> id;
  sc_in<bool> clock;
  sc_in<sc_uint<3> > in_a;
  sc_in<sc_uint<3> > in_b;
  sc_out<sc_uint<3> >
                      out_c;
  void my_thread();

  SC_CTOR(my_module){
  SC_THREAD(my_thread);
  sensitive << clock.pos();
  }
};
```

Thread Implementation

```
//my_module.cpp
void my_module::
                my_thread(){
while(true){
 if (id.read())
  out_c.write(in_a.read());
 else
  out_c.write(in_b.read());
 wait();
}
};
```

CThread

- Almost identical to **SC_THREAD**, but implements "clocked threads"
- Sensitive only to one edge of one and only one clock
- It is not triggered if inputs other than the clock change

- Models the behavior of unregistered inputs and registered outputs
- Useful for high level simulations, where the clock is used as the only synchronization device
- Adds ***wait_until( )*** and ***watching( )*** semantics for easy deployment.

Counter Example

```
SC_MODULE(countsub)
{
  sc_in<double>  in1;
  sc_in<double>  in2;
  sc_out<double> sum;
  sc_out<double> diff;
  sc_in<bool>    clk;
  void addsub();

  // Constructor:
  SC_CTOR(countsub)
  {
// declare addsub as SC_METHOD
     SC_METHOD(addsub);
     // make it sensitive to
     // positive clock
     sensitive_pos << clk;
  }
};
```




```
// addsub method
void countsub::addsub()
{
  double a;
  double b;
  a = in1.read();
  b = in2.read();
  sum.write(a+b);
  diff.write(a-b);
};
```

sc_main()

The top level is a special function called `sc_main`.

- It is in a file named main.cpp or main.c
- `sc_main()` is called by SystemC and is the entry point for your code.
- The execution of `sc_main()` until the `sc_start()` function is called.

```
int sc_main (int argc, char *argv []) {
    // body of function
    sc_start(arg) ;
    return 0 ;
}
```

- `sc_start(arg)` has an optional argument:
  It specifies the number of time units to simulate.
  If it is a null argument the simulation will run forever.

Clocks

- Special object
- How to create ?

  sc_clock ***clock_name*** ("***clock_label***", ***period***, ***duty_ratio***, ***offset***, ***initial_value***);

- Clock connection

  f1.clk(clk_signal); //where f1 is a module

- Clock example:



sc_time

sc_time data type to measure time. Time is expressed in two parts: a numeric magnitude and a time unit e.g. SC_MS, SC_NS, SC_PS, SC_SEC, etc.

```
sc_time t(20, SC_NS);
  //var t of type sc_time with value of 20ns
```

More Examples:

sc_time t_PERIOD(5, SC_NS) ;

sc_time t_TIMEOUT (100, SC_MS) ;

sc_time t_MEASURE, t_CURRENT, t_LAST_CLOCK;

t_MEASURE = (t_CURRENT-t_LAST_CLOCK) ;

if (t_MEASURE > t_HOLD) { error ("Setup violated") }

Time representation in SystemC

Set Time Resolution:

sc_set_time_resolution (10, SC_PS) ;

- Any time value smaller than this is rounded off
- default; 1 Peco-Second

sc_time t2(3.1416, SC_NS); // **t**2 gets 3140 PSEC

To Control Simulation:

sc_start( ) ;

sc_stop( ) ;

To Report Time Information:

sc_time_stamp( ) // returns the current simulation time

cout << sc_time_stamp( ) << endl ;

sc_simulation_time( )

Returns a value of type double with the current simulation time in the current default time unit

sc_event

Event

- **Something that happens at a specific point in time.**
- **Has no value or duration**

sc_event:

- **A class to model an event**
  - Can be triggered and caught.

Important

(the source of a few coding errors):

- **Events have no duration → you must be watching to catch it**
  - If an event occurs, and no processes are waiting to catch it, the event goes unnoticed.

sc_event

You can perform only two actions with an sc_event:

- wait for it
  - `wait(ev1)`
  - `SC_THREAD(my_thread_proc);`
  - `sensitive << ev_1; // or`
  - `sensitive(ev_1)`
- cause it to occur

  `notify(ev1)`

Common misunderstanding:

- `if (event1) do_something`
  - Events have no value
  - You can test a Boolean that is set by the process that caused an event;
  - However, it is problematic to clear it properly.

notify( )

To Trigger an Event:

```
event_name.notify(args);
event_name.notify_delayed(args);
notify(args, event_name);
```

Immediate Notification:

causes processes which are sensitive to the event to be made ready to run in the current evaluate phase of the ***current*** **delta-cycle**.

Delayed Notification:

causes processes which are sensitive to the event to be made ready to run in the evaluate phase of the ***next*** **delta-cycle**.

Timed Notification:

causes processes which are sensitive to the event to be made ready to run at a ***specified time*** in the future.

notify( ) Examples

```
sc_event   my_event ; // event
sc_time    t_zero (0, SC_NS) ; // variable t_zero of type sc_time
sc_time    t(10, SC_MS) ; // variable t of type sc_time
```

Immediate

```
my_event.notify();
notify(my_event); // current delta cycle
```

Delayed

```
my_event.notify_delayed();
my_event.notify(t_zero);
notify(t_zero, my_event); // next delta cycle
```

Timed

```
my_event.notify(t);
notify(t, my_event);
my_event.notify_delayed(t); // 10 ms delay
```

cancel ( )

Cancels pending notifications for an event.

- It is supported for delayed and timed notifications.
- not supported for immediate notifications.

Given:

```
sc_event a, b, c;   // events
sc_time  t_zero (0,SC_NS);   // variable t_zero of type sc_time
sc_time  t(10, SC_MS);   // variable t of type sc_time
…
a.notify();   // current delta cycle
notify(t_zero, b);   // next delta cycle
notify(t, c);   // 10 ms delay
```

Cancel of Event Notification:

```
a.cancel();   // Error! Can't cancel immediate notification
b.cancel();   // cancel notification on event b
c.cancel();   // cancel notification on event c
```

Problem with events

```
SC_MODULE(missing_event) {
    SC_CTOR(missing_event) {
        SC_THREAD(B_thread); // ordered
        SC_THREAD(A_thread); // to cause
        SC_THREAD(C_thread); // problems
    }
     void A_thread( ) {
            a_event.notify( ) ;  // immediate!
            cout << "A sent a_event!" << endl;
     }
     void B_thread() {
            wait(a_event) ;
            cout << "B got a_event!" << endl;
     }
     void C_thread() {
            wait(a_event) ;
            cout << "C got a_event!" << endl;
     }
  sc_event  a_event;
}
```

If wait(a_event) is issued after the immediate notification
a_event.**notify( )**
Then B_thread and C_thread can wait for ever.
Unless a_avent is issued again.

Properly Ordered Events

```
SC_MODULE(ordered_events) {
   SC_CTOR(ordered_events) {
   SC_THREAD(B_thread);
   SC_THREAD(A_thread);
   SC_THREAD(C_thread);
    // ordered to cause problems
   }

void A_thread() {
while (true) {
a_event.notify(SC_ZERO_TIME);
cout << "A sent a_event!" << endl;
wait(c_event);
cout << "A got c_event!" << endl;
}  // endwhile
}
```

```
void B_thread() {
while (true) {
b_event.notify(SC_ZERO_TIME);
cout << "B sent b_event!" << endl;
wait(a_event);
cout << "B got a_event!" << endl;
}  // endwhile
}
void C_thread() {
while (true) {
c_event.notify(SC_ZERO_TIME);
cout << "C sent c_event!" << endl;
wait(b_event);
cout << "C got b_event!" << endl;
}  // endwhile
}
sc_event a_event, b_event, c_event;
} ;
```

Time & Execution Interaction

```
Process_A() {
  //@ t0
  stmtA1;
  stmtA2;
  wait(t1);
  stmtA3;
  stmtA4;
  wait(t2);a
  stmtA5;
  stmtA6;
  wait(t3);
}
```

```
Process_B() {
  //@ t0
  stmtB1;
  stmtB2;
  wait(t1);
  stmtB3;
  stmtB4;
  wait(t2);
  stmtB5;
  stmtB6;
  wait(t3);
}
```

```
Process_C() {
  //@ t0
  stmtC1;
  stmtC2;
  wait(t1);
  stmtC3;
  stmtC4;
  wait(t2);
  stmtC5;
  stmtC6;
  wait(t3);
}
```

```
Process_D() {
  //@ t0
  stmtD1;
  stmtD2;
  wait(t1);
  stmtD3;
  wait(
    SC_ZERO_TIME);
  stmtD4;
  wait(t3);
}
```

Simulated Execution Activity



wait( ) and watching( )

Legacy SystemC code for Clocked Thread

wait(*N*); // delay N clock edges

wait_until (*delay_expr*); // until expr true @ clock

Same as

```
For (i=0; i!=N; i++)
        wait( ) ;                    //similar as wait(N)
do wait ( ) while (!expr) ;  // same as
                                     // wait_until(delay_expr)
```

Previous versions of SystemC also included other constructs to watch signals such as **watching(),**

Traffic Light Controller

Highway

- **Normally has a green light.**

Sensor:

- **A car on the East-West side road triggers the sensor**
  - The highway light: green => yellow => red,
  - Side road light: red => green.



SystemC Model:

- **Uses two different time delays:**
  - green to yellow delay >= yellow to red delay

(to represent the way that a real traffic light works).

Traffic Controller Example

```
// traff.h
#include "systemc.h"

SC_MODULE(traff) {

  // input ports
  sc_in<bool> roadsensor;
  sc_in<bool> clock;

  // output ports
  sc_out<bool> NSred;
  sc_out<bool> NSyellow;
  sc_out<bool> NSgreen;
  sc_out<bool> EWred;
  sc_out<bool> EWyellow;
  sc_out<bool> EWgreen;
  void control_lights();
  int i;
```

```
  // Constructor
  SC_CTOR(traff) {
    SC_THREAD(control_lights);
   // Thread
      sensitive << roadsensor;
      sensitive << clock.pos();
  }
};
```

Traffic Controller Example

```
// traff.cpp
#include "traff.h"
void traff::control_lights() {
  NSred = false;
  NSyellow = false;
  NSgreen = true;
  EWred = true;
  EWyellow = false;
  EWgreen = false;
  while (true) {
    while (roadsensor == false)
        wait();
  NSgreen = false;// road sensor triggered
  NSyellow = true; // set NS to yellow
  NSred = false;
  for (i=0; i<5; i++)
    wait();
  NSgreen = false; // yellow interval over
  NSyellow = false; // set NS to red
  NSred = true; // set EW to green
  EWgreen = true;
  EWyellow = false;
  EWred = false;
  for (i= 0; i<50; i++)
    wait();
```

```
    NSgreen = false; // times up for EW green
    NSyellow = false; // set EW to yellow
    NSred = true;
    EWgreen = false;
    EWyellow = true;
    EWred = false;
    for (i=0; i<5; i++)
              // times up for EW yellow
      wait();
    NSgreen = true; // set EW to red
    NSyellow = false; // set NS to green
    NSred = false;
    EWgreen = false;
    EWyellow = false;
    EWred = true;
    for (i=0; i<50; i++) // wait one more long
      wait(); // interval before allowing
              // a sensor again
    }
}
```

References

- System Design with SystemC, by T. Grotker, S. Liao, G. Martin and S. Swan, Kluwer Academic 2002.

- A SystemC Primer, by J. Bhasker Second Edition 2004, 2002 PDF exists.

- SystemC: From the Ground Up, by D.C. Black, J. Donovan, B. Bunton and A. Keist 2nd edition 2010.

JPEG Compression/Decompression using SystemC

Overview

- Introduction to JPEG Coding and Decoding
- Hardware-Software Partitioning
- FDCT and IDCT HW module for 8 x 8 Block
- JPEG Implementation

Introductory Articles on JPEG Compression and SystemC tutorial documents available at the course webpage. Digital Image Processing by Gonzolez and Wood Chapter 6

JPEG-based Encoding

Four Stages of JPEG Compression

- Preprocessing and dividing an image into 8 x 8 blocks

  Level-shift, for 8-bit gray scale images, subtract 128 from each pixel i.e. pixel[i] = pixel[i] – 128 ;
- DCT, Discrete Cosine Transform of 8 x 8 image blocks.
- Quantization
- ZigZag
- Entropy Encoding either of:
  - Huffman coding
  - Variable Length Coding

JPEG Encoding and Decoding





DCT: Discrete Cosine Transform

Mathematical definitions of 8 x 8 DCT and 8 x 8 IDCT respectively.

$$F(u,v) = \tfrac{1}{4} C(u)\, C(v) \left[\sum_{x=0}^{7} \sum_{y=0}^{7} f(x,y) * \cos((2x+1)u\pi)/16 * \cos((2y+1)v\pi/16) \right]$$

$$f(x,y) = \tfrac{1}{4} \left[\sum_{u=0}^{7} \sum_{v=0}^{7} C(u)\, C(v) F(u,v) * \cos((2x+1)u\pi)/16 * \cos((2y+1)v\pi/16) \right]$$

where $C(u), C(v) = 1/\sqrt{2}$ for $u,v = 0$

$C(u), C(v) = 1$ otherwise

$F(u,v)$ is the Discrete Cosine Transform of 8 x 8 block

$f(x,y)$ is the Inverse Discrete Cosine Transform

Why DCT instead of DFT

DCT is similar to DFT with many advantages

- DCT coefficients are purely real
- Near-optimal for energy compaction
- DCT computation is efficient due to faster algorithms
- Hardware solutions available that do not need multipliers

DCT is extensively used in image compression standards including, JPEG, MPEG-1, MPEG-2, MPEG-4, etc.

$$\begin{pmatrix} 52 & 55 & 61 & 66 & 70 & 61 & 64 & 73 \\ 63 & 59 & 66 & 90 & 109 & 85 & 69 & 72 \\ 62 & 59 & 68 & 113 & 144 & 104 & 66 & 73 \\ 63 & 58 & 71 & 122 & 154 & 106 & 70 & 69 \\ 67 & 61 & 68 & 104 & 126 & 88 & 68 & 70 \\ 79 & 65 & 60 & 70 & 77 & 68 & 58 & 75 \\ 85 & 71 & 64 & 59 & 55 & 58 & 65 & 83 \\ 87 & 79 & 69 & 68 & 65 & 65 & 78 & 94 \end{pmatrix} \quad \text{DCT} \Rightarrow \quad \begin{pmatrix} -415 & -29 & -62 & 25 & 55 & -20 & -1 & 3 \\ 7 & -21 & -62 & 9 & 11 & -7 & -6 & 6 \\ -46 & 8 & 77 & -25 & -30 & 10 & 7 & -5 \\ -50 & 13 & 35 & -15 & -9 & 6 & 0 & 3 \\ 11 & -8 & -13 & -2 & -1 & 1 & -4 & 1 \\ -10 & 1 & 3 & -3 & -1 & 0 & 2 & -1 \\ -4 & -1 & 2 & -1 & 0 & -3 & 1 & -2 \\ -1 & -1 & -1 & -2 & -3 & -1 & 0 & -1 \end{pmatrix}$$

Quantization

The 8x8 block of DCT transformed values is divided by a quantization value for each block entry.

$F_{quantized}(u,v) = F(u,v) / Quantization\_Table(x,y)$

Quantization table :

16	11	10	16	24	40	51	61
12	12	14	19	26	58	60	55
14	13	16	24	40	57	69	56
14	17	22	29	51	87	80	62
18	22	37	56	68	109	103	77
24	35	55	64	81	104	113	92
49	64	78	87	103	121	120	101
72	92	95	98	112	100	103	99

Zig-Zag

It takes the quantized 8x8 block and orders it in a ‘Zig-Zag’ sequence, resulting in a 1-D array of 64 entries,

- This process place low-frequency coefficients (larger values) before the high-frequency ones (nearly zero).
- One can ignore any continuous zeros at the end of block
- Insert a (EOB) at the end of each 8x8 block encoding.



Quantization and ZigZag

$$\begin{pmatrix} -415 & -29 & -62 & 25 & 55 & -20 & -1 & 3 \\ 7 & -21 & -62 & 9 & 11 & -7 & -6 & 6 \\ -46 & 8 & 77 & -25 & -30 & 10 & 7 & -5 \\ -50 & 13 & 35 & -15 & -9 & 6 & 0 & 3 \\ 11 & -8 & -13 & -2 & -1 & 1 & -4 & 1 \\ -10 & 1 & 3 & -3 & -1 & 0 & 2 & -1 \\ -4 & -1 & 2 & -1 & 0 & -3 & 1 & -2 \\ -1 & -1 & -1 & -2 & -3 & -1 & 0 & -1 \end{pmatrix} \div \begin{pmatrix} 16 & 11 & 10 & 16 & 24 & 40 & 51 & 61 \\ 12 & 12 & 14 & 19 & 26 & 58 & 60 & 55 \\ 14 & 13 & 16 & 24 & 40 & 57 & 69 & 56 \\ 14 & 17 & 22 & 29 & 51 & 87 & 80 & 62 \\ 18 & 22 & 37 & 56 & 68 & 109 & 103 & 77 \\ 24 & 35 & 55 & 64 & 81 & 104 & 113 & 92 \\ 49 & 64 & 78 & 87 & 103 & 121 & 120 & 101 \\ 72 & 92 & 95 & 98 & 112 & 100 & 103 & 99 \end{pmatrix}$$

$$\begin{pmatrix} -26 & -3 & -6 & 2 & 2 & 0 & 0 & 0 \\ 1 & -2 & -4 & 0 & 0 & 0 & 0 & 0 \\ -3 & 1 & 5 & -1 & -1 & 0 & 0 & 0 \\ -4 & 1 & 2 & -1 & 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \end{pmatrix}$$

Zig-Zag

[-26 -3 1 -3 -2 -6 2 – 4 1 -4 1 1 5 0 2
0 0 -1 2 0 0 0 0 0 -1 -1 EOB]

FDCT SC_Module

```
struct fdct : sc_module {
  sc_out<double> out64[8][8]; // the dc transformed 8x8 block
  sc_in<double> fcosine[8][8]; // cosine table input
  sc_in<FILE *> sc_input; // input file pointer port
  sc_in<bool> clk; // clock signal
  char input_data[8][8]; // the data read from the input file
  void read_data( void ); // read the 8x8 block
  void calculate_dct( void ); // perform dc transform
  // define fdct as a constructor
  SC_CTOR( fdct ) {
  // read_data method sensitive to +ve & calculate_dct sensitive to
  // -ve clock edge, entire read and dct will take one clock cycle
       SC_METHOD( read_data ); // define read_data as a method
       dont_initialize();
       sensitive << clk.pos;
       SC_METHOD( calculate_dct );
       dont_initialize();
       sensitive << clk.neg;
  }
};
```

DCT Module

```
#include "fdct.h"
void fdct :: calculate_dct( void ) {
unsigned char  u, v, x, y;
double         temp;
   for (u = 0; u < 8; u++) // do forward discrete cosine transform
     for (v = 0; v < 8; v++) {  temp = 0.0;
        for (x = 0; x < 8; x++)
        for (y = 0; y < 8; y++)
          temp += input_data[x][y] * fcosine[x][u].read() *
                fcosine[y][v].read();
        if ((u == 0) && (v == 0)) temp /= 8.0;
        else if (((u == 0) && (v != 0)) || ((u != 0) && (v == 0)))
          temp /= (4.0*sqrt(2.0)); else temp /= 4.0;
        out64[u][v].write(temp);
}  }
void fdct :: read_data( void ) { // read the 8*8 block
   fread(input_data, 1, 64, sc_input.read());
   // shift from range [0, 2^8 - 1] to [2^(8-1), 2^(8-1) - 1]
   for (unsigned char uv = 0; uv < 64; uv++)
        input_data[uv/8][uv%8] -= (char) (pow(2,8-1));
}
```

DCT Module Structures

```
#define PI 3.14159265358979323846264338327795 // the value of PI
unsigned char quant[8][8] =           // quantization table
        {{16,11,10,16,24,40,51,61},
         {12,12,14,19,26,58,60,55},
         {14,13,16,24,40,57,69,56},
         {14,17,22,29,51,87,80,62},
         {18,22,37,56,68,109,103,77},
         {24,35,55,64,81,104,113,92},
         {49,64,78,87,103,121,120,101},
         {72,92,95,98,112,100,103,99}};
unsigned char zigzag_tbl[64]={        // zigzag table
        0,1,5,6,14,15,27,28,
        2,4,7,13,16,26,29,42,
        3,8,12,17,25,30,41,43,
        9,11,18,24,31,40,44,53,
        10,19,23,32,39,45,52,54,
        20,22,33,38,46,51,55,60,
        21,34,37,47,50,56,59,61,
        35,36,48,49,57,58,62,63};
signed char MARKER = 127; // end of block marker
```

Functions: Read File Header

```
#define rnd(x) (((x)>=0)?((signed char)((signed char)((x)+1.5)-
  1)):((signed char)((signed char)((x)-1.5)+1)))
#define rnd2(x) (((x)>=0)?((short int)((short int)((x)+1.5)-
  1)):((short int)((short int)((x)-1.5)+1)))

// read the header of the bitmap and write it to the output file

void write_read_header(FILE *in, FILE *out) {
  unsigned char temp[60]; // temporary array of 60 characters,
         // which is enough for the bitmap header: 54 bytes
  printf("\nInput Header read and written to the output file");
  fread(temp, 1, 54, in); // read 54 bytes and store them in temp
  fwrite(temp, 1, 54, out); // write 54 bytes to the output file
  printf("......Done\n");
  printf("Image is a %d bit Image. Press Enter to Continue\n>",
  temp[28]);
  getchar();
}
```

Functions: Cosine-table

```
// make the cosine table
void make_cosine_tbl(double cosine[8][8]);
void make_cosine_tbl(double cosine[8][8]) {
  printf("Creating the cosine table to be used in FDCT and
  IDCT");
  // calculate the cosine table as defined in the formula
  for (unsigned char i = 0; i < 8; i++)
       for (unsigned char j = 0; j < 8; j++)
            cosine[i][j] = cos((((2*i)+1)*j*PI)/16);
  printf("......Done\n");
}
```

Functions: ZigZag

```
// zigzag the quantized input data

void zigzag_quant(double data[8][8], FILE *output) {
   signed char to_write[8][8];
     // this is the rounded values, to be written to the file
   char last_non_zero_value = 0; // index to last non-zero in a block
    // zigzag data array & copy it to to_write, round the values
    // and find out the index to the last non-zero value in a block
   for (unsigned char i = 0; i < 64; i++) {
    to_write[zigzag_tbl[i]/8][zigzag_tbl[i]%8] =
        rnd(data[i/8][i%8] /   quant[i/8][i%8]);
        if (to_write[i/8][i%8] != 0) last_non_zero_value = i;
  }
   // write all values in the block including the last non-zero value
   for (unsigned char i = 0; i <= last_non_zero_value; i++)
       fwrite(&to_write[i/8][i%8], sizeof(signed char), 1, output);
         // write the end of block marker
   fwrite(&MARKER, sizeof(signed char), 1, output);
}
```

Functions: Main

```
#include "systemc.h"
#include "functions.h"
#include "fdct.h"
#include "idct.h"
#define NS *1e-9 // constant for clock signal is in nanoseconds
int sc_main(int argc, char *argv[]) {
  char choice;
  sc_signal<FILE *> sc_input; // input file pointer signal
  sc_signal<FILE *> sc_output; // output file pointer signal
  sc_signal<double> dct_data[8][8]; // signal to the dc transformed
  sc_signal<double> cosine_tbl[8][8]; // signal for cos-table values
  sc_signal<bool> clk1, clk2; // clock signal for FDCT and IDCT
  FILE *input, *output; // input and output file pointers
  double cosine[8][8]; // cosine table
  double data[8][8]; // data read from signals to be zigzagged
  if (argc == 4) {
     if (!(input = fopen(argv[1], "rb")))
         // some error occurred while trying to open the input file
     printf("\nSystemC JPEG-LAB:\nCannot Open File '%s'\n",argv[1]),
                                                      exit(1);
```

Functions - Main

```
write_read_header(input, output);
            // write the header read from the input file
make_cosine_tbl(cosine); // make the cosine table

// copy cosine and quantization tables onto corresponding signals
for (unsigned char i = 0; i < 8; i++)
     for (unsigned char j = 0; j < 8; j++)
            cosine_tbl[i][j].write(cosine[i][j]);

fdct FDCT("fdct"); // call the forward discrete transform module
// bind the ports
for (unsigned char i = 0; i < 8; i++)
     for (unsigned char j = 0; j < 8; j++) {
        FDCT.out64[i][j](dct_data[i][j]);
        FDCT.fcosine[i][j](cosine_tbl[i][j]);
     }
FDCT.clk(clk1);
FDCT.sc_input(sc_input);
```

Functions: Main

cont.

```
// we must use two different clocks. That will make sure that when
// we want to compress, we only compress and don't decompress it
  sc_start(SC_ZERO_TIME);     // initialize the clock
  if ((choice == 'c') || (choice == 'C')) { // for compression
       while (!(feof(input))) { // create the FDCT clock signal
         clk1.write(1);          // convert the clock to high
         sc_start(10, SC_NS);  // cycle high for 10 nanoseconds
         clk1.write(0);         // start the clock as low
         sc_start(10, SC_NS); //cycle low for 10 nanoseconds
              // read all the signals into the data variable
              // to use these values in a software block
           for (unsigned char i = 0; i < 8; i++)
             for (unsigned char j = 0; j < 8; j++)
                      data[i][j] = dct_data[i][j].read();
         zigzag_quant(data, output);
              // zigzag and quantize the read data
       }
   }
}
```