

MPT Mixture Models for Continuous Data

Daniel W. Heck




25.02.2020

MPT mixture modeling of continuous data

- 1] MPT-RT: Modeling response times with histograms
 - Heck & Erdfelder (2016)
- 2] GPT (generalized processing tree): Parametric modeling
 - Heck, Erdfelder, & Kieslich (2018)
- 3] RT-MPT: Serial-process model for response times
 - Klauer & Kellen (2018)

Mixture distribution

- All of the MPT extensions assume mixture distributions for discrete and continuous observations
 - A Latent RTs: Different processing branches of the MPT model result in different latent distributions $g_j(t)$
 - B Observed RTs: A mixture distribution, defined as $f(t) = \sum_j p_j g_j(t)$
 - C The mixture weights p_j are determined by the MPT structure (= branch probabilities)




MPT-RT: Modeling response times with histograms

- Heck, D. W., & Erdfelder, E. (2016). Extending multinomial processing tree models to measure the relative speed of cognitive processes. *Psychonomic Bulletin & Review*, 23, 1440–1465.
- Heck, D. W., & Erdfelder, E. (2017). Linking process and measurement models of recognition-based decisions. *Psychological Review*, 124, 442–471.

Histogram-Based Approach (Heck & Erdfelder, 2016)

- Categorize RTs into discrete bins (Yantis, Meyer, & Smith, 1991)
 - Example: “Very fast”, “fast”, “slow”, “very slow”
- State-specific distributions are modeled by the parameters L_{jb} :
 - L_{jb} = height of the histogram bins
 - L_{jb} = probability that state j results in observation in the b -th interval




Generalized Processing Tree Models

- Heck, D. W., Erdfelder, E., & Kieslich, P. J. (2018). Generalized processing tree models: Jointly modeling discrete and continuous variables. *Psychometrika*.

Generalized processing tree (GPT) models

- Main difference: Parametric assumptions for component distributions
- The type of distribution depends on continuous variable
 - RTs: log-normal, ex-Gaussian, ...
 - Mouse-tracking measures (see below): Normal distribution
 - Neuro-psychological measures: ...
- The distributions are described by parameters η
 - Normal distribution: mean and SD
 - ex-Gaussian: mean, SD, and mean of exponential




Benefits of the GPT Framework

- A Increased precision in estimating MPT parameters θ
- B Unidentifiable MPT models can become identifiable
- C Flexibility and simplicity

Higher precision of MPT-parameter estimates in GPTs


- The more distinct the latent distributions, the smaller the standard error
- Intuition: Continuous variables improve the “classification” which trials belong to which latent processing states
- 2HTM: “Fast RTs are due to detection, slow RTs are due to guessing”



Identifiability of GPT Models

Example: The feature comparison model of semantic categorization


- The theory assumes two different processes
- f = probability of Process 1 (similarity-based comparison)
- c_1 = accuracy of similarity-based comparison
- c_2 = accuracy of defining-feature comparison
- With discrete responses only, the (MPT) model is not identifiable
 - only 1 free category for 3 free parameters



Identifiability of GPT Models

Identifiability of the feature comparison model

- Solution: Assume Gaussian component distributions for continuous variable
 - MAD = maximum absolute deviation in mouse-tracking
- Order constraint for mean parameters: $\mu_c < \mu_d$
 - Interpretation: More direct trajectories/small MADs for similarity-based comparison
- With both discrete *and* continuous data, model is identifiable
 - The different component distribution allow to disentangle the two processes



GPTs as general-purpose measurement models

- GPTs can be specified as easily as MPTs
 - Implemented in the R package `gpt`
 - Currently under development: <https://github.com/danheck/gpt>
 - Define model in a text file similar to EQN
 - Type of latent distribution(s) defined within R (e.g., `latent="normal"`)

GPT version of 2-high-threshold model

```
# Tree ; Categ. ; MPT equation ; mean, SD (normal distr.)
target ; hit      ; d                ; m_d, sig
target ; hit      ; (1-d)*g          ; m_g, sig
target ; miss     ; (1-d)*(1-g)      ; m_g, sig

lure   ; cr       ; d                ; m_d, sig
lure   ; fa       ; (1-d)*g          ; m_g, sig
lure   ; cr       ; (1-d)*(1-g)      ; m_g, sig
```

Illustration of the gpt Package

```
library("gpt")  
# data from 2(response bias) x 2(memory strength) design:  
# labels: "o30s_cr" = 30% old items / strong memory / correct rejection  
head(heck2016, 3)
```

```
##      cat    rt  
## 1 o30s_cr 1123  
## 2 o30s_cr  671  
## 3 o30s_cr  728
```

```
modelfile <- "models/2htm_exgauss_2x2.txt"  
# first lines:
```

```
## # 30% old / strong memory  
## lure_s30;      o30s_cr   ; (1-dn_s)*(1-g30) ; mu,sig,lambda_g_new30  
## lure_s30;      o30s_cr   ; dn_s              ; mu,sig,lambda_dn_s  
## lure_s30;      o30s_fa   ; (1-dn_s)*g30      ; mu,sig,lambda_g_old30  
##  
## target_s30;    o30s_hit   ; do_s              ; mu,sig,lambda_do_s  
## target_s30;    o30s_hit   ; (1-do_s)*g30      ; mu,sig,lambda_g_old30  
## target_s30;    o30s_miss ; (1-do_s)*(1-g30) ; mu,sig,lambda_g_new30  
##  
## # 30% old / weak memory  
## lure_w30;      o30w_cr   ; (1-dn_w)*(1-g30) ; mu,sig,lambda_g_new30  
## lure_w30;      o30w_cr   ; dn_w              ; mu,sig,lambda_dn_w  
## lure_w30;      o30w_fa   ; (1-dn_w)*g30      ; mu,sig,lambda_g_old30
```

gpt Package: Model Fitting

```
fit <- gpt_fit(x = "cat",      # MPT category
              y = "rt",      # name of continuous variable(s)
              data = heck2016, # example data for 1 person
              file = modelfile, # GPT model file
              latent="exgauss", # family of latent RT distributions
              restrictions=list("dn_s=do_s", "dn_w=do_w"))
```

fit


##	Estimate	SE	CI.lower	CI.upper
## dn_s	0.741	0.027	0.687	0.794
## dn_w	0.477	0.033	0.411	0.542
## g30	0.189	0.031	0.128	0.250
## g70	0.261	0.038	0.186	0.335
## lambda_dn_s	172.252	18.159	136.661	207.844
## lambda_dn_w	191.781	34.625	123.916	259.645
## lambda_do_s	128.288	14.735	99.409	157.168
## lambda_do_w	151.728	18.462	115.543	187.912
## lambda_g_new30	311.612	30.782	251.280	371.944
## lambda_g_new70	460.442	36.205	389.481	531.402
## lambda_g_old30	531.220	86.535	361.615	700.824
## lambda_g_old70	517.069	74.575	370.906	663.233
## mu	633.839	5.369	623.316	644.362
## sig	49.194	4.040	41.277	57.112

```
test_fit(fit, bins = 4)$test      # Dzhaparidze-Nikulin statistic
```

##	statistic	df	p.value
## 1	82.50759	42	0.000189941


gpt Package: Model Fit

```
hist(fit)
```



gpt Package: Model Fit

```
plot(fit)  # cumulative densities
```



RT-MPT: Serial-process modeling of RTs

- Klauer, K. C., & Kellen, D. (2018). RT-MPTs: Process models for response-time distributions based on multinomial processing trees with applications to recognition memory. *Journal of Mathematical Psychology*, 82, 111–130.

RT-MPT Models (Klauer & Kellen, 2018)

- Serial processing assumption: Observed RTs within each MPT branch are the result of a sequence of underlying processes
 - 1] Time for encoding and response execution
 - 2] Completion time for each state in the MPT model
 - 3] Observed RTs in a branch are the sum of encoding and all relevant processing times
- 2HTM components:
 - “Detection RTs”: Encoding + Detection
 - “Guessing RTs”: Encoding + unsuccessful detection + guessing






Illustration of the parametric assumptions

- Encoding and response execution (gray): truncated normal distribution (with mean μ and SD σ)
- Completion times (green): exponential distribution (with rate parameters λ)
- Observed time (blue): sum of encoding and processing times
- Note: Encoding and all completion times are independent







The ordering of the latent MPT states matters

- The 2HTM permits two possible orders:
 - A “Detect-Guess Model”: First detection, then guessing (previous slides)
 - B “Default-Interventionist Model”: First guessing (by default) and the detection process can intervene (see below)
- With the RT-MPT extension, both versions can be tested against each other



Empirical test of different 2HTM versions

- Bayesian hierarchical model (person random effects)
- The Default-Interventionist model fits 5 data sets better
- Effect of manipulations
 - No effect of memory strength on completion time of detection
 - Faster completion times for guessing if response matches the response-bias-condition
- The model fit is satisfactory:



Summary

RT-Extended MPT Models (Heck & Erdfelder, 2016)

- A** No assumptions about shape of latent distributions
- B** RT-extended MPT models are also MPT models
- C** Testing relative speed of processes (stochastic dominance)

GPT Models (Heck, Erdfelder, & Kieslich; 2018)

- A** General approach for modeling discrete and continuous data
- B** New tests of psychological theories (e.g., mouse-tracking)
- C** MPT parameters estimated more precisely
- D** User-friendly software (R package gpt)


RT-MPT (Klauer & Kellen, 2018)

- A** Assumption of serial processing (sum of encoding and completion times)
- B** Hierarchical Bayesian

Appendix

Appendix: GPT Estimates are More Precise

- Higher precision of parameter estimates $\hat{\theta}$
 - The more distinct the latent distributions, the smaller the standard error of $\hat{\theta}$
 - Intuition: Continuous variables improve the classification of trials to latent processing states
 - Upper bound: Precision of MPT model
 - Lower bound: Latent states known




Appendix: GPT Estimates are More Precise

- Simulation of the 2HTM with Gaussian component distributions

- $\mu^{\text{detect}} = 0$ vs. $\mu^{\text{guess}} = 0, \dots, 5$

- Results

- More distinct distributions: smaller standard error of $\hat{\theta}$
 - Upper bound: Precision of MPT model
 - Lower bound: Latent states known



Appendix: Formal Definition of GPT Models

For a vector of discrete responses x , a matrix of continuous variables Y :

- The **joint distribution** f is a finite mixture
 - For a discrete response x and continuous response(s) y :

$$f(x, y \mid \theta, \eta) = \sum_{j=1}^J \delta_{C_j}(\{x\}) \sum_{i=1}^{I_j} p_{ij}(\theta) g_{ij}(y \mid \eta)$$

- **Mixture weights** $p_{ij}(\theta)$
 - Identical to MPT-branch probabilities (probability parameters θ)

$$p_{ij}(\theta) = c_{ij} \prod_{s=1}^S \theta_s^{a_{ijs}} (1 - \theta_s)^{b_{ijs}}$$

- **Basis distributions** $g_{ij}(y \mid \eta)$ for latent states
 - E.g., normal, exGaussian, exWald, ... distributions
 - Product-distributions for multivariate continuous data

Appendix: Formal Definition of GPT Models

- GPT models are a set of parameterized distributions:

$$\mathcal{M}^{\text{GPT}}(\Theta = [0, 1]^{S_1}, \Lambda \subset \mathbb{R}^{S_2}) = \{f(x, \mathbf{y} \mid \boldsymbol{\theta}, \boldsymbol{\eta}) \mid \boldsymbol{\theta} \in \Theta, \boldsymbol{\eta} \in \Lambda\}$$

- Likelihood where trials $k = 1, \dots, K$ fall into disjoint sets M_t that are modeled by $t = 1, \dots, T$ processing trees

$$L(\boldsymbol{\theta}, \boldsymbol{\eta} \mid \mathbf{x}, \mathbf{Y}) = \prod_{t=1}^T \prod_{k \in M_t} f_t(x_k, \mathbf{y}_k \mid \boldsymbol{\theta}, \boldsymbol{\eta})$$

Expectation-Maximization (EM) algorithm

- E: Compute expected probabilities z of being in the cognitive states
 - Continuous variables inform the state-vector z
- M: Maximize likelihood of continuous parameters given the latent-states z

Illustration

- E-step estimates the probability to be in state i in trial k :

$$P(z_k = i \mid \boldsymbol{\theta}, \boldsymbol{\eta}, x_k, \mathbf{y}_k) = \frac{P(z_k = i \mid \boldsymbol{\theta}, x_k) g_{ij}(\mathbf{y}_k \mid \boldsymbol{\eta})}{\sum_i P(z_k = i \mid \boldsymbol{\theta}, x_k) g_{ij}(\mathbf{y}_k \mid \boldsymbol{\eta})}$$

Cat.	RT [ms]	Conf. [1-10]	ERP [mV]	$z_k = 1$...	$z_k = I$
c_1	551	3	1.324	0.43	...	0.09
c_1	502	1	0.921	0.19	...	0.56
c_2	470	6	2.231	0.30	...	0.00
c_1	733	4	1.010	0.14	...	0.47

Identifiability: GPT models with identifiable MPT structure are identifiable if (cf. distribution-free approach):

- Component distributions are observable (Yantis et al., 1991)
- Stepwise deletion of identifiable component distributions (Heck & Erdfelder, 2016)
- Specific matrix has full rank (Heck & Erdfelder, 2016)

Alternative strategy

- Using order constraints to identify GPT models with a nonidentifiable MPT structure
- Label switching of processing paths with component distributions