

Mixture Models for Continuous Data

Generalized Processing Tree Models

Daniel W. Heck




2019-04-30

MPT Modeling with Continuous Data

- 1) MPT-RT: Modeling response times with histograms
 - Heck & Erdfelder (2016)
- 2) GPT (generalized processing tree): Parametric modeling
 - Heck, Erdfelder, & Kieslich (2018)
- 3) RT-MPT: Serial-process model for response times
 - Klauer & Kellen (2018)

Mixture distribution

- All of the MPT extensions assume mixture distributions for discrete and continuous observations
 - A Latent RTs: Different processing branches of the MPT model result in different latent distributions $g_j(t)$
 - B Observed RTs: A mixture distribution, defined as $f(t) = \sum_j p_j g_j(t)$
 - C The mixture weights p_j are determined by the MPT structure (= branch probabilities)




Generalized Processing Tree Models

- Heck, D. W., Erdfelder, E., & Kieslich, P. J. (2018). Generalized processing tree models: Jointly modeling discrete and continuous variables. *Psychometrika*.

Generalized processing tree (GPT) models

- Main difference: Parametric assumptions for component distributions
- The type of distribution depends on continuous variable
 - RTs: log-normal, ex-Gaussian, ...
 - Mouse-tracking measures (see below): Normal distribution
 - Neuro-psychological measures: ...
- The distributions are described by parameters η
 - Normal distribution: mean and SD
 - ex-Gaussian: mean, SD, and mean of exponential




Benefits of the GPT Framework

- A) Increased precision in estimating MPT parameters θ
- B) Unidentifiable MPT models can become identifiable
- C) Flexibility and simplicity

Higher precision of MPT-parameter estimates in GPTs


- The more distinct the latent distributions, the smaller the standard error
- Intuition: Continuous variables improve the “classification” which trials belong to which latent processing states
- 2HTM: “Fast RTs are due to detection, slow RTs are due to guessing”



Identifiability of GPT Models

Example: The feature comparison model of semantic categorization


- The theory assumes two different processes
- f = probability of Process 1 (similarity-based comparison)
- c_1 = accuracy of similarity-based comparison
- c_2 = accuracy of defining-feature comparison
- With discrete responses only, the (MPT) model is not identifiable
 - only 1 free category for 3 free parameters



Identifiability of GPT Models

Identifiability of the feature comparison model

- Solution: Assume Gaussian component distributions for continuous variable
 - MAD = maximum absolute deviation in mouse-tracking
- Order constraint for mean parameters: $\mu_c < \mu_d$
 - Interpretation: More direct trajectories/small MADs for similarity-based comparison
- With both discrete *and* continuous data, model is identifiable
 - The different component distribution allow to disentangle the two processes



GPTs as general-purpose measurement models

- GPTs can be specified as easily as MPTs
 - Implemented in the R package gpt
 - Currently under development: <https://github.com/danheck/gpt>
 - Define model in a text file similar to EQN
 - Type of latent distribution(s) defined within R (e.g., latent="normal")

GPT version of 2-high-threshold model

```
# Tree ; Categ. ; MPT equation ; mean, SD (normal distr.)
target ; hit      ; d                ; m_d, sig
target ; hit      ; (1-d)*g          ; m_g, sig
target ; miss     ; (1-d)*(1-g)      ; m_g, sig

lure   ; cr       ; d                ; m_d, sig
lure   ; fa       ; (1-d)*g          ; m_g, sig
lure   ; cr       ; (1-d)*(1-g)      ; m_g, sig
```

Illustration of the gpt Package

```
library("gpt")  
# data from 2(response bias) x 2(memory strength) design:  
# labels: "o30s_cr" = 30% old items / strong memory / correct rejection  
head(heck2016, 3)
```

```
##      cat    rt  
## 1 o30s_cr 1123  
## 2 o30s_cr  671  
## 3 o30s_cr  728
```

```
modelfile <- "models/2htm_exgauss_2x2.txt"  
# first lines:
```

```
## # 30% old / strong memory  
## lure_s30;      o30s_cr      ; (1-dn_s)*(1-g30) ; mu,sig,lambda_g_new30  
## lure_s30;      o30s_cr      ; dn_s              ; mu,sig,lambda_dn_s  
## lure_s30;      o30s_fa      ; (1-dn_s)*g30       ; mu,sig,lambda_g_old30  
##  
## target_s30;    o30s_hit     ; do_s              ; mu,sig,lambda_do_s  
## target_s30;    o30s_hit     ; (1-do_s)*g30       ; mu,sig,lambda_g_old30  
## target_s30;    o30s_miss    ; (1-do_s)*(1-g30) ; mu,sig,lambda_g_new30  
##  
## # 30% old / weak memory  
## lure_w30;      o30w_cr      ; (1-dn_w)*(1-g30) ; mu,sig,lambda_g_new30  
## lure_w30;      o30w_cr      ; dn_w              ; mu,sig,lambda_dn_w  
## lure_w30;      o30w_fa      ; (1-dn_w)*g30       ; mu,sig,lambda_g_old30
```

gpt Package: Model Fitting

```
fit <- gpt_fit(x = "cat",      # MPT category
              y = "rt",      # name of continuous variable(s)
              data = heck2016, # example data for 1 person
              file = modelfile, # GPT model file
              latent="exgauss", # family of latent RT distributions
              restrictions=list("dn_s=do_s", "dn_w=do_w"))
```

fit


##		Estimate	SE	CI.lower	CI.upper
##	dn_s	0.741	0.027	0.687	0.794
##	dn_w	0.477	0.033	0.411	0.542
##	g30	0.189	0.031	0.128	0.250
##	g70	0.261	0.038	0.186	0.335
##	lambda_dn_s	173.001	18.297	137.139	208.862
##	lambda_dn_w	192.480	34.973	123.934	261.027
##	lambda_do_s	127.979	14.688	99.191	156.766
##	lambda_do_w	152.031	18.506	115.760	188.301
##	lambda_g_new30	311.259	30.941	250.615	371.904
##	lambda_g_new70	460.295	36.207	389.331	531.259
##	lambda_g_old30	531.233	86.513	361.671	700.794
##	lambda_g_old70	516.846	74.478	370.872	662.820
##	mu	633.806	5.371	623.278	644.334
##	sig	49.235	4.045	41.307	57.162

```
test_fit(fit, bins = 4)$test      # Dzhaparidze-Nikulin statistic
```

##	statistic	df	p.value	
##	1	82.38871	42	0.0001960731


gpt Package: Model Fit

```
hist(fit)
```



gpt Package: Model Fit

```
plot(fit)  # cumulative densities
```



RT-MPT: Serial-process modeling of RTs

- Klauer, K. C., & Kellen, D. (2018). RT-MPTs: Process models for response-time distributions based on multinomial processing trees with applications to recognition memory. *Journal of Mathematical Psychology*, 82, 111–130.

RT-MPT Models (Klauer & Kellen, 2018)

- Serial processing assumption: Observed RTs within each MPT branch are the result of a sequence of underlying processes
 - 1) Time for encoding and response execution
 - 2) Completion time for each state in the MPT model
 - 3) Observed RTs in a branch are the sum of encoding and all relevant processing times
- 2HTM components:
 - “Detection RTs”: Encoding + Detection
 - “Guessing RTs”: Encoding + unsuccessful detection + guessing






Illustration of the parametric assumptions

- Encoding and response execution (gray): truncated normal distribution (with mean μ and SD σ)
- Completion times (green): exponential distribution (with rate parameters λ)
- Observed time (blue): sum of encoding and processing times
- Note: Encoding and all completion times are independent




The ordering of the latent MPT states matters

- The 2HTM permits two possible orders:
 - A “Detect-Guess Model”: First detection, then guessing (previous slides)
 - B “Default-Interventionist Model”: First guessing (by default) and the detection process can intervene (see below)
- With the RT-MPT extension, both versions can be tested against each other



Empirical test of different 2HTM versions

- Bayesian hierarchical model (person random effects)
- The Default-Interventionist model fits 5 data sets better
- Effect of manipulations
 - No effect of memory strength on completion time of detection
 - Faster completion times for guessing if response matches the response-bias-condition
- The model fit is satisfactory:



Summary

RT-Extended MPT Models (Heck & Erdfelder, 2016)

- A)** No assumptions about shape of latent distributions
- B)** RT-extended MPT models are also MPT models
- C)** Testing relative speed of processes (stochastic dominance)

GPT Models (Heck, Erdfelder, & Kieslich; 2018)

- A)** General approach for modeling discrete and continuous data
- B)** New tests of psychological theories (e.g., mouse-tracking)
- C)** MPT parameters estimated more precisely
- D)** User-friendly software (R package `gpt`)


RT-MPT (Klauer & Kellen, 2018)

- A)** Assumption of serial processing (sum of encoding and completion times)
- B)** Hierarchical Bayesian

Appendix


Appendix: GPT Estimates are More Precise

- Higher precision of parameter estimates $\hat{\theta}$
 - The more distinct the latent distributions, the smaller the standard error of $\hat{\theta}$
 - Intuition: Continuous variables improve the classification of trials to latent processing states
 - Upper bound: Precision of MPT model
 - Lower bound: Latent states known



Appendix: GPT Estimates are More Precise

- Simulation of the 2HTM with Gaussian component distributions
 - $\mu^{\text{detect}} = 0$ vs. $\mu^{\text{guess}} = 0, \dots, 5$
- Results
 - More distinct distributions: smaller standard error of $\hat{\theta}$
 - Upper bound: Precision of MPT model
 - Lower bound: Latent states known



Appendix: Formal Definition of GPT Models

For a vector of discrete responses x , a matrix of continuous variables Y :

- The **joint distribution** f is a finite mixture
 - For a discrete response x and continuous response(s) y :

$$f(x, y \mid \theta, \eta) = \sum_{j=1}^J \delta_{C_j}(\{x\}) \sum_{i=1}^{I_j} p_{ij}(\theta) g_{ij}(y \mid \eta)$$

- **Mixture weights** $p_{ij}(\theta)$
 - Identical to MPT-branch probabilities (probability parameters θ)

$$p_{ij}(\theta) = c_{ij} \prod_{s=1}^S \theta_s^{a_{ijs}} (1 - \theta_s)^{b_{ijs}}$$

- **Basis distributions** $g_{ij}(y \mid \eta)$ for latent states
 - E.g., normal, exGaussian, exWald, ... distributions
 - Product-distributions for multivariate continuous data

Appendix: Formal Definition of GPT Models

- GPT models are a set of parameterized distributions:

$$\mathcal{M}^{\text{GPT}}(\Theta = [0, 1]^{S_1}, \Lambda \subset \mathbb{R}^{S_2}) = \{f(x, \mathbf{y} \mid \boldsymbol{\theta}, \boldsymbol{\eta}) \mid \boldsymbol{\theta} \in \Theta, \boldsymbol{\eta} \in \Lambda\}$$

- Likelihood where trials $k = 1, \dots, K$ fall into disjoint sets M_t that are modeled by $t = 1, \dots, T$ processing trees

$$L(\boldsymbol{\theta}, \boldsymbol{\eta} \mid \mathbf{x}, \mathbf{Y}) = \prod_{t=1}^T \prod_{k \in M_t} f_t(x_k, \mathbf{y}_k \mid \boldsymbol{\theta}, \boldsymbol{\eta})$$

Expectation-Maximization (EM) algorithm

- E: Compute expected probabilities z of being in the cognitive states
 - Continuous variables inform the state-vector z
- M: Maximize likelihood of continuous parameters given the latent-states z

Illustration

- E-step estimates the probability to be in state i in trial k :

$$P(z_k = i \mid \boldsymbol{\theta}, \boldsymbol{\eta}, x_k, \mathbf{y}_k) = \frac{P(z_k = i \mid \boldsymbol{\theta}, x_k) g_{ij}(\mathbf{y}_k \mid \boldsymbol{\eta})}{\sum_i P(z_k = i \mid \boldsymbol{\theta}, x_k) g_{ij}(\mathbf{y}_k \mid \boldsymbol{\eta})}$$

Cat.	RT [ms]	Conf. [1-10]	ERP [mV]	$z_k = 1$...	$z_k = I$
c_1	551	3	1.324	0.43	...	0.09
c_1	502	1	0.921	0.19	...	0.56
c_2	470	6	2.231	0.30	...	0.00
c_1	733	4	1.010	0.14	...	0.47

Identifiability: GPT models with identifiable MPT structure are identifiable if (cf. distribution-free approach):

- Component distributions are observable (Yantis et al., 1991)
- Stepwise deletion of identifiable component distributions (Heck & Erdfelder, 2016)
- Specific matrix has full rank (Heck & Erdfelder, 2016)

Alternative strategy

- Using order constraints to identify GPT models with a nonidentifiable MPT structure
- Label switching of processing paths with component distributions