

One task, two hash-bound artifacts

CARA_LO_CHEMBL1006579_IC50_0001 • 50 observed supports • 119 candidates • 73 feasible • budget k=10

SYSTEM-VISIBLE INPUT CARD

schema: specguard.decision-card-input.v1 • candidate activity is absent

Assay context and provenance

target CHEMBL5491 • IC50 • pChEMBL (higher_is_better) • source CARA
benchmark 0.1.0 • data cara-lo-all/0.1.0

Observed support evidence

IDs, structures, descriptors, and measured pChEMBL are visible.

compound ID	SMILES	pChEMBL	MW	cLogP
CHEMBL209448	<chem>N#Cc1ccccc1-c1cc2[nH]c3ccc(O)cc3c2c...</chem>	6.72	353.3	3.45
CHEMBL209594	<chem>COc1ccccc1-c1cc2[nH]c3ccc(O)cc3c2c...</chem>	7.62	358.4	3.59

Candidate action space

IDs, structures, and permitted descriptors are visible; there is no activity field.

candidate ID	SMILES	MW	cLogP	TPSA
CHEMBL209388	<chem>Cn1c2ccc(O)cc2c2c3c(c(-c4ccccc4Cl)c...</chem>	376.8	4.24	71.3
CHEMBL209486	<chem>O=C1NC(=O)c2c1c(-c1cccs1)cc1[nH]c3c...</chem>	334.4	3.64	82.2

Hard action and eligibility constraints

OUTPUT exactly 10 • candidate-pool IDs • unique • exclude support
CANDIDATE parseable SMILES • $MW \leq 500$ • $cLogP \leq 4.5$
forbidden SMARTS list: empty

Ordered output schema

rank: integer
candidate_id: string
confidence: optional number
→ ranked top-10 batch

visibility boundary

SCORER-ONLY OUTCOMES

schema: specguard.scorer-outcomes.v1
never supplied to deployable systems

Cryptographic binding

same task_id
system_input_sha256:
72fc5ddec707d656...a1158a5f

Retrospective candidate outcomes

One outcome for every candidate ID.

candidate_id	hidden pChEMBL
CHEMBL209388	7.24
CHEMBL209486	6.85

Evaluator use after selection

Join selected candidate IDs to outcomes.
Compute feasible utility, NDCG@10,
and constrained regret.
Oracle access is upper-bound only.

Leakage boundary: candidate activity is prohibited by the input schema; the evaluator joins the separate, hash-bound scorer row only after an action is issued.