

Packet Tracer - Configure DTP

Name: Danica Marie A. Dumalagan

Date: February 10, 2023

Addressing Table

Device	Interface	IP Address	Subnet Mask
PC1	NIC	192.168.10.1	255.255.255.0
PC2	NIC	192.168.20.1	255.255.255.0
PC3	NIC	192.168.30.1	255.255.255.0
PC4	NIC	192.168.30.2	255.255.255.0
PC5	NIC	192.168.20.2	255.255.255.0
PC6	NIC	192.168.10.2	255.255.255.0
S1	VLAN 99	192.168.99.1	255.255.255.0
S2	VLAN 99	192.168.99.2	255.255.255.0
S3	VLAN 99	192.168.99.3	255.255.255.0

Objectives

- Configure static trunking
- Configure and Verify DTP

Background / Scenario

As the number of switches in a network increases, the administration necessary to manage the VLANs and trunks can be challenging. To ease some of the VLAN and trunking configurations, trunk negotiation between network devices is managed by the Dynamic Trunking Protocol (DTP), and is automatically enabled on Catalyst 2960 and Catalyst 3650 switches.

In this activity, you will configure trunk links between the switches. You will assign ports to VLANs and verify end-to-end connectivity between hosts in the same VLAN. You will configure trunk links between the switches, and you will configure VLAN 999 as the native VLAN.

Instructions

Part 1: Verify VLAN configuration.

Verify the configured VLANs on the switches.

- On S1, go to privileged EXEC mode and enter the **show vlan brief** command to verify the VLANs that are present.

```
S1# show vlan brief
```

```
VLAN Name                Status    Ports
-----
1    default                active    Fa0/1, Fa0/2, Fa0/3, Fa0/4
```

Fa0/5, Fa0/6, Fa0/7, Fa0/8
 Fa0/9, Fa0/10, Fa0/11, Fa0/12
 Fa0/13, Fa0/14, Fa0/15, Fa0/16
 Fa0/17, Fa0/18, Fa0/19, Fa0/20
 Fa0/21, Fa0/22, Fa0/23, Fa0/24
 Gig0/1, Gig0/2

99 Management active
 999 Native active
 1002 fddi-default active
 1003 token-ring-default active
 1004 fddinet-default active
 1005 trnet-default active

- b. Repeat Step 1a on S2 and S3.

What VLANs are configured on the switches?

1 default, 99 Management, 999 Native, 1002 fddi-default, 1003 token-ring-default, 1004 fddinet-default, 1005 trnet-default

Part 2: Create additional VLANs on S2 and S3.

- a. On S2, create VLAN 10 and name it Red.

S2(config)# **vlan 10**
 S2(config-vlan)# **name Red**

- b. Create VLANs 20 and 30 according to the table below.

VLAN Number	VLAN Name
10	Red
20	Blue
30	Yellow

- c. Verify the addition of the new VLANs. Enter **show vlan brief** at the privileged EXEC mode.

In addition to the default VLANs, which VLANs are configured on S2?

10 Red, 20 Blue, 30 Yellow

- d. Repeat the previous steps to create the additional VLANs on S3.

Part 3: Assign VLANs to Ports

Use the **switchport mode access** command to set access mode for the access links. Use the **switchport access vlan** *vlan-id* command to assign a VLAN to an access port.

Ports	Assignments	Network
S2 F0/1 – 8 S3 F0/1 – 8	VLAN 10 (Red)	192.168.10.0 /24
S2 F0/9 – 16 S3 F0/9 – 16	VLAN 20 (Blue)	192.168.20.0 /24
S2 F0/17 – 24 S3 F0/17 – 24	VLAN 30 (Yellow)	192.168.30.0 /24

- a. Assign VLANs to ports on S2 using assignments from the table above.

```
S2(config-if)# interface range f0/1 - 8
S2(config-if-range)# switchport mode access
S2(config-if-range)# switchport access vlan 10
S2(config-if-range)# interface range f0/9 -16
S2(config-if-range)# switchport mode access
S2(config-if-range)# switchport access vlan 20
S2(config-if-range)# interface range f0/17 - 24
S2(config-if-range)# switchport mode access
S2(config-if-range)# switchport access vlan 30
```

- b. Assign VLANs to ports on S3 using the assignments from the table above.

Now that you have the ports assigned to VLANs, try to ping from **PC1** to **PC6**.

Was the ping successful? Explain.

No. They are on different VLANs.

Part 4: Configure Trunks on S1, S2, and S3.

Dynamic trunking protocol (DTP) manages the trunk links between Cisco switches. Currently, all the switchports are in the default trunking mode, which is dynamic auto. In this step, you will change the trunking mode to dynamic desirable for the link between switches S1 and S2. The link between switches S1 and S3 will be set as a static trunk. Use VLAN 999 as the native VLAN in this topology.

- a. On switch S1, configure the trunk link to dynamic desirable on the GigabitEthernet 0/1 interface. The configuration of S1 is shown below.

```
S1(config)# interface g0/1
S1(config-if)# switchport mode dynamic desirable
```

What will be the result of trunk negotiation between S1 and S2?

A trunk line was configured between S1 and S2.

- b. On switch S2, verify that the trunk has been negotiated by entering the **show interfaces trunk** command. Interface GigabitEthernet 0/1 should appear in the output.

What is the mode and status for this port?

Mode: Auto; Status: trunking

- c. For the trunk link between S1 and S3, configure interface GigabitEthernet 0/2 as a static trunk link on S1. In addition, disable DTP negotiation on interface G0/2 on S1.

```
S1(config)# interface g0/2
S1(config-if)# switchport mode trunk
S1(config-if)# switchport nonegotiate
```

- d. Use the **show dtp** command to verify the status of DTP.

```
S1# show dtp
Global DTP information
  Sending DTP Hello packets every 30 seconds
  Dynamic Trunk timeout is 300 seconds
  1 interfaces using DTP
```

- e. Verify trunking is enabled on all the switches using the **show interfaces trunk** command.

```
S1# show interfaces trunk
```

Port	Mode	Encapsulation	Status	Native vlan
Gig0/1	desirable	n-802.1q	trunking	1
Gig0/2	on	802.1q	trunking	1

Port	Vlans allowed on trunk
Gig0/1	1-1005
Gig0/2	1-1005

Port	Vlans allowed and active in management domain
Gig0/1	1,99,999
Gig0/2	1,99,999

Port	Vlans in spanning tree forwarding state and not pruned
Gig0/1	1,99,999
Gig0/2	1,99,999

What is the native VLAN for these trunks currently?

VLAN 1

- f. Configure VLAN 999 as the native VLAN for the trunk links on S1.

```
S1(config)# interface range g0/1 - 2
```

```
S1(config-if-range)# switchport trunk native vlan 999
```

What messages did you receive on S1? How would you correct it?

VLAN 999 must be configured as a native VLAN for all switches.

- g. On S2 and S3, configure VLAN 999 as the native VLAN.
- h. Verify trunking is successfully configured on all the switches. You should be able ping one switch from another switch in the topology using the IP addresses configured on the SVI.
- i. Attempt to ping from PC1 to PC6.

Why was the ping unsuccessful? (Hint: Look at the 'show vlan brief' output from all three switches. Compare the outputs from the 'show interface trunk' on all switches.)

VLAN 10, 20 and 30 were not configured on S1.

- j. Correct the configuration as necessary.

Part 5: Reconfigure trunk on S3.

- a. Issue the 'show interface trunk' command on S3.

What is the mode and encapsulation on G0/2?

Mode: on; Encapsulation: 802.1q

- b. Configure G0/2 to match G0/2 on S1.

What is the mode and encapsulation on G0/2 after the change?

Mode: on; Encapsulation: 802.1q

- c. Issue the command 'show interface G0/2 switchport' on switch S3.

What is the 'Negotiation of Trunking' state displayed?

Off

Part 6: Verify end to end connectivity.

- From PC1 ping PC6.
- From PC2 ping PC5.
- From PC3 ping PC4.

Part 7: Post your screenshots

On the PT Activity window, make sure that the completion grade is **100%**. Click on the **Check Results** button and select the **Assessment Items** tab. Take a screen shot of the whole window, showing the table of assessment items, and the score/item count. Own your photo by placing a watermark on your photo with your name and USC ID Number. Paste your screenshot below:

Cisco Packet Tracer - D:\JinBus\CpE 3212\3.5.5 Packet Tracer - Configure DTP.pka

File Edit Options View Tools Extensions Window Help

Activity Results Time Elapsed: 00:47:13

Congratulations Danica Marie A. Dumalagan! You completed the activity.

Overall Feedback **Assessment Items** Connectivity Tests

Expand/Collapse All Show Incorrect Items

Assessment Items	Status	Points	Component(s)	Feedback
Network				
S1				
Ports				
GigabitEthernet0/1				
Dynamic Mode	Correct	4	DTP Config	
Native VLAN	Correct	4	Trunk Config	
GigabitEthernet0/2				
Dynamic Mode	Correct	1	Switching	
Native VLAN	Correct	4	Trunk Config	
Nonegotiate	Correct	4	DTP Config	
Port Mode	Correct	1	Other	
VLANs				
VLAN 10		1	Switching	
VLAN Name	Correct	2	VLAN Config	
VLAN 20		1	Switching	
VLAN Name	Correct	2	VLAN Config	
VLAN 30		1	Switching	
VLAN Name	Correct	2	VLAN Config	
S2				
Ports				
FastEthernet0/1		0	Other	
Access VLAN	Correct	2	VLAN Config	
FastEthernet0/12		0	Other	
Access VLAN	Correct	2	VLAN Config	
FastEthernet0/20		0	Other	
Access VLAN	Correct	2	VLAN Config	
GigabitEthernet0/1		0	Other	
Native VLAN	Correct	4	Trunk Config	
VLANs				
VLAN 10		1	Switching	
VLAN Name	Correct	1	Switching	
VLAN 20		1	Switching	
VLAN Name	Correct	1	Switching	
VLAN 30		1	Switching	
VLAN Name	Correct	1	Switching	
S3				
Ports				
FastEthernet0/11		0	Other	
Access VLAN	Correct	2	VLAN Config	
FastEthernet0/2		0	Other	
Access VLAN	Correct	2	VLAN Config	
FastEthernet0/20		0	Other	

Score : 61/61

Item Count : 25/25

Component	Items/Total	Score
DTP Config	4/4	16/16
Other	1/1	1/1
Switching	4/4	4/4
Trunk Config	4/4	16/16
VLAN Config	12/12	24/24

Danica Marie A. Dumalagan
18103276

Close