

Packet Tracer - Configure Router Interfaces

Name: Danica Marie A. Dumalagan

Date: February 4, 2023

Addressing Table

Device	Interface	IP Address/Prefix	Default Gateway
R1	G0/0	172.16.20.1 /25	N/A
	G0/1	172.16.20.129 /25	N/A
	S0/0/0	209.165.200.225 /30	N/A
PC1	NIC	172.16.20.10 /25	172.16.20.1
PC2	NIC	172.16.20.138 /25	172.16.20.129
R2	G0/0	2001:db8:c0de:12::1/64	N/A
	G0/1	2001:db8:c0de:13::1/64	N/A
	S0/0/1	2001:db8:c0de:11::1/64	N/A
		fe80::2	N/A
PC3	NIC	2001:db8:c0de:12::a/64	fe80::2
PC4	NIC	2001:db8:c0de:13::a/64	fe80::2

Objectives

Part 1: Configure IPv4 Addressing and Verify Connectivity

Part 2: Configure IPv6 Addressing and Verify Connectivity

Background

Routers R1 and R2 each have two LANs. Your task is to configure the appropriate addressing on each device and verify connectivity between the LANs.

Note: The user EXEC password is cisco. The privileged EXEC password is class.

Instructions

Part 1: Configure IPv4 Addressing and Verify Connectivity

Step 1: Assign IPv4 addresses to R1 and LAN devices.

Referring to the **Addressing Table**, configure IP addressing for **R1** LAN interfaces, **PC1** and **PC2**. The serial interface has already configured.

Step 2: Verify connectivity.

PC1 and PC2 should be able to ping each other and the Dual Stack Server.

Part 2: Configure IPv6 Addressing and Verify Connectivity

Step 1: Assign IPv6 addresses to R2 and LAN devices.

Referring to the **Addressing Table**, configure IP addressing for **R2 LAN interfaces**, **PC3** and **PC4**. The serial interface is already configured.

Step 2: Verify connectivity.

PC3 and PC4 should be able to ping each other and the Dual Stack Server.

Part 3: Post your screenshots

On the PT Activity window, make sure that the completion grade is **100%**. Click on the **Check Results** button and select the **Assessment Items** tab. Take a screen shot of the whole window, showing the table of assessment items, and the score/item count. Own your photo by placing a watermark on your photo with your name and USC ID Number. Paste your screenshot below:

