

Ethical Hacking Report for ieschandomonte.edu.es

=== Nmap Scan Result ===

Starting Nmap 7.96 (<https://nmap.org>) at 2025-05-09 21:15 Hora de verano romance

Nmap scan report for ieschandomonte.edu.es (82.98.132.46)

Host is up (0.0038s latency).

rDNS record for 82.98.132.46: hl842.dinaser.com

Not shown: 998 filtered tcp ports (no-response)

PORT	STATE	SERVICE	VERSION
21/tcp	open	ftp	vsftpd 2.0.8 or later
22/tcp	open	ssh	OpenSSH 7.4p1 Debian 10+deb9u10 (protocol 2.0)

Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at <https://nmap.org/submit/> .

Nmap done: 1 IP address (1 host up) scanned in 16.98 seconds

=== Vulnerability Analysis ===

This is an FTP (File Transfer Protocol) server listening at port 21 of the machine with IP address `82.98.132.46` and a running version of vsftpd, which stands for Very Fast Tiny File Transfer Protocol daemon written in C language on Unix-like operating systems (FT Pv1).

Here are some potential vulnerabilities or misconfigurations:

****Potential Vulnerability/Misconfiguration Based On The Nmap Scan Results For ieschandomonte.edu.es ****

From the results of your nmap scan, there appears to be no open FTP port (21) that is not in a 'filtered' state or an uncommon one like 5000-6000 and so on as well which are usually seen during penetration testing. This might suggest possible vulnerabilities based off the lack of such ports being discovered by nmap scan, possibly related to FTP (File Transfer Protocol).

In fact a SSH port is also open:22 in this case suggesting that it could be an authentication or authorization issue from external parties if one were successful. The version displayed for vsftpd on the NMAP report indicates????? v2.0.8???which does not appear to contain any significant vulnerabilities as of now, but still a good idea to check more in advance and also consider whether it's vulnerable or open-ended based off what you can do with this service (maybe even exploit for remote code execution).

****Attack Vectors Based On Your Analysis: ****

Based on the lack of exposed FTP ports, there are a few attack vectors that could be used. For instance if an unauthorized user has access to these services they may potentially gain control over data or system configuration changes in your server/network by exploiting vulnerabilities related with SSH and thus misconfigurations like those above (unless proper authentication methods such as password-less login, public key based auth are implemented).

This analysis is pretty broad because the lack of exposed ports implies that we're not dealing directly at risk from potential security risks. However if there were other vulnerabilities identified in your nmap scan you would need to consider those too and potentially exploit them for exploiting further targets or getting a deeper insight into how these services could be used by an attacker, like accessing system information (system version/information) with FTP access rights using the default credentials.

It's important also that any potential vulnerabilities should not only affect one IP address but can potentially impact entire networks if done right and at a sufficient level of confidence due to its high likelihood for exposure in larger environments, such as an organization or network where there are

many machines being targeted simultaneously (multiple targeting).

The best approach would be conducting thorough testing on your identified services/ports using different exploits until you find the vulnerabilities that allow access. It's also recommended to implement a more sophisticated security strategy than just FTP for better system safeguards, like password hashing or secure remote administration tools such as pfSense (FreeBSD Packet Firewall).