



In The Name of God

Operating Systems Assignment

Instructor: Shameli

Computer Assignment #2
Faculty of Computer
Engineering and Science

Assignment 2 – Memory Management

This project consists of writing a program that translates logical to physical addresses for a virtual address space of size $2^{16} = 65,536$ bytes. Your program will read from a file containing logical addresses and, using a TLB as well as a page table, will translate each logical address to its corresponding physical address and output the value of the byte stored at the translated physical address. The goal behind this project is to simulate the steps involved in translating logical to physical addresses.

Specifics

Your program will read a file containing several 32-bit integer numbers that represent logical addresses. However, you need only be concerned with 16-bit addresses, so you must mask the rightmost 16 bits of each logical address. These 16 bits are divided into (i) an 8-bit page number and (ii) 8-bit page offset. Other specifics include the following:

- 16 entries in the TLB
- 256 entries in the page table
- Page size of 256 bytes
- 256 frames in the physical memory
- Frame size of 256 bytes
- Physical memory of 65,536 bytes (256 frames * 256-byte frame size)

Address Translation

Your program will translate logical to physical addresses using a TLB and page table. First, the page number is extracted from the logical address, and the TLB is consulted. In the case of a TLB-hit, the frame number is obtained from the TLB. In the case of a TLB-miss, the page table must be consulted. In the latter case, either the frame number is obtained from the page table or a page fault occurs.

Handling Page Faults

Your program will implement demand paging. The backing store (e.g., your disk) is represented by the file BACKING STORE.bin, a binary file of size 65,536 bytes. When a page fault occurs, you will read in a 256-byte page from the file BACKING STORE.bin and store it in an available page frame in physical memory.

For example, if a logical address with page number 15 resulted in a page fault, your program would read in page 15 from BACKING STORE.bin (remember that pages begin at 0 and are 256 bytes in size) and store it in a page frame in physical memory. Once this frame is stored (and the page table and TLB are updated), subsequent accesses to page 15 will be resolved by either the TLB or the page table.

You will need to treat BACKING STORE.bin as a random-access file so that you can randomly seek to certain positions of the file for reading. We suggest using the standard C library functions for performing I/O, including `fopen()`, `fread()`, `fseek()`, and `fclose()`. The size of physical memory is the same as the size of the virtual address space (65,536 bytes), so you do not need to be concerned about page replacements during a page fault. Later, we describe a

modification to this project using a smaller amount of physical memory; at that point, a page-replacement strategy will be required.

Test File

We provide the file `addresses.txt`, which contains integer values representing logical addresses ranging from 0 - 65,535 (the size of the virtual address space). Your program will open this file, read each logical address and translate it to its corresponding physical address, and output the value of the signed byte at the physical address.

How to Begin

First, write a simple program that extracts the page number and offset (an 8-bit page number and 8-bit page offset) from the following integer numbers:

1, 256, 32768, 32769, 128, 65534, 33153

Perhaps the easiest way to do this is by using the operators for bit-masking and bit-shifting. Once you can correctly establish the page number and offset from an integer number, you are ready to begin. Initially, we suggest that you bypass the TLB and use only a page table. You can integrate the TLB once your page table is working properly. Remember, address translation can work without a TLB; the TLB just makes it faster. When you are ready to implement the TLB, recall that it has only 16 entries, so you will need to use a replacement strategy when you update a full TLB. You can use FIFO for updating your TLB.

How to Run Your Program

Your program should run as follows:

```
./a.out addresses.txt
```

Your program will read in the file `addresses.txt`, which contains 1,000 logical addresses ranging from 0 to 65,535. Your program is to translate each logical address to a physical address and determine the contents of the signed byte stored at the correct physical address. Your program is to output the following values:

1. The logical address being translated (the integer value being read from `addresses.txt`).
2. The corresponding physical address (what your program translates the logical address to).
3. The signed byte value stored at the translated physical address.

We also provide the file `correct.txt`, which contains the correct output values for the file `addresses.txt`. You should use this file to determine if your program is correctly translating logical to physical addresses. Statistics After completion, your program is to report the following statistics:

1. Page-fault rate: the percentage of address references that resulted in page faults.
2. TLB hit rate: the percentage of address references that were resolved in the TLB.

Since the logical addresses in `addresses.txt` were generated randomly and do not reflect any memory access locality, do not expect to have a high TLB hit rate.

Modifications

This project assumes that physical memory is the same size as the virtual address space. In practice, physical memory is typically much smaller than a virtual address space. A suggested modification is to use a smaller physical address space. We recommend using 128 page frames rather than 256. This change will require modifying your program so that it keeps track of free page frames as well as implementing a page-replacement policy using LRU.

How to submit your assignment?

You should zip all your source code and upload it through the courseware.

Please use the following format to name your file:

OS_CA_<num>_<studentId>.zip