

# Combined Proof Methods for Multimodal Logic

---

Daniella Angelos

March 20, 2018


Cláudia Nalon — University of Brasilia

# Introduction

---

## **in Computer Science:**

Develop languages to model situations



# Multimodal Logic ( $K_n$ )

- Propositional Symbols ( $\mathcal{P} = \{p, q, r \dots\}$ )
- Operators ( $\neg, \vee, \boxed{a}$ ) with  $a \in \mathcal{A} = \{1, \dots, n\}$

## Well Formed Formulae (WFF)

- Propositional Symbols  $\mathcal{P}$
- If  $\varphi$  and  $\psi$  are each a WFF then also are:
  1.  $\neg\varphi$
  2.  $\varphi \vee \psi$
  3.  $\boxed{a}\varphi$

Let  $W$  be a set of possible worlds and  $R_a$  a binary relation over these worlds for some  $a \in \mathcal{A}$ :

**Possibility:**  $\Diamond \varphi$  is true at  $w \in W$  iff  $\varphi$  is true at some  $w' \in W$  such that  $wR_a w'$


Let  $W$  be a set of possible worlds and  $R_a$  a binary relation over these worlds for some  $a \in \mathcal{A}$ :

**Possibility:**  $\Diamond \varphi$  is true at  $w \in W$  iff  $\varphi$  is true at some  $w' \in W$  such that  $wR_aw'$


**Necessity:**  $\Box \varphi$  is true at  $w \in W$  iff  $\varphi$  is true at all  $w' \in W$  such that  $wR_aw'$



## Example



# Example




Formulae true in  $w$ :

$$\Box 1 p$$

$$\Box 1 q \wedge \Box 2 \neg q$$

$$\Diamond \Diamond r$$

## Example




Formulae true in  $w$ :

$\boxed{1}p$  : modal level of  $p = 1$

$\boxed{1}q \wedge \boxed{2}\neg q$

$\Diamond\Diamond r$

## Example



Formulae true in  $w$ :

$\Box 1 p$  : modal level of  $p = 1$

$\Box 1 q \wedge \Box 2 \neg q$

$\Diamond \Diamond r$  : modal level of  $r = 2$

$$\mathfrak{M} = (W, w_0, R_1, \dots, R_n, \pi)$$

$$\mathfrak{M} = (W, w_0, R_1, \dots, R_n, \pi)$$

- Set of possible worlds  $W$

$$\mathfrak{M} = (W, w_0, R_1, \dots, R_n, \pi)$$

- Set of possible worlds  $W$
- Root of model  $w_0 \in W$

$$\mathfrak{M} = (W, w_0, R_1, \dots, R_n, \pi)$$

- Set of possible worlds  $W$
- Root of model  $w_0 \in W$
- A finite number of binary relations  $R_a$  over the worlds in  $W$ ,  
 $R_a \subseteq W \times W$ , with  $a \in \mathcal{A}$



$$\mathfrak{M} = (W, w_0, R_1, \dots, R_n, \pi)$$

- Set of possible worlds  $W$
- Root of model  $w_0 \in W$
- A finite number of binary relations  $R_a$  over the worlds in  $W$ ,  
 $R_a \subseteq W \times W$ , with  $a \in \mathcal{A}$
- Valuation function to propositional symbols  
 $\pi : W \times \mathcal{P} \rightarrow \{true, false\}$

Let  $\varphi$  be a WFF and  $\mathfrak{M} = (W, w_0, R_1, \dots, R_n, \pi)$  a model in  $K_n$ :

# Satisfiability Relation

Let  $\varphi$  be a WFF and  $\mathfrak{M} = (W, w_0, R_1, \dots, R_n, \pi)$  a model in  $K_n$ :

$$\langle \mathfrak{M}, w \rangle \models \varphi$$

# Satisfiability Relation

Let  $\varphi$  be a WFF and  $\mathfrak{M} = (W, w_0, R_1, \dots, R_n, \pi)$  a model in  $K_n$ :

$$\langle \mathfrak{M}, w \rangle \models \varphi$$

- $\langle \mathfrak{M}, w \rangle \models p$  iff  $\pi(w, p) = \text{true}$

# Satisfiability Relation

Let  $\varphi$  be a WFF and  $\mathfrak{M} = (W, w_0, R_1, \dots, R_n, \pi)$  a model in  $K_n$ :

$$\langle \mathfrak{M}, w \rangle \models \varphi$$

- $\langle \mathfrak{M}, w \rangle \models p$  iff  $\pi(w, p) = \text{true}$
- $\langle \mathfrak{M}, w \rangle \models \neg\psi$  iff  $\langle \mathfrak{M}, w \rangle \not\models \psi$

# Satisfiability Relation

Let  $\varphi$  be a WFF and  $\mathfrak{M} = (W, w_0, R_1, \dots, R_n, \pi)$  a model in  $K_n$ :

$\langle \mathfrak{M}, w \rangle \models \varphi$

- $\langle \mathfrak{M}, w \rangle \models p$  iff  $\pi(w, p) = \text{true}$
- $\langle \mathfrak{M}, w \rangle \models \neg\psi$  iff  $\langle \mathfrak{M}, w \rangle \not\models \psi$
- $\langle \mathfrak{M}, w \rangle \models \psi \vee \delta$  iff  $\langle \mathfrak{M}, w \rangle \models \psi$  or  $\langle \mathfrak{M}, w \rangle \models \delta$

# Satisfiability Relation

Let  $\varphi$  be a WFF and  $\mathfrak{M} = (W, w_0, R_1, \dots, R_n, \pi)$  a model in  $K_n$ :

$$\langle \mathfrak{M}, w \rangle \models \varphi$$

- $\langle \mathfrak{M}, w \rangle \models p$  iff  $\pi(w, p) = \text{true}$
- $\langle \mathfrak{M}, w \rangle \models \neg\psi$  iff  $\langle \mathfrak{M}, w \rangle \not\models \psi$
- $\langle \mathfrak{M}, w \rangle \models \psi \vee \delta$  iff  $\langle \mathfrak{M}, w \rangle \models \psi$  or  $\langle \mathfrak{M}, w \rangle \models \delta$
- $\langle \mathfrak{M}, w \rangle \models \boxed{a}\psi$  iff for all  $w' \in W$  such that  $wR_a w'$ , with  $a \in \mathcal{A}$ , we have that  $\langle \mathfrak{M}, w' \rangle \models \psi$

A formula  $\varphi \in \text{WFF}$  is said to be *locally satisfiable* in  $K_n$  if exists a model  $\mathfrak{M}$  such that  $\langle \mathfrak{M}, w_0 \rangle \models \varphi$ .



# Satisfiability

A formula  $\varphi \in \text{WFF}$  is said to be *locally satisfiable* in  $K_n$  if exists a model  $\mathfrak{M}$  such that  $\langle \mathfrak{M}, w_0 \rangle \models \varphi$ .

$$\mathfrak{M} \models_L \varphi$$

# Satisfiability

A formula  $\varphi \in \text{WFF}$  is said to be *locally satisfiable* in  $K_n$  if exists a model  $\mathfrak{M}$  such that  $\langle \mathfrak{M}, w_0 \rangle \models \varphi$ .

$$\mathfrak{M} \models_L \varphi$$

A formula  $\varphi \in \text{WFF}$  is said to be *globally satisfiable* in  $K_n$  if exists a model  $\mathfrak{M}$  such that  $\langle \mathfrak{M}, w \rangle \models \varphi$  for all  $w$ .

# Satisfiability

A formula  $\varphi \in \text{WFF}$  is said to be *locally satisfiable* in  $K_n$  if exists a model  $\mathfrak{M}$  such that  $\langle \mathfrak{M}, w_0 \rangle \models \varphi$ .

$$\mathfrak{M} \models_L \varphi$$

A formula  $\varphi \in \text{WFF}$  is said to be *globally satisfiable* in  $K_n$  if exists a model  $\mathfrak{M}$  such that  $\langle \mathfrak{M}, w \rangle \models \varphi$  for all  $w$ .

$$\mathfrak{M} \models_G \varphi$$

# Satisfiability

A formula  $\varphi \in \text{WFF}$  is said to be *locally satisfiable* in  $K_n$  if exists a model  $\mathfrak{M}$  such that  $\langle \mathfrak{M}, w_0 \rangle \models \varphi$ .

$$\mathfrak{M} \models_L \varphi$$

A formula  $\varphi \in \text{WFF}$  is said to be *globally satisfiable* in  $K_n$  if exists a model  $\mathfrak{M}$  such that  $\langle \mathfrak{M}, w \rangle \models \varphi$  for all  $w$ .

$$\mathfrak{M} \models_G \varphi$$

A set  $\mathcal{F}$  of WFF is said to be (locally of globally) satisfiable, if the conjunction of each  $\varphi \in \mathcal{F}$  is satisfiable.

# Problem

Given any set  $\Phi$  of well formed formulae, to determine if  $\Phi$  is (locally or globally) satisfiable in  $K_n$ .

# Problem

Given any set  $\Phi$  of well formed formulae, to determine if  $\Phi$  is (locally or globally) satisfiable in  $K_n$ .

- Local satisfiability: PSPACE-Complete (Halpern and Moses – 1992),

# Problem

Given any set  $\Phi$  of well formed formulae, to determine if  $\Phi$  is (locally or globally) satisfiable in  $K_n$ .

- Local satisfiability: PSPACE-Complete (Halpern and Moses – 1992),
- Global satisfiability: EXPTIME-Complete (E. Spaan – 1993).

# Layered Resolution

---



$$\bigwedge_i ml : C_i$$

$$\bigwedge_i ml : C_i$$

- literal clause:

$$ml : \bigvee_{b=1}^r l_b$$

$$\bigwedge_i ml : C_i$$

- literal clause:

$$ml : \bigvee_{b=1}^r l_b$$

- $a$ -positive clause:

$$ml : l' \Rightarrow \boxed{a} l$$

$$\bigwedge_i ml : C_i$$

- literal clause:

$$ml : \bigvee_{b=1}^r l_b$$

- $a$ -positive clause:

$$ml : l' \Rightarrow \boxed{a} l$$

- $a$ -negative clause:

$$ml : l' \Rightarrow \diamond_a l$$

$$\bigwedge_i ml : C_i$$

- literal clause:

$$ml : \bigvee_{b=1}^r l_b$$

- $a$ -positive clause:

$$ml : l' \Rightarrow \boxed{a} l$$

- $a$ -negative clause:

$$ml : l' \Rightarrow \diamond_a l$$

where  $l$  is a propositional symbol or its negation

$$\begin{array}{l} \text{[LRES]} \quad ml : D \vee l \\ \quad \quad \quad ml : D' \vee \neg l \\ \hline \quad \quad \quad ml : D \vee D' \end{array}$$

$$\begin{array}{l}
 \text{[GEN1]} \quad \begin{array}{l}
 ml : \quad l'_1 \Rightarrow \boxed{a} \neg l_1 \\
 \vdots \\
 ml : \quad l'_m \Rightarrow \boxed{a} \neg l_m \\
 ml : \quad l' \Rightarrow \boxed{a} \neg l \\
 \hline
 ml + 1 : \quad l_1 \vee \dots \vee l_m \vee l \\
 \hline
 ml : \quad \neg l'_1 \vee \dots \vee \neg l'_m \vee \neg l'
 \end{array}
 \end{array}$$

$$\begin{array}{l}
 \text{[GEN3]} \quad \begin{array}{l}
 ml : \quad l'_1 \Rightarrow \boxed{a} \neg l_1 \\
 \vdots \\
 ml : \quad l'_m \Rightarrow \boxed{a} \neg l_m \\
 ml : \quad l' \Rightarrow \boxed{a} \neg l \\
 \hline
 ml + 1 : \quad l_1 \vee \dots \vee l_m \\
 \hline
 ml : \quad \neg l'_1 \vee \dots \vee \neg l'_m \vee \neg l'
 \end{array}
 \end{array}$$

- A theorem prover that implements this modal resolution-based calculus
- It also implements several refinements and simplification techniques
- KSP performs pretty well!
- But not so well when there is a large number of variables in one particular level



- A theorem prover that implements this modal resolution-based calculus
- It also implements several refinements and simplification techniques
- K<sub>S</sub>P performs pretty well!
- But not so well when there is a large number of variables in one particular level

## Problem

As resolution relies on saturation, the performance of K<sub>S</sub>P for such entries deteriorates.

We take advantage of the great theoretical and practical efforts that have been directed in improving the efficiency of CDCL SAT solvers, to reduce the time  $K\zeta P$  spends during saturation.

# CDCL SAT Solvers

---

Given a formula in classical propositional logic, does this formula have a satisfying assignment?



- Generic combinatorial tool and search platform

- Generic combinatorial tool and search platform
- DPLL Procedure

- Generic combinatorial tool and search platform
- DPLL Procedure
- Watched literals, restart strategies, deletion mechanisms, branching heuristics, learning mechanisms etc



## Example

$$\varphi = (p \vee t \vee \neg q) \wedge (p \vee \neg r) \wedge (q \vee r \vee s)$$

## Example


$$\varphi = (p \vee t \vee \neg q) \wedge (p \vee \neg r) \wedge (q \vee r \vee s)$$

$$p = \text{false}$$

## Example

$$\varphi = (p \vee t \vee \neg q) \wedge (p \vee \neg r) \wedge (q \vee r \vee s)$$

$p = \text{false}$




$r = \text{false}$

## Example

$$\varphi = (p \vee t \vee \neg q) \wedge (p \vee \neg r) \wedge (q \vee r \vee s)$$

$$t = \text{false}$$

$$p = \text{false}$$




A black arrow points from the text  $p = \text{false}$  to the text  $r = \text{false}$ .

$$r = \text{false}$$

## Example

$$\varphi = (p \vee t \vee \neg q) \wedge (p \vee \neg r) \wedge (q \vee r \vee s)$$

$t = false$



$q = false$




$p = false$



$r = false$


## Example

$$\varphi = (p \vee t \vee \neg q) \wedge (p \vee \neg r) \wedge (q \vee r \vee s)$$




## Example

$$\varphi = (p \vee t \vee \neg q) \wedge (p \vee \neg r) \wedge (q \vee r \vee s) \wedge (\neg s \vee \neg u) \wedge (y \vee x) \wedge (y \vee u \vee \neg x)$$



## Example


$$\varphi = (p \vee t \vee \neg q) \wedge (p \vee \neg r) \wedge (q \vee r \vee s) \wedge (\neg s \vee \neg u) \wedge (y \vee x) \wedge (y \vee u \vee \neg x)$$






## Example

$$\varphi = (p \vee t \vee \neg q) \wedge (p \vee \neg r) \wedge (q \vee r \vee s) \wedge (\neg s \vee \neg u) \wedge (y \vee x) \wedge (y \vee u \vee \neg x)$$




## Example

$$\varphi = (p \vee t \vee \neg q) \wedge (p \vee \neg r) \wedge (q \vee r \vee s) \wedge (\neg s \vee \neg u) \wedge (y \vee x) \wedge (y \vee u \vee \neg x)$$



## Example

$$\varphi = (p \vee t \vee \neg q) \wedge (p \vee \neg r) \wedge (q \vee r \vee s) \wedge (\neg s \vee \neg u) \wedge (y \vee x) \wedge (y \vee u \vee \neg x)$$



# Implication Graph

# Implication Graph

- Vertices are assigned variables


# Implication Graph

- Vertices are assigned variables
- Edges are antecedent clauses

Analyses the conflict and learns a new clause

# Conflict analysis

$$\varphi = (p \vee t \vee \neg q) \wedge (p \vee \neg r) \wedge (q \vee r \vee s) \wedge (\neg s \vee \neg u) \wedge (y \vee x) \wedge (y \vee u \vee \neg x)$$






# Conflict analysis

$$\varphi = (p \vee t \vee \neg q) \wedge (p \vee \neg r) \wedge (q \vee r \vee s) \wedge (\neg s \vee \neg u) \wedge (y \vee x) \wedge (y \vee u \vee \neg x)$$

new clause:  $(p \vee t \vee y)$



# Combination

---

During the main loop of K<sub>S</sub>P, we will feed the SAT solver with the propositional clauses at a particular modal level.

During the main loop of K<sub>S</sub>P, we will feed the SAT solver with the propositional clauses at a particular modal level.

- The SAT solver finds a model for the set of clauses

During the main loop of K<sub>S</sub>P, we will feed the SAT solver with the propositional clauses at a particular modal level.

- The SAT solver finds a model for the set of clauses
- The SAT solver returns one or more new clauses

## Example

$$1 : l_1 \Rightarrow \Box \neg p$$

$$1 : l_2 \Rightarrow \Box \neg t$$

$$1 : l_3 \Rightarrow \Diamond \neg y$$

$$2 : \{p, t, \neg q\}$$

$$2 : \{p, \neg r\}$$

$$2 : \{q, r, s\}$$

$$2 : \{\neg s, \neg u\}$$

$$2 : \{y, x\}$$

$$2 : \{y, u, \neg x\}$$

# Example

$$1 : l_1 \Rightarrow \Box \neg p$$

$$1 : l_2 \Rightarrow \Box \neg t$$

$$1 : l_3 \Rightarrow \Diamond \neg y$$

$$2 : \{p, t, \neg q\}$$

$$2 : \{p, \neg r\}$$

$$2 : \{q, r, s\}$$

$$2 : \{\neg s, \neg u\}$$

$$2 : \{y, x\}$$

$$2 : \{y, u, \neg x\}$$

[GEN1]

$$ml : l'_1 \Rightarrow \Box \neg l_1$$

$$\vdots$$

$$ml : l'_m \Rightarrow \Box \neg l_m$$

$$ml : l' \Rightarrow \Diamond \neg l$$

$$\frac{ml + 1 : l_1 \vee \dots \vee l_m \vee l}{ml : \neg l'_1 \vee \dots \vee \neg l'_m \vee \neg l'}$$

# Example

$$1 : l_1 \Rightarrow \Box \neg p$$

$$1 : l_2 \Rightarrow \Box \neg t$$

$$1 : l_3 \Rightarrow \Diamond \neg y$$

$$2 : \{p, t, \neg q\}$$

$$2 : \{p, \neg r\}$$

$$2 : \{q, r, s\}$$

$$2 : \{\neg s, \neg u\}$$

$$2 : \{y, x\}$$

$$2 : \{y, u, \neg x\}$$

$$2 : \{p, t, y\}$$

[GEN1]

$$ml : l'_1 \Rightarrow \Box \neg l_1$$

$\vdots$

$$ml : l'_m \Rightarrow \Box \neg l_m$$

$$ml : l' \Rightarrow \Diamond \neg l$$

$$ml + 1 : l_1 \vee \dots \vee l_m \vee l$$

$$ml : \neg l'_1 \vee \dots \vee \neg l'_m \vee \neg l'$$



# Example

$$1 : l_1 \Rightarrow \Box \neg p$$

$$1 : l_2 \Rightarrow \Box \neg t$$

$$1 : l_3 \Rightarrow \Diamond \neg y$$

$$2 : \{p, t, \neg q\}$$

$$2 : \{p, \neg r\}$$

$$2 : \{q, r, s\}$$

$$2 : \{\neg s, \neg u\}$$

$$2 : \{y, x\}$$

$$2 : \{y, u, \neg x\}$$

$$2 : \{p, t, y\}$$

$$1 : \{\neg l_1, \neg l_2, \neg l_3\}$$

[GEN1]

$$ml : l'_1 \Rightarrow \Box \neg l_1$$

$$\vdots$$

$$ml : l'_m \Rightarrow \Box \neg l_m$$

$$ml : l' \Rightarrow \Diamond \neg l$$

$$\frac{ml + 1 : l_1 \vee \dots \vee l_m \vee l}{ml : \neg l'_1 \vee \dots \vee \neg l'_m \vee \neg l'}$$

# Conclusion

---

We believe that calling the SAT solver from the main loop of KSP will significantly improve its performance.



## Future Work

1. Choose a SAT solver and evaluate this choice

## Future Work

1. Choose a SAT solver and evaluate this choice
2. Automated integration with KSP

## Future Work

1. Choose a SAT solver and evaluate this choice
2. Automated integration with KSP
3. Define metrics for tests and select benchmarks

## Future Work

1. Choose a SAT solver and evaluate this choice
2. Automated integration with KSP
3. Define metrics for tests and select benchmarks
4. Exhaustively testing



## Future Work

1. Choose a SAT solver and evaluate this choice
2. Automated integration with KSP
3. Define metrics for tests and select benchmarks
4. Exhaustively testing
5. Collect and analyse data

## Future Work

1. Choose a SAT solver and evaluate this choice
2. Automated integration with KSP
3. Define metrics for tests and select benchmarks
4. Exhaustively testing
5. Collect and analyse data
6. Write the dissertation

# Future Work

1. Choose a SAT solver and evaluate this choice
2. Automated integration with K<sub>S</sub>P
3. Define metrics for tests and select benchmarks
4. Exhaustively testing
5. Collect and analyse data
6. Write the dissertation

Activities	Months									
	March	April	May	June	July	August	September	October	November	December
1	x	x								
2	x	x	x	x						
3				x	x					
4					x	x	x	x		
5							x	x	x	
6	x	x	x	x	x	x	x	x	x	x

**Thank you!**

---

# Combined Proof Methods for Multimodal Logic

---

Daniella Angelos

March 20, 2018

Cláudia Nalon — University of Brasilia