# How to notify Breeze

ATTO folding mobility scooter · Lithium-ion battery 48V / 5.2Ah / 249.6Wh · Battery model GD009-13S2P · Meets IATA requirements

**What is in this file:** this page · flight day page · notification letter · manufacturer letter · battery certificates (MSDS and UN 38.3)
**To print:** pages 1 to 3 are enough. Keep the whole file on your phone to show the certificates if asked.

## 1 What we filled in for you

- Your full name, booking reference, flights and dates, phone and email
- Your signature and the date, on the notification letter (page 3)

## 2 Notify Breeze

- Tell Breeze about your scooter before you fly, through the Guest Empowerment Team on **flybreeze.com** (email or text)
- Breeze carries folding powered scooters at no extra charge
- Check in at the ticket counter at least 1 hour before the usual check-in time for other guests

⏱ **When: No notice is required. Check in at least 1 hour before the usual check-in time**

## 3 On flight day

- Bring this file printed, and keep it on your phone
- At check-in, tell the agent you have a folding mobility scooter with a lithium battery
- Fold the scooter and switch it off. Take out the battery and carry it in your hand luggage

* Helper tool only. The file was created automatically from the details you entered and may contain mistakes or omissions. You are responsible for checking the details, completing any missing document and sending it to the airline. MovingLife is not responsible in any way for an error, omission, refusal, delay or requirement of an airline or an airport, and no claim may be made against it. The final decision belongs to the airline only.

Breeze movinglife

# Flight day ✈

1. Arrive at the airport early. Many airlines ask for at least 2 hours before a domestic flight, so check yours
2. Bring **this file** printed, and keep it on your phone
3. At check-in, tell the agent you have a **folding mobility scooter** with a lithium battery
4. **Fold** the scooter and **switch it off**
5. **Take out the battery**. It flies with you in your hand luggage
6. Keep the scooter **charger** in your hand luggage, not in your checked bag
7. Have a flight kit? **Put it on** the scooter before you hand it over
8. If asked, show the **manufacturer letter** and the **battery certificates** (page 4 and on)




Fold to trolley mode




Take out the battery and carry it with you

**Your rights.** Airlines flying to and from the US must help you with boarding and with your mobility device, at no charge. If a problem comes up, ask for the airline's Complaints Resolution Official.



**We recommend flying with the ATTO flight kit**
A protective cover that keeps the scooter safe while it is loaded onto the plane.
Learn more: us.movinglife.com

# Powered Mobility Device Notification

To: Breeze, Special Assistance / Accessibility Services · Please keep with the booking · Device: ATTO folding mobility scooter by Movinglife LTD

> **Request:** I will travel with the battery powered mobility device described below. Please note it on my reservation (battery powered mobility aid with a lithium-ion battery, WCLB) and tell me about any additional requirement.

| Passenger and flight | |
|---|---|
| Full name (as in the passport) | |
| Booking reference | |
| Flight numbers and dates | |
| Phone / Email | |

| Mobility device | |
|---|---|
| Device type | **Electric folding mobility scooter** |
| Manufacturer / model | **Movinglife LTD · ATTO** |
| Weight | **28.2 kg (62 lb) without battery · battery 1.8 kg (4 lb)** |
| Folded dimensions (L × W × H) | **39 × 42 × 72 cm (15.4 × 16.5 × 28.3 in)** |
| Unfolded dimensions (L × W × H) | **120 × 56 × 89 cm (47.2 × 22 × 35 in)** |
| Tools needed to prepare for flight? | **No** |

| Battery | |
|---|---|
| Battery type | **Lithium-ion, dry, non-spillable** |
| Number of batteries | **1 · spare batteries: 0** |
| Voltage / capacity / energy | **48V / 5.2Ah / 249.6 Wh** |
| Battery model / manufacturer | **GD009-13S2P · Dongguan Kingin Power Co., Ltd** |
| Test standard | **UN 38.3 · report MRI1AVBG2672847U5** |
| Air transport | **Meets IATA DGR requirements** |
| Removable / can be disconnected / original manufacturer battery | **Yes / Yes / Yes** |

**Preparation for flight**

- Fold to trolley mode, power OFF at the tiller.
- Remove the lithium-ion battery and carry it in the cabin in a protective pouch, with the terminals protected against short circuit.
- The charger travels with the passenger, not in checked baggage.

**Attached documents**

- Manufacturer's air transport confirmation letter
- Battery safety data sheet (MSDS) and UN 38.3 summary
- Battery spec and label (including Wh)
- Manufacturer's manual (bring it to the airport)

Passenger signature _____ Date _____

I declare that the details above are correct and match the device I will travel with.

# Movinglife LTD

www.movinglife.com · Israel +972 73 391 3999 · info@movinglife.com

In the US: Movinglife USA · +1 559 354 1089 · us.movinglife.com

**To: Airline Check-in / Dangerous Goods Acceptance Staff**

## Subject: Air Transport Confirmation, ATTO Mobility Scooter and Lithium ion Battery

This letter confirms that the mobility device described below is a battery-powered mobility aid manufactured / supplied by Movinglife LTD, and that its battery meets the requirements for carriage by air as a passenger mobility aid.

| | |
|---|---|
| Device | **ATTO electric folding mobility scooter** |
| Manufacturer | **Movinglife LTD** |
| Weight / folded dimensions | **28.2 kg without battery (battery 1.8 kg) · 39 × 42 × 72 cm (L×W×H)** |
| Battery type | **Lithium-ion, removable, original manufacturer battery** |
| Battery model / manufacturer | **GD009-13S2P · Dongguan Kingin Power Co., Ltd** |
| Rating | **48V · 5.2Ah · 249.6 Wh (one battery)** |
| Testing | **UN Manual of Tests and Criteria, Part III, sub-section 38.3 (UN 38.3) · report MRI1AVBG2672847U5** |

**Transport instructions:** fold the scooter into trolley mode and switch it off. Remove the lithium-ion battery (249.6 Wh, in accordance with the IATA Dangerous Goods Regulations for battery-powered mobility aids) and carry it in the passenger cabin, with the terminals protected against short circuit and the battery placed in a protective pouch. No tools are required. The scooter frame contains no other battery.

The battery's Material Safety Data Sheet (MSDS), including the UN 38.3 transport information, is attached (ATTO Flight Safety Certificates).

movinglife

# ATTO MOBILITY SCOOTER

# Flight Safety Certificates

## LITHIUM-ION BATTERY 249.6 Wh

### DRY, NON SPILLABLE

Battery dimensions: 32x14x11cm  Weight 1.8kg


| Page | Document | Standard / Doc |
|---|---|---|
| 2 | OVERVIEW | FDA / CE |
| 3-14 | BATTERY SAFETY DATA SHEET | MSDS |
| 15 | SCOOTER DIMENSIONS | |


movinglife

www.movinglife.com

Take to Airport


Li-ion

FDA APPROVED

CE




FREE WHEEL HANDLE



MOTOR

BATTERY

# MATERIAL SAFETY DATA SHEET

**Rechargeable Li-ion Battery**

**Model: GD009-13S2P**

| Prepared by | Approved by |
|---|---|
| Cindy Chen | Jack Zhou |
| Jun 5, 2023 | Jun 6, 2023 |

# Material Safety Data Sheet

Reference to ST/SG/AC.10/30/Rev.9(GHS)

## Section 1 - Chemical Product and Company Identification

**Chemical Product Identification**
**Sample Name:** Lithium-ion Battery pack
**Sample Model:** GD009-13S2P
**Recommended Uses:** N/A
**Restrictions on Use:** N/A
**Supplier Name:** Dongguan Kingin Power Co., Ltd.
**Address:** No.702, Floor 7th, Block B, Honghai Intelligent Valley, No.50, Jinjiaotang Fumin Road, Zhutang Village, Fenggang Town, Dongguan City
**Phone Number:** 15283330307
**FAX:** 0769-88023775
**E-mail:** zhuozhiguang@kingin.cn
**Emergency Phone Number:** 0769-88023775

## Section 2 - Hazards Identification

**Emergency overview:** This product is a battery. Intended use of the product should not result in exposure to the chemical substance. In case of rupture the below hazards exist.

**Classification according to GHS**
Acute toxicity, oral (4)
Skin corrosion/irritation (2)
Serious eye damage/eye irritation (2A)
Specific target organ toxicity, single exposure; Respiratory tract irritation (3)

**Label elements**

**Hazard pictogram(s);**



**Signal word:** Warning

**Hazard statement(s):**

H302 Harmful if swallowed

H315 Causes skin irritation

H319 Causes serious eye irritation

H335 May cause respiratory irritation

**Precautionary statement(s):**

**Prevention:**

P264 Wash skin and clothing thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves, protective clothing, eye protection, face protection.

P261 Avoid breathing dust, fume, gas, mist, vapours, spray.

P271 Use only outdoors or in a well-ventilated area.

**Response:**

P301 + P312 IF SWALLOWED: Call a POISON CENTER if you feel unwell.

P330 Rinse mouth.

P302 + P352 IF ON SKIN: Wash with plenty water.

P321 Specific treatment (See additional emergency instructions).

P333 + P313 If skin irritation or rash occurs: Get medical advice.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER, if you feel unwell.

**Storage**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

**Disposal:**

P501 Send contents to approved waste treatment plants.

**Other hazards**

**Physical and chemical hazards:** See Section 10

**Human health hazards:** See Section 11

**Environmental hazards:** See Section 12

## Section 3 - Composition/Information on Ingredients

**Chemical characterization:** Mixture

| Chemical Composition | CAS No. | EC# | Weight (%) |
|---|---|---|---|
| Cobaltate, lithium | 12190-79-3 | 235-362-0 | 41 |
| Graphite | 7782-42-5 | 231-955-3 | 25 |
| Polypropylene | 9003-07-0 | 618-352-4 | 2 |
| Copper | 7440-50-8 | 231-159-6 | 5 |
| Aluminium | 7429-90-5 | 231-072-3 | 8 |
| Nickel | 7440-02-0 | 231-111-4 | 3 |
| Rubber, chloroprene, gas | 69028-37-1 | --- | 2 |
| Phosphate(1-), hexafluoro-, lithium | 21324-40-3 | 244-334-7 | 9 |
| Polyvinylidene fluoride resin | 24937-79-9 | 607-458-6 | 2 |
| Cellulose, carboxymethyl ether | 9000-11-7 | 618-326-2 | 3 |

## Section 4 - First Aid Measures

**Description of first aid measures**

**General information** No special measures required.

**After eye contact**

Flush eyes with plenty of water for several minutes while holding eyelids open. Get medical attention if irritation persists.

**After skin contact**

Remove contaminated clothing and shoes. Immediately wash with water and soap and rinse thoroughly. Wash clothing and shoes before reuse. If irritation occurs, get medical attention.

**After inhalation**

Remove victim to fresh area. Administer artificial respiration if breathing is difficult. Seek medical attention.

**After swallowing**

Do not induce vomiting. Get medical attention.

**Personal protective equipment for first-aid responders:** No data available.

**Most important symptoms/effects, acute and delayed:** No data available.

**Indication of immediate medical attention and special treatment needed:** Treat symptomatically.

## Section 5 - Fire Fighting Measures

**Suitable extinguishing media:**

Small Fire**:** Dry chemical, $CO_2$, water spray or regular foam. Large Fire**:** Water spray, fog or regular foam.

Move containers from fire area if you can do it without risk.

**Unsuitable extinguishing media:**

No data available.

**Specific Hazards arising from the chemical:**

Special hazards arising from the substance or mixture

Battery may burst and release hazardous decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolyte that may vent, ignite and produce sparks when subjected to high temperature (>150 °C (302 °F)), when damaged or abused (e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in close proximity.

**Specific protective actions for fire-fighters:**

Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.

## Section 6 - Accidental Release Measures

**Personal precautions:**

As an immediate precautionary measure, isolate spill or leak area for at least 25 meters (75 feet) in all directions. Keep unauthorized personnel away. Stay upwind, uphill and/or upstream. Ventilate closed spaces before entering. Large Spill: Consider initial downwind evacuation for at least 100 meters (330 feet).

**Protective equipment:**

No data available.

**Emergency procedures:**

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Absorb with earth, sand or other non-combustible material. Leaking batteries and contaminated absorbent material should be placed in metal containers.

**Environmental precautions:**

Do not allow material to be released to the environment without proper governmental permits.

**Methods and materials for containment and cleaning up:**

For all waste handing must refer to United Nations, National and Local Regulations for disposal.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## Section 7 - Handling and Storage

**Precautions for safe handling:**

Avoid short circuiting the battery. Avoid mechanical damage of the battery. Do not open or disassemble.

Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity. Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps.

**Conditions for safe storage, including any incompatibilities:**

Store in a cool, dry, well-ventilated place. Keep away from heat, avoiding the long time of sunlight.

## Section 8 - Exposure Controls/Personal Protection

**Control parameters**

| CAS No. | ACGIH | NIOSH | OSHA |
|---|---|---|---|
| 12190-79-3 | N/A | N/A | N/A |
| 7782-42-5 | TLV-TWA 2mg/$m^3$ | REL-TWA 2.5mg/$m^3$ | PEL-TWA 15mppcf<br>PEL-TWA 20mppcf |
| 9003-07-0 | N/A | N/A | N/A |
| 7440-50-8 | TLV-TWA 0.2mg/$m^3$<br>TLV-TWA 1mg/$m^3$ | REL-TWA 1mg/$m^3$<br>REL-TWA 0.1mg/$m^3$ | PEL-TWA 0.1mg/$m^3$<br>PEL-TWA 1mg/$m^3$ |
| 7429-90-5 | TLV-TWA 1mg/$m^3$ | REL-TWA 2mg/$m^3$<br>REL-TWA 5mg/$m^3$<br>REL-TWA 10mg/$m^3$ | PEL-TWA 5mg/$m^3$<br>PEL-TWA 15mg/$m^3$ |
| 7440-02-0 | TLV-TWA 1.5mg/$m^3$ | REL-TWA 0.015mg/$m^3$ | PEL-TWA 1mg/$m^3$ |
| 69028-37-1 | N/A | N/A | N/A |
| 21324-40-3 | N/A | N/A | N/A |
| 24937-79-9 | N/A | N/A | N/A |
| 9000-11-7 | N/A | N/A | N/A |

**Appropriate engineering controls:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

**Personal Protective Equipment:**

**Respiratory protection:** Wear suitable protective mask. For a large large number of battery leakages, wear chemical protective clothing, including self-contained breathing apparatus.

**Hand Protection:** Wear appropriate protective gloves to reduce skin contact.

**Eye Protection:** Wear safety goggles or eye protection combined with respiratory protection.

**Skin and Body Protection:** Working environment required, wear suitable protective clothing to minimize contact with skin. The type of protective equipment must be according to the concentration and the content of certain hazardous substances in the workplace.

## Section 9 - Physical and Chemical Properties

| | |
|---|---|
| **Information on basic physical and chemical properties** | |
| **Colour:** | Black. |
| **Physical State:** | Prismatic. |
| **Odour:** | Not available. |
| **pH:** | Not available. |
| **Melting point/freezing point:** | Not available. |
| **Boiling point or initial boiling point and boiling range:** | Not available. |
| **Flash Point:** | Not available. |
| **Flammability:** | Not available. |
| **Solubility:** | Not available. |
| **Lower and upper explosion limit/flammability limit:** | Not available. |
| **Auto-ignition temperature:** | Not available. |
| **Decomposition temperature:** | Not available. |
| **Kinematic viscosity:** | Not available. |
| **Partition coefficient: n-octanol/water (log value):** | Not available. |
| **Vapour pressure:** | Not available. |
| **Density and/or relative density:** | Not available. |
| **Relative vapour density:** | Not available. |
| **Particle characteristics:** | Not available. |
| **Other information:** | |
| **Voltage** | 48V |
| **Electric capacity** | 5200mAh |
| **Electric Energy** | 249.6Wh |

## Section 10 - Stability and Reactivity

**Reactivity:** No data available.
**Chemical stability:** Stable.
**Possibility of hazardous reactions:** No data available.
**Conditions to Avoid:** Flames, sparks, and other sources of ignition, incompatible materials.
**Incompatible materials:** Oxidizing agents, acid base.
**Hazardous decomposition products:** Carbon monoxide, carbon dioxide, lithium oxide fumes.

# Section 11 - Toxicological Information

**Acute Toxicity:**

| CAS No. | LC50/LD50 |
|---|---|
| 12190-79-3 | No data available. |
| 7782-42-5 | No data available. |
| 9003-07-0 | No data available. |
| 7440-50-8 | No data available. |
| 7429-90-5 | No data available. |
| 7440-02-0 | LD50 Rat (oral): >9000mg/kg |
| 69028-37-1 | No data available. |
| 21324-40-3 | No data available. |
| 24937-79-9 | No data available. |
| 9000-11-7 | No data available. |

**Skin corrosion/irritation:** No data available.
**Serious eye damage/irritation:** No data available.
**Respiratory or Skin sensitization:** No data available.
**Germ Cell mutagenicity:** No data available.
**Carcinogenicity:** No data available.
**Reproductive toxicity:** No data available.
**Specific target organ toxicity-Single exposure:** No data available.
**Specific target organ toxicity-Repeated exposure:** No data available.
**Aspiration hazard:** No data available.
**Information on the likely routes of exposure:** No data available.
**Eye:** No data available.
**Skin:** No data available.
**Ingestion:** No data available.
**Inhalation:** No data available.

# Section 12 - Ecological Information

**Ecological Toxicity:** No data available.
**Persistence and degradability:** No data available.
**Bioaccumulative Potential:** No data available.
**Mobility in Soil:** No data available.
**Other adverse effects:** No data available.

## Section 13 - Disposal Considerations

**Disposal methods:**


**Recommendation:**

Consult state, local or national regulations to ensure proper disposal.

**Uncleaned packaging**

**Recommendation:** Disposal must be made according to official regulations.

## Section 14 - Transport Information

| | | |
|---|---|---|
| **UN or ID Number** | | |
| **IATA** | UN3480 | UN3171 |
| **IMDG** | UN3480 | UN3171 |
| **Model Regulation** | UN3480 | UN3171 |
| **Proper Shipping Name/Description** | | |
| **IATA** | Lithium ion batteries<br>Battery-powered vehicle | |
| **IMDG** | LITHIUM ION BATTERIES<br>BATTERY-POWERED VEHICLE | |
| **Model Regulation** | LITHIUM ION BATTERIES<br>BATTERY-POWERED VEHICLE | |
| **Class or Div.(Sub Hazard)** | | |
| **IATA** | 9 | |
| **IMDG** | 9 | |
| **Model Regulation** | 9 | |
| **Packing group** | | |
| **IATA** | N/A | |
| **IMDG** | N/A | |
| **Model Regulation** | N/A | |
| **Hazard Label**<br>**IATA**<br>**IMDG**<br>**Model Regulation** |  <br>965: |  <br>952: |
| **Environmental hazards**<br>**Marine pollutant:** | No | |
| **IMDG EmS:** | F-A. S-I | |
| **Special precautions for user** | No information available. | |

**Transport information:** The Lithium-ion battery pack GD009-13S2P has passed the test UN38.3, according

to the report ID: MRI1AVBG2672847U5.

Watt-hour exceeds the standard. The goods are packaged according to the packaging Instruction 965 section IA of IATA DGR 64th Edition for transportation, Cargo aircraft only.

Watt-hour exceeds the standard. The goods are packaged according to the special provision 230, 348, 384 of IMDG (40-20).

Watt-hour exceeds the standard. The goods are packaged according to the special provision 230, 348, 384 of <<Recommendations On The Transport Of Dangerous Goods-Model Regulations>> (22nd).

The goods are packaged according to the packaging Instruction 952 of IATA DGR 64th Edition for transportation, it belongs to dangerous goods. Be shipped by passenger and cargo aircraft.

The goods are packaged according to the special provision 388, 962, 971 of IMDG (40-20), it belongs to dangerous goods.

The goods are packaged according to the special provision 388 of <<Recommendations On The Transport Of Dangerous Goods-Model Regulations>> (22nd), it belongs to dangerous goods.

Separate batteries to prevent short-circuiting. and they should be packed in strong package during transport. Lithium cell or battery should incorporate a safety venting device or be designed to prevent a violent rupture under normal transport conditions. Keep away from high temperature and open flames.

**Note: State of Charge (SoC) not exceeding 30% of their rated capacity. (By air, Lithium ion batteries)**
**Batteries weight in the package <5kg. (By air, Batteries installed in equipment)**

**Transport Fashion:** By air, by sea, by railway, by road.

## Section 15 - Regulatory Information

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

| CAS No. | TSCA | IECSC | DSL/NDSL | EINECS/ ELINCS/ NLP |
|---|---|---|---|---|
| 12190-79-3 | Listed | Listed | Listed DSL | Listed |
| 7782-42-5 | Listed | Listed | Listed DSL | Listed |
| 9003-07-0 | Listed | Listed | Listed DSL | Listed |
| 7440-50-8 | Listed | Listed | Listed DSL | Listed |
| 7429-90-5 | Listed | Listed | Listed DSL | Listed |
| 7440-02-0 | Listed | Listed | Listed DSL | Listed |
| 69028-37-1 | Listed | Listed | Listed DSL | Listed |
| 21324-40-3 | Listed | Listed | Listed DSL | Listed |

| | | | | |
|---|---|---|---|---|
| 24937-79-9 | Listed | Listed | Listed DSL | Listed |
| 9000-11-7 | Listed | Listed | Listed DSL | Listed |

## Section 16 - Other Information

Issue Date: 2023-03-13
Issue Department: Technical department
Modification record:
Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Other Information:
CAS: (Chemical Abstracts Service);
EC: (European Commission);
ACGIH: (American Conference of Governmental Industrial Hygienists);
NIOSH: (US National Institute for Occupational Safety and Health);
OSHA: (US Occupational Safety and Health);
TLV: (Threshold Limit Value)
TWA: (Time Weighted Average);
STEL: (Short Term Exposure Limit);
PEL: (Permissible Exposure Level);
REL: (Recommended Exposure Limit);
PC-STEL: (Permissible concentration-short time exposure limit);
PC-TWA: (Permissible concentration-time weighted average);
IARC: (International Agency for Research on Cancer);
LC50: (Lethal concentration, 50 percent kill);
LD50: (Lethal dose, 50 percent kill);
EC50: (Median effective concentration);
BCF: (Bioconcentration Factor);
BOD: (Biochemical oxygen demand);
IECSC: (Inventory of Existing Chemical Substances in China);
NOEC: (No observed effect concentration);
NTP: (US National Toxicology Program);
RTECS: (Registry of Toxic Effects of Chemical Substances);
TOC: (Total Organic Carbon);
TSCA: (Toxic Substances Control Act of USA);

DSL: (the Domestic Substances List of Canada);
NDSL: (the Non-domestic Substances List of Canada);
IATA: (International Air Transport Association);
IMDG: (International Maritime Dangerous Goods);
TDG: (Recommendations on the TRANSPORT OF DANGEROUS GOODS Model Regulations)
The original report which report No. is MRICF6CG2915147U3 be replaced by this report, and it will be canceled immediately and doesn't have any legal validity. Please compliance with this report.
2023-03-13

***End of report***

## Scooter Sizes & Dimensions

- For sending to the cargo bay:

  In trolley mode (folded, as shown in picture) 72x42x39 cm




Trolley Mode
62.2 lbs (28.2 Kg)
w/out battery

For more information please contact Moving Life



USA +1-347-761-3317

UK +44-(0)20-3769 7530

Israel +972-(0)73-391 3999



info@movinglife.com

Take to Airport

All Rights Reserved © 2023 Moving Life Ltd.