movinglife

Lufthansa City

كيف ترسلون إلى لوفتهانزا سيتي

سكوتر ATTO · بطارية ليثيوم 48V / 5.2Ah / 249.6Wh · موديل البطارية GD009-13S2P · تلبّي متطلبات IATA

ماذا في هذا الملف: هذه الصفحة · صفحة ليوم الرحلة · نموذج شركة الطيران · رسالة المصنّع · شهادات البطارية (MSDS وUN 38.3)

1 ماذا تملأون في النموذج

- اسم العائلة والاسم الأول، رمز الحجز (6 رموز)، البريد

2 أرسلوه إلى شركة الطيران

- بعد الحجز أرسلوه بزر Send form في النموذج
- أسئلة: **lufthansa.com/help**، هاتف مجاني **0800 8384267**

⏱ **الموعد: بعد الحجز وقبل الرحلة**

3 يوم الرحلة

- احتفظوا بالنموذج معكم طوال الرحلة
- أحضروا الملف مطبوعًا
- عند الكاونتر اطووا السكوتر وأطفئوه وأخرجوا البطارية
- تصعد البطارية معكم إلى الطائرة في حقيبة اليد، والأقطاب مغطاة

* أداة مساعدة وتسهيل فقط. أُعدّ الملف تلقائيًا بحسب التفاصيل المُدخلة وقد يحتوي على أخطاء أو نواقص. المسؤولية عن فحص التفاصيل واستكمال أي مستند ناقص وإرساله إلى شركة الطيران تقع على المستخدم وحده. MovingLife غير مسؤولة بأي شكل عن أي خطأ أو نقص أو رفض أو تأخير أو شرط من شركة الطيران أو المطار، ولن تُقبل أي مطالبة ضدها. القرار النهائي لشركة الطيران وحدها.

MovingLife · 073 391 3999 · info@movinglife.com

movinglife

Lufthansa City

يوم الرحلة ✈

1. احضروا إلى المطار **قبل 3 ساعات من الرحلة**
2. أحضروا **هذا الملف** مطبوعًا
3. عند الكاونتر **اطووا** السكوتر و**أطفئوه**
4. **أخرجوا البطارية.** تصعد معكم إلى الطائرة في حقيبة اليد
5. خذوا **الشاحن** الخاص بالسكوتر في حقيبة اليد، وليس في الحقيبة الكبيرة
6. عندكم طقم طيران؟ **ألبسوه** للسكوتر قبل التسليم
7. إذا سألوا، اعرضوا **رسالة المصنّع** و**شهادات الطيران**



اطووا إلى وضع العربة



أخرجوا البطارية وخذوها في حقيبة اليد



ننصح بالسفر مع طقم الطيران لـ ATTO

غطاء واقٍ يحمي السكوتر أثناء تحميله على الطائرة.

للطلب: **073 391 3999** · تفاصيل: movinglife.co.il/products/atto-flight-kit

Informationen Elektrische Mobilitätshilfe
Electric mobility device information form

A STAR ALLIANCE MEMBER

Passagierinformationen
Passenger information

Name, Vorname:
Name, first name:

Aktueller Buchungscode (sechs-stellig):
Current booking code (six digits):

E-Mail-Adresse:
Email address:

Art und Spezifikation der Mobilitätshilfe
Type and specification of mobility device

Bitte füllen Sie hier nur den linken oder den rechten Teil des Formulars aus.
Please fill in only the left or the right part of this form here.

☐ **Batteriebetriebener Rollstuhl**
Battery powered wheelchair
oder / or
☒ **Andere batteriebetriebene Mobilitätshilfe (z. B. Scooter)**
Other mobility device (e.g. scooter)

☐ **Manueller Rollstuhl plus batteriebetriebene Antriebshilfe (z. B. Zuggerät)**
Manual wheelchair plus battery powered add-on unit (e.g. tractor)

Hersteller:
Manufacturer: Movinglife LTD

Modell:
Model: ATTO

Hersteller der Antriebshilfe:
Manufacturer of the add-on unit:

Antriebshilfe Modell:
Model add-on unit:

Ist die Rückenlehne faltbar? / Is the back rest foldable?
☒ **Ja** / Yes ☐ **Nein** / No

Gewicht und Dimensionen (gefaltet, wenn möglich):
Weight and dimensions (folded, when possible):

Gewicht / Weight:	28.2	**kg**
Länge / Length:	39	**cm**
Breite / Width:	42	**cm**
Höhe / Height:	72	**cm**

Rollstuhl / Wheelchair **(WCMP):**

Gewicht / Weight: **kg**

Ist die Rückenlehne faltbar?
Is the back rest foldable?
☐ **Ja** / Yes ☐ **Nein** / No

Dimensionen (gefaltet):
Dimensions (folded):
Länge / Length: **cm**
Breite / Width: **cm**
Höhe / Height: **cm**

Antriebshilfe / Add-on unit:

Gewicht / Weight: **kg**

Länge / Length: **cm**
Breite / Width: **cm**
Höhe / Height: **cm**

Werden für den Transport Teile entfernt? / Are parts removed for transport? ☒ **Ja** / Yes ☐ **Nein** / No

Laut Hersteller für den Transport speziell zu beachten:
To be considered for transport specifically according to manufacturer:

Fold into trolley mode (folded 39x42x72 cm; unfolded 120x56x89 cm). Turn power OFF at the tiller, then remove the single Li-ion battery (48V 5.2Ah 249.6Wh, GD009-13S2P) and carry it in the cabin with terminals protected against short circuit. No tools required. Original manufacturer battery.

Batterie Informationen
Battery information

Lithium Ionen Batterie / Lithium ion battery

Leistung in Wh / Battery rating in Wh: 249.6

☒ **WCLX – Entfernbare Batterie**
Abnehmbare Batterien und Ersatzbatterien müssen in der Passagierkabine transportiert werden. Dafür gelten folgende Limits:
- Entweder max. 2 Batterien mit jeweils bis zu 300 Wh, inkl. 1 Ersatzbatterie
- Oder max. 4 Batterien mit jeweils bis zu 160 Wh, inkl. max. 2 Ersatzbatterien

Removable battery
Removable batteries and spare batteries must be carried in the passenger cabin. For those the following limit is applicable:
- either max. 2 batteries up to 300 Wh each, incl. 1 spare battery
- or max. 4 batteries up to 160 Wh each, incl. max. 2 spare batteries.

☐ **WCLB – Vom Hersteller fix verbaute / *nicht entfernbare* Batterie**
Im Falle von vom Hersteller fix verbauter / nicht abnehmbarer Batterie(n) müssen die Batterieanschlüsse vor Kurzschlüssen isoliert, und Stromkreise im Gerät unter brochen werden, um eine unbeabsichtigte Inbetriebnahme zu verhindern.

Permanently installed by the manufacturer's design / *non removable* battery
- In case of permanently installed by the manufacturer's design / non-removable battery(ies) the battery terminals must be protected from short circuits and electrical circuits have to be isolated to prevent unintentional activation.

☐ **WCBD – Auslaufsichere Batterie oder Trockenbatterie z. B. Gel, Nickel-Kadmium, Nickel-Metall-Hydrid, wartungsfreie versiegelte Bleisäure-Batterie**
- Max. 1 Ersatzbatterie einer auslaufsicheren Nassbatterie oder 2 Ersatzbatterien im Falle von Nickel-Metall-Hydrid (NiMH) oder Trockenbatterien
- Mitnahme der abgenommenen Batterie und Ersatzbatterie(n) nur als aufgegebenes Gepäck

Non-spillable or dry cell battery e.g. gel, nickel-cadmium, nickel-metal hydride, sealed-lead-acid battery
- Max. 1 spare wet, non-spillable battery or 2 spare nickel-metal hydride (NiMH) or dry cell batteries
- Acceptance of removed and spare battery(ies) in checked baggage only

☐ **WCBW – Nicht-auslaufsichere Batterie/Nassbatterie**
- Nur zulässig als aufgegebenes Gepäck, wenn das Gerät in einer aufrechten Position verladen, verstaut, gesichert und ausgeladen werden kann

Spillable – wet cell battery
- Only accepted as checked baggage provided the device can be loaded, stowed, secured and unloaded always in an upright position

Anzahl der Batterien für den Antrieb
Number of batteries for operation: 1

Ist die Batterie abnehmbar? ☒ **Ja** / Yes ☐ **Nein** / No
Is the battery removable?

Wie viele Ersatzbatterien transportieren Sie?
How many spare batteries do you carry? 0

Informationen Elektrische Mobilitätshilfe
Electric mobility device information form

A STAR ALLIANCE MEMBER

Wichtig für den sicheren Transport Ihrer elektrischen Mobilitätshilfe

- Wenn Sie Unterstützung in Ihrer Mobilität benötigen, können Sie die Reise mit Ihrer eigenen elektrischen Mobilitätshilfe anfragen.
- Buchen Sie zuerst Ihren Flug. Danach füllen Sie bitte das Online-Formular aus und schicken es uns über die „Formular senden"-Funktion.
- Bitte führen Sie das ausgefüllte Formular für die Dauer Ihrer Reise mit sich, entweder in gedruckter Form oder elektronisch. Sofern sich die Angaben nicht ändern, verwenden Sie es gerne auch für Ihre folgenden Reisen.
- **Bei Fragen kontaktieren Sie uns über: www.lufthansa.com/hilfe**
- **Weitere Unterstützung erhalten Sie auch unter der international kostenlosen Servicenummer**

0800 8384267

Important for the safe transport of your electric mobility device

- If you require mobility assistance, you can request travel with your own electric mobility device.
- First, book your flight. Then, please fill in the online form and send it via the "Send form"-button.
- Please take the completed form with you for the entire journey, either in printed form or digital. Provided the information does not change, please re-use it for your next trips.
- **If you have further questions please contact us via: www.lufthansa.com/help**
- **For further support, please call the international toll-free service number**

0800 8384267

Bitte beachten Sie

- Batteriebetriebene Mobilitätshilfen fallen unter die Gefahrgutregelung
- Je nach Batterieart gelten entsprechende Transportbedingungen

In jedem Fall gilt:

- Elektrische Stromkreise müssen unterbrochen sein
- Schützen Sie freiliegende Batterieanschlüsse vor Kurzschluss, z. B. mit einem Klebeband, um eine unbeabsichtigte Aktivierung des Gerätes zu verhindern
- Bei Transport inklusive Batterie, schalten Sie bitte Ihr Gerät komplett aus:
  - Ziehen Sie den Schlüssel ab
  - Deaktivieren Sie Ihr Gerät mittels Steuerhebel, Schalter oder Knopf oder anderen Isoliermechanismus, wie vom Hersteller für den Transport vorgesehen
- Transportieren Sie entfernte Batterien und Ersatzbatterien in der originalen Verpackung des Herstellers oder einer anderen geeigneten, stabilen Verpackung

Please observe

- Battery powered mobility devices are subject to the dangerous goods regulations
- Depending on the battery type, respective transport conditions are applicable

In any case:

- The battery power must be isolated
- Protect exposed battery terminals from short circuits, e.g. by taping the terminals, to prevent the mobility device from inadvertent activation
- In case of transport including the battery, please turn off your device completely:
  - Remove the key
  - Deactivate the device using the joystick or an isolation switch or button, or other isolation mechanism as required by the manufacturer for transport
- Transport removed batteries or spare batteries in the original manufacturer's packaging or other strong, rigid packaging

Hiermit bestätige ich folgendes:

- ☑ Alle Werkzeuge, welche für die Transportvorbereitung meiner Mobilitätshilfe notwendig sind, werden mitgeführt.
- ☑ Das Hersteller-Handbuch mit den Transportanleitungen kann bei Bedarf vorgelegt werden.
- ☑ Eine geeignete Transporttasche für abnehmbare Teile wird mitgeführt.
- ☑ Das Sicherheitsdatenblatt der Batterie meiner Mobilitätshilfe oder das Zertifikat für den Lufttransport liegt dieser E-Mail bei.

I hereby acknowledge the following:

- ☑ All tools required to prepare my mobility device for transport are provided.
- ☑ The manufacturer's handbook with instructions for transporting the mobility device is available on request.
- ☑ A suitable bag for transportation of removable parts is provided.
- ☑ The safety data sheet or certificate for air transport of the battery of my mobility device is included in this email.

Achtung: Check-in Agenten

Vergleiche die markierten Angaben zur Spezifikation mit der mitgebrachten Mobilitätshilfe.

- Prüfe das gebuchte Service und das bestätigte Gerät im Reservierungs-/ Check-in-System

Die mitgebrachte Mobilitätshilfe stimmt mit den bestätigten Details in der Reservierung überein?

- Der Transport ist damit im Rahmen der Gefahrgutbestimmungen und Beförderungsregeln genehmigt
- Akzeptiere die Mobilitätshilfe gemäss „Procedure for electric wheelchair/mobility device" im GPM 7.4.2

Der Service ist **nicht** bestätigt oder die mitgebrachte Mobilitätshilfe stimmt **nicht** mit dem gebuchten Service überein?

- Stelle die Einhaltung der Gefahrgutbestimmungen, Beförderungsregeln und die Genehmigung für den Transport sicher
- Folge der Anleitung für „Unreserved wheelchairs and mobility devices" im GPM 7.4.2

Attention: Check-in agents

Compare the specification related data in the shaded boxes with the mobility device presented.

- Check the confirmed service and approved device in the reservation/check-in system

The presented mobility device matches the confirmed details in the reservation?

- Thus, the transport is approved, in line with the dangerous goods regulations and transport rules
- Accept the mobility device according to the "Procedure for electric wheelchair/mobility device" in GPM 7.4.2

The service is **not** confirmed or the presented mobility device does **not** match the booked service?

- Ensure the transport approval and compliance with the dangerous goods regulations and transport rules
- Apply the procedure for "Unreserved wheelchairs and mobility devices" in GPM 7.4.2

LHG200026 August/2025

Drucken / Print

Movinglife LTD

www.movinglife.com · Israel +972 73 391 3999 · info@movinglife.com

To: Airline Check-in / Dangerous Goods Acceptance Staff

Subject: Air Transport Confirmation, ATTO Mobility Scooter and Lithium ion Battery

This letter confirms that the mobility device described below is a battery-powered mobility aid manufactured / supplied by Movinglife LTD, and that its battery meets the requirements for carriage by air as a passenger mobility aid.

Device	**ATTO electric folding mobility scooter**
Manufacturer	**Movinglife LTD**
Weight / folded dimensions	**28.2 kg without battery (battery 1.8 kg) · 39 × 42 × 72 cm (L×W×H)**
Battery type	**Lithium-ion, removable, original manufacturer battery**
Battery model / manufacturer	**GD009-13S2P · Dongguan Kingin Power Co., Ltd**
Rating	**48V · 5.2Ah · 249.6 Wh (one battery)**
Testing	**UN Manual of Tests and Criteria, Part III, sub-section 38.3 (UN 38.3) · report MRI1AVBG2672847U5**

Transport instructions: fold the scooter into trolley mode and switch it off. Remove the lithium-ion battery (249.6 Wh, in accordance with the IATA Dangerous Goods Regulations for battery-powered mobility aids) and carry it in the passenger cabin, with the terminals protected against short circuit and the battery placed in a protective pouch. No tools are required. The scooter frame contains no other battery.

The battery's Material Safety Data Sheet (MSDS), including the UN 38.3 transport information, is attached (ATTO Flight Safety Certificates).

movinglife

ATTO MOBILITY SCOOTER

Flight Safety Certificates

LITHIUM-ION BATTERY 249.6 Wh

DRY, NON SPILLABLE

Battery dimensions: 32x14x11cm Weight 1.8kg

Page	Document	Standard / Doc
2	OVERVIEW	FDA / CE
3-14	BATTERY SAFETY DATA SHEET	MSDS
15	SCOOTER DIMENSIONS	

movinglife

www.movinglife.com

Take to Airport


Li-ion

FDA APPROVED

CE



FREE WHEEL HANDLE



MOTOR

BATTERY

MATERIAL SAFETY DATA SHEET

Rechargeable Li-ion Battery

Model: GD009-13S2P

Prepared by	Approved by
Cindy Chen	Jack Zhou
Jun 5, 2023	Jun 6, 2023

Material Safety Data Sheet

Reference to ST/SG/AC.10/30/Rev.9(GHS)

Section 1 - Chemical Product and Company Identification

Chemical Product Identification
Sample Name: Lithium-ion Battery pack
Sample Model: GD009-13S2P
Recommended Uses: N/A
Restrictions on Use: N/A
Supplier Name: Dongguan Kingin Power Co., Ltd.
Address: No.702, Floor 7th, Block B, Honghai Intelligent Valley, No.50, Jinjiaotang Fumin Road, Zhutang Village, Fenggang Town, Dongguan City
Phone Number: 15283330307
FAX: 0769-88023775
E-mail: zhuozhiguang@kingin.cn
Emergency Phone Number: 0769-88023775

Section 2 - Hazards Identification

Emergency overview: This product is a battery. Intended use of the product should not result in exposure to the chemical substance. In case of rupture the below hazards exist.

Classification according to GHS
Acute toxicity, oral (4)
Skin corrosion/irritation (2)
Serious eye damage/eye irritation (2A)
Specific target organ toxicity, single exposure; Respiratory tract irritation (3)

Label elements

Hazard pictogram(s);



Signal word: Warning

Hazard statement(s):

H302 Harmful if swallowed

H315 Causes skin irritation

H319 Causes serious eye irritation

H335 May cause respiratory irritation

Precautionary statement(s):

Prevention:

P264 Wash skin and clothing thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves, protective clothing, eye protection, face protection.

P261 Avoid breathing dust, fume, gas, mist, vapours, spray.

P271 Use only outdoors or in a well-ventilated area.

Response:

P301 + P312 IF SWALLOWED: Call a POISON CENTER if you feel unwell.

P330 Rinse mouth.

P302 + P352 IF ON SKIN: Wash with plenty water.

P321 Specific treatment (See additional emergency instructions).

P333 + P313 If skin irritation or rash occurs: Get medical advice.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER, if you feel unwell.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Send contents to approved waste treatment plants.

Other hazards

Physical and chemical hazards: See Section 10

Human health hazards: See Section 11

Environmental hazards: See Section 12

Section 3 - Composition/Information on Ingredients

Chemical characterization: Mixture

Chemical Composition	CAS No.	EC#	Weight (%)
Cobaltate, lithium	12190-79-3	235-362-0	41
Graphite	7782-42-5	231-955-3	25
Polypropylene	9003-07-0	618-352-4	2
Copper	7440-50-8	231-159-6	5
Aluminium	7429-90-5	231-072-3	8
Nickel	7440-02-0	231-111-4	3
Rubber, chloroprene, gas	69028-37-1	---	2
Phosphate(1-), hexafluoro-, lithium	21324-40-3	244-334-7	9
Polyvinylidene fluoride resin	24937-79-9	607-458-6	2
Cellulose, carboxymethyl ether	9000-11-7	618-326-2	3

Section 4 - First Aid Measures

Description of first aid measures

General information No special measures required.

After eye contact

Flush eyes with plenty of water for several minutes while holding eyelids open. Get medical attention if irritation persists.

After skin contact

Remove contaminated clothing and shoes. Immediately wash with water and soap and rinse thoroughly. Wash clothing and shoes before reuse. If irritation occurs, get medical attention.

After inhalation

Remove victim to fresh area. Administer artificial respiration if breathing is difficult. Seek medical attention.

After swallowing

Do not induce vomiting. Get medical attention.

Personal protective equipment for first-aid responders: No data available.

Most important symptoms/effects, acute and delayed: No data available.

Indication of immediate medical attention and special treatment needed: Treat symptomatically.

Section 5 - Fire Fighting Measures

Suitable extinguishing media:

Small Fire**:** Dry chemical, CO_2, water spray or regular foam. Large Fire**:** Water spray, fog or regular foam.

Move containers from fire area if you can do it without risk.

Unsuitable extinguishing media:

No data available.

Specific Hazards arising from the chemical:

Special hazards arising from the substance or mixture

Battery may burst and release hazardous decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolyte that may vent, ignite and produce sparks when subjected to high temperature (>150 °C (302 °F)), when damaged or abused (e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in close proximity.

Specific protective actions for fire-fighters:

Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.

Section 6 - Accidental Release Measures

Personal precautions:

As an immediate precautionary measure, isolate spill or leak area for at least 25 meters (75 feet) in all directions. Keep unauthorized personnel away. Stay upwind, uphill and/or upstream. Ventilate closed spaces before entering. Large Spill: Consider initial downwind evacuation for at least 100 meters (330 feet).

Protective equipment:

No data available.

Emergency procedures:

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Absorb with earth, sand or other non-combustible material. Leaking batteries and contaminated absorbent material should be placed in metal containers.

Environmental precautions:

Do not allow material to be released to the environment without proper governmental permits.

Methods and materials for containment and cleaning up:

For all waste handing must refer to United Nations, National and Local Regulations for disposal.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Section 7 - Handling and Storage

Precautions for safe handling:

Avoid short circuiting the battery. Avoid mechanical damage of the battery. Do not open or disassemble.

Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity. Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well-ventilated place. Keep away from heat, avoiding the long time of sunlight.

Section 8 - Exposure Controls/Personal Protection

Control parameters

CAS No.	ACGIH	NIOSH	OSHA
12190-79-3	N/A	N/A	N/A
7782-42-5	TLV-TWA 2mg/m^3	REL-TWA 2.5mg/m^3	PEL-TWA 15mppcf PEL-TWA 20mppcf
9003-07-0	N/A	N/A	N/A
7440-50-8	TLV-TWA 0.2mg/m^3 TLV-TWA 1mg/m^3	REL-TWA 1mg/m^3 REL-TWA 0.1mg/m^3	PEL-TWA 0.1mg/m^3 PEL-TWA 1mg/m^3
7429-90-5	TLV-TWA 1mg/m^3	REL-TWA 2mg/m^3 REL-TWA 5mg/m^3 REL-TWA 10mg/m^3	PEL-TWA 5mg/m^3 PEL-TWA 15mg/m^3
7440-02-0	TLV-TWA 1.5mg/m^3	REL-TWA 0.015mg/m^3	PEL-TWA 1mg/m^3
69028-37-1	N/A	N/A	N/A
21324-40-3	N/A	N/A	N/A
24937-79-9	N/A	N/A	N/A
9000-11-7	N/A	N/A	N/A

Appropriate engineering controls:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Personal Protective Equipment:

Respiratory protection: Wear suitable protective mask. For a large large number of battery leakages, wear chemical protective clothing, including self-contained breathing apparatus.

Hand Protection: Wear appropriate protective gloves to reduce skin contact.

Eye Protection: Wear safety goggles or eye protection combined with respiratory protection.

Skin and Body Protection: Working environment required, wear suitable protective clothing to minimize contact with skin. The type of protective equipment must be according to the concentration and the content of certain hazardous substances in the workplace.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties	
Colour:	Black.
Physical State:	Prismatic.
Odour:	Not available.
pH:	Not available.
Melting point/freezing point:	Not available.
Boiling point or initial boiling point and boiling range:	Not available.
Flash Point:	Not available.
Flammability:	Not available.
Solubility:	Not available.
Lower and upper explosion limit/flammability limit:	Not available.
Auto-ignition temperature:	Not available.
Decomposition temperature:	Not available.
Kinematic viscosity:	Not available.
Partition coefficient: n-octanol/water (log value):	Not available.
Vapour pressure:	Not available.
Density and/or relative density:	Not available.
Relative vapour density:	Not available.
Particle characteristics:	Not available.
Other information:	
Voltage	48V
Electric capacity	5200mAh
Electric Energy	249.6Wh

Section 10 - Stability and Reactivity

Reactivity: No data available.
Chemical stability: Stable.
Possibility of hazardous reactions: No data available.
Conditions to Avoid: Flames, sparks, and other sources of ignition, incompatible materials.
Incompatible materials: Oxidizing agents, acid base.
Hazardous decomposition products: Carbon monoxide, carbon dioxide, lithium oxide fumes.

Section 11 - Toxicological Information

Acute Toxicity:

CAS No.	LC50/LD50
12190-79-3	No data available.
7782-42-5	No data available.
9003-07-0	No data available.
7440-50-8	No data available.
7429-90-5	No data available.
7440-02-0	LD50 Rat (oral): >9000mg/kg
69028-37-1	No data available.
21324-40-3	No data available.
24937-79-9	No data available.
9000-11-7	No data available.

Skin corrosion/irritation: No data available.
Serious eye damage/irritation: No data available.
Respiratory or Skin sensitization: No data available.
Germ Cell mutagenicity: No data available.
Carcinogenicity: No data available.
Reproductive toxicity: No data available.
Specific target organ toxicity-Single exposure: No data available.
Specific target organ toxicity-Repeated exposure: No data available.
Aspiration hazard: No data available.
Information on the likely routes of exposure: No data available.
Eye: No data available.
Skin: No data available.
Ingestion: No data available.
Inhalation: No data available.

Section 12 - Ecological Information

Ecological Toxicity: No data available.
Persistence and degradability: No data available.
Bioaccumulative Potential: No data available.
Mobility in Soil: No data available.
Other adverse effects: No data available.

Section 13 - Disposal Considerations

Disposal methods:


Recommendation:

Consult state, local or national regulations to ensure proper disposal.

Uncleaned packaging

Recommendation: Disposal must be made according to official regulations.

Section 14 - Transport Information

UN or ID Number		
IATA	UN3480	UN3171
IMDG	UN3480	UN3171
Model Regulation	UN3480	UN3171
Proper Shipping Name/Description		
IATA	Lithium ion batteries Battery-powered vehicle	
IMDG	LITHIUM ION BATTERIES BATTERY-POWERED VEHICLE	
Model Regulation	LITHIUM ION BATTERIES BATTERY-POWERED VEHICLE	
Class or Div.(Sub Hazard)		
IATA	9	
IMDG	9	
Model Regulation	9	
Packing group		
IATA	N/A	
IMDG	N/A	
Model Regulation	N/A	
Hazard Label **IATA** **IMDG** **Model Regulation**	 965:	 952:
Environmental hazards **Marine pollutant:**	No	
IMDG EmS:	F-A. S-I	
Special precautions for user	No information available.	

Transport information: The Lithium-ion battery pack GD009-13S2P has passed the test UN38.3, according

to the report ID: MRI1AVBG2672847U5.

Watt-hour exceeds the standard. The goods are packaged according to the packaging Instruction 965 section IA of IATA DGR 64th Edition for transportation, Cargo aircraft only.

Watt-hour exceeds the standard. The goods are packaged according to the special provision 230, 348, 384 of IMDG (40-20).

Watt-hour exceeds the standard. The goods are packaged according to the special provision 230, 348, 384 of <<Recommendations On The Transport Of Dangerous Goods-Model Regulations>> (22nd).

The goods are packaged according to the packaging Instruction 952 of IATA DGR 64th Edition for transportation, it belongs to dangerous goods. Be shipped by passenger and cargo aircraft.

The goods are packaged according to the special provision 388, 962, 971 of IMDG (40-20), it belongs to dangerous goods.

The goods are packaged according to the special provision 388 of <<Recommendations On The Transport Of Dangerous Goods-Model Regulations>> (22nd), it belongs to dangerous goods.

Separate batteries to prevent short-circuiting. and they should be packed in strong package during transport. Lithium cell or battery should incorporate a safety venting device or be designed to prevent a violent rupture under normal transport conditions. Keep away from high temperature and open flames.

Note: State of Charge (SoC) not exceeding 30% of their rated capacity. (By air, Lithium ion batteries)
Batteries weight in the package <5kg. (By air, Batteries installed in equipment)

Transport Fashion: By air, by sea, by railway, by road.

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

CAS No.	TSCA	IECSC	DSL/NDSL	EINECS/ ELINCS/ NLP
12190-79-3	Listed	Listed	Listed DSL	Listed
7782-42-5	Listed	Listed	Listed DSL	Listed
9003-07-0	Listed	Listed	Listed DSL	Listed
7440-50-8	Listed	Listed	Listed DSL	Listed
7429-90-5	Listed	Listed	Listed DSL	Listed
7440-02-0	Listed	Listed	Listed DSL	Listed
69028-37-1	Listed	Listed	Listed DSL	Listed
21324-40-3	Listed	Listed	Listed DSL	Listed

24937-79-9	Listed	Listed	Listed DSL	Listed
9000-11-7	Listed	Listed	Listed DSL	Listed

Section 16 - Other Information

Issue Date: 2023-03-13
Issue Department: Technical department
Modification record:
Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Other Information:
CAS: (Chemical Abstracts Service);
EC: (European Commission);
ACGIH: (American Conference of Governmental Industrial Hygienists);
NIOSH: (US National Institute for Occupational Safety and Health);
OSHA: (US Occupational Safety and Health);
TLV: (Threshold Limit Value)
TWA: (Time Weighted Average);
STEL: (Short Term Exposure Limit);
PEL: (Permissible Exposure Level);
REL: (Recommended Exposure Limit);
PC-STEL: (Permissible concentration-short time exposure limit);
PC-TWA: (Permissible concentration-time weighted average);
IARC: (International Agency for Research on Cancer);
LC50: (Lethal concentration, 50 percent kill);
LD50: (Lethal dose, 50 percent kill);
EC50: (Median effective concentration);
BCF: (Bioconcentration Factor);
BOD: (Biochemical oxygen demand);
IECSC: (Inventory of Existing Chemical Substances in China);
NOEC: (No observed effect concentration);
NTP: (US National Toxicology Program);
RTECS: (Registry of Toxic Effects of Chemical Substances);
TOC: (Total Organic Carbon);
TSCA: (Toxic Substances Control Act of USA);

DSL: (the Domestic Substances List of Canada);
NDSL: (the Non-domestic Substances List of Canada);
IATA: (International Air Transport Association);
IMDG: (International Maritime Dangerous Goods);
TDG: (Recommendations on the TRANSPORT OF DANGEROUS GOODS Model Regulations)
The original report which report No. is MRICF6CG2915147U3 be replaced by this report, and it will be canceled immediately and doesn't have any legal validity. Please compliance with this report.
2023-03-13

End of report

Scooter Sizes & Dimensions

- For sending to the cargo bay:

  In trolley mode (folded, as shown in picture) 72x42x39 cm



Trolley Mode
62.2 lbs (28.2 Kg)
w/out battery

For more information please contact Moving Life



USA +1-347-761-3317

UK +44-(0)20-3769 7530

Israel +972-(0)73-391 3999



info@movinglife.com

Take to Airport

All Rights Reserved © 2023 Moving Life Ltd.